


md2pdf: Markdown to PDF, with the Mermaid diagrams drawn

`md2pdf FILE.md` writes `FILE.pdf` beside the source. It works offline: GitHub renders Mermaid in the browser, but a PDF that you mail or print needs the diagrams already drawn.



```
md2pdf FILE.md # writes FILE.pdf; prints its path
md2pdf docs/*.md # several at once; exit 1 if any failed
MD2PDF_CHROME=/path/to/chrome md2pdf FILE.md
```

What it does

- **Draws every ``mermaid block** as an SVG via mermaid-cli. A block that does not parse fails the file (exit 1, error on stderr), so a broken diagram is never shipped silently.
- **Reads YAML front matter as metadata** rather than printing it.
- **Prints tables unsplit.** If it finds md-table-fit (in a tools/md-table-fit/ folder above the file, or beside this script), it runs --join first, so wrapped table rows print as one row each.
- **Shrinks code blocks too wide for the page** (down to 5 pt) instead of cutting them off.
- **Turns pages for wide diagrams.** A diagram that prints larger in landscape gets a landscape A4 page of its own.

Requirements

Need	Install
mmdc (mermaid-cli)	npm install -g @mermaid-js/mermaid-cli. This also fetches a chrome-headless-shell into ~/.cache/puppeteer, which md2pdf reuses.
pandoc	brew install pandoc or apt install pandoc
headless Chrome	Found in this order: \$MD2PDF_CHROME; puppeteer's newest chrome-headless-shell; chromium or google-chrome on PATH; the macOS Google Chrome app
python3	Optional, only for the md-table-fit join step

The Lua filter and the HTML template are written inline by the script, so there is nothing else to install. Put the script on your PATH:

```
ln -s "$PWD/tools/md2pdf/md2pdf" ~/.local/bin/md2pdf
```

Auto-run from the pi coding agent

pi-extension/md2pdf.js is a [pi](#) extension. After every write or edit to a .md file that holds a mermaid block, or a bash call that changed one, it runs md2pdf and appends the result to the tool output. If a diagram fails to parse, the model sees md2pdf FAILED and fixes it.

```
cp tools/md2pdf/pi-extension/md2pdf.js ~/.pi/agent/extensions/
```

It finds md2pdf on PATH, or at \$MD2PDF. Where md2pdf isn't installed it does nothing. It skips .git, node_modules, data, _extracted and virtualenvs when looking for files a bash command changed.