Haptic Immersion

Author: Abdelkrim Mebarki
Master's Program in Computer Science – Artificial Intelligence & Applications
Department of Computer Science – Faculty of Mathematics and Computer Science
University of Science and Technology of Oran
December 30, 2025

1. Introduction

The final cognitive stage in a VR environment capable of producing a strong feeling of immersion is **full interaction**. This interaction primarily relies on the user's perception of the virtual world. However, this perception is ultimately a fully created *illusion*, as it is mediated through technological interfaces—HMD, controllers or haptic devices—rather than through direct physical contact as in the physical world.
Perception in VR can support **static or passive exploration**, where the user can observe the environment but cannot alter its elements. It can also enable **dynamic or interactive exploration**, where the user makes decisions based on the sensory data gathered from the system, such as visual, auditory, or haptic cues. The decisions typically involve selecting an option from a set of available choices.
The **haptic dimension** plays a dual and crucial role in the interaction process. First, it enriches the user's perceptual experience by adding tactile, kinaesthetic, and force-feedback information to the collected sensory data. Second, it serves as an input/output channel through which user can implement and execute decisions within the virtual world, reinforcing the sense of agency and enhancing overall immersion.

1.1. Why Do We Use Haptics in Virtual Reality?

Haptics in VR serve two primary purposes: **locating the user's body within the virtual space** and **enabling meaningful interaction with virtual entities**.
For the **spatial localization**, the system should determine both the **position** of the user's body (The virtual identity)—typically captured through motion-tracking technologies—and the **posture** or configuration of the user limbs, which may be inferred through computer vision techniques: Segmentation techniques and advanced image-analysis algorithms.
To **act upon virtual objects**, the system relies on **effort-based input mechanisms** and **haptic feedback devices**. These technologies allow users not only to manipulate virtual elements within but also to receive tactile or force-related responses that simulate real-world physical interactions. The resulting reciprocal loop of action and feedback significantly enhances the application realism, precision, and immersion.

2. The Haptic Dimension: Terminology and Sensory Foundations

In this context, the term **haptic** refers to the human sense of touch in its broadest and large interpretation. Unlike **vision** or **audition**, haptic perception is **not localized to a single sensory organ** but emerges from the combined activity of multiple sensory systems distributed throughout the full body. These systems allow humans to perceive the contact, the movement, the force, the posture, and the physical interaction with the environment. In the context of virtual reality and interactive systems, understanding the haptic dimension requires distinguishing between several closely related sensory sub-modalities.

2.1. Proprioception

Proprioception is the sense enabling individuals to perceive position, orientation, and movement of their body and limbs in the space, without relying on the visual input. It results from integration of sensory information originating from body muscles, tendons, joints, and skin. Proprioception also incorporates elements of kinesthetic and vestibular perception, making it essential for coordinated movement and bodily awareness. In virtual environments, proprioception plays a critical role in embodiment, allowing users to feel that their virtual actions correspond to their physical movements making the immersion fully natural.

2.2. Vestibular Sense

The **vestibular sense** in the human body is responsible for the perception of balance, head position, and motion, including the acceleration and deceleration. This information is acquired through the vestibular system located in the inner ear, particularly the semi-circular canals and otolith organs. Although VR systems cannot directly stimulate the vestibular head organs, they can indirectly influence vestibular perception through visual motion cues, synchronized movement, and motion platforms. The proper alignment between visual and vestibular information is crucial to maintaining the user comfort and to preventing motion sickness over experiences.

Available on zenodo – DOI : 10.5281/zenodo.18092969

2.3. Tactile Sense

The **tactile sense** pertains to the perceived sensations through skin resulting from physical contact. It is associated with the perception of pressure and texture, mediated by mechanoreceptors embedded in the skin. In contrast, thermal sensations and nociceptive sensations (pain) are generally considered separate components of cutaneous perception. In VR applications, tactile feedback is commonly simulated using vibration, pressure, or surface modulation to convey contact with virtual elements.

2.4. Kinaesthesia

Kinaesthesia, often closely associated with proprioception, refers more specifically to the sensation of body movement and limbs. It arises from sensory receptors located in muscles, tendons, and joints, providing information about motion, effort, and resistance. **Kinaesthetic perception** is fundamental for user tasks involving manipulation, navigation, and physical interaction with the artificial creation. In immersive systems, kinaesthesia is frequently stimulated through force-based interfaces that resist, guide, or constrain the user movements.

2.5. Cutaneous Sense

The **cutaneous sense** encompasses all the sensations originating from the skin, including pressure, temperature, and pain representing the direct form of physical contact perception. While pressure-based stimulation is widely used in haptic interfaces, temperature and pain are less commonly simulated due to technical and ergonomic limitations and body safety considerations. Nevertheless, the cutaneous sense remains a core component of the VR haptic perception, contributing significantly to realism perception and material recognition.

2.6. Force Feedback

Force feedback refers to the mechanical generation of forces applied to the user body stimulating the kinaesthetic and cutaneous sensory systems. Force feedback devices employ motors, actuators, or brakes to create resistance, weight, or constraint corresponding to interactions with artificially created objects. This form of feedback is coupled with visual displays to ensure the consistency between what the user sees and what he physically feels. Force feedback is a key enabler of realistic interaction in virtual environments, particularly in simulation platforms, training, and rehabilitation applications.

3. The Four Fundamental Modalities of Cutaneous Sensation

The human tactile perception detects **four main types of stimulation**, each one corresponding to a different class of skin receptors. These modalities form the basis of all tactile sensations:

3.1. Mechanical Stimulation

Including any physical deformation of the skin –

- ➔ **Pressure**
- ➔ **Indentation (touch)**
- ➔ **Vibration**
- ➔ **Stretching and shear**
- ➔ **Texture perception**

Theses sensations are detected by **mechanoreceptors** (Merkel cells, Meissner corpuscles, Pacinian corpuscles, and Ruffini endings)

> 👉 *Most haptic devices reproduce mechanical stimuli (vibration, pressure, deformation).*

3.2. Thermal Stimulation

This refers to sensations of **Heat** and **Cold**. Thermal changes are detected by **thermoreceptors** (warm and cold receptors in the skin).

> 👉 Some haptic devices simulate temperature using:
> - Thermoelectric modules (Peltier elements)
> - Conductive heating or cooling surfaces
> - Phase-change materials

3.3. Chemical Stimulation

The human skin can perceive **Irritants**, **pH changes**, and **Certain molecules**. Chemical stimulation is mostly related to **pain, itch**, and **protective reflexes**, not to ordinary touch.

☞ Haptic devices do NOT use chemical stimulation, because: it is unsafe, slow, unpredictable, and uncomfortable. It exists mainly in medical or research contexts, not VR/AR.

3.4. 4. Electrical Stimulation

Electrical currents stimulate nerves in the skin, creating: artificial touch sensations, tingling, tapping, and proprioceptive illusions. This is called **electrotactile stimulation**.

☞ Some modern haptic devices use electrotactile feedback, because it is: lightweight (no motors), fast, silent.

Examples – **Teslasuit**, **NeoSensory Buzz band**, **Haply electrotactile arrays (research prototypes)**, **UC Berkeley skin patches (electroadhesion-based haptics)**

Modality	Detected by Skin	Used in Haptic Devices?	Examples
Mechanical	Yes	✓ Very common	vibration motors, pneumatic actuators, soft robotics
Thermal	Yes	✓ Rare but emerging	Peltier modules, thermal haptics
Chemical	Yes	✗ Not used (dangerous)	medical tests only
Electrical	Yes	✓ Modern research & suits	Teslasuit, electrotactile pads

4. Effort-Based Input Mechanisms vs Haptic Feedback Devices

In VR, it is important to distinguish between **effort-based input mechanisms** and **haptic feedback devices**, as they play complementary but opposite roles within the interaction loop. Together, they form a bidirectional interaction system. The first captures the user's physical intentions, while the second conveys the system's response back to the user from the virtual world, enabling natural, intuitive, and immersive interaction in virtual reality environments.

4.1. Effort-Based Input Mechanisms (Input → System)

These mechanisms refer to **how the user *acts on* the virtual environment** capturing the *effort* or *force* the user intentionally applies in order to perform an action. Their main purpose is to detect the user actions. These types of devices measure user-generated **forces**, **movements**, or **muscle activity** that serve as **input channels** to control or manipulate virtual objects. In short, they interpret what the user *wants to do* inside the VR world.

Examples –

- ➔ A VR controller sensing pressure on its trigger.
- ➔ A force sensor measuring how hard the user pushes or pulls.
- ➔ A data glove detecting finger flexion forces.
- ➔ EMG-based interfaces reading muscle activation to infer effort.

4.2. Haptic Feedback Devices (System → User)

They refer to **how the virtual environment *responds to* the user** inputs producing sensations that simulate real physical interactions. Their purpose is *to provide tactile or force sensations back to the user.* These devices generate **tactile cues** (vibration, texture, temperature) or **kinaesthetic cues** (resistance, force, weight, torque) to increase realism in VR worlds by substituting or mimicking real-world physical responses.

Examples –

- ➔ A controller that vibrates when hitting a virtual object.
- ➔ A force-feedback joystick that resists movement.
- ➔ A haptic glove simulating texture or pressure.
- ➔ A VR exoskeleton arm applying torque to simulate weight.

One-Sentence Distinction – Effort-based input captures what the user is trying to do while haptic feedback devices tell the user what the virtual world is "doing back."

5. Tactile Displays (Cutaneous Haptic Systems)

Tactile displays or cutaneous **haptic systems**, are designed to simulate the sensitivity of human skin by the generation of surface-level sensations. Unlike force-feedback devices acting on muscles and joints, tactile displays stimulate skin receptors to convey information related to contact with virtual objects.

5.1. Pressure-Based Stimulation

This technique is one of the most fundamental tactile cues used in cutaneous haptics enabling users to perceive contact, surface texture, and object compliance. By applying localized pressure to the human skin, tactile displays create the illusion of interacting with solid, soft, or deformable virtual surfaces.

5.2. Vibration-Based Feedback

Vibration is widely employed to represent roughness, impacts, and surface irregularities of virtual entities. High-frequency vibrations are typically used to simulate fine textures, while short vibration impulses often signal collisions or discrete interaction events within the artificial world.

5.3. Thermal Stimulation

Thermal feedback announces sensations of heat and cold. It provides material-related cues associated with different surfaces such as metal, ice, or warm objects. Even a minimal temperature variation can significantly enhance realism by reinforcing and complementing the perceived visual information.

5.4. Physical Touch and Dynamic Contact

Tactile displays reproduce physical touch sensations such as objects pressing against the skin or moving across it. It encompasses dynamic contact patterns supporting sensations like sliding, tapping, or brushing, thereby enriching the sense of interaction.

5.5. Skin Stretch and Shear Feedback

Advanced tactile techniques involve **skin stretch** and **shear stimulation**. They generate directional cues related to friction, motion, or slip and are particularly effective for conveying movement across surfaces or supporting precise object manipulation.

5.6. Contactless and Electrical Tactile Technologies

Emerging tactile technologies extend feedback beyond direct classical mechanical contact. **Ultrasonic mid-air haptics** use focused ultrasound to produce contactless tactile sensations in free space. Electrotactile stimulations apply controlled electrical impulses in order to simulate pressure or complex textures without relying on mechanical actuators.

5.7. Air-Based and Soft-Robotic Approaches

Additional tactile feedback techniques include the **pneumatic** or the **air-jet systems,** where pulsed air simulates touch or airflow. **Soft-robotic actuators** deform to convey sensations of squishiness and elasticity allowing for more organic and compliant tactile interactions.

5.8. Vibroacoustic and Resonance-Based Haptics

Finally, **vibroacoustic** or **resonance-based haptic** systems rely on high-frequency vibrations to reproduce fine textures and sharp impacts enriching tactile interaction by adding subtle yet informative surface cues in VR environments.

6. Force-Feedback Devices (Kinesthetic Haptic Displays)

Force-feedback devices or **kinesthetic haptic displays**, apply controlled mechanical forces to the user's body to simulate physical interaction with virtual entities. Unlike tactile displays that stimulate skin surface, they act on muscles and joints, enabling users to perceive forces, resistance, and movement constraints.

6.1. Resistance and Mechanical Properties

One of the main functions of force-feedback systems resisting user movements, thereby simulating physical properties such as weight, inertia, stiffness, and mass. By opposing motion, these peripherals create the sensation that virtual objects possess substance and realistic mechanical behavior.

6.2. Motion Constraints and Collision Simulation

Force-feedback devices can constrain user motion too. This happens to reproduce collisions or the presence of solid surfaces. When a user encounters virtual boundaries or obstacles, the device limits the user movements accordingly, reinforcing the illusion of contact with rigid or impenetrable objects.

6.3. Directional Forces and Motion Guidance

In addition to resistance and constraints, force-feedback systems can apply directional forces guiding motion or indicate properties of virtual objects. This guidance is particularly valuable in training and rehabilitation contexts, where forces can assist, correct, or deliberately resist the user movements in controlled and repeatable manner.

6.4. Simulation of Deformable and Soft Objects

Another advanced force-feedback technology enables the simulation of deformable or soft virtual objects. **Soft-robotic actuators**, constructed from flexible materials such as silicone or electroactive polymers, deform under interaction conveying sensations of elasticity, compliance, or squishiness, closely approximating the behavior of real-world soft materials.

6.5. Shape-Memory Alloy–Based Actuation

Other force-feedback approaches rely on **shape-memory alloys (SMA)**. SMA change shape when they are electrically activated making it possible to generate localized or finger-level resistance. They are particularly well suited for wearable configurations, including haptic gloves and soft exoskeletons.

6.6. Exoskeletons and High-Force Actuation Systems

Exoskeleton-based systems extend force feedback to the fingers, hands, or arms, providing precise resistance and guided movement. In this context, pneumatic and hydraulic systems use fluid pressure to apply larger forces and are often employed in full-body system configurations. Electromechanical linear actuators offer high-precision force or torque and are used in desktop-based or training simulators.

6.7. Integrated and Hybrid Force-Feedback Platforms

Finally, force-feedback technologies can be integrated into larger platforms such as **haptic chairs** or **locomotion systems** to simulate a whole-body motion, impacts, or environmental effects. Hybrid devices enhance realism by combining kinesthetic force feedback with tactile stimulation, resulting in a more complete and convincing sensorimotor experience in VR.

7. Design Constraints and Challenges in Haptic Systems

7.1. System Bulk and Mechanical Complexity

Haptic and force-feedback devices remain inherently cumbersome due to their mechanical complexity, physical size, and overall weight. They often rely on rigid structures, multiple actuators, and external support frames to generate precise forces or tactile cues. While such an architecture enables high-fidelity feedback, it can reduce portability and the ergonomic user comfort. As a result, integrating haptic technologies into everyday virtual or augmented reality applications requires a very careful balance between performance, ergonomics, and practical and technical deployment constraints.

7.2. Installation Requirements and Safety Considerations

The installation of haptic systems introduces technical and safety challenges, particularly in relation to electrical conductors, power delivery, and actuator behavior. Poor insulation, inadequate cable management, or control system failures may expose users to real electrical risks or unintended mechanical forces. In order to mitigate these hazards, haptic systems have to adhere to a strict safety standard and incorporate fail-safe mechanisms, robust control logic, and real-time monitoring ensuring reliable and secure operation during human interaction.

7.3. Degree of Motion Freedom and Device Grounding

The degree of motion freedom provided by a haptic device impacts directly both realism and usability. Grounded systems, fixed to an external structure such as a desk or frame, generate high forces and precise motion constraints but inherently limit the user mobility. In contrast, ungrounded or wearable devices allow greater freedom of movement and support mobile or room-scale experiences, although this typically comes at the cost of considerable reduced force output and stability. Choosing between grounded and ungrounded designs therefore involves a careful trade-off based on application requirements.

7.4. Control of Stimulus Magnitude

The magnitude of haptic stimuli has a critical role in shaping the perceived intensity and realism of interaction. Weak feedback may fail to convey meaningful physical properties, while excessive forces, pressures, or vibrations can overwhelm the user or distort perception. Effective haptic system design depends on precise control of stimulus amplitude to achieve the perceptual relevance without compromising the user comfort or the system reliability.

7.5. Modulation Within Human Tolerance Limits

Crucially, all haptic stimuli must be modulated within the physiological and perceptual limits of the human body. Muscles, joints, and sensory receptors possess well-defined tolerance thresholds beyond which discomfort, fatigue, or injury occur. Respecting these limits through well-defined and adaptive control strategies, safety constraints, and user-specific calibration is very essential to ensure both physical safety and long-term usability, while still maintaining a convincing and immersive sensorimotor experience.