Introduction to Animated Applications

Author: Abdelkrim Mebarki

Master's Program in Computer Science – Artificial Intelligence & Applications
Department of Computer Science – Faculty of Mathematics and Computer Science
University of Science and Technology of Oran

October 18, 2025

1. Application domains

Animated Multimedia Applications are present in every domain of informatics. They play crucial roles whenever communication engages multiple modalities and multiple dimensions of human perception. Here are some application domains:

1.1. Artificial Intelligence and Intelligent Assistance

Applied in games, software guidance, and e-governance platforms to improve decision-making, automate management processes, and personalize user experiences.

1.2. E-Learning

Development of interactive educational material, didactic courses, and multimedia demonstrations that facilitate remote and lifelong learning making it more efficient.

1.3. Accessibility

Design of software, games, and applications adapted for people with disabilities (e.g., visually impaired or hearing-impaired users), improving inclusivity and equal access to digital resources.

1.4. Extended Reality (VR – AR)

Creation of immersive and mixed environments that simulate real or imagined scenarios for training, entertainment, therapy, and exploration.

1.5. Performance and Decision Support

Solutions that optimize usage efficiency, assist in complex and tough decision-making, and provide analytical support in professional contexts.

1.6. Communication

Enrichment of traditional communication channels through multimedia elements such as video conferencing, interactive media, and social platforms.

1.7. Scientific Applications

Use of simulations (e.g., chemical reactions, physical processes) and advanced data and information visualization to support research, experimentation, and knowledge dissemination.

2. What is Computer Animation?

Computer animations are digital generation of motion and transformation within a multimedia scene, enabling the visualization of changes in objects or hollow entities over time. They provide a dynamic representation that goes beyond static imagery by simulating temporal evolution.

2.1. Underlying Nature

The physical world is naturally dynamic, ruled by time-dependent phenomena such as movement, transformation, and interaction. Capturing this dynamic concept is essential for accurately reflecting reality or building convincing virtual scenarios.

2.2. Perceptual Dimension

Human beings perceive dynamic scenes directly through their sensory systems, particularly vision and hearing, which are highly sensitive to movement and temporal variation. Computer animations exploit this perceptual capacity and present visual sequences that align with natural cognitive processes, thereby creating a continuous sense of intuitive motion.

Available on zenodo – DOI : 10.5281/zenodo.17387686

2.3. Dynamic in multimedia modalities

The vision is a perceptual modality that is **intrinsically spatial** rather than inherently dynamic. The human perceives the world through **static snapshots** captured at discrete units in time; motion and dynamic change are **interpreted by the brain** as a succession of these static frames processed over time. On the other hand, **sound and haptic perception** are **fundamentally dynamic**, as they depend on **temporal variation** for their definition and perception. It is clear that there is no existence of "static sound" or "static touch sensation" in the physical or perceptual sense. Both of the two modalities require **continuous change over time** (pressure fluctuations for sound, or force and motion variations for haptics) to be perceived. While vision constructs motion from stillness, audition and touch can only **exist through movement and temporal evolution**.

3. How to create a computer animation?

To create an animation, we must follow a **pipeline** defined over **three stages**, each including one or more steps:

3.1. Static Definition

This stage involves the design of the virtual environment and its components via two steps:

- ➔ **Asset creation**: Modeling, texturing, scanning, photography, or importing ready-made assets.
- ➔ **Scene setup**: Placing objects in the virtual environment, defining lighting and spatial relationships.

  → The resulting models correspond to the **static virtual world**.

3.2. Dynamic Virtual World

In this stage, we introduce motion and transformation via one step:

- ➔ **Animation**: Introducing movement through keyframes, motion capture, procedural animation, or physics-based simulations.

  → Here the *scenario* governs how objects/entities evolve over time. This matches your **scenario-driven dynamic world**.

3.3. Computer Animation (Perceptual Rendering)

In this stage, we translate the dynamic scene into perceivable motion via two steps:

- ➔ **Rendering**: Computing and displaying frames that visualize the dynamic world.
- ➔ **Post-production**: Adding effects, synchronization, and refinement to create continuity and realism.

  → This produces the **illusion of movement** perceived by the user.

4. Animation classifications

Animation can be classified according to two main dimensions: the **mode of execution** and the **mode of use**.

4.1. By Mode of Execution (How the animation is produced)

- ➔ **Frame-by-frame animation** → Traditional cinema, cartoons, stop-motion (each frame drawn/recorded individually).
- ➔ **Automated/Procedural animation** → Generated automatically by rules, physics, algorithms, or AI (e.g., simulating fluids, growing a tree, ragdoll physics).

4.2. By Mode of Use (How the animation is delivered/consumed)

- ➔ **Real-time animation** → Computed on the fly, responding to user input (e.g., video games, VR, simulators).
- ➔ **Pre-rendered animation** → Precomputed and played back as a sequence of frames (e.g., animated films, cinematic cutscenes).

5. Interactivity in Multimedia Applications

Interactivity is a key concept in any multimedia application if user immersion or engagement is sought.

5.1. Definition and Scope

Interactivity in multimedia applications is the capacity of the system to adapt the rendering of its content in real time according to the user actions, inputs, and behaviors. Unlike non-interactive media, which present fixed and predetermined content, interactive multimedia generates or modifies content dynamically, creating a feedback loop continuous over time between system and user.

5.2. Synchronized Rendering

A distinctive feature of advanced interactive application is the synchronization between user inputs and actions and media rendering. In such contexts, the content is not static but generated or modified on the fly in response to the user's behavior. Examples include:

- ➔ **Virtual Reality (VR) environments and games** – User head and body movements instantly modify the viewpoint and the scene rendering.
- ➔ **AI-powered support assistants** – Dynamically adjust dialogues, visualizations, or recommendations depending on user queries.
- ➔ **Training simulators** (e.g., flight or surgical simulators) – Every user action has an immediate effect on the simulated environment.

This synchronized interactivity transforms media from a passive and static communication channel into a responsive and adaptive system, enhancing immersion, personalization, and learning effectiveness.

5.3. Technical Realization of Interactive Rendering

The implementation of synchronized interactivity relies on four components:

Input Capture

- ➔ Devices such as controllers, motion sensors, eye trackers, or microphones capture user actions in real time.
- ➔ These signals are continuously sampled and transmitted to the application.

Processing and Interpretation

- ➔ The system interprets the user input through computing algorithms, including physics engines, gesture recognition, natural language processing, and AI decision-making models.
- ➔ Predictive models can be used to anticipate user actions, allowing proactive adaptation of content.

Content Generation

- ➔ The multimedia content elements (graphics, animations, sounds, or haptic feedback) are dynamically generated or updated based on the interpreted input.
- ➔ Rendering engines (2D/3D graphics pipelines, audio engines) ensure that the response of the system is perceptually seamless.

Feedback Delivery

- ➔ The adapted content is rendered back to the user through visual, auditory, or tactile peripherals.
- ➔ Synchronization ensures that the feedback latency remains below the human perceptual thresholds, maintaining immersion and engagement.

☑ **In summary:** Interactive multimedia applications go beyond the static content delivery by establishing a real-time, synchronized deal loop between the user and the system. This deal is achieved through the continuous capture, interpretation, generation, and feedback of multimedia data and decisions. The result is a dynamic and adaptive environment where user actions and inputs directly shape the evolution of the content, enabling user engagement and immersive experiences such as VR and AR, AI-driven assistance, and advanced training simulations.