



Lecture 49 Review: Syncing Local Variables with Incoming Props

A quick-reference guide to the core concepts introduced in lecture 49. Review this table to solidify your understanding of Svelte 5's prop reactivity before moving on.

SCENARIO / OBJECTIVE	IMPLEMENTATION RULES
How to sync a local variable with an incoming prop? Keep a local variable continuously updated when the parent passes new data.	 CORRECT: Use the <code>\$derived</code> rune to maintain a continuous reactive connection. <pre>let likes = \$derived(post.likes);</pre>  WARNING: Don't use <code>\$state</code>, which only reads the prop once during creation and then ignores future updates. <pre>let likes = \$state(post.likes);</pre>

How to temporarily override a derived value?

Update the UI immediately before the server confirms the change (Optimistic UI).



CORRECT: Reassign the `$derived` variable directly. The override will be washed away when the parent updates the prop.

```
likes += 1;
```



WARNING: Don't declare the derived variable with `const` if you intend to override it.

How to two-way bind a prop?

Allow a child component to push changes back up to the parent component.



CORRECT: Declare the prop as `$bindable()`.

```
let { text =  
  $bindable('') } =  
  $props();
```



WARNING: Don't mutate standard, one-way props directly.

How to write a multi-statement derivation?

Use an intermediate variable or loop to calculate a derived value.



CORRECT: Pass a callback function into

```
$derived.by() .
```

```
`let str =  
$derived.by(() =>  
{ return  
  text.trim(); });`
```



WARNING: Don't mutate other state inside the derivation. It must be side-effect-free.

How to destructure a prop?

Pull properties off the `$props` object without losing reactivity.



CORRECT: Read properties directly from the object in the template, or read through an intermediate prop object.

```
let p = $props();  
<p>{p.title}</p>
```



WARNING: Don't destructure into primitives, which severs the reactive connection.

```
let { title } =  
$props();
```

How to sync an editable local draft?

A form draft that the user can edit, but also syncs if the parent updates the source.



CORRECT: Carefully combine

`$state(prop.value)` with an `$effect()` to push upstream changes into the local draft.

```
$effect(() => {  
  draft = user.name;  
});
```



WARNING: Default to `$derived` first; only reach for this when editability and continuous sync are both required.