

APT

Geotechnical Solutions Ltd

CONSTANT DISCHARGE AND RECOVERY

BOREHOLE TEST RECORD, APT GEOTECHNICAL SOLUTIONS

BOREHOLE NO:	MDW 14	LATITUDE:		CONTRACTOR:	APT
ALTBH NO:		LONGITUDE:		SITE NAME:	MALUNDWE
ALT BH NO:		ELEVATION:		CLIENT:	LMC
BOREHOLE DEPTH:	180	DATUM/LEVEL ABOVE CASING(m):		EXISTING PUMP:	NEW HOLE
WATER LEVEL:	58.24	CASING HEIGHT(m):	0.23	CONTRACTOR	
DEPTH OF PUMP:	148.25	DIAMETER PUMP INLET(mm):	230	PUMP TYPE	W110 - 2

CONSTANT DISCHARGE TEST & RECOVERY

TEST STARTED:				TEST COMPLETED:			
DATE	TIME	DATE	TIME	DATE	TIME	DATE	TIME
13-10-25	09:30						
DISCHARGE BOREHOLE				OBSERVATION HOLE 1			
TIME	WATER	DRAW	YIELD	TIME	WATER	DRAW	RECOVERY
(MIN)	LEVEL (M)	DOWN (M)	(L/S)	(MIN)	LEVEL (M)	DOWN (M)	WATER LEVEL(M)
0				0			
0.5	61.38	3.14		0.5	86.43	0.00	27.04
1	63.82	5.58		1	83.67	0.00	27.04
2	68.31	10.07		2	75.42	0.00	27.04
3	71.51	13.27	3.89	3	70.20	0.00	27.04
5	75.95	17.71	4.05	5	65.95	0.00	27.04
7	78.94	20.70	4.21	7	63.85	-0.01	27.04
10	81.82	23.58	4.10	10	63.35	-0.01	27.04
15	84.50	26.26	4.18	15	62.58	-0.02	27.04
20	85.90	27.66	4.36	20	62.03	-0.02	27.04
30	87.45	29.21	4.40	30	61.29	-0.02	27.04
40	88.19	29.95	4.22	40	60.82	-0.02	27.05
60	88.92	30.68	4.21	60	60.27	-0.02	27.05
90	89.13	30.89	4.14	90	59.84	-0.03	27.05
120	89.37	31.13	4.19	120	59.60	-0.03	27.03
150	89.22	30.98	4.15	150	59.46	-0.03	27.03
180	89.01	30.77	4.13	180	59.40	-0.03	27.02
210	89.43	31.19	4.20	210	59.26	-0.01	27.01
240	89.93	31.35	4.10	240	59.18	0.00	27.00
300	89.43	31.19	4.05	300	59.08	0.00	27.99
360	89.43	31.19	4.10	360	58.99	0.01	26.97
420	89.13	30.89	4.09	420	58.92	0.03	26.97
480	89.14	30.90	4.18	480	58.88	0.04	26.97
540	89.68	31.44	4.11	540	58.83	0.04	26.96
600	90.06	31.82	4.13	600	58.81	0.04	26.96
720	89.81	31.57	4.17	720	58.76	0.05	26.96
840	89.92	31.68	4.09	840	58.70	0.06	26.96
960	90.68	32.44	4.35	960	58.63	0.06	26.96
1080	91.06	32.82	4.39	1080	58.57	0.06	26.96
1200	91.19	32.95	4.10	1200	58.54	0.08	26.98
1320	91.09	32.85	4.18	1320	58.53	0.08	26.98
1440	90.54	32.30	4.12	1440	58.52	0.10	26.98
1560	90.04	31.80	4.15	1560	58.48	0.12	26.99
1680				1680	58.41		
1800	89.90	31.66	4.05	1800	58.41	0.15	26.95
1920	89.82	31.58	4.06	1920	58.39	0.22	26.95
2040	90.23	31.99	4.08	2040	58.37	0.22	26.95
2160	90.76	32.52	4.08	2160	58.37	0.22	26.95
2280	91.02	32.78	4.16	2280	58.33	0.25	26.95
2400	91.10	32.86	4.13	2400	58.32	0.25	26.95
2520	91.15	32.91	4.10	2520	58.32	0.28	26.95
2640	91.36	33.12	4.21	2640	58.29	0.32	26.95
2760	91.45	33.21	4.16	2760	58.31	0.34	26.95
2880	90.71	32.47	4.17	2880	58.32	0.34	26.95
3000	90.14	31.90	4.00	3000	58.28	0.35	26.94
3120	89.90	31.66	4.08	3120	58.26	0.35	26.93
3240	89.94	31.70	3.92	3240	58.25	0.34	26.93
3360	89.96	31.72	3.99	3360		0.35	
3480	90.52	32.28	4.01	3480	26.84	0.36	
3600	90.97	32.73	4.06	3600	26.84	0.36	
3720	91.19	32.95	4.12	3720	26.85	0.37	
3840	91.36	33.12	4.10	3840	26.84	0.36	
3960	91.54	33.30	4.06	3960	26.83	0.35	
4080	91.70	33.46	4.01	4080	26.83	0.35	
4200	91.69	33.45	4.12	4200	26.85	0.37	
4320	91.00	32.76	4.08	4320	26.84	0.36	
4560	90.38	32.14	3.89	4560	26.82	0.34	
4800	90.61	32.37	4.06	4800	26.82	0.34	
5040	91.27	33.03	4.01	5040	26.82	0.34	
5280	91.66	33.42	4.02	5280	26.82	0.34	
5520	91.98	33.74	4.04	5520	26.82	0.34	
5760	91.17	32.93	3.97	5760	26.88	0.40	
6000				6000			
6240	90.99	32.75	4.10	6240	26.93	0.45	
6480	91.60	33.36	4.01	6480	26.99	0.51	
6720	91.75	33.51	4.00	6720	26.94	0.51	
6960	92.07	33.83	3.97	6960	26.98	0.50	
7200	91.17	32.93		7200	27.04	0.56	

AVAILABLE PRAWDOWN : 90.01