

57 / 62

CMS 매핑 필드 (유사 매칭 포함)

6

확인 필요 (추정·미매핑)

Category	Field (CMS)	Value
Video	Imaging Device	1/2.7" Progressive CMOS
Video	Max Resolution	2688×1520
Video	Main Stream Resolution	2688×1520, 2304×1296, 1920×1080, 1280×720
Video	Sub Stream Resolution	1280×720, 640×480, 320×240
Video	Mobile Stream Resolution	N/A
Video	Max Framerate	15fps/15fps (60Hz/50Hz)
Video	Min. Illumination (Color)	0.005 lux @ F1.2 (AGC ON)
Video	Min. Illumination (B/W)	0 lux @ IR ON
Lens	Focal Length	2.8mm
Lens	Lens Type	Fixed
Lens	Angular Field of View	H:109.7° V:57.6° D:131°
Lens	Max. Aperture Ratio	F1.2
Lens	Min. Object Distance	4.9ft (1.5m)
Pan / Tilt / Rotate	Pan / Tilt / Rotate Range	Four flexible lenses in one track, slide range: -50° to 50°, tilt: 0° to 75°, rotate: 0° to 90°
Operational	Day & Night	Full Color Mode / Day & Night Mode / Smart Illumination
Operational	Wide Dynamic Range	120dB
Operational	Digital Noise Reduction	3D DNR
Operational	Analytics	Human & Vehicle, Tripwire Detection, Stationary Object Detection, Tripwire Count, Heat Map, Crowd Density, Queue Length, License Plate, Rare Sound, Loitering, Region Entrance, Region Exiting
Operational	Active Deterrence	Yes
Operational	Camera Title	Up to 31 characters
Operational	Backlight Compensation	BLC, HLC, WDR
Operational	Motion Detection	Rectangle Grid (8 Levels of Sensitivity)
Operational	Privacy Masking	6 Rectangle Zones
Operational	Gain Control	Auto
Operational	White Balance	Auto/Manual
Operational	Electric Shutter Speed	Auto / Manual (1/5 ~ 1/20000s)
Operational	Video Rotation	Flip, Corridor, Angle Adjustment
Operational	Alarm Triggers	Motion, Alarm, Sound Detection
Operational	Alarm Events	Warning Light, Siren, Event Push, E-mail Notification, Image file upload via FTP, Video file upload via FTP, Micro SD recording at event triggered
Operational	Light Viewable Length	IR: Up to 65ft (20m), White Light: Up to 65ft (20m)

Category	Field (CMS)	Value
Network	Ethernet	RJ45(10/100BASE-T)
Network	Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Network	Bitrate Control	CBR (256Kbps ~ 8Mbps), VBR (256Kbps ~ 8Mbps)
Network	Streaming	Unicast / Multicast
Network	Application Programming Interface	ONVIF Profile S/G/T/M
Security	Additional Security 추정	IP address filter, Password protection, Digest authentication, Complicated password, IEEE 802.1X authentication, WSSE for ONVIF, Brute-Force Defense, HTTPS TLS 1.2/1.3, SNMPv1.3, RTSP over HTTPS, Security audit log, Encrypted firmware, Host authentication (MAC-address), Auto logout, watermark, Secure boot
General	SD Card Slot	Micro SD slot, up to 512GB
General	Starllion Ready	Yes
General	Ingress Protection	IP67, IK08
General	Camera System	Network
General	Product Series	Diversity
General	Product Dimensions	Ø7.87" × 3.46" (Ø200 × 88 mm)
General	Product Weight	6.48 lb (2.94 kg)
General	Material	Metal
General	Color	White
Mechanical	Housing Style	Multi-sensor
DORI	Detect (25PPM/ 8PPF)	Detection 167ft (50.9m), Observation 66.9ft (20.4m), Recognition 33.5ft (10.2m), Identification 16.7ft (5.1m)
Interface	Alarm Input	1 x Input, 1 x Output
Interface	Audio Input	Built-in MIC / Speaker
Electrical & Environmental	Power Consumption	12VDC: max. 16.8 W, 24VAC: max. 17.86 W, PoE+ (48V): max. 18.7 W
Electrical & Environmental	Operating Temperature	-22°F to 140°F (-30°C to +60°C) / ≤ 90% RH
Electrical & Environmental	Power Input Voltage	PoE+ (IEEE 802.3at) / 12VDC / 24VAC
Certification & Standards	NDAA Compliant	Yes
Certification & Standards	EMC	EN 55032:2015+A1:2020, EN 55035:2017+A11:2020, EN IEC 61000-3-2:2019+A2:2020, EN 61000-3-3:2013+A2:2021+AC:2022-01
Certification & Standards	Safety	CE: EN IEC 62368-1:2020+A11:2020, FCC: FCC Rules and Regulations Part 15 Subpart B
Performance	Video Compression	H.265/H.264/H.265+/H.264+/MJPEG
Performance	Audio Compression	G.711A/U

완전 일치가 아니라 유사 항목으로 자동 추정한 필드와, 대응 항목을 찾지 못한 필드입니다. 편집기에서 확인·수정하세요.

Security → Additional Security IP address filter, Password protection, Digest authentication, Complicated password, I	추정 매핑
White LED → — 8	미매핑
Red / Blue LED → — N/A	미매핑
GENERAL General → — CBR (256Kbps ~ 8Mbps), VBR (256Kbps ~ 8Mbps)	미매핑
Environment → EMC CE-RoHS:(EU) 2015/863, IEC60529, IEC60068-2-14	추천 있음
IR LED → — 8	미매핑

2 검출

2 반영

2 표준

Field	유형	수정 내용	변경 (전 → 후)
Alarm Events	표준	microSD 표준 표기 (한 단어)	Micro SD → microSD
SD Card Slot	표준	microSD 표준 표기 (한 단어)	Micro SD → microSD

2 검출

2 반영

2 표준

Field	수정 전	수정 후	반영
Alarm Events	Warning Light, Siren, Event Push, E-mail Notification, Image file upload via FTP, Video file upload via FTP, Micro SD recording at event triggered	Warning Light, Siren, Event Push, E-mail Notification, Image file upload via FTP, Video file upload via FTP, microSD recording at event triggered	반영
SD Card Slot	Micro SD slot, up to 512GB	microSD slot, up to 512GB	반영

AVC-NCMMS161F04

AI

NDAA
COMPLIANT

TAA
COMPLIANT

CE

FC

16MP H.265 MULTI-SENSOR NETWORK CAMERA

OVERVIEW

- 4MP x 4ch Multi-directional, each sensor manually adjustable
- 2688x1520 H.265/H.265+/H.264/H.264+/MJPEG
- Max. resolution: 2688x1520
- Full Color / Active Deterrence Camera
- 2.8mm Fixed Lens (F1.2)
- 3D DNR, WDR, HLC, BLC
- Intelligent Analytics
- IR LED/ White Light LED
- Built-in MIC / Speaker
- Built-in microSD card slot, up to 512GB
- IP67 / IK08 ingress protection
- PoE+ / 12VDC / 24VAC power supply
- Remote monitoring with mobile app and management software

DIMENSIONS

Unit : inch(mm)



OPTIONAL ACCESSORIES

SPECIFICATIONS (1 / 2)

VIDEO	
Imaging Device	1/2.7" Progressive CMOS
Max Resolution	2688x1520
Main Stream Resolution	2688x1520, 2304x1296, 1920x1080, 1280x720
Sub Stream Resolution	1280x720, 640x480, 320x240
Mobile Stream Resolution	N/A
Max Framerate	15fps/15fps (60Hz/50Hz)
Min. Illumination (Color)	0.005 lux @ F1.2 (AGC ON)
Min. Illumination (B/W)	0 lux @ IR ON
LENS	
Focal Length	2.8mm
Lens Type	Fixed
Angular Field of View	H:109.7° V:57.6° D:131°
Max. Aperture Ratio	F1.2
Min. Object Distance	4.9ft (1.5m)
PAN / TILT / ROTATE	
Pan / Tilt / Rotate Range	Four flexible lenses in one track, slide range: -50° to 50°, tilt: 0° to 75°, rotate: 0° to 90°
OPERATIONAL	
Day & Night	Full Color Mode / Day & Night Mode / Smart Illumination
Wide Dynamic Range	120dB
Digital Noise Reduction	3D DNR
Analytics	Human & Vehicle, Tripwire Detection, Stationary Object Detection, Tripwire Count, Heat Map, Crowd Density, Queue Length, License Plate, Rare Sound, Loitering, Region Entrance, Region Exiting
Active Deterrence	Yes
Camera Title	Up to 31 characters
Backlight Compensation	BLC, HLC, WDR
Motion Detection	Rectangle Grid (8 Levels of Sensitivity)
Privacy Masking	6 Rectangle Zones
Gain Control	Auto
White Balance	Auto/Manual
Electric Shutter Speed	Auto / Manual (1/5 ~ 1/20000s)
Video Rotation	Flip, Corridor, Angle Adjustment
Alarm Triggers	Motion, Alarm, Sound Detection
Alarm Events	Warning Light, Siren, Event Push, E-mail Notification, Image file upload via FTP, Video file upload via FTP, microSD recording at event triggered
Light Viewable Length	IR: Up to 65ft (20m), White Light: Up to 65ft (20m)
NETWORK	
Ethernet	RJ45(10/100BASE-T)
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Bitrate Control	CBR (256Kbps ~ 8Mbps), VBR (256Kbps ~ 8Mbps)
Streaming	Unicast / Multicast
Application Programming Interface	ONVIF Profile S/G/T/M

SPECIFICATIONS

(2 / 2)

SECURITY	
Additional Security	IP address filter, Password protection, Digest authentication, Complicated password, IEEE 802.1X authentication, WSSE for ONVIF, Brute-Force Defense, HTTPS TLS 1.2/1.3, SNMPv1.3, RTSP over HTTPS, Security audit log, Encrypted firmware, Host authentication (MAC-address), Auto logout, watermark, Secure boot
GENERAL	
SD Card Slot	microSD slot, up to 512GB
Starllion Ready	Yes
Ingress Protection	IP67, IK08
Camera System	Network
Product Series	Diversity
Product Dimensions	Ø7.87" × 3.46" (Ø200 × 88 mm)
Product Weight	6.48 lb (2.94 kg)
Material	Metal
Color	White
MECHANICAL	
Housing Style	Multi-sensor
DORI	
Detect (25PPM/ 8PPF)	Detection 167ft (50.9m), Observation 66.9ft (20.4m), Recognition 33.5ft (10.2m), Identification 16.7ft (5.1m)
INTERFACE	
Alarm Input	1 x Input, 1 x Output
Audio Input	Built-in MIC / Speaker
ELECTRICAL & ENVIRONMENTAL	
Power Consumption	12VDC: max. 16.8 W, 24VAC: max. 17.86 W, PoE+ (48V): max. 18.7 W
Operating Temperature	-22°F to 140°F (-30°C to +60°C) / ≤ 90% RH
Power Input Voltage	PoE+ (IEEE 802.3at) / 12VDC / 24VAC
CERTIFICATION & STANDARDS	
NDAA Compliant	Yes
EMC	EN 55032:2015+A1:2020, EN 55035:2017+A11:2020, EN IEC 61000-3-2:2019+A2:2024, EN 61000-3-3:2013+A2:2022+AC
Safety	CE: EN IEC 62368-1:2020+A11:2020, FCC: FCC Rules and Regulations Part 15 Subpart B
PERFORMANCE	
Video Compression	H.265/H.264/H.265+/H.264+/MJPEG
Audio Compression	G.711A/U

AVC-NCMMS161F04

AI

NDAA
COMPLIANT

TAA
COMPLIANT

CE

FC

16MP H.265 MULTI-SENSOR NETWORK CAMERA

OVERVIEW

- 4MP x 4ch Multi-directional, each sensor manually adjustable
- 2688x1520 H.265/H.265+/H.264/H.264+/MJPEG
- Max. resolution: 2688x1520
- Full Color / Active Deterrence Camera
- 2.8mm Fixed Lens (F1.2)
- 3D DNR, WDR, HLC, BLC
- Intelligent Analytics
- IR LED/ White Light LED
- Built-in MIC / Speaker
- Built-in microSD card slot, up to 512GB
- IP67 / IK08 ingress protection
- PoE+ / 12VDC / 24VAC power supply
- Remote monitoring with mobile app and management software

DIMENSIONS

Unit : inch(mm)



OPTIONAL ACCESSORIES

SPECIFICATIONS (1 / 2)

VIDEO	
Image Sensor	1/2.7" Progressive CMOS
Max. Resolution	2688x1520
Main Stream Resolution	2688x1520, 2304x1296, 1920x1080, 1280x720
Sub Stream Resolution	1280x720, 640x480, 320x240
Mobile Stream Resolution	N/A
Max. Framerate	15fps/15fps (60Hz/50Hz)
Min. Illumination (Color)	0.005 lux @ F1.2 (AGC ON)
Min. Illumination (B/W)	0 lux @ IR ON
Video Compression	H.265/H.264/H.265+/H.264+/MJPEG
Audio Compression	G.711A/U
Focal Length	2.8mm
Lens Type	Fixed
Angular Field of View	H:109.7° V:57.6° D:131°
Max. Aperture Ratio	F1.2
Min. Object Distance	4.9ft (1.5m)
DORI	Detection 167ft (50.9m), Observation 66.9ft (20.4m), Recognition 33.5ft (10.2m), Identification 16.7ft (5.1m)
Pan / Tilt / Rotate Range	Four flexible lenses in one track, slide range: -50° to 50°, tilt: 0° to 75°, rotate: 0° to 90°
IR LED	8
White LED	8
Red / Blue LED	N/A
Light Viewable Length	IR: Up to 65ft (20m), White Light: Up to 65ft (20m)
Image Mode	Full Color Mode / Day & Night Mode / Smart Illumination
Audio	Built-in MIC / Speaker
Alarm	1 x Input, 1 x Output
Wide Dynamic Range	120dB
Digital Noise Reduction	3D DNR
Analytics	Human & Vehicle, Tripwire Detection, Stationary Object Detection, Tripwire Count, Heat Map, Crowd Density, Queue Length, License Plate, Rare Sound, Loitering, Region Entrance, Region Exiting
Active Deterrence	Yes
Camera Title	Up to 31 characters
Backlight Compensation	BLC, HLC, WDR
Motion Detection	Rectangle Grid (8 Levels of Sensitivity)
Privacy Masking	6 Rectangle Zones
Gain Control	Auto
White Balance	Auto/Manual
Electronic Shutter Speed	Auto / Manual (1/5 ~ 1/20000s)
Video Rotation	Flip, Corridor, Angle Adjustment
Alarm Triggers	Motion, Alarm, Sound Detection
Alarm Events	Warning Light, Siren, Event Push, E-mail Notification, Image file upload via FTP, Video file upload via FTP, Micro SD recording at event triggered

SPECIFICATIONS (2 / 2)

NETWORK	
Ethernet	RJ45(10/100BASE-T)
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Security	IP address filter, Password protection, Digest authentication, Complicated password, IEEE 802.1X authentication, WSSE for ONVIF, Brute-Force Defense, HTTPS TLS 1.2/1.3, SNMPv1.3, RTSP over HTTPS, Security audit log, Encrypted firmware, Host authentication (MAC-address), Auto logout, watermark, Secure boot
Bitrate Control	CBR (256Kbps ~ 8Mbps), VBR (256Kbps ~ 8Mbps)
Streaming	Unicast / Multicast
Application Programming Interface	ONVIF Profile S/G/T/M
GENERAL General	CBR (256Kbps ~ 8Mbps), VBR (256Kbps ~ 8Mbps)
SD Card Slot	Micro SD slot, up to 512GB
Starllion Ready	Yes
Ingress Protection	IP67, IK08
Camera System	Network
Product Series	Diversity
Product Dimensions	Ø7.87" × 3.46" (Ø200 × 88 mm)
Product Weight	6.48 lb (2.94 kg)
Material	Metal
Color	White
Housing Style	Multi-sensor
ELECTRICAL & ENVIRONMENTAL	
Power Consumption	12VDC: max. 16.8 W, 24VAC: max. 17.86 W, PoE+ (48V): max. 18.7 W
Power Input Voltage	PoE+ (IEEE 802.3at) / 12VDC / 24VAC
Operating Condition	-22°F to 140°F (-30°C to +60°C) / ≤ 90% RH
CERTIFICATION & STANDARDS	
NDAA Compliant	Yes
EMC	EN 55032:2015+A1:2020, EN 55035:2017+A11:2020, EN IEC 61000-3-2:2019+A2:2024, EN 61000-3-3:2013+A2:2022+A1
Safety	CE: EN IEC 62368-1:2020+A11:2020, FCC: FCC Rules and Regulations Part 15 Subpart B
Environment	CE-RoHS:(EU) 2015/863, IEC60529, IEC60068-2-14