

38

확인 필요 (추정·미매핑)

	Value
	1/1.8"
추정	Main Stream : 4MP (2688×1520), 3MP (2304×1296),1080P (1920×1080), 720P (1280×720) Sub Stream : 720P (1280×720),VGA (640×480),QVGA (320×240) Mobile Stream : VGA (640×480), QVGA (320×240)
Color) 추정	Color : 0.0005lux @ F1.0(AGC on); B/W 0 lux @ IR ON
추정	Progressive CMOS
	2.8–12 mm
	Ø16.7
view	Horizontal:110–40°, Vertical:57–22°, Diagonal:137–46°
tio	F No. 1.2
nce	W:5.74 ft (1.75 m), T:17.09 ft (5.21 m)
nge	WDR
uction	3D DNR
	Default warm light, switchable infrared light
	Off/On (8 Level)
	Auto/Manual
peed	1/5 ~ 1/20000s
ngth 추정	Up to 98.43 ft (30 m)
정	Up to 82.02 ft (25 m)
	Full Color Mode/Day&Night Mode/Smart Illumination
	RJ45 (10/100BASE-T)
	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
정	CBR/VBR
amming Interface	ONVIF (Profile S/G/T)
cation 추정	1 RJ45 10 M / 100 M self-adaptive Ethernet port
y 추정	IP address filter; complicated password; Authenticated username and password
n	IP67
	Metal
	1 input, 1 output
	1 input (RCA), 1 output (RCA), Built-in microphone&Speaker
on 추정	4-pin waterproof connector, 3.5DC connector, 60 W (deviation: ± 2 W) Solar panels, max.8.7W
perature	Charging : -4 °F to 113 °F (-20 °C to 45 °C) Discharging : -4 °F to 140 °F (-20 °C to 60 °C)

AVC-SNDB41M-4G	
	Value
ty 추정	-4 °F to 140 °F (-20 °C to 60 °C). Humidity 95% or less (non-condensing)
on 추정	H.265/H.264/H.265+/H.264+/MJPEG

AVC-SNDB41M-4G	
을 항목을 찾지 못한 필드입니다. 편집기에서 확인·수정하세요.	
	추정 매핑
	추정 매핑
	추정 매핑
	추정 매핑
	추정 매핑
	추정 매핑
n	추정 매핑
80P (1920×1080), 720P (1280×720) Sub	추정 매핑
	추정 매핑
username and password	추정 매핑
	추정 매핑
(non-condensing)	추정 매핑
eviation: ± 2 W) Solar panels, max	추정 매핑
	추천 있음
	추천 있음
	추천 있음

을 항목을 찾지 못한 필드입니다. 편집기에서 확인·수정하세요.

	추천 있음
	추천 있음
rossing Counting, Heat Map, Crow	추천 있음
	추천 있음
	미매핑
chrome : V.57 above Edge : V.	미매핑
	추천 있음
/7/8/12/13/18/19/20/25/26/28 WCDMA	추천 있음
	미매핑
	미매핑
	추천 있음
	추천 있음
	추천 있음
	추천 있음
	추천 있음
on	추천 있음
	추천 있음

을 항목을 찾지 못한 필드입니다. 편집기에서 확인·수정하세요.

age	추천 있음
	추천 있음
	미매핑
	미매핑
	미매핑

준

3 표기

	변경 (전 → 후)
공백	5lux @ F1.0 → 5 lux @ F1.0
표기 (한 단어)	Micro SD → microSD
	, → ,
	, → ,
	, → ,
호 띄어쓰기	IEEE802.11 → IEEE 802.11
이 공백 (W)	7W → 7 W
이 공백 (W)	0W → 0 W

준

3 표기

	수정 후	반영
0(AGC on); B/W 0 lux @ IR ON	Color : 0.0005 lux @ F1.0(AGC on); B/W 0 lux @ IR ON	반영
2GB	microSD slot, up to 512GB	반영
88×1520), 3MP 920×1080), 720P (1280×720) Sub 20),VGA (640×480),QVGA am : VGA (640×480), QVGA	Main Stream : 4MP (2688×1520), 3MP (2304×1296), 1080P (1920×1080), 720P (1280×720) Sub Stream : 720P (1280×720), VGA (640×480), QVGA (320×240) Mobile Stream : VGA (640×480), QVGA (320×240)	반영
	IEEE 802.11b/g/n; 2.4 G	반영
ector, 3.5DC connector, 60 W r panels, max.8.7W	4-pin waterproof connector, 3.5DC connector, 60 W (deviation: ± 2 W) Solar panels, max.8.7 W	반영
	60 W ± 5%	반영

AVC-SNDB41M-4G AI

NDAACOMPLIANT |  TAA COMPLIANT | CE | FCC

DIMENSIONS

64+/MJPEG

Unit : inch(mm)

nt

still image

NE (Mobile



×

×



VIDEO
Stream : 4MP (2688x1520), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720)
Stream : 720P (1280x720), VGA (640x480), QVGA (320x240)
le Stream : VGA (640x480), QVGA (320x240)
: 0.0005 lux @ F1.0(AGC on); B/W 0 lux @ IR ON
ressive CMOS
LENS
2 mm
7
ontal:110-40°, Vertical:57-22°, Diagonal:137-46°
1.2
4 ft (1.75 m), T:17.09 ft (5.21 m)
OPERATIONAL
NR
lt warm light, switchable infrared light
n (8 Level)
Manual
1/20000s
98.43 ft (30 m)
82.02 ft (25 m)
Color Mode/Day&Night Mode/Smart Illumination
NETWORK
(10/100BASE-T)
P, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
VBR
F (Profile S/G/T)
SECURITY
5 10 M / 100 M self-adaptive Ethernet port
dress filter; complicated password; Authenticated username and password
GENERAL
INTERFACE
ut, 1 output
ut (RCA), 1 output (RCA), Built-in microphone&Speaker
ELECTRICAL & ENVIRONMENTAL
waterproof connector, 3.5DC connector, 60 W (deviation: ± 2 W) Solar panels, max.8.7 W
ging : -4 °F to 113 °F (-20 °C to 45 °C)
arging : -4 °F to 140 °F (-20 °C to 60 °C)
to 140 °F (-20 °C to 60 °C). Humidity 95% or less (non-condensing)
PERFORMANCE
/H.264/H.265+/H.264+/MJPEG

AVC-SNDB41M-4G AI

NDAACOMPLIANT |  TAA COMPLIANT | CE | FCC

DIMENSIONS

64+/MJPEG

Unit : inch(mm)

nt

still image

NE (Mobile



×

×



VIDEO
2688(H)×1520(V)
ressive CMOS
: 0.0005lux @ F1.0(AGC on); B/W 0 lux @ IR ON
LENS
2 mm
1.2
ontal:110-40°, Vertical:57-22°, Diagonal:137-46°
4 ft (1.75 m), T:17.09 ft (5.21 m)
y
OPERATIONAL
98.43 ft (30 m)
82.02 ft (25 m)
ult warm light, switchable infrared light
n (8 Level)
NR
Color Mode/Day&Night Mode/Smart Illumination
'Manual
1/20000s
SD slot, up to 512GB
ut, 1 output
ut (RCA), 1 output (RCA), Built-in microphone&Speaker
strian&Vehicle, Line Crossing, Object Detection, Crossing Counting, Heat Map, Crowd Density, Queue Length, se Plate, Rare Sound, Intrusion, Region Entrance, Region Exiting
NETWORK
(10/100BASE-T)
s/H.264/H.265+/H.264+/MJPEG
Stream : 4MP (2688x1520), 3MP (2304x1296),1080P (1920x1080), 720P (1280x720)
Stream : 720P (1280x720),VGA (640x480),QVGA (320x240)
le Stream : VGA (640x480), QVGA (320x240)
bps ~ 16Mbps
VBR
P, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
dress filter; complicated password; Authenticated username and password
F (Profile S/G/T)
11
I : V12.1 above
ox : V.52 above
le chrome : V.57 above
: V.79 above
MOBILE COMMUNICATION
SIM
DD : Band 38/39/40/41
DD : Band 1/2/3/4/5/7/8/12/13/18/19/20/25/26/28
MA : Band 1/2/4/5/6/8/19
50/EGSM900/DCS1800/PCS1900
INTERFACES
5 10 M / 100 M self-adaptive Ethernet port
02.11b/g/n; 2.4 G
ENVIRONMENTAL
to 140 °F (-20 °C to 60 °C). Humidity 95% or less (non-condensing)
ELECTRICAL
waterproof connector, 3.5DC connector, 60 W (deviation: ± 2 W) Solar panels, max.8.7W
MECHANICAL
BATTERY
um
n × 4 packs
All the contents on the AVYCON's digital and printed marketing materials include product names, part number, unique identification letters, etc., are trademarks of AVYCON. Any unauthorized use or distribution of trademarked contents is strictly prohibited by law. In addition, graphical designs, images, features, and specifications on such materials may differ from the actual products and subject to change without notice. For the latest product information/specification please visit our website or contact one of our product specialists at marketing@avycon.com
ging : -4 °F to 113 °F (-20 °C to 45 °C)
arging : -4 °F to 140 °F (-20 °C to 60 °C)