

32 / 57

CMS 매핑 필드 (유사 매칭 포함)

38

확인 필요 (추정·미매핑)

Category	Field (CMS)	Value
Video	Imaging Device	1/1.8"
Video	Max Resolution 추정	Main Stream : 4MP (2688×1520), 3MP (2304×1296),1080P (1920×1080), 720P (1280×720) Sub Stream : 720P (1280×720),VGA (640×480),QVGA (320×240) Mobile Stream : VGA (640×480), QVGA (320×240)
Video	Min. Illumination (Color) 추정	Color : 0.0005lux @ F1.0(AGC on); B/W 0 lux @ IR ON
Video	Imaging System 추정	Progressive CMOS
Lens	Focal Length 추정	2.8–12 mm
Lens	Lens Type	Ø16.7
Lens	Angular Field of View	Horizontal:110-40°, Vertical:57-22°, Diagonal:137-46°
Lens	Max. Aperture Ratio	F No. 1.2
Lens	Min. Object Distance	W:5.74 ft (1.75 m), T:17.09 ft (5.21 m)
Operational	Wide Dynamic Range	WDR
Operational	Digital Noise Reduction	3D DNR
Operational	Light Type 추정	Default warm light, switchable infrared light
Operational	Motion Detection	Off/On (8 Level)
Operational	White Balance	Auto/Manual
Operational	Electric Shutter Speed	1/5 ~ 1/20000s
Operational	Light Viewable Length 추정	Up to 98.43 ft (30 m)
Operational	IR Wavelength 추정	Up to 82.02 ft (25 m)
Operational	Image Setting	Full Color Mode/Day&Night Mode/Smart Illumination
Network	Ethernet	RJ45 (10/100BASE-T)
Network	Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Network	Bitrate Control 추정	CBR/VBR
Network	Application Programming Interface	ONVIF (Profile S/G/T)
Security	Network Authentication 추정	1 RJ45 10 M / 100 M self-adaptive Ethernet port
Security	Additional Security 추정	IP address filter; complicated password; Authenticated username and password
General	Ingress Protection	IP67
General	Material	Metal
Interface	Alarm Input	1 input, 1 output
Interface	Audio Input	1 input (RCA), 1 output (RCA), Built-in microphone&Speaker
Electrical & Environmental	Power Consumption 추정	4-pin waterproof connector, 3.5DC connector, 60 W (deviation: ± 2 W) Solar panels, max.8.7W
Electrical & Environmental	Operating Temperature	Charging : -4 °F to 113 °F (-20 °C to 45 °C) Discharging : -4 °F to 140 °F (-20 °C to 60 °C)

Category	Field (CMS)	Value
Electrical & Environmental	Operating Humidity 추정	-4 °F to 140 °F (-20 °C to 60 °C). Humidity 95% or less (non-condensing)
Performance	Video Compression 추정	H.265/H.264/H.265+/H.264+/MJPEG

완전 일치가 아니라 유사 항목으로 자동 추정한 필드와, 대응 항목을 찾지 못한 필드입니다. 편집기에서 확인·수정하세요.

Scanning System → Imaging System Progressive CMOS	추정 매핑
Min. Illumination → Min. Illumination (Color) Color : 0.0005lux @ F1.0(AGC on); B/W 0 lux @ IR ON	추정 매핑
Focal Length (Zoom Ratio) → Focal Length 2.8–12 mm	추정 매핑
IR Viewable Length → Light Viewable Length Up to 98.43 ft (30 m)	추정 매핑
WarmLight Viewable Length → IR Wavelength Up to 82.02 ft (25 m)	추정 매핑
Type of complementary light → Light Type Default warm light, switchable infrared light	추정 매핑
Video Compression Format → Video Compression H.265/H.264/H.265+/H.264+/MJPEG	추정 매핑
Resolution → Max Resolution Main Stream : 4MP (2688×1520), 3MP (2304×1296),1080P (1920×1080), 720P (1280×720) Sub	추정 매핑
Bitrate control method → Bitrate Control CBR/VBR	추정 매핑
Security → Additional Security IP address filter; complicated password; Authenticated username and password	추정 매핑
Network → Network Authentication 1 RJ45 10 M / 100 M self-adaptive Ethernet port	추정 매핑
Operating Conditions → Operating Humidity -4 °F to 140 °F (-20 °C to 60 °C). Humidity 95% or less (non-condensing)	추정 매핑
Power → Power Consumption 4-pin waterproof connector, 3.5DC connector, 60 W (deviation: ± 2 W) Solar panels, max	추정 매핑
Effective Pixels → EPA (Effective Projected Area) 4MP 2688(H)×1520(V)	추천 있음
On-Board Storage → Mirror Image Micro SD slot, up to 512GB	추천 있음
Custom Voice → Function Control Yes	추천 있음

완전 일치가 아니라 유사 항목으로 자동 추정한 필드와, 대응 항목을 찾지 못한 필드입니다. 편집기에서 확인·수정하세요.

Hardware Reset → Alarm Events Yes	추천 있음
Smart Feature → Sharpness Pedestrian&Vehicle, Line Crossing, Object Detection, Crossing Counting, Heat Map, Crow	추천 있음
Video Quality Adjustment → Bitrate Control 256Kbps ~ 16Mbps	추천 있음
IP → — IPv6	미매핑
Web Viewer → — IE10/11 Safari : V12.1 above Firefox : V.52 above Google chrome : V.57 above Edge : V.	미매핑
SIM Card Type → SD Card Slot Micro SIM	추천 있음
Frequency → Streaming LTE-TDD : Band 38/39/40/41 LTE-FDD : Band 1/2/3/4/5/7/8/12/13/18/19/20/25/26/28 WCDMA	추천 있음
GSM → — GSM850/EGSM900/DCS1800/PCS1900	미매핑
Wi-Fi → — IEEE802.11b/g/n; 2.4 G	미매핑
Battery Type → Pattern Scan Lithium	추천 있음
Capacity → Camera Title 8.4 Ah × 4 packs	추천 있음
Battery Voltage → Power Input Voltage 10.8V	추천 있음
Max. Output Voltage → Power Input Voltage 12.6V	추천 있음
Battery Life → Pattern Scan More than 500 cycles	추천 있음
Battery Weight → Product Weight 1.49 lb (678 g)× 4 packs	추천 있음
Monocrystalline silicon → Mobile Stream Resolution photoelectric efficiency > 24%	추천 있음
Standard output power (@STC) → Alarm Output 60W ± 5%	추천 있음

완전 일치가 아니라 유사 항목으로 자동 추정한 필드와, 대응 항목을 찾지 못한 필드입니다. 편집기에서 확인·수정하세요.

Open circuit voltage (@STC) → Power Input Voltage 17V ± 5%	추천 있음
Standard operating → Streaming 14.8V/4.1A or 15V/4A	추천 있음
Short circuit current (@STC) → — < 4.3A	미매핑
IR LED → — 4	미매핑
WarmLight → — 4	미매핑

- 8 검출
- 6 반영
- 3 단위
- 2 표준
- 3 표기

Field	유형	수정 내용	변경 (전 → 후)
Min. Illumination	단위	lux·@ 사이 공백	5lux @ F1.0 → 5 lux @ F1.0
On-Board Storage	표준	microSD 표준 표기 (한 단어)	Micro SD → microSD
Resolution	표기	셈표 뒤 공백	, → ,
Resolution	표기	셈표 뒤 공백	, → ,
Resolution	표기	셈표 뒤 공백	, → ,
Wi-Fi	표준	IEEE 표준번호 띄어쓰기	IEEE802.11 → IEEE 802.11
Power	단위	수치·단위 사이 공백 (W)	7W → 7 W
Standard output power (@STC)	단위	수치·단위 사이 공백 (W)	0W → 0 W

8검출

6반영

3단위

2표준

3표기

Field	수정 전	수정 후	반영
Min. Illumination	Color : 0.0005lux @ F1.0(AGC on); B/W 0 lux @ IR ON	Color : 0.0005 lux @ F1.0(AGC on); B/W 0 lux @ IR ON	반영
On-Board Storage	Micro SD slot, up to 512GB	microSD slot, up to 512GB	반영
Resolution	Main Stream : 4MP (2688×1520), 3MP (2304×1296),1080P (1920×1080), 720P (1280×720) Sub Stream : 720P (1280×720),VGA (640×480),QVGA (320×240) Mobile Stream : VGA (640×480), QVGA (320×240)	Main Stream : 4MP (2688×1520), 3MP (2304×1296), 1080P (1920×1080), 720P (1280×720) Sub Stream : 720P (1280×720), VGA (640×480), QVGA (320×240) Mobile Stream : VGA (640×480), QVGA (320×240)	반영
Wi-Fi	IEEE802.11b/g/n; 2.4 G	IEEE 802.11b/g/n; 2.4 G	반영
Power	4-pin waterproof connector, 3.5DC connector, 60 W (deviation: ± 2 W) Solar panels, max.8.7W	4-pin waterproof connector, 3.5DC connector, 60 W (deviation: ± 2 W) Solar panels, max.8.7 W	반영
Standard output power (@STC)	60W ± 5%	60 W ± 5%	반영

AVC-SNDB41M-4G

AI



OVERVIEW

- 4MP (2688x1520) H.265/H.264/H.265+/H.264+/MJPEG
- Max. resolution: 2688x1520
- Full Color / Active Deterrence Camera
- 2.8-12mm Motorized Lens (F1.2)
- 3D DNR, WDR, HLC, BLC, ROI encoding
- Intelligent Analytics
- White Light LED / Strobe (Blue & Red) Light
- Built-in MIC / Speaker
- Built-in microSD card slot with video and still image capture function (up to 512GB)
- Standalone with solar panel and battery
- Support 4G (LTE-TDD, LTE-FDD, TD-SCDMA) communication
- IP67 ingress protection
- Support remote monitoring by AVYCON ONE (Mobile APP) and AVYCON CMSONE (CMS)

DIMENSIONS

Unit : inch(mm)



OPTIONAL ACCESSORIES



SPECIFICATIONS

VIDEO	
Imaging Device	1/1.8"
Max Resolution	Main Stream : 4MP (2688x1520), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720) Sub Stream : 720P (1280x720), VGA (640x480), QVGA (320x240) Mobile Stream : VGA (640x480), QVGA (320x240)
Min. Illumination (Color)	Color : 0.0005 lux @ F1.0(AGC on); B/W 0 lux @ IR ON
Imaging System	Progressive CMOS
LENS	
Focal Length	2.8-12 mm
Lens Type	Ø16.7
Angular Field of View	Horizontal:110-40°, Vertical:57-22°, Diagonal:137-46°
Max. Aperture Ratio	F No. 1.2
Min. Object Distance	W:5.74 ft (1.75 m), T:17.09 ft (5.21 m)
OPERATIONAL	
Wide Dynamic Range	WDR
Digital Noise Reduction	3D DNR
Light Type	Default warm light, switchable infrared light
Motion Detection	Off/On (8 Level)
White Balance	Auto/Manual
Electric Shutter Speed	1/5 ~ 1/20000s
Light Viewable Length	Up to 98.43 ft (30 m)
IR Wavelength	Up to 82.02 ft (25 m)
Image Setting	Full Color Mode/Day&Night Mode/Smart Illumination
NETWORK	
Ethernet	RJ45 (10/100BASE-T)
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Bitrate Control	CBR/VBR
Application Programming Interface	ONVIF (Profile S/G/T)
SECURITY	
Network Authentication	1 RJ45 10 M / 100 M self-adaptive Ethernet port
Additional Security	IP address filter; complicated password; Authenticated username and password
GENERAL	
Ingress Protection	IP67
Material	Metal
INTERFACE	
Alarm Input	1 input, 1 output
Audio Input	1 input (RCA), 1 output (RCA), Built-in microphone&Speaker
ELECTRICAL & ENVIRONMENTAL	
Power Consumption	4-pin waterproof connector, 3.5DC connector, 60 W (deviation: ± 2 W) Solar panels, max.8.7 W
Operating Temperature	Charging : -4 °F to 113 °F (-20 °C to 45 °C) Discharging : -4 °F to 140 °F (-20 °C to 60 °C)
Operating Humidity	-4 °F to 140 °F (-20 °C to 60 °C). Humidity 95% or less (non-condensing)
PERFORMANCE	
Video Compression	H.265/H.264/H.265+/H.264+/MJPEG

AVC-SNDB41M-4G

AI



OVERVIEW

- 4MP (2688x1520) H.265/H.264/H.265+/H.264+/MJPEG
- Max. resolution: 2688x1520
- Full Color / Active Deterrence Camera
- 2.8-12mm Motorized Lens (F1.2)
- 3D DNR, WDR, HLC, BLC, ROI encoding
- Intelligent Analytics
- White Light LED / Strobe (Blue & Red) Light
- Built-in MIC / Speaker
- Built-in microSD card slot with video and still image capture function (up to 512GB)
- Standalone with solar panel and battery
- Support 4G (LTE-TDD, LTE-FDD, TD-SCDMA) communication
- IP67 ingress protection
- Support remote monitoring by AVYCON ONE (Mobile APP) and AVYCON CMSONE (CMS)

DIMENSIONS

Unit : inch(mm)



OPTIONAL ACCESSORIES



SPECIFICATIONS

VIDEO	
Imaging Device	1/1.8"
Effective Pixels	4MP 2688(H)×1520(V)
Scanning System	Progressive CMOS
Min. Illumination	Color : 0.0005lux @ F1.0(AGC on); B/W 0 lux @ IR ON
LENS	
Focal Length (Zoom Ratio)	2.8–12 mm
Max. Aperture Ratio	F No. 1.2
Angular Field of View	Horizontal:110-40°, Vertical:57-22°, Diagonal:137-46°
Min. Object Distance	W:5.74 ft (1.75 m), T:17.09 ft (5.21 m)
Lens Type	Ø16.7
OPERATIONAL	
IR LED	4
WarmLight	4
IR Viewable Length	Up to 98.43 ft (30 m)
WarmLight Viewable Length	Up to 82.02 ft (25 m)
Type of complementary light	Default warm light, switchable infrared light
Motion Detection	Off/On (8 Level)
Wide Dynamic Range	WDR
Digital Noise Reduction	3D DNR
Image Setting	Full Color Mode/Day&Night Mode/Smart Illumination
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 512GB
Alarm	1 input, 1 output
Audio	1 input (RCA), 1 output (RCA), Built-in microphone&Speaker
Custom Voice	Yes
Hardware Reset	Yes
Smart Feature	Pedestrian&Vehicle, Line Crossing, Object Detection, Crossing Counting, Heat Map, Crowd Density, Queue Length, License Plate, Rare Sound, Intrusion, Region Entrance, Region Exiting
NETWORK	
Ethernet	RJ45 (10/100BASE-T)
Video Compression Format	H.265/H.264/H.265+/H.264+/MJPEG
Resolution	Main Stream : 4MP (2688x1520), 3MP (2304x1296),1080P (1920x1080), 720P (1280x720) Sub Stream : 720P (1280x720),VGA (640x480),QVGA (320x240) Mobile Stream : VGA (640x480), QVGA (320x240)
Video Quality Adjustment	256Kbps ~ 16Mbps
Bitrate control method	CBR/VBR
IP	IPv6
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Security	IP address filter; complicated password; Authenticated username and password
Application Programming Interface	ONVIF (Profile S/G/T)
Web Viewer	IE10/11 Safari : V12.1 above Firefox : V.52 above Google chrome : V.57 above Edge : V.79 above
MOBILE COMMUNICATION	
SIM Card Type	Micro SIM
Frequency	LTE-TDD : Band 38/39/40/41 LTE-FDD : Band 1/2/3/4/5/7/8/12/13/18/19/20/25/26/28 WCDMA : Band 1/2/4/5/6/8/19
GSM	GSM850/EGSM900/DCS1800/PCS1900
INTERFACES	
Network	1 RJ45 10 M / 100 M self-adaptive Ethernet port
Wi-Fi	IEEE802.11b/g/n; 2.4 G
ENVIRONMENTAL	
Operating Conditions	-4 °F to 140 °F (-20 °C to 60 °C). Humidity 95% or less (non-condensing)
Ingress Protection	IP67
ELECTRICAL	
Power	4-pin waterproof connector, 3.5DC connector, 60 W (deviation: ± 2 W) Solar panels, max.8.7W
MECHANICAL	
Material	Metal
BATTERY	
Battery Type	Lithium
Capacity	8.4 Ah × 4 packs
Battery Voltage	10.8V
Max. Output Voltage	12.6V
Operating Temperature	Charging : -4 °F to 113 °F (-20 °C to 45 °C) Discharging : -4 °F to 140 °F (-20 °C to 60 °C)

Copyright © 2026 AVYCON. All rights reserved.

AVYCONwww.avycon.com

All the contents on the AVYCON's digital and printed marketing materials include product names, part number, unique identification letters, etc., are trademarks of AVYCON. Any unauthorized use or distribution of trademarked contents is strictly prohibited by law. In addition, graphical designs, images, features, and specifications on such materials may differ from the actual products and subject to change without notice. For the latest product information/specification please visit our website or contact one of our product specialists at marketing@avycon.com