



LA COPA MUNDIAL DE LA FIFA 2026

DEL 11 DE JULIO DE 2026

COANFITRIONADA POR CANADÁ • MÉXICO • ESTADOS UNIDOS

- 48 SELECCIONES
- 104 PARTIDOS
- EN 16 CIUDADES SEDE

¡Y EL ARRANQUE EN EL LEGENDARIO ESTADIO AZTECA DE CDMX!

**¡VIVE LA EMOCIÓN EN UNA
PANTALLA LED GIGANTE
QUE TE LLEVARÁ AL LIMITE DEL PARTIDO EN VIVO!**



IDAV MEXICO S.A. DE C.V.

AV. DURANGO 269 COLONIA ROMA CDMX C.P.06700 TELEFONO 55 1193 9536 / 55 8645 1856

Abjen

SYSKOM

PLANAR

LEYARD

LIGHTHOUSE
CREATE YOUR LIGHT

TECHNOLOGY
SHOWCASE

IDAV GROUP



- CALIDAD VISUAL SUPERIOR
- SONIDO ENVOLVENTE
- AMBIENTES TEMÁTICOS
- TRANSMISIÓN EN VIVO SIN INTERRUPCIONES

CONVIERTE TU RESTAURANTE EN LA MEJOR SEDE PARA DISFRUTAR DEL MUNDIAL. CALIDAD VISUAL SUPERR, AMBIENTE ENVOLVENTE, Y LA PASIÓN DE MILLONES... TODO EN UN SOLO LGA.



IDAV MEXICO S.A. DE C.V.
AV. DURANGO 269 COLONIA ROMA CDMX C.P.06700 TELEFONO 55 1193 9536 / 55 8645 1856

Aben

SYSCOM

PLANAR

LEYARD

LIGHTHOUSE
CREATE IMPACT

**TECHNOLOGY
SHOWCASE**

IDAV GROUP



P1.56MM 3 METROS DE LARGO X 2 METROS DE ALTO \$ 599,577.90 + IVA LIMITADO A 300PIEZAS
GARANTIA DE 5 AÑOS

• Specification

Product Model	
Product Model	DS-D4015CW-2F
Product Type	
Product Type	Fine Pixel Pitch Indoor Full-color LED Display
Cabinet	
Pixel Configuration	SMD Triad LED
Pixel Pitch	1.56 mm (0.061")
Pixel Pitch Category	P1.5
Pixel Density	409600 dots/m ²
Modules Component	2 × 2
Dimension (W × H × D)	600 (W) mm × 337.5 (H) mm × 29.5 (D) mm (23.622" × 13.287" × 1.161")
Resolution	384 × 216
Area	0.2025 m ²
Weight	3.4 kg
Cabinet Material	Aluminium die casting
Maintenance Method	Front maintenance for all components
Module	
Dimension	300 mm × 168.75 mm
Module Resolution	192 × 108
Display	
White Balance Brightness	600 cd/m ²
Color Temperature	3000 K to 10000 K adjustable
Viewing Angle	160° (H)/160° (V)
Contrast Ratio	5000:1
Color Uniformity	≤ ± 0.003Cx, Cy
Brightness Uniformity	≥ 97%
Processing Performance	
Driving Method	Constant current driving
Scanning Amount	54
Frame Frequency	60 Hz
Refresh Rate	3840 Hz
Grey Level	16 bit
Power	
Max. Consumption	≤ 390 W/m ² (600 nits)
Average Consumption	≤ 130 W/m ²
Input Voltage	100~240 VAC ± 10%
Working Environment	
Working Temperature	-10 °C to 40 °C (14 °F to 104 °F)
Working Humidity	10% RH to 60% RH (without condensation)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Storage Humidity	10% RH to 85% RH (without condensation)
General	
Package Dimension (W × H × D)	722 (W) mm × 438 (H) mm × 193 (D) mm (28.425 " × 17.244 " × 7.598 ")



IDAV MEXICO S.A. DE C.V.
AV. DURANGO 269 COLONIA ROMA CDMX C.P.06700 TELEFONO 55 1193 9536 / 55 8645 1856





P1.75MM 3 METROS DE LARGO X 2 METROS DE ALTO \$ 497,762.50 + IVA LIMITADO A 300PIEZAS

GARANTIA DE 5 AÑOS

• Specification

Product Model	
Product Model	DS-D4018CW-2F
Product Type	
Product Type	Fine Pixel Pitch Indoor Full-color LED Display
Cabinet	
Pixel Configuration	SMD Triad LED
Pixel Pitch	1.875 mm (0.074")
Pixel Pitch Category	P1.8
Pixel Density	284,444 dots/m ²
Modules Component	2 × 2
Dimension (W × H × D)	600 (W) mm × 337.5 (H) mm × 29.5 (D) mm (23.622" × 13.287" × 1.161")
Resolution	320 × 180
Area	0.2025 m ²
Weight	3.4 kg
Cabinet Material	Aluminium die casting
Maintenance Method	Front maintenance for all components
Module	
Dimension	300 mm × 168.75 mm
Module Resolution	160 × 90
Display	
White Balance Brightness	600 cd/m ²
Color Temperature	3000 K to 10000 K adjustable
Viewing Angle	160° (H)/160° (V)
Contrast Ratio	5000:1
Color Uniformity	≤ ± 0.003Cx, Cy
Brightness Uniformity	≥ 97%
Processing Performance	
Driving Method	Constant current driving
Scanning Amount	45
Frame Frequency	60 Hz
Refresh Rate	3840 Hz
Grey Level	16 bit
Power	
Max. Consumption	≤ 400 W/m ² (600 nits)
Average Consumption	≤ 140 W/m ²
Input Voltage	100~240 VAC ± 10%
Working Environment	
Working Temperature	-10 °C to 40 °C (14 °F to 104 °F)
Working Humidity	10% RH to 60% RH (without condensation)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Storage Humidity	10% RH to 85% RH (without condensation)
General	
Package Dimension (W × H × D)	722 (W) mm × 438 (H) mm × 193 (D) mm (28.425" × 17.244" × 7.598")



IDAV MEXICO S.A. DE C.V.
AV. DURANGO 269 COLONIA ROMA CDMX C.P.06700 TELEFONO 55 1193 9536 / 55 8645 1856



P2.5MM 3 METROS DE LARGO X 2 METROS DE ALTO \$ 321,716.90+ IVA LIMITADO A 133PIEZAS

GARANTIA DE 5 AÑOS

• Specification

Model		DS-D4025CS-1F
Product Model	Product Model	DS-D4025CS-1F
Product Type	Product Type	Indoor small pitch full color LED
Cabinet	Pixel Configuration	SMD Triad LED
	Pixel Pitch Category	P2.5
	Pixel Pitch	2.5 mm
	Pixel Density	160000 dots/m²
	Modules Component	2 × 3
	Dimensions (W × H × D)	640 mm × 480 mm × 58.6 mm × (25.197 " × 18.898 " × 2.307 ")
	Resolution	256 × 192
	Area	0.3072 m²
	Weight	7.55 kg
	Cabinet Material	Die cast aluminum
Module	Maintenance Method	Complete front maintenance
	Dimensions	320×160mm
	Module Resolution	128×64
Display	White Balance Brightness	600 cd/m²
	Color Temperature	3000-10000 K adjustable
	Viewing Angle	160°(H)/160°(V)
	Contrast Ratio	3000:1
	Color Uniformity	≤ ± 0.003Cx, Cy
	Brightness Uniformity	≥ 97%
	Driving Method	Constant current driving
Processing Performance	Frame Frequency	60 Hz
	Refresh Rate	3840 Hz
	Grey Level	Up to 16 bit
	Max. Consumption	≤450W/m²



IDAV MEXICO S.A. DE C.V.
AV. DURANGO 269 COLONIA ROMA CDMX C.P.06700 TELEFONO 55 1193 9536 / 55 8645 1856

