

Comparitive Performance Report for cbt-12thMar-4k-ls26-writes-5+1-isal vs cbt-13thMar-4k-jamiels5-writes-5+1-isal

Table of contents


- Comparison summary for cbt-12thMar-4k-ls26-writes-5+1-isal vs cbt-13thMar-4k-jamiels5-writes-5+1-isal
- Response Curves
 - Random Write
- Configuration yaml files
 - results

Comparison summary for cbt-12thMar-4k-ls26-writes-5+1-isal vs cbt-13thMar-4k-jamiels5-writes-5+1-isal

Random Write	cbt_12thMar_4k_ls26_writes5plus1isal	cbt_13thMar_4k_jamiels5_writes5plus1isal	%change throughput	%change latency
4K	9328 IOps@54.9ms	9682 IOps@39.7ms	4%	-28%
8K	8356 IOps@61.2ms	7136 IOps@109.8ms	-15%	79%
64K	42 MB/s@25.0ms	40 MB/s@26.2ms	-5%	5%

Response Curves

Random Write



Configuration yaml files

Only yaml files that differ by more than 20 lines from the yaml file for the baseline directory will be added here in addition to the baseline yaml

results

```

librbdfio:
  cmd_path: /usr/local/bin/fio
  fio_out_format: json
  log_avg_msec: 100
  log_bw: true
  log_iops: true
  log_lat: true
  norandommap: true
  osd_ra:
    - 4096
  poolname: rbd_replicated
  prefill:
    blocksize: 64k
    numjobs: 1
  procs_per_volume:
    - 1
  ramp: 30
  time: 90
  time_based: true
  use_existing_volumes: true
  vol_size: 65625
  volumes_per_client:
    - 8
  workloads:
    4krandomwrite:
      jobname: randwrite
      mode: randwrite
      numjobs:
        - 1
      op_size: 4096
      total_iodepth:
        - 2
        - 4
        - 8
        - 16
        - 32
        - 64
        - 128
        - 256
        - 384
        - 512
        - 768
    8krandomwrite:
      jobname: randwrite
      mode: randwrite
      numjobs:
        - 1
      op_size: 8192
      total_iodepth:
        - 2
        - 4
        - 8
        - 16
        - 32
        - 64
        - 128
        - 256
        - 384
        - 512
        - 768
  precondition:

```

```

    jobname: preconditionrw
    mode: randwrite
    monitor: false
    numjobs:
      - 1
    op_size: 65536
    time: 600
    total_iodepth:
      - 16
cluster:
  archive_dir: /tmp/cbt
  ceph_mgr_cmd: /usr/bin/ceph-mgr
  ceph_mon_cmd: /usr/bin/ceph-mon
  ceph_osd_cmd: /usr/bin/ceph-osd
  ceph_run_cmd: /usr/bin/ceph-run
  ceph_cmd: /usr/bin/ceph
  clients:
    - --- server1 ---
  clusterid: ceph
  conf_file: /cbt/ceph.conf.4x1x1.fs
  fs: xfs
  head: --- server1 ---
  iterations: 1
  mgrs:
    --- server1 ---:
      a: null
  mkfs_opts: -f -i size=2048
  mons:
    --- server1 ---:
      a: --- IP Address --:6789
  mount_opts: -o inode64,noatime,logbsize=256k
  osds:
    - --- server1 ---
  osds_per_node: 6
  pdsh_ssh_args: -a -x -l%u %h
  rados_cmd: /usr/bin/rados
  rbd_cmd: /usr/bin/rbd
  tmp_dir: /tmp/cbt
  use_existing: true
  user: root
monitoring_profiles:
  collectl:
    args: -c 18 -sCD -i 10 -P -oz -F0 --rawtoo --sep ";" -f {collectl_dir}
  librbd fio:
    cmd_path: /usr/local/bin/fio
    fio_out_format: json
    log_avg_msec: 100
    log_bw: true
    log_iops: true
    log_lat: true
    norandommap: true
    osd_ra:
      - 4096
    poolname: rbd_replicated
    prefill:
      blocksize: 64k
      numjobs: 1
    procs_per_volume:
      - 1
    ramp: 30
    time: 90
    time_based: true

```

```

use_existing_volumes: true
vol_size: 65625
volumes_per_client:
- 8
workloads:
  4krandomwrite:
    jobname: randwrite
    mode: randwrite
    numjobs:
    - 1
    op_size: 4096
    total_iodepth:
    - 2
    - 4
    - 8
    - 16
    - 32
    - 64
    - 128
    - 256
    - 384
    - 512
    - 768
  8krandomwrite:
    jobname: randwrite
    mode: randwrite
    numjobs:
    - 1
    op_size: 8192
    total_iodepth:
    - 2
    - 4
    - 8
    - 16
    - 32
    - 64
    - 128
    - 256
    - 384
    - 512
    - 768
  precondition:
    jobname: precond1rw
    mode: randwrite
    monitor: false
    numjobs:
    - 1
    op_size: 65536
    time: 600
    total_iodepth:
    - 16
cluster:
  archive_dir: /tmp/cbt
  ceph_mgr_cmd: /usr/bin/ceph-mgr
  ceph_mon_cmd: /usr/bin/ceph-mon
  ceph_osd_cmd: /usr/bin/ceph-osd
  ceph_run_cmd: /usr/bin/ceph-run
  ceph_cmd: /usr/bin/ceph
  clients:
  - --- server1 ---
  clusterid: ceph
  conf_file: /cbt/ceph.conf.4x1x1.fs
  fs: xfs

```



```

head: --- server1 ---
iterations: 1
mgrs:
  --- server1 ---:
    a: null
mkfs_opts: -f -i size=2048
mons:
  --- server1 ---:
    a: --- IP Address --:6789
mount_opts: -o inode64,noatime,logbsize=256k
osds:
- --- server1 ---
  osds_per_node: 6
  pdsh_ssh_args: -a -x -l%u %h
  rados_cmd: /usr/bin/rados
  rbd_cmd: /usr/bin/rbd
  tmp_dir: /tmp/cbt
  use_existing: true
  user: root
monitoring_profiles:
  collectl:
    args: -c 18 -sCD -i 10 -P -oz -FO --rawtoo --sep ";" -f {collectl_dir}

```