EECS 484, Winter 2026- Database Management Systems

Normalization

Chapter 19

Instructor: Barzan Mozafari

University of Michigan, Ann Arbor

Review


DB design
ER diagram
Relational
Schema
Relational
Algebra
Relational
Calculus
SQL
DB App

Today


DB design
ER diagram
Relational
Schema
Normalization
Relational
Algebra
Relational
Calculus
SQL
DB App

Database Design: The Story So Far

- Requirements Analysis
  - Data stored, operations, apps, …
- Conceptual Database Design
  - Model high-level description of the data, constraints, ER model
- Logical Database Design
  - Choose a DBMS and design a database schema
- Schema Refinement
  - Normalize relations, avoid redundancy, anomalies…
- Physical Database Design
  - Examine physical database structures like indices, restructure…
- Security Design

Form/Spreadsheet

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$7
			Paint	blue	$10
			Flowers	pink	$3
2	Beanery	A2, A3	Dynamite	boom	$8

Good or bad table?

Form/Spreadsheet

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$8
			Paint	blue	$10
			Flowers	pink	$3
2	Beanery	A2, A3	Dynamite	boom	$8

Problems

- (Supplier ID, item) appears to be the key, but it is NULL in many places=> Implicit dependencies between rows
- Addresses can be multi-valued

Normalization

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$7
			Paint	blue	$10
			Flowers	pink	$3
2	Beanery	A2, A3	Dynamite	boom	$8

The above is not a good table!

Going to proper set of tables is called "normalization".

- avoid redundancy of data
- capture the dependencies inherent in the data

Normalization Theory

Goal: Design ‘good’ tables

Normalization is like doing laundry.
It feels good in theory, but nobody wants to do it all the way to BCNF.

- What is good?
  - We want tables where the attributes depend on the primary key, on the whole key, and nothing but the key.
- How to check for goodness?
  - Use normal forms (NFs): each NF excludes certain “anomalies”, 1NF, 2NF, 3NF, BCNF, 4NF, 5NF
- How to fix bad tables?
  - Decomposition: break larger tables into smaller ones



1st Normal Form – First Step

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$7
1	Acme	A1	Paint	blue	$10
1	Acme	A2	Flowers	pink	$3
2	Beanery	A2	Dynamite	boom	$8
2	Beanery	A3	Dynamite	boom	$8

1. Each ingle-valued
2. Each row contains all the relevant data
   - Exception: we allow NULLs, unless part of primary key

1 & 2 ⇒We have a relational table:

Rows can be reordered, all rows independent.

What is Wrong with Redundancy?

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$7
1	Acme	A1	Paint	blue	$10
1	Acme	A1	Flowers	pink	$3
2	Beanery	A2	Dynamite	boom	$8
2	Beanery	A3	Dynamite	boom	$8

Redundant storage: For each different item, we also store the address of the supplier.

Redundancy Problems

- Redundant storage (space)
  - A supplier supplies multiple items
- Update anomalies
  - Change address of a supplier
  - Need to change all instances!
- Insertion anomalies
  - Insert a supplier
  - Has to insert other (unrelated) info too
- Deletion anomalies
  - What if we want to delete the last item tuple?
  - Has to delete other (unrelated) info too

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$8
1	Acme	A1	Paint	blue	$10
1	Acme	A2	Flowers	pink	$3
2	Beanery	A2	Dynamite	boom	$8
2	Beanery	A[illegible]	[illegible]	[illegible]	[illegible]

Dealing with Redundancy

- Redundancy arises when schema forces an unnatural association among attributes
- The new trick we will learn today is to use the notion of functional dependencies

Solution to Redundancy: Decomposition

Split large relation to smaller ones

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$7
1	Acme	A1	Paint	blue	$10
1	Acme	A1	Flowers	pink	$3
2	Beanery	A2	Dynamite	boom	$8
2	Beanery	A3	Dynamite	boom	$8

Supplier ID	Supplier Name
1	Acme
2	Beanery

Item	Desc
Dynamite	boom
Paint	blue
Flowers	pink

Supplier ID	Supplier Address
1	A1
2	A2
2	A3

Supp ID	Item	Price
1	Dynamite	$7
1	Paint	$10
1	Flowers	$3
2	Dynamite	$8

- What columns to decompose on?
  - Need to learn about Normal Forms

Normal Forms

- Certain kind of decomposition
- Guarantees that certain problems won't occur & obeys certain rules:
  - 1 NF : No set-valued attrs
  - 2 NF : Historical
  - 3 NF : …
  - BCNF : Boyce-Codd Normal Form

Functional Dependencies (FD)

FDs capture dependencies among attributes

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$7
1	Acme	A1	Paint	blue	$10
1	Acme	A2	Flowers	pink	$3
2	Beanery	A2	Dynamite	boom	$8
2	Beanery	A3	Dynamite	boom	$8

- ‘Suppl depends on the Supp
- What does ‘depends on’ mean?

FD: Definition

- Notation: a → b
- Read as: ‘a’ functionally determines ‘b’
- **Informally**: If you know ‘a’, there is only one ‘b’ to match.

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$7
1	Acme	A1	Paint	blue	$10
1	Acme	A2	Flowers	pink	$3
2	Beanery	A2	Dynamite	boom	$8
2	Beanery	A3	Dynamite	boom	$8

FD: Definition

- Notation: a → b
- Read as: ‘a’ functionally determines ‘b’
- **Informally**: If you know ‘a’, there is only one ‘b’ to match.
- **Formally**: A form of Integrity Constraint

D: $X \rightarrow Y$ X and Y subsets of relation R’s attributes

$t1 \in r,\ t2 \in r,\ \prod_X (t1) = \prod_X (t2) \Rightarrow \prod_y (t1) = \prod_y (t2)$

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$7
1	Acme	A1	Paint	blue	$10
1	Acme	A2	Flowers	pink	$3
2	Beanery	A2	Dynamite	boom	$8
2	Beanery	A3	Dynamite	boom	$8

FD: Example

FDs capture dependencies among attributes

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$7
1	Acme	A1	Paint	blue	$10
1	Acme	A2	Flowers	pink	$3
2	Beanery	A2	Dynamite	boom	$8
2	Beaner			boom	$8

FD: Example

FDs capture dependencies among attributes

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$7
1	Acme	A1	Paint	blue	$10
1	Acme	A2	Flowers	pink	$3
2	Beanery	A2	Dynamite	boom	$8
2	Beanery	A2	Dynamite	boom	$8

- Supplier ID → Supplier Name
- Item → Desc
- Supplier ID, Item → Price

More on FDs

- An FD is a statement about all allowable relations.
  - Based only on application semantics, not a table instance

Primary Key IC: special case of FD

- Role of FDs in detecting redundancy

Example: Relation R with 4 attributes, XYZK

X → Y causes redundancy

(X,Y)=(1,10) and (X,Y)=(2,20) stored multiple times

X	Y	Z	K
1	10	11	A
1	10	12	B
2	20	22	C
2	20	23	D

How to find all the implied FDs?

- F+: Closure of F = Set of all FDs (including the derived ones)

Supplier ID → Supplier Name
Item → Desc
Supplier ID, Item → Price
…

- How to obtain?
  - F+ obtained by repeatedly applying Armstrong's Axioms



Armstrong's Inference Axioms

- Axiom#1: Reflexive Property:
  - (Supplier ID, Item#) -> Item#
  - Obviously, if we know (Supplier ID and item#) pair, we know the item#
- In general, given attribute sets X and Y
  - Reflexivity: If $X \supseteq Y$, then $X \rightarrow Y$
- In the above example, Y is [Item#]. X is [Supplier ID, Item#].
- This is called a trivial dependency.

All the Inference Axioms

- Armstrong's Axioms (X, Y, Z are sets of attributes): 'sound' and 'complete'
  - Reflexivity: If $X \supseteq Y$, then $X \rightarrow Y$ (trivial dependency)
  - Augmentation: If $X \rightarrow Y$, then $XZ \rightarrow YZ$ for any Z
  - Transitivity: If $X \rightarrow Y$ and $Y \rightarrow Z$, then $X \rightarrow Z$

    e.g. ename → ejob, ejob → esal; ⇒ ename → esal
- Additional useful rules (derivable):
  - Union: If $X \rightarrow Y$ and $X \rightarrow Z$, then $X \rightarrow YZ$
  - Decomposition: If $X \rightarrow YZ$, then $X \rightarrow Y$ and $X \rightarrow Z$

Deriving Union Rule from Axioms

- Prove: if $X \rightarrow Y$ and $X \rightarrow Z$ then $X \rightarrow YZ$
- Proof:

- Reflexivity: If $Y \subseteq X$, then $X \rightarrow Y$ (trivial dependency)
- Augmentation: If $X \rightarrow Y$, then $XZ \rightarrow YZ$ for any Z
- Transitivity: If $X \rightarrow Y$ and $Y \rightarrow Z$, then $X \rightarrow Z$

Deriving Union Rule from Axioms

- Prove: if $X \rightarrow Y$ and $X \rightarrow Z$ then $X \rightarrow YZ$
- Proof:

  1. $X \rightarrow Y$ (given)
  2. $X \rightarrow Z$ (given)
  3. $XX \rightarrow XZ$ or $X \rightarrow XZ$ (augmentation of 2)
  4. $XZ \rightarrow YZ$ (augmentation of 1)
  5. $X \rightarrow YZ$ (transitivity of 3 and 4)

- Possible to derive the decomposition rule from the basic Armstrong rules

Solution to Redundancy: Decomposition

Split large relation to smaller ones

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$7
1	Acme	A1	Paint	blue	$10
1	Acme	A1	Flowers	pink	$3
2	Beanery	A2	Dynamite	boom	$8
2	Beanery	A3	Dynamite	boom	$8

Supplier ID	Supplier Name
1	Acme
2	Beanery

Item	Desc
Dynamite	boom
Paint	blue
Flowers	pink

Supplier ID	Supplier Address
1	A1
2	A2
2	A3

Supp ID	Item	Price
1	Dynamite	$7
1	Paint	$10
1	Flowers	$3
2	Dynamite	$8

Advantages:

- Eliminate redundancy and anomalies
- Lossless join when done right

Solution to Redundancy: Decomposition

- Split large relations to smaller ones

Supplier ID	Supplier Name	Supplier Address	Item	Desc	Price
1	Acme	A1	Dynamite	boom	$7
1	Acme	A1	Paint	blue	$10
1	Acme	A1	Flowers	pink	$3
2	Beanery	A2	Dynamite	boom	$8
2	Beanery	A3	Dynamite	boom	$8

Supplier ID	Supplier Name
1	Acme
2	Beanery

Supplier ID	Supplier Address
1	A1
2	A2
2	A3

Item	Desc
Dynamite	boom
Paint	blue
Flowers	pink

Supp ID	Item	Price
1	Dynamite	$7
1	Paint	$10
1	Flowers	$3
2	Dynamite	$8

- Problems with decomposition
  - Some queries become more expensive (more joins)
  - Lossless Join: Can we reconstruct the original relation from instances of the decomposed relations?

Must have

  - Dependency Preservation: Can we check dependencies without having to join the decomposed relations?

Good to have

Lossless Join Decompositions

- Relation R, FDs F; Decomposed to X, Y
- Lossless-Join decomposition if:

$\pi_X(r) \bowtie \pi_Y(r) = r$ for **every** instance r of R

- Note, $r \subseteq \pi_X(r) \bowtie \pi_Y(r)$ is always true, not vice versa, unless the join is lossless
- Can generalize to three or more relations

Example: R = {A, B, C}, X={A,B}, Y={B,C}

R

A	B	C
1	2	3
4	5	6
7	2	8

$\pi_X(R)$

A	B
1	2
4	5
7	2

$\pi_Y(R)$

B	C
2	3
5	6
2	8

$\pi_X(R) \bowtie \pi_Y(R)$

A	B	C
1	2	3
4	5	6
7	2	8
1	2	8
7	2	3

Lossless Join (cont.)

- Relation R, FDs F; Decomposed to X, Y
  - Test: lossless-join w.r.t. F if and only if F^+ contains:

$$X \cap Y \rightarrow X, \quad \text{or} \quad X \cap Y \rightarrow Y$$

i.e. attributes common to X and Y contain a super key for either X or Y

(Note: Different test needed for decomposition into more than two relations.)

Lossless join decomposition is always required!

Decomposition into 3+ relations

- There is an if-and-only-if test called **Chase Algorithm** (not covered in this class)
- **A practical shortcut:**
  - if you can show your N-way decomposition was produced by a sequence of binary splits, and each binary split satisfies the two-relation test ($X \cap Y \rightarrow X$ or $X \cap Y \rightarrow Y$), then the overall decomposition is guaranteed lossless.
  - Note: This shortcut is sufficient but not necessary: some lossless decompositions can't be verified this way and require the full chase.

Lossless Decomposition: Example

ssn	cid	grade	name	addr
123	413	A	Smith	Main
123	415	B	Smith	Main
234	211	A	Jones	Huron

ssn->name, address
ssn, cid -> grade

R1

ssn	cid	grade
123	413	A
123	415	B
234	211	A

ssn, cid -> grade

R2

ssn	name	addr
123	Smith	Main
234	Jones	Huron

ssn->name, address

Dependency Preserving Decomposition

- **Informally**: We don't want the original FDs to span two tables.
- R has a dependency-preserving decomposition to X, Y if $F^+ = (F_x \cup F_y)^+$
- **Definition:** F_X all those FDs in F which only mention attrs from X
- Note: F is not necessarily = $F_x \cup F_y$
- Example: R (sailor, boat, date) F: {D → S, D → B}

- Consider decomp. to X (sailor, boat) and Y (boat, date)
- We have F_Y: {D → B}, F_X: {}. $\{D \rightarrow S, D \rightarrow B\}^+ \neq \{D \rightarrow B\}^+$
- To enforce D → S, must join X and Y (expensive)

The above is not dependency preserving

Boyce-Codd Normal Form (BCNF)

- Rel. R with FDs F is in BCNF if, for all $X \rightarrow A$ in F^+
  - $A \subseteq X$ (trivial FD), or
  - X is a super key

X:subset of attributes

A: single attribute

i.e. all non-trivial FDs over R are due to keys.

⇒No redundancy (at least none due to FDs)⇒Most desirable norm. form

Example: The following set of relations are all in BCNF given the following FDs:

Supplier ID → Supplier Name

Supplier ID	Supplier Name
1	Acme
2	Beanery

Item → Desc

Item	Desc
Dynamite	boom
Paint	blue
Flowers	pink

Supplier ID, Item → Price

Supp ID	Item	Price
1	Dynamite	$7
1	Paint	$10
1	Flowers	$3
2	Dynamite	$8

3NF

- Relation R with FDs F is in 3NF if, for all $X \rightarrow A$ in F^+
  - $A \subseteq X$ (trivial dependency) or
  - X is a super key or
  - A is part of some (minimal) key for R **(prime attribute)**

  Minimality of a key (i.e. not a super key) is crucial!

X:subset of attributes

A: single attribute

- BCNF implies 3NF, but 3NF does not imply BCNF

Lossless-join, dependency-preserving decomposition of R into a collection of 3NF relations is always possible.

3NF: Example

- Consider Reserves(Sailor, Boat, Date, CreditCard)
  - F={SBD -> SBDC, S -> C} (not 3NF)

    Why? SBD is the only key, S not a key, C not a key
  - If **additionally** C -> S, then CBD -> SBDC (i.e., CBD is also a key).
    → Now in 3NF!

Note the redundancy in (S, C); 3NF permits this type of redundancy

- Compromise used when BCNF not achievable, or performance considerations

S	B	D	C
S1	B1	D1	C1
S1	B2	D2	C1
S2	B3	D3	C2

Relation R with FDs F is in 3NF if, for all $X \rightarrow A$ in F^+

- $A \subseteq X$ (trivial dependency) or
- X is a super key or
- A is part of some (minimal) key for R **(prime attribute)**

Minimality of a key (i.e, not a super key) is crucial!

Time to practice ☺



Exercise 1: BCNF or 3NF?

- Relation R=(A,B,C,D,E)
- FDs:

  $A \rightarrow BC$

  $CD \rightarrow E$

  $B \rightarrow D$

  $E \rightarrow A$

Hint:
1. Use Armstrong's Axioms to compute F+
2. Identify the keys

- Is R in BCNF?
- Is R in 3NF?

- Reflexivity: If $Y \subseteq X$, then $X \rightarrow Y$ (trivial dependency)
- Augmentation: If $X \rightarrow Y$, then $XZ \rightarrow YZ$ for any Z
- Transitivity: If $X \rightarrow Y$ and $Y \rightarrow Z$, then $X \rightarrow Z$

Answer

- **F+**
  - A->B
  - A->C
  - A->D
  - A->E
  - CD->E
  - B->D
  - E->A
- **Keys:** A, E, CD, BC
- **Is R in BCNF?**
  - No, because of B->D
- **Is R in 3NF?**
  - Yes

F :

- $A \rightarrow BC$
- $CD \rightarrow E$
- $B \rightarrow D$
- $E \rightarrow A$

- Reflexivity: If $Y \subseteq X$, then $X \rightarrow Y$ (trivial dependency)
- Augmentation: If $X \rightarrow Y$, then $XZ \rightarrow YZ$ for any Z
- Transitivity: If $X \rightarrow Y$ and $Y \rightarrow Z$, then $X \rightarrow Z$

Exercise 2: FDs & Normal Forms

Suppose you are given the following relation R: ABCDEF

BC -> D

CD -> B

D -> E

ACD -> F

1. Find the keys of R
2. List all of the above FDs that violate BCNF
3. List all of the above FDs that violate 3NF

Answer

== FDs: ==
BC -> D
CD -> B
D -> E
ACD -> F

1. Identify keys:

ACD -> F

CD -> B => ACD -> B

D -> E => ACD -> E

ACD is a key

BC -> D => ABC->D

D -> E & ABC->D => ABC->E

ABC->D=>ACABC->ACD simplifies to ABC->ACD

ABC->ACD & ACD ->F => ABC->F

ABC is a key

2. FDs that Violate BCNF:

BC->D, CD->B, D->E

3. FD that Violates 3NF: D->E

Decomposition into BCNF

High-Level Algorithm

Input: a relation R with FDs F

1. Identify if any FDs violate BCNF
   - If $X \rightarrow Y$ violates BCNF, decompose R into **R - Y and XY**
2. Repeat for every $X \rightarrow Y$ that violates BCNF.

Output: a collection of relations that are in BCNF

- Does this algorithm provide a lossless join decomposition?
  - Yes! Notice that X is a key for the relation XY
- Is this algorithm dependency preserving? Not necessarily!
- Several dependencies may cause violation of BCNF.
  - The order in which we "deal with" them may lead to different relations!

Algorithm for BCNF
Input: Relation R, FDs F

done = false;

result = {R};

compute F^+;

while (not done) do

  if $\exists$ $R_i \in$ result and R_i is not in BCNF

    let $\alpha \rightarrow \beta$ be a nontrivial FD that holds in R_i

      such that $(\alpha \rightarrow R_i) \notin F^+$ and $\alpha \cap \beta = \varnothing$;

    result=(result$-R_i$) $\cup$ ($R_i - \beta$) $\cup$ (α,β) ;

  else done=true ;

Exercise 3: Fix R to be in BCNF

- Relation R=(A,B,C,D,E)
- FDs: $A \rightarrow BC$, $CD \rightarrow E$, $B \rightarrow D$, $E \rightarrow A$
- Keys: A, BC, CD, E
- $B \rightarrow D$ violates BCNF
- Decompose R:
- Is this decomposition lossless join?
- Is it dependency preserving?

Answer

- Relation R=(A,B,C,D,E)
- FDs: $A \rightarrow BC$, $CD \rightarrow E$, $B \rightarrow D$, $E \rightarrow A$
- Keys: A, BC, CD, E
- $B \rightarrow D$ violates BCNF
- Decompose R into:
  - R1=(A,B,C,E) R2=(B,D)
- Is this decomposition lossless join?
  - Yes! $R1 \cap R2 = B$ and $B \rightarrow R2$
- Is it dependency preserving?
  - F1: $A \rightarrow BC$, $E \rightarrow A$
  - F2: $B \rightarrow D$
  - No! $CD \rightarrow E$ is not in $(F1 \cup F2)^+$

In this case,
leave it in 3NF

Exercise 4

Suppose you are given the following relation R: ABCDEF with the following FDS:

- BC -> D
- CD -> B
- D -> E
- ACD -> F

Now decompose R into R1 and R2, and specify which decomposition (if any) satisfies lossless join property? Which one is dependency preserving?

- R1: ACDF, R2: ABCDE
- R1: BCD, R2: ABEF

Answer

- Keys: ACD, ABC (See exercise 2)
- R1: ACDF, R2: ABCDE
  - It is lossless, because the common attrs are ACD which is a key in R1 (and also in R2)
  - It is dependency preserving too
- R1: BCD, R2: ABEF
  - It is not lossless, because the common attr is B which is not a key in either of the smaller relations
  - It is not dep. preserving: ACD->F & D->E are not in the closure of the union of the FDs

Refining an Initial Schema

- Suppose you are given the following schema. You are asked to normalize it:
- IS (<u>item</u>, name, desc, loc, price)
  S (<u>name</u>, addr)

- Requirement: A supplier keeps all items of the same name in the same location FD: name → loc

Normalization Example

IS (<u>item</u>, name, desc, loc, price)
S (<u>name</u>, addr)

FDs = {i → ndlp, n → la}

- IS is not in BCNF, due to n → l
- Break it up: IS(<u>i</u>,n,d,p), Loc(<u>n</u>,l)
- S(<u>n</u>,a) remains unchanged
- Now notice same key for S and Loc, so merge
- Loc (name, addr, loc)

Refining an Initial Schema

- IS (item, name, desc, loc, price)
  S (name, addr)

- A supplier keeps all items of the same name in the same location FD: name → loc

```
Solution:
IS (item, name, desc, price)
Loc (name, addr, loc)
```

New Schema

Normalization: Summary

- Bad schemas lead to redundancy
  - Redundant storage, update, insert, and delete anomaly
- To "correct" bad schemas: decompose relations
  - Must be a lossless-join decomposition
  - Would like dependency preserving decompositions
- Desired Normal Forms
  - BCNF: allow only super-key functional dependencies
  - 3NF: allow dependencies with prime attributes on the RHS
    - Allows a limited form of redundancy
    - Trades off performance (avoid joins) for redundancy

Exercises

19.1, 19.5, 19.25

Next…

Storage and Indexing

Optional Slides

- The following slides are optional
- They're just a visual aid that Mozafari came up with when he took the undergrad DB class himself (2004)
  - Thankfully, normal forms haven't changed since!
- They helped him memorize all these confusing normal forms when he was preparing for his own exam
  - Back then, they had to learn about 4NF and 5NF too!
  - Lucky you: don't even have to learn about 2NF these days!
- Use these illustrations if you find them useful

BCNF



3NF



3NF



3NF


Key 1
Other Attributes
A1
Disallowed
(Transitive
Dep.)
Disallowed
(Partial
Dependency)
A2
Key 2
A3

2NF



Basic Normalization

- Write keys -> attribute mappings
- One table for each

Supplier ID	Supplier Name	Item	Desc	Price
1	Acme	Dynamite	boom	$7
1	Acme	Paint	blue	$10
1	Acme	Flowers	pink	$3
2	Beanery	Dynamite	boom	$8
2	Beanery	Dynamite	boom	$8

- Supplier ID → Supplier Name
- Item → Desc
- Supplier ID, Item → Price

Supplier ID	Supplier Name
1	Acme
2	Beanery

Item	Desc
Dynamite	boom
Paint	blue
Flowers	pink

Supp ID	Item	Price
1	Dynamite	$7
1	Paint	$10
1	Flowers	$3
2	Dynamite	$8

Example: Constraints on Entity Set



- S(name, item, desc, addr, price)
  - FD: {n,i} → {n,i,d,a,p}
  - FD: {n} → {a}
  - FD: {i} → {d}
- Decompose to: NA, ID, INP

- Spl(name, item, price)
  - FD: {n,i} → {n, i, p}
- Sup(name, addr)
  - FD: {n} → {n, a}
- Item (item, desc)
  - FD: {i} → {i, d}

ER design is subjective and can have many E + Rs
FDs: deeper understanding of schema