

CSC 330 —Programming Languages
Spring 2015
Assignment No. 7
Version 1.0

Note 1 **This assignment is to be done individually**

Note 2 You can discuss the assignment with others. Talk about what you need to do, not how it is done. And do not share code.

- Due date: March 27, 2015, at the beginning of the class.
- This assignment is worth 1% of your total course mark.
- Submit electronically via Connex a single file with your solutions.
- At the beginning of the class **submit a paper copy of your program.**

Objectives

After completing this assignment, you will have experience comparing the functional programming and object oriented paradigms.

Introduction

For this assignment, you will complete and extend two implementations of an interpreter for a small “language” for two-dimensional geometry objects. An implementation in SML is mostly completed for you. An implementation in Ruby is mostly not completed. The SML implementation is structured with functions and pattern-matching. The Ruby implemented is structured with subclasses and methods, including some mind-bending double dispatch and other dynamic dispatch to stick with an OOP style (even where I think the functional style is easier to understand—we will see what you think at the end of this assignment).

Language Semantics

Our “language” has five kinds of values and four other kinds of expressions. The representation of expressions depends on the metalanguage (SML or Ruby), with this same semantics:

- A `NoPoints` represents the empty set of two-dimensional points.
- A `Point` represents a two-dimensional point with an x-coordinate and a y-coordinate. Both coordinates are floating-point numbers.
- A `Line` is a non-vertical infinite line in the plane, represented by a *slope* and an *intercept* (as in $y = mx + b$ where m is the slope and b is the intercept), both floating-point numbers.
- A `VerticalLine` is an infinite vertical line in the plane, represented by its x-coordinate.
- A `LineSegment` is a (finite) line segment, represented by the x- and y-coordinates of its end-points (so four total floating-point numbers).

- An **Intersect** expression is not a value. It has two subexpressions. The semantics is to evaluate the subexpressions (in the same environment) and then return the value that is the intersection (in the geometric sense) of the two subresults. For example, the intersection of two lines could be one of:
 - **NoPoints**, if the lines are parallel
 - a **Point**, if the lines intersect
 - a **Line**, if the lines have the same slope and intercept (see the note below about what “the same” means for floating-point numbers)
- A **Let** expression is not a value. It is like let-expressions in other languages we have studied: The first subexpression is evaluated and the result bound to a variable that is added to the environment for evaluating the second subexpression.
- A **Var** expression is not a value. It is for using variables in the environment: We look up a string in the environment to get a geometric value.
- A **Shift** expression is not a value. It has a *deltaX* (a floating-point number), a *deltaY* (a floating-point number), and a subexpression. The semantics is to evaluate the subexpression and then *shift* the result by *deltaX* (in the x-direction; positive is “to the right”) and *deltaY* (in the y-direction; positive is “up”). More specifically, shifting for each form of value is as follows:
 - **NoPoints** remains **NoPoints**.
 - A **Point** representing (x, y) becomes a **Point** representing $(x + \text{deltaX}, y + \text{deltaY})$.
 - A **Line** with slope m and intercept b becomes a **Line** with slope m and an intercept of $b + \text{deltaY} - m \cdot \text{deltaX}$.
 - A **VerticalLine** becomes a **VerticalLine** shifted by *deltaX*; the *deltaY* is irrelevant.
 - A **LineSegment** has its endpoints shift by *deltaX* and *deltaY*.

Note on Floating-Point Numbers

Because arithmetic with floating-point numbers can introduce small rounding errors, it is rarely appropriate to use equality to decide if two floating-point numbers are “the same.” Instead, the provided code uses a helper function/method to decide if two floating-point numbers are “real close” (for our purposes, within .00001) and all your code should follow this approach as needed. For example, two points are the same if their x-coordinates are within .00001 and their y-coordinates are within .00001.

Expression Preprocessing

To simplify the interpreter, we first preprocess expressions. Preprocessing takes an expression and produces a new, equivalent expression with the following invariants:

- No **LineSegment** anywhere in the expression has endpoints that are the same as (i.e., real close to) each other. Such a line-segment should be replaced with the appropriate **Point**. For example in ML syntax, `LineSegment(3.2,4.1,3.2,4.1)` should be replaced with `Point(3.2,4.1)`.

- Every `LineSegment` has its first endpoint (the first two `real` values in SML) to the left (lower x-value) of the second endpoint. If the x-coordinates of the two endpoints are the same (real close), then the first endpoint has its first endpoint below (lower y-value) the second endpoint. For any `LineSegment` not meeting this requirement, replace it with a `LineSegment` with the same endpoints reordered.

The SML Code

Most of the SML solution is given to you. All you have to do is add preprocessing (problem 1) and `Shift` expressions (problem 2). The sample solution added much less than 60 lines of code. As always, line counts are just a rough guide.

Notice the SML code is organized around a datatype-definition for expressions, functions for the different operations, and pattern-matching to identify different cases. The interpreter `eval_prog` uses a helper function `intersect` with cases for every combination of geometric value (so with 5 kinds of values there are 25 cases though some are handled together via pattern-matching). The surprisingly complicated part is the algorithm for intersecting two line segments.

The Ruby Code

Much of the Ruby solution is not given to you. To get you started in the desired way, we have defined classes for each kind of expression in our language, as well as appropriate superclasses. We have implemented parts of each class and left comments with what you need to do to complete the implementation as described in more detail in problems 3 and 4. The sample solution added about 200 lines of Ruby code, many of which were `end`. As always, line counts are just a rough guide.

Notice the Ruby code is organized around classes where each class has methods for various operations. All kinds of expressions need methods for preprocessing and evaluation. They are subclasses of `GeometryExpression` just like all ML constructors are part of the `geom_exp` datatype (though the `GeometryExpression` class turns out not to be so useful). The value subclasses also need methods for shifting and intersection and they subclass `GeometryValue` so that some shared methods can be inherited (in analogy with some uses of wildcard patterns and helper functions in ML).

Your Ruby code should follow these general guidelines:

- All your geometry-expression objects should be **immutable**: assign to instance variables only when constructing an object. **To “change” a field, create a new object.**
- The geometry-expression objects have public getter methods: like in the SML code, the entire program can assume the expressions have various coordinates, subexpressions, etc.
- Unlike in SML, you do not need to define exceptions since without a type-checker we can just “assume” the right objects are used in the right places. You can also use `raise` with just a string as appropriate.
- Follow OOP-style. In particular, operations should be instance methods and you **should not use methods like `is_a?`, `instance_of?`, `class`, etc.** This makes problem 4 much more difficult, but that is the purpose of the problem.

Your task, should you choose to accept it

1. Implement an SML function `preprocess_prog` of type `geom_exp -> geom_exp` to implement expression preprocessing as defined above. The idea is that evaluating program `e` would be done with `eval_prog (preprocess_prog e, [])` where the `[]` is the empty list for the empty environment.
2. Add shift expressions as defined above to the SML implementation by adding the constructor `Shift of real * real * geom_exp` to the definition of `geom_exp` and adding appropriate branches to `eval_prog` and `preprocess_prog`. (The first `real` is *deltaX* and the second is *deltaY*.) **Do not change other functions.** In particular, there is no need to change `intersect` because this function is used only for values in our geometry language and shift expressions are not geometry values.
3. Complete the Ruby implementation **except for intersection**, which means skip for now additions to the `Intersect` class and, more importantly, methods related to intersection in other classes. **Do not modify the code given to you.** Follow this approach:
 - Every subclass of `GeometryExpression` should have a `preprocess_prog` method that takes no arguments and returns the geometry object that is the result of preprocessing `self`. To avoid mutation, return a new instance of the same class unless it is trivial to determine that `self` is already an appropriate result.
 - Every subclass of `GeometryExpression` should have an `eval_prog` method that takes one argument, the environment, which you should represent as an array whose elements are two-element arrays: a Ruby string (the variable name) in index 0 and an object that is a value in our language in index 1. As in any interpreter, pass the appropriate environment when evaluating subexpressions. (This is fairly easy since we do not have closures.) To make sure you handle both scope and shadowing correctly:
 - **Do not ever mutate an environment**; create a new environment as needed instead. Be careful what methods you use on arrays to avoid mutation.
 - The `eval_prog` method in `Var` is given to you. Make sure the environments you create work correctly with this definition.

The result of `eval_prog` is the result of “evaluating the expression represented by `self`,” so, as we expect with OOP style, the cases of ML’s `eval_prog` are spread among our classes, just like with `preprocess_arg`.

 - Every subclass of `GeometryValue` should have a `shift` method that takes two arguments `dx` and `dy` and returns the result of shifting `self` by `dx` and `dy`. In other words, all values in the language “know how to `shift` themselves to create new objects.” Hence the `eval_prog` method in the `Shift` class should be very short.
 - REMEMBER YOU SHOULD NOT USE ANY METHOD LIKE `is_a?`, `instance_of?`, `class`, ETC.
 - Analogous to SML, an overall program `e` would be evaluated via `e.preprocess_prog.eval_prog []` (notice we use an array for the environment).- 4. . Implement intersection in your Ruby solution following the directions here, in which we require both double dispatch and a separate use of dynamic dispatch for the line-segment

case. Remember all the different cases in ML will appear somewhere in the Ruby solution, just arranged very differently.

- Implement `preprocess_prog` and `eval_prog` in the `Intersect` class. This is not difficult, much like your prior work in the `Shift` class is not difficult. This is because every subclass of `GeometryValue` will have an `intersect` method that “knows how to intersect itself” with another geometry-value passed as an argument.
- Every subclass of `GeometryValue` needs an `intersect` method, but these will be short. The argument is another geometry-value, but we do not know what kind. So we use double dispatch and call the appropriate method on the argument passing `self` to the method. For example, the `Point` class has an `intersect` method that calls `intersectPoint` with `self`.
- So methods `intersectNoPoints`, `intersectPoint`, `intersectLine`, `intersectVerticalLine`, and `intersectLineSegment` defined in each of our 5 subclasses of `GeometryValue` handle the 25 possible intersection combinations:
 - The 9 cases involving `NoPoints` are done for you. See the `GeometryValue` class—there is nothing more you need to do.
 - Next do the 9 remaining cases involving combinations that do not involve `LineSegment`. You will need to understand double-dispatch to avoid `is_a?` and `instance_of?`. As in the ML code, 3 of these 9 cases can just use one of the other cases because intersection is commutative.
 - What remains are the 7 cases where one value is a `LineSegment` and the other is not `NoPoints`. These cases are all “done” for you because all subclasses of `GeometryValue` inherit an `intersectLineSegment` method that will be correct for all of them. But it calls `intersectWithSegmentAsLineResult`, which you need to implement for each subclass of `GeometryValue`. Here is how this method should work:

*

- * It takes one argument, which is a line segment. (In ML the corresponding variable was a `real*real*real*real`, but here it will actually be an instance of `LineSegment` and you can use the getter methods `x1`, `y1`, `x2`, and `y2` as needed.)
- * It **assumes** that `self` is the intersection of (1) some not-provided geometry-value and (2) the line (vertical or not) containing the segment given as an argument.
- * It **returns** the intersection of the not-provided geometry-value and the segment given as an argument.

Together the 5 `intersectWithSegmentAsLineResult` methods you write will implement the same algorithm as on lines 110–169 of the ML code.

Advice

Advice for Approaching the Assignment:

- Understand the high-level structure of the code and how the SML and Ruby files are structured in different ways before diving into the details.
- Approach the questions in order even though there is some flexibility (e.g., it is possible to do the Ruby problems before the SML problems).

- Because almost all the SML code is given to you, for much of the Ruby implementation, you can port the corresponding part of the SML solution. Doing so makes your job much easier (e.g., you need not re-figure out facts about geometry). Porting existing code to a new language is a useful and realistic skill to develop. It also helps teach the similarities and differences between languages.
- Be sure to test each line of your Ruby code. Dynamically typed languages require testing things that other languages catch for you statically. Ruby will not even tell you statically if you misspell a method name or instance variable.

Provided Code

Download and edit `hw7.sml` and `hw7.rb` from the course website. I have provided tests cases as usual. Use them to understand what you need to do and test your code. My recommendation: keep track of what you have done and what you need to do.

Evaluation

Solutions should be:

1. Correct. We will play your game and we don't like games that crash or act in unexpected ways.
2. In good style, including indentation and line breaks.

As usual, submit only two files: `hw7.sml` and `hw7.rb`