

EECS-213, Fall 2015

Lab Assignment L3: The Buffer Bomb

Due: Nov. 16, 11:59PM

Introduction

This assignment will help you develop a detailed understanding of IA-32 calling conventions and stack organization. It involves applying a series of *buffer overflow attacks* on an executable file `bufbomb` in the lab directory.

Note: In this lab, you will gain firsthand experience with one of the methods commonly used to exploit security weaknesses in operating systems and network servers. Our purpose is to help you learn about the runtime operation of programs and to understand the nature of this form of security weakness so that you can avoid it when you write system code. We do not condone the use of this or any other form of attack to gain unauthorized access to any system resources. There are criminal statutes governing such activities.

Logistics

As usual, this is a team project.

You must do the assignment on one of the lab machines ([Wilkinson/T Lab machines](#)).

We generated the lab using `gcc`'s `-m32` flag, so all code produced by the compiler follows IA-32 rules, even if the host is an x86-64 system. This should be enough to convince you that the compiler can use any calling convention it wants, so long as it's consistent.

Hand Out Instructions

You can obtain your buffer bomb by pointing your Web browser at:

`http://gpubox.wot.eecs.northwestern.edu:18213/`

The server will return a `tar` file called `buflab-handout.tar` to your browser. Start by copying `buflab-handout.tar` to a (protected) directory in which you plan to do your work. Then give the command `"tar xvf buflab-handout.tar"`. This will create a directory called `buflab-handout` containing the following three executable files:

bufbomb: The buffer bomb program you will attack.

makecookie: Generates a “cookie” based on your userid.

hex2raw: A utility to help convert between string formats.

In the following instructions, we will assume that you have copied the three programs to a protected local directory, and that you are executing them in that local directory.

Userids and Cookies

Phases of this lab will require a slightly different solution from each student. The correct solution will be based on your userid.

A *cookie* is a string of eight hexadecimal digits that is (with high probability) unique to your userid. You can generate your cookie with the `makecookie` program giving your userid as the argument. For example:

```
unix> ./makecookie bovik
0x1005b2b7
```

In two of your three buffer attacks, your objective will be to make your cookie show up in places where it ordinarily would not.

The BUFBOMB Program

The BUFBOMB program reads a string from standard input. It does so with the function `getbuf` defined below:

```
1 /* Buffer size for getbuf */
2 #define NORMAL_BUFFER_SIZE 32
3
4 int getbuf()
5 {
6     char buf[NORMAL_BUFFER_SIZE];
7     Gets(buf);
8     return 1;
9 }
```

The function `Gets` is similar to the standard library function `gets`—it reads a string from standard input (terminated by ‘\n’ or end-of-file) and stores it (along with a null terminator) at the specified destination. In this code, you can see that the destination is an array `buf` having sufficient space for **32 characters**.

`Gets` (and `gets`) grabs a string off the input stream and stores it into its destination address (in this case `buf`). However, `Gets()` has no way of determining whether `buf` is large enough to store the whole input. It simply copies the entire input string, possibly overrunning the bounds of the storage allocated at the destination.

If the string typed by the user to `getbuf` is no more than 31 characters long, it is clear that `getbuf` will return 1, as shown by the following execution example:

```
unix> ./bufbomb -u bovik
Type string: I love 213.
Dud: getbuf returned 0x1
```

Typically an error occurs if we type a longer string:

```
unix> ./bufbomb -u bovik
Type string: It is easier to love this class when you are a TA.
Ouch!: You caused a segmentation fault!
```

As the error message indicates, overrunning the buffer typically causes the program state to be corrupted, leading to a memory access error. Your task is to be more clever with the strings you feed `BUFBOMB` so that it does more interesting things. These are called *exploit* strings.

`BUFBOMB` takes several different command line arguments:

`-u userid`: Operate the bomb for the indicated `userid`. You should always provide this argument for several reasons:

- It is required to submit your successful attacks to the grading server.
- `BUFBOMB` determines the cookie you will be using based on your `userid`, as does the program `MAKECOOKIE`.
- We have built features into `BUFBOMB` so that some of the key stack addresses you will need to use depend on your `userid`'s cookie.

`-h`: Print list of possible command line arguments.

`-s`: Submit your solution exploit string to the grading server.

At this point, you should think about the x86 stack structure a bit and figure out what entries of the stack you will be targeting. You may also want to think about *exactly* why the last example created a segmentation fault, although this is less clear.

Your exploit strings will typically contain byte values that do not correspond to the ASCII values for printing characters. The program `HEX2RAW` can help you generate these *raw* strings. It takes as input a *hex-formatted* string. In this format, each byte value is represented by two hex digits. For example, the string “012345” could be entered in hex format as “30 31 32 33 34 35.” (Recall that the ASCII code for decimal digit x is $0 \times 3x$.)

The hex characters you pass `HEX2RAW` should be separated by whitespace (blanks or newlines). I recommend separating different parts of your exploit string with newlines while you're working on it. `HEX2RAW` also supports C-style block comments, so you can mark off sections of your exploit string. For example:

```
bf 66 7b 32 78 /* mov    $0x78327b66,%edi */
```

Be sure to leave space around both the starting and ending comment strings (`'/*'`, `'*/'`) so they will be properly ignored.

If you generate a hex-formatted exploit string in the file `exploit.txt`, you can apply the raw string to BUFBOMB in several different ways:

1. You can set up a series of pipes to pass the string through HEX2RAW.

```
unix> cat exploit.txt | ./hex2raw | ./bufbomb -u bovik
```

2. You can store the raw string in a file and use I/O redirection to supply it to BUFBOMB:

```
unix> ./hex2raw < exploit.txt > exploit-raw.txt
unix> ./bufbomb -u bovik < exploit-raw.txt
```

This approach can also be used when running BUFBOMB from within GDB:

```
unix> gdb bufbomb
(gdb) run -u bovik < exploit-raw.txt
```

Important points:

- Your exploit string must not contain byte value `0x0A` at any intermediate position, since this is the ASCII code for newline (`'\n'`). When `Gets` encounters this byte, it will assume you intended to terminate the string.
- HEX2RAW expects two-digit hex values separated by a whitespace. So if you want to create a byte with a hex value of 0, you need to specify 00. To create the word `0xDEADBEEF` you should pass `DE AD BE EF` to HEX2RAW.

When you have correctly solved one of the levels, say level 0:

```
../hex2raw < smoke-bovik.txt | ../bufbomb -u bovik
Userid: bovik
Cookie: 0x1005b2b7
Type string:Smoke!: You called smoke()
VALID
NICE JOB!
```

then you can submit your solution to the grading server using the `-s` option:

```
../hex2raw < smoke-bovik.txt | ../bufbomb -u bovik -s
Userid: bovik
Cookie: 0x1005b2b7
Type string:Smoke!: You called smoke()
VALID
Sent exploit string to server to be validated.
NICE JOB!
```

The server will test your exploit string to make sure it really works, and it will update the Buffer Lab scoreboard page indicating that your userid (listed by your cookie for anonymity) has completed this level.

You can view the scoreboard by pointing your Web browser at

`http://gpubox.wot.eecs.northwestern.edu:18213/scoreboard`

Unlike the Bomb Lab, there is no penalty for making mistakes in this lab. Feel free to fire away at BUFBOMB with any string you like. Of course, you shouldn't brute force this lab either, since it would take longer than you have to do the assignment.

IMPORTANT NOTE: You can work on your buffer bomb on any Linux machine, but in order to submit your solution, you will need to be running on one of the Wilkinson or T-Lab machines.

Level 0: Candle (10 pts)

The function `getbuf` is called within BUFBOMB by a function `test` having the following C code:

```
1 void test()
2 {
3     int val;
4     /* Put canary on stack to detect possible corruption */
5     volatile int local = uniqueval();
6
7     val = getbuf();
8
9     /* Check for corrupted stack */
10    if (local != uniqueval()) {
11        printf("Sabotaged!: the stack has been corrupted\n");
12    }
13    else if (val == cookie) {
14        printf("Boom!: getbuf returned 0x%x\n", val);
15        validate(3);
16    } else {
17        printf("Dud: getbuf returned 0x%x\n", val);
18    }
19 }
```

When `getbuf` executes its return statement (line 5 of `getbuf`), the program ordinarily resumes execution within function `test` (at line 7 of this function). We want to change this behavior. Within the file `bufbomb`, there is a function `smoke` having the following C code:

```
void smoke()
{
    printf("Smoke!: You called smoke()\n");
    validate(0);
    exit(0);
}
```

Your task is to get BUFBOMB to execute the code for `smoke` when `getbuf` executes its return statement, rather than returning to `test`. Note that your exploit string may also corrupt parts of the stack not directly related to this stage, but this will not cause a problem, since `smoke` causes the program to exit directly.

Some Advice:

- All the information you need to devise your exploit string for this level can be determined by examining a disassembled version of BUFBOMB. Use `objdump -d` to get this dissembled version.
- Be careful about byte ordering.
- You might want to use GDB to step the program through the last few instructions of `getbuf` to make sure it is doing the right thing.
- The placement of `buf` within the stack frame for `getbuf` depends on which version of GCC was used to compile `bufbomb`, so you will have to read some assembly to figure out its true location.

Level 1: Sparkler (10 pts)

Within the file `bufbomb` there is also a function `fizz` having the following C code:

```
void fizz(int val)
{
    if (val == cookie) {
        printf("Fizz!: You called fizz(0x%x)\n", val);
        validate(1);
    } else
        printf("Misfire: You called fizz(0x%x)\n", val);
    exit(0);
}
```

Similar to Level 0, your task is to get BUFBOMB to execute the code for `fizz` rather than returning to `test`. In this case, however, you must make it appear to `fizz` as if you have passed your `cookie` as its argument. How can you do this?

Some Advice:

- Note that the program won't really call `fizz`—it will simply execute its code. This has important implications for where on the stack you want to place your `cookie`.

Level 2: Firecracker (15 pts)

A much more sophisticated form of buffer attack involves supplying a string that encodes actual machine instructions. The exploit string then overwrites the return pointer with the starting address of these instructions

on the stack. When the calling function (in this case `getbuf`) executes its `ret` instruction, the program will start executing the instructions on the stack rather than returning. With this form of attack, you can get the program to do almost anything. The code you place on the stack is called the *exploit* code. This style of attack is tricky, though, because you must get machine code onto the stack and set the return pointer to the start of this code.

Within the file `bufbomb` there is a function `bang` having the following C code:

```
int global_value = 0;

void bang(int val)
{
    if (global_value == cookie) {
        printf("Bang!: You set global_value to 0x%x\n", global_value);
        validate(2);
    } else
        printf("Misfire: global_value = 0x%x\n", global_value);
    exit(0);
}
```

Similar to Levels 0 and 1, your task is to get `BUFBOMB` to execute the code for `bang` rather than returning to `test`. Before this, however, you must set global variable `global_value` to your `userid`'s cookie. Your exploit code should set `global_value`, push the address of `bang` on the stack, and then execute a `ret` instruction to cause a jump to the code for `bang`.

Some Advice:

- You can use GDB to get the information you need to construct your exploit string. Set a breakpoint within `getbuf` and run to this breakpoint. Determine parameters such as the address of `global_value` and the location of the buffer.
- Determining the byte encoding of instruction sequences by hand is tedious and prone to errors. You can let tools do all of the work by writing an assembly code file containing the instructions and data you want to put on the stack. Assemble this file with `gcc -m32 -c` and disassemble it with `objdump -d`. You should be able to get the exact byte sequence that you will type at the prompt. (A brief example of how to do this is included at the end of this writeup.)
- Keep in mind that your exploit string depends on your machine, your compiler, and even your `userid`'s cookie. Do all of your work on one of the machines assigned by your instructor, and make sure you include the proper `userid` on the command line to `BUFBOMB`.
- Watch your use of address modes when writing assembly code. Note that `movl $0x4, %eax` moves the *value* `0x00000004` into register `%eax`; whereas `movl 0x4, %eax` moves the *value at* memory location `0x00000004` into `%eax`. Since that memory location is usually undefined, the second instruction will cause a segfault!
- Do not attempt to use either a `jmp` or a `call` instruction to jump to the code for `bang`. These instructions use PC-relative addressing, which is very tricky to set up correctly. Instead, push an address on the stack and use the `ret` instruction.

Logistical Notes

Handin occurs to the grading server whenever you correctly solve a level *and* use the `-s` option. Upon receiving your solution, the server will validate your string and update the Buffer Lab scoreboard Web page, which you can view by pointing your Web browser at

```
http://gpubox.wot.eecs.northwestern.edu:18213/scoreboard
```

You should be sure to check this page after your submission to make sure your string has been validated. (If you really solved the level, your string *should* be valid.)

Note that each level is graded individually. You do not need to do them in the specified order, but you will get credit only for the levels for which the server receives a valid message. You can check the Buffer Lab scoreboard to see how far you've gotten.

The grading server creates the scoreboard by using the latest results it has for each phase.

Good luck and have fun!

Generating Byte Codes

Using GCC as an assembler and OBJDUMP as a disassembler makes it convenient to generate the byte codes for instruction sequences. For example, suppose we write a file `example.S` containing the following assembly code:

```
# Example of hand-generated assembly code

    push $0xabcdef          # Push value onto stack
    add  $17,%eax           # Add 17 to %eax
    .align 4                # Following will be aligned on multiple of 4
    .long 0xfedcba98        # A 4-byte constant
```

The code can contain a mixture of instructions and data. Anything to the right of a '#' character is a comment.

We can now assemble and disassemble this file:

```
unix> gcc -m32 -c example.S
unix> objdump -d example.o > example.d
```

The generated file `example.d` contains the following lines

```
0: 68 ef cd ab 00          push    $0xabcdef
5: 83 c0 11                add     $0x11,%eax
8: 98                      cwtl
9: ba                     .byte 0xba
a: dc fe                 fdivr   %st,%st(6)
```


Each line shows a single instruction. The number on the left indicates the starting address (starting with 0), while the hex digits after the ':' character indicate the byte codes for the instruction. Thus, we can see that the instruction `push $0xABCDEF` has hex-formatted byte code `68 ef cd ab 00`.

Starting at address 8, the disassembler gets confused. It tries to interpret the bytes in the file `example.o` as instructions, but these bytes actually correspond to data. Note, however, that if we read off the 4 bytes starting at address 8 we get: `98 ba dc fe`. This is a byte-reversed version of the data word `0xFEDCBA98`. This byte reversal represents the proper way to supply the bytes as a string, since a little endian machine lists the least significant byte first.

Finally, we can read off the byte sequence for our code as:

```
68 ef cd ab 00 83 c0 11 98 ba dc fe
```

This string can then be passed through `HEX2RAW` to generate a proper input string we can give to `BUFBOMB`. Alternatively, we can edit `example.d` to look like this:

```
68 ef cd ab 00 /* push    $0xabcdef */
83 c0 11 /* add      $0x11,%eax */
98
ba dc fe
```

which is also a valid input we can pass through `HEX2RAW` before sending to `BUFBOMB`.