SUPPLEMENT: SPECULATIVE DECODING ACROSS CONSUMER SYSTEMS

Anonymous Authors[1]

A SUPPLEMENT SCOPE

This separate appendix accompanies manuscript v0.3, hardware-complete / runtime-reserved. It supplies statistical and measurement-boundary details without introducing a new result or a runtime implementation. All scientific limitations also appear in the main text. Internal source paths, repository identifiers and evidence hashes remain in the private evidence ledger rather than the anonymous PDF.

B FROZEN ESTIMATORS

Table A1 preserves each campaign's estimator. The primary sample unit is the prompt. Repeated observations contribute to its summary, rather than being treated as independent prompts. Pair ratios divide matched baseline decode time by speculative decode time. A geometric mean across prompt summaries is used for headline speedup. B570 timing remains diagnostic regardless of its statistical estimator.

The B570 finalizer builds its prompt vector in the insertion order of the archived pair records. Sorting by task ID changes the finite fixed-seed bootstrap endpoints even though it leaves the underlying estimator unchanged. Exact replay retains that original order. The M4 HumanEval lower endpoint uses a different order statistic from M4 24Q and RTX; those frozen conventions are retained. None of these prompt intervals captures the full distribution of possible thermal, session or runtime states.

C ENERGY BOUNDARIES AND ALLOWED CLAIMS

Ratios above one favor speculation within the named boundary. For M4 fixed-$k = 2$, the package ratio is 1.013 [0.990, 1.034], neutral within uncertainty. The registered $p_{\min} = 0.9$ secondary condition has a package-efficiency ratio 1.041 [1.018, 1.065]. This is not a replacement for the primary condition and does not establish a material additional speed gain. B570 serialized board efficiency is 0.302 [0.285, 0.320]; correctness failure restricts it to diagnosis. No between-platform energy ranking is valid.

D ROUND ACCOUNTING AND STATE SEMANTICS

The 358H target keeps its low-level context across rounds. Candidate evaluation, invalid-suffix rollback when needed, and correction or bonus decoding belong to the complete target-side timing region. Every OpenVINO proposal call receives the entire committed prefix. Its synchronous timing combines reconstruction and proposal; neither term can be isolated from this experiment without changing the measured execution.

The CPU path records 11,520 committed output tokens over 4,677 rounds; the NPU path records 11,520 over 4,686 rounds. Their directly measured C values are 2.4631 and 2.4584. Using the arithmetic baseline time per output token and arithmetic component totals yields CPU $(D, R, X) = (0.4304, 2.9767, 0.00124)$ and NPU $(4.1251, 2.9435, 0.00130)$. The resulting ratios 0.7227 and 0.3477 match ratios of total times, not the prompt-GM headline estimator.

Historical M4/RTX accepted-draft counters exclude correction or bonus output and have output-boundary effects. They are not substituted for the directly recorded 358H committed-progress metric. Likewise, target-forward PP2/PP1 ratios are never presented as complete realized target-round cost.

E DEVIATIONS AND PROVENANCE BOUNDARIES

The M4 corrected synthetic ceiling was preregistered but not executed. Earlier synthetic acceptance diagnostics are not a substitute. The representative and separately preregistered code workloads stay distinct. Early MLX precision/correctness failures are qualification history, not failures of the final Metal Q8_0 path.

The B570 formal v2 correctness failure triggered its stop rule. A later six-prompt serialized probe passed 18/18 pairs, but full-workload serialization yielded only 60/90. Earlier remote-interaction-contaminated verification observations

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the Machine Learning and Systems (MLSys) Conference. Do not distribute.

Table A1. Frozen statistical policies. GM = geometric mean. Indices below are zero-based order statistics of sorted bootstrap draws; NumPy quantiles use the original analyzer's convention.

Campaign	Within prompt	Resamples	Seed	CI endpoints / generator
M4 24Q	GM of 3 ratios	10,000	20260907	[249,9749]; Python Random
M4 HumanEval	GM of 3 ratios	100,000	20260910	[2500,97499]; Python Random
RTX HumanEval	GM of 3 ratios	10,000	20260910	[249,9749]; Python Random
B570 fallback	GM of 3 ratios	10,000	20260910	[250,9750]; Python Random
358H Phase 3	Median of 3 ratios	10,000	20260919	Quantiles .025/.975; NumPy default_rng

Table A2. Sensor boundaries and allowed interpretations. No cells are combined into whole-system energy.

Campaign	Measurement boundary	Allowed statement
M4 HumanEval	Silemetry CPU + GPU + ANE package aggregate; separate DRAM excluded	Exact fixed-$k = 2$ energy neutral within uncertainty; registered threshold variant secondary
RTX 5070 Ti Laptop	NVIDIA board / CPU package are distinct domains; follow-up process window includes loading	No formal serialized HumanEval energy comparison
B570 fallback	Arc adapter board only; no CPU package or wall power	Diagnostic board efficiency only; path not globally exact
358H Phase 3	No qualified end-to-end energy boundary	No end-to-end CPU claim; NPU energy not admissible

are excluded from the plotted final serialized cells. A legacy "exact" field label in historical artifacts does not establish workload-global equality.

Windows follow-up derived tables and numerical captures support the manuscript, but historical raw per-run provenance is weaker. The CUDA score capture came from a separate same-commit instrumented build and does not replace formal measurements. The 358H source reconstruction remains `STRONGLY_SUPPORTED`, not proven exact historical upstream identity. Its completed Phase-3 records supersede the blocked-preflight empty scaffold. These are retained qualifications, not unresolved invitations to alter frozen experiments.

F Verification Context Lookup

Table A3 retains all context cells behind the main verification figure. Values are target-forward ratios, not complete target-side round cost or integrated speedup. Context ranges do not represent uncertainty intervals. RTX denotes RTX 5070 Ti Laptop throughout this appendix.

G Evidence Inventory

Table A4 collects the observed regimes and evidence classes. These are case descriptions, not a hardware ranking, population-wide failure rate, or exhaustive taxonomy. M4's separate-session studies establish opposite observed outcomes; neither diagnosed mechanism is assigned to that contrast.

Table A3. Verification-path lookup. Each row is a measured context cell; ratios are shown to six decimal places from the frozen source. Qualification describes the associated execution path. M4 contexts and B570 contexts are prefix lengths; RTX uses the reported context depth. The stacks and context sets are not matched.

Path	Context (tokens)	V_2^{micro}	Qualification
M4 Metal	512	1.022182	Qualified shared path
M4 Metal	2048	1.076126	Qualified shared path
M4 Metal	8192	1.032264	Qualified shared path
RTX batched	0	1.009030	Correctness-blocked; diagnostic
RTX batched	256	0.983148	Correctness-blocked; diagnostic
RTX serialized	0	2.430996	Exact secondary control
RTX serialized	256	2.137011	Exact secondary control
B570 fast	512	1.242576	45/90 exact; diagnostic, inadmissible
B570 fast	2048	1.637295	45/90 exact; diagnostic, inadmissible
B570 serialized	512	1.982668	60/90 exact; diagnostic, inadmissible
B570 serialized	2048	1.991707	60/90 exact; diagnostic, inadmissible

Table A4. Evidence inventory across tested regimes. P: primary; S: secondary; M: mechanism; D: diagnostic. Both B570 paths remain globally inadmissible diagnostics. RTX serialized controls group CPU-to-RTX and RTX-to-RTX, each 90/90 exact. The 358H P/M entries separate primary outcomes from mechanism-supported decomposition. Fractions count generated-token equality, not functional correctness. Case annotations are descriptive and non-exhaustive.

Case	Qualification	Outcome	Class	Case annotation
M4 representative 24Q	Qualified; 72/72 exact	Negative	P	Workload-conditioned
M4 HumanEval30	Qualified; 90/90 exact	Profitable	P	Workload-conditioned
RTX batched	Blocked; gate failed	Not admissible	M	Verification-constrained
RTX serialized controls	Qualified; 90/90 each exact	Negative	S	Verification-constrained
B570 fast	Inadmissible; 45/90 exact	Not admissible	D	Correctness-blocked
B570 serialized	Inadmissible; 60/90 exact	Not admissible	D	Correctness-blocked
358H CPU	Qualified; 90/90 exact	Negative	P/M	Target-side dominated 87.34% target side
358H NPU	Qualified; 90/90 exact	Negative	P/M	State-interface bound 58.35% replay + proposal