Reference-Preserving Speculative Decoding on Consumer Systems: Diagnosis, Repair Scope, and Measured Cost

Chengzhan Li

University of Electronic Science and Technology of China

Abstract

Speculative decoding changes the numerical history of a quantized runtime as well as its execution cost. When an application requires a fixed ordinary greedy output, the runtime must establish where constraints are needed and whether the qualified design saves time. We connect local state/path diagnosis, phase-scoped repair and measured comparisons with ordinary and matched target-only execution. Natural donor-state crosses on CUDA and Vulkan distinguish current-path, retained-state and interaction effects; a separate B570 fork study shows that immediate agreement can coexist with later divergence. On RTX, a query-layout transformation retains batched projection and feed-forward work. Target prefill and continuation form an inclusion-minimal passing set within a tested four-switch family, and the frozen design qualifies full responses on 24 project-unused inputs. Resident-request speed is 1.742 times ordinary execution; the matched draft-free path already achieves 1.683 times, leaving a 1.035-times speculative increment. Seven tasks regress against matched request time, and one round reverses direction. Wider fixed-capacity drafting and a B570 endpoint repair qualify while losing performance. Auxiliary M4 and 358H cases bound the value of added control and draft-only optimization. These results support a configuration-specific decision process from diagnosis through qualification to cost comparison; repair evidence remains restricted to the tested Qwen3 family.

Keywords: speculative decoding, numerical consistency, execution state, runtime design, performance evaluation, consumer systems

1. Introduction

Speculative decoding uses a draft to propose tokens and a target to evaluate several positions at once [1]. On consumer systems, this extra work within a request can amortize target execution when memory capacity and request traffic limit batching across requests. The implementation also changes how the target executes: scalar continuation becomes multi-position verification, cache contents follow a different history, and rejected positions require reconciliation. A valid sampling rule therefore leaves two practical questions open: does the quantized runtime reproduce the required output, and does it reduce the cost of producing it?

We study systems in which ordinary greedy decoding under a fixed runtime configuration defines the reference. Such a requirement arises in regression tests and applications that need repeatable outputs. Reference preservation means matching the registered token sequence or endpoint; it does not establish that the answer is functionally correct or that every intermediate floating-point value is identical. The runtime designer must choose where to enforce consistency and then measure the resulting cost. A constraint can repair one input while breaking another, or recover the output at the expense of the intended acceleration.

The visible token prefix does not determine the necessary constraint. Two executions can emit identical tokens while retaining different key/value (KV) values, pending tokens or sampler history. Their next decision can follow the retained state, the current execution recipe, or an interaction between the two. Conversely, different scores can produce the same immediate greedy decision while later outputs diverge. Distinguishing these cases helps decide whether to constrain state formation, current verification, or both.

A repair may improve the target path before a draft is added. Comparing repaired speculation only with ordinary decoding measures the combined deployment change. A matched target-only execution, using the repaired path without a draft, measures how much additional benefit speculation supplies. Both paths must be executed and charged under the same output requirement; acceptance rates and target-call counts cannot replace their measured costs.

An RTX continuation intervention repairs one task and regresses another, leaving aggregate reference agreement unchanged. A later phase-scoped attention implementation qualifies full responses on 24 inputs unused in the accessible project history. Its resident-request speed is 1.742× ordinary decoding, but the matched draft-free path already achieves 1.683×; adding speculation gives 1.035×. A distinct B570 implementation preserves its registered endpoint while remaining substantially slower than both draft-free baselines. We organize the study around three questions:

1. **RQ1**, diagnosis: does the observed deviation follow retained state, the current recipe, or their interaction?

Email address: chengzhan.li@std.uestc.edu.cn (Chengzhan Li)

2. **RQ2**, repair: which phase constraints preserve the reference within a defined implementation family?
3. **RQ3**, cost: after qualification, what benefit remains against ordinary decoding and the matched target path?

The contribution is a linked diagnosis, repair and cost evaluation within explicit output contracts. Natural donor-state crosses with own-path controls distinguish local state, path and interaction effects on CUDA and Vulkan; a separate same-state B570 fork study establishes the limits of immediate agreement. The RTX query-layout transformation retains batched projection and feed-forward work, and a complete four-switch factorial identifies a sufficient target-phase scope within the tested family. Measured ordinary/matched/speculative comparisons separate the full deployment gain from the speculative increment. B570 supplies a qualified-but-slower counterexample, while the auxiliary M4 and 358H cases delimit the value of added control and draft-only optimization.

The study concerns runtime design and finite qualification. Its crosses are offline experiments, and the repair remains specific to the tested Qwen3 family and configurations. Sections 2 and 3 define the implementation context and measurement contracts; Sections 4–6 answer the three questions. Section 7 draws the resulting design choices and states their limits. The supplement retains campaign details, historical results and the complete evidence trail.

2. Runtime Architecture and Research Context

2.1. Execution as a stateful transaction

A speculative iteration advances a committed prefix through drafting, target verification and reconciliation. The draft proposes up to k tokens; the target evaluates the pending token and proposal positions, often in a caller batch containing several tokens. Acceptance, correction and a possible bonus token determine the committed output. Rejected positions must be removed or reconciled before the next iteration, and stopping follows the registered EOG and cap rule. Figure 1 connects these operations to the state and phase controls studied here.

Target and draft retain distinct state (Figure 1A). KV ownership, logical positions, pending logits or tokens, sampler history and loop counters connect successive calls. A token can already be sampled and accepted into the sampler while still awaiting evaluation into the cache. Repeating or omitting either event changes the transaction. The early intervention frontends therefore preserve pending and sampler state as well as KV. The later B570 candidate binds phases within one target context and live sampler; the measured RTX candidate uses no state transplant.

Microbatch capacity UB limits how the backend partitions a caller batch. It is distinct from k, the occupied query count and the frontend's output reservation. A UB2 caller may contain only one continuation token; increasing k can reduce caller count while increasing the number of micrographs; changing output reservation can alter the recipe without changing UB. Capacity, occupied queries and output reservation must therefore be distinguished when interpreting diagnostic crosses and performance counters.

The implementations use pinned llama.cpp releases and private frontends [2]. The late RTX path uses Qwen3-8B and Qwen3-0.6B [3], both Q8_0, with non-flash CUDA attention. Its transformation uses existing ggml views and operations, with no new CUDA arithmetic kernel or acceptance rule. B570 uses Vulkan and a distinct phase-binding frontend. Historical Metal and OpenVINO cases retain their own contracts. Because hardware, backend and frontend vary together, these cases compare execution designs rather than hardware alone.

2.2. Reference preservation and determinism

Our requirement fixes an ordinary path and an output endpoint. A matching token sequence may still have different logits or cache values, while a repeat-stable candidate can consistently disagree with the reference. Numerical-consistency work explains how execution shapes and reductions affect this distinction. Batch-invariant inference constrains reduction strategies across batches [4]. LLM-42 combines decode–verify–rollback, padded verification shapes and replacement of decoded KV entries with verifier entries; it permits different consistent strategies for prefill and decode [5]. Stage-Replay examines fixed-prefix precision controls and bidirectional cache transplantation [6]. Vosti specifies and verifies deterministic system behavior [7], and MarginGate uses margin-triggered verification with repair of confirmed mismatches [8].

We use these consistency and verification principles to connect natural donor-state diagnosis to a query-layout and phase design, then test finite native-output qualification and paid cost. Table 1 summarizes this scope. We do not implement a same-contract comparison with LLM-42, Stage-Replay or Vosti, so the results establish no speed or preservation advantage over those methods.

2.3. Performance and heterogeneous execution

Prior work uses heterogeneous placement and draft-budget control to improve execution. Dovetail and DuoDecoding exploit complementary CPU/GPU capabilities [11, 12]; TurboSpec and BanditSpec adapt speculation to execution conditions [13, 14]. The published HeteroSpec studies contextual heterogeneity in verification allocation [15]. We require preservation of a selected ordinary output and measure whether the transformation reduces cost.

Lossless but Not Free examines consumer backend cost and cache choreography when verification fails to amortize target work [9]. Performance or Illusion? shows why reductions in apparent decoding work do not guarantee production-engine performance [10]. We add reference qualification and the matched draft-free comparator to that decision. M4 control and 358H offload illustrate separate cost limits; neither replicates the RTX repair.

3. Study Design and Measurement Contracts

3.1. Systems, inputs, and evidence roles

The principal cases use the contracts in Table 2. All final targets are Qwen3-8B: changing the device, draft representation or




Figure 1: State ownership and implemented consistency controls. (A) Target and draft keep distinct state through proposal, verification and reconciliation. (B) The RTX query view moves query columns into the batch axis while retaining batched projection and FFN work; numbered tiles are illustrative. (C) Role and phase select the query-batch graph flag, which must also match for topology reuse. The measured RTX candidate uses no state transplant. Section 5 defines the transformation and its implementation guards.

backend does not create a second target family. HumanEval [16] and sanitized MBPP [17] supply coding inputs; M4 also uses a prospective Spec-Bench partition [18]. Prompt construction remains campaign-specific. The measured output property is reference reproduction, not benchmark test-pass accuracy.

The late RTX and B570 candidates use non-flash attention, greedy sampling and separately frozen capacities, phase settings and runtime/model bindings (Supplement §S1 and §S5.2). Their campaigns remain separate. The five evidence roles are: prediction reproduces native behavior; selected-boundary crosses diagnose local dependence; exposed probes select a repair; a frozen recipe is checked on project-unused inputs; and separate paid sessions measure qualified cost. Repetitions describe stability and cost variation. Forks and within-request decision events belong to their parent tasks and do not increase the independent input count.

For the RTX expansion, eligibility and the recipe were frozen before new reference outputs were generated. The exposure audit excluded previously executed or ambiguous inputs and selected 24 MBPP tasks from 224 eligible candidates. No eligible unused HumanEval inputs remained at that stage, so a pre-output amendment selected MBPP. Project-unused means absent from accessible project execution records, not unseen during training. The panel becomes exposed when reused for width studies and later CPU analyses. B570's 15-input panel follows its own accessible-history audit; omitted RTX bulk records were not independently rescanned.

3.2. *Registering the output requirement*

Let $R(x)$ denote ordinary output under fixed weights, tokenizer, prompt formatting, sampler, runtime, backend and stopping rule. RTX qualification compares the full response array, length, terminal ID and stop reason, and checks reference repeat stability. The expansion contains a complete $24 \times 4 \times 4$ task/condition/repetition matrix: 384 rows and 96 qualified responses per condition. Reference lengths range from 11 to 128 IDs; 23 tasks stop at EOG and one at the cap.

B570 retains IDs through the first runtime EOG or token 128, whichever comes first. A speculative response can satisfy this endpoint requirement while containing additional raw suffix IDs. Those IDs remain charged. Endpoint equality, raw-array equality and unknown historical raw comparisons are reported separately. Historical re-tokenized-text checks retain their original weaker contract (Supplement §S1).

A latency ratio qualifies as a reference-preserving speedup only after the output gate passes. A shorter divergent response does not qualify, and repeat stability alone cannot certify agreement with R. The finite checks establish neither functional correctness nor equality of all intermediate values or arbitrary future outputs.

Table 1: Research context and additional evidence in this study. The cited methods are not same-contract performance baselines.

Prior work	Established basis	Additional evidence here
Batch-invariant inference; LLM-42 [4, 5]	Reduction/shape consistency; verified tokens and KV reconciliation	Qwen3 query views and phase dispatch, finite qualification, and ordinary/matched paid costs
Stage-Replay; Vosti [6, 7]	Fixed-prefix state intervention; specified system determinism	Natural donor × current-recipe crosses with shams; output qualification in a tested implementation family
Consumer cost anatomy; Performance or Illusion? [9, 10]	Backend verification cost and limits of performance proxies	Qualified fixed-UB width failure and separation of target-path from speculative request gains

Table 2: Principal study contracts. Each case processes one request at a time. Historical text checks, which are weaker than direct-ID qualification, are retained separately in the supplement.

Case	Runtime/model setting	Output and exposure	Paid interval
RTX expansion	5070 Ti Laptop; CUDA; Q8_0 target/draft; private b10839-based frontend	Full response through EOG/cap128; 24 project-unused MBPP, four repeats	Server generation; resident HTTP request
B570 repair	Arc B570; Vulkan; Q8_0 target/draft; phase-binding frontend	First-EOG/cap128 endpoint; 15 project-unused inputs, two repeats	Native generation; whole request; host return
M4 runtime	MacBook Air M4; Metal; Q8_0 target/draft	Direct generated IDs; prospective 30 HumanEval plus 30 Spec-Bench, three repeats	Registered post-prefill runtime interval
358H stateful	Arc B390 Vulkan target; symmetric INT4 OpenVINO CPU/NPU draft	Direct IDs; 30 prompts, three repeats per draft condition	Registered stateful interval and target-work accounting

3.3. Controlled state and current-recipe crosses

At a naturally reached boundary, express the decision as

$$d = F(p, s, e), \tag{1}$$

where p is the committed prefix, s the retained runtime/numerical state and e the current execution recipe. Cross two naturally formed donors s_0, s_1 with recipes e_0, e_1, holding the registered prefix and current logical input fixed. In the resulting matrix, a within-row change is a current-recipe effect for that donor; a within-column change is a donor-state effect for that recipe. Dependence on one factor only under a particular value of the other indicates a local interaction. Token IDs are categories; their numerical differences are not effect sizes.

A valid cross requires consistent cache ownership and positions, faithful restoration, and compatible pending and sampler semantics. Own-path shams restore each donor under its native recipe and compare with uninterrupted execution. Natural donors use online proposals, without feeding future reference answers or a recorded proposal tape into the candidate. Earlier sealed-proposal prediction studies answer a separate reproduction question (Supplement §S2.1). The selected cuts probe known sensitivity; they do not estimate its prevalence or provide a complete counterfactual suffix for every cell.

3.4. Two paid baselines and task-level estimation

Let M be target-only execution on the repaired path and C speculation on that path. Together with ordinary R, they distinguish the deployment change R/C, target-path change R/M and incremental draft benefit M/C. Each baseline is executed and charged. R is the registered comparator; it is not a proven optimum over ordinary implementations.

For late RTX and B570, first take each task's median absolute time in each condition, then form its baseline/candidate ratio. For n complete task pairs,

$$S_{b/c} = \exp\left[\frac{1}{n}\sum_{i=1}^{n}\log\left(t_{i,b}/t_{i,c}\right)\right]. \tag{2}$$

A ratio above one favors the denominator path. For common tasks and this aggregation,

$$S_{R/C} = S_{R/M}S_{M/C}. \tag{3}$$

This multiplicative identity cannot allocate attention, KV, synchronization or host cost. M4 retains its frozen estimator and random streams; 358H uses a median of paired ratios before the task geometric mean, a different estimator.

RTX ordinary-reference ratios are a later CPU reanalysis of the same paid records; the expansion originally emphasized matched comparisons. Descriptive 95% intervals resample the 24 task-median ratios with 10,000 common index resamples, NumPy PCG64 seed 20261008 and linear/type-7 quantiles. The earlier bootstrap convention remains in Supplement §S4.1. Task resampling does not estimate session or day variation, and round-specific geometric means are reported separately from the task-median estimator.

The RTX server-generation field `predicted_ms` charges draft and verification work between its timestamps, excluding initial prompt work and first sampling and potentially final bookkeeping. Resident-request time covers non-streaming HTTP response receipt and parsing. Loading, warmup, boundary telemetry and shutdown are excluded; post-response asynchronous cleanup is not certified inside this interval. Their difference is not a measured host component. B570's native-generation,

whole-request and host-return boundaries are defined separately in Supplement §S5.4. Unlike timers are not pooled into a platform ranking.

4. Locating the Consistency Boundary (RQ1)

4.1. A repair and a regression under the same intervention

The continuation experiment tests whether a local path change can recover the reference. The RTX intervention changes target continuation from UB2 to UB1 while retaining prefill, draft settings and caller grouping. On 19 exposed HumanEval tasks, the predictor reproduces both native conditions in all 57 repeated complete arrays. HumanEval/15 repairs, /25 regresses and /18 remains divergent, leaving reference agreement at 51/57 in both conditions. The unchanged aggregate conceals opposing task effects, so continuation-only control does not satisfy recovery without regression.

A separately selected 24-task MBPP panel reaches 72/72 prediction/native agreement in each condition, but only 66/72 reference agreement. MBPP/304 remains a divergent 47-ID response while changing token 488 to 481 at zero-based position 33. Accurate prediction of a changed response does not establish reference recovery. We therefore examine retained state and the current call separately.

4.2. Natural donor state crossed with the current call

In Figure 2, rows select naturally formed donor states and columns select the current recipe at a shared committed prefix. Horizontal changes expose current-path dependence; vertical changes expose retained-state dependence. The displayed IDs label decisions rather than numerical distances. A change confined to one donor/recipe pairing indicates an interaction. Own-path shams check that restoration itself preserves the native decision.

For RTX, N0 and N1 denote the native baseline and continuation-intervention histories. Four exposed HumanEval probes yield 24 donors, 48 state/current-path forks and 24 shams across repetitions. Donors preserve actual pending state, cache positions and sampler history. The shams pass and forking leaves the original context unchanged. At /15's 13-token cut, either donor gives 9147 under current UB2 and 4199 under UB1 at the third submitted decision (Figure 2A). The local decision follows the current path. At /25's four-token cut, only the N1-donor/current-UB1 cell changes, producing the sequence 271,750,8168 rather than beginning with 1406 (Figure 2B). This is a local interaction between state and path. The selected /18 and /31 cuts are discrete nulls, which do not establish invariance over their remaining trajectories.

All 12 prompt-KV donor comparisons agree, whereas 70 of 72 generated-prefix K/V tensor comparisons differ; the tested first-layer K/V remain equal. The discriminating /15 bonus row is itself a single-token microbatch under either history. Its final nominal shape alone therefore cannot explain the decision: inputs and preceding state formation also matter. The evidence motivates attention-related controls without isolating a unique kernel cause. Auxiliary short continuations and their 1,278 forwards are diagnostic work, not a paid performance panel.

4.3. One unchanged block does not certify the remaining trajectory

A separate B570 experiment forks the same live state, with byte-checked KV, at the first eligible verification block after at least 64 committed IDs. It processes that block under UB1 or UB128. Twenty-four reserved prompts and three repetitions produce 72 eligible forks. Every paired raw score record changes, yet immediate top-1 IDs and acceptance decisions remain equal across 195 paired decision events: no execution or task changes its immediate decision.

Complete committed-ID trajectories in Figure 2F differ in 18/72 executions from six of 24 tasks. Later alternate blocks continue to use UB128, and proposals evolve under the accepted history. This result concerns a sustained continuation policy, not one altered block followed by restoration. Qualification must therefore check the registered output beyond the sampled block: a local discrete null can coexist with later divergence, and score movement alone does not predict an immediate decision change. Neither the 72 forks nor the 195 internal events constitute additional independent tasks.

4.4. B570 crosses identify a whole-recipe boundary

For B570, N1 labels the repaired prior frontend. The figure labels the alternate HumanEval donor Alt. (E_k1_ub2) and the ordinary MBPP/72 donor N0. Neither denotes the later phase-binding candidate. These crosses test whether the RTX diagnostic distinction remains useful in a different runtime. Three tasks in six repeated contexts provide 12 own-path shams and 24 auxiliary target cells. Restored states retain checked byte contents, sequence-zero ownership and logical positions. At HumanEval/145's prefix 56, the selected matrix is $[(71465, 279), (279, 279)]$; at /42's prefix 73 it is $[(432, 1817), (1817, 1817)]$ (Figure 2D,E). Both show a local interaction. At MBPP/72's prefix 40, $[(320, 320), (308, 308)]$ varies only with donor state, under identical current UB1/output-reservation-3 columns (Figure 2C).

The HumanEval recipes change microbatch capacity and output reservation together, so the factor tested is the whole recipe. These crosses do not isolate UB or transfer the RTX repair to Vulkan. Full counterfactual continuations for each cell are unavailable; the subsequent B570 candidate undergoes its own native endpoint qualification. The greedy sampler history, clone metadata and shams support the tested restoration, while opaque sampler bytes and general stochastic-state restoration remain outside that check. At the same committed prefix, local path, state and interaction dependence can require different control placements.

4.5. Prediction and simple execution constrain added machinery

Prediction fidelity alone does not establish an online repair mechanism. B570 prospective prediction matches 72/72 native arrays on a reserved 24-task cohort even though reference agreement is 60/72. RTX's initial target-only batched-path predictor reaches 24/36 and fails its frozen 36/36 gate, so no reserved inference follows. A later independent-proposal replay obtains




Figure 2: Three local dependencies and the limit of a local check. Rows select natural donor states; columns select the current recipe. Token IDs are categorical; filled tiles group equal IDs, and links mark equality or difference between adjacent cells. (A) RTX /15 follows the current path. (B) RTX /25 and (D,E) B570 HumanEval show interactions. (C) B570 MBPP/72 follows retained state under identical UB1/reservation3 columns. The B570 HumanEval columns change UB and output reservation together. N0 in (C) is the ordinary donor; Alt. in (D,E) is the cross recipe E_k1_ub2. Here r denotes output reservation; the two HumanEval recipes use UB1/r = 3 and UB2/r = 2. Own-path shams pass. (F) A separate B570 study finds 0/72 immediate but 18/72 downstream changes under sustained alternate UB128 continuation; it does not isolate a single-block aftereffect.

H2/native and reference-only/native agreement of 72/72, again with 60/72 reference agreement. The later study resolves the earlier reproduction interface, but neither result establishes cheap online correction.

On the 19 RTX tasks, draft-free U_2 reproduces all 57 intervention N_1 arrays and stop boundaries, including /15's repair and /25's regression. It needs no draft, transplant, proposal tape or reference answer. This establishes output equivalence, without a speed claim or demonstrated equality of live logits/KV.

Offline screening provides no supported evidence-acquisition advantage over direct enumeration. RTX direct enumeration and proxy screening both abstain after 114 record equivalents beyond common acquisition; B570 direct verification requires 72 and proxy screening 144. Unknown counterfactuals remain unknown. These are evidence-acquisition counts, not latency measurements. RQ1 identifies local diagnostic distinctions; an automatic repair selector remains unvalidated.

5. Phase-Scoped Implementation and Qualification (RQ2)

5.1. Constraining attention while retaining batched work

The RTX design targets the attention graph rather than serializing the whole network. An initial implementation builds one non-flash Qwen3 attention subgraph per query and concatenates the results. The later query-batch implementation represents query columns in the ggml batch dimension, allowing existing operations to process them in parallel while preserving one-column query structure. Projection, output projection and feed-forward computation remain batched (Figure 1B).

After the existing query/key/value permutations, the supported single-KV-stream query has dimensions $(d, q, h, 1)$. A `ggml_view_4d` reinterprets it as $(d, 1, h, q)$, preserving the source strides and assigning the original query-column stride to the new batch axis. Shared K/V broadcast across query batches; the mask view changes from $(n_{\mathrm{KV}}, q, 1, 1)$ to $(n_{\mathrm{KV}}, 1, 1, q)$. Existing key-query multiplication, softmax, value multiplication and contiguous recombination perform attention. The design retains the tested scalar-query computation structure locally while preserving parallel work elsewhere; it adds no new backend arithmetic.

Implementation guards admit Qwen3 non-flash attention, one KV stream and compatible mask dimensions, with no attention bias, sinks or MLA value projection. The initial limit is four queries; a later width build extends the admitted graph to eight. Native qualification is required within those guards, and unsupported model graphs, precisions or backends inherit no preservation claim.

5.2. Phase dispatch and graph reuse are part of the implementation

The transformation must be active in the intended phase, including when diagnostic capture is disabled. A process-fixed mask and thread-local guard select target prefill/continuation bits 1/2 and draft prefill/continuation bits 4/8 (Figure 1C). The guard restores the prior active state on exit and executes before the capture-disabled fast path returns to native decoding. Diagnostic settings therefore cannot silently bypass the constraint.

The active query-batch flag is copied into graph parameters and context. Reuse is rejected if it differs from the cached topology key, preventing a phase-layout mismatch even when ordinary microbatch fields agree. A new prompt resets the phase to prefill. Role and phase therefore control graph construction and reuse directly.

Qualification checks captured multi-query nodes and capture-on/off behavior; paid capture-off sessions omit observer metadata and forced witness synchronization. The optional target-state-move branch is inactive in the expansion configuration. The measured candidate charges native drafting, verification and reconciliation without that transplant. Implementation details and timer boundaries are retained in Supplement §S3.1.

5.3. The finite phase family

The factorial tests which phases require the query-batch constraint in this implementation. Figure 3A tests all 16 masks at $k = 3$/UB4 on four exposed HumanEval probes, twice each: 128 requests. Outputs and stop boundaries are repeat-stable. Masks 3, 7, 11 and 15 pass the complete panel. /15 and /31 pass every mask, /25 needs at least one target-phase bit, and /18 needs both; draft bits do not change this pattern.

Mask 3 alone has no passing strict subset, making it inclusion-minimal in the tested four-switch family. This selects a sufficient target-phase scope, not a universal requirement on every input or implementation. Acceptance, cache ownership and stopping still need to preserve the transaction. The factorial also uses different geometry from the earlier UB2/UB1 intervention, so /15's all-mask agreement does not negate that path effect.

A smaller scope need not be faster. In a separate 19-task, six-repetition cost panel, mask 3 gives 1.278× generation and 1.113× request speed against matched target-only. Removing draft constraints from mask 15 adds only 1.004× generation speed, with descriptive interval [0.998, 1.009], below the frozen 1.03× extra-generation gate. The later 24-input expansion gives 1.015× over mask 15. Scope selection therefore follows qualification, with its cost assessed separately.

5.4. Frozen inputs and geometry boundaries

The frozen mask-3/$k = 3$/UB4 recipe qualifies all 96 candidate responses on the 24-input expansion. Matched target-only and mask-15 speculation also qualify. This extends the repair from exposed probes to a separately frozen panel, within the same model family and configuration.

Figure 3B tests the geometry boundary on an independent 11-input panel at $(k, \mathrm{UB}) = (1, 2), (3, 4), (5, 6), (7, 8)$ and caps128/256/512, using fresh scalar references and two repeats. The first two pairs qualify; MBPP/229 fails at both wider pairs across all caps and repetitions while matched controls pass. The earlier HumanEval/18 wide target-only failure remains a separate boundary outside this denominator. The longest observed reference has 261 IDs, so cap512 is a limit rather than evidence of a 512-token trajectory.

At MBPP/229's common 47-token prefix, crossing naturally retained ordinary and constrained states under two current UB6 layouts changes the EOG decision with the donor. Current layout changes continuous scores without a separate discrete flip; four own-path shams pass. This local retained-state effect explains why changing only the current layout at that boundary is insufficient, without identifying a unique cause of all width failures. Two cap contexts repeat one task boundary. The joint k/UB sweep remains distinct from the fixed-UB draft-width cost experiment in Section 6.

5.5. A separate B570 implementation and qualification scope

The B570 candidate uses a different control interface: it forms target state with the ordinary prompt caller and output reservation, samples the pending token once, then binds continuation from UB128 to UB1 in the same context and live sampler. A private API synchronizes, changes capacity and requests scheduler reservation under a frozen context/batch/sequence contract. Instrumented checks compare serialized KV across binding; paid capture-off requests omit witness readbacks. The existing $k = 2$, draft-UB1 accept/bonus/rollback loop remains.

The candidate qualifies 12 development requests, 112 requests on 56 exposed inputs and 30 requests on 15 project-unused inputs under its endpoint contract. It removes the old second context and three witness readbacks but does not implement the RTX query-layout transformation. Earlier B570 repair produced a local long-panel gain yet failed MBPP/72 on a new-input panel and five UB2 alternatives (Supplement §S5.1). The later same-context binding provides a separately qualified repair whose cost is assessed in the following comparisons.

6. Does the Qualified Design Pay? (RQ3)

6.1. RTX: deployment gain and speculative increment

The RTX comparison separates two decisions before measuring their benefit (Figure 4A). Ordinary target-only R uses mask 0/UB1; matched target-only M uses mask 3/UB4; speculative C, also denoted C_3, adds a draft at $k = 3$ on that path. A fourth condition, C_{15}, constrains all phases. Each of four balanced rounds uses a separate resident process for each condition, with one excluded warmup and 24 formal requests per process. Condition and task orders rotate and recorded cache reuse is zero. The comparisons share tasks and a campaign, without sharing one simultaneous resident process.

In Table 3 and Figure 4B,C, generation speed is 1.170× ordinary and 1.169× matched target-only, with 22/24 tasks faster in either comparison. Resident-request speed is 1.742× ordinary but 1.035× matched. The target-only path change itself gives $R/M = 1.683\times$ request speed. Thus most of the measured deployment improvement is already available without a draft;




Figure 3: Qualification of phase scope and geometry. (A) All 16 masks at $k = 3$, UB4 and cap128 on four HumanEval probes, with two repetitions (128 requests). Filled squares enable constraints; circles indicate full-response matches and crosses failures. Passing masks are 3/7/11/15; mask 3 is inclusion-minimal within this four-switch family. (B) A separate 11-input panel changes k and UB jointly at caps128/256/512, using fresh scalar references and two repeats. MBPP/229 fails at UB6/8 while matched controls pass. Actual output length reaches at most 261; the earlier HE/18 target-only failure is outside this panel.

1.742× describes the complete change, whereas 1.035× is the speculative increment on the matched path.

Table 3: RTX frozen expansion paid ratios: 24 task medians, four repeats. Gen. denotes generation; Request denotes resident request. Intervals describe task resampling. C_3 is mask 3 speculation.

Ratio	Timer	Speed	95% interval
R/C_3	Gen.	1.170	[1.117,1.218]
R/C_3	Request	1.742	[1.655,1.827]
M/C_3	Gen.	1.169	[1.117,1.217]
M/C_3	Request	1.035	[1.005,1.063]
R/M	Gen.	1.001	[0.995,1.008]
R/M	Request	1.683	[1.590,1.766]

The identity in Equation 3 holds for all 48 task-timer cells and both aggregate timers. Generation R/M is near parity while request R/M is much larger. The target-path change affects prefill microbatch/attention behavior and continuation capacity jointly, and the timer boundaries differ. Their contrast cannot allocate a measured host, attention, KV or synchronization share. A faster qualified ordinary implementation could also narrow the deployment benefit: the registered R is an executed reference, not a proven fastest ordinary decoder.

6.2. *Task variation and session uncertainty*

Figure 5A,B shows all 24 tasks in the same request-sorted order and scale. Generation improves on 22/24 tasks, but request time improves on only 17/24. Seven tasks regress against matched execution, despite all 24 being faster than ordinary request cost. The average request gain therefore does not justify an unconditional per-task acceleration claim.

The within-round matched-request geometric means in Figure 5C are 1.029, 0.940, 1.052 and 1.044: round 2 reverses direction. These round summaries differ from the geometric mean formed after taking each task's four-repetition absolute-time medians. The descriptive task-bootstrap interval for that median-based aggregate lies above one, but does not remove the observed round reversal or estimate independent session/day uncertainty.

The operating point is qualified and positive in aggregate, with a small, uneven request increment. Separate resident sessions, laptop scheduling and thermal variation can affect that estimate; balanced order and task medians do not eliminate session confounding. The larger generation gain applies to its defined interval rather than replacing the request result. Independent session/day replication would be needed to assess stable deployment acceleration.

A separate serial resident-reset study checks whether the anchor preserves output when reused across requests. Two orders retain the registered reference after target-state reset, with matched generation/request speeds about 1.181 × /1.039×. This supports finite reset semantics for the original $k = 3$/UB4 recipe, without establishing concurrency, throughput or resident qualification of the widened draft. These rows are not pooled with the expansion.




Figure 4: Deployment gain and incremental draft benefit. (A) R is ordinary target-only execution, M the repaired target-only path, and C speculation on that path. (B,C) Geometric means of 24 task ratios formed from four-repetition absolute-time medians; bars show descriptive 95% task-bootstrap intervals. A ratio above one favors the denominator. Generation and resident-request timers use different intervals and axis ranges. Request ratios satisfy $R/C = (R/M)(M/C)$; this multiplication separates comparisons rather than component costs.

6.3. Fixed UB: wider drafting qualifies but becomes slower

The fixed-UB experiment tests the cost of widening a qualified draft. Unlike the joint k/UB geometry sweep, this experiment fixes UB4 and mask 3 while testing $k = 3, 5, 7$ on 24 now-exposed MBPP inputs and four exposed HumanEval probes. Each width qualifies in two repetitions. The highest passing width, $k = 7$, is then measured in a separate capture-off arm: four conditions, four repetitions and 448 formal requests. Qualification timings do not select the width by speed.

Relative to $k = 3$, $k = 7$ gives 0.829× generation and 0.890× request speed. Against matched target-only it gives 0.997 × /0.950×, whereas the anchor gives 1.203 × /1.068× in this campaign. Ordinary same-width speculation fails its output gate, so its timing cannot serve as qualified speed evidence. For these inputs and this configuration, the measured anchor is preferable to the wider qualified draft.

Caller reduction does not reduce all recorded work. Drafted tokens rise from 3,528 to 5,392, while accepted draft tokens rise from 2,772 to 3,192. Separate captured qualification sessions record target continuation caller counts falling from 305 to 199 but micrographs increasing from 305 to 397. These counts include their own warmups and forced synchronization; they cannot be divided into formal timing to create a component profile. Micrographs are not CUDA kernel launches, and no unique slowdown component is isolated.

At $k = 7$, matched generation/request speed is 0.953×/0.919× on 24 MBPP inputs and 1.308 × /1.164× on four HumanEval probes. Four exposed probes do not validate an online routing rule. Supplement §S4.3 retains these partitions and the longer-cap checks under their own timers and panels.

6.4. B570: repair improves an old path but loses to strong baselines

The B570 repair's formal four-condition matrix contains 119/120 payloads; old N1's first-round MBPP/400 record is missing after an infrastructure interruption. Its time remains unknown, without imputation or a scientific rerun. Ordinary R, matched M and candidate C each have 30 complete responses and 15 two-round task-median pairs. Old-N1 comparisons use 14 complete pairs.

The candidate fails the latency objective against both strong baselines (Table 4). Generation/whole-request speed is 0.283 × /0.201× against ordinary R and 0.286×/0.206× against matched target-only. Both baselines are faster in every available paired round. The target-only paths are close in cost, with $R/M = 0.989 \times /0.979\times$; the roughly fivefold candidate request cost is therefore not explained by the target-path consistency constraint alone.

Against the prior old-N1 frontend, the candidate improves generation/request speed by 3.993 × /2.634× over 14 pairs. That improvement is relative to a slow frontend and does not establish a benefit over ordinary deployment. MBPP/245 also reverses the old-path whole/host request comparison in round 2. Endpoint recovery and aggregate improvement do not guarantee improvement in every round.

The endpoint contract retains all online work. Candidate endpoint IDs total 1,150 while raw IDs total 1,176, with all 26




Figure 5: Variation behind the matched RTX benefit. (A,B) All 24 tasks share order and scale; ratios use four-repetition absolute-time medians. Generation improves on 22/24 and request time on 17/24. Filled circles denote faster speculation and open left triangles slower speculation, separately for each timer. Dashed lines mark parity; dotted lines mark task-median geometric means. (C) Geometric means within four request rounds, with reversal in round 2. Round summaries are not the task-median estimator or a session-level uncertainty interval.

Table 4: B570 paid baseline/candidate task-median ratios. n counts complete two-round task pairs: 15 for R/C, M/C and R/M, and 14 for old N1/C. Gen., Request and Host denote generation, whole request and host-observed time. The missing old-N1 task is not imputed; raw suffix work stays charged.

Ratio	n	Gen.	Request	Host
R/C	15	0.283	0.201	0.202
M/C	15	0.286	0.206	0.206
Old N1/C	14	3.993	2.634	2.633
R/M	15	0.989	0.979	0.979

suffix IDs charged. The records contain 888 drafted and 702 accepted tokens, and target/draft continuation caller-token totals of 1,332/1,362. These quantities describe different parts of the transaction; endpoint equality does not assert raw suffix equality. Removing witness readbacks, an extra context and handoff improves the frontend, but phase reservation, synchronization, drafting and rollback remain. Without a full component profile, the remaining bottleneck cannot be assigned uniquely. The paid decision is to reject this candidate for latency against R and M.

6.5. *Global serialization, control, and draft-side limits*

Global serialization can recover output while increasing cost. An earlier RTX arm qualifies 57/57 arrays on 19 exposed tasks but achieves 0.677× target-only speed, with descriptive interval [0.662, 0.692] and no task faster. Its synchronized post-prefill-to-slot-release timer includes instrumentation and logging. It is a separate negative operating point, not an earlier point on the expansion's server-generation curve; Supplement §S6.4 retains the host amendment and preceding V3 stop.

The prospective M4 control campaign has 60 tasks, three conditions, three repeats and 540 requests under a post-prefill contract. Always speculation and Guard each qualify 180/180 direct-ID comparisons. Target-only/Always speed is 1.347×, but the paired secondary Guard/Always latency ratio is 1.027, with descriptive interval [1.013, 1.044]: the measured guard is slower. A hindsight oracle choosing only target-only or Always offers about 0.069% further geometric-mean latency reduction. This narrow two-action opportunity does not bound intra-request policies; the primary and secondary statistical streams remain distinct (Supplement §S6.6).

On 358H, CPU/NPU drafting each qualifies 90 direct-ID comparisons but gives 0.734 × /0.352× speed. With measured target work and committed progress fixed, eliminating every other non-

negative cost yields prompt-estimator ceilings of 0.837×/0.845×. Even that idealization needs a uniform target-work reduction of at least 16.28%/15.52% to reach parity. Draft-only optimization cannot close this conditional budget; changing the target path or state interface requires new qualification and measurement. These are necessary budgets, not achieved optimizations or an impossibility result for NPUs (Supplement §S6.7). M4 and 358H inform separate design decisions and do not replicate the RTX repair.

7. Design Implications and Limits

7.1. Constrain the transaction where evidence warrants it

The diagnostic distinction guides control placement. A current-path effect motivates constraining verification geometry; a retained-state effect motivates preserving state formation or changing its interface; an interaction requires testing both. The RTX design applies target-phase attention constraints, whereas B570 binds a whole recipe within one context. These are distinct implementations informed by local observations, without a unique kernel diagnosis or an automatic selector.

Own-path shams validate restoration at the tested boundary; crosses reveal local dependence; complete registered-output checks qualify the candidate. B570's unchanged immediate decisions and changed continuation make the last step essential. Cost follows qualification: constraining fewer phases or accepting a wider draft can still fail the performance objective.

7.2. Use both paid baselines for operating decisions

The ordinary comparison answers whether the deployment change helps; the matched comparison answers whether adding a draft helps on the repaired path. RTX exposes a substantial draft-free target-path opportunity followed by a modest, uneven request increment. Both values are needed to choose an implementation. A faster qualified ordinary decoder could reduce the former, since the registered R is not a demonstrated optimum.

The measured RTX anchor is preferable to its slower qualified wider draft. For latency, reject the B570 recipe against both strong baselines and avoid adding the measured M4 guard on an assumed control benefit. The 358H conditional budget requires changes to target work or state interfaces beyond draft-only optimization. Each decision follows its own output and timer contract, rather than a pooled hardware ranking.

7.3. Scope of the evidence

The repair covers one Qwen3 target/draft family, finite panels and pinned runtime variants. RTX's project-unused panel consists of 24 selected MBPP inputs; unused refers to accessible project history, not training exposure. Changed geometry needs renewed qualification, as the failures demonstrate. No second-family result or preservation guarantee on arbitrary inputs is established.

Discrete agreement is weaker than numerical equivalence. The score/KV witnesses do not separate every reduction, precision, layout or scheduling effect, and shams cannot exhaust hidden backend state. Selected cuts and a four-switch family cannot establish universal minimality. Prior preservation methods were not implemented as same-contract baselines, so superiority over them remains untested.

Task medians and descriptive intervals leave session, thermal and infrastructure variation unresolved. The B570 old-N1 payload and some historical raw comparisons remain missing. Timer and historical energy domains differ; later direct-ID qualification cannot validate earlier text-based timing. The reproducible CPU checks cover included sources and exports, with original-host private-archive audits identified separately in Supplement §S7.

8. Conclusion

Preserving a fixed ordinary greedy output requires a runtime to account for retained state and current execution, then qualify the complete output under an explicit configuration. In the tested RTX implementation, a query-layout change during target prefill and continuation retains other batched work and qualifies a finite full-response panel. Natural crosses motivate that scope, while the complete phase matrix and wider-geometry failures bound it.

Measured cost determines whether the qualified design is useful. The RTX request speed is 1.742× ordinary execution; the draft-free target path already gives 1.683×, and speculation adds 1.035× relative to that matched path. The increment is uneven and reverses in one round. A wider qualified draft loses, B570 endpoint repair remains slower than strong baselines, and the auxiliary M4/358H cases constrain the value of added control and draft-only optimization. These findings support local diagnosis, configuration-specific qualification and measurement against both baselines. They do not establish repair beyond the tested Qwen3 family, superiority to external methods under the same contract, or stability across independent sessions.

Manuscript preparation and reproducibility

OpenAI ChatGPT/Codex was used to assist with restructuring and drafting text, source and bibliography checks, CPU analysis and plotting code, and the execution-architecture illustration. Quantitative figures are generated from the identified experimental exports, without generative replacement of observations. The author is responsible for the final manuscript.

Supplement §S7 documents the frozen exports, source bindings and CPU-only checks used to reconstruct the figures and arithmetic. These checks do not rerun model inference or reaudit the private raw archives. No public deposit of the complete author-review evidence package is asserted here.

References

[1] Y. Leviathan, M. Kalman, Y. Matias, Fast inference from transformers via speculative decoding, in: Proceedings of the 40th International Conference on Machine Learning, Vol. 202, PMLR, 2023, pp. 19274–19286, accessed 9 October 2026.
URL https://proceedings.mlr.press/v202/leviathan23a.html

[2] ggml-org llama.cpp contributors, llama.cpp [software], Releases b10809 and b10839; private study patches included in the author source package, b10809 released 4 September 2026; b10839 released 7 September 2026. Accessed 9 October 2026 (2026).
URL https://github.com/ggml-org/llama.cpp/releases/tag/b10839

[3] A. Yang, et al., Qwen3 technical report, arXiv preprint arXiv:2505.09388v1, accessed 9 October 2026 (2025). doi:10.48550/arXiv.2505.09388.
URL https://arxiv.org/abs/2505.09388v1

[4] H. He, Thinking Machines Lab, Defeating nondeterminism in llm inference, Thinking Machines Lab: Connectionism, accessed 9 October 2026 (2025). doi:10.64434/tml.20250910.
URL https://thinkingmachines.ai/blog/defeating-nondeterminism-in-llm-inference/

[5] R. Gond, A. K. Kamath, R. Ramjee, A. Panwar, LLM-42: Enabling determinism in LLM inference with verified speculation, arXiv preprint arXiv:2601.17768v2, accessed 9 October 2026 (2026). doi:10.48550/arXiv.2601.17768.
URL https://arxiv.org/abs/2601.17768v2

[6] A. B. Lorup, Stage-replay divergence follows the KV cache: Fixed-prefix precision controls and bidirectional cache transplantation, arXiv preprint arXiv:2607.28495v1, accessed 9 October 2026 (2026). doi:10.48550/arXiv.2607.28495.
URL https://arxiv.org/abs/2607.28495v1

[7] J. Qin, A. Du, D. Zhang, M. Lentz, D. Zhuo, Vosti: Specifying, implementing, and verifying deterministic llm inference, arXiv preprint arXiv:2609.38981v1, accessed 9 October 2026; arXiv reports DOI registration pending (2026). doi:10.48550/arXiv.2609.38981.
URL https://arxiv.org/abs/2609.38981v1

[8] K. Chu, Y. Zhou, W. Zhang, MarginGate: Sparse margin-triggered verification for batch-invariant LLM inference, arXiv preprint arXiv:2605.30218v1, accessed 9 October 2026 (2026). doi:10.48550/arXiv.2605.30218.
URL https://arxiv.org/abs/2605.30218v1

[9] P. Chordiya, Lossless but not free: An empirical anatomy of speculative decoding on consumer hardware, arXiv preprint arXiv:2607.17283v1, accessed 9 October 2026 (2026). doi:10.48550/arXiv.2607.17283.
URL https://arxiv.org/abs/2607.17283v1

[10] X. Liu, J. Yu, J. Park, I. Stoica, A. Cheung, Speculative decoding: Performance or illusion?, in: Proceedings of Machine Learning and Systems, Vol. 8, 2026, accessed 9 October 2026.
URL https://proceedings.mlsys.org/paper_files/paper/2026/hash/554e056fe2b6d9fd27ffcd3367ae1267-Abstract-Conference.html

[11] L. Zhang, Z. Zhang, B. Xu, R. Li, Z. Tian, S. Mei, D. Li, Dovetail: A CPU/GPU heterogeneous speculative decoding for LLM inference, arXiv preprint arXiv:2412.18934v2, accessed 9 October 2026 (2025). doi:10.48550/arXiv.2412.18934.
URL https://arxiv.org/abs/2412.18934v2

[12] K. Lv, H. Guo, Q. Guo, X. Qiu, DuoDecoding: Hardware-aware heterogeneous speculative decoding with dynamic multi-sequence drafting, arXiv preprint arXiv:2503.00784v1, accessed 9 October 2026 (2025). doi:10.48550/arXiv.2503.00784.
URL https://arxiv.org/abs/2503.00784v1

[13] X. Liu, J. Park, L. Hu, W. Kwon, Z. Li, C. Zhang, K. Du, X. Mo, K. You, A. Cheung, Z. Deng, I. Stoica, H. Zhang, TurboSpec: Closed-loop speculation control system for optimizing LLM serving goodput, arXiv preprint arXiv:2406.14066v3, accessed 9 October 2026 (2025). doi:10.48550/arXiv.2406.14066.
URL https://arxiv.org/abs/2406.14066v3

[14] Y. Hou, F. Zhang, C. Du, X. Zhang, J. Pan, T. Pang, C. Du, V. Tan, Z. Yang, BanditSpec: Adaptive speculative decoding via bandit algorithms, in: Proceedings of the 42nd International Conference on Machine Learning, Vol. 267, PMLR, 2025, pp. 24045–24079, accessed 9 October 2026.
URL https://proceedings.mlr.press/v267/hou25h.html

[15] S. Liu, Y. Ye, Q. Zhu, Z. Cao, Y. He, HeteroSpec: Leveraging contextual heterogeneity for efficient speculative decoding, in: Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), Association for Computational Linguistics, 2026, pp. 12930–12947, accessed 9 October 2026. doi:10.18653/v1/2026.acl-long.589.
URL https://aclanthology.org/2026.acl-long.589/

[16] M. Chen, J. Tworek, H. Jun, Q. Yuan, H. Ponde de Oliveira Pinto, J. Kaplan, H. Edwards, Y. Burda, N. Joseph, G. Brockman, A. Ray, R. Puri, G. Krueger, M. Petrov, H. Khlaaf, G. Sastry, P. Mishkin, B. Chan, S. Gray, N. Ryder, M. Pavlov, A. Power, L. Kaiser, M. Bavarian, C. Winter, P. Tillet, F. Petroski Such, D. Cummings, M. Plappert, F. Chantzis, E. Barnes, A. Herbert-Voss, W. Hebgen Guss, A. Nichol, A. Paino, N. Tezak, J. Tang, I. Babuschkin, S. Balaji, S. Jain, W. Saunders, C. Hesse, A. N. Carr, J. Leike, J. Achiam, V. Misra, E. Morikawa, A. Radford, M. Knight, M. Brundage, M. Murati, K. Mayer, P. Welinder, B. McGrew, D. Amodei, S. McCandlish, I. Sutskever, W. Zaremba, Evaluating large language models trained on code, arXiv preprint arXiv:2107.03374v2, accessed 9 October 2026 (2021). doi:10.48550/arXiv.2107.03374.
URL https://arxiv.org/abs/2107.03374v2

[17] J. Austin, A. Odena, M. Nye, M. Bosma, H. Michalewski, D. Dohan, E. Jiang, C. Cai, M. Terry, Q. Le, C. Sutton, Program synthesis with large language models, arXiv preprint arXiv:2108.07732v1, accessed 9 October 2026 (2021). doi:10.48550/arXiv.2108.07732.
URL https://arxiv.org/abs/2108.07732v1

[18] H. Xia, Z. Yang, Q. Dong, P. Wang, Y. Li, T. Ge, T. Liu, W. Li, Z. Sui, Unlocking efficiency in large language model inference: A comprehensive survey of speculative decoding, in: Findings of the Association for Computational Linguistics: ACL 2024, Association for Computational Linguistics, 2024, pp. 7655–7671, accessed 9 October 2026. doi:10.18653/v1/2024.findings-acl.456.
URL https://aclanthology.org/2024.findings-acl.456/

Supplementary Material

The supplemental evidence for manuscript v0.14.5 covers output contracts, implementation boundaries, campaign-level results, negative findings, historical measurements and missing observations. Task panels and timer conventions remain distinct. The author source package reproduces figures and arithmetic from committed exports without model inference. Verification covers inspected sources and exports, with inherited original-host raw audits identified separately. Sections S1–S7 are numbered independently of the main manuscript.

Contents

S1 Study Units, Contracts, and Frozen Sources 13

S2 Diagnosis: Predictions, Interventions, and Natural Crosses 14
- S2.1 Prediction closes a different question from reference recovery . . . 14
- S2.2 Controlled prefill and continuation interventions 14
- S2.3 Same-state block and continuation comparison on B570 . . . 14
- S2.4 Natural donor-state × current-recipe crosses . . 15
- S2.5 Bridge and offline selection limits . . . 15

S3 Implementation and Phase Qualification 15
- S3.1 RTX query layout and dispatch . . . 15
- S3.2 Factorial and scope-cost results . . . 15
- S3.3 Implementation variants and paid-boundary changes . . . 16

S4 RTX Expansion, Statistics, Width, and Reset 16
- S4.1 Complete expansion and two timer boundaries . 16
- S4.2 Geometry failures and their natural-state check 16
- S4.3 Fixed UB4 and width costs . . . 17
- S4.4 Resident reset as a finite serial check . . . 17

S5 B570 Repair, Missingness, Suffixes, and Paid Costs 17
- S5.1 Earlier finite closeout: a positive local case and failures . . . 17
- S5.2 Same-context phase binding . . . 18
- S5.3 Qualification counts and unresolved raw comparisons . . . 18
- S5.4 All measured timers and work . . . 18

S6 Historical Costs, Stops, Control, and Target-Work Budgets 19
- S6.1 Early four-system inventory and unchanged estimators . . . 19
- S6.2 Target-forward proxies and energy boundaries . 20
- S6.3 Fresh direct-ID gates and independent latency arm 21
- S6.4 V3 stop, V4 recovery, and protocol amendment 21
- S6.5 RTX efficiency screening . . . 22
- S6.6 M4 formal control and oracle opportunity . . . 22
- S6.7 358H state interface, threshold gate, and conditional budgets . . . 23

S7 CPU Reconstruction, Provenance, and Access Limits 23

S1. Study Units, Contracts, and Frozen Sources

The principal campaigns use different study units (Table S1). The author source package's complete experiment-destination ledger assigns every inherited group to the main text, this supplement, or a preserved historical record, with exact repository entries. Discovery, engineering qualification, formal output checks, auxiliary crosses and capture-off costs are different evidence classes. Their counts are not added to create an independent sample size.

For diagnosis, Section S2 contains predictions, controlled interventions and donor-state crosses. RTX graph and phase qualification are in Section S3; the expanded R/M/C comparisons, per-task medians, width failures and reset checks are in Section S4. B570's missing payload, endpoint/raw distinctions and paid suffix work are in Section S5. Section S6 retains historical estimators, stops and energy domains, with M4 control in Section S6.6 and 358H state/cost budgets in Section S6.7. Section S7 distinguishes this revision's CPU checks from inherited raw audits.

The late RTX target/draft pair is Qwen3-8B/0.6B Q8_0, with full CUDA offload, flash attention off, one slot, context 4096, caller batch capacity 2048, 24 threads and greedy seed 123. The ordinary reference is mask 0/UB1. Matched target-only and the anchor use mask 3/UB4, with the anchor's $k = 3$. The expansion starts from a frozen private server and CUDA libraries. Four separate resident processes per round each receive one excluded warmup and 24 formal requests. Condition order and task order rotate. Zero actual cache reuse is recorded; the final-slot `tokens_cached` field is not a cache-hit measure.

In the late cost tables, R denotes the executed ordinary reference, M the matched repaired target-only path, and C the speculative candidate. RTX C_3 and C_{15} use masks 3 and 15; B570 old N1 is a separate earlier frontend. A baseline/candidate ratio above one favors the candidate. These labels do not pool unlike campaigns or timers.

The 24 expansion inputs are unused in the accessible experiment inventory at selection. An unused HumanEval pool is unavailable at that stage; the amendment selecting MBPP is recorded before new outputs. Of 224 eligible MBPP inputs, 24 are frozen. This exposure audit establishes neither absence of training contamination nor a random population sample. The width and post-hoc ordinary analyses subsequently reuse those exposed inputs.

RTX qualification compares every generated response ID and its EOG/cap128 termination metadata. B570 comparison selects the first inclusive EOG or cap128 endpoint from actual committed IDs; raw post-endpoint suffixes are retained. Historical parsed-text agreement re-tokenizes text and is weaker. M4 formal runtime and 358H Phase 3 use their own direct generated-ID contracts. A later strict-ID pass does not retrospectively qualify historical timings. Token equality is neither functional code correctness nor bitwise logit/KV equality.

The source package includes authenticated copies of selected implementation patches and original reports alongside compact

Table S1: Campaign units and distinct roles. Panels overlap unless described as project-unused at their own freeze.

Campaign	Units	Role
RTX continuation intervention	43 tasks, three repeats, two recipes	Predictions/native outputs; repairs and regressions
RTX natural crosses	Four probes; 24 donors, 48 forks, 24 shams	Selected aligned boundaries; auxiliary costs excluded
B570 block/continuation study	24 tasks, 72 runs, 195 events	Immediate and downstream effects
RTX phase factorial	16 masks, four probes, two repeats	128 qualification requests
RTX scope cost	19 exposed tasks; three conditions, six repeats	342 formal requests, 18 excluded warmups
RTX input expansion	24 project-unused MBPP tasks; four conditions, four repeats	384 formal requests, 16 excluded warmups
RTX fixed-UB width	28 exposed tasks; three widths, two repeats	168 qualification requests; separate 448-request cost arm
B570 natural crosses	Three tasks, six repeated contexts, 12 shams	State × whole recipe; 24 auxiliary cells
B570 expanded cost	15 project-unused tasks, four conditions, two rounds	119/120 payloads; 15 or 14 complete pairs
M4 formal runtime	60 tasks, three conditions, three repeats	540 formal requests; direct-ID gate
358H closed Phase 3	30 tasks, three repeats per draft device	90 direct-ID pairs per path

exports. Full private raw archives and external model/runtime assets are referenced rather than included. Local verification operates on those exports without inference; version and inheritance receipts remain in the author package (Section S7).

S2. Diagnosis: Predictions, Interventions, and Natural Crosses

S2.1. Prediction closes a different question from reference recovery

The B570 target-partition predictor is frozen after 36/36 discovery comparisons. On 24 reserved HumanEval tasks, three repeats give 72/72 predictor/native complete endpoint agreements, while reference/native agreement is only 60/72. All four reference-divergent classifications and first-divergence indices reproduce. They are HumanEval/134 at index 88 (914 to 1946), /42 at 73 (432 to 1817), /145 at 103 (1184 to 686), and /138 at 93 (14374 to 9064). H1 passes its gate; H2 is not built in that B570 study. Prediction matches native behavior while the reference disagreement remains.

The RTX H1 transfer uses 12 discovery tasks with three repeats and reaches 24/36 against a 36/36 gate. It stops before any reserved inference; H2 is not implemented in that study. A later independently frozen proposal-replay study evaluates 24 reserved tasks. H2/native and a fresh draft-free R-only replay each reach 72/72; ordinary reference/native reaches 60/72. The replay explains complete native output under its numerical routines, but does not establish a cheaper qualified online correction. Its separately orchestrated workers share pinned routines with the native implementation; they are not an independent numerical implementation.

RTX V4 has 19 HumanEval tasks, with P/R and R-only/native each 57/57. Ordinary target-only UB2/native and UB1 reference/native each reach 51/57. The same task panel is used for fresh timing, not a newly untouched cohort. Section S6 records the host-policy amendment and preceding V3 termination separately.

S2.2. Controlled prefill and continuation interventions

B570 changes target prefill UB1 to UB128, while target continuation and draft stay UB1. The protocol also samples and accepts the first pending token and transfers KV, logits, logical positions and a post-accept sampler clone. Both baseline and intervention predictions match native execution 72/72. Reference agreement improves from 60/72 to 72/72: four exposed failures repair and 20 stable controls remain equal. This intervention does not isolate a pure prefill operator or KV-only cause.

RTX changes target continuation UB2 to UB1, leaving prefill, draft UB2, $k = 2$ and caller grouping fixed. Across 19 HumanEval and 24 statically selected MBPP tasks, both predictors match their native paths in all 129 comparisons per recipe. Reference agreement stays 117/129. HumanEval/15 repairs, /25 regresses and /18 remains divergent, giving 51/57 before and after. MBPP/304 and /463 remain divergent, giving 66/72 before and after. MBPP/304's 47-ID output changes at zero-based index 33 from 488 to 481. The equal aggregate success counts conceal task-level repairs and regressions.

Unchanged-capacity shams test handoff at the same boundary. Historical global-UB1 also changed prefill/draft and effectively used 12 native threads; this controlled intervention explicitly uses 24. Its G0 qualification includes 75 newly checked native arrays at 24 threads and 45 unchanged worker arrays reused. It is not 120 new native 24-thread measurements. These differences prevent an argument that this intervention alone establishes universal phase necessity.

S2.3. Same-state block and continuation comparison on B570

The sampled-fork study uses the 24 reserved tasks, three repeats and a frozen boundary at the first eligible verification

block after at least 64 committed IDs. Two paths start from the same retained donor state and process the registered block. Scores differ in all 72 runs, while immediate top-1 and decision outcomes remain equal across all 195 internal decision events. Downstream output changes in 18 runs from six tasks. The alternate continuation retains later UB128 blocks, with proposals evolving under its accepted history; the secondary result does not isolate one altered block followed by restoration. Immediate agreement cannot stand in for complete trajectory agreement. Runs and decision events are not independent additional tasks; the raw verifier results cited here are inherited original-host results, not a new private-payload audit.

S2.4. Natural donor-state × current-recipe crosses

The RTX experiment uses four selected probes, three repetitions and two naturally formed donors at aligned committed boundaries. Each donor is forked under both current recipes, and own-path shams reproduce uninterrupted output. There are 24 donors, 48 forks and 24 shams. Target-only auxiliary replay is diagnostic rather than paid deployment performance.

For HumanEval/15, the shared committed cut is 13. At the third auxiliary decision, the two donor rows are identical: $[9147, 4199]$ under current UB2/UB1. Each full three-ID auxiliary array begins $[6256, 5987]$, followed by the displayed ID. At this cut, the observed decision follows current recipe. HumanEval/25 shares four committed IDs and its first-decision matrix is $[[1406, 1406], [1406, 271]]$. The bottom-right three-ID array is $[271, 750, 8168]$, whereas the other cells begin with 1406. This supports an interaction at the selected boundary. HumanEval/18 and /31 are local nulls under the measured crosses. Logical prompt KV matches in 12/12 donor comparisons, while generated-region KV differs in 70/72 layer-side comparisons; the first layer matches. Tensor inequality alone does not identify a unique kernel. The 1,278 recorded auxiliary forwards are not latency measurements.

B570's later natural crosses use six repeated contexts over three tasks, with 12 own-path shams. HumanEval/145 gives $[[71465, 279], [279, 279]]$ and /42 gives $[[432, 1817], [1817, 1817]]$: both support a local interaction between state and recipe. MBPP/72 gives $[[320, 320], [308, 308]]$, supporting a state effect; its current columns are deliberately identical (UB1, reservation 3). The two HumanEval recipes change both microbatch and output reservation, so this is a whole-recipe cross rather than an isolated UB factor. Recorded target score-array difference counts are 3,987,448, 5,218,133 and 6,072,820 across the three cases. Opaque sampler/RNG bytes are not independently available; the greedy contract, clone history and shams bound the claim. The later crosses do not retroactively become experiments in the earlier B570 closeout.

S2.5. Bridge and offline selection limits

The ordinary target-only U2 bridge compares 19 exposed tasks, three recipes and three repetitions: 171 fresh arrays. U2 reproduces intervention N1 at 57/57 complete arrays and strict boundaries, while both match ordinary reference on 17/19 tasks. U2 uses one occupied continuation token despite UB2 capacity. This simpler reproducer limits claims that the complex replay frontend is necessary; equal output does not imply equal numerical state.

The offline selector feasibility study compares existing evidence acquisition and decision rules. RTX direct enumeration and proxy acquisition each require 114 equivalents and abstain under the measured criterion. B570 direct enumeration uses 72 while the proxy uses 144. These equivalents are not measured latency. Unobserved MBPP U2 counterfactuals remain unknown. The feasibility study is complete and negative; it produces no validated automatic online selector.

S3. Implementation and Phase Qualification

S3.1. RTX query layout and dispatch

The source-bound implementation modifies the non-flash attention graph, not the quantized projection/FFN kernels or the greedy acceptance algorithm. After the standard query permutation, a query tensor with dimensions $(d, q, h, 1)$ is viewed as $(d, 1, h, q)$. KV tensors broadcast over the query batch dimension. The corresponding mask is viewed with the matching layout; existing matrix multiplication, softmax, value multiplication and recombination operations then evaluate each query column with the registered geometry. Batched projection, FFN and output computation remain available. This shape description is about graph operations, not independently traced CUDA kernel dispatch.

Assertions restrict the tested graph to Qwen3 non-flash attention, one KV stream and supported query widths, without attention bias, sinks or MLA. The initial patch supports up to four queries; the width study extends the admitted graph to eight. Unsupported cases do not inherit qualification. The earlier implementation creates per-query attention subgraphs before the later query-batch transformation; their costs differ.

The four-switch patch records model role and phase through a thread-local guard entered before graph capture/fast-path selection. Target prefill and continuation have bits 1 and 2; draft prefill and continuation have bits 4 and 8. The process mask selects enabled phases. A disabled phase returns to the native graph. The graph parameters and reuse check include the query-batch flag, preventing reuse across differing constraint modes. Reset re-enters prefill. The switches therefore select the graph during execution. Capture-off bypasses observer metadata and forced witness synchronization. The optional continuation state-move helper is inactive in the frozen expansion because its activating environment variable is absent.

The exact scripts, native delta and reports are included under `source_records/benchmarks/rtx_consistency_contract_v1` and `rtx_consistency_phase2`. The author source package records their Git blob and SHA-256 identities. The portable manuscript code does not apply patches or execute these runtimes.

S3.2. Factorial and scope-cost results

All 16 phase masks are run on HumanEval/15, /18, /25 and /31 twice. The task-level booleans in the original A1 result agree

with the committed 16-row aggregate export. Passing masks are 3, 7, 11 and 15; all repeat stably. Masks contain target prefill and continuation when they pass. HumanEval/15 and /31 pass throughout this family; /25 needs at least one target bit; /18 needs both. The main manuscript's phase-qualification matrix shows every mask and probe.

Mask 3 is inclusion-minimal among passing masks in this fixed four-switch family: no strict subset passes. The finite search establishes neither a universal phase requirement nor the necessity of each bit on every input, and it does not cover all possible constraints. Natural crosses identify local dependencies; the factorial qualifies implementations under a different complete-output gate.

The independent scope-cost arm uses 19 exposed tasks, three conditions and six balanced repeats: 342 formal requests and 18 excluded warmups, capture off. Mask 3 speculation versus matched target-only gives generation/request speed 1.278076 × /1.112977×. Mask 15 versus mask 3 cost gives 1.003569 × /1.025686×, with 12/19 generation and 17/19 request tasks faster. The extra generation interval is [0.997739, 1.009456]. Per-round generation ratios are 1.008646, 0.998091, 1.004328, 1.003691, 1.007860 and 1.006777. The predefined optimization gate also requires generation speed at least 1.03, request speed at least 1.00 and at least four of six faster rounds. It is not met because the aggregate generation gain is too small. Qualification does not imply a speed gain from fewer constraints.

S3.3. Implementation variants and paid-boundary changes

Table S2 retains the early local implementation comparisons. Their baselines and observer costs differ from the final frozen expansion. Request gains against global UB1 include a prefill/path change; they are not matched speculative increments. The strict final local comparison disables observers and matches target graph, UB4 and prefill, giving 1.256449× generation and 1.077451× request over 19 task medians, with 19/19 and 16/19 tasks faster. All observations are from that campaign, not paired with later costs.

The ordinary $k = 3$ path in the second campaign qualifies only 68/76, with /18 and /25 failing in every repeat. Its timing cannot become a lossless speed claim. Serial, per-query and query-batch comparisons preserve both successful and unsuccessful cost outcomes.

S4. RTX Expansion, Statistics, Width, and Reset

S4.1. Complete expansion and two timer boundaries

The expansion contains exactly 384 complete unique formal keys: 24 tasks, four conditions and four repeats. All four conditions qualify 96/96 full responses; ordinary reference is stable in all repeats. Lengths range from 11 to 128 IDs; 23 tasks stop at EOG and one at cap128. No extra full-stream suffix is present in the selected response records. This does not certify any unrecorded internal sampling stream.

The retained server generation field is `predicted_ms`: the interval from its prompt/first-sample boundary to the last generation update, with the source's minimum one-microsecond floor. It charges draft and target work within the interval, excludes initial prefill and first sampling, and may exclude final bookkeeping. Resident-request time is client wall time for complete non-streaming response receipt and parsing. Model load, process startup, excluded warmups, boundary telemetry and shutdown are outside it; post-response asynchronous cleanup is not certified inside it. Neither timer is a component profile. Subtraction of generation from request does not identify a host, KV or attention cost.

For each condition/task, take the median of four absolute times, form baseline/candidate ratios, then their unweighted geometric mean across tasks. Table S3 reports all 12 timer comparisons. The ordinary-reference comparisons are post-hoc CPU analyses of already paid, qualified observations. They are not new measurements or a new preregistered primary campaign. The mathematical identity $R/C = (R/M)(M/C)$ holds for 48 task-timer cells and both aggregate timers; it is not an additive cost decomposition.

The primary descriptive CPU bootstrap uses NumPy Generator PCG64, seed 20261008, 10,000 task resamples of 24 indices in saved task order, and one shared index matrix for comparisons. Percentiles use linear/type-7 interpolation. The historical interval convention uses Python `random.Random.choices`, seed 20261005, 4,000 draws and sorted indices 99/3899. The author source package retains both conventions without replacing one with the other. No bootstrap treats repetitions or conditions as additional independent inputs.

Tables S4 and S5 give all absolute medians and primary ratios. The seven matched-request regressions are listed explicitly beneath the latter. Four matched-request round geometric means are retained; round 2 is 0.940220×. Task resampling cannot remove that observed reversal or estimate independent day/session uncertainty.

S4.2. Geometry failures and their natural-state check

The wider-geometry boundary arm uses 11 exposed tasks, (k, UB) pairs $(1, 2), (3, 4), (5, 6), (7, 8)$, caps 128/256/512, three modes and two repetitions: 792 formal requests and 24 excluded warmups. MBPP/229 fails at $k = 5$/UB6 and $k = 7$/UB8 across all caps and repeats, 12 failures. Ordinary and matched wider target-only controls pass this task. The earlier HumanEval/18 wide failure remains a separate boundary outside this panel. Maximum actual output length is 261, so cap512 is not evidence of 512 generated positions on every task.

At a shared 47-ID prefix for MBPP/229, naturally formed ordinary and constrained donors are crossed with current UB6 layouts. Four own-path shams over two caps pass. The donor state changes whether EOG is selected under both current layouts; current geometry changes scores without independently flipping this observed decision. EOG-minus-alternative margins are $[-0.09283, -0.62923]$ for one donor and $[0.99707, 1.48868]$ for the other. They are selected-alternative margins, not true top-two margins. Maximum measured score differences are approximately 0.44920 and 0.38070. This is a local same-prefix witness, not a complete counterfactual suffix, a unique kernel identification or a new independent task for each cap.

Table S2: Earlier RTX implementation variants. Ratios are baseline/candidate under each stated campaign.

Candidate; comparison baseline	ID gate	Generation	Request
Global serial $k = 2$; global UB1 target	57/57	0.677	0.795
Per-query $k = 2$; global UB1 target	57/57	0.746	1.041
Per-query $k = 3$; new frontend global UB1	76/76	1.084	1.562
Query-batch $k = 3$; new frontend global UB1	76/76	1.242	1.852
Query-batch $k = 3$; strict matched target	76/76	1.256	1.077

Table S3: All RTX expansion comparisons, baseline/candidate. Each uses 24 task medians; C_3/C_{15} are mask 3/15 speculation.

Ratio	Timer	Speed	Descriptive interval	Faster
R/C_3	Gen.	1.170124	[1.117013,1.217681]	22/24
M/C_3	Gen.	1.169238	[1.117115,1.217153]	22/24
R/M	Gen.	1.000758	[0.995290,1.007752]	11/24
R/C_{15}	Gen.	1.152348	[1.099880,1.199192]	22/24
M/C_{15}	Gen.	1.151475	[1.099968,1.198554]	22/24
C_{15}/C_3	Gen.	1.015426	[1.007525,1.024253]	20/24
R/C_3	Request	1.741569	[1.654608,1.827079]	24/24
M/C_3	Request	1.035071	[1.004552,1.063481]	17/24
R/M	Request	1.682560	[1.589801,1.766329]	24/24
R/C_{15}	Request	1.690202	[1.610916,1.768226]	24/24
M/C_{15}	Request	1.004542	[0.975846,1.031662]	12/24
C_{15}/C_3	Request	1.030391	[1.022464,1.038939]	23/24

S4.3. Fixed UB4 and width costs

Holding mask 3 and UB4 fixed, $k = 3, 5, 7$ each qualifies 56/56 requests on 28 exposed tasks in two repeats. The widest passing $k = 7$ is selected from qualification alone, followed by a separate capture-off cost arm with four conditions, four repetitions, 448 requests and 16 excluded warmups. Table S6 retains pooled and saved MBPP/HumanEval partitions. The ordinary wider speculative condition fails qualification and has no admissible speed result.

Formal draft/accepted counts are 3,528/2,772 at $k = 3$ and 5,392/3,192 at $k = 7$. Separate captured qualification counts give 305/232/199 target caller calls for $k = 3/5/7$, but 305/463/397 micrographs. They include their own warmups and witness synchronization and are not a kernel-launch profile or a denominator for the formal timing. Long-cap fixed-UB checks remain qualified, with matched speed about $1.0001\times$ /$0.9649\times$ at cap256 and $0.9715\times$ /$0.9340\times$ at cap512. The caps, timers and small exposed task panels remain distinct from the expansion.

S4.4. Resident reset as a finite serial check

The resident D study contains 100 reset/capture requests including four warmups, and a separate 96-request cost arm with four excluded warmups. Two task orders retain reference output for the anchor recipe. Matched generation/request speed is approximately $1.1812\times$ /$1.0385\times$. This serial resident-loop check covers reset semantics, without establishing concurrent scheduling, throughput, multi-slot behavior or resident qualification of the widened draft.

S5. B570 Repair, Missingness, Suffixes, and Paid Costs

S5.1. Earlier finite closeout: a positive local case and failures

The earlier B570 closeout's normative audit establishes completion of 1,456 core records (`COMPLETE_FINITE_SCOPE_AUDITED`). The completed audit supersedes historical report wording that normative closure was incomplete. The original findings remain finite: on the shared 24-task MBPP panel, the repaired old N1 qualifies but gives only $0.188525\times$ /$0.179055\times$ generation/request speed against ordinary R, and $0.804023\times$ /$0.693541\times$ against matched target-only. The old N0/N1 comparison is $0.999522\times$ /$1.247059\times$: request progress against N0 does not imply ordinary-reference benefit.

On eight project-unused MBPP inputs, N1 and its matched path fail MBPP/72 in all four repeats. Five UB2 alternatives retain failures involving HumanEval/42, /145 or /138 and receive a NO-GO decision. The local $k = 3$/UB4/cap128 candidate on seven exposed longer probes is a positive finite case, with $1.345798\times$ generation and $1.048339\times$ request speed. It does not replace the failed expanded qualification. Long-cap anchor qualification passes 84/84 at caps256/512, with longest actual response 261 IDs. No natural state cross occurs in this earlier study; the crosses in Section S2 are later experiments.

A wrongly placed UHD730 campaign of 190 requests is classified as infrastructure evidence and excluded from scientific B570 data. Its records and recovery remain preserved. Recovery does not authorize outcome-dependent retuning or replacement of failed tasks. The later phase-binding candidate is a distinct implementation.

Table S4: RTX generation absolute task medians (ms) and ratios. MBPP task IDs follow the saved order.

Task	R ms	M ms	C_3 ms	R/C_3	M/C_3
439	590.217	553.925	516.623	1.142453	1.072203
415	2870.787	2805.883	2469.301	1.162591	1.136307
124	408.370	416.421	495.281	0.824523	0.840778
234	276.411	279.562	243.149	1.136797	1.149754
441	347.456	350.851	258.048	1.346478	1.359637
229	1106.948	1104.535	823.986	1.343408	1.340479
12	458.673	453.639	368.023	1.246319	1.232641
458	273.815	275.552	243.791	1.123157	1.130278
299	454.850	457.803	386.201	1.177755	1.185404
443	1084.726	1079.483	898.341	1.207477	1.201642
18	588.585	588.574	535.248	1.099649	1.099629
93	253.047	253.966	200.438	1.262473	1.267058
437	296.111	295.709	248.526	1.191467	1.189851
230	341.034	344.760	255.338	1.335622	1.350213
253	478.293	476.294	367.254	1.302351	1.296908
436	431.820	432.591	325.377	1.327139	1.329507
115	431.379	433.787	402.353	1.072139	1.078124
133	475.426	478.179	421.431	1.128124	1.134655
448	1609.686	1615.810	1311.434	1.227425	1.232094
274	1023.130	1019.728	895.225	1.142875	1.139076
454	274.751	273.346	246.048	1.116658	1.110950
393	386.363	387.622	395.548	0.976780	0.979963
242	229.418	233.043	192.592	1.191210	1.210035
397	478.100	476.432	415.627	1.150309	1.146296

S5.2. Same-context phase binding

The B570 candidate preserves one live target context and sampler. Ordinary-reference prefill uses UB128 with caller output reservation 512/per-sequence reservation 1; the frontend samples the pending first token once, binds continuation UB1 and synchronizes/reserves the scheduler, and consumes and accepts that saved token once in the native loop. Native $k = 2$, draft-UB1 proposal, acceptance, bonus and rollback follow. The private API patch changes phase parameters and reservation within the context; it adds no model arithmetic, Vulkan shader or precision change. It has no task-ID routing, known reference token, margin-based correction or extra reference forward.

Unlike old N1, it removes a second target context, state handoff and three serialized witness readbacks. Capture-on checks compare KV before and after binding; capture-off avoids witness readback. Those checks do not supply a separate profile of the saved cost. The frontend still pays for synchronization, phase reservation, draft work, target work and reconciliation. The author source package includes `phase.h`, `target.cpp`, `native.cpp` and the private-library delta with source bindings.

Figure S1 connects the phase-binding operations to the separate endpoint and paid-work contracts; it also shows why the old-N1 comparison has one fewer complete task pair.

S5.3. Qualification counts and unresolved raw comparisons

Table S7 reports endpoint and raw-array comparisons separately. The 48 baseline-development rows have only 32 ordinary-reference-equal endpoints; they are not all qualified candidate evidence. The 12 shams are separate from the 299 rows in the qualification export. Stage D contains 56 exposed tasks evaluated twice. Stage E combines eight bridge records and 119 formal records; their roles are not interchangeable.

The four-condition formal matrix is 119/120. The missing unit is `E/FORMAL/1/old_N1/MBPP/400`, with `INFRASTRUCTURE_INTERRUPTION_NO_PAYLOAD`. Its runtime cost and interrupted teardown time remain unknown. Each of ordinary R, matched M and candidate C has 30 complete formal observations and 15 complete two-round task pairs. Old N1 has 29 observations and only 14 complete task pairs. The available MBPP/400 old-N1 round is retained but cannot supply its two-round median. There is no interpolation, zero-cost assumption, silent task removal from other comparisons or scientific rerun. The study's administrative closeout remains `PARTIAL_INFRASTRUCTURE_BUDGET_CLOSED`.

S5.4. All measured timers and work

Generation time is the frontend's registered C++ interval, including pending-state initialization, sampler/batch operations, phase binding within that interval, draft/verification, rollback and final synchronization. Whole-request time also includes prefill/reset/cleanup, excluding subsequent disk file writes. Host request time is separately measured by Windows QPC. Earlier A/B stage GetTickCount's 15.625-ms granularity is not substituted for formal C/D/E QPC measurements. Model-load cost is outside these comparisons.

Table S5: RTX request absolute task medians (ms) and ratios. MBPP task IDs follow the saved order.

Task	R ms	M ms	C_3 ms	R/C_3	M/C_3
439	1337.685	804.939	825.507	1.620439	0.975084
415	3638.915	3056.087	2802.469	1.298468	1.090498
124	1087.418	650.070	779.296	1.395385	0.834176
234	971.130	521.843	519.011	1.871115	1.005455
441	1054.836	587.618	541.248	1.948898	1.085673
229	2389.621	1502.739	1305.581	1.830312	1.151012
12	1261.199	714.779	684.524	1.842448	1.044200
458	952.067	520.996	524.541	1.815049	0.993242
299	1190.416	693.830	659.236	1.805751	1.052475
443	1823.804	1324.677	1197.541	1.522958	1.106164
18	1392.036	851.751	824.704	1.687921	1.032796
93	1029.573	512.864	491.369	2.095314	1.043744
437	975.759	524.353	528.602	1.845923	0.991962
230	1254.875	639.720	590.859	2.123815	1.082695
253	1239.853	730.717	654.826	1.893408	1.115894
436	1132.163	660.519	597.764	1.893997	1.104983
115	1189.749	684.664	697.826	1.704936	0.981139
133	1270.639	732.764	714.316	1.778819	1.025826
448	2319.676	1846.448	1578.762	1.469300	1.169555
274	1876.304	1296.957	1220.322	1.537548	1.062799
454	953.416	509.887	523.471	1.821334	0.974050
393	1064.315	627.877	666.169	1.597667	0.942519
242	954.557	478.594	466.815	2.044832	1.025233
397	1163.200	708.823	701.044	1.659239	1.011096

Matched-request regressions: MBPP/439, MBPP/124, MBPP/458, MBPP/437, MBPP/115, MBPP/454, MBPP/393. Round GMs: 1.028699, 0.940220, 1.051749, 1.044236.

The main manuscript's B570 paid-cost table reports all three formal timer aggregates. Table S8 provides all paired task generation and whole-request ratios. R/C and M/C are below one on every complete task and round. Old-N1/C whole and host request ratios reverse on MBPP/245 in round 2, approximately 0.873582 and 0.873603; aggregate old-path improvement therefore does not imply universal improvement.

Candidate formal endpoint IDs total 1,150 and raw IDs 1,176. All 26 suffix IDs are charged. Drafted/accepted IDs total 888/702, and target/draft continuation caller tokens 1,332/1,362. These denominators describe different runtime quantities and cannot be collapsed into one acceptance-adjusted cost. The narrowed target common-sampling measurement of 851.52 ms omits other work; it is not a full component profile. The known complete-campaign host subtotal is approximately 6,541.86 s, excluding the unknown interruption/teardown. It is not the cost of every planned request or a normalized per-task speed estimator.

S6. Historical Costs, Stops, Control, and Target-Work Budgets

S6.1. Early four-system inventory and unchanged estimators

The historical inventory uses MacBook Air M4/Metal (llama.cpp b10809), Core Ultra 9 275HX plus RTX 5070 Ti Laptop/CUDA (b10839), Core i5-13400 plus Arc B570/Vulkan0 (b10839), and Core Ultra X7 358H plus Arc B390/Vulkan0 with an OpenVINO draft. Qwen3-8B Q8_0 is the target. Draft is Qwen3-0.6B Q8_0 except the symmetric INT4 OpenVINO adapter. Hardware, OS, backend, placement and frontend vary jointly. The inventory is not a hardware-only comparison or a common energy/latency ranking.

Table S9 reports the completed historical campaigns. M4's representative 24Q and separately preregistered HumanEval30 have opposite measured outcomes in distinct sessions. This does not identify a workload-only cause. Early MLX precision/correctness failures are separate from the final Q8_0 Metal configuration. RTX historical CPU-to-GPU and same-GPU controls retain different integration costs. B570's formal failure triggers its stop; a later six-prompt serial text probe passes 18/18, whereas its full 30-prompt serial text comparison reaches only 60/90. Remote-interaction-contaminated diagnostic observations are excluded from the final cells. Legacy "exact" labels do not upgrade the text contract.

Historical M4 24Q takes a within-prompt GM of three paired ratios, then resamples prompts 10,000 times with Python Random seed 20260907 and sorted draw indices 249/9749. M4 HumanEval uses the same within-prompt aggregation but 100,000 draws, seed 20260910 and indices 2500/97499. Historical RTX uses 10,000 draws, seed 20260910, indices 249/9749. B570 fall-

Table S6: Fixed-UB4 width costs: baseline/candidate. Anchor is $k = 3$, wide is $k = 7$, and matched has no draft. Partitions are descriptive.

Panel	Ratio	Generation	Request
All (28)	Anchor/Wide	0.829442	0.889868
All (28)	Matched/Wide	0.997404	0.950353
All (28)	Matched/Anchor	1.202501	1.067970
MBPP (24)	Anchor/Wide	0.805961	0.872693
MBPP (24)	Matched/Wide	0.953392	0.918750
HE (4)	Anchor/Wide	0.985408	1.000258
HE (4)	Matched/Wide	1.307590	1.164148




Figure S1: B570 implementation and accounting boundaries. (A) Ordinary prefill, one pending sample, in-place phase binding and the native loop retain one target context and live sampler; this is a source-bound schematic, not a timing profile. Reservation values are total/per sequence. (B) The endpoint gate retains IDs through the first inclusive EOG or cap128, while all online suffix work remains paid. The counts aggregate 30 formal candidate responses. (C) Available payloads and complete two-round task pairs remain distinct; the missing old-N1 MBPP/400 round-1 payload is unavailable, not zero cost.

back uses 10,000 draws, seed 20260910 and indices 250/9750 in archived insertion order. Sorting tasks changes its finite-seed endpoints and is not substituted. 358H uses prompt medians of three paired ratios, 10,000 draws, NumPy default_rng seed 20260919 and .025/.975 quantiles. These policies are not replaced by late RTX's ratio-of-medians estimator.

S6.2. Target-forward proxies and energy boundaries

The historical target-only proxy is

$$V_k^{\text{micro}}(n, e) = T_{\text{target forward}}(k, n, e)/T_{\text{target decode}}(1, n).$$

It omits drafting and can omit correction/bonus, state work and complete target-round bookkeeping. Table S10 retains every context cell. Their ranges span contexts rather than uncertainty intervals. The historical RTX HumanEval/106 diagnostic repeats a same-position argmax change from 2790 to 2629 three times, with a separately instrumented same-commit margin moving from +0.080948 to −0.126457. It is shape-sensitive evidence in that configuration, not a unique kernel cause or a formal timing observation.

M4 HumanEval energy measures the Silemetry CPU+GPU+ANE package aggregate, excluding separate DRAM. Fixed-$k = 2$ package efficiency is 1.013× with interval $[0.990, 1.034]$, so improvement is not established. The registered secondary $p_{\min} = 0.9$ condition has 1.041× $[1.018, 1.065]$, without replacing the primary or establishing material added speed. The corrected synthetic ceiling was registered but not executed; earlier synthetic diagnostics are not a substitute.

RTX board and CPU-package sensors are distinct domains, and follow-up process windows include loading; no formal serial HumanEval energy comparison is claimed. B570 fallback measures adapter-board efficiency 0.302× $[0.285, 0.320]$, without CPU package or wall power, and its output failure confines the result to diagnosis. 358H has no qualified end-to-end energy boundary. No late runtime repair energy, common system-energy

Table S7: B570 candidate qualification stages and raw comparison limits. Equality is to the registered endpoint reference unless stated otherwise.

Stage	Candidate checks	Endpoint equal	Raw reference comparison
C development	12	12	Four equal, eight different
D exposed bridge	112	112	MBPP: 16 equal/48 different; 48 HumanEval raw comparisons unknown
E candidate formal	30	30	Included in the E total below; suffix cost retained
E all available plus bridge	127	127	80 equal, 47 different

Table S8: All B570 two-round task-median speed ratios. G/W denote generation/whole request; old N1 has no complete pair for MBPP/400.

MBPP	R/C G	R/C W	M/C G	M/C W	N1/C G	N1/C W
125	0.320296	0.270051	0.319891	0.243047	2.437945	1.908679
130	0.299904	0.252594	0.304551	0.257891	2.269168	1.978931
132	0.264679	0.162455	0.271252	0.169635	8.515349	4.089033
245	0.298694	0.254655	0.298448	0.255268	1.541642	1.376354
278	0.270026	0.205714	0.271973	0.245382	3.078819	2.321202
312	0.257757	0.195314	0.259093	0.198785	4.282380	2.984986
400	0.265906	0.153521	0.269833	0.158972	–	–
429	0.276956	0.197973	0.281509	0.203527	3.441493	2.411608
435	0.260099	0.151096	0.266645	0.158111	6.873734	3.323427
446	0.305206	0.233673	0.306943	0.272100	2.479117	1.929448
451	0.273297	0.193117	0.276409	0.198226	4.774253	3.079460
470	0.281105	0.243139	0.284055	0.199636	4.389394	2.870175
475	0.276814	0.196772	0.278850	0.201003	5.011890	3.193580
479	0.310439	0.196746	0.312663	0.200719	5.061865	2.965935
69	0.286855	0.163151	0.292541	0.169808	8.776569	4.056630

ranking or concurrent-throughput result is inferred.

S6.3. Fresh direct-ID gates and independent latency arm

Fresh RTX direct-ID v2 has 270 executions on 30 HumanEval tasks, three conditions and three repeats. Batched $k = 2$ reaches 75/90 (25/30 wholly equal prompts) and is blocked; serialized reaches 90/90 and qualifies. Mismatching first indices are /64:114, /106:65, /119:17, /128:41 and /129:21, stable across repeats. All conditions repeat stably. The initial v1 transport study retains 83 executions, 82 valid, and no qualification result: full-log UTF-8 decoding fails on a partial draft fragment after native exit zero. V2 changes observational byte transport and restarts the whole frozen schedule; it imports no v1 formal pairs. The final report stored at the repository's v1 path is a copy of the completed v2 report; it does not document v1 completion.

B570's separate fresh direct-ID campaign also completes 270 executions: fast reaches 60/90 (20/30 prompts), serialized 78/90 (26/30), and both are blocked. Historical fast 45/90 and serial 60/90 are unchanged text-path counts. An initial metadata decoding launch fails before inference with zero formal executions; authorized direct execution of the unchanged frozen runner produces the full campaign. No formal speed is inferred from operational elapsed fields. Neither new gate retroactively qualifies old timings.

The independent RTX matched-latency arm has 180 fresh timing observations and 90/90 fresh complete-ID agreements on 30 tasks. Serialized speed is 0.645816×, interval $[0.629802, 0.659884]$, zero of 30 faster. Condition order uses seed 2026093001; the 10,000 prompt-bootstrap draws use seed 2026093002 and linear percentiles. Native QPC timing starts after synchronized target/draft prefill and covers per-request sampler/state work, drafting, verification, acceptance/correction/bonus, rollback, synchronization, logging/response and slot release. Load and teardown are excluded. Chrono shares the host oscillator; it is not an independent physical clock. The empty-hook probe bounds clock-call overhead, not all logging overhead. The fresh frontend is compiled with Clang 21.1.0 over retained CUDA libraries; OS build 26300 differs from the earlier direct-ID OS26200. These facts preclude synthetic pairing with prior qualification.

S6.4. V3 stop, V4 recovery, and protocol amendment

V3 plans 576 formal condition/repetition rows over 24 tasks. It delivers 126 valid prefix rows: 72 pre-live and 54 cost, with two failures and 448 unreached rows. Native HumanEval/59 emits 128 committed IDs ending at EOG and reports both limit and EOS. The frozen parser accepts only one marker and stops. Exit zero is not sufficient to make capture valid. A-live receives zero formal runs; complete formal accuracy, speed and interval are unavailable. Engineering qualification's 400 runs and parser-negative fixtures do not repair the missing formal endpoint branch. Old failures remain sealed.

V4 fixes that observational endpoint handling under a new freeze, accepting the ordered complete EOS-at-cap case while rejecting contradictory, reversed, duplicate or missing markers. Its 19-task panel initially comprises the remaining project-unused

Table S9: Historical latency outcomes under their original contracts. Intervals are descriptive and source-specific. Text agreement is not a direct-ID certificate.

Campaign	Speed	Interval	Agreement
M4 representative 24Q	0.842	[0.809,0.877]	72/72 text
M4 HumanEval30	1.387	[1.351,1.422]	90/90 text
RTX CPU draft, HumanEval30	0.404	[0.390,0.418]	90/90 text
RTX same-GPU draft, HumanEval30	0.650	[0.629,0.673]	90/90 text
B570 serialized fallback	0.3087	[0.2927,0.3246]	60/90 text
358H CPU stateful, HumanEval30	0.733915	[0.692920,0.771090]	90/90 IDs
358H NPU stateful, HumanEval30	0.351663	[0.332595,0.368949]	90/90 IDs

Table S10: Frozen target-forward proxy lookup. These are neither complete target-round cost nor integrated speed. Historical text agreement applies only under each original comparator.

Path	Context	V_2^{micro}
M4 Metal	512	1.022182
M4 Metal	2048	1.076126
M4 Metal	8192	1.032264
RTX batched	0	1.009030
RTX batched	256	0.983148
RTX serialized	0	2.430996
RTX serialized	256	2.137011
B570 fast	512	1.242576
B570 fast	2048	1.637295
B570 serialized	512	1.982668
B570 serialized	2048	1.991707

HumanEval inputs; subsequent reuse is exposed. It retains 228 pre-live predictor records and adds 57 native live and 171 fresh timing observations: 456 complete formal condition rows. Prediction closure is described in Section S2. The cost arm uses one timer executable and balanced order, each condition appearing in each order position 19 times. Batched qualification remains 51/57 and has no admissible speed/interval. Global serialization qualifies 57/57 but yields 0.677351× [0.661653, 0.691812], zero of 19 faster. Median task absolute times are 1.607 s target and 2.332 s serial; their ratio is not the paired GM. The interval uses 10,000 paired-row draws, seed 2026100204 and linear quantiles.

The V4 numerical sources and assets remain frozen, but a fan-curve change triggers the original strict host-hash stop before live outcomes. Authorized continuation preserves the original `PROVENANCE_INVALID` records, repeated predictor checks and the amendment. Fan/lighting differences become permitted; non-fan material settings remain strict. Predictor data are reused, not relabeled as a fresh untouched cohort. Fan controls stay fixed during the fresh timing arm, with snapshots retained, but can still affect latency. The campaign completed under the disclosed amendment; the original no-deviation host policy did not pass. Instrumented post-prefill-to-slot-release time is distinct from the later server generation field and cannot form a common optimization curve.

S6.5. RTX efficiency screening

The early FA-on/UB512 four-probe pilot qualifies small-model $k = 2$ and $k = 4$, with request/generation speeds 1.277×/1.324× and 1.492×/1.572×. Each FA/UB setting has its own ordinary reference; global UB changes several phases. Expansion to HumanEval/0–7 preserves every failure: final small-model $k = 2$ qualifies 18/24, fragment drafting 21/24 and the mixed strategy 15/24. A mixed result producing 18 rather than the reference 87 IDs is invalid as a speed claim. $k = 2$ repairs /5 but introduces /2; /6 remains divergent. The campaign has 300 formal requests and 48 excluded warmups. Synthetic favorable cases do not support the current headline.

S6.6. M4 formal control and oracle opportunity

The M4 Guard measures cumulative charged generation time per committed ID, including seed/correction/bonus and excluding rejected proposals. It starts on Always speculation and can fall back permanently after a completed round, reconciling invalid target/draft suffixes first. Calibration freezes target cost per ID and selects `E8_M000` from a nine-candidate grid with rounds $\{2, 4, 8\}$ and margins $\{0, 0.05, 0.10\}$. Exactness and calibration regret select the rule; ties use frozen overhead/exploration/margin/ID rules. Disjoint calibration, qualification and held-out task IDs prevent held-out retuning. Online decisions receive no future length, task family, request-specific target latency or oracle answer.

The registered post-prefill clock includes generation initialization, seed sampling, draft/target work, synchronization, reconciliation, control and transition. Load, sampler/speculator setup, initial prefill and the speculative begin hook precede it. This is not whole HTTP request latency. The formal campaign has 60 held-out tasks, 30 each HumanEval and Spec-Bench, three conditions and three repeats. Always and Guard each qualify 180/180 IDs. Table S11 gives their original overall and family estimates.

The primary 10,000-draw bootstrap uses Python Random seed 20260924 in held-out order, with one continued stream for target/Guard, target/Always and Guard/oracle. The paired Guard/Always secondary replay starts a fresh stream of the same seed and uses linear percentiles; it gives latency 1.027076 [1.012956, 1.043559], with Guard faster on 24 and Always on 36 tasks. It is post-study, not the original preregistered endpoint. A separate family-stratified sensitivity uses seed 2026100101, 10,000 draws and HumanEval-then-Spec-Bench order, giving [1.0135, 1.0423]; it leaves the original intervals unchanged.

The per-task two-fixed-mode oracle improves the measured interval by factor 1.0006919671 relative to Always. The implied latency reduction is $1 - 1/1.0006919671 = 0.0006914886$,

Table S11: M4 formal post-prefill baseline/candidate speeds from three-repeat condition medians. Family strata are descriptive.

Panel	Tasks	Target/Always	Target/Guard
Overall	60	1.346894	1.311387
HumanEval	30	1.570011	1.554690
Spec-Bench	30	1.155485	1.106160

approximately 0.069149%. Only Spec-Bench/559 and /95 favor target-only: target times are 11.9085 and 10.9203 s; Always/target latencies 1.0270 and 1.0150; Guard/target 1.0215 and 1.0029. This finite hindsight opportunity is not a bound on all intra-request policies.

A loop-variable shadowing defect records a build-manifest digest in the intended calibration-freeze field. Recovery verifies the actual freeze, source/model/calibration/policy hashes and formal-start links, retaining error markers and the original pipeline `STOPPED` metadata. It does not retune the policy or mutate measurements. Recorded Git order is not a trusted external timestamp. The resolved metadata defect does not change the formal experiment's completion status.

S6.7. 358H state interface, threshold gate, and conditional budgets

The 358H stateful runner is complete; the preceding preflight scaffold was empty and blocked. It keeps the target's low-level context between rounds and charges validation, rejected-suffix rollback, correction/bonus and synchronization within complete target work. Every OpenVINO proposal call receives the full committed prefix. The synchronous region combines replay/reconstruction and proposal, with no separate measurements of those terms.

A prior proxy threshold study passes 18 direct-ID sanity pairs and admits borderline context points, using a favorable zero residual T_x, fixed progress assumptions and seed 20260919, 10,000 empirical draws. It predicts eligibility, not achieved integrated speed. CPU central/optimistic speeds at contexts512/2048/8192 are 0.903680/1.355520, 0.884843/1.327264 and 0.755946/1.133919. NPU values are 0.905553/1.358329, 0.903804/1.355706 and 0.839618/1.259427. The subsequent actual stateful CPU/NPU speeds in Table S9 are lower and qualified, with zero of 30 prompts faster on either path.

Table S12 retains measured progress, components and distinct ceiling estimators. Both paths commit 11,520 IDs, over 4,677 CPU and 4,686 NPU rounds. Arithmetic-total accounting gives normalized $(D, R, X) = (0.4304, 2.9767, 0.00124)$ CPU and $(4.1251, 2.9435, 0.00130)$ NPU. These values reproduce total-time ratios, not prompt GMs. Target-only ceilings assume unchanged baseline, target work and progress with all other nonnegative cost removed.

Let B_{ij} be matched target-only time and T_{ij} measured complete target work for prompt i and repetition j. If optimized speculative time retains this target work and only reduces the other nonnegative costs, its speed S'_{ij} is at most B_{ij}/T_{ij}. Monotonicity of the median and geometric mean then gives the bound under the original prompt estimator:

$$\mathrm{GM}_i \,\mathrm{median}_j\, S'_{ij} \le \mathrm{GM}_i \,\mathrm{median}_j(B_{ij}/T_{ij}). \tag{S1}$$

For a uniform fractional reduction δ in target work, the corresponding zero-other-work ceiling increases by $1/(1-\delta)$. If its original value is $F < 1$, parity therefore requires $\delta \ge 1 - F$. Table S12 reports this necessary budget separately for the prompt and pooled-total estimators. It assumes fixed baseline and committed progress; changing either requires fresh qualification and measurement.

Figure S2 places the measured prompt-estimator speeds beside their conditional ceilings and the necessary target-work cuts. The pooled-total estimator remains separate in Table S12.

No prompt-median ceiling reaches parity; maximum prompt ceilings are 0.9736196764 CPU and 0.9999089575 NPU. One NPU repetition has $B/T = 1.000163695$, so not every individual run-level ceiling is below one. The budgets are necessary arithmetic reductions under fixed progress, not achieved optimizations or proof against NPUs. A persistent-state/wider-target candidate stops at qualification: CPU restore/reconcile correctness is unavailable under the tested representation, and the frozen dynamic-shape NPU IR lacks the required state-capable path. Same-prefix target-only and proposal-replay diagnostics identify greedy divergence but not a unique rollback bug. No formal runtime performance or energy result exists for that failed candidate; the completed earlier Phase-3 costs remain valid under their own contract.

S7. CPU Reconstruction, Provenance, and Access Limits

The complete author-review source package contains editable LaTeX, vector PDF/SVG figures, bibliography, Highlights, CPU verification and build scripts, selected authenticated implementation/report records, the 26-claim evidence map and the 28-group experiment ledger. In that archive, compile `main.tex` or `supplement.tex`; the separate public arXiv source package compiles `arxiv.tex`. All use pdfLaTeX and the supplied assets. The build scripts recheck frozen exports. The figures express categorical relationships and consistent comparison roles while retaining the bound observations, numerical values and intervals. Two supplementary figures explain the bound B570 source/exports and 358H saved estimates/budgets. The double-column supplement includes every inherited table cell and result. Structured and flat source archives are separately rebuilt; compilation does not establish live Overleaf or Editorial Manager acceptance.

The verifiers authenticate the copied-source bindings and reconstruct the RTX 384-row matrix, response-ID digest joins, qualification flags, absolute-time medians, all 12 cost comparisons, descriptive intervals, task regressions, round reversal and ratio identities. They reconstruct B570's 119 formal rows, 15 versus 14 complete task pairs, three timers and paid suffix counts.




Figure S2: 358H measured speed and a conditional optimization budget. (A) Filled circles and bars show the saved speed estimates and descriptive prompt-bootstrap intervals; open diamonds show arithmetic ceilings if all other nonnegative work were removed while baseline, target work and committed progress stayed fixed. All points use the original geometric mean of 30 prompt medians of three paired ratios. Ceiling markers have no confidence intervals. (B) Reaching parity in that optimistic case requires a uniform target-work cut of at least $1 - F$, where F is the original ceiling. These are necessary budgets, not achieved savings or an impossibility claim about NPUs. The 180-row original-host ceiling audit remains inherited.

Table S12: 358H measured accounting and conditional zero-other-work ceilings. Percentages describe the saved synchronous regions; prompt and pooled estimators remain distinct.

Quantity	CPU draft	NPU draft
Committed IDs per round	2.463117	2.458387
Replay plus proposal share (%)	12.6273	58.3474
Complete target-work share (%)	87.3365	41.6342
Residual share (%)	0.0363	0.0184
Actual pooled-total speed	0.7227	0.3477
Pooled-total ceiling	0.8274529834	0.8351858524
Prompt-estimator ceiling	0.8372192092	0.8448401086
Necessary uniform target cut, prompt (%)	16.278079	15.515989
Necessary uniform target cut, pooled (%)	17.254702	16.481415

Phase booleans, natural-cross matrices, fixed-UB task-ratio aggregates and M4 medians/oracle are also checked. Version-specific receipts identify the source, figure, PDF and archive hashes actually checked; earlier receipts retain their historical attribution.

These checks operate on included sources and compact exports. The original runtime reports retain original-host audits, external-asset hashes and references to larger private archives. Those audits are inherited evidence: the current checks neither reopen every raw payload nor rehash omitted model/driver binaries, validate independent absolute timing or rerun inference. Reproducing a summary or task-ratio export is not a complete raw-data audit. The missing B570 payload, interruption cost and unknown historical raw comparisons remain unresolved.

Dataset and software descriptions are cited in the main manuscript [16, 17, 18, 2, 3]. Bibliographic versions and pending metadata checks are documented in the author records. The public arXiv source package contains the manuscript dependencies; it does not include the complete evidence exports or private archives. Permanent public data/software access is not established by these local checks. A second model family, same-contract external method comparisons, stochastic sampling and concurrent throughput are outside the completed evidence scope.