

dispatcher.h

[Go to the documentation of this file.](#)

```
1  #ifndef DISPATCHER_H
2  #define DISPATCHER_H
3
4  #include <QMutex>
5  #include <QThread>
6  #include <QQueue>
7  #include <QStringList>
8
9  class Dispatcher : public QThread
10 {
11     Q_OBJECT
12
13 public:
14     Dispatcher(int twait=1000, QObject *parent = 0);
15     void run(); //!< Run the message dispatcher thread
16     void addMessage(const QString &, const QString &); //!< Add a message to the
    dispatcher queue
17     int numPending(); //!< Return the number of message waiting in the
    dispatcher queue
18     QString current(); //!< Return the most recently dispatched message
19     void setCadence(const int &); //!< Set the dispatch cadence in milliseconds
20     int cadence(); //!< Return the dispatch cadence in milliseconds
21     QStringList queueList(); //!< Return the contents of the dispatcher queue as
    a QStringList
22
23 public slots:
24     void abort(); //!< Abort and clear the dispatcher queue
25
26 signals:
27     void dispatch(const QString &, const QString &); //!< Message ready to dispatch
28     void error(const QString &); //!< Error message to emit
29     void queueChanged(); //!< The queue has changed (new entries, or
    queue advanced)
30
31 private:
32     QMutex mutex; //!< Mutex for the dispatcher thread
33     QQueue<QString> msgQueue; //!< Message queue
34     QString currentMsg; //!< The current message
35     bool abortQueue; //!< Dispatcher abort flag (false=keep going,
    true=abort and clear)
36     int dispatchCadence; //!< Message dispatch cadence (time to wait between
    dispatches) in msec
37 };
38
39 #endif
```