

# HetPipe: Enabling Large DNN Training on (Whimpy) Heterogeneous GPU Clusters through Integration of Pipelined Model Parallelism and Data Parallelism

USENIX ATC 2020

Jay H. Park, Gyeongchan Yun, Chang M. Yi, Nguyen T. Nguyen,  
Seungmin Lee, Jaesik Choi<sup>†</sup>, Sam H. Noh, and **Young-ri Choi**

**UNIST**

ULSAN NATIONAL INSTITUTE OF  
SCIENCE AND TECHNOLOGY


<sup>†</sup> **KAIST**

# Contents

- **Motivation & Background**
- **HetPipe in a Nutshell**
- **Our System: HetPipe**
- **Evaluation**
- **Conclusion**

## Motivation


- DNN (Deep Neural Network) models continue to grow



- Need more powerful GPUs for training!

## Motivation


- Short release cycle of new GPU architectures



*Whimpy GPUs*


- Use of heterogeneous GPUs is inevitable!
- What to do with *whimpy* GPUs?

# DNN Training




**Minibatch  $i$**   
**(Training Data)**

Forward Pass  $i$



Weight Parameter  $w$


Backward Pass  $i$



$$w_{i+1} = w_i - \eta \cdot u_i$$


# Parallelizing DNN Training

## ■ Data parallelism (DP)



- GPU memory limitation

## ■ Model parallelism (MP)




- Low GPU utilization

# Parallelizing DNN Training

## ■ Attempts to improve MP utilization

- Pipelined model parallelism (PMP)

- PipeDream [SOSP'19]
- GPipe [NIPS'19]




- Designed for homogeneous GPUs
- Designed for a single PMP worker







# Challenges in integration PMP+DP in Heterogeneous GPUs



- What weight version should be used by each VW to synchronize with other VWs?

- How do we reduce virtual worker stragglers when we consider DP?

⋮

**Many more in the paper**

## HetPipe Contributions

### **Enable Large DNN Training on Heterogeneous GPUs**

Aggregate heterogeneous resources  
Reduce the straggler problem

### **Integrates PMP + DP**

Novel parameter synchronization model  
WSP (Wave Synchronous Parallel)

### **Proof of WSP Convergence**

# HetPipe Workflow

## Cluster Configuration



### Resource Allocator

Assign  $k$  GPUs to each virtual worker

## DNN Model

### Model Partitioner

Divide model into  $k$  partitions



# HetPipe Workflow

## Cluster Configuration



### Resource Allocator

Assign  $k$  GPUs to each virtual worker

### DNN Model

### Model Partitioner

Divide model into  $k$  partitions




# Outline

- Motivation & Background
- HetPipe in a Nutshell
- **Our System: HetPipe**
  - **Pipelined Model Parallelism Within a VW**
  - Data Parallelism with Multiple VWs
- Evaluation
- Conclusion

# Pipelined Model Parallelism Within a VW

## Execution of a virtual worker



$N_m$  minibatches processed concurrently in pipeline manner

$W_{bcal}$


$W_{bcal}$  is a consistent version of weights within a VW






# Pipelined Model Parallelism Within a VW

- Local staleness ( $S_{bcal}$ ): maximum missing updates



# Pipelined Model Parallelism Within a VW

- Local staleness ( $S_{bcal}$ ): maximum missing updates




# Outline

- Motivation & Background
- HetPipe in a Nutshell
- **Our System: HetPipe**
  - Pipelined Model Parallelism Within a VW
  - **Data Parallelism with Multiple VWs**
- Evaluation
- Conclusion


## Data Parallelism with Multiple VWs

**Wave:** Sequence of concurrently executing  $N_m$  minibatches



## Data Parallelism with Multiple VWs

- ***Push* occurs every clock**



## Blocked minibatch 8

*Push* aggregated updates of wave0 ( $\tilde{u}$ )

$$\tilde{u} = u_1 + u_2 + u_3 + u_4$$

$$\mathbf{w}_{gbbal} \leftarrow \mathbf{w}_{gbbal} + \tilde{\mathbf{u}}$$


## Parameter Server: $w_{gbbal}$



## Data Parallelism with Multiple VWs

- Pull** occurs intermittently - Depending on user defined *clock distance*  $D$ 
  - If  $D = 0$  *pull* occurs every clock


VW1 waits before *pull*  
until VW2 *pushes*



Parameter Server:  $w_{gbbal}$

## Data Parallelism with Multiple VWs

- Pull** occurs intermittently - Depending on user defined *clock distance*  $D$



If  $D = 0$


VW1 waits before *pull*  
until VW2 *pushes*

VW2 *Push* aggregated updates ( $\tilde{u}$ )

$$w_{gbbal} \leftarrow w_{gbbal} + \tilde{u}$$

## Data Parallelism with Multiple VWs

- Pull** occurs intermittently - Depending on user defined *clock distance*  $D$



*If  $D = 0$*


*Pull* occurs  
after all VWs have been pushed

$$w_{bcal} \leftarrow w_{gbbal}$$

Parameter Server:  $w_{gbbal}$

## Data Parallelism with Multiple VWs


- Pull** occurs intermittently - Depending on user defined *clock distance*  $D$



Parameter Server:  $w_{gbbal}$

# Data Parallelism with Multiple VWs


- Local staleness ( $S_{bcal}$ ) and global staleness ( $S_{gbbal}$ ) with WSP



$$W_{gbbal} = W_0 + (u_1 + u_2 + u_3 + u_4)_{vw1, vw2}$$

## Data Parallelism with Multiple VWs

- Local staleness ( $S_{bcal}$ ) and global staleness ( $S_{gbbal}$ ) with WSP



Parameter Server:  $w_{gbbal}$




# Outline

- Motivation & Background
- HetPipe in a Nutshell
- Our System: HetPipe
- **Evaluation**
  - **Setup**
  - **Resource Allocation for Virtual Workers**
  - **Results**
- Conclusion

# Evaluation Setup

## Cluster setup - 4 heterogeneous GPU nodes




## Two DNN models

	ResNet-152	VGG-19
Dataset, minibatch size	ImageNet, 32	
Model parameter size	230 MB	548 MB
Characteristic	Large activation output	Large parameter size

## Resource Allocation for Virtual Workers: NP, ED, HD


### ■ NP (Node Partition)



- Minimum communication overhead within VW
- Performance of each virtual worker varies
- Straggler may degrade performance with DP

## Resource Allocation for Virtual Workers: NP, ED, HD



### ■ ED (Equal Distribution)



- Performance will be the same across the VWs
- Mitigates the straggler problem
- High communication overhead within each VW

## Resource Allocation for Virtual Workers: NP, ED, HD

### ■ HD (Hybrid Distribution)




- Mitigates the straggler problem
- Reduces communication overhead within each VW

# Parameter Placement

- Round-robin policy (default)
  - Can be used in all three policies: **NP**, **ED**, and **HD**

Parameters of each layer:

Example: ED






# Parameter Placement


- Local placement policy

- ED-local

Parameters of each layer:



- Significantly reduces communication overhead



- Parameter communication occurs


# Compare Throughput with Horovod

## ■ Baseline Horovod


- State-of-the-art DP using AllReduce



- For ResNet-152, the whole model is too large to be loaded into a single **G** type GPU (batch size = 32)




ResNet-152



VGG-19

- ED: reduces the straggler problem
- ED-local: significantly reduces communication overhead

# Performance Improvement of Adding Whimpy GPUs




■ Single GPU ■ Horovod ■ HetPipe

- With additional GPUs, HetPipe achieves up to 2.3X speed up
- Additional whimpy systems allow for faster training



# Convergence Results

## ■ ResNet-152




- HetPipe reduces straggler problem in heterogeneous environment

- Adding four more whimpy *G* GPUs, performance improves even more





# Convergence Results

## VGG-19



- HetPipe (D=0) is 29% faster than Horovod

- Higher global staleness (i.e., 32) can degrade convergence performance



## Conclusion

- HetPipe makes it possible to efficiently **train large DNN models with heterogeneous GPUs**
- **Integrate pipelined model parallelism with data parallelism**
- Propose a novel parameter synchronization model: **WSP**
- DNN models converge up to **49% faster with HetPipe**

**Thank you!**

