Dulux Gold Superior Anti-formaldehyde High Opacity Emulsion Paint H8607

Product Description	**Dulux Gold Superior Anti-formaldehyde High Opacity Emulsion Paint** has been upgraded with its formulation, especially on the improvement of the opacity & matt level, making the product very easy to apply & let you deliver the results more efficiently. It has also been upgraded with using the 'Colour Lock' technology which ensures long-lasting colours. The product is odourless & with its natural bamboo charcoal ingredient & anti-formaldehyde formulation, which effectively purifies the indoor air, making the indoor air fresh & healthy. Its anti-bacterial technology helps to kill up to 99.99% of germs and bacteria to create a healthy home environment. The product also provides all-round protection for interior walls, such as water-proof, washable & covering hair-line cracks. With the superior mould-resistance function, it has been tested and proven for fighting common mould in Hong Kong.
Typical Uses	For use on new or previously painted interior masonry surface such as brickwork, plaster, cement and rendering.
Finish	Matt
Advantages	• Odourless & anti-formaldehyde • 99.99% anti-bacterial • Excellent mould-resistance • 'Colour Lock' technology to ensure long-lasting colours • High opacity & super white formulation • Very matt level • Strong water-resistance • Super washability • Smooth paint film • Good leveling • Covers hairline cracks • Good adhesion
Pack Size	1L & 5L
Colour Range	Standard colours CP5 colours
Composition *(Nominal)*	Pigment : Non-lead pigment Binder : Acrylate Copolymer Emulsion Solvent : Water Additives
Volume Solids	White (41%), will be varied after tinting.
Drying Time ***- Touch dry*** ***- Recoat***	Single coat at standard thickness (25°C, 50% R.H.) 0.5-1 hour 2-3 hours Drying times will vary depending on temperature and humidity
Wet Film Thickness	80 um
Dry Film Thickness	33 um
Storage	Always store in a cool (0-40°C) and dry place. Avoid rain and sun exposure and freezing (not below 0°C).
Theoretical Coverage	Theoretically 1 litre of this product can cover 13-16 sqm in 1 coat. Coverage will vary considerably depending on application methods and surface roughness & porosity.
Application	
Thinning	Thin up to 20% (volume ratio) depend on different application methods & temperature. Do not over thin by adding more than 30% (volume ratio) water.
- Brush or Roller	For sealing new or bare surfaces thin with up to 1 part of clean water to 5-10 parts of paint (10-20% volume ratio)
- Conventional Spray	Add up to 1 part clean water to 5 parts of paint (20% volume ratio)
- Airless Spray	Ready for use
Cleaning Up	Clean all equipment with clean water immediately after use
Surface Preparation	Surfaces must be thoroughly clean, dry and free from all loose dirt, chalk or powder. New surfaces such as plaster and concrete should be fully dry before painting, with moisture content less than 14% and pH value below 10. Bare wood and metal surfaces should be primed in the usual way.
- New Wall	1. Fresh concrete must cure at least 30 days and meet application requirement before plastering 2. The plaster must not be too soft. Sand and dust off after dry. 3. To resist alkalis and to obtain best results first apply 1 coat of **Dulux Eco-sense All in 1 Primer (A931-65834)**

Dulux Gold Superior Anti-formaldehyde High Opacity Emulsion Paint H8607

- Previously Painted Surface

1. Remove powdery or flaking paint by scraping followed by using a suitable abrasive paper and dusting off
2. Fill the defects with proper filler
3. To seal powdery surfaces and to obtain best results first apply 1 coat of **Dulux Eco-sense All in 1 Primer (A931-65834)**

- Fungus Growth Wall

1. Remove all fungus by scraping followed by using a suitable abrasive paper and dusting off
2. Wash the surface with appropriate fungus washing. Rinse with clean water and wait till dry.
3. To obtain best results first apply 1 coat of **Dulux Eco-sense All in 1 Primer (A931-65834)**

Notes For Use

1. Read the application instruction thoroughly before use
2. Stir well before use
3. Thin with clean water when necessary. Do not over dilute.
4. Do not hold too much paint on paint brush or roller
5. Do not pour the diluted paint back to the original pack
6. Recommend to use up opened paint quickly
7. Suggest closing the window and turn on the dehumidifier when encounters the high humidity or larger temperature difference situation

Typical Painting System

SURFACE	SYSTEM
Normal, Sound Surfaces	Primer: Dulux Eco-sense All in 1 Primer (A931-65834) (1 coat) Finish: Dulux Gold Superior Anti-formaldehyde High Opacity Emulsion Paint H8607 (2 coats)

Application Precautions

- Do not sand the final coat of paint. If sanding is done on the first coat of finish, ensure that the second coat of finish is applied evenly over the first.
- Apply above 10°C (surface temperature) in dry condition. Do not apply when R.H. is 85% or above.
- When applying deep or bright colour, please control the dilution ratio within 5%. You will need to apply more coats than normal for opacity.

Safety, Health and Environmental Information

- Keep container tightly close and out of the reach of children
- A suitable cartridge mask should be worn when rubbing down
- Ensure good ventilation during application and drying
- Do not breathe vapour/spray
- In case of insufficient ventilation during spraying wear suitable respiratory equipment. All respiratory equipment must meet an appropriate approved standard.
- Keep away from food and drink
- When applying paint it is advisable to wear suitable eye protection
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Remove splashes from skin with soap and water or a recognised skin cleaner
- Care must be taken when transporting paint. Keep container in a secure upright position.
- Contains no added lead and mercury
- Protect from extremes of temperature. Store in a cool place.
- In the event of an accident, contain and collect spillage using sand or earth. Do not empty into drains or water courses. Dispose of any paint waste in accordance with local environmental regulations.

(PLEASE REFER TO PRODUCT SAFETY DATA SHEET BEFORE USE)

Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong: [Flat coatings] VOC content (ready to use) not exceeding 50 g/litre

LIMITATION OF LIABILITY The information detailed in this datasheet is liable to modifications from time to time in the light of experience & normal product development. To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOUR OR COST OF LABOUR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.

For further information or if you have any concerns about using this product, please contact our Sales Department.

Any advice, recommendations, information, assistance or service provided by AkzoNobel in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by AkzoNobel is provided without expressed or implied warranties.

Manufactured by:
Akzo Nobel Paints (Guangzhou) Limited
Bei Wei Ind. Dist., Guangzhou E&T Development Zone,
PRC.

Distributed by:
AKZO NOBEL HK (HOLDINGS) LIMITED
Tel: 2823 1388 Fax: 2866 3232
Website: www.dulux.com.hk

Copyright © 2024 Akzo Nobel Paints Limited. All Rights Reserved
MAR24/H8607V1