

multiagent.

four ways to make Claude Code work in parallel.



~/REPO — CLAUDE --MULTI-AGENT

```
$ claude --multi-agent  
> initializing harness...
```

*One Claude window is already a small team. **Four windows** is a studio. This guide shows the four shapes that team can take — and when each one is the right shape.*

Pick by coordination, not headcount. Side-task → sub-agent. Independent → agent view. Coordinated → team. Total isolation → worktree per terminal.

● LIVE · INTERACTIVE

i.

FOUR APPROACHES · PICK ONE OR LAYER THEM

01

SUB-AGENTS *delegated side tasks*

02

AGENT VIEW *a dashboard of sessions*

APPROACH 01 · IN-SESSION DELEGATION

Sub-agents.

A specialist worker that runs in *its own context window*, finishes a focused task, and returns a summary to the calling session. Use them to keep the main thread clean – research, verification, exploration.

“The point isn't another agent. The point is to keep your main conversation uncluttered.”

Define them as Markdown files under `.claude/agents/`. Each gets its own system prompt, tool allowlist, and (optionally) a smaller model so the work is cheap.

CONTEXT · ISOLATED PARALLEL · YES FILE-CONFLICTS · SHARED CWD

GOOD FOR · RESEARCH, AUDITS

`.CLAUDE/AGENTS/RESEARCHER.MD`

copy

```
----  
name: Researcher  
description: Finds prior art & cites sources  
model: haiku  
tools:  
  - bash  
  - read  
  - webfetch  
----
```

```
# You are an expert researcher.  
# Return citations as a bullet list.
```

PROMPT · MAIN SESSION

copy

```
$ /agents  
→ manage definitions
```

```
$ Have @Researcher dig up the rate-limit RFC, then summarize.  
→ spawning Researcher in isolated context...  
← "Found 3 sources, see notes/rfc-rate-limit.md"
```

ii. ----- SIMULATOR · SPAWN PARALLEL AGENTS

a small studio in your browser

+ SPAWN AGENT

+ SPAWN 4

CLEAR

no agents yet.
PRESS + SPAWN AGENT TO BEGIN

iii. ----- WHICH ONE, WHEN

<i>approach</i>	<i>communication</i>	<i>isolation</i>	<i>best for</i>
Sub-agents	summary back to caller	own context · shared cwd	research, verification, exploration
Agent view	you mediate	own context · own process	independent dispatch-and-check tasks
Agent teams	direct messaging · shared list	own context · shared goal	multi-axis review, complex refactors
Multi-terminal	none — you wire it	full · worktree per session	long-running parallel features

approach

communication

isolation

best for

/batch (worktrees)

via PR review

full · 5-30
worktrees

repo-wide migrations

END OF FILE · EOF // KEEP MAIN CLEAN, FAN OUT THE REST



DOCS · [CODE.CLAUDE.COM/AGENTS](https://code.claude.com/agents)