

1



- Complete reference+FCI for shells 15-25-37
- Partial reference+FCI for shells 9: 8657095065LF with or without accessories

- Max current rating per contacts: 1.5A
- Contact resistance ≤10mΩ
- Insulation resistance ≥5000MΩ
- TEST VOLTAGE
contact/contact ≥1000V
- Finish on contact area: gold over nickel
- Finish on terminal on end : bright pure tin over nickel





-Climatic category	-55° C/125° C/21j
-Corrosion	salt spray:24h

SHELL	A±0.38	B±0.12	C±0.20	D±0.25	PART NUMBER
09	30.81	24.99	19.27	16.21	865709S065TLF
15	39.14	33.32	27.50	24.54	865715S065TLF
25	53.03	47.04	41.27	38.25	865725S065TLF
37	69.32	63.50	57.70	54.71	865737S065TLF

- The "LF" product meets European union Directives and other country regulations as described in 65-22-008.
- The product is not intended to be exposed to a manufacturing solder process.
- Packaging spec: see 65-14-920.

European Views

rev	ecn no	dr	date
A	LS06-0022	MPE	2006/03/1
B	LS06-0095	L60	2006/06/28
C	LS07-0041	MPE	2007/02/12
D	LS07-0162	MPE	2007/06/12
-	-	-	-
-	-	-	-
-	-	-	-

www.fciconnect.com			surface ISO 1302 		tolerance std ISO 406 ISO 1101		projection 		mm 	
			TOLERANCES UNLESS OTHERWISE SPECIFIED							
Dr	M.PESSON	2006/03/11	ANGULAR	LINEAR	0.X	±0.1	size A3	Scale 2		
Eng	M.PESSON	2006/03/11			0.XX	±0.1				
Chr	LEGARRE	2006/03/11			0.XX* ±2*	±0.1		ECN LS07-0162		
Appr	LEGARRE	2006/03/11	Product family				D-SUB	Spec ref -		
			FEMALE IDC CONNECTOR FOR FLAT CABLE .				dwg no C01-8657-0610	Rev.		D
catalog no			-				CUSTOMER	sheet 1 of 1		