UNCONTROLLED DOCUMENT

8.33 [0.328]

3.35 [0.132]

ANDDE

0.50 [0.020]

SQR. (2 PLS.)

PART NUMBER
SSI-LXH387GD

REV.

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
Α	F.C.N. #10BRDR. & REDRAWN.	8.2.01


ø9.00	[ø0.354]	∕- ø7.20	[ø0,283]
		1	
ø5.00	[ø0.197]	l	

3.78 [0.149]

5.00 [0.197]

2.54 [0.100]

13.33 [0.525]



ELECTRO-OPTICAL CH	ARACTERI	STICS TA=25°C		$I_f = 20mA$	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		565		nm	
FORWARD VOLTAGE		2.2	2.6	Vf	
REVERSE VOLTAGE	5.0			V_r	1 _r =100µA
AXIAL INTENSITY		10		mcd	$I_f = 20 \text{mA}$
VIEWING ANGLE		120		2x theta	
EMITTED COLOR:	GREEN				
EPOXY LENS FINISH:	GREEN	DIFFUSED			

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	110	mW
DERATE FROM 25°C	-1.2	mW/'C
OPERATING, STORAGE TEMP.	-40 TO +85	° C
SOLDERING TEMP,	+ 260	*C
2.0mm FROM BODY		3 SEC. MAX

* t<10µS

NOTES:

- 1. SSL-LX433GD LED.
- 2. HOLDER: LXP-SSI-387BSH, LXP-SSI-387BZL.
- 3. PANEL HOLE CUT OUT: 5/16" DIAMETER.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +D.00 -DECIMAL PRECISION MAX. = +0.00 -DECIMAL PRECISION

PART NUMBER

A SSI-LXH387GD

T-5 FRESNEL LENS PANEL MOUNT INDICATOR, 565nm GREEN LED, GREEN DIFFUSED LENS. CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HERBIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 8.2.01
ct PAGE: 1 OF 1
SCALE: N/A