1) #include<stdio.h>

```
int main()
{
   int distance;
   int fare = 100;
   char membership;
   printf("Enter distance travelled:\n");
   scanf("%d", &distance);
   printf("Membership (y/n): ");
   scanf(" %c", &membership);
   if (distance > 10)
      fare = fare + (distance - 10) * 20;
   if (membership == 'y' || membership == 'Y')
      fare = fare - fare * 10 / 100;
   printf("Fare: %d\n", fare);
   return 0;
}
```

---

2) #include <stdio.h>

```
int main() {
   int questions, time, submitted;
   printf("submitted questions:");
   scanf("%d", &questions);
   printf("time:");
   scanf("%d",&time);
   printf("submitted:");
   scanf("%d",&submitted);
   if (questions >= 1 && time > 0 && submitted == 0)
      printf("Submission Allowed");
   else
```

```
    printf("Submission Not Allowed");
  return 0;
}
```

---

3)

```
#include <stdio.h>
int main() {
  int coins, x, y;
  int ben, blackbeard, remaining, pirate;
  printf("Enter total gold coins: ");
  scanf("%d", &coins);
  printf("Enter Long Ben's share percentage: ");
  scanf("%d", &x);
  printf("Enter Blackbeard's share percentage: ");
  scanf("%d", &y);
  ben = coins * x / 100;
  remaining = coins - ben;
  blackbeard = remaining * y / 100;
  remaining = remaining - blackbeard;
  pirate = remaining / 3;
  printf("Long Ben's share: %d\n", ben);
  printf("Blackbeard's share: %d\n", blackbeard);
  printf("Each pirate's share: %d\n", pirate);
  return 0;
}
```

---

4)

```
#include <stdio.h>
int main() {
  int d1, c1, d2, c2;
  int dollars, cents;
  printf("Enter first dollars and cents: ");
```

```
   scanf("%d %d", &d1, &c1);
   printf("Enter second dollars and cents: ");
   scanf("%d %d", &d2, &c2);
   dollars = d1 + d2;
   cents = c1 + c2;
   dollars = dollars + cents / 100;
   cents = cents % 100;
   printf("dollers:%d\n", dollars);
   printf("cents:%d\n", cents);
   return 0;
}
```

---

5)
```
#include <stdio.h>
int main()
{
   float mileage;
   int petrol,distance;
   printf("Enter mileage:");
   scanf("%d",&mileage);
   printf("Enter petrol:");
   scanf("%d",&petrol);
   printf("Enter distance:");
   scanf("%d",&distance);
   if (distance/petrol<=mileage)
      printf("can reach");
   else
      printf("cannot reach");
   return 0;
}
```

---

6) int main()

```
{
   int n, rem, binary = 0, place = 1;
   printf("Enter a no:");
   scanf("%d", &n);

   while (n > 0) {
      rem = n % 2;
      binary = binary + rem * place;
      place = place * 10;
      n = n / 2;
   }
   printf("binary%d", binary);
   return 0;
}
```

---

7) #include <stdio.h>

```
int main()
{
   int p,r,t;
   float intrest,amount,discount,settlement;
   printf("Enter principal amount:");
   scanf("%d",&p);
   printf("Enter Intrest rate:");
   scanf("%d",&r);
   printf("Enter time period:");
   scanf("%d",&t);
   intrest=p*r*t/100;
   amount=p+intrest;
   discount=intrest*2/100;
```

```
    settlement=amount-discount;
    printf("intrest:%.2f\n",intrest);
    printf("amount:%.2f\n",amount);
    printf("discount:%.2f\n",discount);
    printf("settlement:%.2f\n",settlement);
    return 0;
}
```

---

8)
```
#include<stdio.h>
int main()
{
    int experience,performance;
    printf("Enter year of experience:");
    scanf("%d",&experience);
    printf("Enter your performance score:");
    scanf("%d",&performance);
    if (experience<3)
        printf("level:junior level");
    if (experience>=3 && experience<=7 && performance>=80)
        printf("level:Mid level");
    if(experience>7 && performance>=85)
        printf("level:senior level");
    return 0;
}
```

---

9)
```
#include<stdio.h>
int main()
{
    int year, month, days;
    printf("Enter the year:");
    scanf("%d", &year);
```

```
printf("Etnter the month:");
scanf("%d", &month);
if (year < 1900 || year > 9999)
{
   printf("0");
}
else if (month < 1 || month > 12)
{
   printf("0");
}
else
{
   switch (month)
   {
      case 2:
         if (year % 400 == 0 ||
            (year % 4 == 0 && year % 100 != 0))
            days = 29;
         else
            days = 28;
         break;

      case 4:
      case 6:
      case 9:
      case 11:
         days = 30;
         break;

      default:
         days = 31;
```

```
    }

    printf("%d Days", days);
  }

  return 0;
}
```

---

10)

```
#include<stdio.h>
int main()
{
  int a,b;
  printf("Enter electricity units consumed:",a);
  scanf("%d",&a);
  if (a<=200)
    b=a*0.5 ;
  else if(a<=400)
    b=a*0.65+100;
  else if(a<=600)
    b=a*0.80+200;
  else
    b=a*1.25+424;
  printf("cost=%d",b);
  return 0;
}
```