

PANDAS

What is Pandas?

Pandas is a Python library used for working with data sets.

It has functions for analyzing, cleaning, exploring, and manipulating data.

The name "Pandas" has a reference to both "Panel Data", and "Python Data Analysis" and was created by Wes McKinney in 2008.

Why Use Pandas?

Pandas allows us to analyze big data and make conclusions based on statistical theories.

Pandas can clean messy data sets, and make them readable and relevant.

Relevant data is very important in data science.

What Can Pandas Do?

Pandas gives you answers about the data. Like:

Is there a correlation between two or more columns?

What is average value?

Max value?

Min value?

Pandas are also able to delete rows that are not relevant, or contains wrong values, like empty or NULL values. This is called cleaning the data.

DataFrames

Data sets in Pandas are usually multi-dimensional tables, called DataFrames.

Series is like a column, a DataFrame is the whole table.

In [9]:

```
import pandas

mydataset = {
    'cars': ["BMW", "Volvo", "Ford"],
    'passings': [3, 7, 2]
}

myvar = pandas.DataFrame(mydataset)

print(myvar)
print()
print(myvar.loc[0])
```

```
   cars  passings
1  BMW         3
2 Volvo         7
3  Ford         2
```

```
cars      BMW
passings   3
Name: 0, dtype: object
```

In [2]:

```
import pandas as pd

print(pd.__version__)
```

1.0.5

What is a Series?

A Pandas Series is like a column in a table.

It is a one-dimensional array holding data of any type.

In [3]:

```
a = [1, 7, 2]

myvar = pd.Series(a)

print(myvar)
```

```
0    1
1    7
2    2
dtype: int64
```

Labels

If nothing else is specified, the values are labeled with their index number. First value has index 0, second value has index 1 etc.

This label can be used to access a specified value.

In [4]:

```
a = [1, 7, 2]
myvar = pd.Series(a, index = ["x", "y", "z"])
print(myvar)
```

```
x    1
y    7
z    2
dtype: int64
```

In [5]:

```
# Return the value of "y":
print(myvar["y"])
```

```
7
```

In [6]:

```
calories = {"day1": 420, "day2": 380, "day3": 390}
myvar = pd.Series(calories)
print(myvar)
```

```
day1    420
day2    380
day3    390
dtype: int64
```

In [7]:

```
# Create a Series using only data from "day1" and "day2":
```

```
import pandas as pd

calories = {"day1": 420, "day2": 380, "day3": 390}
myvar = pd.Series(calories, index = ["day1", "day2"])
print(myvar)
```

```
day1    420
day2    380
dtype: int64
```

Load Files Into a DataFrame

If your data sets are stored in a file, Pandas can load them into a DataFrame.

In [4]:

```
import pandas
```

```
mydataset = {  
    'cars': ["BMW", "Volvo", "Ford", 'tesla', 'tata'],  
    'passings': [3, 7, 2,4,5]  
}
```

```
myvar = pandas.DataFrame(mydataset)  
print(myvar)  
myvar.to_csv('info.csv')  
# myvar.to_csv('info.csv', index=False)  index pahije nsla tr
```

	cars	passings
1	BMW	3
2	Volvo	7
3	Ford	2
4	tesla	4
5	tata	5

In [5]:

```
myvar.head(2)    #fakt starting che 2 row dakhvel
```

Out[5]:

	cars	passings
0	BMW	3
1	Volvo	7

In [6]:

```
myvar.tail(2)    #fakt Last che 2 row dakhvel
```

Out[6]:

	cars	passings
3	tesla	4
4	tata	5

In [7]:

```
myvar.describe()
```

Out[7]:

	passings
count	5.000000
mean	4.200000
std	1.923538
min	2.000000
25%	3.000000
50%	4.000000
75%	5.000000
max	7.000000

In [6]:

```
#read csv file
import pandas as pd
file= pd.read_csv('student.csv')
print(file)
```

	name	rollno	city
1	rushi	1	pune
2	keshav	2	pune
3	anuja	3	pune
4	shital	4	pune

In [7]:

```
file['rollno'][1]=12 #to change data in file
```

<ipython-input-7-cd732f05db09>:1: SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy (https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy)

```
file['rollno'][1]=12
```

In [8]:

```
print(file)
```

	name	rollno	city
1	rushi	1	pune
2	keshav	12	pune
3	anuja	3	pune
4	shital	4	pune

In [10]:

```
file.index=[10,11,12,13]      #change index  
print(file)
```

	name	rollno	city
10	rushi	1	pune
11	keshav	12	pune
12	anuja	3	pune
13	shital	4	pune

pandas data structure

--series

--dataframe

Series:

Pandas Series is a one-dimensional labelled array capable of holding data of any type (integer, string, float, python objects, etc.). The axis labels are collectively called indexes. Pandas Series is nothing but a column in an excel sheet. Labels need not be unique but must be a hashable type. The object supports both integer and label-based indexing and provides a host of methods for performing operations involving the index.

	<i>Name</i>	<i>Team</i>	<i>Number</i>
0	Avery Bradley	Boston Celtics	0.0
1	John Holland	Boston Celtics	30.0
2	Jonas Jerebko	Boston Celtics	8.0
3	Jordan Mickey	Boston Celtics	NaN
4	Terry Rozier	Boston Celtics	12.0
5	Jared Sullinger	Boston Celtics	7.0
6	Evan Turner	Boston Celtics	11.0

`ser = pd.Series(df['Name'])`
`ser = pd.Series(df['Team'])`
`ser = pd.Series(df['Number'])`



DataFrame

Pandas DataFrame is a two-dimensional size-mutable, potentially heterogeneous tabular data structure with labeled axes (rows and columns). A Data frame is a two-dimensional data structure, i.e., data is aligned in a regular fashion in rows and columns. Pandas DataFrame consists of three principal components, the data, rows, and columns.

	<i>Name</i>	<i>Team</i>	<i>Number</i>	<i>Position</i>	<i>Age</i>
0	Avery Bradley	Boston Celtics	0.0	PG	25.0
1	John Holland	Boston Celtics	30.0	SG	27.0
2	Jonas Jerebko	Boston Celtics	8.0	PF	29.0
3	Jordan Mickey	Boston Celtics	NaN	PF	21.0
4	Terry Rozier	Boston Celtics	12.0	PG	22.0
5	Jared Sullinger	Boston Celtics	7.0	C	NaN
6	Evan Turner	Boston Celtics	11.0	SG	27.0



In [8]:

```
import numpy as np
import pandas as pd
newdf = pd.DataFrame(np.random.rand(334,5), index=np.arange(334))
newdf
```

Out[8]:

	0	1	2	3	4
0	0.475100	0.173122	0.261321	0.283373	0.710600
1	0.074084	0.895896	0.356004	0.670794	0.367154
2	0.401107	0.409255	0.629785	0.416491	0.632631
3	0.579149	0.065175	0.862828	0.453117	0.251587
4	0.139493	0.700041	0.446373	0.229521	0.774194
...	...	...	...	...	...
329	0.283477	0.349884	0.562985	0.588773	0.890677
330	0.798235	0.205785	0.410589	0.716287	0.429332
331	0.610896	0.282866	0.908540	0.695854	0.008176
332	0.544440	0.414596	0.121202	0.983670	0.750115
333	0.117343	0.038432	0.223937	0.645885	0.837589

334 rows × 5 columns

In [9]:

```
newdf.head()
```

Out[9]:

	0	1	2	3	4
0	0.475100	0.173122	0.261321	0.283373	0.710600
1	0.074084	0.895896	0.356004	0.670794	0.367154
2	0.401107	0.409255	0.629785	0.416491	0.632631
3	0.579149	0.065175	0.862828	0.453117	0.251587
4	0.139493	0.700041	0.446373	0.229521	0.774194

In [12]:

```
newdf.index
```

Out[12]:

```
Int64Index([ 0,  1,  2,  3,  4,  5,  6,  7,  8,  9,
             ...,
            324, 325, 326, 327, 328, 329, 330, 331, 332, 333],
            dtype='int64', length=334)
```


In [13]:

```
newdf.columns
```

Out[13]:

```
RangeIndex(start=0, stop=5, step=1)
```

In [14]:

```
newdf.to_numpy()
```

Out[14]:

```
array([[0.47510047, 0.17312217, 0.26132107, 0.28337312, 0.71059975],
       [0.07408361, 0.89589573, 0.35600446, 0.67079358, 0.36715359],
       [0.4011072 , 0.4092549 , 0.62978493, 0.41649125, 0.6326309 ],
       ...,
       [0.61089631, 0.28286613, 0.90854008, 0.69585439, 0.00817552],
       [0.5444398 , 0.41459605, 0.12120208, 0.98367007, 0.75011469],
       [0.11734308, 0.03843185, 0.22393732, 0.64588467, 0.83758889]])
```

In [15]:

```
newdf.T #row column madhe ani column row madhe convert hotil
```

Out[15]:

	0	1	2	3	4	5	6	7	8	
0	0.475100	0.074084	0.401107	0.579149	0.139493	0.133298	0.768989	0.708546	0.808793	0
1	0.173122	0.895896	0.409255	0.065175	0.700041	0.901605	0.133485	0.111715	0.713773	0
2	0.261321	0.356004	0.629785	0.862828	0.446373	0.901748	0.657082	0.036265	0.008844	0
3	0.283373	0.670794	0.416491	0.453117	0.229521	0.895150	0.528441	0.528502	0.736985	0
4	0.710600	0.367154	0.632631	0.251587	0.774194	0.077758	0.024994	0.577201	0.809680	0

5 rows × 334 columns



In [16]:

```
newdf.sort_index(axis=0, ascending=False)    #reverse sort
```

Out[16]:

	0	1	2	3	4
333	0.117343	0.038432	0.223937	0.645885	0.837589
332	0.544440	0.414596	0.121202	0.983670	0.750115
331	0.610896	0.282866	0.908540	0.695854	0.008176
330	0.798235	0.205785	0.410589	0.716287	0.429332
329	0.283477	0.349884	0.562985	0.588773	0.890677
...	...	...	...	...	...
4	0.139493	0.700041	0.446373	0.229521	0.774194
3	0.579149	0.065175	0.862828	0.453117	0.251587
2	0.401107	0.409255	0.629785	0.416491	0.632631
1	0.074084	0.895896	0.356004	0.670794	0.367154
0	0.475100	0.173122	0.261321	0.283373	0.710600

334 rows × 5 columns

In [17]:

```
newdf[0]
```

Out[17]:

```
0    0.475100
1    0.074084
2    0.401107
3    0.579149
4    0.139493
```

...

```
329  0.283477
330  0.798235
331  0.610896
332  0.544440
333  0.117343
```

Name: 0, Length: 334, dtype: float64

In [18]:

```
type(newdf[0])
```

Out[18]:

pandas.core.series.Series