Situation engineering: separating evidence applicability from availability in AI systems

Geunsik Lim[1*]

[1] College of Information and Communication Engineering, Sungkyunkwan University, Suwon, South Korea .

Corresponding author(s). E-mail(s): leemgs@g.skku.edu;

Abstract

Artificial-intelligence systems can retrieve a well-supported fact yet apply it to the wrong time, scope, epistemic state or possible world. We call this failure *situation blindness* and define *situation engineering* as constructing the query-relative state that governs evidence applicability. We introduce a state interface, Situation-Catching Question Answering, and SituationCatch-Bench, a 4,200-item diagnostic spanning seven applicability categories from temporal change to counterfactual worlds. A deterministic implementation satisfies every invariant under oracle states; accuracy falls to 66.5% under text-inferred states and 45.1% after corruption, and each matched ablation produces a failure confined to its category. These results establish an executable diagnostic, not language-model superiority. Across nine models from seven developers, including two pre-registered replications, explicit situation prompting never detectably beats matched structured prompting, whereas identical claims without timestamps fail on time-dependent items and dating natural temporal questions adds 22–27 points. Language-model sensors recover most cues a rule-based sensor misses, but not information absent from text.

Keywords: large language models, situation engineering, evidence applicability, situation awareness, hallucination, trustworthy artificial intelligence, temporal reasoning, question answering, agent systems

Large language models (LLMs) increasingly answer questions by combining parametric knowledge with retrieved documents, tools, memory and long conversational histories. These mechanisms improve evidence coverage, but they do not guarantee that a system identifies the *situation* in which a fact is valid. A model may read that a person was

appointed and later resigned, yet still name that person as the current office holder. It may turn a proposal into a decision, extend a local policy to an entire organization, answer from information unavailable to the queried observer, or collapse a hypothetical scenario into the real world. In each case the decisive evidence can already be present. The failure is not simply missing knowledge; it is incorrect evidence applicability.

We define *situation blindness* as producing an answer or action that is supported by at least one available claim but inconsistent with the time, scope, modality, observer knowledge or possible world required by the query. This category matters because conventional factuality checks can mark the supporting claim as true while missing that it is true in the wrong situation. Natural question-answering resources already show that a material subset of ordinary questions depends on extra-linguistic time or place, and that updated evidence does not eliminate the resulting performance loss [1–5].

Retrieval-augmented generation supplies external evidence [6]; self-reflective and tool-using systems add critique and action [7–9]; context engineering organizes the inference-time information payload [10]; and agent harnesses mediate tools, memory, permissions, verification and feedback [11, 12]. These layers are necessary, but none requires an explicit answer to a separate question: *which interpretation of the available evidence governs this interaction now?*

We call the corresponding discipline *situation engineering*: the systematic design of representations, sensing interfaces, update rules, validation procedures and response policies that establish the active query-relative world state before an AI system commits to an answer or action. For a query q and evidence E, a minimal state is

$$S(q, E) = \{\mathcal{A}, \mathcal{V}, \mathcal{T}, \mathcal{P}, \mathcal{M}, \mathcal{K}, \mathcal{W}, \mathcal{U}\}, \tag{1}$$

where the variables denote actors, events, valid time, scope, modality and source status, observer-specific knowledge, possible world and unresolved answer-critical information. A policy then selects

$$\pi(S) \in \{\textsc{Answer}, \textsc{Clarify}, \textsc{Retrieve}, \textsc{Abstain}, \textsc{Act}\}. \tag{2}$$

This decomposition separates evidence availability from evidence applicability.

The present paper makes four contributions. First, it defines situation blindness as a testable failure class and relates it to established work on situations, temporal reasoning, belief state tracking and knowledge revision. Second, it specifies situation engineering as a systems contract connecting prompt, context, retrieval, memory, tool, harness, evaluation and serving engineering without subsuming them. Third, it introduces SCQA and SituationCatch-Bench, and uses matched state conditions and component ablations to demonstrate that the specified applicability mechanisms are executable and that all seven are causally separable by ablation. Fourth, it reports audited interventions on nine models from seven developers, partly pre-registered, with retrieval and tool-using agent baselines, a pre-registered test of language models as situation sensors and a pre-registered natural-text temporal study. Their result prevents us from equating an explicit prompt slot with situation awareness, while the failure of timestamp-free evidence on temporal items locates where applicability is lost.




Fig. 1 From situation blindness to an applicability-aware response. **a**, A supported appointment becomes stale after resignation. **b**, retrieval and relevance alone do not require resolution of that transition. **c**, situation engineering constructs a provenance-linked state, validates claim applicability and propagates unresolved variables into response policy. **d**, SituationCatch-Bench isolates seven corresponding diagnostic axes.

This claim boundary distinguishes what we demonstrate from broad language-model generalization.

Situation Engineering framework

Prompt engineering specifies a task; context and retrieval engineering select information; memory engineering retains observations; tools expose capabilities; and harness engineering controls execution. Situation engineering addresses a narrower semantic question: which available claims apply to this query, observer and world now? It is therefore a proposed interface among existing components, not a replacement name for them and not an empirically validated universal layer. Fig. 1 contrasts situation blindness, retrieval-only processing and an applicability-aware response, and summarises the seven diagnostic axes that SituationCatch-Bench isolates.

For query q, evidence E, retained memory M_t, tool observations O_t and harness trace H_t, situation construction produces candidate states $\mathcal{S}_t$ with unresolved variables U_t and provenance P_t:

$$(q, E, M_t, O_t, H_t) \rightarrow (\mathcal{S}_t, U_t, P_t). \tag{3}$$

Each evidence claim is assigned a query-relative applicability value

$$\mathrm{Apply}(e, q, S_t) \in \{\mathrm{valid}, \mathrm{invalid}, \mathrm{unresolved}\}. \tag{4}$$

Preserving *unresolved* is essential. A system should retrieve, clarify or abstain when answer-critical state cannot be established rather than silently converting uncertainty into a plausible binary judgement.

Operations and component boundaries

Six operations define the interface. *Sensing* extracts actors, events, times, modality, source status, scope, observer knowledge and world identity. *Assembly* links observations into candidate states. *Updating* applies supersession, cancellation and belief transitions. *Validation* checks applicability, conflicts, provenance and missing variables. *Policy* selects an answer, retrieval, clarification, abstention or action. *Observability* records the active state and its evidence.

These responsibilities do not absorb neighbouring disciplines. A retriever still owns ranking and freshness; a memory system owns retention; a tool layer owns invocation semantics; a harness owns permissions and recovery; and serving systems own resource efficiency. The proposed situation layer consumes their outputs and returns applicability decisions and unresolved-state signals. Likewise, longer context is not sufficient: it may contain an appointment and a later resignation, a proposal and a final decision, or real and hypothetical claims simultaneously. Applicability requires resolving their relation rather than merely retaining both.

SCQA as a bounded control implementation

Situation-Catching Question Answering (SCQA) instantiates the interface for seven controlled variables. Its deterministic sensor or supplied gold state feeds auditable update rules and an answer/clarify/abstain policy. SCQA has no learned parameters. It is designed to test whether removing a required variable produces the matching failure signature, not to compete with contemporary language models.

Because the generated benchmark and solver share an ontology, the oracle-state experiment is analogous to a protocol conformance suite, and the predicted-state condition still uses generated English.

Testable predictions

The framework yields falsifiable predictions for future matched experiments. Holding model, evidence and computation budget fixed, an explicit situation state should improve the categories whose decisive variables are otherwise implicit. Gains should diminish when a baseline already represents the same state. Predicted-state errors should decompose into sensing, update, policy and generation failures. Corrupting one state slot should selectively damage its matching category. Finally, the benefit must be evaluated jointly with token use, latency, retrieval calls, monetary cost and unnecessary clarification. Failure of these predictions would argue against treating situation engineering as a distinct practical interface.

Results

A controlled benchmark isolates seven applicability invariants

SituationCatch-Bench v0.2 contains 4,200 generated English instances, with 600 instances in each of seven diagnostic categories: temporal state change, omitted answer-critical premises, source conflict, proposed versus confirmed events, local versus




Fig. 2 Oracle-state diagnostic accuracy. Bars show exact action-and-answer accuracy of SCQA (given the oracle situation state) and three heuristic baselines on all $n = 4{,}200$ generated items. The result demonstrates that the specified invariants are executable. It does not estimate end-to-end LLM accuracy because situation variables are supplied rather than inferred. All systems are deterministic, so repeated runs give identical values; no error bars are shown because items share template families and are not independent samples (Methods).

universal scope, observer-dependent knowledge and real versus counterfactual worlds. Every item provides a question, shuffled claims, query time, required state variables, a gold action and, where answerable, a gold answer. The benchmark is intentionally transparent: each category is a software-level test of one applicability invariant rather than a claim to natural linguistic diversity. Within every category the gold answers are balanced and, wherever claim order could decide the answer, the decisive claim is the most recent one in exactly half of the items, so neither a constant answer nor a recency rule can exceed chance on the decisive variable (Methods). Version 0.1 lacked this balancing; it is archived with its results.

Oracle-state control satisfies the generated invariants

SCQA was compared with lexical retrieval, recency-ranked retrieval and a latest-mention rule. All methods received the same generated claims; SCQA alone used the complete oracle situation state and transition semantics. SCQA obtained 100.0% action-and-answer accuracy. Lexical retrieval obtained 54.3%, recency ranking 50.0% and latest mention 47.4% (Fig. 2). These numbers are deterministic consequences of the benchmark and implementation and should be interpreted as regression-test coverage, not as estimates of model performance in a population of natural questions.

The control values are structurally induced. Each control reads one selected claim at face value, and because every category is balanced, such a reading is right about half of the time; the gaps to SCQA are therefore not presented as empirical effect sizes against competitive baselines. The one exception is lexical retrieval on counterfactual items (100%): the question names the hypothetical scenario, so content-word overlap selects the hypothetical claim.

The category-level pattern provides the useful result (Fig. 3). All three controls answer hidden-premise items without asking and score 25%, being right only when a stated premise makes the answer yes. On temporal items they fail whenever the query time precedes the latest event, so recency ranking, which always selects the newest




Fig. 3 Accuracy by diagnostic category. Bars show exact action-and-answer accuracy of each system within each category ($n = 600$ items per category). Each category isolates one applicability variable, enabling mechanism-level failure localization. Values are deterministic; no error bars are shown (Methods).

appointment, scores exactly 50%. On source-conflict and counterfactual items recency is right only when the decisive claim happens to be the newest (50%), and a status-blind reading of modality items is right on every confirmed closure but on only half of the undecided ones (about 75%). Thus a single aggregate "hallucination" label hides distinct and testable mechanisms.

Component ablations produce matched failure signatures

Removing any one of temporal validity, source status, modality, scope, observer knowledge, world identity or missing-variable detection produces exactly 300 errors, all within the matching category and none elsewhere (Fig. 4). In v0.1 the source and world ablations produced no errors, because the decisive claim was always also the most recent; the balanced generator removes that confound, so every ablation now tests its variable. This causal alignment is the main empirical contribution of the controlled study. It shows that the implementation does not merely benefit from a generic instruction to be cautious; behaviour changes when the specific variable required by an item is removed. Because benchmark and solver share the same schema, the result is best viewed as a mechanistic unit test that future neural systems should pass under both gold and predicted states.

Partial observability exposes a sensing gap

We evaluated two observability regimes. In the evidence-complete control, all required variables are supplied in the structured state. In the text-only regime, the sensor must




Fig. 4 Oracle-state component ablations. Bars show SCQA exact action-and-answer accuracy on all $n = 4{,}200$ items when one state variable is removed ('none' is the intact system). Each removal produces exactly 300 errors, all in the category whose variable was removed. Values are deterministic; no error bars are shown (Methods).

reconstruct a state from the rendered claims; variables not expressed in those claims remain unobservable rather than being silently copied from gold metadata. Across all 4,200 diagnostic instances, action-and-answer accuracy fell from 100.0% with gold states to 66.5% with predicted states. Deliberately overwriting source status, modality and scope (which also carries world identity) in the predicted state reduced accuracy further to 45.1%. These are complete executions, not projected values. They show that the oracle result is not preserved when situation sensing is imperfect. Because the texts are generated from the same seven scenario families and the sensor is a transparent rule baseline, these results remain controlled diagnostics rather than evidence of natural-language or LLM generalization, and a partial-observability stress test rather than an estimate of extraction from evidence-complete prose (Methods).

Claim-level scoring localizes the sensor's limitations (Extended Data Table 1). Event type reached 92.3%, modality 100.0%, scope 61.5%, actor 30.8% and joint source/status 34.6%. Temporal expressions and validity intervals scored 0% because the generated claim strings omit the numeric times stored in the hidden schema: a system cannot reconstruct a state variable that is neither expressed nor retrieved. Observer and world slots reached 92.3% and 100.0% under repetitive generated language and are not estimates of natural extraction. In this deterministic pipeline, 1,407 final errors are attributable to sensing, zero to update/policy under gold state, and generation is a fixed renderer.

Progressive stress testing separates execution, sensing and validation

Read as a three-stage stress test, the complete benchmark produces 100.0% $\rightarrow$ 66.5% $\rightarrow$ 45.1%: an oracle state tests execution, a text-derived state adds sensing error, and targeted corruption tests whether unvalidated state can propagate into the answer. The corresponding losses are 33.5 and 21.4 percentage points. This progression is empirical in the limited sense that every stage was executed on all 4,200 items and

Table 1 Evidence ladder and permitted interpretation.

Evidence level	What is available	Permitted claim
E1: formal definition	Situation schema and applicability relation	The failure class is operationally testable
E2: oracle unit tests	4,200 generated instances and matched ablations	Specified invariants are executable and causally separable
E3: natural prevalence	Independent temporal/situated QA literature	Situation dependence occurs in natural questions
E4: predicted-state control	Deterministic text sensor on 4,200 generated items	Sensing errors reduce controlled end-to-end accuracy; natural-text generalization remains open
E5/E6/E8a: multi-model intervention	Nine models, seven developers (Gemini; pre-registered Meta, DeepSeek, Qwen, NVIDIA, rednote, Recursive), $n = 210$, situation/structured/RAG/agent conditions; E7: LLM sensors	Situation prompting never detectably improves on structured prompting; evidence without timestamps fails on temporal items; category differences are exploratory
E8b: natural-text temporal QA	300 SituatedQA questions, two models, pre-registered	The query date raises accuracy on time-dependent natural questions; other categories remain untested on natural text
Deployment / human study	Not completed	Needed for operational safety and human comparison

item-level outputs are archived. It is not a learning curve, a comparison of three models or an estimate of robustness to naturally occurring corruption. In particular, the last stage is an intentionally severe intervention selected to damage source, modality and scope fields; monotonic degradation is therefore a diagnostic expectation rather than an independently discovered population effect.

Natural-language benchmarks establish prevalence, not SCQA efficacy

Independent resources show that situation dependence is not confined to the generated benchmark. SituatedQA reported that approximately 16.5% of sampled NQ-Open questions depended on time or place and that updated evidence did not remove a substantial present-time performance gap [1]. FreshQA, PAT-Questions, TimeQA, ChronoQA and TDBench test related problems in freshness, evolving facts and temporal validity [2–5, 13]. These studies motivate the problem; they are not evaluations of SCQA.

An evidence ladder separates established findings from open claims

Table 1 makes the claim boundary explicit. Within its co-designed conformance suite, the study shows that seven applicability invariants can be represented, executed and independently ablated under oracle states. The audited model studies test, but do not support, a benefit of explicit situation prompts; they locate the loss of applicability in missing timestamps and dates instead.

Table 2 Gemini-family E5 accuracy (%; $n = 210$ items, 30 per category) with 95% cluster-bootstrap confidence intervals (categories as clusters; 3000 resamples), the paired situation−structured contrast, and cost. A contrast interval that excludes zero is a directional estimate only within this bounded analysis.

Model	Direct	Structured	Situation	$\Delta_{\text{sit}-\text{str}}$	Sit. tokens
2.5 Flash	84.8	83.8	81.0	−2.9	297
95% CI	[64.3, 98.6]	[66.2, 97.1]	[63.3, 95.7]	[−15.2, +6.7]	
2.5 Flash Lite	71.0	90.5	75.7	−14.8	269
95% CI	[50.5, 89.5]	[73.3, 100.0]	[56.2, 90.5]	[−24.8, −6.2]	
3.5 Flash	86.2	84.8	81.9	−2.9	289
95% CI	[68.1, 100.0]	[64.3, 100.0]	[57.6, 100.0]	[−8.1, +0.0]	

Situation prompting across seven model developers (E5, E6, E8a)

The controlled results establish that the seven applicability invariants are executable and causally separable (E1–E4); they do not show that *prompting* a language model for an explicit situation state improves it. E5 tests this with three Gemini models, and a pre-registered replication (E6) repeats it unchanged with three open-weight models from Meta, DeepSeek and Qwen; a second pre-registered replication on free endpoints (E8a) adds models from NVIDIA, rednote hi lab and Recursive. Each model answers the same stratified sample (30 items per category, $n = 210$) with evidence, decoding and budget fixed, under a plain *direct* answer, a *structured* JSON prompt or an explicit *situation*-state prompt (Methods). The primary quantity is the within-model paired situation−structured contrast; every run passes the completion audit with no unresolved calls, and E6 and E8a each pass a multi-family audit.

Explicit situation prompting does not improve on structured prompting (Table 2, Extended Data Table 2). The paired differences are −2.9, −14.8 and −2.9 percentage points in Gemini and −4.3, +19.5 and −0.5 in E6, so the pre-registered criterion for an improvement – an interval above zero in at least two of the three E6 families – is not met. The one positive contrast (Llama, +19.5 [+5.2, +36.2]) is a scoring artefact: Llama often wraps its structured JSON in prose or answers with a boolean, which the pre-registered extractor misses. A post-hoc sensitivity analysis that applies one more robust extractor to all six models changes 47 Llama records and turns its contrast into −1.9 [−7.1, +1.9]; under it, situation prompting is never above structured prompting in any model (−1.9 to −14.8 points). Intervals are wide because the benchmark has only seven template families (Methods). The situation prompt costs 2.7–6.2 times the tokens of the direct prompt. E8a reaches the same verdict (+0.5, −6.7 and −11.9 points; Extended Data Table 3), also under the sensitivity rescoring. Flint's negative contrast reflects responses cut off at the output limit, which its mandatory reasoning shares; without them it is 0.0 [−3.1, +2.3] (post hoc; Methods).

Removing metadata shows which variables matter (Extended Data Tables 4, 5 and 6). Because each item has at most three claims, the retrieval condition receives every claim, but as plain text without timestamps, status, source, scope or observers. Temporal accuracy then falls to 44.4% in Gemini, to 23–50% per E6 model and to

50.0–56.7% per E8a model, against 95.6–100% with metadata, as the pre-registered secondary hypothesis predicted in every family, while relevant text alone suffices for most other categories. A tool-using agent, whose searches also omit timestamps, is weakest on temporal items (33.3% in Gemini, 14.4% in E6).

LLM sensors recover most situation cues (E7)

Is the sensing gap specific to the rule-based sensor? In a second pre-registered study (E7), four LLMs receive exactly that sensor's inputs – query time, question and claim texts – and fill the same state slots, which drive the unchanged SCQA engine (Extended Data Table 7). On the same 210 items, end-to-end accuracy rises from 65.7% for the rule sensor to 79.0–87.1%, and on non-temporal items from 71.1% to 85.6–96.1%; source-conflict items go from 0% to 100%. Temporal items stay at 33–40% for every sensor, because the claim texts state no times. Most of the rule sensor's gap is therefore specific to it; what remains is information absent from the text, plus residual errors on observer knowledge and missing premises. Claim-level slot scores track decisions poorly, because harmless vocabulary differences count as errors.

Natural-text temporal questions (E8b)

E8b, pre-registered with E8a, tests natural text: two E8a models answer 300 independently written temporal questions from SituatedQA [1], 75 per date type, without evidence; the applicability variable is the query date (Extended Data Table 8). Dating an otherwise identical question raises accuracy on time-dependent items by +22.2 [+15.5, +28.8] and +26.7 [+18.8, +34.0] points, but not on control items dated at the collection year (−4.0 in both, intervals including zero), as pre-registered. Given the date, the situation prompt again shows no detectable benefit over the structured prompt (+4.7 [0.0, +9.4] and −2.7 [−6.6, +1.0]).

Together, these studies separate what the oracle results cannot: an explicit situation field shows no detectable benefit over structured prompting in nine models from seven developers, whereas the applicability variable itself – timestamps on synthetic evidence, the date on natural questions – is decisive for time-dependent items. Availability without readable applicability is not enough. The natural-text evidence covers only temporal questions and two models; other categories and human agreement still require independent evidence (Methods).

Discussion

The core insight is that relevance is not applicability. Retrieval can return a well-supported statement while a system still applies it to the wrong time, scope, epistemic state or possible world. Situation engineering turns this failure from an informal complaint about "missing context" into a set of state variables, update rules and behavioural consequences that can be tested separately.

A complementary layer, not a replacement vocabulary

The situation contract of equation (3) is meant to prevent conceptual inflation. Retrieval quality should not be renamed situation engineering, and a JSON field named "situation" is not evidence of situation awareness. A system must show that state representation causally changes behaviour in predicted cases, that state uncertainty affects answering or action, and that failures can be assigned to sensing, update, validation, policy or generation.

Implications for hallucination and agent evaluation

A generated claim can be textually entailed by a document yet wrong for the query. Evaluation should therefore record both support and applicability. In free-form generation, claims should be linked to the situation state and provenance on which they depend. In agents, tools should expose preconditions, state transitions and failure semantics rather than only free-text outputs; harnesses should block consequential actions while answer-critical state is unresolved. Evaluation engineering becomes the sensor layer that checks each transition and not merely the final answer.

The response policy is also part of correctness. Clarification and abstention are not failures when the situation is under-specified, although excessive clarification is costly. Future evaluations should therefore report answer accuracy, clarification utility, unnecessary-question rate, abstention precision, selective risk, coverage, latency, token use and monetary cost.

What is established and what remains to be tested

This study defines a formal error class and implements an interoperable state schema with category-specific effects of matched state ablations. It also shows that performance degrades sharply when state must be recovered from partially observable text. Together, these results identify situation sensing as a separate engineering and evaluation target rather than treating every failure as retrieval or generation error.

Of the framework's predictions, the controlled ones hold: corrupting or removing one state variable damages only its matching category, and predicted-state errors decompose into sensing rather than update or policy failures. The first neural prediction does not hold at the prompt level: an explicit situation state did not improve the categories whose decisive variables it names. This is consistent with the prediction that gains should vanish when a baseline already represents the same state, as the structured prompt does, but it means the present evidence does not show a benefit of situation prompting itself. The sensing prediction is also only partly borne out: language-model sensors remove most of the rule sensor's errors, so in this benchmark the residual sensing gap is mainly information the text does not contain. On natural temporal questions the date itself, not the situation prompt, carries the gain (E8b); confirming the general claim requires natural evidence for every category under matched model, evidence and budget (Methods). The SE0–SE4 maturity model and longer research programme are provided in Supplementary Information.

Limitations and risks

The diagnostic data are generated from a schema shared with the solver, so benchmark-solver circularity is intentional and limits external validity. The item count does not equal the number of statistically independent observations because examples share template families. The E1–E4 baselines are software controls. The model studies cover no proprietary family other than Gemini, test natural text only on temporal questions with two models, and two results rest on post-hoc analyses (scoring sensitivity; output truncation). Balancing answers and claim recency removes the shortcuts found in v0.1, but each category still varies only one or two template factors, so other surface regularities may remain. Confidence values are rule-derived and do not constitute neural calibration. No human participants, multilingual evaluation, multimodal sensing or deployed-agent study was completed. The archived three-persona agreement run is explicitly synthetic and validates software plumbing only; it cannot replace independent annotation. Earlier and aborted runs are archived but excluded from scientific results; only the complete run that passes the integrity gate enters the manuscript. These limitations are not resolved by additional prose and require new experiments.

Explicit state can also create new attack surfaces. An adversary may manipulate timestamps, source authority, identity, scope or world labels. A centralized state representation may expose sensitive user information or create false confidence in a flawed schema. Situation-engineered systems therefore require provenance, access control, privacy-preserving memory, conflict visibility and independent evaluation. "Explicit" must not be confused with "correct".

Conclusion

Situation engineering provides a bounded and testable interface between retrieval, state estimation and response policy. The controlled experiments demonstrate that applicability variables have distinct behavioural consequences and that imperfect sensing can erase the advantage of correct update rules. Establishing broad utility now requires the pre-specified natural-text, multi-model comparison against equally resourced structured prompting, temporal retrieval and agent verification.

Methods

Problem formulation

An item consists of a query q, evidence claims E, a query time and, where relevant, an observer or possible-world identifier. A claim may be supported in isolation but inapplicable to the query. We define

$$\mathrm{Apply}(e, q, S) \in \{\mathrm{valid}, \mathrm{invalid}, \mathrm{unresolved}\}, \tag{5}$$

where S is the active situation state. The system first constructs or receives S, then updates competing claims and selects an action from answering, retrieval, clarification, abstention or task-specific action.

The end-to-end system is decomposed as

$$(q, E) \xrightarrow{f_{sense}} \hat{S} \xrightarrow{f_{update}} \hat{S}' \xrightarrow{\pi} a \xrightarrow{g} y. \tag{6}$$

This decomposition supports stage-specific evaluation. The gold-state condition supplies S directly and evaluates f_{update}, π and the deterministic answer renderer. A predicted-state condition applies a text-only deterministic sensor before the same update and policy stages. It evaluates composition on generated claim language, but not f_{sense} on unrestricted natural language.

Relation to prior formalisms

Situation engineering draws on several mature traditions but is not identical to any one of them. Situation semantics treats meaning relative to partial situations [14]. Situation and event calculi formalize how actions change fluents over time [15–17]. Temporal reasoning provides interval relations and validity semantics [18]. Belief revision and truth-maintenance research asks how an agent should update inconsistent commitments [19, 20]. POMDPs and dialogue-state tracking maintain uncertainty over latent states for sequential decisions [21, 22]. Temporal knowledge graphs and bitemporal databases record changing facts and distinguish when a fact is valid from when it is stored [23].

The proposed contribution is a systems-level applicability contract for generative and agentic AI. It requires these representations to connect to natural-language evidence, provenance, unresolved alternatives and a response policy that can answer, retrieve, clarify, abstain or act. Thus the novelty is not a new universal logic. It is the explicit decomposition of modern AI reliability into (i) sensing a situation from heterogeneous evidence, (ii) maintaining a provenance-linked state, (iii) validating applicability and (iv) propagating unresolved state into behaviour. This framing allows existing logical, probabilistic and neural methods to be compared through a common set of interfaces and failure measurements.

A key distinction is that these traditions vary in whether they jointly expose time, observer, possible world, uncertainty, provenance and an answer-or-action gate; the proposed interface requires all of them to be reportable without claiming that their underlying formalisms are new.

Dynamic epistemic logic and common-ground modelling formalize belief-changing information and mutually recognized conversational commitments [24, 25]. Theory-of-mind models, world models and active perception further address attributed beliefs, latent environment state and information acquisition. These traditions reinforce rather than eliminate the need for careful attribution: situation engineering does not claim their theoretical results as new. Its proposed novelty is the systems contract that exposes their state variables to provenance-aware answer/retrieve/clarify/abstain gates in contemporary generative systems.

Situation schema

The schema contains actors and entities; events and state transitions; valid and observation time; scope; modality and source status; observer-specific knowledge; possible-world identity; provenance; and unresolved answer-critical variables. Update rules include temporal supersession, cancellation, source-authority preference where specified, scope containment, observer visibility and world separation. Unresolved variables are preserved rather than converted into a guessed binary state.

SituationCatch-Bench generation

The deterministic generator (seed 20260717) creates 600 instances for each of seven categories using seeded lexical variation and shuffled claim order. Each item includes the question, claims, structured situation fields, gold action, gold answer and category. Version 0.2 balances every category exactly by item index. Temporal queries fall after the last appointment or between the first appointment and the resignation (300 each); hidden-premise questions omit the user's region (300, gold CLARIFY) or state an eligible or ineligible region (150 each); the rumour is newer than the official notice in half of the source-conflict items; modality, scope, observer and counterfactual answers are yes or no in 300 items each; and the undecided proposal (modality) and the factual or hypothetical claim (counterfactual) is the newer claim in half of the relevant items. Version 0.1 fixed one answer per category and always made the decisive claim the most recent, so answer priors and recency solved most categories; it is archived with all of its results. The categories and gold semantics are documented in the bundled datasheet. Generation and evaluation are intentionally co-designed: the benchmark is a conformance suite for explicit semantics, analogous to unit tests for a software protocol, rather than an independent estimate of natural-language performance.

Future benchmark versions should use separate authors for data construction and system development, clustered scenario families, hidden generators, natural and semi-synthetic sources, adjudicated annotations, compositional splits and adversarial state manipulations. Recommended natural-data fields and annotation instructions are supplied in the Supplementary Information.

Reference implementation

SCQA is a deterministic Python reference implementation with no trained parameters. It parses the supplied structured fields, performs category-specific state updates and selects a permitted response. The three software-control baselines each select one claim (the last one mentioned, the most recent one, or the one sharing the most content words with the question after removing a fixed English stop-word list) and read it at face value, ignoring query time, status, source, scope, observers and world. These controls test whether the specified state variables are necessary for the generated invariants; they are not intended to represent competitive LLM, RAG or agent baselines.

Predicted- and corrupted-state evaluation

The predicted-state sensor receives only claim text and infers event type, actor, temporal expression, modality, source status and world or scope using documented deterministic patterns, and reads a premise the user states about themselves in the question ("I live in ..."); it cannot copy hidden gold slots. The downstream engine is unchanged. In a pre-specified corruption condition, predicted source status is replaced by a generic reported source, modality is forced to confirmed and scope is forced to global. All three conditions contain the same 4,200 identifiers and are scored by exact action and answer. Item-level and aggregate outputs are released in `results/state_conditions.csv` and `results/state_conditions_summary.csv`. The sensor is additionally scored claim by claim for actor, event, temporal expression, validity interval, scope, modality, joint source/status, observer-knowledge and world slots. Because claim order is preserved, this comparison does not require learned alignment. The resulting files are `results/predicted_state_slots.csv` and its aggregate summary. We distinguish an *evidence-complete* condition, in which every required slot is supplied, from a *partially observable* condition, in which absent slots must remain unresolved. A text-observable condition must instead render every answer-critical variable in independently authored prose and must not use hidden metadata during sensing. Results should be stratified by these regimes rather than averaging unextractable and extractable slots.

Metrics and analysis

The primary diagnostic measure is exact action-and-answer accuracy. For items requiring clarification, correctness requires selecting clarification rather than providing the latent answer. Category-level accuracy and matched component ablations localize failure mechanisms. Because instances share template families, item-level confidence intervals and P values are not used as primary scientific evidence in the revised manuscript. The released scripts retain item-level summaries for regression testing, but future natural-language studies should use scenario- or template-clustered bootstrap intervals, paired tests, multiple-comparison control and pre-specified primary outcomes.

Rule-derived confidence values from the original implementation are not treated as neural calibration. End-to-end work should report Brier score, expected calibration error, selective risk, risk–coverage area, clarification utility and abstention precision/recall using model- or state-derived probabilities.

Ablation design

Seven ablations independently remove temporal validity, source status, modality, scope, observer knowledge, world identity or missing-variable detection. Each ablation is applied to all items, and its expected effect is specified before execution. The purpose is to test causal alignment between representation and failure category, not to estimate an average treatment effect in natural text. An ablated component falls back to a situation-blind rule: removing time treats every claim as current, removing source status or world identity selects the most recent claim, removing modality or

scope accepts a proposal or a local claim as universal, removing observer knowledge assumes the person saw every claim, and removing missing-variable detection assumes eligibility. In v0.1 the source-status and world-identity ablations produced no errors because the decisive claim was always the most recent; in v0.2 each of the seven ablations produces exactly 300 errors, all in its own category. Baselines, category results and ablations are regenerated by `code/run_diagnostic.py`.

E5 multi-model pilot and confirmatory protocol

The reported E5 pilot uses a stratified sample of 210 SituationCatch-Bench v0.2 items (30 per category; sampling seed 20260718) and three Gemini-family models: `gemini-2.5-flash`, `gemini-2.5-flash-lite` and `gemini-3.5-flash`, the same models as the v0.1 pilot. Because the native API no longer serves the two 2.5 models to new projects, all three were reached through OpenRouter (upstream: Google), with temperature zero, model reasoning disabled and a common 1,024-token output limit; `gemini-3.5-flash` does not allow disabling reasoning there and was run at the minimum reasoning effort. Every recorded call used zero reasoning tokens, matching the thinking-off setting of the v0.1 pilot. The v0.2 run kept the v0.1 conditions, primary contrast, scoring rule and statistical analysis unchanged; only the benchmark and the access route differ. Hosted models can change behind a fixed name and temperature-zero decoding is not guaranteed to be deterministic, so exact reproduction rests on the archived raw responses rather than on re-querying. Each model receives identical evidence under direct, structured and explicit-situation prompts. A separate retrieval condition selects the top three claims by token overlap with the question and supplies their plain text, in time order but without timestamps or other metadata, to the direct-answer prompt; because no item has more than three claims, this condition differs from the direct prompt only in omitting that metadata. A tool-using agent condition follows a ReAct-style loop: the model may issue `search` queries over the item's claims, receives the matching claims, and then answers. Every request, raw response, normalized answer, token count, latency, failure and retry is retained. The completion gate joins records to the frozen sample, rejects missing or unexpected identifiers and requires 30 successful responses in every category for every requested model and condition. The reported run contains no failed calls and passes this gate. Scoring credits CLARIFY/ABSTAIN actions uniformly in plain text and JSON. Hidden-premise accuracy varies strongly with prompt format and evidence rendering (Extended Data Table 4); we do not interpret these differences further.

Accuracy contrasts use category-clustered bootstrap intervals (3,000 resamples, seed 20260726), treating the seven template categories as clusters. These intervals quantify sensitivity across the available template families, not population uncertainty over unrestricted questions. With only seven clusters the percentile intervals are approximate and can lie on a boundary (for example an upper bound of exactly zero), so they are reported descriptively rather than as significance tests. Cost summaries report provider token counts and measured request latency by condition. The bundled 12-item SituatedQA temporal sample is reported only as a smoke test; its size does not support a standalone inferential claim. Only the two date-anchored conditions (structured and situation) are compared there, because the direct prompt omits

the query date and is therefore not a matched control. The frozen manifest, model snapshots and cost accounting are in `code/experiment_manifest.e5.json`, and the audited run is reproduced with `python code/run_e5.py`.

The following larger confirmatory study is specified but has not been executed. It would compare these matched conditions: direct prompting; chain-of-thought or structured prompting; date-aware context; standard RAG; temporal or event-aware RAG; reflection or verification agent; and Situation Engineering. The generation model, evidence set, retrieval corpus, maximum context, output budget and sampling parameters should be held constant where the design permits. The minimum study uses two proprietary and two strong open-weight model families with immutable model identifiers; additional model families test robustness rather than substitute for balanced completion.

The primary intervention contrast must be *same model + same evidence + same computation budget* with versus without the explicit situation layer. A factorial analysis should independently vary prompt, context/retrieval, harness and situation state. Competitive conditions should include long-context prompting, few-shot structured reasoning, self-consistency, self-refinement, Self-RAG, graph or temporal retrieval, dialogue/belief-state tracking, clarification and calibrated abstention.

For each call, researchers should archive the prompt, evidence, raw response, normalized answer, action decision, model identifier, provider, execution date, latency, token use, monetary cost, errors and retries. Evaluation must report gold-state, predicted-state and deliberately corrupted-state conditions. The predicted-state condition should score entity/event extraction, temporal relations, validity intervals, scope, modality, source status, observer knowledge, possible-world identity and final answer. This enables error attribution to sensing, updating, policy or generation.

The natural bridge must include at least one independently constructed temporal or situated benchmark (for example SituatedQA, FreshQA or ChronoQA), with frozen item inclusion and scoring rules. Synthetic diagnostic, natural benchmark and model intervention are reported as separate evidence levels.

The bundled `code/run_multimodel_eval.py` provides provider adapters and refuses to create placeholder outputs when credentials are absent. In v0.1, where the decisive claim was always the newest, the no-metadata retrieval condition was the strongest (91.3%), an artefact that the balanced v0.2 benchmark removes. The v0.1 pilot, earlier quota-truncated free-tier attempts and aborted v0.2 attempts (substitute models and a free-tier native run stopped by its daily quota) remain archived but are excluded from every scientific aggregate. Only the complete records admitted by `code/audit_e5.py` enter the reported E5 tables. Together with E6 and E8 these runs cover seven model developers and one natural-text temporal study, but not the full natural-language confirmatory experiment specified below.

Pre-registered multi-family replication (E6) and LLM sensors (E7)

Both studies were pre-registered in the repository (`paper/PREREGISTRATION_E6_E7.md`) before any study call; the commit history timestamps the design and one amendment. E6 repeats E5 with identical code,

prompts, sample, decoding and conditions in three further developer families, reached through OpenRouter with reasoning disabled: `llama-4-maverick` (Meta), `deepseek-v4.1-flash` (DeepSeek) and `qwen3.8-flash` (Qwen), all with open weights. The amendment, made before any outcome was inspected, replaced the originally planned Anthropic and OpenAI models after the API credit ran out; proprietary families other than Gemini are therefore not covered. The pre-specified decision rule is that explicit situation prompting is said to improve on structured prompting only if the paired 95% cluster-bootstrap interval lies above zero in at least two of the three E6 families. A multi-family audit counts families by model developer and requires at least three.

E7 asks whether the sensing gap of the rule-based sensor is specific to it. An LLM receives exactly the rule sensor's inputs for each of the 210 sample items – the query time, the question and the claim texts, with no metadata – and returns the engine's state slots (event, actor, status, source, scope, observers, stated times and the user's region) from fixed vocabularies. The predicted state is passed unchanged to the SCQA engine, and slots are scored with the rule sensor's scorer, made case-insensitive and with actors matched by whole word for both sensors alike. An invalid output is retried once and then scored as a sensing failure. Claim texts contain no timestamps, so the time slot is unrecoverable by design for every sensor.

Two analyses were added after the data were seen and are reported as such. First, the pre-registered extractor parses a JSON answer only when the whole response is JSON and does not map a boolean answer to yes or no; Llama often wrote prose before its JSON or answered `"answer": false`. A sensitivity analysis (`code/sensitivity_rescore.py`) applies one more robust extractor – the last JSON object in the response, booleans mapped to yes/no – to every record of all six models alike, without altering the archived files; the pre-registered results remain primary. Second, E7's interpretation rule did not fit the data cleanly (the shortfall lay mainly in the unrecoverable time slot, yet claim-level cue-slot accuracy was 69–76%), so we report all pre-registered measures and add the split of end-to-end accuracy into temporal and other items. The multi-family audit was corrected before the analysis to count families by model developer rather than by the gateway that served them.

Pre-registered free-tier replication (E8a) and natural-text study (E8b)

This study had no funding, so E8 uses only zero-price OpenRouter endpoints; every successful call reports a cost of zero. The design (`paper/PREREGISTRATION_E8.md`) was committed before any study call, with one amendment made before any outcome was computed. E8a repeats E6 unchanged (direct, structured, situation and no-metadata retrieval; no agent) with `nemotron-3-ultra-550b-a55b` (NVIDIA), `dots-3-note-preview` (rednote hi lab) and `flint-v1.0` (Recursive), under E6's decision rule. The amendment replaced a planned model that was withdrawn mid-run; its partial records are archived and excluded. Flint's endpoint refuses to disable reasoning, so it ran with minimal reasoning effort, and its reasoning tokens share the 1,024-token output budget. Free endpoints impose a daily request quota; the runner stops without writing a record when it is reached and resumes on a later day, and

transient errors are retried until each item and condition has one success. Items are never imputed, substituted or dropped.

E8b samples 300 questions from the SituatedQA temporal test split [1] (75 per date type, fixed seed; upstream commit and file hash in the pre-registration) and asks two E8a models each question undated with the direct prompt and dated with the direct, structured and situation prompts. The date types are the dataset's collection year (which we use as the control), the start of an answer's validity, and a sampled year or date. A response is correct if it contains any gold answer as a whole word, which misses correct paraphrases in every condition alike. Contrasts use a bootstrap clustered on the upstream question (255 clusters, 3,000 resamples). The upstream repository states no licence, so question texts are not redistributed: archived records keep item identifiers and responses, and a script rebuilds the sample from a clone of the source.

One analysis was added after the data were seen and is labelled post hoc: a response that reaches the output limit is cut off, and when it is not valid JSON the pre-registered extractor falls back to the raw text, so a gold name that appears in the restated evidence can be credited. We therefore report how many responses reach the limit and the contrast on items where neither response does (`code/e8_truncation.py`); only Flint is affected (no more than one E8b response per model reaches the limit).

Prospective test designed to break benchmark–solver coupling

We pre-specify the next test rather than presenting simulated numbers as a completed experiment. An independent data team should sample naturally occurring questions from at least three domains, write evidence packs without access to the SCQA schema or solver, and freeze them before the systems team maps evidence into states. The crossed evaluation uses at least three genuinely independent model families (including an open-weight family), with identical evidence and matched token and tool budgets across direct, structured, temporal-retrieval, verification-agent and situation conditions. Items are split by scenario—not paraphrase—and held-out domains and generator authors are reported separately. Three blinded human annotators label answerability, answer, applicable evidence and required state slots; disagreements are adjudicated only after independent labels are frozen.

Supplementary Note 14 records the pre-specified strata, collection targets and split rules; it reports no outcome values, because none have been measured. The confirmatory claim would require a positive situation-versus-structured paired contrast whose scenario-clustered 95% interval excludes zero in at least two independent families, no material loss against temporal retrieval, and replication on the author-disjoint natural set. Human agreement, selective risk, latency, tokens and cost must be reported regardless of outcome. Until those gates are passed, generator–solver co-design, the absence of proprietary families beyond Gemini, of natural text and of human evaluation remain core limitations rather than prose-resolved concerns.

Generalization and efficiency protocol

External evaluation should pre-register held-out scenario families and test unseen templates, longer event chains, nested scopes, conflicting authoritative sources, multiple observers, multilingual questions and adversarial stale evidence. Splits must occur at scenario or generator-grammar level rather than over lexical variants. Uncertainty intervals should use scenario-clustered resampling. Each condition must report latency, input and output tokens, retrieval and tool calls, retries, monetary cost and clarification overhead. Accuracy gains without matched resource reporting cannot identify the effect of the situation layer.

Human and deployment evaluation

Human evaluation should use at least three independent annotators per natural item, blinded to method, with a documented adjudication procedure. Recommended outcomes include state-slot agreement, answer correctness, appropriateness of clarification or abstention, unnecessary clarification and perceived justification quality. Studies involving participants should report ethics approval or exemption, consent, compensation and privacy handling.

The released annotation program generates separately shuffled, blinded packets for three or more annotators. It requires complete independent labels before computing Fleiss' κ and unanimous agreement for action, answer and state slots; incomplete packets terminate with an error. Disagreements are adjudicated only after independent files are frozen. Blank blinded packets for a 70-item stratified subset are released under `paper/annotation_packets/`. No human agreement value is reported because independent human annotations were not collected. For software testing, a separate command generates three deterministic persona packets with injected disagreements. Its manifest and score output are marked `synthetic: true` and "NOT HUMAN-SUBJECT EVIDENCE"; those values are excluded from the manuscript's empirical claims.

Deployment studies should additionally measure state drift, invalidation latency, recovery after contradictory observations, action-precondition violations, security attacks on state metadata, throughput, tail latency, energy, token use and cost. The state and provenance required to audit a consequential decision should be retained subject to privacy and access-control requirements.

Reproducibility and reporting protocol

The package contains the generator, generated benchmark, reference implementation, predictions, figures, datasheet and exact commands. To make future systems comparable, authors should report: (1) the situation schema; (2) which variables are supplied, retrieved or inferred; (3) update and conflict semantics; (4) response and action policies; (5) provenance and observability; (6) stage-specific errors; (7) prompt, context, retrieval, memory, tool and harness configurations; and (8) resource costs. A machine-readable experiment manifest is recommended.

Ethics and use of generative AI

The controlled benchmark contains no personal records or human participants. Generative AI assisted drafting and software development. The author inspected the code, generated outputs, calculations and references and remains responsible for the manuscript. No empirical values were fabricated to represent unexecuted model calls or human studies.

Data availability

SituationCatch-Bench v0.2 is included in the public source repository at https://github.com/leemgs/sage and in the submission package as `paper/data/situationcatch_bench.jsonl`, together with its deterministic generator, datasheet and item-level outputs. This package is sufficient to reproduce the controlled results. The item-level raw responses of all language-model studies are under `paper/results/raw*`. SituatedQA question texts are not redistributed because the source states no licence; the archived E8b records keep item identifiers and responses, and `code/prepare_situatedqa_eval.py` rebuilds the sample from the public source. The exact reviewed version is identified by the Git commit or release tag supplied with the submission. Repository-owned materials are distributed under the MIT licence; third-party data retain their source licences. No unminted DOI is represented as an existing deposit.

Code availability

The complete executable implementation is included under `code/`. Running `python code/run_diagnostic.py` regenerates the benchmark and the data for Figs. 2–4, and `PYTHONPATH=code python code/run_experiments.py` regenerates gold-, predicted- and corrupted-state outputs, without network access or proprietary dependencies. The multi-model adapter records raw responses and errors and never creates synthetic API results. The annotation program requires three complete independent packets before reporting agreement and labels simulated-persona runs as synthetic rather than human evidence. Source and item-level outputs are also available at https://github.com/leemgs/sage. The repository README records exact commands; `SHA256SUMS.txt` records packaged artefact checksums. A public release tag should identify the reviewed version; no DOI is claimed unless an archive deposit has actually been minted.

Author Contributions

G.L.: Conceptualization, Formal analysis, Investigation, Methodology, Software, Validation, Visualization, Writing – original draft, Writing – review & editing.

Competing Interests

The author declares no competing interests.

Acknowledgements

The author received no specific funding for this work.

References

[1] Zhang, M. J. Q. & Choi, E. SituatedQA: incorporating extra-linguistic contexts into QA. In *Proc. EMNLP*, 7371–7387 (2021).

[2] Vu, T. et al. FreshLLMs: refreshing large language models with search engine augmentation. In *Findings of the Association for Computational Linguistics: ACL 2024*, 13697–13720 (2024).

[3] Meem, J., Rashid, M., Dong, Y. & Hristidis, V. PAT-Questions: a self-updating benchmark for present-anchored temporal question-answering. In *Findings of the Association for Computational Linguistics: ACL 2024*, 13129–13148 (2024).

[4] Chen, W., Wang, X. & Wang, W. Y. A dataset for answering time-sensitive questions. In *Proc. Neural Information Processing Systems Track on Datasets and Benchmarks* **1** (2021).

[5] Chen, Z. et al. A question answering dataset for temporal-sensitive retrieval-augmented generation (ChronoQA). *Sci. Data* **12**, 1855 (2025).

[6] Lewis, P. et al. Retrieval-augmented generation for knowledge-intensive NLP tasks. *Adv. Neural Inf. Process. Syst.* **33**, 9459–9474 (2020).

[7] Asai, A., Wu, Z., Wang, Y., Sil, A. & Hajishirzi, H. Self-RAG: learning to retrieve, generate, and critique through self-reflection. In *Proc. International Conference on Learning Representations* (2024).

[8] Yao, S. et al. ReAct: synergizing reasoning and acting in language models. In *Proc. International Conference on Learning Representations* (2023).

[9] Schick, T. et al. Toolformer: language models can teach themselves to use tools. *Adv. Neural Inf. Process. Syst.* **36**, 68539–68551 (2023).

[10] Mei, L. et al. A survey of context engineering for large language models. Preprint at https://arxiv.org/abs/2507.13334 (2025).

[11] Zhong, H. & Zhu, S. AI harness engineering: a runtime substrate for foundation-model software agents. Preprint at https://arxiv.org/abs/2605.13357 (2026).

[12] Lin, J. et al. Agentic harness engineering: observability-driven automatic evolution of coding-agent harnesses. Preprint at https://arxiv.org/abs/2604.25850 (2026).

[13] Kim, S., Wang, J., Xie, X. & Whang, S. E. Harnessing temporal databases for systematic evaluation of factual time-sensitive question answering in large language models. In *Proc. International Conference on Learning Representations* (2026).

[14] Barwise, J. & Perry, J. *Situations and Attitudes* (MIT Press, 1983).

[15] McCarthy, J. & Hayes, P. J. Some philosophical problems from the standpoint of artificial intelligence. In *Machine Intelligence 4* (eds Meltzer, B. & Michie, D.) 463–502 (Edinburgh Univ. Press, 1969).

[16] Kowalski, R. & Sergot, M. A logic-based calculus of events. *New Gener. Comput.* **4**, 67–95 (1986).

[17] Reiter, R. *Knowledge in Action: Logical Foundations for Specifying and Implementing Dynamical Systems* (MIT Press, 2001).

[18] Allen, J. F. Maintaining knowledge about temporal intervals. *Commun. ACM* **26**, 832–843 (1983).
[19] Alchourrón, C. E., Gärdenfors, P. & Makinson, D. On the logic of theory change: partial meet contraction and revision functions. *J. Symb. Logic* **50**, 510–530 (1985).
[20] Doyle, J. A truth maintenance system. *Artif. Intell.* **12**, 231–272 (1979).
[21] Kaelbling, L. P., Littman, M. L. & Cassandra, A. R. Planning and acting in partially observable stochastic domains. *Artif. Intell.* **101**, 99–134 (1998).
[22] Henderson, M., Thomson, B. & Williams, J. D. The second dialog state tracking challenge. In *Proc. SIGDIAL*, 263–272 (2014).
[23] Snodgrass, R. T. Temporal databases. In *Theories and Methods of Spatio-Temporal Reasoning in Geographic Space* (eds Frank, A. U., Campari, I. & Formentini, U.) Lecture Notes in Computer Science Vol. 639, 22–64 (Springer, 1992).
[24] van Benthem, J. Dynamic logic for belief revision. *J. Appl. Non-Classical Logics* **17**, 129–155 (2007).
[25] Stalnaker, R. Common ground. *Linguist. Philos.* **25**, 701–721 (2002).

Extended Data

Extended Data Table 1 Claim-level accuracy of the deterministic text sensor ($n = 7{,}800$ claims per slot).

Slot	Actor	Event	Time	Validity	Scope	Modality	Source	Observer	World
Accuracy (%)	30.8	92.3	0.0	0.0	61.5	100.0	30.8	92.3	100.0

Extended Data Table 2 E6 multi-family replication accuracy (open-weight Meta, DeepSeek and Qwen models) (%; $n = 210$ items, 30 per category) with 95% cluster-bootstrap confidence intervals (categories as clusters; 3000 resamples), the paired situation−structured contrast, and cost. A contrast interval that excludes zero is a directional estimate only within this bounded analysis.

Model	Direct	Structured	Situation	$\Delta_{\text{sit}-\text{str}}$	Sit. tokens
deepseek-v4.1 Flash	85.7	88.6	84.3	−4.3	336
95% CI	[64.3, 99.0]	[71.4, 100.0]	[62.4, 100.0]	[−11.9, +0.0]	
llama-4-maverick	82.9	72.4	91.9	+19.5	673
95% CI	[62.4, 99.0]	[54.3, 89.0]	[77.1, 100.0]	[+5.2, +36.2]	
qwen3.8 Flash	84.8	89.0	88.6	−0.5	371
95% CI	[61.4, 100.0]	[71.4, 100.0]	[65.7, 100.0]	[−9.0, +7.1]	

Extended Data Table 3 E8a free-tier replication accuracy (NVIDIA, rednote hi lab and Recursive models; Flint runs with minimal reasoning, whose tokens are included) (%; $n = 210$ items, 30 per category) with 95% cluster-bootstrap confidence intervals (categories as clusters; 3000 resamples), the paired situation−structured contrast, and cost. A contrast interval that excludes zero is a directional estimate only within this bounded analysis.

Model	Direct	Structured	Situation	$\Delta_{\text{sit}-\text{str}}$	Sit. tokens
dots-3-note	87.1	91.4	91.9	+0.5	273
95% CI	[69.0, 100.0]	[73.8, 100.0]	[74.3, 100.0]	[+0.0, +1.9]	
Nemotron-3-Ultra	91.0	91.9	85.2	−6.7	320
95% CI	[71.4, 100.0]	[74.3, 100.0]	[63.3, 100.0]	[−17.1, +0.0]	
Flint-v1.0	83.8	74.3	62.4	−11.9	1034
95% CI	[65.2, 97.6]	[56.7, 89.5]	[43.8, 81.9]	[−24.8, −1.0]	

Extended Data Table 4 Retrieval-augmented (RAG), full-evidence prompting, and a tool-using agent, mean accuracy over the three Gemini models on the $n = 210$ sample. RAG answers from the top-3 lexically retrieved claims, which for these items are all of the item's claims as plain text in time order without timestamps or other metadata; Structured and Situation see all claims with their metadata; Agent may issue its own search queries over the item's claims before answering. Descriptively, on the two categories that most require reasoning over the applicability state – temporal validity and observer knowledge – the full-evidence conditions score above both retrieval and the agent; this category-level pattern is exploratory, and none of the retrieval-, prompt-, or tool-based interventions dominates overall.

Category	RAG (no metadata)	Structured	Situation	Agent
Temporal	44.4	97.8	95.6	33.3
Observer	88.9	98.9	95.6	84.4
Counterfact.	100.0	97.8	85.6	77.8
Scope	100.0	94.4	98.9	94.4
Source confl.	90.0	100.0	86.7	80.0
Modality	62.2	74.4	63.3	82.2
Hidden prem.	70.0	41.1	31.1	44.4
Overall	79.4	86.3	79.5	71.0

Extended Data Table 5 Retrieval-augmented (RAG), full-evidence prompting, and a tool-using agent, mean accuracy over the three open-weight E6 models (Meta, DeepSeek, Qwen) on the $n = 210$ sample. RAG answers from the top-3 lexically retrieved claims, which for these items are all of the item's claims as plain text in time order without timestamps or other metadata; Structured and Situation see all claims with their metadata; Agent may issue its own search queries over the item's claims before answering. Pre-registered scoring. Without timestamps, temporal accuracy falls to 34.4% (23–50% per model) against 100% with them, as in E5. The Structured column is lowered by a scoring artefact for one model, whose prose-wrapped or boolean JSON answers the extractor misses (Methods); category comparisons are exploratory.

Category	RAG (no metadata)	Structured	Situation	Agent
Temporal	34.4	100.0	100.0	14.4
Observer	100.0	75.6	100.0	88.9
Counterfact.	100.0	95.6	100.0	95.6
Scope	100.0	84.4	100.0	100.0
Source confl.	95.6	100.0	100.0	84.4
Modality	60.0	84.4	81.1	96.7
Hidden prem.	31.1	43.3	36.7	58.9
Overall	74.4	83.3	88.3	77.0

Extended Data Table 6 Retrieval-augmented (RAG) and full-evidence prompting, mean accuracy over the three free-tier E8a models (NVIDIA, rednote hi lab, Recursive) on the $n = 210$ sample. RAG answers from the top-3 lexically retrieved claims, which for these items are all of the item's claims as plain text in time order without timestamps or other metadata; Structured and Situation see all claims with their metadata. Pre-registered H2: temporal accuracy without metadata is below structured temporal accuracy in each model (50.0–56.7% versus 96.7–100%; per-model values in `paper/results/e8_rag_by_model.json`).

Category	RAG (no metadata)	Structured	Situation
Temporal	52.2	98.9	96.7
Observer	94.4	94.4	80.0
Counterfact.	100.0	91.1	84.4
Scope	100.0	97.8	97.8
Source confl.	88.9	95.6	95.6
Modality	61.1	81.1	68.9
Hidden prem.	35.6	42.2	35.6
Overall	76.0	85.9	79.8

Extended Data Table 7 E7: LLMs as situation sensors on the $n = 210$ E5 items. Every sensor receives only the query time, question and claim texts; its state is passed unchanged to the SCQA engine. End-to-end is exact action-and-answer accuracy (%); the other columns are claim-level slot accuracy (%), scored identically for all sensors. Claim texts state no times, so Time is unrecoverable by design.

Sensor	End-to-end	Actor	Event	Scope	Modality	Source	Observer	World	Time
Rule-based	65.7	30.8	92.3	61.5	100.0	35.1	92.3	100.0	0.0
`deepseek-v4.1-flash`	87.1	79.7	98.7	47.2	96.7	58.5	84.6	47.9	0.0
`gemini-2.5-flash`	86.2	79.0	96.9	50.0	89.7	28.7	89.2	50.0	0.0
`llama-4-maverick`	79.0	66.4	89.2	50.3	94.9	54.6	83.1	54.1	0.0
`qwen3.8-flash`	84.8	64.4	91.5	62.8	92.6	55.1	84.6	80.0	0.0

Extended Data Table 8 E8b: natural-text temporal questions (SituatedQA test split, $n = 300$, 75 per date type; free model endpoints). Accuracy (%) for the undated question (Undated), the dated question with the same prompt (Dated), and the structured and situation prompts on the dated question. Contrasts are paired differences in percentage points with 95% bootstrap intervals clustered on the source question: situation−structured on all items (H1), and dated−undated on time-dependent items (H2, $n = 225$) and on control items dated at the dataset's collection year (Ctrl, $n = 75$).

Model	Undated	Dated	Struct.	Sit.	H1	H2	Ctrl
dots-3-note	30.0	45.7	45.0	49.7	+4.7	+22.2	−4.0
95% CI					[+0.0, +9.4]	[+15.5, +28.8]	[−13.3, +5.3]
Nemotron-3-Ultra	36.7	55.7	61.7	59.0	−2.7	+26.7	−4.0
95% CI					[−6.6, +1.0]	[+18.8, +34.0]	[−9.3, +0.0]