Status	Finished
Started	Wednesday, 28 October 2026, 10:29 PM
Completed	Wednesday, 28 October 2026, 10:39 PM
Duration	9 mins 40 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the output of the following Code?

str1="123456789"

print(str1[2:6:2])

Answer: 35 ✓

Question **2**

Correct

Mark 1.00 out of 1.00

What will be the output of below Python code?

```
str1="Information"
print(str1[2:8])
```

Answer: format ✓

Question **3**

Correct

Mark 1.00 out of 1.00

Strings are immutable?

Select one:

- True ✓
- False

Question **4**

Correct

Mark 1.00 out of 1.00

What is the output of “hello”+1+2+3 ?

a. hello6

b. Error ✓

c. hello123

d. hello

Question **5**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
print('Ab!2'.swapcase())
```

a. aB1@

b. ab12

c. aB!2 ✓

d. AB!@

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
str1='vijayakumar'
str2='.'
str3='---'
print(str1[-1:])
```

a. 'r' ✓

b. None of the above

c. vijayakuma

d. ramukayajiv

Question **7**

Correct

Mark 1.00 out of 1.00

What is the index value of ‘i’ in string “Learning”

a. 6

b. 3

c. 5 ✓

d. 7

Question **8**

Correct

Mark 1.00 out of 1.00

Which of the following are valid string manipulation functions in Python?

a. All of the mentioned ✓

b. strip()

c. count()

d. upper()

Question **9**

Correct

Mark 1.00 out of 1.00

Python considered the character enclosed in triple quotes as String.

Select one:

True ✓

False

Question **10**

Correct

Mark 1.00 out of 1.00

What is the output of the following?

```
i = 0
while i < 3:
        print(i)
        i += 1
else:
        print(0)
```

a. 0 1 2

b. 0 1 2 3 0

c. 0 1 2 0 ✓

d. Error

Question **11**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
line = "I'll come by then."
eline = ""
for i in line:
    eline += chr(ord(i)+3)
print(eline)
```

a. l*oo@frph@e|$wkhq1

b. L*oo#frph#e|#wkhq1 ✓

c. O*oo#Frph#E|#wKhq1

d. L*oo frph e| wkhq1

Question **12**

Correct

Mark 1.00 out of 1.00

What will the below Python code will return?

```
str1="save paper,save plants"
str1.find("save")
```

a. It returns the last index position of the first occurance of "save" in the given string str1.

b. It returns the first index position of the first occurance of "save" in the given string str1. ✓

c. It returns the first index position of the last occurance of "save" in the given string str1.

d. It returns the last index position of the last occurance of "save" in the given string str1.

Question **13**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
my_string = 'arvijayakumar'
for i in range(my_string):
    print(i)
```

a. arvjayakumar

b. 0 1 2 3 ... 12

1.

c. Error ✓

d. None

Question **14**

Correct

Mark 1.00 out of 1.00

What will be the output of the following code?

a = '2'

b = 4

print(a*b)

Answer: 2222 ✓

Question **15**

Correct

Mark 1.00 out of 1.00

What will be the output of the following code?

```
a = '2'
b = '1'
print(a+b)
```

Answer: 21 ✓

Status	Finished
Started	Thursday, 29 October 2026, 10:31 PM
Completed	Thursday, 29 October 2026, 10:47 PM
Duration	15 mins 56 secs
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Write a Python program to get one string and reverses a string. The input string is given as an array of characters `char[]` .

You may assume all the characters consist of printable ascii characters.

Example 1:

```
Input:
hello
Output:
olleh
```

Example 2:

```
Input:
Hannah
Output:
hannaH
```

Answer: (penalty regime: 0 %)

```
def reverse_string():
    # Read the input string and convert it into a list of characters char[]
    char_array = list(input())

    # Reverse the array in-place using Python's built-in reverse method
    char_array.reverse()

    # Print the reversed string
    print("".join(char_array))

if __name__ == "__main__":
    reverse_string()
```

	Input	Expected	Got	
✓	hello	olleh	olleh	✓
✓	Hannah	hannaH	hannaH	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **2**

Correct

Mark 1.00 out of 1.00

Given a **non-empty** string s and an abbreviation abbr, return whether the string matches with the given abbreviation.

A string such as "word" contains only the following valid abbreviations:

["word", "1ord", "w1rd", "wo1d", "wor1", "2rd", "w2d", "wo2", "1o1d", "1or1", "w1r1", "1o2", "2r1", "3d", "w3", "4"]

Notice that only the above abbreviations are valid abbreviations of the string "word". Any other string is not a valid abbreviation of "word".

Note:

Assume s contains only lowercase letters and abbr contains only lowercase letters and digits.

Example 1:

Input

internationalization
i12iz4n

Output

true

Explanation

Given **s** = "internationalization", **abbr** = "i12iz4n":

Return true.

Example 2:

Input

apple
a2e

Output

false

Explanation

Given **s** = "apple", **abbr** = "a2e":

Return false.

Answer: (penalty regime: 0 %)

```
import sys


def validWordAbbreviation(s: str, abbr: str) -> bool:
    i = 0  # Pointer for string s
    j = 0  # Pointer for string abbr

    while i < len(s) and j < len(abbr):
        if abbr[j].isdigit():
            # Leading zero rule: A number cannot start with '0'
            if abbr[j] == "0":
                return False

            num = 0
            # Parse the full multi-digit number
            while j < len(abbr) and abbr[j].isdigit():
                num = num * 10 + int(abbr[j])
                j += 1

            # Skip 'num' characters in s
            i += num
        else:
            # Characters must match
            if s[i] != abbr[j]:
                return False
            i += 1
            j += 1

    # Both pointers must reach the end
    return i == len(s) and j == len(abbr)


def main():
    input_data = sys.stdin.read().split()
    if not input_data:
        return

    s = input_data[0]
    abbr = input_data[1]

    if validWordAbbreviation(s, abbr):
        print("true")
    else:
        print("false")


if __name__ == "__main__":
    main()
```

	Input	Expected	Got	
✓	internationalization i12iz4n	true	true	✓

	Input	Expected	Got	
✓	apple a2e	false	false	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **3**

Correct

Mark 1.00 out of 1.00

Given a string s containing just the characters '(', ')', '{', '}', '[' and ']', determine if the input string is valid.

An input string is valid if:

Open brackets must be closed by the same type of brackets.

Open brackets must be closed in the correct order.

Constraints:

1 <= s.length <= 10^4

s consists of parentheses only '()[]{}'.

For example:

Test	Result
`print(ValidParenthesis("()"))`	`true`
`print(ValidParenthesis("()[]{}"))`	`true`
`print(ValidParenthesis("(]"))`	`false`

Answer: (penalty regime: 0 %)

Reset answer

```
def ValidParenthesis(s):
    stack = []
    bracket_map = {")": "(", "}": "{", "]": "["}

    for char in s:
        if char in bracket_map:
            top_element = stack.pop() if stack else "#"
            if bracket_map[char] != top_element:
                return "false"
        else:
            stack.append(char)

    return "true" if len(stack) == 0 else "false"
```

	Test	Expected	Got	
✓	`print(ValidParenthesis("()"))`	`true`	`true`	✓
✓	`print(ValidParenthesis("()[]{}"))`	`true`	`true`	✓
✓	`print(ValidParenthesis("(]"))`	`false`	`false`	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **4**

Correct

Mark 1.00 out of 1.00

A pangram is a sentence where every letter of the English alphabet appears at least once.

Given a string sentence containing only lowercase English letters, return true if sentence is a pangram, or false otherwise.

Example 1:

Input:

thequickbrownfoxjumpsoverthelazydog

Output:

true

Explanation: sentence contains at least one of every letter of the English alphabet.

Example 2:

Input:

arvijayakumar

Output: false

Constraints:

1 <= sentence.length <= 1000

sentence consists of lowercase English letters.

For example:

Test	Result
`print(checkPangram('thequickbrownfoxjumpsoverthelazydog'))`	`true`
`print(checkPangram('arvijayakumar'))`	`false`

Answer: (penalty regime: 0 %)

Reset answer

```
def checkPangram(s):
    # Returns True if all 26 unique lowercase English letters are present
    return len(set(s)) == 26


# If the testing platform expects lowercase string outputs directly:
def checkPangram(s):
    return "true" if len(set(s)) == 26 else "false"
```

	Test	Expected	Got	
✓	`print(checkPangram('thequickbrownfoxjumpsoverthelazydog'))`	`true`	`true`	✓
✓	`print(checkPangram('arvijayakumar'))`	`false`	`false`	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **5**

Correct

Mark 1.00 out of 1.00

The program must accept **N** series of keystrokes as string values as the input. The character **^** represents undo action to clear the last entered keystroke. The program must print the string typed after applying the undo operations as the output. If there are no characters in the string then print **-1** as the output.

Boundary Condition(s):

1 <= N <= 100
1 <= Length of each string <= 100

Input Format:

The first line contains the integer N.
The next N lines contain a string on each line.

Output Format:

The first N lines contain the string after applying the undo operations.

Example Input/Output 1:

Input:

3
Hey ^ goooo^^glee^
lucke^y ^charr^ms
ora^^nge^^^^

Output:

Hey google
luckycharms
-1

Answer: (penalty regime: 0 %)

```
import sys


def process_keystrokes(s):
    stack = []
    for char in s:
        if char == "^":
            if stack:
                stack.pop()
        else:
            stack.append(char)

    result = "".join(stack)
    return result if result else "-1"

```

```
16
17 def main():
18     input_data = sys.stdin.read().splitlines()
19     if not input_data:
20         return
21
22     n = int(input_data[0].strip())
23
24     for i in range(1, n + 1):
25         if i < len(input_data):
26             print(process_keystrokes(input_data[i]))
27
28
29 if __name__ == "__main__":
30     main()
```

	Input	Expected	Got	
✓	3 Hey ^ goooo^^glee^ lucke^y ^charr^ms ora^^nge^^^^	Hey google luckycharms -1	Hey google luckycharms -1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **6**

Correct

Mark 1.00 out of 1.00

Consider the below words as key words and check the given input is key word or not.

keywords: {break, case, continue, default, defer, else, for, func, goto, if, map, range, return, struct, type, var}

Input format:

Take string as an input from stdin.

Output format:

Print the word is key word or not.

Example Input:

break

Output:

break is a keyword

Example Input:

IF

Output:

IF is not a keyword

For example:

Input	Result
break	break is a keyword
IF	IF is not a keyword

Answer: (penalty regime: 0 %)

```
import sys


def check_keyword():
    # Set of keywords given in the problem statement
    keywords = {
        "break",
        "case",
        "continue",
        "default",
        "defer",
        "else",
        "for",
        "func",
        "goto",
        "if",
        "map",
        "range",
        "return",
        "struct",
        "type",
        "var",
    }

    # Read input from standard input
    input_data = sys.stdin.read().split()

    # Process each word from the input
    for word in input_data:
        if word in keywords:
```

```
            print(f"{word} is a keyword")
        else:
            print(f"{word} is not a keyword")


if __name__ == "__main__":
    check_keyword()
```

	Input	Expected	Got	
✓	break	break is a keyword	break is a keyword	✓
✓	IF	IF is not a keyword	IF is not a keyword	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **7**

Correct

Mark 1.00 out of 1.00

Assume that the given string has enough memory.

Don't use any extra space(IN-PLACE)

Sample Input 1

a2b4c6

Sample Output 1

aabbbbccccccc

Answer: (penalty regime: 0 %)

```
import sys


def expand_string(s):
    result = []
    i = 0
    n = len(s)

    while i < n:
        char = s[i]
        i += 1
        count = 0

        # Extract multi-digit numbers if present
        while i < n and s[i].isdigit():
            count = count * 10 + int(s[i])
            i += 1

        result.append(char * count)

    return "".join(result)


def main():
    input_data = sys.stdin.read().split()
    if input_data:
        print(expand_string(input_data[0]))


if __name__ == "__main__":
    main()
```

	Input	Expected	Got	
✓	a2b4c6	aabbbbccccccc	aabbbbccccccc	✓
✓	a12b3d4	aaaaaaaaaaaabbbdddd	aaaaaaaaaaaabbbdddd	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **8**

Correct

Mark 1.00 out of 1.00

Find if a String2 is substring of String1. If it is, return the index of the first occurrence. else return -1.

Sample Input 1

thistest123string

123

Sample Output 1

8

Answer: (penalty regime: 0 %)

```
import sys


def find_substring_index():
    # Read inputs from standard input
    input_data = sys.stdin.read().split()
    if len(input_data) < 2:
        return

    string1 = input_data[0]
    string2 = input_data[1]

    # str.find() returns the lowest index of the substring if found, otherwise -1
    index = string1.find(string2)

    print(index)


if __name__ == "__main__":
    find_substring_index()
```

	Input	Expected	Got	
✓	thistest123string 123	8	8	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **9**

Correct

Mark 1.00 out of 1.00

Given a string S which is of the format USERNAME@DOMAIN.EXTENSION, the program must print the EXTENSION, DOMAIN, USERNAME in the reverse order.

Input Format:

The first line contains S.

Output Format:

The first line contains EXTENSION.
The second line contains DOMAIN.
The third line contains USERNAME.

Boundary Condition:

1 <= Length of S <= 100

Example Input/Output 1:

Input:

abcd@gmail.com

Output:

com
gmail
abcd

For example:

Input	Result
arvijayakumar@rajalakshmi.edu.in	edu.in rajalakshmi arvijayakumar

Answer: (penalty regime: 0 %)

```
import sys


def parse_email():
    input_data = sys.stdin.read().split()
    if not input_data:
        return

    s = input_data[0]

    # Split the email at '@' into username and domain_with_extension
    username, domain_part = s.split("@", 1)

    # Split the domain_part at the first '.' to separate the domain name from the extension
    domain, extension = domain_part.split(".", 1)

    # Print in reverse order: EXTENSION, DOMAIN, USERNAME
    print(extension)
    print(domain)
    print(username)


if __name__ == "__main__":
```

```
24 |    parse_email()
```

	Input	Expected	Got	
✓	abcd@gmail.com	com gmail abcd	com gmail abcd	✓
✓	arvijayakumar@rajalakshmi.edu.in	edu.in rajalakshmi arvijayakumar	edu.in rajalakshmi arvijayakumar	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **10**

Correct

Mark 1.00 out of 1.00

Given a string, determine if it is a palindrome, considering only alphanumeric characters and ignoring cases.

Note: For the purpose of this problem, we define empty string as valid palindrome.

Example 1:

```
Input:
A man, a plan, a canal: Panama

Output:
1
```

Example 2:

```
Input:
race a car

Output:
0
```

Constraints:

- `s` consists only of printable ASCII characters.

Answer: (penalty regime: 0 %)

```
import sys


def isPalindrome(s: str) -> int:
    # Filter out non-alphanumeric characters and convert to lowercase
    filtered_chars = [char.lower() for char in s if char.isalnum()]

    # Check if the filtered list reads the same forward and backward
    if filtered_chars == filtered_chars[::-1]:
        return 1
    else:
        return 0


def main():
    # Read the input line from standard input
    input_data = sys.stdin.read().rstrip("\r\n")

    print(isPalindrome(input_data))


if __name__ == "__main__":
    main()
```

	Input	Expected	Got	
✓	A man, a plan, a canal: Panama	1	1	✓
✓	race a car	0	0	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.