Status	Finished
Started	Thursday, 29 October 2026, 10:58 PM
Completed	Thursday, 29 October 2026, 11:01 PM
Duration	2 mins 52 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which of the following is not the scope of variable?

a. Global
b. None of the mentioned
c. Local
d. Outside ✓

Question **2**

Correct

Mark 1.00 out of 1.00

What is the output of the following display() function call?

```
def display(**kwargs):
   for i in kwargs:
      print(i)
display(emp="Kelly", salary=9000)
```

a. Kelly
9000

b. TypeError

c. ('emp', 'Kelly')
('salary', 9000)

d. emp ✓
salary

Question **3**

Correct

Mark 1.00 out of 1.00

What will be the output of the following Python code?

```
def maximum(x, y):
    if x > y:
        return x
    elif x == y:
        return 'The numbers are equal'
    else:
        return y
print(maximum(2, 3))
```

- a. 3 ✓
- b. None of the mentioned
- c. 2
- d. The numbers are equal

Question **4**

Correct

Mark 1.00 out of 1.00

Which of the following function headers is correct?

- a. def fun(a, b, c = 3, d)
- b. def fun(a = 2, b, c = 3)
- c. def fun(a = 2, b = 3, c)
- d. def fun(a, b = 2, c = 3) ✓

Question **5**

Correct

Mark 1.00 out of 1.00

____ can be defined as a named group of instructions that accomplish a specific task when it is invoked/called.

- a. Operator
- b. Function ✓
- c. Token
- d. Datatype

Question **6**

Correct

Mark 1.00 out of 1.00

In a program, a function can be called ____ times.

- a. 5
- b. Multiple times ✓
- c. 3
- d. 2

Question **7**

Correct

Mark 1.00 out of 1.00

Python function always returns a value

Select one:

- True ✓
- False

Question **8**

Correct

Mark 1.00 out of 1.00

Which of the following is not the type of function argument?

- a. Required argument
- b. Keyword argument
- c. initial argument ✓
- d. default argument

Question **9**

Correct

Mark 1.00 out of 1.00

Which keyword is used for defining a function?

a. Function

b. Fun

c. Define

d. def ✓

Question **10**

Correct

Mark 1.00 out of 1.00

Which module is to be imported for using randint function?

a. rand

b. randomrange

c. randrange

d. random ✓

Question **11**

Correct

Mark 1.00 out of 1.00

def cal(n1) : What is n1?

a. None of the mentioned

b. Parameter ✓

c. Argument

d. Keyword

Question **12**

Correct

Mark 1.00 out of 1.00

Which of the following items are present in the function header?

- a. Both A and B ✓
- b. A. function name
- c. B. parameter list
- d. return value

Question **13**

Correct

Mark 1.00 out of 1.00

6. Which of the following is not the built-in function?

- a. dictionary( ) ✓
- b. print( )
- c. input( )
- d. tuple( )

Question **14**

Correct

Mark 1.00 out of 1.00

The function can be called in the program by writing function name followed by ____.

- a. { }
- b. ( ) ✓
- c. None of the mentioned
- d. [ ]

Question **15**

Correct

Mark 1.00 out of 1.00

What will be the output of the following Python code?

```
def printMax(a, b):
    if a > b:
        print(a, 'is maximum')
    elif a == b:
        print(a, 'is equal to', b)
    else:
        print(b, 'is maximum')
printMax(3, 4)
```

a. 4 is maximum ✓

b. 3

c. 4

d. None of the mentioned

Status	Finished
Started	Thursday, 29 October 2026, 10:50 PM
Completed	Thursday, 29 October 2026, 10:55 PM
Duration	5 mins 20 secs
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 2.00 out of 2.00

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: U = 2^a * 3^b * 5^c, where a, b and c are nonnegative integers.

For example:

Test	Result
`print(checkUgly(6))`	`ugly`
`print(checkUgly(21))`	`not ugly`

Answer: (penalty regime: 0 %)

Reset answer

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
def checkUgly(n):
    if n <= 0:
        return "not ugly"

    for factor in [2, 3, 5]:
        while n % factor == 0:
            n //= factor

    return "ugly" if n == 1 else "not ugly"
```

	Test	Expected	Got	
✓	`print(checkUgly(6))`	`ugly`	`ugly`	✓
✓	`print(checkUgly(21))`	`not ugly`	`not ugly`	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **2**

Correct

Mark 2.00 out of 2.00

A strobogrammatic number is a number that looks the same when rotated 180 degrees (looked at upside down).

Write a program to determine if a number is strobogrammatic. The number is represented as a string.

Example 1:

Input:

69

Output:

true

Example 2:

Input:

88

Output:

true

Example 3:

Input:

962

Output:

false

Example 4:

Input:

1

Output:

true

For example:

Test	Result
`print(Strobogrammatic(69))`	`True`
`print(Strobogrammatic(962))`	`False`

Answer: (penalty regime: 0 %)

Reset answer

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
def Strobogrammatic(n):
    # Convert input to string to handle both integer and string inputs
    num_str = str(n)

    # Dictionary mapping strobogrammatic pairs
    lookup = {"0": "0", "1": "1", "6": "9", "8": "8", "9": "6"}

    left = 0
    right = len(num_str) - 1

    while left <= right:
        # If the character is not valid or does not match its rotated counterpart
        if (
            num_str[left] not in lookup
            or lookup[num_str[left]] != num_str[right]
        ):
            return False
        left += 1
```

	Test	Expected	Got	
✓	print(Strobogrammatic(69))	True	True	✓
✓	print(Strobogrammatic(88))	True	True	✓
✓	print(Strobogrammatic(962))	False	False	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **3**

Correct

Mark 2.00 out of 2.00

An e-commerce company plans to give their customers a special discount for Christmas.

They are planning to offer a flat discount. The discount value is calculated as the sum of all

the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints

1 <= orderValue< 10e100000

Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
`print(christmasDiscount(578))`	`12`

Answer: (penalty regime: 0 %)

Reset answer

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
def christmasDiscount(n):
    # Set of prime digits (2, 3, 5, 7)
    prime_digits = {'2', '3', '5', '7'}

    # Calculate the sum of all prime digits in the given orderValue
    discount = sum(int(digit) for digit in str(n) if digit in prime_digits)

    return discount
```

	Test	Expected	Got	
✓	`print(christmasDiscount(578))`	12	12	✓
✓	`print(christmasDiscount(57))`	12	12	✓
✓	`print(christmasDiscount(222))`	6	6	✓
✓	`print(christmasDiscount(77777))`	35	35	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **4**

Correct

Mark 2.00 out of 2.00

Write a function that returns the value of a+aa+aaa+aaaa with a given digit as the value of a.

Suppose the following input is supplied to the program:

9

Then, the output should be:

9+99+999+9999=11106

Sample Input Format:

9

Sample Output format:

11106

For example:

Test	Result
`print(Summation(8))`	`9872`

Answer: (penalty regime: 0 %)

Reset answer

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
def Summation(n):
    # Convert digit to string to easily form 'a', 'aa', 'aaa', 'aaaa'
    a = str(n)

    # Compute the terms
    t1 = int(a)
    t2 = int(a * 2)
    t3 = int(a * 3)
    t4 = int(a * 4)

    # Return the sum of a + aa + aaa + aaaa
    return t1 + t2 + t3 + t4
```

	Test	Expected	Got	
✓	`print(Summation(8))`	`9872`	`9872`	✓
✓	`print(Summation(10))`	`10203040`	`10203040`	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **5**

Correct

Mark 2.00 out of 2.00

complete function to implement coin change making problem i.e. finding the minimum

number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer: (penalty regime: 0 %)

Reset answer

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
def coinChange(n):
    # Since the highest coin value is 4, we use a greedy approach:
    # 1. Take as many 4-value coins as possible (n // 4)
    # 2. Add 1 coin for any remaining amount (remainder 1, 2, or 3)
    return (n // 4) + (1 if n % 4 != 0 else 0)
```

	Test	Expected	Got	
✓	`print(coinChange(16))`	4	4	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.