

TASKS

Question:1

Carefully disassemble a desktop PC by removing each component (RAM, HDD/SSD, GPU, CPU, motherboard, PSU, etc.) in the correct order and take a clear photo of each part as you remove it?

Answer: I would carefully disassemble the desktop PC under proper supervision and document each component as it is removed.

Removal order:

RAM - Remove and photograph the RAM modules.

HDD/SSD - Remove the storage drive and take a clear photo.

GPU - Remove the graphics card and take a photo.

CPU Cooler - Remove the CPU cooling unit and photograph it.

CPU - Remove the processor carefully and take a clear photo.

Motherboard - Remove the motherboard and take photos.

PSU - Remove the power supply unit and take photos.

Question:2

Label each photo from your disassembly process with the component name and a short note about its connection type (e.g., SATA, PCIe, ATX power, DIMM slot)?

Answer: 1. Component Name: SATA Connector.

Connector Type: SATA

Note: Used to connect HDD/SSD to the motherboard for data transfer.

2. Component Name: PCIe Slot.

Connection Type: PCLE

Note: Used to connect expansion cards such as a graphics card.

3. Component Name: ATX Power Connector.

Connection Type: ATX Power

Note: Supplies power from the SMPS to the motherboard.

4. Component Name: DIMM Slot

Connection Type: ATX Power

Note: Used to install RAM on the motherboard.

Question:3

Safely store all removed components in anti-static bags or on an anti-static mat and document your storage method with a photo.

Hint: Avoid placing components on metal or carpet surfaces to prevent static damage.

Answer: All removed components should be stored safely in anti-static bags or on an anti-static mat. They should be kept away from metal and carpet surfaces to prevent electrostatic discharge (ESD). This helps protect sensitive components from damage. Take a clear photo of the stored components and attach it as proof.

Question:4

Reassemble the PC step-by-step, apply thermal paste to the CPU before installing the cooler, and photograph each major step?

Answer: 1. Switch off and unplug the PC from the power supply.

2. Open the CPU cabinet and remove the existing cooler and CPU carefully.

3. Clean the CPU surface and cooler using a soft, lint-free cloth.

4. Place the CPU correctly into the motherboard socket and lock it.

5. Apply a small amount of thermal paste (about pea-sized) to the center of the CPU.

6. Install the CPU cooler carefully and tighten the screws evenly.

7. Reconnect the cooler fan cable to the CPU_FAN header.
8. Reinstall the RAM, graphics card, storage devices, and other components.
9. Connect all power and data cables properly.
10. Close the cabinet, connect to the power supply, and switch on the PC.
11. Check that the PC starts properly, and the CPU temperature is normal.
12. Take photographs of each major step for documentation.

Question: 5

Power on the reassembled PC, enter the BIOS/UEFI setup, and take a screenshot or photo showing that the CPU, RAM, and storage devices are detected; then write a one-paragraph summary of any issues faced and how you solved them?

Answer: After reassembling the PC, I powered it on and entered the BIOS/UEFI setup. I checked the system information and confirmed that the CPU, RAM, and storage device were detected correctly. The CPU model and RAM capacity were displayed, and the storage drive was also recognized by the BIOS/UEFI. I did not face any major issues during the process. All components were properly connected, and the PC booted normally. This confirmed that the PC was successfully reassembled, and all the main hardware components were working properly.