ForceBalance Developer API Guide version 1.1

Generated by Doxygen 1.7.6.1

Contents

1 Project Roadmap **1**

1.1 Most Recently Implemented: . . . 1

1.2 Current Development Goals, for version 1.2.2: . . . 1

1.3 Longterm Development Ideas . . . 1

2 Todo List **1**

3 Namespace Index **3**

3.1 Packages . . . 3

4 Class Index **5**

4.1 Class Hierarchy . . . 5

5 Class Index **7**

5.1 Class List . . . 7

6 File Index **10**

6.1 File List . . . 10

7 Namespace Documentation **11**

7.1 forcebalance Namespace Reference . . . 11

7.1.1 Variable Documentation . . . 13

7.2 forcebalance::abinitio Namespace Reference . . . 13

7.2.1 Detailed Description . . . 13

7.2.2 Function Documentation . . . 13

7.2.3 Variable Documentation . . . 14

7.3 forcebalance::abinitio_internal Namespace Reference . . . 14

7.3.1 Detailed Description . . . 14

7.4 forcebalance::amberio Namespace Reference . . . 15

7.4.1 Detailed Description . . . 15

7.4.2 Function Documentation . . . 15

7.4.3 Variable Documentation . . . 16

7.5 forcebalance::binding Namespace Reference . . . 16

7.5.1 Detailed Description . . . 17

7.5.2 Function Documentation . . . 17

7.5.3 Variable Documentation . . . 17

7.6 forcebalance::chemistry Namespace Reference . . . 17

7.6.1 Function Documentation . . . 18

7.6.2 Variable Documentation . . . 18
7.7 forcebalance::contact Namespace Reference . . . 20
7.7.1 Function Documentation . . . 20
7.8 forcebalance::counterpoise Namespace Reference . . . 21
7.8.1 Detailed Description . . . 21
7.8.2 Variable Documentation . . . 22
7.9 forcebalance::custom_io Namespace Reference . . . 22
7.9.1 Detailed Description . . . 22
7.9.2 Variable Documentation . . . 23
7.10 forcebalance::engine Namespace Reference . . . 23
7.10.1 Variable Documentation . . . 23
7.11 forcebalance::finite_difference Namespace Reference . . . 24
7.11.1 Function Documentation . . . 24
7.11.2 Variable Documentation . . . 27
7.12 forcebalance::forcefield Namespace Reference . . . 27
7.12.1 Detailed Description . . . 28
7.12.2 Function Documentation . . . 29
7.12.3 Variable Documentation . . . 30
7.13 forcebalance::gmxio Namespace Reference . . . 30
7.13.1 Detailed Description . . . 31
7.13.2 Function Documentation . . . 32
7.13.3 Variable Documentation . . . 33
7.14 forcebalance::gmxqpio Namespace Reference . . . 35
7.14.1 Function Documentation . . . 35
7.14.2 Variable Documentation . . . 35
7.15 forcebalance::interaction Namespace Reference . . . 35
7.15.1 Detailed Description . . . 36
7.15.2 Variable Documentation . . . 36
7.16 forcebalance::leastsq Namespace Reference . . . 36
7.16.1 Function Documentation . . . 36
7.16.2 Variable Documentation . . . 36
7.17 forcebalance::liquid Namespace Reference . . . 37
7.17.1 Detailed Description . . . 37
7.17.2 Function Documentation . . . 37
7.17.3 Variable Documentation . . . 37
7.18 forcebalance::Mol2 Namespace Reference . . . 38
7.18.1 Variable Documentation . . . 38

7.19 forcebalance::mol2io Namespace Reference . . . 38
7.19.1 Detailed Description . . . 38
7.19.2 Variable Documentation . . . 39
7.20 forcebalance::molecule Namespace Reference . . . 39
7.20.1 Function Documentation . . . 40
7.20.2 Variable Documentation . . . 47
7.21 forcebalance::moments Namespace Reference . . . 50
7.21.1 Detailed Description . . . 50
7.21.2 Variable Documentation . . . 50
7.22 forcebalance::nifty Namespace Reference . . . 50
7.22.1 Detailed Description . . . 52
7.22.2 Function Documentation . . . 53
7.22.3 Variable Documentation . . . 65
7.23 forcebalance::objective Namespace Reference . . . 67
7.23.1 Detailed Description . . . 67
7.23.2 Variable Documentation . . . 67
7.24 forcebalance::openmmio Namespace Reference . . . 68
7.24.1 Detailed Description . . . 69
7.24.2 Function Documentation . . . 69
7.24.3 Variable Documentation . . . 73
7.25 forcebalance::optimizer Namespace Reference . . . 73
7.25.1 Detailed Description . . . 74
7.25.2 Function Documentation . . . 74
7.25.3 Variable Documentation . . . 74
7.26 forcebalance::output Namespace Reference . . . 75
7.27 forcebalance::parser Namespace Reference . . . 75
7.27.1 Detailed Description . . . 76
7.27.2 Function Documentation . . . 77
7.27.3 Variable Documentation . . . 79
7.28 forcebalance::psi4io Namespace Reference . . . 80
7.28.1 Detailed Description . . . 80
7.28.2 Variable Documentation . . . 81
7.29 forcebalance::PT Namespace Reference . . . 81
7.29.1 Variable Documentation . . . 81
7.30 forcebalance::qchemio Namespace Reference . . . 82
7.30.1 Detailed Description . . . 82
7.30.2 Function Documentation . . . 82

7.30.3 Variable Documentation . . . 83
7.31 forcebalance::target Namespace Reference . . . 83
7.31.1 Variable Documentation . . . 83
7.32 forcebalance::tinkerio Namespace Reference . . . 83
7.32.1 Detailed Description . . . 84
7.32.2 Function Documentation . . . 84
7.32.3 Variable Documentation . . . 85
7.33 forcebalance::vibration Namespace Reference . . . 86
7.33.1 Detailed Description . . . 86
7.33.2 Variable Documentation . . . 86

8 Class Documentation **86**
8.1 forcebalance.abinitio.AbInitio Class Reference . . . 86
8.1.1 Detailed Description . . . 90
8.1.2 Constructor & Destructor Documentation . . . 90
8.1.3 Member Function Documentation . . . 91
8.1.4 Member Data Documentation . . . 99
8.2 forcebalance.amberio.AbInitio_AMBER Class Reference . . . 104
8.2.1 Detailed Description . . . 108
8.2.2 Constructor & Destructor Documentation . . . 109
8.2.3 Member Function Documentation . . . 109
8.2.4 Member Data Documentation . . . 119
8.3 forcebalance.gmxio.AbInitio_GMX Class Reference . . . 124
8.3.1 Detailed Description . . . 128
8.3.2 Constructor & Destructor Documentation . . . 129
8.3.3 Member Function Documentation . . . 129
8.3.4 Member Data Documentation . . . 139
8.4 forcebalance.abinitio_internal.AbInitio_Internal Class Reference . . . 144
8.4.1 Detailed Description . . . 148
8.4.2 Constructor & Destructor Documentation . . . 149
8.4.3 Member Function Documentation . . . 149
8.4.4 Member Data Documentation . . . 158
8.5 forcebalance.openmmio.AbInitio_OpenMM Class Reference . . . 163
8.5.1 Detailed Description . . . 167
8.5.2 Constructor & Destructor Documentation . . . 168
8.5.3 Member Function Documentation . . . 168
8.5.4 Member Data Documentation . . . 177

8.6 forcebalance.tinkerio.AbInitio_TINKER Class Reference . . . 183
8.6.1 Detailed Description . . . 187
8.6.2 Constructor & Destructor Documentation . . . 187
8.6.3 Member Function Documentation . . . 187
8.6.4 Member Data Documentation . . . 197
8.7 forcebalance.forcefield.BackedUpDict Class Reference . . . 202
8.7.1 Detailed Description . . . 203
8.7.2 Constructor & Destructor Documentation . . . 203
8.7.3 Member Function Documentation . . . 203
8.7.4 Member Data Documentation . . . 203
8.8 forcebalance.BaseClass Class Reference . . . 203
8.8.1 Detailed Description . . . 204
8.8.2 Constructor & Destructor Documentation . . . 204
8.8.3 Member Function Documentation . . . 204
8.8.4 Member Data Documentation . . . 205
8.9 forcebalance.BaseReader Class Reference . . . 205
8.9.1 Detailed Description . . . 206
8.9.2 Constructor & Destructor Documentation . . . 206
8.9.3 Member Function Documentation . . . 206
8.9.4 Member Data Documentation . . . 208
8.10 forcebalance.binding.BindingEnergy Class Reference . . . 209
8.10.1 Detailed Description . . . 211
8.10.2 Constructor & Destructor Documentation . . . 211
8.10.3 Member Function Documentation . . . 211
8.10.4 Member Data Documentation . . . 217
8.11 forcebalance.tinkerio.BindingEnergy_TINKER Class Reference . . . 219
8.11.1 Detailed Description . . . 221
8.11.2 Constructor & Destructor Documentation . . . 221
8.11.3 Member Function Documentation . . . 222
8.11.4 Member Data Documentation . . . 228
8.12 forcebalance.output.CleanFileHandler Class Reference . . . 230
8.12.1 Detailed Description . . . 230
8.12.2 Member Function Documentation . . . 230
8.13 forcebalance.output.CleanStreamHandler Class Reference . . . 230
8.13.1 Detailed Description . . . 230
8.13.2 Constructor & Destructor Documentation . . . 230
8.13.3 Member Function Documentation . . . 231

8.14 forcebalance.counterpoise.Counterpoise Class Reference . . . 231
8.14.1 Detailed Description . . . 233
8.14.2 Constructor & Destructor Documentation . . . 233
8.14.3 Member Function Documentation . . . 233
8.14.4 Member Data Documentation . . . 240
8.15 forcebalance.engine.Engine Class Reference . . . 241
8.15.1 Detailed Description . . . 243
8.15.2 Constructor & Destructor Documentation . . . 243
8.15.3 Member Function Documentation . . . 244
8.15.4 Member Data Documentation . . . 244
8.16 forcebalance.forcefield.FF Class Reference . . . 245
8.16.1 Detailed Description . . . 247
8.16.2 Constructor & Destructor Documentation . . . 247
8.16.3 Member Function Documentation . . . 248
8.16.4 Member Data Documentation . . . 254
8.17 forcebalance.output.ForceBalanceLogger Class Reference . . . 257
8.17.1 Detailed Description . . . 258
8.17.2 Constructor & Destructor Documentation . . . 258
8.17.3 Member Function Documentation . . . 258
8.17.4 Member Data Documentation . . . 258
8.18 forcebalance.amberio.FrcMod_Reader Class Reference . . . 259
8.18.1 Detailed Description . . . 260
8.18.2 Constructor & Destructor Documentation . . . 260
8.18.3 Member Function Documentation . . . 260
8.18.4 Member Data Documentation . . . 261
8.19 forcebalance.psi4io.GBS_Reader Class Reference . . . 262
8.19.1 Detailed Description . . . 264
8.19.2 Constructor & Destructor Documentation . . . 264
8.19.3 Member Function Documentation . . . 264
8.19.4 Member Data Documentation . . . 266
8.20 forcebalance.custom_io.Gen_Reader Class Reference . . . 267
8.20.1 Detailed Description . . . 269
8.20.2 Constructor & Destructor Documentation . . . 269
8.20.3 Member Function Documentation . . . 269
8.20.4 Member Data Documentation . . . 270
8.21 forcebalance.gmxio.GMX Class Reference . . . 271
8.21.1 Detailed Description . . . 273

8.21.2 Constructor & Destructor Documentation . . . 273
8.21.3 Member Function Documentation . . . 274
8.21.4 Member Data Documentation . . . 276
8.22 forcebalance.psi4io.Grid_Reader Class Reference . . . 277
8.22.1 Detailed Description . . . 278
8.22.2 Constructor & Destructor Documentation . . . 278
8.22.3 Member Function Documentation . . . 278
8.22.4 Member Data Documentation . . . 280
8.23 forcebalance.interaction.Interaction Class Reference . . . 281
8.23.1 Detailed Description . . . 284
8.23.2 Constructor & Destructor Documentation . . . 284
8.23.3 Member Function Documentation . . . 284
8.23.4 Member Data Documentation . . . 291
8.24 forcebalance.gmxio.Interaction_GMX Class Reference . . . 293
8.24.1 Detailed Description . . . 296
8.24.2 Constructor & Destructor Documentation . . . 296
8.24.3 Member Function Documentation . . . 297
8.24.4 Member Data Documentation . . . 304
8.25 forcebalance.openmmio.Interaction_OpenMM Class Reference . . . 306
8.25.1 Detailed Description . . . 309
8.25.2 Constructor & Destructor Documentation . . . 309
8.25.3 Member Function Documentation . . . 310
8.25.4 Member Data Documentation . . . 316
8.26 forcebalance.tinkerio.Interaction_TINKER Class Reference . . . 318
8.26.1 Detailed Description . . . 321
8.26.2 Constructor & Destructor Documentation . . . 321
8.26.3 Member Function Documentation . . . 322
8.26.4 Member Data Documentation . . . 328
8.27 forcebalance.gmxio.ITP_Reader Class Reference . . . 330
8.27.1 Detailed Description . . . 332
8.27.2 Constructor & Destructor Documentation . . . 333
8.27.3 Member Function Documentation . . . 333
8.27.4 Member Data Documentation . . . 334
8.28 forcebalance.leastsq.LeastSquares Class Reference . . . 336
8.28.1 Detailed Description . . . 338
8.28.2 Constructor & Destructor Documentation . . . 338
8.28.3 Member Function Documentation . . . 338

8.28.4 Member Data Documentation . . . 344
8.29 forcebalance.nifty.LineChunker Class Reference . . . 346
8.29.1 Detailed Description . . . 346
8.29.2 Constructor & Destructor Documentation . . . 346
8.29.3 Member Function Documentation . . . 346
8.29.4 Member Data Documentation . . . 347
8.30 forcebalance.liquid.Liquid Class Reference . . . 347
8.30.1 Detailed Description . . . 349
8.30.2 Constructor & Destructor Documentation . . . 350
8.30.3 Member Function Documentation . . . 350
8.30.4 Member Data Documentation . . . 357
8.31 forcebalance.gmxio.Liquid_GMX Class Reference . . . 360
8.31.1 Detailed Description . . . 363
8.31.2 Constructor & Destructor Documentation . . . 363
8.31.3 Member Function Documentation . . . 363
8.31.4 Member Data Documentation . . . 370
8.32 forcebalance.openmmio.Liquid_OpenMM Class Reference . . . 374
8.32.1 Detailed Description . . . 376
8.32.2 Constructor & Destructor Documentation . . . 376
8.32.3 Member Function Documentation . . . 377
8.32.4 Member Data Documentation . . . 384
8.33 forcebalance.tinkerio.Liquid_TINKER Class Reference . . . 388
8.33.1 Detailed Description . . . 390
8.33.2 Constructor & Destructor Documentation . . . 390
8.33.3 Member Function Documentation . . . 390
8.33.4 Member Data Documentation . . . 398
8.34 forcebalance.Mol2.mol2 Class Reference . . . 401
8.34.1 Detailed Description . . . 402
8.34.2 Constructor & Destructor Documentation . . . 402
8.34.3 Member Function Documentation . . . 402
8.34.4 Member Data Documentation . . . 406
8.35 forcebalance.Mol2.mol2_atom Class Reference . . . 407
8.35.1 Detailed Description . . . 408
8.35.2 Constructor & Destructor Documentation . . . 408
8.35.3 Member Function Documentation . . . 408
8.35.4 Member Data Documentation . . . 410
8.36 forcebalance.Mol2.mol2_bond Class Reference . . . 411

8.36.1 Detailed Description . . . 412
8.36.2 Constructor & Destructor Documentation . . . 412
8.36.3 Member Function Documentation . . . 412
8.36.4 Member Data Documentation . . . 414
8.37 forcebalance.amberio.Mol2_Reader Class Reference . . . 414
8.37.1 Detailed Description . . . 416
8.37.2 Constructor & Destructor Documentation . . . 416
8.37.3 Member Function Documentation . . . 416
8.37.4 Member Data Documentation . . . 417
8.38 forcebalance.mol2io.Mol2_Reader Class Reference . . . 418
8.38.1 Detailed Description . . . 419
8.38.2 Constructor & Destructor Documentation . . . 420
8.38.3 Member Function Documentation . . . 420
8.38.4 Member Data Documentation . . . 421
8.39 forcebalance.Mol2.mol2_set Class Reference . . . 422
8.39.1 Detailed Description . . . 422
8.39.2 Constructor & Destructor Documentation . . . 422
8.39.3 Member Function Documentation . . . 422
8.39.4 Member Data Documentation . . . 423
8.40 forcebalance.molecule.Molecule Class Reference . . . 423
8.40.1 Detailed Description . . . 426
8.40.2 Constructor & Destructor Documentation . . . 426
8.40.3 Member Function Documentation . . . 426
8.40.4 Member Data Documentation . . . 442
8.41 forcebalance.molecule.MolfileTimestep Class Reference . . . 444
8.41.1 Detailed Description . . . 444
8.42 forcebalance.moments.Moments Class Reference . . . 444
8.42.1 Detailed Description . . . 446
8.42.2 Constructor & Destructor Documentation . . . 446
8.42.3 Member Function Documentation . . . 447
8.42.4 Member Data Documentation . . . 453
8.43 forcebalance.tinkerio.Moments_TINKER Class Reference . . . 455
8.43.1 Detailed Description . . . 457
8.43.2 Constructor & Destructor Documentation . . . 458
8.43.3 Member Function Documentation . . . 458
8.43.4 Member Data Documentation . . . 466
8.44 forcebalance.gmxqpio.Monomer_QTPIE Class Reference . . . 467

8.44.1 Detailed Description . . . 469
8.44.2 Constructor & Destructor Documentation . . . 470
8.44.3 Member Function Documentation . . . 470
8.44.4 Member Data Documentation . . . 477
8.45 forcebalance.objective.Objective Class Reference . . . 478
8.45.1 Detailed Description . . . 480
8.45.2 Constructor & Destructor Documentation . . . 480
8.45.3 Member Function Documentation . . . 480
8.45.4 Member Data Documentation . . . 481
8.46 forcebalance.openmmio.OpenMM_Reader Class Reference . . . 482
8.46.1 Detailed Description . . . 483
8.46.2 Constructor & Destructor Documentation . . . 484
8.46.3 Member Function Documentation . . . 484
8.46.4 Member Data Documentation . . . 485
8.47 forcebalance.optimizer.Optimizer Class Reference . . . 486
8.47.1 Detailed Description . . . 489
8.47.2 Constructor & Destructor Documentation . . . 489
8.47.3 Member Function Documentation . . . 489
8.47.4 Member Data Documentation . . . 495
8.48 forcebalance.objective.Penalty Class Reference . . . 497
8.48.1 Detailed Description . . . 498
8.48.2 Constructor & Destructor Documentation . . . 498
8.48.3 Member Function Documentation . . . 498
8.48.4 Member Data Documentation . . . 500
8.49 forcebalance.nifty.Pickler_LP Class Reference . . . 501
8.49.1 Detailed Description . . . 501
8.49.2 Constructor & Destructor Documentation . . . 501
8.50 forcebalance.qchemio.QCIn_Reader Class Reference . . . 502
8.50.1 Detailed Description . . . 503
8.50.2 Constructor & Destructor Documentation . . . 503
8.50.3 Member Function Documentation . . . 503
8.50.4 Member Data Documentation . . . 504
8.51 forcebalance.output.RawFileHandler Class Reference . . . 506
8.51.1 Detailed Description . . . 506
8.51.2 Member Function Documentation . . . 506
8.52 forcebalance.output.RawStreamHandler Class Reference . . . 506
8.52.1 Detailed Description . . . 507

8.52.2 Constructor & Destructor Documentation . . . 507
8.52.3 Member Function Documentation . . . 507
8.53 forcebalance.psi4io.RDVR3_Psi4 Class Reference . . . 507
8.53.1 Detailed Description . . . 510
8.53.2 Constructor & Destructor Documentation . . . 510
8.53.3 Member Function Documentation . . . 510
8.53.4 Member Data Documentation . . . 516
8.54 forcebalance.target.RemoteTarget Class Reference . . . 518
8.54.1 Detailed Description . . . 520
8.54.2 Constructor & Destructor Documentation . . . 520
8.54.3 Member Function Documentation . . . 520
8.54.4 Member Data Documentation . . . 526
8.55 forcebalance.target.Target Class Reference . . . 527
8.55.1 Detailed Description . . . 529
8.55.2 Constructor & Destructor Documentation . . . 530
8.55.3 Member Function Documentation . . . 531
8.55.4 Member Data Documentation . . . 537
8.56 forcebalance.psi4io.THCDF_Psi4 Class Reference . . . 538
8.56.1 Detailed Description . . . 540
8.56.2 Constructor & Destructor Documentation . . . 541
8.56.3 Member Function Documentation . . . 541
8.56.4 Member Data Documentation . . . 548
8.57 forcebalance.tinkerio.Tinker_Reader Class Reference . . . 550
8.57.1 Detailed Description . . . 551
8.57.2 Constructor & Destructor Documentation . . . 552
8.57.3 Member Function Documentation . . . 552
8.57.4 Member Data Documentation . . . 553
8.58 forcebalance.nifty.Unpickler_LP Class Reference . . . 554
8.58.1 Detailed Description . . . 554
8.58.2 Constructor & Destructor Documentation . . . 554
8.59 forcebalance.vibration.Vibration Class Reference . . . 555
8.59.1 Detailed Description . . . 557
8.59.2 Constructor & Destructor Documentation . . . 557
8.59.3 Member Function Documentation . . . 558
8.59.4 Member Data Documentation . . . 564
8.60 forcebalance.tinkerio.Vibration_TINKER Class Reference . . . 565
8.60.1 Detailed Description . . . 566

8.60.2 Constructor & Destructor Documentation . . . 566
8.60.3 Member Function Documentation . . . 567

9 File Documentation **567**

9.1 __init__.py File Reference . . . 567
9.2 abinitio.py File Reference . . . 568
9.3 abinitio_internal.py File Reference . . . 568
9.4 amberio.py File Reference . . . 569
9.5 api.dox File Reference . . . 569
9.6 binding.py File Reference . . . 569
9.7 chemistry.py File Reference . . . 570
9.8 contact.py File Reference . . . 570
9.9 counterpoise.py File Reference . . . 570
9.10 custom_io.py File Reference . . . 571
9.11 engine.py File Reference . . . 571
9.12 finite_difference.py File Reference . . . 572
9.13 forcefield.py File Reference . . . 572
9.14 gmxio.py File Reference . . . 573
9.15 gmxqpio.py File Reference . . . 574
9.16 interaction.py File Reference . . . 574
9.17 leastsq.py File Reference . . . 575
9.18 liquid.py File Reference . . . 575
9.19 Mol2.py File Reference . . . 576
9.20 mol2io.py File Reference . . . 576
9.21 molecule.py File Reference . . . 576
9.22 moments.py File Reference . . . 578
9.23 nifty.py File Reference . . . 578
9.24 objective.py File Reference . . . 581
9.25 openmmio.py File Reference . . . 581
9.26 optimizer.py File Reference . . . 582
9.27 output.py File Reference . . . 583
9.28 parser.py File Reference . . . 583
9.29 psi4io.py File Reference . . . 584
9.30 PT.py File Reference . . . 584
9.31 qchemio.py File Reference . . . 585
9.32 target.py File Reference . . . 585
9.33 tinkerio.py File Reference . . . 585

9.34 vibration.py File Reference 586

1 Project Roadmap

ForceBalance is a work in progress and is continually being improved and expanded! Here are some current and future project development ideas.

Some notes on updating the version:

The formalism for the version number goes something like this:

v1.2.1[ab][1-9]-123

where:

- 1.2.1 stands for major release (may break compatibility), medium-sized release (important features), minor release (improvements)
- a or b, if present, stands for alpha or beta release, with numbers standing for the n-th alpha or beta release
- -123 stands for the number of commits that follow the manually specified release.

To manually specify a release, create a tag and push it to the remote repository: git tag -a v1.2.1 -m "version 1.2.1" git push --tags

The version number should then be automatically generated by "git describe" which is run by setup.py at installation.

Finally, remember to update the version number in the documentation generation scripts!

1.1 Most Recently Implemented:

- Implementing and expanding support for running target calculations in parallel across multiple nodes
- Development of a ForceBalance GUI interface to complement the current command line interface
- Expand unit test cases to provide more thorough coverage of forcebalance modules

1.2 Current Development Goals, for version 1.2.2:

- More comprehensive tutorial to walk users through the initial process of setting up targets and preparing for a successful ForceBalance run

1.3 Longterm Development Ideas

- Visualization of running calculations

2 Todo List

Member forcebalance.abinitio.AbInitio.__init__

Obtain the number of true atoms (or the particle -> atom mapping) from the force field.

Member forcebalance.abinitio.AbInitio.get_energy_force_

Parallelization over snapshots is not implemented yet

Member forcebalance.abinitio.AbInitio.read_reference_data

Add an option for picking any slice out of qdata.txt, helpful for cross-validation

Closer integration of reference data with program - leave behind the qdata.txt format? (For now, I like the readability of qdata.txt)

The WHAM Boltzmann weights are generated by external scripts (wanalyze.py and make-wham-data.sh) and passed in; perhaps these scripts can be added to the ForceBalance distribution or integrated more tightly.

Closer integration of reference data with program - leave behind the qdata.txt format? (For now, I like the readability of qdata.txt)

The WHAM Boltzmann weights are generated by external scripts (wanalyze.py and make-wham-data.sh) and passed in; perhaps these scripts can be added to the ForceBalance distribution or integrated more tightly.

Closer integration of reference data with program - leave behind the qdata.txt format? (For now, I like the readability of qdata.txt)

The WHAM Boltzmann weights are generated by external scripts (wanalyze.py and make-wham-data.sh) and passed in; perhaps these scripts can be added to the ForceBalance distribution or integrated more tightly.

Closer integration of reference data with program - leave behind the qdata.txt format? (For now, I like the readability of qdata.txt)

The WHAM Boltzmann weights are generated by external scripts (wanalyze.py and make-wham-data.sh) and passed in; perhaps these scripts can be added to the ForceBalance distribution or integrated more tightly.

Closer integration of reference data with program - leave behind the qdata.txt format? (For now, I like the readability of qdata.txt)

The WHAM Boltzmann weights are generated by external scripts (wanalyze.py and make-wham-data.sh) and passed in; perhaps these scripts can be added to the ForceBalance distribution or integrated more tightly.

Closer integration of reference data with program - leave behind the qdata.txt format? (For now, I like the readability of qdata.txt)

The WHAM Boltzmann weights are generated by external scripts (wanalyze.py and make-wham-data.sh) and passed in; perhaps these scripts can be added to the ForceBalance distribution or integrated more tightly.

Member forcebalance.counterpoise.Counterpoise.loadxyz

I should probably put this into a more general library for reading coordinates.

Member forcebalance.forcefield.FF.mktransmat

Only project out changes in total charge of a molecule, and perhaps generalize to fragments of molecules or other types of parameters.

The AMOEBA selection of charge depends not only on the atom type, but what that atom is bonded to.

Member forcebalance.forcefield.FF.rsmake

Pass in rsfactors through the input file

Class forcebalance.gmxio.ITP_Reader

Note that I can also create the opposite virtual site position by changing the atom labeling, woo!

Member forcebalance.openmmio.OpenMM_Reader.build_pid

Add a link here

Member forcebalance.optimizer.Optimizer.GeneticAlgorithm

Massive parallelization hasn't been implemented yet

Member forcebalance.optimizer.Optimizer.Scan_Values

Maybe a multidimensional grid can be done.

Member forcebalance.tinkerio.Tinker_Reader.feed

Put the rescaling factors for TINKER parameters in here. Currently we're using the initial value to determine the rescaling factor which is not very good.

Namespace forcebalance::gmxio

Even more stuff from forcefield.py needs to go into here.

Even more stuff from forcefield.py needs to go into here.

Member forcebalance::gmxio.pdict

This needs to become more flexible because the parameter isn't always in the same field. Still need to figure out how to do this.

How about making the PDIHS less ugly?

Member forcebalance::nifty.floatornan

I could use suggestions for making this better.

Member forcebalance::parser.parse_inputs

Implement internal coordinates.

Implement sampling correction.

Implement charge groups.

3 Namespace Index

3.1 Packages

Here are the packages with brief descriptions (if available):

forcebalance 11

forcebalance::abinitio
Ab-initio fitting module (energies, forces, resp) 13

forcebalance::abinitio_internal
Internal implementation of energy matching (for TIP3P water only) 14

forcebalance::amberio
AMBER force field input/output 15

forcebalance::binding
Binding energy fitting module 16

forcebalance::chemistry 17

forcebalance::contact 20

forcebalance::counterpoise
Match an empirical potential to the counterpoise correction for basis set superposition error (BSSE) 21

forcebalance::custom_io
Custom force field parser 22

forcebalance::engine 23

forcebalance::finite_difference 24

forcebalance::forcefield
Force field module 27

forcebalance::gmxio
GROMACS input/output 30

forcebalance::gmxqpio 35

forcebalance::interaction
Interaction energy fitting module 35

forcebalance::leastsq 36

forcebalance::liquid
Matching of liquid bulk properties 37

forcebalance::Mol2 38

forcebalance::mol2io
Mol2 I/O 38

forcebalance::molecule 39

forcebalance::moments
Multipole moment fitting module 50

forcebalance::nifty
Nifty functions, intended to be imported by any module within ForceBalance 50

forcebalance::objective
ForceBalance objective function 67

forcebalance::openmmio
OpenMM input/output 68

forcebalance::optimizer
Optimization algorithms 73

forcebalance::output 75

forcebalance::parser
Input file parser for ForceBalance jobs 75

forcebalance::psi4io
PSI4 force field input/output 80

forcebalance::PT 81

forcebalance::qchemio
Q-Chem input file parser 82

forcebalance::target 83

forcebalance::tinkerio
TINKER input/output 83

forcebalance::vibration
Vibrational mode fitting module 86

4 Class Index

4.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

- **forcebalance.forcefield.BackedUpDict** 202
- **forcebalance.BaseClass** 203
  - **forcebalance.engine.Engine** 241
    - **forcebalance.gmxio.GMX** 271
  - **forcebalance.forcefield.FF** 245
  - **forcebalance.objective.Objective** 478
  - **forcebalance.optimizer.Optimizer** 486
  - **forcebalance.target.Target** 527
    - **forcebalance.abinitio.AbInitio** 86
      - **forcebalance.abinitio_internal.AbInitio_Internal** 144
      - **forcebalance.amberio.AbInitio_AMBER** 104
      - **forcebalance.gmxio.AbInitio_GMX** 124
      - **forcebalance.openmmio.AbInitio_OpenMM** 163
      - **forcebalance.tinkerio.AbInitio_TINKER** 183
    - **forcebalance.binding.BindingEnergy** 209
      - **forcebalance.tinkerio.BindingEnergy_TINKER** 219
    - **forcebalance.counterpoise.Counterpoise** 231
    - **forcebalance.gmxqpio.Monomer_QTPIE** 467
    - **forcebalance.interaction.Interaction** 281
      - **forcebalance.gmxio.Interaction_GMX** 293
      - **forcebalance.openmmio.Interaction_OpenMM** 306
      - **forcebalance.tinkerio.Interaction_TINKER** 318
    - **forcebalance.leastsq.LeastSquares** 336
      - **forcebalance.psi4io.THCDF_Psi4** 538
    - **forcebalance.liquid.Liquid** 347
      - **forcebalance.gmxio.Liquid_GMX** 360

forcebalance.openmmio.Liquid_OpenMM 374

forcebalance.tinkerio.Liquid_TINKER 388

forcebalance.moments.Moments 444

forcebalance.tinkerio.Moments_TINKER 455

forcebalance.psi4io.RDVR3_Psi4 507

forcebalance.target.RemoteTarget 518

forcebalance.vibration.Vibration 555

forcebalance.BaseReader 205

forcebalance.amberio.FrcMod_Reader 259

forcebalance.amberio.Mol2_Reader 414

forcebalance.custom_io.Gen_Reader 267

forcebalance.gmxio.ITP_Reader 330

forcebalance.mol2io.Mol2_Reader 418

forcebalance.openmmio.OpenMM_Reader 482

forcebalance.psi4io.GBS_Reader 262

forcebalance.psi4io.Grid_Reader 277

forcebalance.qchemio.QCIn_Reader 502

forcebalance.tinkerio.Tinker_Reader 550

forcebalance.output.CleanFileHandler 230

forcebalance.output.CleanStreamHandler 230

forcebalance.output.ForceBalanceLogger 257

forcebalance.nifty.LineChunker 346

forcebalance.Mol2.mol2 401

forcebalance.Mol2.mol2_atom 407

forcebalance.Mol2.mol2_bond 411

forcebalance.Mol2.mol2_set 422

forcebalance.molecule.Molecule 423

forcebalance.molecule.MolfileTimestep 444

forcebalance.objective.Penalty 497

forcebalance.nifty.Pickler_LP 501

forcebalance.output.RawFileHandler 506

forcebalance.output.RawStreamHandler 506

forcebalance.nifty.Unpickler_LP 554

forcebalance.tinkerio.Vibration_TINKER 565

5 Class Index

5.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

forcebalance.abinitio.AbInitio
Subclass of Target for fitting force fields to ab initio data 86

forcebalance.amberio.AbInitio_AMBER
Subclass of Target for force and energy matching using AMBER 104

forcebalance.gmxio.AbInitio_GMX
Subclass of AbInitio for force and energy matching using normal GROMACS 124

forcebalance.abinitio_internal.AbInitio_Internal
Subclass of Target for force and energy matching using an internal implementation 144

forcebalance.openmmio.AbInitio_OpenMM
Subclass of AbInitio for force and energy matching using OpenMM 163

forcebalance.tinkerio.AbInitio_TINKER
Subclass of Target for force and energy matching using TINKER 183

forcebalance.forcefield.BackedUpDict 202

forcebalance.BaseClass
Provides some nifty functions that are common to all ForceBalance classes 203

forcebalance.BaseReader
The 'reader' class 205

forcebalance.binding.BindingEnergy
Improved subclass of Target for fitting force fields to binding energies 209

forcebalance.tinkerio.BindingEnergy_TINKER
Subclass of BindingEnergy for binding energy matching using TINKER 219

forcebalance.output.CleanFileHandler
File handler that does not write terminal escape codes and carriage returns to files 230

forcebalance.output.CleanStreamHandler
Similar to RawStreamHandler except it does not write terminal escape codes 230

forcebalance.counterpoise.Counterpoise
Target subclass for matching the counterpoise correction 231

forcebalance.engine.Engine
Base class for all engines 241

forcebalance.forcefield.FF
Force field class 245

forcebalance.output.ForceBalanceLogger
This logger starts out with a default handler that writes to stdout addHandler removes this default the first time another handler is added 257

forcebalance.amberio.FrcMod_Reader
Finite state machine for parsing FrcMod force field file 259

forcebalance.psi4io.GBS_Reader
Interaction type -> Parameter Dictionary 262

forcebalance.custom_io.Gen_Reader
Finite state machine for parsing custom GROMACS force field files 267

forcebalance.gmxio.GMX
Derived from Engine object for carrying out general purpose GROMACS calculations 271

forcebalance.psi4io.Grid_Reader
Finite state machine for parsing DVR grid files 277

forcebalance.interaction.Interaction
Subclass of Target for fitting force fields to interaction energies 281

forcebalance.gmxio.Interaction_GMX
Subclass of Interaction for interaction energy matching using GROMACS 293

forcebalance.openmmio.Interaction_OpenMM
Subclass of Target for interaction matching using OpenMM 306

forcebalance.tinkerio.Interaction_TINKER
Subclass of Target for interaction matching using TINKER 318

forcebalance.gmxio.ITP_Reader
Finite state machine for parsing GROMACS force field files 330

forcebalance.leastsq.LeastSquares
Subclass of Target for general least squares fitting 336

forcebalance.nifty.LineChunker 346

forcebalance.liquid.Liquid
Subclass of Target for liquid property matching 347

forcebalance.gmxio.Liquid_GMX 360

forcebalance.openmmio.Liquid_OpenMM 374

forcebalance.tinkerio.Liquid_TINKER 388

forcebalance.Mol2.mol2
This is to manage one mol2 series of lines on the form: 401

forcebalance.Mol2.mol2_atom
This is to manage mol2 atomic lines on the form: 1 C1 5.4790 42.2880 49.5910 C.ar 1 <1> 0.0424 407

forcebalance.Mol2.mol2_bond
This is to manage mol2 bond lines on the form: 1 1 2 ar 411

forcebalance.amberio.Mol2_Reader
Finite state machine for parsing Mol2 force field file 414

forcebalance.mol2io.Mol2_Reader
Finite state machine for parsing Mol2 force field file 418

forcebalance.Mol2.mol2_set 422

forcebalance.molecule.Molecule
Lee-Ping's general file format conversion class 423

forcebalance.molecule.MolfileTimestep
Wrapper for the timestep C structure used in molfile plugins 444

forcebalance.moments.Moments
Subclass of Target for fitting force fields to multipole moments (from experiment or theory) 444

forcebalance.tinkerio.Moments_TINKER
Subclass of Target for multipole moment matching using TINKER 455

forcebalance.gmxqpio.Monomer_QTPIE
Subclass of Target for monomer properties of QTPIE (implemented within gromacs WCV branch) 467

forcebalance.objective.Objective
Objective function 478

forcebalance.openmmio.OpenMM_Reader
Class for parsing OpenMM force field files 482

forcebalance.optimizer.Optimizer
Optimizer class 486

forcebalance.objective.Penalty
Penalty functions for regularizing the force field optimizer 497

forcebalance.nifty.Pickler_LP
A subclass of the python Pickler that implements pickling of _ElementTree types 501

forcebalance.qchemio.QCIn_Reader
Finite state machine for parsing Q-Chem input files 502

forcebalance.output.RawFileHandler
Exactly like output.FileHandler except it does no extra formatting before sending logging messages to the file 506

forcebalance.output.RawStreamHandler
Exactly like output.StreamHandler except it does no extra formatting before sending logging messages to the stream 506

forcebalance.psi4io.RDVR3_Psi4
Subclass of Target for R-DVR3 grid fitting 507

forcebalance.target.RemoteTarget 518

forcebalance.target.Target
Base class for all fitting targets 527

forcebalance.psi4io.THCDF_Psi4 538

forcebalance.tinkerio.Tinker_Reader
Finite state machine for parsing TINKER force field files 550

forcebalance.nifty.Unpickler_LP
A subclass of the python Unpickler that implements unpickling of _ElementTree types 554

forcebalance.vibration.Vibration
Subclass of Target for fitting force fields to vibrational spectra (from experiment or theory) 555

forcebalance.tinkerio.Vibration_TINKER
Subclass of Target for vibrational frequency matching using TINKER 565

6 File Index

6.1 File List

Here is a list of all files with brief descriptions:

__init__.py 567

abinitio.py 568

abinitio_internal.py 568

amberio.py 569

binding.py 569

chemistry.py 570

contact.py 570

counterpoise.py 570

custom_io.py 571

engine.py 571

finite_difference.py 572

forcefield.py 572

gmxio.py 573

gmxqpio.py 574

interaction.py 574

leastsq.py 575

liquid.py 575

Mol2.py 576

mol2io.py 576

molecule.py 576

moments.py 578

nifty.py 578

objective.py 581

openmmio.py 581

optimizer.py 582

output.py 583

parser.py 583

psi4io.py 584

PT.py 584

qchemio.py 585

target.py 585

tinkerio.py 585

vibration.py 586

7 Namespace Documentation

7.1 forcebalance Namespace Reference

Packages

- namespace abinitio

  Ab-initio fitting module (energies, forces, resp).
- namespace abinitio_internal

  Internal implementation of energy matching (for TIP3P water only)
- namespace amberio

  AMBER force field input/output.
- namespace binding

  Binding energy fitting module.
- namespace chemistry
- namespace contact
- namespace counterpoise

Match an empirical potential to the counterpoise correction for basis set superposition error (BSSE).

- namespace custom_io

  Custom force field parser.
- namespace engine
- namespace finite_difference
- namespace forcefield

  Force field module.
- namespace gmxio

  GROMACS input/output.
- namespace gmxqpio
- namespace interaction

  Interaction energy fitting module.
- namespace leastsq
- namespace liquid

  Matching of liquid bulk properties.
- namespace Mol2
- namespace mol2io

  Mol2 I/O.
- namespace molecule
- namespace moments

  Multipole moment fitting module.
- namespace nifty

  Nifty functions, intended to be imported by any module within ForceBalance.
- namespace objective

  ForceBalance objective function.
- namespace openmmio

  OpenMM input/output.
- namespace optimizer

  Optimization algorithms.
- namespace output
- namespace parser

  Input file parser for ForceBalance jobs.
- namespace psi4io

  PSI4 force field input/output.
- namespace PT
- namespace qchemio

  Q-Chem input file parser.
- namespace target
- namespace tinkerio

  TINKER input/output.
- namespace vibration

  Vibrational mode fitting module.

Classes

- class BaseClass

  Provides some nifty functions that are common to all ForceBalance classes.
- class BaseReader

  The 'reader' class.

Variables

- tuple __version__ = pkg_resources.get_distribution("forcebalance")

7.1.1 Variable Documentation

7.1.1.1 string forcebalance::__version__ = pkg_resources.get_distribution("forcebalance")

Definition at line 17 of file __init__.py.

7.2 forcebalance::abinitio Namespace Reference

Ab-initio fitting module (energies, forces, resp).

Classes

- class AbInitio
  Subclass of Target for fitting force fields to ab initio data.

Functions

- def weighted_variance
  A more generalized version of build_objective which is callable for derivatives, but the covariance is not there anymore.
- def weighted_variance2
  A bit of a hack, since we have to subtract out two mean quantities to get Hessian elements.
- def build_objective
  This function builds an objective function (number) from the complicated polytensor and covariance matrices.

Variables

- tuple logger = getLogger(__name__)

7.2.1 Detailed Description

Ab-initio fitting module (energies, forces, resp).

Author

Lee-Ping Wang

Date

05/2012

7.2.2 Function Documentation

7.2.2.1 def forcebalance.abinitio.build_objective (*SPiXi, WCiW, Z, Q0, M0, NCP1, subtract_mean* = `True`)

This function builds an objective function (number) from the complicated polytensor and covariance matrices.

Definition at line 1156 of file abinitio.py.

7.2.2.2 def forcebalance.abinitio.weighted_variance (*SPiXi, WCiW, Z, L, R, NCP1, subtract_mean* = `True`)

A more generalized version of build_objective which is callable for derivatives, but the covariance is not there anymore.

Definition at line 1126 of file abinitio.py.

Here is the call graph for this function:

7.2.2.3 def forcebalance.abinitio.weighted_variance2 (*SPiXi, WCiW, Z, L, R, L2, R2, NCP1, subtract_mean* = `True`)

A bit of a hack, since we have to subtract out two mean quantities to get Hessian elements.

Definition at line 1140 of file abinitio.py.

Here is the call graph for this function:

7.2.3 Variable Documentation

7.2.3.1 tuple forcebalance::abinitio::logger = getLogger(__name__)

Definition at line 24 of file abinitio.py.

7.3 forcebalance::abinitio_internal Namespace Reference

Internal implementation of energy matching (for TIP3P water only)

Classes

- class AbInitio_Internal

  Subclass of Target for force and energy matching using an internal implementation.

7.3.1 Detailed Description

Internal implementation of energy matching (for TIP3P water only)

Author

Lee-Ping Wang

Date

04/2012

7.4 forcebalance::amberio Namespace Reference

AMBER force field input/output.

Classes

- class Mol2_Reader

  Finite state machine for parsing Mol2 force field file.
- class FrcMod_Reader

  Finite state machine for parsing FrcMod force field file.
- class AbInitio_AMBER

  Subclass of Target for force and energy matching using AMBER.

Functions

- def is_mol2_atom

Variables

- tuple logger = getLogger(__name__)
- dictionary mol2_pdict = {'COUL':{'Atom':[1], 8:''}}
- dictionary frcmod_pdict

7.4.1 Detailed Description

AMBER force field input/output. This serves as a good template for writing future force matching I/O modules for other programs because it's so simple.

Author

Lee-Ping Wang

Date

01/2012

7.4.2 Function Documentation

7.4.2.1 def forcebalance.amberio.is_mol2_atom (*line*)

Definition at line 35 of file amberio.py.

Here is the call graph for this function:

7.4.3 Variable Documentation

7.4.3.1 dictionary forcebalance::amberio::frcmod_pdict

Initial value:

```
{'BONDS': {'Atom':[0], 1:'K', 2:'B'},
                 'ANGLES':{'Atom':[0], 1:'K', 2:'B'},
                 'PDIHS1':{'Atom':[0], 2:'K', 3:'B'},
                 'PDIHS2':{'Atom':[0], 2:'K', 3:'B'},
                 'PDIHS3':{'Atom':[0], 2:'K', 3:'B'},
                 'PDIHS4':{'Atom':[0], 2:'K', 3:'B'},
                 'PDIHS5':{'Atom':[0], 2:'K', 3:'B'},
                 'PDIHS6':{'Atom':[0], 2:'K', 3:'B'},
                 'IDIHS' :{'Atom':[0], 1:'K', 3:'B'},
                  'VDW':{'Atom':[0], 1:'S', 2:'T'}
                  }
```

Definition at line 23 of file amberio.py.

7.4.3.2 tuple forcebalance::amberio::logger = getLogger(__name__)

Definition at line 19 of file amberio.py.

7.4.3.3 dictionary forcebalance::amberio::mol2_pdict = {'COUL':{'Atom':[1], 8:''}}

Definition at line 21 of file amberio.py.

7.5 forcebalance::binding Namespace Reference

Binding energy fitting module.

Classes

- class BindingEnergy

  Improved subclass of Target for fitting force fields to binding energies.

Functions

- def parse_interactions

  Parse through the interactions input file.

Variables

- tuple logger = getLogger(__name__)

7.5.1 Detailed Description

Binding energy fitting module.

Author

Lee-Ping Wang

Date

05/2012

7.5.2 Function Documentation

7.5.2.1 def forcebalance.binding.parse_interactions (*input_file*)

Parse through the interactions input file.

Parameters

in	*input_file*	The name of the input file.

Definition at line 31 of file binding.py.

Here is the call graph for this function:

7.5.3 Variable Documentation

7.5.3.1 tuple forcebalance::binding::logger = getLogger(__name__)

Definition at line 23 of file binding.py.

7.6 forcebalance::chemistry Namespace Reference

Functions

- def LookupByMass
- def BondStrengthByLength

Variables

- tuple BondEnergies = defaultdict(lambda:defaultdict(dict))

- list Radii

  Covalent radii from Cordero et al.
- dictionary PeriodicTable
- list Elements
- list BondChars = ['-','=','3']
- string data_from_web
- tuple line = line.expandtabs()
- tuple BE = float(line.split()[1])
- tuple L = float(line.split()[2])
- tuple atoms = re.split('[-=3]', line.split()[0])
- list A = atoms[0]
- list B = atoms[1]
- tuple bo = BondChars.index(re.findall('[-=3]', line.split()[0])[0])

7.6.1 Function Documentation

7.6.1.1 def forcebalance.chemistry.BondStrengthByLength (*A, B, length, artol* = 0.33, *bias* = 0.0)

Definition at line 164 of file chemistry.py.

7.6.1.2 def forcebalance.chemistry.LookupByMass (*mass*)

Definition at line 155 of file chemistry.py.

7.6.2 Variable Documentation

7.6.2.1 list forcebalance::chemistry::A = atoms[0]

Definition at line 149 of file chemistry.py.

7.6.2.2 tuple forcebalance::chemistry::atoms = re.split('[-=3]', line.split()[0])

Definition at line 148 of file chemistry.py.

7.6.2.3 list forcebalance::chemistry::B = atoms[1]

Definition at line 150 of file chemistry.py.

7.6.2.4 tuple forcebalance::chemistry::BE = float(line.split()[1])

Definition at line 146 of file chemistry.py.

7.6.2.5 tuple forcebalance::chemistry::bo = BondChars.index(re.findall('[-=3]', line.split()[0])[0])

Definition at line 151 of file chemistry.py.

7.6.2.6 list forcebalance::chemistry::BondChars = ['-','=','3']

Definition at line 49 of file chemistry.py.

7.6.2.7 tuple forcebalance::chemistry::BondEnergies = defaultdict(lambda:defaultdict(dict))

Definition at line 7 of file chemistry.py.

7.6.2.8 string forcebalance::chemistry::data_from_web

Definition at line 51 of file chemistry.py.

7.6.2.9 list forcebalance::chemistry::Elements

Initial value:

```
["None",'H','He',
            'Li','Be','B','C','N','O','F','Ne',
            'Na','Mg','Al','Si','P','S','Cl','Ar',
            'K','Ca','Sc','Ti','V','Cr','Mn','Fe','Co','Ni','Cu','Zn','Ga','Ge'
      ,'As','Se','Br','Kr',
            'Rb','Sr','Y','Zr','Nb','Mo','Tc','Ru','Rh','Pd','Ag','Cd','In','Sn
      ','Sb','Te','I','Xe',
            'Cs','Ba','La','Ce','Pr','Nd','Pm','Sm','Eu','Gd','Tb','Dy','Ho','
      Er','Tm','Yb',
            'Lu','Hf','Ta','W','Re','Os','Ir','Pt','Au','Hg','Tl','Pb','Bi','Po
      ','At','Rn',
            'Fr','Ra','Ac','Th','Pa','U','Np','Pu','Am','Cm','Bk','Cf','Es','Fm
      ','Md','No','Lr','Rf','Db','Sg','Bh','Hs','Mt']
```

Definition at line 40 of file chemistry.py.

7.6.2.10 tuple forcebalance::chemistry::L = float(line.split()[2])

Definition at line 147 of file chemistry.py.

7.6.2.11 tuple forcebalance::chemistry::line = line.expandtabs()

Definition at line 145 of file chemistry.py.

7.6.2.12 dictionary forcebalance::chemistry::PeriodicTable

Initial value:

```
{'H' : 1.0079, 'He' : 4.0026,
                 'Li' : 6.941, 'Be' : 9.0122, 'B' : 10.811, 'C' : 12.0107, 'N'
      : 14.0067, 'O' : 15.9994, 'F' : 18.9984, 'Ne' : 20.1797,
                 'Na' : 22.9897, 'Mg' : 24.305, 'Al' : 26.9815, 'Si' : 28.0855,
       'P' : 30.9738, 'S' : 32.065, 'Cl' : 35.453, 'Ar' : 39.948,
                 'K' : 39.0983, 'Ca' : 40.078, 'Sc' : 44.9559, 'Ti' : 47.867, '
      V' : 50.9415, 'Cr' : 51.9961, 'Mn' : 54.938, 'Fe' : 55.845, 'Co' : 58.9332,
                 'Ni' : 58.6934, 'Cu' : 63.546, 'Zn' : 65.39, 'Ga' : 69.723, '
      Ge' : 72.64, 'As' : 74.9216, 'Se' : 78.96, 'Br' : 79.904, 'Kr' : 83.8,
                 'Rb' : 85.4678, 'Sr' : 87.62, 'Y' : 88.9059, 'Zr' : 91.224, '
      Nb' : 92.9064, 'Mo' : 95.94, 'Tc' : 98, 'Ru' : 101.07, 'Rh' : 102.9055,
                 'Pd' : 106.42, 'Ag' : 107.8682, 'Cd' : 112.411, 'In' : 114.818
      , 'Sn' : 118.71, 'Sb' : 121.76, 'Te' : 127.6, 'I' : 126.9045, 'Xe' : 131.293,
                 'Cs' : 132.9055, 'Ba' : 137.327, 'La' : 138.9055, 'Ce' : 140.1
      16, 'Pr' : 140.9077, 'Nd' : 144.24, 'Pm' : 145, 'Sm' : 150.36,
                 'Eu' : 151.964, 'Gd' : 157.25, 'Tb' : 158.9253, 'Dy' : 162.5,
      'Ho' : 164.9303, 'Er' : 167.259, 'Tm' : 168.9342, 'Yb' : 173.04,
                  'Lu' : 174.967, 'Hf' : 178.49, 'Ta' : 180.9479, 'W' : 183.84,
      'Re' : 186.207, 'Os' : 190.23, 'Ir' : 192.217, 'Pt' : 195.078,
                  'Au' : 196.9665, 'Hg' : 200.59, 'Tl' : 204.3833, 'Pb' : 207.2,
       'Bi' : 208.9804, 'Po' : 209, 'At' : 210, 'Rn' : 222,
                  'Fr' : 223, 'Ra' : 226, 'Ac' : 227, 'Th' : 232.0381, 'Pa' : 23
      1.0359, 'U' : 238.0289, 'Np' : 237, 'Pu' : 244,
                  'Am' : 243, 'Cm' : 247, 'Bk' : 247, 'Cf' : 251, 'Es' : 252, '
      Fm' : 257, 'Md' : 258, 'No' : 259,
                  'Lr' : 262, 'Rf' : 261, 'Db' : 262, 'Sg' : 266, 'Bh' : 264, '
      Hs' : 277, 'Mt' : 268}
```

Definition at line 25 of file chemistry.py.

7.6.2.13 list forcebalance::chemistry::Radii

Initial value:

```
[0.31, 0.28, # H and He
          1.28, 0.96, 0.84, 0.76, 0.71, 0.66, 0.57, 0.58, # First row elements
          1.66, 1.41, 1.21, 1.11, 1.07, 1.05, 1.02, 1.06, # Second row elements
          2.03, 1.76, 1.70, 1.60, 1.53, 1.39, 1.61, 1.52, 1.50,
          1.24, 1.32, 1.22, 1.22, 1.20, 1.19, 1.20, 1.20, 1.16, # Third row
       elements, K through Kr
          2.20, 1.95, 1.90, 1.75, 1.64, 1.54, 1.47, 1.46, 1.42,
          1.39, 1.45, 1.44, 1.42, 1.39, 1.39, 1.38, 1.39, 1.40, # Fourth row
       elements, Rb through Xe
          2.44, 2.15, 2.07, 2.04, 2.03, 2.01, 1.99, 1.98,
          1.98, 1.96, 1.94, 1.92, 1.92, 1.89, 1.90, 1.87, # Fifth row elements,
       s and f blocks
           1.87, 1.75, 1.70, 1.62, 1.51, 1.44, 1.41, 1.36,
           1.36, 1.32, 1.45, 1.46, 1.48, 1.40, 1.50, 1.50, # Fifth row elements,
       d and p blocks
           2.60, 2.21, 2.15, 2.06, 2.00, 1.96, 1.90, 1.87, 1.80, 1.69]
```

Covalent radii from Cordero et al.

'Covalent radii revisited' Dalton Transactions 2008, 2832-2838.

Definition at line 10 of file chemistry.py.

7.7 forcebalance::contact Namespace Reference

Functions

- def atom_distances

  For each frame in xyzlist, compute the (euclidean) distance between pairs of atoms whos indices are given in contacts.
- def residue_distances

  For each frame in xyzlist, and for each pair of residues in the array contact, compute the distance between the closest pair of atoms such that one of them belongs to each residue.

7.7.1 Function Documentation

7.7.1.1 def forcebalance.contact.atom_distances (*xyzlist, atom_contacts*)

For each frame in xyzlist, compute the (euclidean) distance between pairs of atoms whos indices are given in contacts.

xyzlist should be a traj_length x num_atoms x num_dims array of type float32

contacts should be a num_contacts x 2 array where each row gives the indices of 2 atoms whos distance you care to monitor.

Returns: traj_length x num_contacts array of euclidean distances

Note: For nice wrappers around this, see the prepare_trajectory method of various metrics in metrics.py

Definition at line 27 of file contact.py.

Here is the call graph for this function:

7.7.1.2 def forcebalance.contact.residue_distances (*xyzlist, residue_membership, residue_contacts*)

For each frame in xyzlist, and for each pair of residues in the array contact, compute the distance between the closest pair of atoms such that one of them belongs to each residue.

xyzlist should be a traj_length x num_atoms x num_dims array of type float32

residue_membership should be a list of lists where residue_membership[i] gives the list of atomindices that belong to residue i. residue_membership should NOT be a numpy 2D array unless you really mean that all of the residues have the same number of atoms

residue_contacts should be a 2D numpy array of shape num_contacts x 2 where each row gives the indices of the two RESIDUES who you are interested in monitoring for a contact.

Returns: a 2D array of traj_lenth x num_contacts where out[i,j] contains the distance between the pair of atoms, one from residue_membership[residue_contacts[j,0]] and one from residue_membership[residue_contacts[j,1]] that are closest.

Definition at line 86 of file contact.py.

7.8 forcebalance::counterpoise Namespace Reference

Match an empirical potential to the counterpoise correction for basis set superposition error (BSSE).

Classes

- class Counterpoise

  Target subclass for matching the counterpoise correction.

Variables

- tuple logger = getLogger(__name__)

7.8.1 Detailed Description

Match an empirical potential to the counterpoise correction for basis set superposition error (BSSE). Here we test two different functional forms: a three-parameter Gaussian repulsive potential and a four-parameter Gaussian which goes smoothly to an exponential. The latter can be written in two different ways - one which gives us control over the exponential, the switching distance and the Gaussian decay constant, and another which gives us control over the Gaussian and the switching distance. They are called 'CPGAUSS', 'CPEXPG', and 'CPGEXP'. I think the third option is the best although our early tests have indicated that none of the force fields perform particularly well for the water dimer.

This subclass of Target implements the 'get' method.

Author

Lee-Ping Wang

Date

12/2011

7.8.2 Variable Documentation

7.8.2.1 tuple forcebalance::counterpoise::logger = getLogger(__name__)

Definition at line 29 of file counterpoise.py.

7.9 forcebalance::custom_io Namespace Reference

Custom force field parser.

Classes

- class Gen_Reader

  Finite state machine for parsing custom GROMACS force field files.

Variables

- list cptypes = [None, 'CPGAUSS', 'CPEXPG', 'CPGEXP']

  Types of counterpoise correction.
- list ndtypes = [None]

  Types of NDDO correction.
- dictionary fdict

  Section -> Interaction type dictionary.
- dictionary pdict

  Interaction type -> Parameter Dictionary.

7.9.1 Detailed Description

Custom force field parser. We take advantage of the sections in GROMACS and the 'interaction type' concept, but these interactions are not supported in GROMACS; rather, they are computed within our program.

Author

Lee-Ping Wang

Date

12/2011

7.9.2 Variable Documentation

7.9.2.1 list forcebalance::custom_io::cptypes = [None, 'CPGAUSS', 'CPEXPG', 'CPGEXP']

Types of counterpoise correction.

Definition at line 16 of file custom_io.py.

7.9.2.2 dictionary forcebalance::custom_io::fdict

Initial value:

```
{
    'counterpoise'  : cptypes    }
```

Section -> Interaction type dictionary.

Definition at line 21 of file custom_io.py.

7.9.2.3 list forcebalance::custom_io::ndtypes = [None]

Types of NDDO correction.

Definition at line 18 of file custom_io.py.

7.9.2.4 dictionary forcebalance::custom_io::pdict

Initial value:

```
{'CPGAUSS':{3:'A', 4:'B', 5:'C'},
         'CPGEXP' :{3:'A', 4:'B', 5:'G', 6:'X'},
         'CPEXPG' :{3:'A1', 4:'B', 5:'X0', 6:'A2'}
         }
```

Interaction type -> Parameter Dictionary.

Definition at line 25 of file custom_io.py.

7.10 forcebalance::engine Namespace Reference

Classes

- class Engine

  Base class for all engines.

Variables

- tuple logger = getLogger(__name__)

7.10.1 Variable Documentation

7.10.1.1 tuple forcebalance::engine::logger = getLogger(__name__)

Definition at line 17 of file engine.py.

7.11 forcebalance::finite_difference Namespace Reference

Functions

- def f1d2p

  A two-point finite difference stencil.
- def f1d5p

  A highly accurate five-point finite difference stencil for computing derivatives of a function.
- def f1d7p

  A highly accurate seven-point finite difference stencil for computing derivatives of a function.
- def f12d7p
- def f12d3p

  A three-point finite difference stencil.
- def in_fd

  Invoking this function from anywhere will tell us whether we're being called by a finite-difference function.
- def fdwrap

  A function wrapper for finite difference designed for differentiating 'get'-type functions.
- def fdwrap_G

  A driver to fdwrap for gradients (see documentation for fdwrap) Inputs: tgt = The Target containing the objective function that we want to differentiate mvals0 = The 'central' values of the mathematical parameters - i.e.
- def fdwrap_H

  A driver to fdwrap for Hessians (see documentation for fdwrap) Inputs: tgt = The Target containing the objective function that we want to differentiate mvals0 = The 'central' values of the mathematical parameters - i.e.

Variables

- tuple logger = getLogger(__name__)

7.11.1 Function Documentation

7.11.1.1 def forcebalance.finite_difference.f12d3p (*f, h, f0* = `None`)

A three-point finite difference stencil.

This function does either two computations or three, depending on whether the 'center' value is supplied. This is done in order to avoid recomputing the center value many times.

The first derivative is evaluated using central difference. One advantage of using central difference (as opposed to forward difference) is that we get zero at the bottom of a parabola.

Using this formula we also get an approximate second derivative, which can then be inserted into the diagonal of the Hessian. This is very useful for optimizations like BFGS where the diagonal determines how far we step in the parameter space.

How to use: use fdwrap or something similar to generate a one-variable function from the (usually) much more complicated function that we wish to differentate. Then pass it to this function.

Inputs: f = The one-variable function f(x) that we're differentiating h = The finite difference step size, usually a small number

Outputs: fp = The finite difference derivative of the function f(x) around x=0.

Definition at line 109 of file finite_difference.py.

Here is the call graph for this function:

7.11.1.2 def forcebalance.finite_difference.f12d7p (*f, h*)

Definition at line 75 of file finite_difference.py.

Here is the call graph for this function:

7.11.1.3 def forcebalance.finite_difference.f1d2p (*f, h, f0* = `None`)

A two-point finite difference stencil.

This function does either two computations or one, depending on whether the 'center' value is supplied. This is done in order to avoid recomputing the center value many times when we repeat this function for each index of the gradient.

How to use: use fdwrap or something similar to generate a one-variable function from the (usually) much more complicated function that we wish to differentate. Then pass it to this function.

Inputs: f = The one-variable function f(x) that we're differentiating h = The finite difference step size, usually a small number

Outputs: fp = The finite difference derivative of the function f(x) around x=0.

Definition at line 29 of file finite_difference.py.

Here is the call graph for this function:

7.11.1.4 def forcebalance.finite_difference.f1d5p (*f, h*)

A highly accurate five-point finite difference stencil for computing derivatives of a function.

It works on both scalar and vector functions (i.e. functions that return arrays). Since the function does four computations, it's costly but recommended if we really need an accurate reference value.

The function is evaluated at points -2h, -h, +h and +2h and these values are combined to make the derivative according to: `http://www.holoborodko.com/pavel/numerical-methods/numerical-derivative/central-differen`

How to use: use fdwrap or something similar to generate a one-variable function from the (usually) much more complicated function that we wish to differentate. Then pass it to this function.

Inputs: f = The one-variable function f(x) that we're differentiating h = The finite difference step size, usually a small number

Outputs: fp = The finite difference derivative of the function f(x) around x=0.

Definition at line 60 of file finite_difference.py.

Here is the call graph for this function:

7.11.1.5 def forcebalance.finite_difference.f1d7p (*f, h*)

A highly accurate seven-point finite difference stencil for computing derivatives of a function.

Definition at line 70 of file finite_difference.py.

Here is the call graph for this function:

7.11.1.6 def forcebalance.finite_difference.fdwrap (*func, mvals0, pidx, key =* `None`*, kwargs*)

A function wrapper for finite difference designed for differentiating 'get'-type functions.

Since our finite difference stencils take single-variable functions and differentiate them around zero, and our objective function is quite a complicated function, we need a wrapper to serve as a middleman. The alternative would be to copy the finite difference formula to wherever we're taking the derivative, and that is prone to mistakes.

Inputs: func = Either get_X or get_G; these functions return dictionaries. ['X'] = 1.23, ['G'] = [0.12, 3,45, ...] mvals0 = The 'central' values of the mathematical parameters - i.e. the wrapped function's origin is here. pidx = The index of the parameter that we're differentiating key = either 'G' or 'X', the value we wish to take out of the dictionary kwargs = Anything else we want to pass to the objective function (for instance, Project.Objective takes Order as an argument)

Outputs: func1 = Wrapped version of func, which takes a single float argument.

Definition at line 147 of file finite_difference.py.

Here is the call graph for this function:

7.11.1.7 def forcebalance.finite_difference.fdwrap_G (*tgt, mvals0, pidx*)

A driver to fdwrap for gradients (see documentation for fdwrap) Inputs: tgt = The Target containing the objective function that we want to differentiate mvals0 = The 'central' values of the mathematical parameters - i.e.

the wrapped function's origin is here. pidx = The index of the parameter that we're differentiating

Definition at line 166 of file finite_difference.py.

Here is the call graph for this function:

7.11.1.8 def forcebalance.finite_difference.fdwrap_H (*tgt, mvals0, pidx*)

A driver to fdwrap for Hessians (see documentation for fdwrap) Inputs: tgt = The Target containing the objective function that we want to differentiate mvals0 = The 'central' values of the mathematical parameters - i.e.

the wrapped function's origin is here. pidx = The index of the parameter that we're differentiating

Definition at line 177 of file finite_difference.py.

7.11.1.9 def forcebalance.finite_difference.in_fd ( )

Invoking this function from anywhere will tell us whether we're being called by a finite-difference function.

This is mainly useful for deciding when to update the 'qualitative indicators' and when not to.

Definition at line 121 of file finite_difference.py.

7.11.2 Variable Documentation

7.11.2.1 tuple forcebalance::finite_difference::logger = getLogger(__name__)

Definition at line 7 of file finite_difference.py.

7.12 forcebalance::forcefield Namespace Reference

Force field module.

Classes

- class BackedUpDict
- class FF

  Force field class.

Functions

- def determine_fftype

  Determine the type of a force field file.
- def rs_override

  This function takes in a dictionary (rsfactors) and a string (termtype).

Variables

- tuple logger = getLogger(__name__)
- dictionary FF_Extensions
- dictionary FF_IOModules

7.12.1 Detailed Description

Force field module. In ForceBalance a 'force field' is built from a set of files containing physical parameters. These files can be anything that enter into any computation - our original program was quite dependent on the GROMACS force field format, but this program is set up to allow very general input formats.

We introduce several important concepts:

1) Adjustable parameters are allocated into a vector.

To cast the force field optimization as a math problem, we treat all of the parameters on equal footing and write them as indices in a parameter vector.

2) A mapping from interaction type to parameter number.

Each element in the parameter vector corresponds to one or more interaction types. Whenever we change the parameter vector and recompute the objective function, this amounts to changing the physical parameters in the simulations, so we print out new force field files for external programs. In addition, when these programs are computing the objective function we are often in low-level subroutines that compute terms in the energy and force. If we need an analytic derivative of the objective function, then these subroutines need to know which index of the parameter vector needs to be modified.

This is done by way of a hash table: for example, when we are computing a Coulomb interaction between atom 4 and atom 5, we can build the words 'COUL4' and 'COUL5' and look it up in the parameter map; this gives us two numbers (say, 10 and 11) corresponding to the eleventh and twelfth element of the parameter vector. Then we can compute the derivatives of the energy w/r.t. these parameters (in this case, COUL5/rij and COUL4/rij) and increment these values in the objective function gradient.

In custom-implemented force fields (see counterpoisematch.py) the hash table can also be used to look up parameter values for computation of interactions. This is probably not the fastest way to do things, however.

3) Distinction between physical and mathematical parameters.

The optimization algorithm works in a space that is related to, but not exactly the same as the physical parameter space. The reasons for why we do this are:

a) Each parameter has its own physical units. On the one hand it's not right to treat different physical units all on the same footing, so nondimensionalization is desirable. To make matters worse, the force field parameters can be

small as 1e-8 or as large as 1e+6 depending on the parameter type. This means the elements of the objective function gradient / Hessian have elements that differ from each other in size by 10+ orders of magnitude, leading to mathematical instabilities in the optimizer.

b) The parameter space can be constrained, most notably for atomic partial charges where we don't want to change the overall charge on a molecule. Thus we wish to project out certain movements in the mathematical parameters such that they don't change the physical parameters.

c) We wish to regularize our optimization so as to avoid changing our parameters in very insensitive directions (linear dependencies). However, the sensitivity of the objective function to changes in the force field depends on the physical units!

For all of these reasons, we introduce a 'transformation matrix' which maps mathematical parameters onto physical parameters. The diagonal elements in this matrix are rescaling factors; they take the mathematical parameter and magnify it by this constant factor. The off-diagonal elements correspond to rotations and other linear transformations, and currently I just use them to project out the 'increase the net charge' direction in the physical parameter space.

Note that with regularization, these rescaling factors are equivalent to the widths of prior distributions in a maximum likelihood framework. Because there is such a correspondence between rescaling factors and choosing a prior, they need to be chosen carefully. This is work in progress. Another possibility is to sample the width of the priors from a noninformative distribution -- the hyperprior (we can choose the Jeffreys prior or something). This is work in progress.

Right now only GROMACS parameters are supported, but this class is extensible, we need more modules!

Author

Lee-Ping Wang

Date

04/2012

7.12.2 Function Documentation

7.12.2.1 def forcebalance.forcefield.determine_fftype (*ffname, verbose* = `False`)

Determine the type of a force field file.

It is possible to specify the file type explicitly in the input file using the syntax 'force_field.ext:type'. Otherwise this function will try to determine the force field type by extension.

Definition at line 145 of file forcefield.py.

7.12.2.2 def forcebalance.forcefield.rs_override (*rsfactors, termtype, Temperature* = `298.15`)

This function takes in a dictionary (rsfactors) and a string (termtype).

If termtype matches any of the strings below, rsfactors[termtype] is assigned to one of the numbers below.

This is LPW's attempt to simplify the rescaling factors.

Parameters

`out`	*rsfactors*	The computed rescaling factor.
`in`	*termtype*	The interaction type (corresponding to a physical unit)
`in`	*Temperature*	The temperature for computing the kT energy scale

Definition at line 1172 of file forcefield.py.

7.12.3 Variable Documentation

7.12.3.1 dictionary forcebalance::forcefield::FF_Extensions

Initial value:

```
{"itp" : "gmx",
                  "in"  : "qchem",
                  "prm" : "tinker",
                  "gen" : "custom",
                  "xml" : "openmm",
                  "frcmod" : "frcmod",
                  "mol2" : "mol2",
                  "gbs"  : "gbs",
                  "grid" : "grid"
                   }
```

Definition at line 117 of file forcefield.py.

7.12.3.2 dictionary forcebalance::forcefield::FF_IOModules

Initial value:

```
{"gmx": gmxio.ITP_Reader ,
                 "qchem": qchemio.QCIn_Reader ,
                 "tinker": tinkerio.Tinker_Reader ,
                 "custom": custom_io.Gen_Reader ,
                 "openmm" : openmmio.OpenMM_Reader,
                 "frcmod" : amberio.FrcMod_Reader,
                 "mol2" : amberio.Mol2_Reader,
                 "gbs" : psi4io.GBS_Reader,
                 "grid" : psi4io.Grid_Reader
                  }
```

Definition at line 129 of file forcefield.py.

7.12.3.3 tuple forcebalance::forcefield::logger = getLogger(__name__)

Definition at line 115 of file forcefield.py.

7.13 forcebalance::gmxio Namespace Reference

GROMACS input/output.

Classes

- class ITP_Reader

  Finite state machine for parsing GROMACS force field files.
- class GMX

  Derived from Engine object for carrying out general purpose GROMACS calculations.
- class AbInitio_GMX

  Subclass of AbInitio for force and energy matching using normal GROMACS.
- class Liquid_GMX
- class Interaction_GMX

  Subclass of Interaction for interaction energy matching using GROMACS.

Functions

- def edit_mdp

  Create or edit a Gromacs MDP file.
- def parse_atomtype_line

  Parses the 'atomtype' line.
- def rm_gmx_baks

Variables

- tuple logger = getLogger(__name__)
- list nftypes = [None, 'VDW', 'VDW_BHAM']

  VdW interaction function types.
- list pftypes = [None, 'VPAIR', 'VPAIR_BHAM']

  Pairwise interaction function types.
- list bftypes = [None, 'BONDS', 'G96BONDS', 'MORSE']

  Bonded interaction function types.
- list aftypes

  Angle interaction function types.
- list dftypes = [None, 'PDIHS', 'IDIHS', 'RBDIHS', 'PIMPDIHS', 'FOURDIHS', None, None, 'TABDIHS', 'PDIHMULS']

  Dihedral interaction function types.
- dictionary fdict

  Section -> Interaction type dictionary.
- dictionary pdict

  Interaction type -> Parameter Dictionary.
- string shot_mdp

7.13.1 Detailed Description

GROMACS input/output.

Todo Even more stuff from forcefield.py needs to go into here.

Author

Lee-Ping Wang

Date

12/2011

Todo Even more stuff from forcefield.py needs to go into here.

Author

Lee-Ping Wang

Date

12/2011

7.13.2 Function Documentation

7.13.2.1 def forcebalance.gmxio.edit_mdp (*fin, fout, options, verbose* = `False`)

Create or edit a Gromacs MDP file.

Parameters

in	*fin*	Input file name.
in	*fout*	Output file name, can be the same as input file name.
in	*options*	Dictionary containing mdp options. Existing options are replaced, new options are added at the end.

Definition at line 37 of file gmxio.py.

Here is the call graph for this function:

7.13.2.2 def forcebalance.gmxio.parse_atomtype_line (*line*)

Parses the 'atomtype' line.

Parses lines like this:

```
opls_135 CT 6 12.0107 0.0000 A 3.5000e-01 2.7614e-01
```

```
C 12.0107 0.0000 A 3.7500e-01 4.3932e-01
```

```
Na 11 22.9897 0.0000 A 6.068128070229e+03 2.662662556402e+01 0.0000e+00 ; PARM
5 6
```

Look at all the variety!

Parameters

in	*line*	Input line.

Returns

answer Dictionary containing:
atom type
bonded atom type (if any)
atomic number (if any)
atomic mass
charge
particle type
force field parameters
number of optional fields

Definition at line 183 of file gmxio.py.

Here is the call graph for this function:

7.13.2.3 def forcebalance.gmxio.rm_gmx_baks (*dir*)

Definition at line 430 of file gmxio.py.

7.13.3 Variable Documentation

7.13.3.1 list forcebalance::gmxio::aftypes

Initial value:

```
[None, 'ANGLES', 'G96ANGLES', 'CROSS_BOND_BOND',
           'CROSS_BOND_ANGLE', 'UREY_BRADLEY', 'QANGLES']
```

Angle interaction function types.

Definition at line 93 of file gmxio.py.

7.13.3.2 list forcebalance::gmxio::bftypes = [None, 'BONDS', 'G96BONDS', 'MORSE']

Bonded interaction function types.

Definition at line 91 of file gmxio.py.

7.13.3.3 list forcebalance::gmxio::dftypes = [None, 'PDIHS', 'IDIHS', 'RBDIHS', 'PIMPDIHS', 'FOURDIHS', None, None, 'TABDIHS', 'PDIHMULS']

Dihedral interaction function types.

Definition at line 96 of file gmxio.py.

7.13.3.4 dictionary forcebalance::gmxio::fdict

Initial value:

```
{
    'atomtypes'     : nftypes,
    'nonbond_params': pftypes,
    'bonds'         : bftypes,
    'bondtypes'     : bftypes,
    'angles'        : aftypes,
    'angletypes'    : aftypes,
    'dihedrals'     : dftypes,
    'dihedraltypes' : dftypes,
     'virtual_sites2': ['NONE','VSITE2'],
     'virtual_sites3': ['NONE','VSITE3','VSITE3FD','VSITE3FAD','VSITE3OUT'],
     'virtual_sites4': ['NONE','VSITE4FD','VSITE4FDN']
     }
```

Section -> Interaction type dictionary.

Based on the section you're in and the integer given on the current line, this looks up the 'interaction type' - for example, within bonded interactions there are four interaction types: harmonic, G96, Morse, and quartic interactions.

Definition at line 104 of file gmxio.py.

7.13.3.5 tuple forcebalance::gmxio::logger = getLogger(__name__)

Definition at line 28 of file gmxio.py.

7.13.3.6 list forcebalance::gmxio::nftypes = [None, 'VDW', 'VDW_BHAM']

VdW interaction function types.

Definition at line 87 of file gmxio.py.

7.13.3.7 dictionary forcebalance::gmxio::pdict

Interaction type -> Parameter Dictionary.

A list of supported GROMACS interaction types in force matching. The keys in this dictionary (e.g. 'BONDS','ANGLES') are values in the interaction type dictionary. As the program loops through the force field file, it first looks up the interaction types in 'fdict' and then goes here to do the parameter lookup by field.

Todo This needs to become more flexible because the parameter isn't always in the same field. Still need to figure out how to do this.

How about making the PDIHS less ugly?

Definition at line 127 of file gmxio.py.

7.13.3.8 list forcebalance::gmxio::pftypes = [None, 'VPAIR', 'VPAIR_BHAM']

Pairwise interaction function types.

Definition at line 89 of file gmxio.py.

7.13.3.9 string forcebalance::gmxio::shot_mdp

Initial value:

```
"""integrator   = md
dt              = 0.001
nsteps          = 0
nstxout         = 0
nstfout         = 1
nstenergy       = 1
nstxtcout       = 0
xtc_grps        = System
energygrps      = System

nstlist         = 0
ns_type         = simple
rlist           = 0.0
vdwtype         = cut-off
coulombtype     = cut-off
rcoulomb        = 0.0
rvdw            = 0.0
constraints     = none
pbc             = no
"""
```

Definition at line 438 of file gmxio.py.

7.14 forcebalance::gmxqpio Namespace Reference

Classes

- class Monomer_QTPIE

  Subclass of Target for monomer properties of QTPIE (implemented within gromacs WCV branch).

Functions

- def get_monomer_properties

Variables

- tuple logger = getLogger(__name__)

7.14.1 Function Documentation

7.14.1.1 def forcebalance.gmxqpio.get_monomer_properties (*print_stuff* = 0)

Definition at line 28 of file gmxqpio.py.

Here is the call graph for this function:

7.14.2 Variable Documentation

7.14.2.1 tuple forcebalance::gmxqpio::logger = getLogger(__name__)

Definition at line 22 of file gmxqpio.py.

7.15 forcebalance::interaction Namespace Reference

Interaction energy fitting module.

Classes

- class Interaction

  Subclass of Target for fitting force fields to interaction energies.

Variables

- tuple logger = getLogger(__name__)

7.15.1 Detailed Description

Interaction energy fitting module.

Author

Lee-Ping Wang

Date

05/2012

7.15.2 Variable Documentation

7.15.2.1 tuple forcebalance::interaction::logger = getLogger(__name__)

Definition at line 21 of file interaction.py.

7.16 forcebalance::leastsq Namespace Reference

Classes

- class LeastSquares
  Subclass of Target for general least squares fitting.

Functions

- def CheckBasis
- def LastMvals

Variables

- tuple logger = getLogger(__name__)
- CHECK_BASIS = False
- LAST_MVALS = None

7.16.1 Function Documentation

7.16.1.1 def forcebalance.leastsq.CheckBasis ( )

Definition at line 24 of file leastsq.py.

7.16.1.2 def forcebalance.leastsq.LastMvals ( )

Definition at line 29 of file leastsq.py.

7.16.2 Variable Documentation

7.16.2.1 forcebalance::leastsq::CHECK_BASIS = False

Definition at line 23 of file leastsq.py.

7.16.2.2 forcebalance::leastsq::LAST_MVALS = None

Definition at line 28 of file leastsq.py.

7.16.2.3 tuple forcebalance::leastsq::logger = getLogger(__name__)

Definition at line 21 of file leastsq.py.

7.17 forcebalance::liquid Namespace Reference

Matching of liquid bulk properties.

Classes

- class Liquid

  Subclass of Target for liquid property matching.

Functions

- def weight_info

Variables

- tuple logger = getLogger(__name__)

7.17.1 Detailed Description

Matching of liquid bulk properties. Under development.

author Lee-Ping Wang

Date

04/2012

7.17.2 Function Documentation

7.17.2.1 def forcebalance.liquid.weight_info (*W, PT, N_k, verbose* = `True`)

Definition at line 32 of file liquid.py.

7.17.3 Variable Documentation

7.17.3.1 tuple forcebalance::liquid::logger = getLogger(__name__)

Definition at line 30 of file liquid.py.

7.18 forcebalance::Mol2 Namespace Reference

Classes

- class mol2_atom

  This is to manage mol2 atomic lines on the form: 1 C1 5.4790 42.2880 49.5910 C.ar 1 <1> 0.0424.
- class mol2_bond

  This is to manage mol2 bond lines on the form: 1 1 2 ar.
- class mol2

  This is to manage one mol2 series of lines on the form:
- class mol2_set

Variables

- tuple data = mol2_set(sys.argv[1], subset=["RNAse.xray.inh8.1QHC"])

7.18.1 Variable Documentation

7.18.1.1 tuple forcebalance::Mol2::data = mol2_set(sys.argv[1], subset=["RNAse.xray.inh8.1QHC"])

Definition at line 651 of file Mol2.py.

7.19 forcebalance::mol2io Namespace Reference

Mol2 I/O.

Classes

- class Mol2_Reader

  Finite state machine for parsing Mol2 force field file.

Variables

- dictionary mol2_pdict = {'COUL':{'Atom':[1], 6:''}}

7.19.1 Detailed Description

Mol2 I/O. This serves as a good template for writing future force matching I/O modules for other programs because it's so simple.

Author

Lee-Ping Wang

Date

05/2012

7.19.2 Variable Documentation

7.19.2.1 dictionary forcebalance::mol2io::mol2_pdict = {'COUL':{'Atom':[1], 6:''}}

Definition at line 18 of file mol2io.py.

7.20 forcebalance::molecule Namespace Reference

Classes

- class MolfileTimestep

  Wrapper for the timestep C structure used in molfile plugins.
- class Molecule

  Lee-Ping's general file format conversion class.

Functions

- def getElement
- def elem_from_atomname

  Given an atom name, attempt to get the element in most cases.
- def nodematch
- def isint

  ONLY matches integers! If you have a decimal point? None shall pass!
- def isfloat

  Matches ANY number; it can be a decimal, scientific notation, integer, or what have you.
- def BuildLatticeFromLengthsAngles

  This function takes in three lattice lengths and three lattice angles, and tries to return a complete box specification.
- def BuildLatticeFromVectors

  This function takes in three lattice vectors and tries to return a complete box specification.
- def format_xyz_coord

  Print a line consisting of (element, x, y, z) in accordance with .xyz file format.
- def format_gro_coord

  Print a line in accordance with .gro file format, with six decimal points of precision.
- def format_xyzgen_coord

  Print a line consisting of (element, p, q, r, s, t, ...) where (p, q, r) are arbitrary atom-wise data (this might happen, for instance, with atomic charges)
- def format_gro_box

  Print a line corresponding to the box vector in accordance with .gro file format.
- def is_gro_coord

  Determines whether a line contains GROMACS data or not.
- def is_charmm_coord

  Determines whether a line contains CHARMM data or not.
- def is_gro_box

  Determines whether a line contains a GROMACS box vector or not.
- def add_strip_to_mat
- def pvec
- def grouper

  Groups a big long iterable into groups of ten or what have you.

- def even_list

  Creates a list of number sequences divided as evenly as possible.
- def both
- def diff
- def either
- def EulerMatrix

  Constructs an Euler matrix from three Euler angles.
- def ComputeOverlap

  Computes an 'overlap' between two molecules based on some fictitious density.
- def AlignToDensity

  Computes a "overlap density" from two frames.
- def AlignToMoments

  Pre-aligns molecules to 'moment of inertia'.
- def get_rotate_translate
- def cartesian_product2

  Form a Cartesian product of two NumPy arrays.
- def main

Variables

- tuple FrameVariableNames
- tuple AtomVariableNames = set(['elem', 'partial_charge', 'atomname', 'atomtype', 'tinkersuf', 'resid', 'resname', 'qcsuf', 'qm_ghost', 'chain', 'altloc', 'icode'])
- tuple MetaVariableNames = set(['fnm', 'ftype', 'qcrems', 'qctemplate', 'charge', 'mult', 'bonds'])
- tuple QuantumVariableNames = set(['qcrems', 'qctemplate', 'charge', 'mult', 'qcsuf', 'qm_ghost'])
- AllVariableNames = QuantumVariableNames|AtomVariableNames|MetaVariableNames|FrameVariableNames
- list Radii
- list Elements
- tuple PeriodicTable
- float bohrang = 0.529177249

  One bohr equals this many angstroms.
- tuple splitter = re.compile(r'(\s+|\S+)')
- tuple Box = namedtuple('Box',['a','b','c','alpha','beta','gamma','A','B','C','V'])
- int radian = 180
- Alive

7.20.1 Function Documentation

7.20.1.1 def forcebalance.molecule.add_strip_to_mat (*mat, strip*)

Definition at line 441 of file molecule.py.

7.20.1.2 def forcebalance.molecule.AlignToDensity (*elem, xyz1, xyz2, binary* = `False`)

Computes a "overlap density" from two frames.

This function can be called by AlignToMoments to get rid of inversion problems

Definition at line 544 of file molecule.py.

Here is the call graph for this function:

7.20.1.3 def forcebalance.molecule.AlignToMoments (*elem, xyz1, xyz2* = `None`)

Pre-aligns molecules to 'moment of inertia'.

If xyz2 is passed in, it will assume that xyz1 is already aligned to the moment of inertia, and it simply does 180-degree rotations to make sure nothing is inverted.

Definition at line 556 of file molecule.py.

7.20.1.4 def forcebalance.molecule.both (*A, B, key*)

Definition at line 479 of file molecule.py.

7.20.1.5 def forcebalance.molecule.BuildLatticeFromLengthsAngles (*a, b, c, alpha, beta, gamma*)

This function takes in three lattice lengths and three lattice angles, and tries to return a complete box specification.

Definition at line 261 of file molecule.py.

Here is the call graph for this function:

7.20.1.6 def forcebalance.molecule.BuildLatticeFromVectors (*v1, v2, v3*)

This function takes in three lattice vectors and tries to return a complete box specification.

The hash function is something we can use to discard two things that are obviously not equal. Here we neglect the hash. Return a list of the sorted atom numbers in this graph. Return a string of atoms, which serves as a rudimentary 'fingerprint' : '99,100,103,151' . Return an array of the elements. For instance ['H' 'C' 'C' 'H']. Create an Empirical Formula Get a list of the coordinates.

Definition at line 276 of file molecule.py.

7.20.1.7 def forcebalance.molecule.cartesian_product2 (*arrays*)

Form a Cartesian product of two NumPy arrays.

Definition at line 617 of file molecule.py.

7.20.1.8 def forcebalance.molecule.ComputeOverlap (*theta, elem, xyz1, xyz2*)

Computes an 'overlap' between two molecules based on some fictitious density.

Good for fine-tuning alignment but gets stuck in local minima.

Definition at line 527 of file molecule.py.

Here is the call graph for this function:

7.20.1.9 def forcebalance.molecule.diff (*A, B, key*)

Definition at line 482 of file molecule.py.

7.20.1.10 def forcebalance.molecule.either (*A, B, key*)

Definition at line 490 of file molecule.py.

7.20.1.11 def forcebalance.molecule.elem_from_atomname (*atomname*)

Given an atom name, attempt to get the element in most cases.

Definition at line 194 of file molecule.py.

7.20.1.12 def forcebalance.molecule.EulerMatrix (*T1, T2, T3*)

Constructs an Euler matrix from three Euler angles.

Definition at line 499 of file molecule.py.

Here is the call graph for this function:

7.20.1.13 def forcebalance.molecule.even_list (*totlen, splitsize*)

Creates a list of number sequences divided as evenly as possible.

Definition at line 461 of file molecule.py.

Here is the call graph for this function:

7.20.1.14 def forcebalance.molecule.format_gro_box (*box*)

Print a line corresponding to the box vector in accordance with .gro file format.

Parameters

in	*box*	Box NamedTuple

Definition at line 392 of file molecule.py.

Here is the call graph for this function:

7.20.1.15 def forcebalance.molecule.format_gro_coord (*resid, resname, aname, seqno, xyz*)

Print a line in accordance with .gro file format, with six decimal points of precision.

Parameters

in	*resid*	The number of the residue that the atom belongs to
in	*resname*	The name of the residue that the atom belongs to
in	*aname*	The name of the atom
in	*seqno*	The sequential number of the atom
in	*xyz*	A 3-element array containing x, y, z coordinates of that atom

Definition at line 371 of file molecule.py.

Here is the call graph for this function:

7.20.1.16 def forcebalance.molecule.format_xyz_coord (*element, xyz, tinker =* `False`)

Print a line consisting of (element, x, y, z) in accordance with .xyz file format.

Parameters

in	*element*	A chemical element of a single atom
in	*xyz*	A 3-element array containing x, y, z coordinates of that atom

Definition at line 355 of file molecule.py.

Here is the call graph for this function:

7.20.1.17 def forcebalance.molecule.format_xyzgen_coord (*element, xyzgen*)

Print a line consisting of (element, p, q, r, s, t, ...) where (p, q, r) are arbitrary atom-wise data (this might happen, for instance, with atomic charges)

Parameters

in	*element*	A chemical element of a single atom
in	*xyzgen*	A N-element array containing data for that atom

Definition at line 383 of file molecule.py.

Here is the call graph for this function:

7.20.1.18 def forcebalance.molecule.get_rotate_translate (*matrix1, matrix2*)

Definition at line 579 of file molecule.py.

Here is the call graph for this function:

7.20.1.19 def forcebalance.molecule.getElement (*mass*)

Definition at line 189 of file molecule.py.

Here is the call graph for this function:

7.20.1.20 def forcebalance.molecule.grouper (*n, iterable*)

Groups a big long iterable into groups of ten or what have you.

Definition at line 455 of file molecule.py.

Here is the call graph for this function:

7.20.1.21 def forcebalance.molecule.is_charmm_coord (*line*)

Determines whether a line contains CHARMM data or not.

Parameters

in	*line*	The line to be tested

Definition at line 419 of file molecule.py.

Here is the call graph for this function:

7.20.1.22 def forcebalance.molecule.is_gro_box (*line*)

Determines whether a line contains a GROMACS box vector or not.

Parameters

in	*line*	The line to be tested

Definition at line 432 of file molecule.py.

Here is the call graph for this function:

7.20.1.23 def forcebalance.molecule.is_gro_coord (*line*)

Determines whether a line contains GROMACS data or not.

Parameters

in	*line*	The line to be tested

Definition at line 404 of file molecule.py.

Here is the call graph for this function:

7.20.1.24 def forcebalance.molecule.isfloat (*word*)

Matches ANY number; it can be a decimal, scientific notation, integer, or what have you.

Definition at line 250 of file molecule.py.

7.20.1.25 def forcebalance.molecule.isint (*word*)

ONLY matches integers! If you have a decimal point? None shall pass!

Definition at line 245 of file molecule.py.

Here is the call graph for this function:

7.20.1.26 def forcebalance.molecule.main ( )

Definition at line 2648 of file molecule.py.

7.20.1.27 def forcebalance.molecule.nodematch (*node1, node2*)

Definition at line 239 of file molecule.py.

Here is the call graph for this function:

7.20.1.28 def forcebalance.molecule.pvec (*vec*)

Definition at line 450 of file molecule.py.

7.20.2 Variable Documentation

7.20.2.1 forcebalance::molecule::Alive

Definition at line 281 of file molecule.py.

7.20.2.2 forcebalance::molecule::AllVariableNames = QuantumVariableNames|AtomVariableNames|MetaVariableNames|FrameVariableNames

Definition at line 137 of file molecule.py.

7.20.2.3 tuple forcebalance::molecule::AtomVariableNames = set(['elem', 'partial_charge', 'atomname', 'atomtype', 'tinkersuf', 'resid', 'resname', 'qcsuf', 'qm_ghost', 'chain', 'altloc', 'icode'])

Definition at line 120 of file molecule.py.

7.20.2.4 float forcebalance::molecule::bohrang = 0.529177249

One bohr equals this many angstroms.

Definition at line 237 of file molecule.py.

7.20.2.5 tuple forcebalance::molecule::Box = namedtuple('Box',['a','b','c','alpha','beta','gamma','A','B','C','V'])

Definition at line 257 of file molecule.py.

7.20.2.6 list forcebalance::molecule::Elements

Initial value:

```
["None",'H','He',
            'Li','Be','B','C','N','O','F','Ne',
            'Na','Mg','Al','Si','P','S','Cl','Ar',
            'K','Ca','Sc','Ti','V','Cr','Mn','Fe','Co','Ni','Cu','Zn','Ga','Ge'
      ,'As','Se','Br','Kr',
            'Rb','Sr','Y','Zr','Nb','Mo','Tc','Ru','Rh','Pd','Ag','Cd','In','Sn
      ','Sb','Te','I','Xe',
            'Cs','Ba','La','Ce','Pr','Nd','Pm','Sm','Eu','Gd','Tb','Dy','Ho','
      Er','Tm','Yb',
            'Lu','Hf','Ta','W','Re','Os','Ir','Pt','Au','Hg','Tl','Pb','Bi','Po
      ','At','Rn',
            'Fr','Ra','Ac','Th','Pa','U','Np','Pu','Am','Cm','Bk','Cf','Es','Fm
      ','Md','No','Lr','Rf','Db','Sg','Bh','Hs','Mt']
```

Definition at line 164 of file molecule.py.

7.20.2.7 tuple forcebalance::molecule::FrameVariableNames

Initial value:

```
set(['xyzs', 'comms', 'boxes', 'qm_forces', 'qm_energies', 'qm_interaction',
                          'qm_espxyzs', 'qm_espvals', 'qm_extchgs', '
      qm_mulliken_charges', 'qm_mulliken_spins'])
```

Definition at line 106 of file molecule.py.

7.20.2.8 tuple forcebalance::molecule::MetaVariableNames = set(['fnm', 'ftype', 'qcrems', 'qctemplate', 'charge', 'mult', 'bonds'])

Definition at line 133 of file molecule.py.

7.20.2.9 tuple forcebalance::molecule::PeriodicTable

Initial value:

```
OrderedDict([('H' , 1.0079), ('He' , 4.0026),
                            ('Li' , 6.941), ('Be' , 9.0122), ('B' , 10.811), (
      'C' , 12.0107), ('N' , 14.0067), ('O' , 15.9994), ('F' , 18.9984), ('Ne' , 20.17
      97),
                            ('Na' , 22.9897), ('Mg' , 24.305), ('Al' , 26.9815
      ), ('Si' , 28.0855), ('P' , 30.9738), ('S' , 32.065), ('Cl' , 35.453), ('Ar' , 3
      9.948),
                            ('K' , 39.0983), ('Ca' , 40.078), ('Sc' , 44.9559)
```

```
, ('Ti' , 47.867), ('V' , 50.9415), ('Cr' , 51.9961), ('Mn' , 54.938), ('Fe' , 5
5.845), ('Co' , 58.9332),
                            ('Ni' , 58.6934), ('Cu' , 63.546), ('Zn' , 65.39),
 ('Ga' , 69.723), ('Ge' , 72.64), ('As' , 74.9216), ('Se' , 78.96), ('Br' , 79.9
04), ('Kr' , 83.8),
                            ('Rb' , 85.4678), ('Sr' , 87.62), ('Y' , 88.9059),
 ('Zr' , 91.224), ('Nb' , 92.9064), ('Mo' , 95.94), ('Tc' , 98), ('Ru' , 101.07)
, ('Rh' , 102.9055),
                            ('Pd' , 106.42), ('Ag' , 107.8682), ('Cd' , 112.41
1), ('In' , 114.818), ('Sn' , 118.71), ('Sb' , 121.76), ('Te' , 127.6), ('I' , 1
26.9045), ('Xe' , 131.293),
                            ('Cs' , 132.9055), ('Ba' , 137.327), ('La' , 138.9
055), ('Ce' , 140.116), ('Pr' , 140.9077), ('Nd' , 144.24), ('Pm' , 145), ('Sm'
, 150.36),
                            ('Eu' , 151.964), ('Gd' , 157.25), ('Tb' , 158.925
3), ('Dy' , 162.5), ('Ho' , 164.9303), ('Er' , 167.259), ('Tm' , 168.9342), ('Yb
' , 173.04),
                             ('Lu' , 174.967), ('Hf' , 178.49), ('Ta' , 180.947
9), ('W' , 183.84), ('Re' , 186.207), ('Os' , 190.23), ('Ir' , 192.217), ('Pt' ,
 195.078),
                             ('Au' , 196.9665), ('Hg' , 200.59), ('Tl' , 204.38
33), ('Pb' , 207.2), ('Bi' , 208.9804), ('Po' , 209), ('At' , 210), ('Rn' , 222)
,
                             ('Fr' , 223), ('Ra' , 226), ('Ac' , 227), ('Th' ,
232.0381), ('Pa' , 231.0359), ('U' , 238.0289), ('Np' , 237), ('Pu' , 244),
                             ('Am' , 243), ('Cm' , 247), ('Bk' , 247), ('Cf' ,
251), ('Es' , 252), ('Fm' , 257), ('Md' , 258), ('No' , 259),
                             ('Lr' , 262), ('Rf' , 261), ('Db' , 262), ('Sg' ,
266), ('Bh' , 264), ('Hs' , 277), ('Mt' , 268)])
```

Definition at line 174 of file molecule.py.

7.20.2.10 tuple forcebalance::molecule::QuantumVariableNames = set(['qcrems', 'qctemplate', 'charge', 'mult', 'qcsuf', 'qm_ghost'])

Definition at line 135 of file molecule.py.

7.20.2.11 int forcebalance::molecule::radian = 180

Definition at line 258 of file molecule.py.

7.20.2.12 list forcebalance::molecule::Radii

Initial value:

```
[0.31, 0.28, # H and He
        1.28, 0.96, 0.84, 0.76, 0.71, 0.66, 0.57, 0.58, # First row elements
        1.66, 1.41, 1.21, 1.11, 1.07, 1.05, 1.02, 1.06, # Second row elements
        2.03, 1.76, 1.70, 1.60, 1.53, 1.39, 1.61, 1.52, 1.50,
        1.24, 1.32, 1.22, 1.22, 1.20, 1.19, 1.20, 1.20, 1.16, # Third row
    elements, K through Kr
        2.20, 1.95, 1.90, 1.75, 1.64, 1.54, 1.47, 1.46, 1.42,
        1.39, 1.45, 1.44, 1.42, 1.39, 1.39, 1.38, 1.39, 1.40, # Fourth row
    elements, Rb through Xe
        2.44, 2.15, 2.07, 2.04, 2.03, 2.01, 1.99, 1.98,
        1.98, 1.96, 1.94, 1.92, 1.92, 1.89, 1.90, 1.87, # Fifth row elements,
    s and f blocks
         1.87, 1.75, 1.70, 1.62, 1.51, 1.44, 1.41, 1.36,
         1.36, 1.32, 1.45, 1.46, 1.48, 1.40, 1.50, 1.50, # Fifth row elements,
    d and p blocks
         2.60, 2.21, 2.15, 2.06, 2.00, 1.96, 1.90, 1.87, 1.80, 1.69]
```

Definition at line 150 of file molecule.py.

7.20.2.13 tuple forcebalance::molecule::splitter = re.compile(r'(\s+|\S+)')

Definition at line 254 of file molecule.py.

7.21 forcebalance::moments Namespace Reference

Multipole moment fitting module.

Classes

- class Moments

  Subclass of Target for fitting force fields to multipole moments (from experiment or theory).

Variables

- tuple logger = getLogger(__name__)

7.21.1 Detailed Description

Multipole moment fitting module.

Author

Lee-Ping Wang

Date

09/2012

7.21.2 Variable Documentation

7.21.2.1 tuple forcebalance::moments::logger = getLogger(__name__)

Definition at line 22 of file moments.py.

7.22 forcebalance::nifty Namespace Reference

Nifty functions, intended to be imported by any module within ForceBalance.

Classes

- class Pickler_LP

  A subclass of the python Pickler that implements pickling of _ElementTree types.
- class Unpickler_LP

  A subclass of the python Unpickler that implements unpickling of _ElementTree types.
- class LineChunker

Functions

- def pvec1d

  Printout of a 1-D vector.
- def pmat2d

  Printout of a 2-D matrix.
- def encode
- def segments
- def commadash
- def uncommadash
- def printcool

  Cool-looking printout for slick formatting of output.
- def printcool_dictionary

  See documentation for printcool; this is a nice way to print out keys/values in a dictionary.
- def isint

  ONLY matches integers! If you have a decimal point? None shall pass!
- def isfloat

  Matches ANY number; it can be a decimal, scientific notation, what have you CAUTION - this will also match an integer.
- def isdecimal

  Matches things with a decimal only; see isint and isfloat.
- def floatornan

  Returns a big number if we encounter NaN.
- def col

  Given any list, array, or matrix, return a 1-column matrix.
- def row

  Given any list, array, or matrix, return a 1-row matrix.
- def flat

  Given any list, array, or matrix, return a single-index array.
- def orthogonalize

  Given two vectors vec1 and vec2, project out the component of vec1 that is along the vec2-direction.
- def invert_svd

  Invert a matrix using singular value decomposition.
- def get_least_squares
- def statisticalInefficiency

  Compute the (cross) statistical inefficiency of (two) timeseries.
- def lp_dump

  Use this instead of pickle.dump for pickling anything that contains _ElementTree types.
- def lp_load

  Use this instead of pickle.load for unpickling anything that contains _ElementTree types.
- def getWorkQueue
- def getWQIds
- def createWorkQueue
- def destroyWorkQueue
- def queue_up

  Submit a job to the Work Queue.
- def queue_up_src_dest

  Submit a job to the Work Queue.
- def wq_wait1

This function waits ten seconds to see if a task in the Work Queue has finished.

- def wq_wait

  This function waits until the work queue is completely empty.
- def onefile
- def GoInto
- def allsplit
- def Leave
- def MissingFileInspection
- def LinkFile
- def CopyFile
- def link_dir_contents
- def remove_if_exists

  Remove the file if it exists (doesn't return an error).
- def which
- def warn_press_key
- def warn_once

  Prints a warning but will only do so once in a given run.
- def concurrent_map

  Similar to the bultin function map().
- def multiopen

  This function be given any of several variable types (single file name, file object, or list of lines, or a list of the above) and give a list of files:

Variables

- tuple logger = getLogger(__name__)
- float kb = 0.0083144100163

  Boltzmann constant.
- float eqcgmx = 2625.5002

  Q-Chem to GMX unit conversion for energy.
- float fqcgmx = 49621.9

  Q-Chem to GMX unit conversion for force.
- float bohrang = 0.529177249

  One bohr equals this many angstroms.
- string XMLFILE = 'x'

  Pickle uses 'flags' to pickle and unpickle different variable types.
- WORK_QUEUE = None
- tuple WQIDS = defaultdict(list)
- list specific_lst
- tuple specific_dct = dict(list(itertools.chain(*[[(j,i[1]) for j in i[0]] for i in specific_lst])))

7.22.1 Detailed Description

Nifty functions, intended to be imported by any module within ForceBalance. Table of Contents:

- I/O formatting
- Math: Variable manipulation, linear algebra, least squares polynomial fitting

- Pickle: Expand Python's own pickle to accommodate writing XML etree objects
- Commands for submitting things to the Work Queue
- Various file and process management functions
- Development stuff (not commonly used)

Named after the mighty Sniffy Handy Nifty (King Sniffy)

Author

Lee-Ping Wang

Date

12/2011

7.22.2 Function Documentation

7.22.2.1 def forcebalance.nifty.allsplit (*Dir*)

Definition at line 767 of file nifty.py.

Here is the call graph for this function:

7.22.2.2 def forcebalance.nifty.col (*vec*)

Given any list, array, or matrix, return a 1-column matrix.

Input: vec = The input vector that is to be made into a column

Output: A column matrix

Definition at line 271 of file nifty.py.

Here is the call graph for this function:

7.22.2.3 def forcebalance.nifty.commadash (*l*)

Definition at line 82 of file nifty.py.

Here is the call graph for this function:

7.22.2.4 def forcebalance.nifty.concurrent_map (*func, data*)

Similar to the bultin function map().

But spawn a thread for each argument and apply ‘func‘ concurrently.

Note: unlike map(), we cannot take an iterable argument. ‘data‘ should be an indexable sequence.

Definition at line 1022 of file nifty.py.

7.22.2.5 def forcebalance.nifty.CopyFile (*src, dest*)

Definition at line 817 of file nifty.py.

Here is the call graph for this function:

7.22.2.6 def forcebalance.nifty.createWorkQueue (*wq_port, debug* = `True`)

Definition at line 580 of file nifty.py.

7.22.2.7 def forcebalance.nifty.destroyWorkQueue ( )

Definition at line 590 of file nifty.py.

Here is the call graph for this function:

7.22.2.8 def forcebalance.nifty.encode (*l*)

Definition at line 73 of file nifty.py.

Here is the call graph for this function:

7.22.2.9 def forcebalance.nifty.flat (*vec*)

Given any list, array, or matrix, return a single-index array.

Parameters

in	*vec*	The data to be flattened

Returns

answer The flattened data

Definition at line 290 of file nifty.py.

Here is the call graph for this function:

7.22.2.10 def forcebalance.nifty.floatornan (*word*)

Returns a big number if we encounter NaN.

Parameters

in	*word*	The string to be converted

Returns

answer The string converted to a float; if not a float, return 1e10

Todo I could use suggestions for making this better.

Definition at line 253 of file nifty.py.

Here is the call graph for this function:

7.22.2.11 def forcebalance.nifty.get_least_squares (*x, y, w* = `None`, *thresh* = `1e-12`)

```
 __                    __
|                        |
| 1 (x0) (x0)^2 (x0)^3 |
| 1 (x1) (x1)^2 (x1)^3 |
| 1 (x2) (x2)^2 (x2)^3 |
| 1 (x3) (x3)^2 (x3)^3 |
| 1 (x4) (x4)^2 (x4)^3 |
|__                    __|
```

Parameters

in	*X*	(2-D array) An array of X-values (see above)
in	*Y*	(array) An array of Y-values (only used in getting the least squares coefficients)
in	*w*	(array) An array of weights, hopefully normalized to one.
out	*Beta*	The least-squares coefficients
out	*Hat*	The hat matrix that takes linear combinations of data y-values to give fitted y-values (weights)
out	*yfit*	The fitted y-values
out	*MPPI*	The Moore-Penrose pseudoinverse (multiply by Y to get least-squares coefficients, multiply by dY/dk to get derivatives of least-squares coefficients)

Definition at line 358 of file nifty.py.

Here is the call graph for this function:

7.22.2.12 def forcebalance.nifty.getWorkQueue ( )

Definition at line 572 of file nifty.py.

7.22.2.13 def forcebalance.nifty.getWQIds ( )

Definition at line 576 of file nifty.py.

Here is the call graph for this function:

7.22.2.14 def forcebalance.nifty.GoInto (*Dir*)

Definition at line 759 of file nifty.py.

7.22.2.15 def forcebalance.nifty.invert_svd (*X, thresh* = `1e-12`)

Invert a matrix using singular value decomposition.

Parameters

in	*X*	The matrix to be inverted
in	*thresh*	The SVD threshold; eigenvalues below this are not inverted but set to zero

Returns

Xt The inverted matrix

Definition at line 317 of file nifty.py.

Here is the call graph for this function:

7.22.2.16 def forcebalance.nifty.isdecimal (*word*)

Matches things with a decimal only; see isint and isfloat.

Parameters

in	*word*	String (for instance, '123', '153.0', '2.', '-354')

Returns

answer Boolean which specifies whether the string is a number with a decimal point

Definition at line 243 of file nifty.py.

Here is the call graph for this function:

7.22.2.17 def forcebalance.nifty.isfloat (*word*)

Matches ANY number; it can be a decimal, scientific notation, what have you CAUTION - this will also match an integer.

Parameters

in	*word*	String (for instance, '123', '153.0', '2.', '-354')

Returns

answer Boolean which specifies whether the string is any number

Definition at line 233 of file nifty.py.

Here is the call graph for this function:

7.22.2.18 def forcebalance.nifty.isint (*word*)

ONLY matches integers! If you have a decimal point? None shall pass!

Parameters

in	*word*	String (for instance, '123', '153.0', '2.', '-354')

Returns

answer Boolean which specifies whether the string is an integer (only +/- sign followed by digits)

Definition at line 222 of file nifty.py.

Here is the call graph for this function:

7.22.2.19 def forcebalance.nifty.Leave (*Dir*)

Definition at line 773 of file nifty.py.

7.22.2.20 def forcebalance.nifty.link_dir_contents (*abssrcdir, absdestdir*)

Definition at line 827 of file nifty.py.

7.22.2.21 def forcebalance.nifty.LinkFile (*src, dest, nosrcok* = `False`)

Definition at line 804 of file nifty.py.

Here is the call graph for this function:

7.22.2.22 def forcebalance.nifty.lp_dump (*obj, file, protocol* = `None`)

Use this instead of pickle.dump for pickling anything that contains _ElementTree types.

Definition at line 550 of file nifty.py.

Here is the call graph for this function:

7.22.2.23 def forcebalance.nifty.lp_load (*file*)

Use this instead of pickle.load for unpickling anything that contains _ElementTree types.

Definition at line 555 of file nifty.py.

Here is the call graph for this function:

7.22.2.24 def forcebalance.nifty.MissingFileInspection (*fnm*)

Definition at line 794 of file nifty.py.

Here is the call graph for this function:

7.22.2.25 def forcebalance.nifty.multiopen (*arg*)

This function be given any of several variable types (single file name, file object, or list of lines, or a list of the above) and give a list of files:

[file1, file2, file3 ...]

each of which can then be iterated over:

[[file1_line1, file1_line2 ...], [file2_line1, file2_line2 ...]]

Definition at line 1052 of file nifty.py.

7.22.2.26 def forcebalance.nifty.onefile (*ext, arg* = None)

Definition at line 741 of file nifty.py.

Here is the call graph for this function:

7.22.2.27 def forcebalance.nifty.orthogonalize (*vec1, vec2*)

Given two vectors vec1 and vec2, project out the component of vec1 that is along the vec2-direction.

Parameters

in	*vec1*	The projectee (i.e. output is some modified version of vec1)
in	*vec2*	The projector (component subtracted out from vec1 is parallel to this)

Returns

answer A copy of vec1 but with the vec2-component projected out.

Definition at line 304 of file nifty.py.

7.22.2.28 def forcebalance.nifty.pmat2d (*mat2d, precision* = 1, *loglevel* = INFO)

Printout of a 2-D matrix.

Parameters

in	*mat2d*	a 2-D matrix

Definition at line 66 of file nifty.py.

Here is the call graph for this function:

7.22.2.29 def forcebalance.nifty.printcool (*text, sym* = "#", *bold* = False, *color* = 2, *ansi* = None, *bottom* = '-', *minwidth* = 50, *center* = True)

Cool-looking printout for slick formatting of output.

Parameters

in	*text*	The string that the printout is based upon. This function will print out the string, ANSI-colored and enclosed in the symbol for example:
		`#################`
		`### I am cool ###`
		`#################`

in	*sym*	The surrounding symbol
in	*bold*	Whether to use bold print
in	*color*	The ANSI color: 1 red 2 green 3 yellow 4 blue 5 magenta 6 cyan 7 white
in	*bottom*	The symbol for the bottom bar
in	*minwidth*	The minimum width for the box, if the text is very short then we insert the appropriate number of padding spaces

Returns

bar The bottom bar is returned for the user to print later, e.g. to mark off a 'section'

Definition at line 155 of file nifty.py.

Here is the call graph for this function:

7.22.2.30 def forcebalance.nifty.printcool_dictionary (*Dict*, *title* = "General options", *bold* = False, *color* = 2, *keywidth* = 25, *topwidth* = 50, *center* = True, *leftpad* = 0)

See documentation for printcool; this is a nice way to print out keys/values in a dictionary.

The keys in the dictionary are sorted before printing out.

Parameters

in	*dict*	The dictionary to be printed
in	*title*	The title of the printout

Definition at line 198 of file nifty.py.

Here is the call graph for this function:

7.22.2.31 def forcebalance.nifty.pvec1d (*vec1d*, *precision* = 1, *loglevel* = INFO)

Printout of a 1-D vector.

Parameters

in	*vec1d*	a 1-D vector

Definition at line 55 of file nifty.py.

Here is the call graph for this function:

7.22.2.32 def forcebalance.nifty.queue_up (*wq, command, input_files, output_files, tgt =* `None`, *verbose =* `True`)

Submit a job to the Work Queue.

Parameters

in	*wq*	(Work Queue Object)
in	*command*	(string) The command to run on the remote worker.
in	*input_files*	(list of files) A list of locations of the input files.
in	*output_files*	(list of files) A list of locations of the output files.

Definition at line 605 of file nifty.py.

Here is the call graph for this function:

7.22.2.33 def forcebalance.nifty.queue_up_src_dest (*wq, command, input_files, output_files, tgt =* `None`, *verbose =* `True`)

Submit a job to the Work Queue.

This function is a bit fancier in that we can explicitly specify where the input files come from, and where the output files go to.

Parameters

in	*wq*	(Work Queue Object)
in	*command*	(string) The command to run on the remote worker.
in	*input_files*	(list of 2-tuples) A list of local and remote locations of the input files.
in	*output_files*	(list of 2-tuples) A list of local and remote locations of the output files.

Definition at line 637 of file nifty.py.

7.22.2.34 def forcebalance.nifty.remove_if_exists (*fnm*)

Remove the file if it exists (doesn't return an error).

Definition at line 838 of file nifty.py.

7.22.2.35 def forcebalance.nifty.row (*vec*)

Given any list, array, or matrix, return a 1-row matrix.

Parameters

in	*vec*	The input vector that is to be made into a row

Returns

answer A row matrix

Definition at line 281 of file nifty.py.

Here is the call graph for this function:

7.22.2.36 def forcebalance.nifty.segments (*e*)

Definition at line 76 of file nifty.py.

Here is the call graph for this function:

7.22.2.37 def forcebalance.nifty.statisticalInefficiency (*A_n, B_n* = None, *fast* = False, *mintime* = 3, *warn* = True)

Compute the (cross) statistical inefficiency of (two) timeseries.

Notes The same timeseries can be used for both A_n and B_n to get the autocorrelation statistical inefficiency. The fast method described in Ref [1] is used to compute g.

References [1] J. D. Chodera, W. C. Swope, J. W. Pitera, C. Seok, and K. A. Dill. Use of the weighted histogram analysis method for the analysis of simulated and parallel tempering simulations. JCTC 3(1):26-41, 2007.

Examples

Compute statistical inefficiency of timeseries data with known correlation time.

>>> import timeseries >>> A_n = timeseries.generateCorrelatedTimeseries(N=100000, tau=5.0) >>> g = statisticalInefficiency(A_n, fast=True)

Parameters

in	*A_n*	(required, numpy array) - A_n[n] is nth value of timeseries A. Length is deduced from vector.
in	*B_n*	(optional, numpy array) - B_n[n] is nth value of timeseries B. Length is deduced from vector. If supplied, the cross-correlation of timeseries A and B will be estimated instead of the autocorrelation of timeseries A.
in	*fast*	(optional, boolean) - if True, will use faster (but less accurate) method to estimate correlation time, described in Ref. [1] (default: False)
in	*mintime*	(optional, int) - minimum amount of correlation function to compute (default: 3) - The algorithm terminates after computing the correlation time out to mintime when the correlation function furst goes negative. Note that this time may need to be increased if there is a strong initial negative peak in the correlation function.

Returns

g The estimated statistical inefficiency (equal to 1 + 2 tau, where tau is the correlation time). We enforce g >= 1.0.

Definition at line 434 of file nifty.py.

7.22.2.38 def forcebalance.nifty.uncommadash (*s*)

Definition at line 92 of file nifty.py.

Here is the call graph for this function:

7.22.2.39 def forcebalance.nifty.warn_once (*warning*, *warnhash* = None)

Prints a warning but will only do so once in a given run.

Definition at line 998 of file nifty.py.

Here is the call graph for this function:

7.22.2.40 def forcebalance.nifty.warn_press_key (*warning*, *timeout* = 10)

Definition at line 983 of file nifty.py.

Here is the call graph for this function:

7.22.2.41 def forcebalance.nifty.which (*fnm*)

Definition at line 842 of file nifty.py.

7.22.2.42 def forcebalance.nifty.wq_wait (*wq*, *wait_time* = 10, *wait_intvl* = 10, *print_time* = 60, *verbose* = False)

This function waits until the work queue is completely empty.

Definition at line 730 of file nifty.py.

Here is the call graph for this function:

7.22.2.43 def forcebalance.nifty.wq_wait1 (*wq*, *wait_time* = 10, *wait_intvl* = 1, *print_time* = 60, *verbose* = False)

This function waits ten seconds to see if a task in the Work Queue has finished.

Definition at line 658 of file nifty.py.

Here is the call graph for this function:

7.22.3 Variable Documentation

7.22.3.1 float forcebalance::nifty::bohrang = 0.529177249

One bohr equals this many angstroms.

Definition at line 45 of file nifty.py.

7.22.3.2 float forcebalance::nifty::eqcgmx = 2625.5002

Q-Chem to GMX unit conversion for energy.

Definition at line 41 of file nifty.py.

7.22.3.3 float forcebalance::nifty::fqcgmx = 49621.9

Q-Chem to GMX unit conversion for force.

Definition at line 43 of file nifty.py.

7.22.3.4 float forcebalance::nifty::kb = 0.0083144100163

Boltzmann constant.

Definition at line 39 of file nifty.py.

7.22.3.5 tuple forcebalance::nifty::logger = getLogger(__name__)

Definition at line 34 of file nifty.py.

7.22.3.6 tuple forcebalance::nifty::specific_dct = dict(list(itertools.chain(*[[(j,i[1]) for j in i[0]] for i in specific_lst])))

Definition at line 792 of file nifty.py.

7.22.3.7 list forcebalance::nifty::specific_lst

Initial value:

```
1 [(['mdrun','grompp','trjconv','g_energy','g_traj'], "Make sure to install
       GROMACS and add it to your path (or set the gmxpath option)"),
2                 (['force.mdin', 'stage.leap'], "This file is needed for setting
       up AMBER force matching targets"),
3                 (['conf.pdb', 'mono.pdb'], "This file is needed for setting up
       OpenMM condensed phase property targets"),
4                 (['liquid.xyz', 'liquid.key', 'mono.xyz', 'mono.key'], "This
       file is needed for setting up OpenMM condensed phase property targets"),
5                 (['dynamic', 'analyze', 'minimize', 'testgrad', 'vibrate', '
      optimize', 'polarize', 'superpose'], "Make sure to install TINKER and add it to
       your path (or set the tinkerpath option)"),
6                 (['runcuda.sh', 'npt.py', 'npt_tinker.py'], "This file belongs
       in the ForceBalance source directory, not sure why it is missing"),
7                 (['input.xyz'], "This file is needed for TINKER molecular
       property targets"),
8                 (['.*key$', '.*xyz$'], "I am guessing this file is probably
       needed by TINKER"),
9                 (['.*gro$', '.*top$', '.*itp$', '.*mdp$', '.*ndx$'], "I am
       guessing this file is probably needed by GROMACS")
10                 ]
```

Definition at line 780 of file nifty.py.

7.22.3.8 forcebalance::nifty::WORK_QUEUE = None

Definition at line 567 of file nifty.py.

7.22.3.9 tuple forcebalance::nifty::WQIDS = defaultdict(list)

Definition at line 570 of file nifty.py.

7.22.3.10 string forcebalance::nifty::XMLFILE = 'x'

Pickle uses 'flags' to pickle and unpickle different variable types.

Here we use the letter 'x' to signify that the variable type is an XML file.

Definition at line 496 of file nifty.py.

7.23 forcebalance::objective Namespace Reference

ForceBalance objective function.

Classes

- class Objective

  Objective function.
- class Penalty

  Penalty functions for regularizing the force field optimizer.

Variables

- tuple logger = getLogger(__name__)
- dictionary Implemented_Targets

  The table of implemented Targets.
- list Letters = ['X','G','H']

  This is the canonical lettering that corresponds to : objective function, gradient, Hessian.

7.23.1 Detailed Description

ForceBalance objective function.

7.23.2 Variable Documentation

7.23.2.1 dictionary forcebalance::objective::Implemented_Targets

Initial value:

```
{
    'ABINITIO_GMX':AbInitio_GMX,
    'ABINITIO_TINKER':AbInitio_TINKER,
    'ABINITIO_OPENMM':AbInitio_OpenMM,
    'ABINITIO_AMBER':AbInitio_AMBER,
    'ABINITIO_INTERNAL':AbInitio_Internal,
    'VIBRATION_TINKER':Vibration_TINKER,
    'LIQUID_OPENMM':Liquid_OpenMM,
    'LIQUID_TINKER':Liquid_TINKER,
     'LIQUID_GMX':Liquid_GMX,
     'COUNTERPOISE':Counterpoise,
     'THCDF_PSI4':THCDF_Psi4,
     'RDVR3_PSI4':RDVR3_Psi4,
     'INTERACTION_TINKER':Interaction_TINKER,
     'INTERACTION_OPENMM':Interaction_OpenMM,
     'BINDINGENERGY_TINKER':BindingEnergy_TINKER,
     'MOMENTS_TINKER':Moments_TINKER,
```

```
    'MONOMER_QTPIE':Monomer_QTPIE,
    'REMOTE_TARGET':RemoteTarget,
    }
```

The table of implemented Targets.

Definition at line 74 of file objective.py.

7.23.2.2 list forcebalance::objective::Letters = ['X','G','H']

This is the canonical lettering that corresponds to : objective function, gradient, Hessian.

Definition at line 96 of file objective.py.

7.23.2.3 tuple forcebalance::objective::logger = getLogger(__name__)

Definition at line 17 of file objective.py.

7.24 forcebalance::openmmio Namespace Reference

OpenMM input/output.

Classes

- class OpenMM_Reader

  Class for parsing OpenMM force field files.
- class Liquid_OpenMM
- class AbInitio_OpenMM

  Subclass of AbInitio for force and energy matching using OpenMM.
- class Interaction_OpenMM

  Subclass of Target for interaction matching using OpenMM.

Functions

- def get_dipole

  Return the current dipole moment in Debye.
- def ResetVirtualSites

  Given a set of OpenMM-compatible positions and a System object, compute the correct virtual site positions according to the System.
- def CopyAmoebaBondParameters
- def CopyAmoebaOutOfPlaneBendParameters
- def CopyAmoebaAngleParameters
- def CopyAmoebaInPlaneAngleParameters
- def CopyAmoebaVdwParameters
- def CopyAmoebaMultipoleParameters
- def CopyHarmonicBondParameters
- def CopyHarmonicAngleParameters
- def CopyPeriodicTorsionParameters
- def CopyNonbondedParameters
- def do_nothing
- def CopySystemParameters

Copy parameters from one system (i.e.

- def UpdateSimulationParameters
- def SetAmoebaVirtualExclusions
- def MTSVVVRIntegrator

  Create a multiple timestep velocity verlet with velocity randomization (VVVR) integrator.

Variables

- tuple logger = getLogger(__name__)
- dictionary suffix_dict
- string pdict = "XML_Override"

  pdict is a useless variable if the force field is XML.

7.24.1 Detailed Description

OpenMM input/output.

Author

Lee-Ping Wang

Date

04/2012

7.24.2 Function Documentation

7.24.2.1 def forcebalance.openmmio.CopyAmoebaAngleParameters (*src, dest*)

Definition at line 111 of file openmmio.py.

Here is the call graph for this function:

7.24.2.2 def forcebalance.openmmio.CopyAmoebaBondParameters (*src, dest*)

Definition at line 97 of file openmmio.py.

Here is the call graph for this function:

7.24.2.3 def forcebalance.openmmio.CopyAmoebaInPlaneAngleParameters (*src, dest*)

Definition at line 120 of file openmmio.py.

Here is the call graph for this function:

7.24.2.4 def forcebalance.openmmio.CopyAmoebaMultipoleParameters (*src, dest*)

Definition at line 133 of file openmmio.py.

Here is the call graph for this function:

7.24.2.5 def forcebalance.openmmio.CopyAmoebaOutOfPlaneBendParameters (*src, dest*)

Definition at line 103 of file openmmio.py.

Here is the call graph for this function:

7.24.2.6 def forcebalance.openmmio.CopyAmoebaVdwParameters (*src, dest*)

Definition at line 129 of file openmmio.py.

Here is the call graph for this function:

7.24.2.7 def forcebalance.openmmio.CopyHarmonicAngleParameters (*src, dest*)

Definition at line 141 of file openmmio.py.

Here is the call graph for this function:

7.24.2.8 def forcebalance.openmmio.CopyHarmonicBondParameters (*src, dest*)

Definition at line 137 of file openmmio.py.

Here is the call graph for this function:

7.24.2.9 def forcebalance.openmmio.CopyNonbondedParameters (*src, dest*)

Definition at line 149 of file openmmio.py.

Here is the call graph for this function:

7.24.2.10 def forcebalance.openmmio.CopyPeriodicTorsionParameters (*src, dest*)

Definition at line 145 of file openmmio.py.

Here is the call graph for this function:

7.24.2.11 def forcebalance.openmmio.CopySystemParameters (*src, dest*)

Copy parameters from one system (i.e.

that which is created by a new force field) sto another system (i.e. the one stored inside the Target object). DANGER: These need to be implemented manually!!!

Definition at line 163 of file openmmio.py.

Here is the call graph for this function:

7.24.2.12 def forcebalance.openmmio.do_nothing (*src, dest*)

Definition at line 156 of file openmmio.py.

7.24.2.13 def forcebalance.openmmio.get_dipole (*simulation, q* = `None`, *positions* = `None`)

Return the current dipole moment in Debye.

Note that this quantity is meaningless if the system carries a net charge.

Definition at line 36 of file openmmio.py.

Here is the call graph for this function:

7.24.2.14 def forcebalance.openmmio.MTSVVVRIntegrator (*temperature, collision_rate, timestep, system, ninnersteps* = 4)

Create a multiple timestep velocity verlet with velocity randomization (VVVR) integrator.

ARGUMENTS

temperature (numpy.unit.Quantity compatible with kelvin) - the temperature collision_rate (numpy.unit.Quantity compatible with 1/picoseconds) - the collision rate timestep (numpy.unit.Quantity compatible with femtoseconds) - the integration timestep system (simtk.openmm.System) - system whose forces will be partitioned ninnersteps (int) - number of inner timesteps (default: 4)

RETURNS

integrator (openmm.CustomIntegrator) - a VVVR integrator

NOTES

This integrator is equivalent to a Langevin integrator in the velocity Verlet discretization with a timestep correction to ensure that the field-free diffusion constant is timestep invariant. The inner velocity Verlet discretization is transformed into a multiple timestep algorithm.

REFERENCES

VVVR Langevin integrator: * http://arxiv.org/abs/1301.3800 * http://arxiv.org/abs/1107.-2967 (to appear in PRX 2013)

TODO

Move initialization of 'sigma' to setting the per-particle variables.

Definition at line 241 of file openmmio.py.

7.24.2.15 def forcebalance.openmmio.ResetVirtualSites (*positions, system*)

Given a set of OpenMM-compatible positions and a System object, compute the correct virtual site positions according to the System.

Definition at line 66 of file openmmio.py.

Here is the call graph for this function:

7.24.2.16 def forcebalance.openmmio.SetAmoebaVirtualExclusions (*system*)

Definition at line 188 of file openmmio.py.

Here is the call graph for this function:

7.24.2.17 def forcebalance.openmmio.UpdateSimulationParameters (*src_system, dest_simulation*)

Definition at line 182 of file openmmio.py.

Here is the call graph for this function:

7.24.3 Variable Documentation

7.24.3.1 tuple forcebalance::openmmio::logger = getLogger(__name__)

Definition at line 24 of file openmmio.py.

7.24.3.2 string forcebalance::openmmio::pdict = "XML_Override"

pdict is a useless variable if the force field is XML.

Definition at line 320 of file openmmio.py.

7.24.3.3 dictionary forcebalance::openmmio::suffix_dict

Initial value:

```
1 { "HarmonicBondForce" : {"Bond" : ["class1","class2"]},
2                 "HarmonicAngleForce" : {"Angle" : ["class1","class2","class3"],
      },
3                 "PeriodicTorsionForce" : {"Proper" : ["class1","class2","class3
      ","class4"],},
4                 "NonbondedForce" : {"Atom": ["type"]},
5                 "AmoebaBondForce" : {"Bond" : ["class1","class2"]},
6                 "AmoebaAngleForce" : {"Angle" : ["class1","class2","class3"]},
7                 "AmoebaStretchBendForce" : {"StretchBend" : ["class1","class2",
      "class3"]},
8                 "AmoebaVdwForce" : {"Vdw" : ["class"]},
9                 "AmoebaMultipoleForce" : {"Multipole" : ["type","kz","kx"], "
      Polarize" : ["type"]},
10                 "AmoebaUreyBradleyForce" : {"UreyBradley" : ["class1","class2",
      "class3"]},
11                 "Residues.Residue" : {"VirtualSite" : ["index"]}
12                 }
```

Definition at line 306 of file openmmio.py.

7.25 forcebalance::optimizer Namespace Reference

Optimization algorithms.

Classes

- class Optimizer

  Optimizer class.

Functions

- def Counter
- def GoodStep

Variables

- tuple logger = getLogger(__name__)
- int ITERATION_NUMBER = 0
- int GOODSTEP = 0

7.25.1 Detailed Description

Optimization algorithms. My current implementation is to have a single optimizer class with several methods contained inside.

Author

Lee-Ping Wang

Date

12/2011

7.25.2 Function Documentation

7.25.2.1 def forcebalance.optimizer.Counter ( )

Definition at line 29 of file optimizer.py.

Here is the call graph for this function:

7.25.2.2 def forcebalance.optimizer.GoodStep ( )

Definition at line 33 of file optimizer.py.

7.25.3 Variable Documentation

7.25.3.1 int forcebalance::optimizer::GOODSTEP = 0

Definition at line 27 of file optimizer.py.

7.25.3.2 int forcebalance::optimizer::ITERATION_NUMBER = 0

Definition at line 25 of file optimizer.py.

7.25.3.3 tuple forcebalance::optimizer::logger = getLogger(__name__)

Definition at line 22 of file optimizer.py.

7.26 forcebalance::output Namespace Reference

Classes

- class ForceBalanceLogger

  This logger starts out with a default handler that writes to stdout addHandler removes this default the first time another handler is added.
- class RawStreamHandler

  Exactly like output.StreamHandler except it does no extra formatting before sending logging messages to the stream.
- class RawFileHandler

  Exactly like output.FileHandler except it does no extra formatting before sending logging messages to the file.
- class CleanStreamHandler

  Similar to RawStreamHandler except it does not write terminal escape codes.
- class CleanFileHandler

  File handler that does not write terminal escape codes and carriage returns to files.

7.27 forcebalance::parser Namespace Reference

Input file parser for ForceBalance jobs.

Functions

- def read_mvals
- def read_pvals
- def read_priors
- def read_internals
- def printsection

  Print out a section of the input file in a parser-compliant and readable format.
- def parse_inputs

  Parse through the input file and read all user-supplied options.

Variables

- tuple logger = getLogger(__name__)
- dictionary gen_opts_types

  Default general options.
- dictionary tgt_opts_types

  Default fitting target options.
- tuple all_opts_names = list(itertools.chain(∗[i.keys() for i in gen_opts_types.values()]))
- list iocc = []

  Check for uniqueness of option names.
- dictionary gen_opts_defaults = {}

  Default general options - basically a collapsed veresion of gen_opts_types.
- dictionary subdict = {}
- dictionary tgt_opts_defaults = {}

  Default target options - basically a collapsed version of tgt_opts_types.
- dictionary bkwd = {"simtype" : "type", "masterfile" : "binding_txt"}

Option maps for maintaining backward compatibility.

- list mainsections = ["SIMULATION","TARGET","OPTIONS","END","NONE"]

  Listing of sections in the input file.

- dictionary ParsTab

  ParsTab that refers to subsection parsers.

7.27.1 Detailed Description

Input file parser for ForceBalance jobs. Additionally, the location for all default options.

Although I will do my best to write good documentation, for many programs the input parser becomes the most up-to-date source for documentation. So this is a great place to write lots of comments for those who implement new functionality.

There are two types of sections for options - GENERAL and TARGET. Since there can be many fitting targets within a single job (i.e. we may wish to fit water trimers and hexamers, which constitutes two fitting targets) the input is organized into sections, like so:

$options

gen_option_1 Big

gen_option_2 Mao

$target

tgt_option_1 Sniffy

tgt_option_2 Schmao

$target

tgt_option_1 Nifty

tgt_option_2 Jiffy

$end

In this case, two sets of target options are generated in addition to the general option.

(Note: "Target" used to be called "Simulation". Backwards compatibility is maintained.)

Each option is meant to be parsed as a certain variable type.

- String option values are read in directly; note that only the first two words in the line are processed
- Some strings are capitalized when they are read in; this is mainly for function tables like OptTab and TgtTab
- List option types will pick up all of the words on the line and use them as values, plus if the option occurs more than once it will aggregate all of the values.
- Integer and float option types are read in a pretty straightforward way
- Boolean option types are always set to true, unless the second word is '0', 'no', or 'false' (not case sensitive)
- Section option types are meant to treat more elaborate inputs, such as the user pasting in output parameters from a previous job as input, or a specification of internal coordinate system. I imagine that for every section type I would have to write my own parser. Maybe a ParsTab of parsing functions would work. :)

To add a new option, simply add it to the dictionaries below and give it a default value if desired. If you add an entirely new type, make sure to implement the interpretation of that type in the parse_inputs function.

Author

Lee-Ping Wang

Date

11/2012

7.27.2 Function Documentation

7.27.2.1 def forcebalance.parser.parse_inputs (*input_file* = `None`)

Parse through the input file and read all user-supplied options.

This is usually the first thing that happens when an executable script is called. Our parser first loads the default options, and then updates these options as it encounters keywords.

Each keyword corresponds to a variable type; each variable type (e.g. string, integer, float, boolean) is treated differently. For more elaborate inputs, there is a 'section' variable type.

There is only one set of general options, but multiple sets of target options. Each target has its own section delimited by the *$target* keyword, and we build a list of target options.

Parameters

in	*input_file*	The name of the input file.

Returns

options General options.
tgt_opts List of fitting target options.

Todo Implement internal coordinates.

Implement sampling correction.

Implement charge groups.

Definition at line 396 of file parser.py.

Here is the call graph for this function:

7.27.2.2 def forcebalance.parser.printsection (*heading, optdict, typedict*)

Print out a section of the input file in a parser-compliant and readable format.

At the time of writing of this function, it's mainly intended to be called by MakeInputFile.py. The heading is printed first (it is something like $options or $target). Then it loops through the variable types (strings, allcaps, etc...) and the keys in each variable type. The one-line description of each key is printed out as a comment, and then the key itself is printed out along with the value provided in optdict. If optdict is None, then the default value is printed out instead.

Parameters

in	*heading*	Heading, either $options or $target
in	*optdict*	Options dictionary or None.
in	*typedict*	Option type dictionary, either gen_opts_types or tgt_opts_types specified in this file.

Returns

Answer List of strings for the section that we are printing out.

Definition at line 299 of file parser.py.

Here is the call graph for this function:

7.27.2.3 def forcebalance.parser.read_internals (*fobj*)

Definition at line 273 of file parser.py.

7.27.2.4 def forcebalance.parser.read_mvals (*fobj*)

Definition at line 248 of file parser.py.

Here is the call graph for this function:

7.27.2.5 def forcebalance.parser.read_priors (*fobj*)

Definition at line 264 of file parser.py.

Here is the call graph for this function:

7.27.2.6 def forcebalance.parser.read_pvals (*fobj*)

Definition at line 256 of file parser.py.

Here is the call graph for this function:

7.27.3 Variable Documentation

7.27.3.1 tuple forcebalance::parser::all_opts_names = list(itertools.chain(∗[i.keys() for i in gen_opts_types.values()]))

Definition at line 213 of file parser.py.

7.27.3.2 dictionary forcebalance::parser::bkwd = {"simtype" : "type", "masterfile" : "binding_txt"}

Option maps for maintaining backward compatibility.

Definition at line 243 of file parser.py.

7.27.3.3 dictionary forcebalance::parser::gen_opts_defaults = {}

Default general options - basically a collapsed veresion of gen_opts_types.

Definition at line 227 of file parser.py.

7.27.3.4 dictionary forcebalance::parser::gen_opts_types

Default general options.

Note that the documentation is included in part of the key; this will aid in automatic doc-extraction. :) In the 5-tuple we have: Default value, priority (larger number means printed first), short docstring, description of scope, list of filter strings for pulling out pertinent targets (MakeInputFile.py)

Definition at line 65 of file parser.py.

7.27.3.5 list forcebalance::parser::iocc = []

Check for uniqueness of option names.

Definition at line 216 of file parser.py.

7.27.3.6 tuple forcebalance::parser::logger = getLogger(__name__)

Definition at line 60 of file parser.py.

7.27.3.7 list forcebalance::parser::mainsections = ["SIMULATION","TARGET","OPTIONS","END","NONE"]

Listing of sections in the input file.

Definition at line 246 of file parser.py.

7.27.3.8 dictionary forcebalance::parser::ParsTab

Initial value:

```
{"read_mvals" : read_mvals,
            "read_pvals" : read_pvals,
            "priors"     : read_priors,
```

```
4             "internal"   : read_internals
5             }
```

ParsTab that refers to subsection parsers.

Definition at line 277 of file parser.py.

7.27.3.9 dictionary forcebalance::parser::subdict = {}

Definition at line 229 of file parser.py.

7.27.3.10 dictionary forcebalance::parser::tgt_opts_defaults = {}

Default target options - basically a collapsed version of tgt_opts_types.

Definition at line 235 of file parser.py.

7.27.3.11 dictionary forcebalance::parser::tgt_opts_types

Default fitting target options.

Definition at line 126 of file parser.py.

7.28 forcebalance::psi4io Namespace Reference

PSI4 force field input/output.

Classes

- class GBS_Reader

  Interaction type -> Parameter Dictionary.
- class THCDF_Psi4
- class Grid_Reader

  Finite state machine for parsing DVR grid files.
- class RDVR3_Psi4

  Subclass of Target for R-DVR3 grid fitting.

Variables

- tuple logger = getLogger(__name__)

7.28.1 Detailed Description

PSI4 force field input/output. This serves as a good template for writing future force matching I/O modules for other programs because it's so simple.

Author

Lee-Ping Wang

Date

01/2012

7.28.2 Variable Documentation

7.28.2.1 tuple forcebalance::psi4io::logger = getLogger(__name__)

Definition at line 24 of file psi4io.py.

7.29 forcebalance::PT Namespace Reference

Variables

- dictionary PeriodicTable
- list Elements

7.29.1 Variable Documentation

7.29.1.1 list forcebalance::PT::Elements

Initial value:

```
["None",'H','He',
            'Li','Be','B','C','N','O','F','Ne',
            'Na','Mg','Al','Si','P','S','Cl','Ar',
            'K','Ca','Sc','Ti','V','Cr','Mn','Fe','Co','Ni','Cu','Zn','Ga','Ge'
      ,'As','Se','Br','Kr',
            'Rb','Sr','Y','Zr','Nb','Mo','Tc','Ru','Rh','Pd','Ag','Cd','In','Sn
      ','Sb','Te','I','Xe',
            'Cs','Ba','La','Ce','Pr','Nd','Pm','Sm','Eu','Gd','Tb','Dy','Ho','
      Er','Tm','Yb',
            'Lu','Hf','Ta','W','Re','Os','Ir','Pt','Au','Hg','Tl','Pb','Bi','Po
      ','At','Rn',
            'Fr','Ra','Ac','Th','Pa','U','Np','Pu','Am','Cm','Bk','Cf','Es','Fm
      ','Md','No','Lr','Rf','Db','Sg','Bh','Hs','Mt']
```

Definition at line 18 of file PT.py.

7.29.1.2 dictionary forcebalance::PT::PeriodicTable

Initial value:

```
{'H' : 1.0079, 'He' : 4.0026,
                 'Li' : 6.941, 'Be' : 9.0122, 'B' : 10.811, 'C' : 12.0107, 'N'
      : 14.0067, 'O' : 15.9994, 'F' : 18.9984, 'Ne' : 20.1797,
                 'Na' : 22.9897, 'Mg' : 24.305, 'Al' : 26.9815, 'Si' : 28.0855,
       'P' : 30.9738, 'S' : 32.065, 'Cl' : 35.453, 'Ar' : 39.948,
                 'K' : 39.0983, 'Ca' : 40.078, 'Sc' : 44.9559, 'Ti' : 47.867, '
      V' : 50.9415, 'Cr' : 51.9961, 'Mn' : 54.938, 'Fe' : 55.845, 'Co' : 58.9332,
                 'Ni' : 58.6934, 'Cu' : 63.546, 'Zn' : 65.39, 'Ga' : 69.723, '
      Ge' : 72.64, 'As' : 74.9216, 'Se' : 78.96, 'Br' : 79.904, 'Kr' : 83.8,
                 'Rb' : 85.4678, 'Sr' : 87.62, 'Y' : 88.9059, 'Zr' : 91.224, '
      Nb' : 92.9064, 'Mo' : 95.94, 'Tc' : 98, 'Ru' : 101.07, 'Rh' : 102.9055,
                 'Pd' : 106.42, 'Ag' : 107.8682, 'Cd' : 112.411, 'In' : 114.818
      , 'Sn' : 118.71, 'Sb' : 121.76, 'Te' : 127.6, 'I' : 126.9045, 'Xe' : 131.293,
                 'Cs' : 132.9055, 'Ba' : 137.327, 'La' : 138.9055, 'Ce' : 140.1
      16, 'Pr' : 140.9077, 'Nd' : 144.24, 'Pm' : 145, 'Sm' : 150.36,
                 'Eu' : 151.964, 'Gd' : 157.25, 'Tb' : 158.9253, 'Dy' : 162.5,
      'Ho' : 164.9303, 'Er' : 167.259, 'Tm' : 168.9342, 'Yb' : 173.04,
                  'Lu' : 174.967, 'Hf' : 178.49, 'Ta' : 180.9479, 'W' : 183.84,
      'Re' : 186.207, 'Os' : 190.23, 'Ir' : 192.217, 'Pt' : 195.078,
                  'Au' : 196.9665, 'Hg' : 200.59, 'Tl' : 204.3833, 'Pb' : 207.2,
       'Bi' : 208.9804, 'Po' : 209, 'At' : 210, 'Rn' : 222,
```

```
12                 'Fr' : 223, 'Ra' : 226, 'Ac' : 227, 'Th' : 232.0381, 'Pa' : 23
      1.0359, 'U' : 238.0289, 'Np' : 237, 'Pu' : 244,
13                 'Am' : 243, 'Cm' : 247, 'Bk' : 247, 'Cf' : 251, 'Es' : 252, '
      Fm' : 257, 'Md' : 258, 'No' : 259,
14                 'Lr' : 262, 'Rf' : 261, 'Db' : 262, 'Sg' : 266, 'Bh' : 264, '
      Hs' : 277, 'Mt' : 268}
```

Definition at line 3 of file PT.py.

7.30 forcebalance::qchemio Namespace Reference

Q-Chem input file parser.

Classes

- class QCIn_Reader

  Finite state machine for parsing Q-Chem input files.

Functions

- def QChem_Dielectric_Energy

Variables

- tuple logger = getLogger(__name__)
- list ndtypes = [None]

  Types of counterpoise correction cptypes = [None, 'BASS', 'BASSP'] Types of NDDO correction.
- dictionary pdict

  Section -> Interaction type dictionary.

7.30.1 Detailed Description

Q-Chem input file parser.

7.30.2 Function Documentation

7.30.2.1 def forcebalance.qchemio.QChem_Dielectric_Energy (*fnm, wq*)

Definition at line 74 of file qchemio.py.

Here is the call graph for this function:

7.30.3 Variable Documentation

7.30.3.1 tuple forcebalance::qchemio::logger = getLogger(__name__)

Definition at line 11 of file qchemio.py.

7.30.3.2 list forcebalance::qchemio::ndtypes = [None]

Types of counterpoise correction cptypes = [None, 'BASS', 'BASSP'] Types of NDDO correction.

Definition at line 16 of file qchemio.py.

7.30.3.3 dictionary forcebalance::qchemio::pdict

Initial value:

```
{'BASS':{0:'A', 1:'C'},
         'BASSP' :{0:'A', 1:'B', 2:'C'}
         }
```

Section -> Interaction type dictionary.

fdict = { 'basis' : bastypes } Interaction type -> Parameter Dictionary.

Definition at line 23 of file qchemio.py.

7.31 forcebalance::target Namespace Reference

Classes

- class Target

  Base class for all fitting targets.
- class RemoteTarget

Variables

- tuple logger = getLogger(__name__)

7.31.1 Variable Documentation

7.31.1.1 tuple forcebalance::target::logger = getLogger(__name__)

Definition at line 17 of file target.py.

7.32 forcebalance::tinkerio Namespace Reference

TINKER input/output.

Classes

- class Tinker_Reader

  Finite state machine for parsing TINKER force field files.

- class Liquid_TINKER
- class AbInitio_TINKER

  Subclass of Target for force and energy matching using TINKER.
- class Vibration_TINKER

  Subclass of Target for vibrational frequency matching using TINKER.
- class Moments_TINKER

  Subclass of Target for multipole moment matching using TINKER.
- class BindingEnergy_TINKER

  Subclass of BindingEnergy for binding energy matching using TINKER.
- class Interaction_TINKER

  Subclass of Target for interaction matching using TINKER.

Functions

- def write_key_with_prm

  Copies a TINKER .key file but changes the parameter keyword as necessary to reflect the ForceBalance settings.
- def modify_key

  Performs in-place modification of a TINKER .key file.

Variables

- tuple logger = getLogger(__name__)
- dictionary pdict

7.32.1 Detailed Description

TINKER input/output. This serves as a good template for writing future force matching I/O modules for other programs because it's so simple.

Author

Lee-Ping Wang

Date

01/2012

7.32.2 Function Documentation

7.32.2.1 def forcebalance.tinkerio.modify_key (*src, in_dict*)

Performs in-place modification of a TINKER .key file.

The input dictionary contains key:value pairs such as "polarization direct". If the key exists in the TINKER file, then that line is modified such that it contains the value in the dictionary. Note that this "key" is not to be confused with the .key extension in the TINKER file that we're modifying.

Sometimes keys like 'archive' do not have a value, in which case the dictionary should contain a None value or a blank space.

If the key doesn't exist in the TINKER file, then the key:value pair will be printed at the end.

Parameters

in	*src*	Name of the TINKER file to be modified.
in	*in_dict*	Dictionary containing key-value pairs used to modify the TINKER file.

Definition at line 200 of file tinkerio.py.

7.32.2.2 def forcebalance.tinkerio.write_key_with_prm (*src*, *dest*, *prmfnm* = None, *ffobj* = None)

Copies a TINKER .key file but changes the parameter keyword as necessary to reflect the ForceBalance settings.

Definition at line 144 of file tinkerio.py.

Here is the call graph for this function:

7.32.3 Variable Documentation

7.32.3.1 tuple forcebalance::tinkerio::logger = getLogger(__name__)

Definition at line 30 of file tinkerio.py.

7.32.3.2 dictionary forcebalance::tinkerio::pdict

Initial value:

```
1 {'VDW'          : {'Atom':[1], 2:'S',3:'T',4:'D'}, # Van der Waals distance,
       well depth, distance from bonded neighbor?
2          'BOND'         : {'Atom':[1,2], 3:'K',4:'B'},     # Bond force
       constant and equilibrium distance (Angstrom)
3          'ANGLE'        : {'Atom':[1,2,3], 4:'K',5:'B'},   # Angle force
       constant and equilibrium angle
4          'UREYBRAD'     : {'Atom':[1,2,3], 4:'K',5:'B'},   # Urey-Bradley force
       constant and equilibrium distance (Angstrom)
5          'MCHARGE'       : {'Atom':[1,2,3], 4:''},          # Atomic charge
6          'DIPOLE'       : {0:'X',1:'Y',2:'Z'},             # Dipole moment in
       local frame
7          'QUADX'        : {0:'X'},                         # Quadrupole moment,
       X component
8          'QUADY'        : {0:'X',1:'Y'},                   # Quadrupole moment,
       Y component
9          'QUADZ'        : {0:'X',1:'Y',2:'Z'},             # Quadrupole moment,
       Y component
10          'POLARIZE'     : {'Atom':[1], 2:'A',3:'T'},       # Atomic dipole
       polarizability
11          'BOND-CUBIC'   : {'Atom':[], 0:''},    # Below are global parameters.
12          'BOND-QUARTIC' : {'Atom':[], 0:''},
13          'ANGLE-CUBIC'  : {'Atom':[], 0:''},
14          'ANGLE-QUARTIC': {'Atom':[], 0:''},
15          'ANGLE-PENTIC' : {'Atom':[], 0:''},
16          'ANGLE-SEXTIC' : {'Atom':[], 0:''},
17          'DIELECTRIC'   : {'Atom':[], 0:''},
18          'POLAR-SOR'    : {'Atom':[], 0:''}
19                                            # Ignored for now: stretch/bend
       coupling, out-of-plane bending,
```

```
20                                                  # torsional parameters,
      pi-torsion, torsion-torsion
21          }
```

Definition at line 32 of file tinkerio.py.

7.33 forcebalance::vibration Namespace Reference

Vibrational mode fitting module.

Classes

- class Vibration

  Subclass of Target for fitting force fields to vibrational spectra (from experiment or theory).

Variables

- tuple logger = getLogger(__name__)

7.33.1 Detailed Description

Vibrational mode fitting module.

Author

Lee-Ping Wang

Date

08/2012

7.33.2 Variable Documentation

7.33.2.1 tuple forcebalance::vibration::logger = getLogger(__name__)

Definition at line 22 of file vibration.py.

8 Class Documentation

8.1 forcebalance.abinitio.AbInitio Class Reference

Subclass of Target for fitting force fields to ab initio data.

Inheritance diagram for forcebalance.abinitio.AbInitio:

Collaboration diagram for forcebalance.abinitio.AbInitio:

Public Member Functions

- def __init__

  Initialization; define a few core concepts.
- def read_topology
- def build_invdist
- def compute_netforce_torque
- def read_reference_data

  Read the reference ab initio data from a file such as qdata.txt.
- def prepare_temp_directory

  Prepare the temporary directory, by default does nothing.
- def indicate
- def energy_force_transformer_all
- def energy_force_transformer
- def get_energy_force_

  LPW 06-30-2013.
- def get_resp_

Electrostatic potential fitting.

- def get

  Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- whamboltz_wts

  Initialize the base class.
- qmboltz_wts

  QM Boltzmann weights.
- eqm

  Reference (QM) energies.
- emd0

  Energies of the sampling simulation.
- fqm

  Reference (QM) forces.
- espxyz

  ESP grid points.
- espval

  ESP values.
- qfnm

  The qdata.txt file that contains the QM energies and forces.
- qmatoms

  The number of atoms in the QM calculation (Irrelevant if not fitting forces)
- e_err

  Qualitative Indicator: average energy error (in kJ/mol)
- e_err_pct

- f_err

  Qualitative Indicator: average force error (fractional)
- f_err_pct
- esp_err

  Qualitative Indicator: "relative RMS" for electrostatic potential.
- nf_err
- nf_err_pct
- tq_err_pct
- use_nft

  Whether to compute net forces and torques, or not.
- ns

  Read in the trajectory file.
- traj
- nparticles

  The number of (atoms + drude particles + virtual sites)
- AtomLists

  This is a default-dict containing a number of atom-wise lists, such as the residue number of each atom, the mass of each atom, and so on.
- new_vsites

  Read in the topology.
- save_vmvals

  Save the mvals from the last time we updated the vsites.
- topology_flag
- force_map
- nnf
- ntq
- force
- w_force
- nesp
- fitatoms
- whamboltz
- nftqm
- fref
- w_energy
- w_netforce
- w_torque
- e_ref
- f_ref
- nf_ref
- tq_ref
- tq_err
- w_resp
- invdists
- respterm
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.

- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.1.1 Detailed Description

Subclass of Target for fitting force fields to ab initio data.

Currently Gromacs-X2, Gromacs, Tinker, OpenMM and AMBER are supported.

We introduce the following concepts:

- The number of snapshots
- The reference energies and forces (eqm, fqm) and the file they belong in (qdata.txt)
- The sampling simulation energies (emd0)
- The WHAM Boltzmann weights (these are computed externally and passed in)
- The QM Boltzmann weights (computed internally using the difference between eqm and emd0)

There are also these little details:

- Switches for whether to turn on certain Boltzmann weights (they stack)
- Temperature for the QM Boltzmann weights
- Whether to fit a subset of atoms

This subclass contains the 'get' method for building the objective function from any simulation software (a driver to run the program and read output is still required). The 'get' method can be overridden by subclasses like AbInitio_GMX.

Definition at line 47 of file abinitio.py.

8.1.2 Constructor & Destructor Documentation

8.1.2.1 def forcebalance.abinitio.AbInitio.__init__ (*self, options, tgt_opts, forcefield*)

Initialization; define a few core concepts.

Todo Obtain the number of true atoms (or the particle -> atom mapping) from the force field.

Reimplemented from forcebalance.target.Target.

Reimplemented in forcebalance.gmxio.AbInitio_GMX, forcebalance.openmmio.AbInitio_OpenMM, forcebalance.tinkerio.AbInitio_TINKER, forcebalance.amberio.AbInitio_AMBER, and forcebalance.abinitio_internal.AbInitio_Internal.

Definition at line 57 of file abinitio.py.

Here is the call graph for this function:

8.1.3 Member Function Documentation

8.1.3.1 def forcebalance.abinitio.AbInitio.build_invdist (*self, mvals*)

Definition at line 168 of file abinitio.py.

Here is the call graph for this function:

8.1.3.2 def forcebalance.abinitio.AbInitio.compute_netforce_torque (*self, xyz, force, QM* = `False`)

Definition at line 204 of file abinitio.py.

8.1.3.3 def forcebalance.abinitio.AbInitio.energy_force_transformer (*self, i*)

Definition at line 459 of file abinitio.py.

Here is the call graph for this function:

8.1.3.4 def forcebalance.abinitio.AbInitio.energy_force_transformer_all (*self*)

Definition at line 442 of file abinitio.py.

Here is the call graph for this function:

8.1.3.5 def forcebalance.abinitio.AbInitio.get (*self, mvals, AGrad* = `False`, *AHess* = `False`)

Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.

See abinitio for an example.

Reimplemented from forcebalance.target.Target.

Definition at line 1100 of file abinitio.py.

8.1.3.6 def forcebalance.abinitio.AbInitio.get_energy_force_ (*self, mvals, AGrad* = `False`, *AHess* = `False`)

LPW 06-30-2013.

This subroutine builds the objective function (and optionally its derivatives) from a general simulation software. This is in contrast to using GROMACS-X2, which computes the objective function and prints it out; then 'get' only needs to call GROMACS and read it in.

This subroutine interfaces with simulation software 'drivers'. The driver is only expected to give the energy and forces.

Now this subroutine may sound trivial since the objective function is simply a least-squares quantity (M-Q)^2 - but there are a number of nontrivial considerations. I will list them here.

0) Polytensor formulation: Because there may exist covariance between different components of the force (or covariance between the energy and the force), we build the objective function by taking outer products of vectors that have the form [E F_1x F_1y F_1z F_2x F_2y ...], and then we trace it with the inverse of the covariance matrix to get the objective function.

This version implements both the polytensor formulation and the standard formulation.

1) Boltzmann weights and normalization: Each snapshot has its own Boltzmann weight, which may or may not be normalized. This subroutine does the normalization automatically.

2) Subtracting out the mean energy gap: The zero-point energy difference between reference data and simulation is meaningless. This subroutine subtracts it out.

3) Hybrid ensembles: This program builds a combined objective function from both MM and QM ensembles, which is rigorously better than using a single ensemble.

Note that this subroutine does not do EVERYTHING that GROMACS-X2 can do, which includes:

1) Internal coordinate systems 2) 'Sampling correction' (deprecated, since it doesn't seem to work) 3) Analytic derivatives

In the previous code (ForTune) this subroutine used analytic first derivatives of the energy and force to build the deriva-

tives of the objective function. Here I will take a simplified approach, because building the derivatives are cumbersome. For now we will return the objective function ONLY. A two-point central difference should give us the first and diagonal second derivative anyhow.

Todo Parallelization over snapshots is not implemented yet

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient
in	*AHess*	Switch to turn on analytic Hessian

Returns

Answer Contribution to the objective function

Definition at line 534 of file abinitio.py.

8.1.3.7 def forcebalance.target.Target.get_G (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.1.3.8 def forcebalance.target.Target.get_H (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.1.3.9 def forcebalance.abinitio.AbInitio.get_resp_ (*self*, *mvals*, *AGrad* = `False`, *AHess* = `False`)

Electrostatic potential fitting.

Implements the RESP objective function. (In Python so obviously not optimized.) This function takes the mathematical parameter values and returns the charges on the ATOMS (fancy mapping going on)

Definition at line 1001 of file abinitio.py.

8.1.3.10 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.1.3.11 def forcebalance.abinitio.AbInitio.indicate (*self*)

Definition at line 422 of file abinitio.py.

Here is the call graph for this function:

8.1.3.12 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.1.3.13 def forcebalance.abinitio.AbInitio.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory, by default does nothing.

Reimplemented in forcebalance.gmxio.AbInitio_GMX, forcebalance.openmmio.AbInitio_OpenMM, forcebalance.tinkerio.AbInitio_TINKER, and forcebalance.amberio.AbInitio_AMBER.

Definition at line 419 of file abinitio.py.

8.1.3.14 def forcebalance.target.Target.printcool_table (*self*, *data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.1.3.15 def forcebalance.abinitio.AbInitio.read_reference_data (*self*)

Read the reference ab initio data from a file such as qdata.txt.

Todo Add an option for picking any slice out of qdata.txt, helpful for cross-validation

Todo Closer integration of reference data with program - leave behind the qdata.txt format? (For now, I like the readability of qdata.txt)

After reading in the information from qdata.txt, it is converted into the GROMACS energy units (kind of an arbitrary choice); forces (kind of a misnomer in qdata.txt) are multipled by -1 to convert gradients to forces.

We also subtract out the mean energies of all energy arrays because energy/force matching does not account for zero-point energy differences between MM and QM (i.e. energy of electrons in core orbitals).

The configurations in force/energy matching typically come from a the thermodynamic ensemble of the MM force field at some temperature (by running MD, for example), and for many reasons it is helpful to introduce non-Boltzmann weights in front of these configurations. There are two options: WHAM Boltzmann weights (for combining the weights of several simulations together) and QM Boltzmann weights (for converting MM weights into QM weights). Note that the two sets of weights 'stack'; i.e. they can be used at the same time.

A 'hybrid' ensemble is possible where we use 50% MM and 50% QM weights. Please read more in LPW and Troy Van Voorhis, JCP Vol. 133, Pg. 231101 (2010), doi:10.1063/1.3519043.

Todo The WHAM Boltzmann weights are generated by external scripts (wanalyze.py and make-wham-data.sh) and passed in; perhaps these scripts can be added to the ForceBalance distribution or integrated more tightly.

Finally, note that using non-Boltzmann weights degrades the statistical information content of the snapshots. This problem will generally become worse if the ensemble to which we're reweighting is dramatically different from the one we're sampling from. We end up with a set of Boltzmann weights like [1e-9, 1e-9, 1.0, 1e-9, 1e-9 ...] and this is essentially just one snapshot. I believe Troy is working on something to cure this problem.

Here, we have a measure for the information content of our snapshots, which comes easily from the definition of information entropy:

S = -1∗Sum_i(P_i∗log(P_i)) InfoContent = exp(-S)

With uniform weights, InfoContent is equal to the number of snapshots; with horrible weights, InfoContent is closer to one.

Definition at line 317 of file abinitio.py.

8.1.3.16 def forcebalance.abinitio.AbInitio.read_topology (*self*)

Reimplemented in forcebalance.gmxio.AbInitio_GMX, and forcebalance.openmmio.AbInitio_OpenMM.

Definition at line 164 of file abinitio.py.

8.1.3.17 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.1.3.18 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.1.3.19 def forcebalance.target.Target.sget (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.1.3.20 def forcebalance.target.Target.stage (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.1.3.21 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.1.3.22 def forcebalance.target.Target.wq_complete (*self*) `[inherited]`

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.1.4 Member Data Documentation

8.1.4.1 forcebalance::abinitio.AbInitio::AtomLists

This is a default-dict containing a number of atom-wise lists, such as the residue number of each atom, the mass of each atom, and so on.

Reimplemented in forcebalance.gmxio.AbInitio_GMX.

Definition at line 92 of file abinitio.py.

8.1.4.2 forcebalance::abinitio.AbInitio::e_err

Qualitative Indicator: average energy error (in kJ/mol)

Definition at line 85 of file abinitio.py.

8.1.4.3 forcebalance::abinitio.AbInitio::e_err_pct

Definition at line 85 of file abinitio.py.

8.1.4.4 forcebalance::abinitio.AbInitio::e_ref

Definition at line 534 of file abinitio.py.

8.1.4.5 forcebalance::abinitio.AbInitio::emd0

Energies of the sampling simulation.

Definition at line 79 of file abinitio.py.

8.1.4.6 forcebalance::abinitio.AbInitio::eqm

Reference (QM) energies.

Definition at line 78 of file abinitio.py.

8.1.4.7 forcebalance::abinitio.AbInitio::esp_err

Qualitative Indicator: "relative RMS" for electrostatic potential.

Definition at line 87 of file abinitio.py.

8.1.4.8 forcebalance::abinitio.AbInitio::espval

ESP values.

Definition at line 82 of file abinitio.py.

8.1.4.9 forcebalance::abinitio.AbInitio::espxyz

ESP grid points.

Definition at line 81 of file abinitio.py.

8.1.4.10 forcebalance::abinitio.AbInitio::f_err

Qualitative Indicator: average force error (fractional)

Definition at line 86 of file abinitio.py.

8.1.4.11 forcebalance::abinitio.AbInitio::f_err_pct

Definition at line 86 of file abinitio.py.

8.1.4.12 forcebalance::abinitio.AbInitio::f_ref

Definition at line 534 of file abinitio.py.

8.1.4.13 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.1.4.14 forcebalance::abinitio.AbInitio::fitatoms

Definition at line 317 of file abinitio.py.

8.1.4.15 forcebalance::abinitio.AbInitio::force

Definition at line 317 of file abinitio.py.

8.1.4.16 forcebalance::abinitio.AbInitio::force_map

Definition at line 204 of file abinitio.py.

8.1.4.17 forcebalance::abinitio.AbInitio::fqm

Reference (QM) forces.

Definition at line 80 of file abinitio.py.

8.1.4.18 forcebalance::abinitio.AbInitio::fref

Definition at line 317 of file abinitio.py.

8.1.4.19 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.1.4.20 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.1.4.21 forcebalance::abinitio.AbInitio::invdists

Definition at line 1001 of file abinitio.py.

8.1.4.22 forcebalance::abinitio.AbInitio::nesp

Definition at line 317 of file abinitio.py.

8.1.4.23 forcebalance::abinitio.AbInitio::new_vsites

Read in the topology.

Read in the reference data Prepare the temporary directory The below two options are related to whether we want to rebuild virtual site positions. Rebuild the distance matrix if virtual site positions have changed

Definition at line 97 of file abinitio.py.

8.1.4.24 forcebalance::abinitio.AbInitio::nf_err

Definition at line 87 of file abinitio.py.

8.1.4.25 forcebalance::abinitio.AbInitio::nf_err_pct

Definition at line 87 of file abinitio.py.

8.1.4.26 forcebalance::abinitio.AbInitio::nf_ref

Definition at line 534 of file abinitio.py.

8.1.4.27 forcebalance::abinitio.AbInitio::nftqm

Definition at line 317 of file abinitio.py.

8.1.4.28 forcebalance::abinitio.AbInitio::nnf

Definition at line 204 of file abinitio.py.

8.1.4.29 forcebalance::abinitio.AbInitio::nparticles

The number of (atoms + drude particles + virtual sites)

Definition at line 90 of file abinitio.py.

8.1.4.30 forcebalance::abinitio.AbInitio::ns

Read in the trajectory file.

Definition at line 89 of file abinitio.py.

8.1.4.31 forcebalance::abinitio.AbInitio::ntq

Definition at line 204 of file abinitio.py.

8.1.4.32 forcebalance::abinitio.AbInitio::objective

Definition at line 1100 of file abinitio.py.

8.1.4.33 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.1.4.34 forcebalance::abinitio.AbInitio::qfnm

The qdata.txt file that contains the QM energies and forces.

Definition at line 83 of file abinitio.py.

8.1.4.35 forcebalance::abinitio.AbInitio::qmatoms

The number of atoms in the QM calculation (Irrelevant if not fitting forces)

Definition at line 84 of file abinitio.py.

8.1.4.36 forcebalance::abinitio.AbInitio::qmboltz_wts

QM Boltzmann weights.

Definition at line 77 of file abinitio.py.

8.1.4.37 forcebalance::abinitio.AbInitio::respterm

Definition at line 1001 of file abinitio.py.

8.1.4.38 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.1.4.39 forcebalance::abinitio.AbInitio::save_vmvals

Save the mvals from the last time we updated the vsites.

Definition at line 98 of file abinitio.py.

8.1.4.40 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.1.4.41 forcebalance::abinitio.AbInitio::topology_flag

Reimplemented in forcebalance.gmxio.AbInitio_GMX, and forcebalance.openmmio.AbInitio_OpenMM.

Definition at line 164 of file abinitio.py.

8.1.4.42 forcebalance::abinitio.AbInitio::tq_err

Definition at line 534 of file abinitio.py.

8.1.4.43 forcebalance::abinitio.AbInitio::tq_err_pct

Definition at line 87 of file abinitio.py.

8.1.4.44 forcebalance::abinitio.AbInitio::tq_ref

Definition at line 534 of file abinitio.py.

8.1.4.45 forcebalance::abinitio.AbInitio::traj

Definition at line 89 of file abinitio.py.

8.1.4.46 forcebalance::abinitio.AbInitio::use_nft

Whether to compute net forces and torques, or not.

Definition at line 88 of file abinitio.py.

8.1.4.47 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.1.4.48 forcebalance::abinitio.AbInitio::w_energy

Definition at line 534 of file abinitio.py.

8.1.4.49 forcebalance::abinitio.AbInitio::w_force

Definition at line 317 of file abinitio.py.

8.1.4.50 forcebalance::abinitio.AbInitio::w_netforce

Definition at line 534 of file abinitio.py.

8.1.4.51 forcebalance::abinitio.AbInitio::w_resp

Definition at line 1001 of file abinitio.py.

8.1.4.52 forcebalance::abinitio.AbInitio::w_torque

Definition at line 534 of file abinitio.py.

8.1.4.53 forcebalance::abinitio.AbInitio::whamboltz

Definition at line 317 of file abinitio.py.

8.1.4.54 forcebalance::abinitio.AbInitio::whamboltz_wts

Initialize the base class.

Number of snapshots Whether to use WHAM Boltzmann weights Whether to use the Sampling Correction Whether to match Absolute Energies (make sure you know what you're doing) Whether to use the Covariance Matrix Whether to use QM Boltzmann weights The temperature for QM Boltzmann weights Number of atoms that we are fitting Whether to fit Energies. Whether to fit Forces. Whether to fit Electrostatic Potential. Weights for the three components. Option for how much data to write to disk. Whether to do energy and force calculations for the whole trajectory, or to do one calculation per snapshot. OpenMM-only option - whether to run the energies and forces internally. Whether we have virtual sites (set at the global option level) WHAM Boltzmann weights

Definition at line 76 of file abinitio.py.

8.1.4.55 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- abinitio.py

8.2 forcebalance.amberio.AbInitio_AMBER Class Reference

Subclass of Target for force and energy matching using AMBER.

Inheritance diagram for forcebalance.amberio.AbInitio_AMBER:

Collaboration diagram for forcebalance.amberio.AbInitio_AMBER:

Public Member Functions

- def __init__

  Initialization; define a few core concepts.
- def prepare_temp_directory

  Prepare the temporary directory, by default does nothing.
- def energy_force_driver_all_external_
- def energy_force_driver_all
- def read_topology
- def build_invdist
- def compute_netforce_torque
- def read_reference_data

  Read the reference ab initio data from a file such as qdata.txt.
- def indicate
- def energy_force_transformer_all
- def energy_force_transformer
- def get_energy_force_

  LPW 06-30-2013.
- def get_resp_

  Electrostatic potential fitting.
- def get

  Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- trajfnm

  Name of the trajectory, we need this BEFORE initializing the SuperClass.
- all_at_once

  all_at_once is not implemented.
- whamboltz_wts

  Initialize the base class.
- qmboltz_wts

  QM Boltzmann weights.
- eqm

  Reference (QM) energies.
- emd0

  Energies of the sampling simulation.
- fqm

  Reference (QM) forces.
- espxyz

  ESP grid points.
- espval

  ESP values.
- qfnm

  The qdata.txt file that contains the QM energies and forces.
- qmatoms

  The number of atoms in the QM calculation (Irrelevant if not fitting forces)
- e_err

  Qualitative Indicator: average energy error (in kJ/mol)
- e_err_pct
- f_err

  Qualitative Indicator: average force error (fractional)
- f_err_pct
- esp_err

  Qualitative Indicator: "relative RMS" for electrostatic potential.
- nf_err
- nf_err_pct
- tq_err_pct
- use_nft

  Whether to compute net forces and torques, or not.
- ns

  Read in the trajectory file.
- traj
- nparticles

  The number of (atoms + drude particles + virtual sites)
- AtomLists

  This is a default-dict containing a number of atom-wise lists, such as the residue number of each atom, the mass of each atom, and so on.
- new_vsites

  Read in the topology.
- save_vmvals

Save the mvals from the last time we updated the vsites.

- topology_flag
- force_map
- nnf
- ntq
- force
- w_force
- nesp
- fitatoms
- whamboltz
- nftqm
- fref
- w_energy
- w_netforce
- w_torque
- e_ref
- f_ref
- nf_ref
- tq_ref
- tq_err
- w_resp
- invdists
- respterm
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.2.1 Detailed Description

Subclass of Target for force and energy matching using AMBER.

Implements the prepare and energy_force_driver methods. The get method is in the base class.

Definition at line 171 of file amberio.py.

8.2.2 Constructor & Destructor Documentation

8.2.2.1 def forcebalance.amberio.AbInitio_AMBER.__init__ (*self, options, tgt_opts, forcefield*)

Initialization; define a few core concepts.

Todo Obtain the number of true atoms (or the particle -> atom mapping) from the force field.

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 174 of file amberio.py.

8.2.3 Member Function Documentation

8.2.3.1 def forcebalance.abinitio.AbInitio.build_invdist (*self, mvals*) [inherited]

Definition at line 168 of file abinitio.py.

Here is the call graph for this function:

8.2.3.2 def forcebalance.abinitio.AbInitio.compute_netforce_torque (*self, xyz, force, QM* = False) [inherited]

Definition at line 204 of file abinitio.py.

8.2.3.3 def forcebalance.amberio.AbInitio_AMBER.energy_force_driver_all (*self*)

Definition at line 228 of file amberio.py.

8.2.3.4 def forcebalance.amberio.AbInitio_AMBER.energy_force_driver_all_external_ (*self*)

Definition at line 190 of file amberio.py.

Here is the call graph for this function:

8.2.3.5 def forcebalance.abinitio.AbInitio.energy_force_transformer (*self, i*) [inherited]

Definition at line 459 of file abinitio.py.

Here is the call graph for this function:

8.2.3.6 def forcebalance.abinitio.AbInitio.energy_force_transformer_all (*self*) [inherited]

Definition at line 442 of file abinitio.py.

Here is the call graph for this function:

8.2.3.7 def forcebalance.abinitio.AbInitio.get (*self, mvals, AGrad* = False, *AHess* = False) [inherited]

Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.

See abinitio for an example.

Reimplemented from forcebalance.target.Target.

Definition at line 1100 of file abinitio.py.

8.2.3.8 def forcebalance.abinitio.AbInitio.get_energy_force_ (*self, mvals, AGrad* = False, *AHess* = False) [inherited]

LPW 06-30-2013.

This subroutine builds the objective function (and optionally its derivatives) from a general simulation software. This is in contrast to using GROMACS-X2, which computes the objective function and prints it out; then 'get' only needs to call GROMACS and read it in.

This subroutine interfaces with simulation software 'drivers'. The driver is only expected to give the energy and forces.

Now this subroutine may sound trivial since the objective function is simply a least-squares quantity (M-Q)^2 - but there

are a number of nontrivial considerations. I will list them here.

0) Polytensor formulation: Because there may exist covariance between different components of the force (or covariance between the energy and the force), we build the objective function by taking outer products of vectors that have the form [E F_1x F_1y F_1z F_2x F_2y ...], and then we trace it with the inverse of the covariance matrix to get the objective function.

This version implements both the polytensor formulation and the standard formulation.

1) Boltzmann weights and normalization: Each snapshot has its own Boltzmann weight, which may or may not be normalized. This subroutine does the normalization automatically.

2) Subtracting out the mean energy gap: The zero-point energy difference between reference data and simulation is meaningless. This subroutine subtracts it out.

3) Hybrid ensembles: This program builds a combined objective function from both MM and QM ensembles, which is rigorously better than using a single ensemble.

Note that this subroutine does not do EVERYTHING that GROMACS-X2 can do, which includes:

1) Internal coordinate systems 2) 'Sampling correction' (deprecated, since it doesn't seem to work) 3) Analytic derivatives

In the previous code (ForTune) this subroutine used analytic first derivatives of the energy and force to build the derivatives of the objective function. Here I will take a simplified approach, because building the derivatives are cumbersome. For now we will return the objective function ONLY. A two-point central difference should give us the first and diagonal second derivative anyhow.

Todo Parallelization over snapshots is not implemented yet

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient
in	*AHess*	Switch to turn on analytic Hessian

Returns

Answer Contribution to the objective function

Definition at line 534 of file abinitio.py.

8.2.3.9 def forcebalance.target.Target.get_G (*self, mvals =* None) [inherited]

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.2.3.10 def forcebalance.target.Target.get_H (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.2.3.11 def forcebalance.abinitio.AbInitio.get_resp_ (*self*, *mvals*, *AGrad* = `False`, *AHess* = `False`) `[inherited]`

Electrostatic potential fitting.

Implements the RESP objective function. (In Python so obviously not optimized.) This function takes the mathematical parameter values and returns the charges on the ATOMS (fancy mapping going on)

Definition at line 1001 of file abinitio.py.

8.2.3.12 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) `[inherited]`

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.2.3.13 def forcebalance.abinitio.AbInitio.indicate (*self*) [inherited]

Definition at line 422 of file abinitio.py.

Here is the call graph for this function:

8.2.3.14 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.2.3.15 def forcebalance.amberio.AbInitio_AMBER.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory, by default does nothing.

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 181 of file amberio.py.

Here is the call graph for this function:

8.2.3.16 def forcebalance.target.Target.printcool_table (*self*, *data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.2.3.17 def forcebalance.abinitio.AbInitio.read_reference_data (*self*) `[inherited]`

Read the reference ab initio data from a file such as qdata.txt.

Todo Add an option for picking any slice out of qdata.txt, helpful for cross-validation

Todo Closer integration of reference data with program - leave behind the qdata.txt format? (For now, I like the readability of qdata.txt)

After reading in the information from qdata.txt, it is converted into the GROMACS energy units (kind of an arbitrary choice); forces (kind of a misnomer in qdata.txt) are multipled by -1 to convert gradients to forces.

We also subtract out the mean energies of all energy arrays because energy/force matching does not account for zero-point energy differences between MM and QM (i.e. energy of electrons in core orbitals).

The configurations in force/energy matching typically come from a the thermodynamic ensemble of the MM force field at some temperature (by running MD, for example), and for many reasons it is helpful to introduce non-Boltzmann weights in front of these configurations. There are two options: WHAM Boltzmann weights (for combining the weights of several simulations together) and QM Boltzmann weights (for converting MM weights into QM weights). Note that the two sets of weights 'stack'; i.e. they can be used at the same time.

A 'hybrid' ensemble is possible where we use 50% MM and 50% QM weights. Please read more in LPW and Troy Van Voorhis, JCP Vol. 133, Pg. 231101 (2010), doi:10.1063/1.3519043.

Todo The WHAM Boltzmann weights are generated by external scripts (wanalyze.py and make-wham-data.sh) and passed in; perhaps these scripts can be added to the ForceBalance distribution or integrated more tightly.

Finally, note that using non-Boltzmann weights degrades the statistical information content of the snapshots. This problem will generally become worse if the ensemble to which we're reweighting is dramatically different from the one we're sampling from. We end up with a set of Boltzmann weights like [1e-9, 1e-9, 1.0, 1e-9, 1e-9 ...] and this is essentially just one snapshot. I believe Troy is working on something to cure this problem.

Here, we have a measure for the information content of our snapshots, which comes easily from the definition of information entropy:

S = -1∗Sum_i(P_i∗log(P_i)) InfoContent = exp(-S)

With uniform weights, InfoContent is equal to the number of snapshots; with horrible weights, InfoContent is closer to one.

Definition at line 317 of file abinitio.py.

8.2.3.18 def forcebalance.abinitio.AbInitio.read_topology (*self*) [inherited]

Reimplemented in forcebalance.gmxio.AbInitio_GMX, and forcebalance.openmmio.AbInitio_OpenMM.

Definition at line 164 of file abinitio.py.

8.2.3.19 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.2.3.20 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.2.3.21 def forcebalance.target.Target.sget (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.2.3.22 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) `[inherited]`

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.2.3.23 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.2.3.24 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.2.4 Member Data Documentation

8.2.4.1 forcebalance::amberio.AbInitio_AMBER::all_at_once

all_at_once is not implemented.

Definition at line 176 of file amberio.py.

8.2.4.2 forcebalance::abinitio.AbInitio::AtomLists [inherited]

This is a default-dict containing a number of atom-wise lists, such as the residue number of each atom, the mass of each atom, and so on.

Reimplemented in forcebalance.gmxio.AbInitio_GMX.

Definition at line 92 of file abinitio.py.

8.2.4.3 forcebalance::abinitio.AbInitio::e_err [inherited]

Qualitative Indicator: average energy error (in kJ/mol)

Definition at line 85 of file abinitio.py.

8.2.4.4 forcebalance::abinitio.AbInitio::e_err_pct [inherited]

Definition at line 85 of file abinitio.py.

8.2.4.5 forcebalance::abinitio.AbInitio::e_ref [inherited]

Definition at line 534 of file abinitio.py.

8.2.4.6 forcebalance::abinitio.AbInitio::emd0 [inherited]

Energies of the sampling simulation.

Definition at line 79 of file abinitio.py.

8.2.4.7 forcebalance::abinitio.AbInitio::eqm [inherited]

Reference (QM) energies.

Definition at line 78 of file abinitio.py.

8.2.4.8 forcebalance::abinitio.AbInitio::esp_err [inherited]

Qualitative Indicator: "relative RMS" for electrostatic potential.

Definition at line 87 of file abinitio.py.

8.2.4.9 forcebalance::abinitio.AbInitio::espval [inherited]

ESP values.

Definition at line 82 of file abinitio.py.

8.2.4.10 forcebalance::abinitio.AbInitio::espxyz [inherited]

ESP grid points.

Definition at line 81 of file abinitio.py.

8.2.4.11 forcebalance::abinitio.AbInitio::f_err [inherited]

Qualitative Indicator: average force error (fractional)

Definition at line 86 of file abinitio.py.

8.2.4.12 forcebalance::abinitio.AbInitio::f_err_pct [inherited]

Definition at line 86 of file abinitio.py.

8.2.4.13 forcebalance::abinitio.AbInitio::f_ref [inherited]

Definition at line 534 of file abinitio.py.

8.2.4.14 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.2.4.15 forcebalance::abinitio.AbInitio::fitatoms [inherited]

Definition at line 317 of file abinitio.py.

8.2.4.16 forcebalance::abinitio.AbInitio::force [inherited]

Definition at line 317 of file abinitio.py.

8.2.4.17 forcebalance::abinitio.AbInitio::force_map [inherited]

Definition at line 204 of file abinitio.py.

8.2.4.18 forcebalance::abinitio.AbInitio::fqm [inherited]

Reference (QM) forces.

Definition at line 80 of file abinitio.py.

8.2.4.19 forcebalance::abinitio.AbInitio::fref [inherited]

Definition at line 317 of file abinitio.py.

8.2.4.20 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.2.4.21 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.2.4.22 forcebalance::abinitio.AbInitio::invdists [inherited]

Definition at line 1001 of file abinitio.py.

8.2.4.23 forcebalance::abinitio.AbInitio::nesp [inherited]

Definition at line 317 of file abinitio.py.

8.2.4.24 forcebalance::abinitio.AbInitio::new_vsites [inherited]

Read in the topology.

Read in the reference data Prepare the temporary directory The below two options are related to whether we want to rebuild virtual site positions. Rebuild the distance matrix if virtual site positions have changed

Definition at line 97 of file abinitio.py.

8.2.4.25 forcebalance::abinitio.AbInitio::nf_err [inherited]

Definition at line 87 of file abinitio.py.

8.2.4.26 forcebalance::abinitio.AbInitio::nf_err_pct [inherited]

Definition at line 87 of file abinitio.py.

8.2.4.27 forcebalance::abinitio.AbInitio::nf_ref [inherited]

Definition at line 534 of file abinitio.py.

8.2.4.28 forcebalance::abinitio.AbInitio::nftqm [inherited]

Definition at line 317 of file abinitio.py.

8.2.4.29 forcebalance::abinitio.AbInitio::nnf [inherited]

Definition at line 204 of file abinitio.py.

8.2.4.30 forcebalance::abinitio.AbInitio::nparticles [inherited]

The number of (atoms + drude particles + virtual sites)

Definition at line 90 of file abinitio.py.

8.2.4.31 forcebalance::abinitio.AbInitio::ns [inherited]

Read in the trajectory file.

Definition at line 89 of file abinitio.py.

8.2.4.32 forcebalance::abinitio.AbInitio::ntq [inherited]

Definition at line 204 of file abinitio.py.

8.2.4.33 forcebalance::abinitio.AbInitio::objective [inherited]

Definition at line 1100 of file abinitio.py.

8.2.4.34 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.2.4.35 forcebalance::abinitio.AbInitio::qfnm [inherited]

The qdata.txt file that contains the QM energies and forces.

Definition at line 83 of file abinitio.py.

8.2.4.36 forcebalance::abinitio.AbInitio::qmatoms [inherited]

The number of atoms in the QM calculation (Irrelevant if not fitting forces)

Definition at line 84 of file abinitio.py.

8.2.4.37 forcebalance::abinitio.AbInitio::qmboltz_wts [inherited]

QM Boltzmann weights.

Definition at line 77 of file abinitio.py.

8.2.4.38 forcebalance::abinitio.AbInitio::respterm [inherited]

Definition at line 1001 of file abinitio.py.

8.2.4.39 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.2.4.40 forcebalance::abinitio.AbInitio::save_vmvals [inherited]

Save the mvals from the last time we updated the vsites.

Definition at line 98 of file abinitio.py.

8.2.4.41 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.2.4.42 forcebalance::abinitio.AbInitio::topology_flag [inherited]

Reimplemented in forcebalance.gmxio.AbInitio_GMX, and forcebalance.openmmio.AbInitio_OpenMM.

Definition at line 164 of file abinitio.py.

8.2.4.43 forcebalance::abinitio.AbInitio::tq_err [inherited]

Definition at line 534 of file abinitio.py.

8.2.4.44 forcebalance::abinitio.AbInitio::tq_err_pct [inherited]

Definition at line 87 of file abinitio.py.

8.2.4.45 forcebalance::abinitio.AbInitio::tq_ref [inherited]

Definition at line 534 of file abinitio.py.

8.2.4.46 forcebalance::abinitio.AbInitio::traj [inherited]

Definition at line 89 of file abinitio.py.

8.2.4.47 forcebalance::amberio.AbInitio_AMBER::trajfnm

Name of the trajectory, we need this BEFORE initializing the SuperClass.

Definition at line 175 of file amberio.py.

8.2.4.48 forcebalance::abinitio.AbInitio::use_nft [inherited]

Whether to compute net forces and torques, or not.

Definition at line 88 of file abinitio.py.

8.2.4.49 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.2.4.50 forcebalance::abinitio.AbInitio::w_energy [inherited]

Definition at line 534 of file abinitio.py.

8.2.4.51 forcebalance::abinitio.AbInitio::w_force [inherited]

Definition at line 317 of file abinitio.py.

8.2.4.52 forcebalance::abinitio.AbInitio::w_netforce [inherited]

Definition at line 534 of file abinitio.py.

8.2.4.53 forcebalance::abinitio.AbInitio::w_resp [inherited]

Definition at line 1001 of file abinitio.py.

8.2.4.54 forcebalance::abinitio.AbInitio::w_torque [inherited]

Definition at line 534 of file abinitio.py.

8.2.4.55 forcebalance::abinitio.AbInitio::whamboltz [inherited]

Definition at line 317 of file abinitio.py.

8.2.4.56 forcebalance::abinitio.AbInitio::whamboltz_wts [inherited]

Initialize the base class.

Number of snapshots Whether to use WHAM Boltzmann weights Whether to use the Sampling Correction Whether to match Absolute Energies (make sure you know what you're doing) Whether to use the Covariance Matrix Whether to use QM Boltzmann weights The temperature for QM Boltzmann weights Number of atoms that we are fitting Whether to fit Energies. Whether to fit Forces. Whether to fit Electrostatic Potential. Weights for the three components. Option for how much data to write to disk. Whether to do energy and force calculations for the whole trajectory, or to do one calculation per snapshot. OpenMM-only option - whether to run the energies and forces internally. Whether we have virtual sites (set at the global option level) WHAM Boltzmann weights

Definition at line 76 of file abinitio.py.

8.2.4.57 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- amberio.py

8.3 forcebalance.gmxio.AbInitio_GMX Class Reference

Subclass of AbInitio for force and energy matching using normal GROMACS.

Inheritance diagram for forcebalance.gmxio.AbInitio_GMX:

Collaboration diagram for forcebalance.gmxio.AbInitio_GMX:

Public Member Functions

- def __init__

  Initialization; define a few core concepts.
- def prepare_temp_directory

  Prepare the temporary directory, by default does nothing.
- def read_topology
- def energy_force_driver

  Computes the energy and force using GROMACS for a single snapshot.
- def energy_force_driver_all

  Computes the energy and force using GROMACS for a trajectory.
- def generate_vsite_positions

  Call mdrun in order to update the virtual site positions.
- def build_invdist
- def compute_netforce_torque
- def read_reference_data

  Read the reference ab initio data from a file such as qdata.txt.
- def indicate
- def energy_force_transformer_all
- def energy_force_transformer
- def get_energy_force_

  LPW 06-30-2013.
- def get_resp_

  Electrostatic potential fitting.
- def get

  Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- engine

  Default file names for coordinates, top and mdp files.
- AtomMask
- AtomLists

  This is a default-dict containing a number of atom-wise lists, such as the residue number of each atom, the mass of each atom, and so on.
- topology_flag
- whamboltz_wts

  Initialize the base class.
- qmboltz_wts

  QM Boltzmann weights.
- eqm

  Reference (QM) energies.
- emd0

  Energies of the sampling simulation.
- fqm

  Reference (QM) forces.
- espxyz

  ESP grid points.
- espval

  ESP values.
- qfnm

  The qdata.txt file that contains the QM energies and forces.
- qmatoms

  The number of atoms in the QM calculation (Irrelevant if not fitting forces)
- e_err

  Qualitative Indicator: average energy error (in kJ/mol)
- e_err_pct
- f_err

  Qualitative Indicator: average force error (fractional)
- f_err_pct
- esp_err

  Qualitative Indicator: "relative RMS" for electrostatic potential.
- nf_err
- nf_err_pct
- tq_err_pct
- use_nft

  Whether to compute net forces and torques, or not.
- ns

  Read in the trajectory file.
- traj
- nparticles

  The number of (atoms + drude particles + virtual sites)
- new_vsites

  Read in the topology.
- save_vmvals

Save the mvals from the last time we updated the vsites.

- force_map
- nnf
- ntq
- force
- w_force
- nesp
- fitatoms
- whamboltz
- nftqm
- fref
- w_energy
- w_netforce
- w_torque
- e_ref
- f_ref
- nf_ref
- tq_ref
- tq_err
- w_resp
- invdists
- respterm
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.3.1 Detailed Description

Subclass of AbInitio for force and energy matching using normal GROMACS.

Implements the prepare_temp_directory and energy_force_driver methods.

Definition at line 638 of file gmxio.py.

8.3.2 Constructor & Destructor Documentation

8.3.2.1 def forcebalance.gmxio.AbInitio_GMX.__init__ (*self, options, tgt_opts, forcefield*)

Initialization; define a few core concepts.

Todo Obtain the number of true atoms (or the particle -> atom mapping) from the force field.

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 640 of file gmxio.py.

8.3.3 Member Function Documentation

8.3.3.1 def forcebalance.abinitio.AbInitio.build_invdist (*self, mvals*) [inherited]

Definition at line 168 of file abinitio.py.

Here is the call graph for this function:

8.3.3.2 def forcebalance.abinitio.AbInitio.compute_netforce_torque (*self, xyz, force, QM* = `False`) [inherited]

Definition at line 204 of file abinitio.py.

8.3.3.3 def forcebalance.gmxio.AbInitio_GMX.energy_force_driver (*self, shot*)

Computes the energy and force using GROMACS for a single snapshot.

This does not require GROMACS-X2.

Definition at line 668 of file gmxio.py.

Here is the call graph for this function:

8.3.3.4 def forcebalance.gmxio.AbInitio_GMX.energy_force_driver_all (*self*)

Computes the energy and force using GROMACS for a trajectory.

This does not require GROMACS-X2.

Definition at line 673 of file gmxio.py.

8.3.3.5 def forcebalance.abinitio.AbInitio.energy_force_transformer (*self, i*) [inherited]

Definition at line 459 of file abinitio.py.

Here is the call graph for this function:

8.3.3.6 def forcebalance.abinitio.AbInitio.energy_force_transformer_all (*self*) [inherited]

Definition at line 442 of file abinitio.py.

Here is the call graph for this function:

8.3.3.7 def forcebalance.gmxio.AbInitio_GMX.generate_vsite_positions (*self*)

Call mdrun in order to update the virtual site positions.

Definition at line 678 of file gmxio.py.

Here is the call graph for this function:

8.3.3.8 def forcebalance.abinitio.AbInitio.get (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.

See abinitio for an example.

Reimplemented from forcebalance.target.Target.

Definition at line 1100 of file abinitio.py.

8.3.3.9 def forcebalance.abinitio.AbInitio.get_energy_force_ (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

LPW 06-30-2013.

This subroutine builds the objective function (and optionally its derivatives) from a general simulation software. This is in contrast to using GROMACS-X2, which computes the objective function and prints it out; then 'get' only needs to call GROMACS and read it in.

This subroutine interfaces with simulation software 'drivers'. The driver is only expected to give the energy and forces.

Now this subroutine may sound trivial since the objective function is simply a least-squares quantity (M-Q)^2 - but there are a number of nontrivial considerations. I will list them here.

0) Polytensor formulation: Because there may exist covariance between different components of the force (or covariance between the energy and the force), we build the objective function by taking outer products of vectors that have the form [E F_1x F_1y F_1z F_2x F_2y ...], and then we trace it with the inverse of the covariance matrix to get the objective function.

This version implements both the polytensor formulation and the standard formulation.

1) Boltzmann weights and normalization: Each snapshot has its own Boltzmann weight, which may or may not be normalized. This subroutine does the normalization automatically.

2) Subtracting out the mean energy gap: The zero-point energy difference between reference data and simulation is meaningless. This subroutine subtracts it out.

3) Hybrid ensembles: This program builds a combined objective function from both MM and QM ensembles, which is rigorously better than using a single ensemble.

Note that this subroutine does not do EVERYTHING that GROMACS-X2 can do, which includes:

1) Internal coordinate systems 2) 'Sampling correction' (deprecated, since it doesn't seem to work) 3) Analytic derivatives

In the previous code (ForTune) this subroutine used analytic first derivatives of the energy and force to build the derivatives of the objective function. Here I will take a simplified approach, because building the derivatives are cumbersome. For now we will return the objective function ONLY. A two-point central difference should give us the first and diagonal second derivative anyhow.

Todo Parallelization over snapshots is not implemented yet

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient
in	*AHess*	Switch to turn on analytic Hessian

Returns

Answer Contribution to the objective function

Definition at line 534 of file abinitio.py.

8.3.3.10 def forcebalance.target.Target.get_G (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.3.3.11 def forcebalance.target.Target.get_H (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.3.3.12 def forcebalance.abinitio.AbInitio.get_resp_ (*self*, *mvals*, *AGrad* = `False`, *AHess* = `False`) `[inherited]`

Electrostatic potential fitting.

Implements the RESP objective function. (In Python so obviously not optimized.) This function takes the mathematical parameter values and returns the charges on the ATOMS (fancy mapping going on)

Definition at line 1001 of file abinitio.py.

8.3.3.13 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) `[inherited]`

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.3.3.14 def forcebalance.abinitio.AbInitio.indicate (*self*) [inherited]

Definition at line 422 of file abinitio.py.

Here is the call graph for this function:

8.3.3.15 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.3.3.16 def forcebalance.gmxio.AbInitio_GMX.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory, by default does nothing.

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 659 of file gmxio.py.

Here is the call graph for this function:

8.3.3.17 def forcebalance.target.Target.printcool_table (*self*, *data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.3.3.18 def forcebalance.abinitio.AbInitio.read_reference_data (*self*) `[inherited]`

Read the reference ab initio data from a file such as qdata.txt.

Todo Add an option for picking any slice out of qdata.txt, helpful for cross-validation

Todo Closer integration of reference data with program - leave behind the qdata.txt format? (For now, I like the readability of qdata.txt)

After reading in the information from qdata.txt, it is converted into the GROMACS energy units (kind of an arbitrary choice); forces (kind of a misnomer in qdata.txt) are multipled by -1 to convert gradients to forces.

We also subtract out the mean energies of all energy arrays because energy/force matching does not account for zero-point energy differences between MM and QM (i.e. energy of electrons in core orbitals).

The configurations in force/energy matching typically come from a the thermodynamic ensemble of the MM force field at some temperature (by running MD, for example), and for many reasons it is helpful to introduce non-Boltzmann weights in front of these configurations. There are two options: WHAM Boltzmann weights (for combining the weights of several simulations together) and QM Boltzmann weights (for converting MM weights into QM weights). Note that the two sets of weights 'stack'; i.e. they can be used at the same time.

A 'hybrid' ensemble is possible where we use 50% MM and 50% QM weights. Please read more in LPW and Troy Van Voorhis, JCP Vol. 133, Pg. 231101 (2010), doi:10.1063/1.3519043.

Todo The WHAM Boltzmann weights are generated by external scripts (wanalyze.py and make-wham-data.sh) and passed in; perhaps these scripts can be added to the ForceBalance distribution or integrated more tightly.

Finally, note that using non-Boltzmann weights degrades the statistical information content of the snapshots. This problem will generally become worse if the ensemble to which we're reweighting is dramatically different from the one we're sampling from. We end up with a set of Boltzmann weights like [1e-9, 1e-9, 1.0, 1e-9, 1e-9 ...] and this is essentially just one snapshot. I believe Troy is working on something to cure this problem.

Here, we have a measure for the information content of our snapshots, which comes easily from the definition of information entropy:

S = -1∗Sum_i(P_i∗log(P_i)) InfoContent = exp(-S)

With uniform weights, InfoContent is equal to the number of snapshots; with horrible weights, InfoContent is closer to one.

Definition at line 317 of file abinitio.py.

8.3.3.19 def forcebalance.gmxio.AbInitio_GMX.read_topology (*self*)

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 662 of file gmxio.py.

8.3.3.20 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.3.3.21 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.3.3.22 def forcebalance.target.Target.sget (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.3.3.23 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) `[inherited]`

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.3.3.24 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.3.3.25 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.3.4 Member Data Documentation

8.3.4.1 forcebalance::gmxio.AbInitio_GMX::AtomLists

This is a default-dict containing a number of atom-wise lists, such as the residue number of each atom, the mass of each atom, and so on.

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 644 of file gmxio.py.

8.3.4.2 forcebalance::gmxio.AbInitio_GMX::AtomMask

Definition at line 644 of file gmxio.py.

8.3.4.3 forcebalance::abinitio.AbInitio::e_err [inherited]

Qualitative Indicator: average energy error (in kJ/mol)

Definition at line 85 of file abinitio.py.

8.3.4.4 forcebalance::abinitio.AbInitio::e_err_pct [inherited]

Definition at line 85 of file abinitio.py.

8.3.4.5 forcebalance::abinitio.AbInitio::e_ref [inherited]

Definition at line 534 of file abinitio.py.

8.3.4.6 forcebalance::abinitio.AbInitio::emd0 [inherited]

Energies of the sampling simulation.

Definition at line 79 of file abinitio.py.

8.3.4.7 forcebalance::gmxio.AbInitio_GMX::engine

Default file names for coordinates, top and mdp files.

Initialize base class. Build keyword dictionaries to pass to engine. Create engine object.

Definition at line 644 of file gmxio.py.

8.3.4.8 forcebalance::abinitio.AbInitio::eqm [inherited]

Reference (QM) energies.

Definition at line 78 of file abinitio.py.

8.3.4.9 forcebalance::abinitio.AbInitio::esp_err [inherited]

Qualitative Indicator: "relative RMS" for electrostatic potential.

Definition at line 87 of file abinitio.py.

8.3.4.10 forcebalance::abinitio.AbInitio::espval [inherited]

ESP values.

Definition at line 82 of file abinitio.py.

8.3.4.11 forcebalance::abinitio.AbInitio::espxyz [inherited]

ESP grid points.

Definition at line 81 of file abinitio.py.

8.3.4.12 forcebalance::abinitio.AbInitio::f_err [inherited]

Qualitative Indicator: average force error (fractional)

Definition at line 86 of file abinitio.py.

8.3.4.13 forcebalance::abinitio.AbInitio::f_err_pct [inherited]

Definition at line 86 of file abinitio.py.

8.3.4.14 forcebalance::abinitio.AbInitio::f_ref [inherited]

Definition at line 534 of file abinitio.py.

8.3.4.15 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.3.4.16 forcebalance::abinitio.AbInitio::fitatoms [inherited]

Definition at line 317 of file abinitio.py.

8.3.4.17 forcebalance::abinitio.AbInitio::force [inherited]

Definition at line 317 of file abinitio.py.

8.3.4.18 forcebalance::abinitio.AbInitio::force_map [inherited]

Definition at line 204 of file abinitio.py.

8.3.4.19 forcebalance::abinitio.AbInitio::fqm [inherited]

Reference (QM) forces.

Definition at line 80 of file abinitio.py.

8.3.4.20 forcebalance::abinitio.AbInitio::fref [inherited]

Definition at line 317 of file abinitio.py.

8.3.4.21 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.3.4.22 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.3.4.23 forcebalance::abinitio.AbInitio::invdists [inherited]

Definition at line 1001 of file abinitio.py.

8.3.4.24 forcebalance::abinitio.AbInitio::nesp [inherited]

Definition at line 317 of file abinitio.py.

8.3.4.25 forcebalance::abinitio.AbInitio::new_vsites [inherited]

Read in the topology.

Read in the reference data Prepare the temporary directory The below two options are related to whether we want to rebuild virtual site positions. Rebuild the distance matrix if virtual site positions have changed

Definition at line 97 of file abinitio.py.

8.3.4.26 forcebalance::abinitio.AbInitio::nf_err [inherited]

Definition at line 87 of file abinitio.py.

8.3.4.27 forcebalance::abinitio.AbInitio::nf_err_pct [inherited]

Definition at line 87 of file abinitio.py.

8.3.4.28 forcebalance::abinitio.AbInitio::nf_ref [inherited]

Definition at line 534 of file abinitio.py.

8.3.4.29 forcebalance::abinitio.AbInitio::nftqm [inherited]

Definition at line 317 of file abinitio.py.

8.3.4.30 forcebalance::abinitio.AbInitio::nnf [inherited]

Definition at line 204 of file abinitio.py.

8.3.4.31 forcebalance::abinitio.AbInitio::nparticles [inherited]

The number of (atoms + drude particles + virtual sites)

Definition at line 90 of file abinitio.py.

8.3.4.32 forcebalance::abinitio.AbInitio::ns [inherited]

Read in the trajectory file.

Definition at line 89 of file abinitio.py.

8.3.4.33 forcebalance::abinitio.AbInitio::ntq [inherited]

Definition at line 204 of file abinitio.py.

8.3.4.34 forcebalance::abinitio.AbInitio::objective [inherited]

Definition at line 1100 of file abinitio.py.

8.3.4.35 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.3.4.36 forcebalance::abinitio.AbInitio::qfnm [inherited]

The qdata.txt file that contains the QM energies and forces.

Definition at line 83 of file abinitio.py.

8.3.4.37 forcebalance::abinitio.AbInitio::qmatoms [inherited]

The number of atoms in the QM calculation (Irrelevant if not fitting forces)

Definition at line 84 of file abinitio.py.

8.3.4.38 forcebalance::abinitio.AbInitio::qmboltz_wts [inherited]

QM Boltzmann weights.

Definition at line 77 of file abinitio.py.

8.3.4.39 forcebalance::abinitio.AbInitio::respterm [inherited]

Definition at line 1001 of file abinitio.py.

8.3.4.40 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.3.4.41 forcebalance::abinitio.AbInitio::save_vmvals [inherited]

Save the mvals from the last time we updated the vsites.

Definition at line 98 of file abinitio.py.

8.3.4.42 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types

that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.3.4.43 forcebalance::gmxio.AbInitio_GMX::topology_flag

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 662 of file gmxio.py.

8.3.4.44 forcebalance::abinitio.AbInitio::tq_err [inherited]

Definition at line 534 of file abinitio.py.

8.3.4.45 forcebalance::abinitio.AbInitio::tq_err_pct [inherited]

Definition at line 87 of file abinitio.py.

8.3.4.46 forcebalance::abinitio.AbInitio::tq_ref [inherited]

Definition at line 534 of file abinitio.py.

8.3.4.47 forcebalance::abinitio.AbInitio::traj [inherited]

Definition at line 89 of file abinitio.py.

8.3.4.48 forcebalance::abinitio.AbInitio::use_nft [inherited]

Whether to compute net forces and torques, or not.

Definition at line 88 of file abinitio.py.

8.3.4.49 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.3.4.50 forcebalance::abinitio.AbInitio::w_energy [inherited]

Definition at line 534 of file abinitio.py.

8.3.4.51 forcebalance::abinitio.AbInitio::w_force [inherited]

Definition at line 317 of file abinitio.py.

8.3.4.52 forcebalance::abinitio.AbInitio::w_netforce [inherited]

Definition at line 534 of file abinitio.py.

8.3.4.53 forcebalance::abinitio.AbInitio::w_resp [inherited]

Definition at line 1001 of file abinitio.py.

8.3.4.54 forcebalance::abinitio.AbInitio::w_torque [inherited]

Definition at line 534 of file abinitio.py.

8.3.4.55 forcebalance::abinitio.AbInitio::whamboltz [inherited]

Definition at line 317 of file abinitio.py.

8.3.4.56 forcebalance::abinitio.AbInitio::whamboltz_wts [inherited]

Initialize the base class.

Number of snapshots Whether to use WHAM Boltzmann weights Whether to use the Sampling Correction Whether to match Absolute Energies (make sure you know what you're doing) Whether to use the Covariance Matrix Whether to use QM Boltzmann weights The temperature for QM Boltzmann weights Number of atoms that we are fitting Whether to fit Energies. Whether to fit Forces. Whether to fit Electrostatic Potential. Weights for the three components. Option for how much data to write to disk. Whether to do energy and force calculations for the whole trajectory, or to do one calculation per snapshot. OpenMM-only option - whether to run the energies and forces internally. Whether we have virtual sites (set at the global option level) WHAM Boltzmann weights

Definition at line 76 of file abinitio.py.

8.3.4.57 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- gmxio.py

8.4 forcebalance.abinitio_internal.AbInitio_Internal Class Reference

Subclass of Target for force and energy matching using an internal implementation.

Inheritance diagram for forcebalance.abinitio_internal.AbInitio_Internal:

Collaboration diagram for forcebalance.abinitio_internal.AbInitio_Internal:

Public Member Functions

- def __init__

  Initialization; define a few core concepts.
- def energy_force_driver_all

  Here we actually compute the interactions and return the energies and forces.
- def read_topology
- def build_invdist
- def compute_netforce_torque
- def read_reference_data

  Read the reference ab initio data from a file such as qdata.txt.
- def prepare_temp_directory

  Prepare the temporary directory, by default does nothing.
- def indicate
- def energy_force_transformer_all
- def energy_force_transformer
- def get_energy_force_

  LPW 06-30-2013.
- def get_resp_

  Electrostatic potential fitting.
- def get

  Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- trajfnm

  Name of the trajectory, we need this BEFORE initializing the SuperClass.
- whamboltz_wts

  Initialize the base class.
- qmboltz_wts

  QM Boltzmann weights.
- eqm

  Reference (QM) energies.
- emd0

  Energies of the sampling simulation.
- fqm

  Reference (QM) forces.
- espxyz

  ESP grid points.
- espval

  ESP values.
- qfnm

  The qdata.txt file that contains the QM energies and forces.
- qmatoms

  The number of atoms in the QM calculation (Irrelevant if not fitting forces)
- e_err

  Qualitative Indicator: average energy error (in kJ/mol)
- e_err_pct
- f_err

  Qualitative Indicator: average force error (fractional)
- f_err_pct
- esp_err

  Qualitative Indicator: "relative RMS" for electrostatic potential.
- nf_err
- nf_err_pct
- tq_err_pct
- use_nft

  Whether to compute net forces and torques, or not.
- ns

  Read in the trajectory file.
- traj
- nparticles

  The number of (atoms + drude particles + virtual sites)
- AtomLists

  This is a default-dict containing a number of atom-wise lists, such as the residue number of each atom, the mass of each atom, and so on.
- new_vsites

  Read in the topology.
- save_vmvals

  Save the mvals from the last time we updated the vsites.
- topology_flag

- force_map
- nnf
- ntq
- force
- w_force
- nesp
- fitatoms
- whamboltz
- nftqm
- fref
- w_energy
- w_netforce
- w_torque
- e_ref
- f_ref
- nf_ref
- tq_ref
- tq_err
- w_resp
- invdists
- respterm
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.4.1 Detailed Description

Subclass of Target for force and energy matching using an internal implementation.

Implements the prepare and energy_force_driver methods. The get method is in the superclass.

The purpose of this class is to provide an extremely simple test case that does not require the user to install any external software. It only runs with one of the included sample test calculations (internal_tip3p), and the objective function is energy matching.

Warning

This class is only intended to work with a very specific test case (internal_tip3p). This is because the topology and ordering of the atoms is hard-coded (12 water molecules with 3 atoms each).
This class does energy matching only (no forces)

Definition at line 37 of file abinitio_internal.py.

8.4.2 Constructor & Destructor Documentation

8.4.2.1 def forcebalance.abinitio_internal.AbInitio_Internal.__init__ (*self, options, tgt_opts, forcefield*)

Initialization; define a few core concepts.

Todo Obtain the number of true atoms (or the particle -> atom mapping) from the force field.

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 40 of file abinitio_internal.py.

8.4.3 Member Function Documentation

8.4.3.1 def forcebalance.abinitio.AbInitio.build_invdist (*self, mvals*) [inherited]

Definition at line 168 of file abinitio.py.

Here is the call graph for this function:

8.4.3.2 def forcebalance.abinitio.AbInitio.compute_netforce_torque (*self, xyz, force, QM* = `False`) [inherited]

Definition at line 204 of file abinitio.py.

8.4.3.3 def forcebalance.abinitio_internal.AbInitio_Internal.energy_force_driver_all (*self*)

Here we actually compute the interactions and return the energies and forces.

I verified this to give the same answer as GROMACS.

Definition at line 50 of file abinitio_internal.py.

8.4.3.4 def forcebalance.abinitio.AbInitio.energy_force_transformer (*self, i*) [inherited]

Definition at line 459 of file abinitio.py.

Here is the call graph for this function:

8.4.3.5 def forcebalance.abinitio.AbInitio.energy_force_transformer_all (*self*) [inherited]

Definition at line 442 of file abinitio.py.

Here is the call graph for this function:

8.4.3.6 def forcebalance.abinitio.AbInitio.get (*self, mvals, AGrad* = False, *AHess* = False) [inherited]

Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.

See abinitio for an example.

Reimplemented from forcebalance.target.Target.

Definition at line 1100 of file abinitio.py.

8.4.3.7 def forcebalance.abinitio.AbInitio.get_energy_force_ (*self, mvals, AGrad* = False, *AHess* = False) [inherited]

LPW 06-30-2013.

This subroutine builds the objective function (and optionally its derivatives) from a general simulation software. This is in contrast to using GROMACS-X2, which computes the objective function and prints it out; then 'get' only needs to call GROMACS and read it in.

This subroutine interfaces with simulation software 'drivers'. The driver is only expected to give the energy and forces.

Now this subroutine may sound trivial since the objective function is simply a least-squares quantity (M-Q)^2 - but there

are a number of nontrivial considerations. I will list them here.

0) Polytensor formulation: Because there may exist covariance between different components of the force (or covariance between the energy and the force), we build the objective function by taking outer products of vectors that have the form [E F_1x F_1y F_1z F_2x F_2y ...], and then we trace it with the inverse of the covariance matrix to get the objective function.

This version implements both the polytensor formulation and the standard formulation.

1) Boltzmann weights and normalization: Each snapshot has its own Boltzmann weight, which may or may not be normalized. This subroutine does the normalization automatically.

2) Subtracting out the mean energy gap: The zero-point energy difference between reference data and simulation is meaningless. This subroutine subtracts it out.

3) Hybrid ensembles: This program builds a combined objective function from both MM and QM ensembles, which is rigorously better than using a single ensemble.

Note that this subroutine does not do EVERYTHING that GROMACS-X2 can do, which includes:

1) Internal coordinate systems 2) 'Sampling correction' (deprecated, since it doesn't seem to work) 3) Analytic derivatives

In the previous code (ForTune) this subroutine used analytic first derivatives of the energy and force to build the derivatives of the objective function. Here I will take a simplified approach, because building the derivatives are cumbersome. For now we will return the objective function ONLY. A two-point central difference should give us the first and diagonal second derivative anyhow.

Todo Parallelization over snapshots is not implemented yet

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient
in	*AHess*	Switch to turn on analytic Hessian

Returns

Answer Contribution to the objective function

Definition at line 534 of file abinitio.py.

8.4.3.8 def forcebalance.target.Target.get_G (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.4.3.9 def forcebalance.target.Target.get_H (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.4.3.10 def forcebalance.abinitio.AbInitio.get_resp_ (*self*, *mvals*, *AGrad* = `False`, *AHess* = `False`) `[inherited]`

Electrostatic potential fitting.

Implements the RESP objective function. (In Python so obviously not optimized.) This function takes the mathematical parameter values and returns the charges on the ATOMS (fancy mapping going on)

Definition at line 1001 of file abinitio.py.

8.4.3.11 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) `[inherited]`

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.4.3.12 def forcebalance.abinitio.AbInitio.indicate (*self*) [inherited]

Definition at line 422 of file abinitio.py.

Here is the call graph for this function:

8.4.3.13 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.4.3.14 def forcebalance.abinitio.AbInitio.prepare_temp_directory (*self, options, tgt_opts*) [inherited]

Prepare the temporary directory, by default does nothing.

Reimplemented in forcebalance.gmxio.AbInitio_GMX, forcebalance.openmmio.AbInitio_OpenMM, forcebalance.tinkerio.AbInitio_TINKER, and forcebalance.amberio.AbInitio_AMBER.

Definition at line 419 of file abinitio.py.

8.4.3.15 def forcebalance.target.Target.printcool_table (*self*, *data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.4.3.16 def forcebalance.abinitio.AbInitio.read_reference_data (*self*) `[inherited]`

Read the reference ab initio data from a file such as qdata.txt.

Todo Add an option for picking any slice out of qdata.txt, helpful for cross-validation

Todo Closer integration of reference data with program - leave behind the qdata.txt format? (For now, I like the readability of qdata.txt)

After reading in the information from qdata.txt, it is converted into the GROMACS energy units (kind of an arbitrary choice); forces (kind of a misnomer in qdata.txt) are multipled by -1 to convert gradients to forces.

We also subtract out the mean energies of all energy arrays because energy/force matching does not account for zero-point energy differences between MM and QM (i.e. energy of electrons in core orbitals).

The configurations in force/energy matching typically come from a the thermodynamic ensemble of the MM force field at some temperature (by running MD, for example), and for many reasons it is helpful to introduce non-Boltzmann weights in front of these configurations. There are two options: WHAM Boltzmann weights (for combining the weights of several simulations together) and QM Boltzmann weights (for converting MM weights into QM weights). Note that the two sets of weights 'stack'; i.e. they can be used at the same time.

A 'hybrid' ensemble is possible where we use 50% MM and 50% QM weights. Please read more in LPW and Troy Van Voorhis, JCP Vol. 133, Pg. 231101 (2010), doi:10.1063/1.3519043.

Todo The WHAM Boltzmann weights are generated by external scripts (wanalyze.py and make-wham-data.sh) and passed in; perhaps these scripts can be added to the ForceBalance distribution or integrated more tightly.

Finally, note that using non-Boltzmann weights degrades the statistical information content of the snapshots. This problem will generally become worse if the ensemble to which we're reweighting is dramatically different from the one we're sampling from. We end up with a set of Boltzmann weights like [1e-9, 1e-9, 1.0, 1e-9, 1e-9 ...] and this is essentially just one snapshot. I believe Troy is working on something to cure this problem.

Here, we have a measure for the information content of our snapshots, which comes easily from the definition of information entropy:

S = -1∗Sum_i(P_i∗log(P_i)) InfoContent = exp(-S)

With uniform weights, InfoContent is equal to the number of snapshots; with horrible weights, InfoContent is closer to one.

Definition at line 317 of file abinitio.py.

8.4.3.17 def forcebalance.abinitio.AbInitio.read_topology (*self*) [inherited]

Reimplemented in forcebalance.gmxio.AbInitio_GMX, and forcebalance.openmmio.AbInitio_OpenMM.

Definition at line 164 of file abinitio.py.

8.4.3.18 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.4.3.19 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.4.3.20 def forcebalance.target.Target.sget (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.4.3.21 def forcebalance.target.Target.stage (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.4.3.22 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.4.3.23 def forcebalance.target.Target.wq_complete (*self*) `[inherited]`

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.4.4 Member Data Documentation

8.4.4.1 forcebalance::abinitio.AbInitio::AtomLists `[inherited]`

This is a default-dict containing a number of atom-wise lists, such as the residue number of each atom, the mass of each atom, and so on.

Reimplemented in forcebalance.gmxio.AbInitio_GMX.

Definition at line 92 of file abinitio.py.

8.4.4.2 forcebalance::abinitio.AbInitio::e_err `[inherited]`

Qualitative Indicator: average energy error (in kJ/mol)

Definition at line 85 of file abinitio.py.

8.4.4.3 forcebalance::abinitio.AbInitio::e_err_pct `[inherited]`

Definition at line 85 of file abinitio.py.

8.4.4.4 forcebalance::abinitio.AbInitio::e_ref [inherited]

Definition at line 534 of file abinitio.py.

8.4.4.5 forcebalance::abinitio.AbInitio::emd0 [inherited]

Energies of the sampling simulation.

Definition at line 79 of file abinitio.py.

8.4.4.6 forcebalance::abinitio.AbInitio::eqm [inherited]

Reference (QM) energies.

Definition at line 78 of file abinitio.py.

8.4.4.7 forcebalance::abinitio.AbInitio::esp_err [inherited]

Qualitative Indicator: "relative RMS" for electrostatic potential.

Definition at line 87 of file abinitio.py.

8.4.4.8 forcebalance::abinitio.AbInitio::espval [inherited]

ESP values.

Definition at line 82 of file abinitio.py.

8.4.4.9 forcebalance::abinitio.AbInitio::espxyz [inherited]

ESP grid points.

Definition at line 81 of file abinitio.py.

8.4.4.10 forcebalance::abinitio.AbInitio::f_err [inherited]

Qualitative Indicator: average force error (fractional)

Definition at line 86 of file abinitio.py.

8.4.4.11 forcebalance::abinitio.AbInitio::f_err_pct [inherited]

Definition at line 86 of file abinitio.py.

8.4.4.12 forcebalance::abinitio.AbInitio::f_ref [inherited]

Definition at line 534 of file abinitio.py.

8.4.4.13 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.4.4.14 forcebalance::abinitio.AbInitio::fitatoms [inherited]

Definition at line 317 of file abinitio.py.

8.4.4.15 forcebalance::abinitio.AbInitio::force [inherited]

Definition at line 317 of file abinitio.py.

8.4.4.16 forcebalance::abinitio.AbInitio::force_map [inherited]

Definition at line 204 of file abinitio.py.

8.4.4.17 forcebalance::abinitio.AbInitio::fqm [inherited]

Reference (QM) forces.

Definition at line 80 of file abinitio.py.

8.4.4.18 forcebalance::abinitio.AbInitio::fref [inherited]

Definition at line 317 of file abinitio.py.

8.4.4.19 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.4.4.20 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.4.4.21 forcebalance::abinitio.AbInitio::invdists [inherited]

Definition at line 1001 of file abinitio.py.

8.4.4.22 forcebalance::abinitio.AbInitio::nesp [inherited]

Definition at line 317 of file abinitio.py.

8.4.4.23 forcebalance::abinitio.AbInitio::new_vsites [inherited]

Read in the topology.

Read in the reference data Prepare the temporary directory The below two options are related to whether we want to rebuild virtual site positions. Rebuild the distance matrix if virtual site positions have changed

Definition at line 97 of file abinitio.py.

8.4.4.24 forcebalance::abinitio.AbInitio::nf_err [inherited]

Definition at line 87 of file abinitio.py.

8.4.4.25 forcebalance::abinitio.AbInitio::nf_err_pct [inherited]

Definition at line 87 of file abinitio.py.

8.4.4.26 forcebalance::abinitio.AbInitio::nf_ref [inherited]

Definition at line 534 of file abinitio.py.

8.4.4.27 forcebalance::abinitio.AbInitio::nftqm [inherited]

Definition at line 317 of file abinitio.py.

8.4.4.28 forcebalance::abinitio.AbInitio::nnf [inherited]

Definition at line 204 of file abinitio.py.

8.4.4.29 forcebalance::abinitio.AbInitio::nparticles [inherited]

The number of (atoms + drude particles + virtual sites)

Definition at line 90 of file abinitio.py.

8.4.4.30 forcebalance::abinitio.AbInitio::ns [inherited]

Read in the trajectory file.

Definition at line 89 of file abinitio.py.

8.4.4.31 forcebalance::abinitio.AbInitio::ntq [inherited]

Definition at line 204 of file abinitio.py.

8.4.4.32 forcebalance::abinitio.AbInitio::objective [inherited]

Definition at line 1100 of file abinitio.py.

8.4.4.33 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.4.4.34 forcebalance::abinitio.AbInitio::qfnm [inherited]

The qdata.txt file that contains the QM energies and forces.

Definition at line 83 of file abinitio.py.

8.4.4.35 forcebalance::abinitio.AbInitio::qmatoms [inherited]

The number of atoms in the QM calculation (Irrelevant if not fitting forces)

Definition at line 84 of file abinitio.py.

8.4.4.36 forcebalance::abinitio.AbInitio::qmboltz_wts [inherited]

QM Boltzmann weights.

Definition at line 77 of file abinitio.py.

8.4.4.37 forcebalance::abinitio.AbInitio::respterm [inherited]

Definition at line 1001 of file abinitio.py.

8.4.4.38 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.4.4.39 forcebalance::abinitio.AbInitio::save_vmvals [inherited]

Save the mvals from the last time we updated the vsites.

Definition at line 98 of file abinitio.py.

8.4.4.40 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.4.4.41 forcebalance::abinitio.AbInitio::topology_flag [inherited]

Reimplemented in forcebalance.gmxio.AbInitio_GMX, and forcebalance.openmmio.AbInitio_OpenMM.

Definition at line 164 of file abinitio.py.

8.4.4.42 forcebalance::abinitio.AbInitio::tq_err [inherited]

Definition at line 534 of file abinitio.py.

8.4.4.43 forcebalance::abinitio.AbInitio::tq_err_pct [inherited]

Definition at line 87 of file abinitio.py.

8.4.4.44 forcebalance::abinitio.AbInitio::tq_ref [inherited]

Definition at line 534 of file abinitio.py.

8.4.4.45 forcebalance::abinitio.AbInitio::traj [inherited]

Definition at line 89 of file abinitio.py.

8.4.4.46 forcebalance::abinitio_internal.AbInitio_Internal::trajfnm

Name of the trajectory, we need this BEFORE initializing the SuperClass.

Definition at line 41 of file abinitio_internal.py.

8.4.4.47 forcebalance::abinitio.AbInitio::use_nft [inherited]

Whether to compute net forces and torques, or not.

Definition at line 88 of file abinitio.py.

8.4.4.48 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.4.4.49 forcebalance::abinitio.AbInitio::w_energy [inherited]

Definition at line 534 of file abinitio.py.

8.4.4.50 forcebalance::abinitio.AbInitio::w_force [inherited]

Definition at line 317 of file abinitio.py.

8.4.4.51 forcebalance::abinitio.AbInitio::w_netforce [inherited]

Definition at line 534 of file abinitio.py.

8.4.4.52 forcebalance::abinitio.AbInitio::w_resp [inherited]

Definition at line 1001 of file abinitio.py.

8.4.4.53 forcebalance::abinitio.AbInitio::w_torque [inherited]

Definition at line 534 of file abinitio.py.

8.4.4.54 forcebalance::abinitio.AbInitio::whamboltz [inherited]

Definition at line 317 of file abinitio.py.

8.4.4.55 forcebalance::abinitio.AbInitio::whamboltz_wts [inherited]

Initialize the base class.

Number of snapshots Whether to use WHAM Boltzmann weights Whether to use the Sampling Correction Whether to match Absolute Energies (make sure you know what you're doing) Whether to use the Covariance Matrix Whether to use QM Boltzmann weights The temperature for QM Boltzmann weights Number of atoms that we are fitting Whether to fit Energies. Whether to fit Forces. Whether to fit Electrostatic Potential. Weights for the three components. Option for how much data to write to disk. Whether to do energy and force calculations for the whole trajectory, or to do one calculation per snapshot. OpenMM-only option - whether to run the energies and forces internally. Whether we have virtual sites (set at the global option level) WHAM Boltzmann weights

Definition at line 76 of file abinitio.py.

8.4.4.56 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- abinitio_internal.py

8.5 forcebalance.openmmio.AbInitio_OpenMM Class Reference

Subclass of AbInitio for force and energy matching using OpenMM.

Inheritance diagram for forcebalance.openmmio.AbInitio_OpenMM:

Collaboration diagram for forcebalance.openmmio.AbInitio_OpenMM:

Public Member Functions

- def __init__

  Initialization; define a few core concepts.
- def read_topology
- def prepare_temp_directory

  Prepare the temporary directory, by default does nothing.
- def energy_force_driver_all_external_
- def energy_force_driver_all_internal_

  Loop through the snapshots and compute the energies and forces using OpenMM.
- def energy_force_driver_all
- def build_invdist
- def compute_netforce_torque
- def read_reference_data

  Read the reference ab initio data from a file such as qdata.txt.
- def indicate
- def energy_force_transformer_all
- def energy_force_transformer
- def get_energy_force_

  LPW 06-30-2013.
- def get_resp_

  Electrostatic potential fitting.
- def get

  Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- trajfnm

  Name of the trajectory, we need this BEFORE initializing the SuperClass.
- platform

  Initialize the SuperClass!
- simulation

  Create the simulation object within this class itself.
- xyz_omms
- topology_flag
- whamboltz_wts

  Initialize the base class.
- qmboltz_wts

  QM Boltzmann weights.
- eqm

  Reference (QM) energies.
- emd0

  Energies of the sampling simulation.
- fqm

  Reference (QM) forces.
- espxyz

  ESP grid points.
- espval

  ESP values.
- qfnm

  The qdata.txt file that contains the QM energies and forces.
- qmatoms

  The number of atoms in the QM calculation (Irrelevant if not fitting forces)
- e_err

  Qualitative Indicator: average energy error (in kJ/mol)
- e_err_pct
- f_err

  Qualitative Indicator: average force error (fractional)
- f_err_pct
- esp_err

  Qualitative Indicator: "relative RMS" for electrostatic potential.
- nf_err
- nf_err_pct
- tq_err_pct
- use_nft

  Whether to compute net forces and torques, or not.
- ns

  Read in the trajectory file.
- traj
- nparticles

  The number of (atoms + drude particles + virtual sites)
- AtomLists

This is a default-dict containing a number of atom-wise lists, such as the residue number of each atom, the mass of each atom, and so on.

- new_vsites

  Read in the topology.
- save_vmvals

  Save the mvals from the last time we updated the vsites.
- force_map
- nnf
- ntq
- force
- w_force
- nesp
- fitatoms
- whamboltz
- nftqm
- fref
- w_energy
- w_netforce
- w_torque
- e_ref
- f_ref
- nf_ref
- tq_ref
- tq_err
- w_resp
- invdists
- respterm
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.5.1 Detailed Description

Subclass of AbInitio for force and energy matching using OpenMM.

Implements the prepare and energy_force_driver methods. The get method is in the superclass.

Definition at line 422 of file openmmio.py.

8.5.2 Constructor & Destructor Documentation

8.5.2.1 def forcebalance.openmmio.AbInitio_OpenMM.__init__ (*self, options, tgt_opts, forcefield*)

Initialization; define a few core concepts.

Todo Obtain the number of true atoms (or the particle -> atom mapping) from the force field.

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 425 of file openmmio.py.

8.5.3 Member Function Documentation

8.5.3.1 def forcebalance.abinitio.AbInitio.build_invdist (*self, mvals*) [inherited]

Definition at line 168 of file abinitio.py.

Here is the call graph for this function:

8.5.3.2 def forcebalance.abinitio.AbInitio.compute_netforce_torque (*self, xyz, force, QM* = False) [inherited]

Definition at line 204 of file abinitio.py.

8.5.3.3 def forcebalance.openmmio.AbInitio_OpenMM.energy_force_driver_all (*self*)

Definition at line 551 of file openmmio.py.

Here is the call graph for this function:

8.5.3.4 def forcebalance.openmmio.AbInitio_OpenMM.energy_force_driver_all_external_ (*self*)

Definition at line 494 of file openmmio.py.

8.5.3.5 def forcebalance.openmmio.AbInitio_OpenMM.energy_force_driver_all_internal_ (*self*)

Loop through the snapshots and compute the energies and forces using OpenMM.

Definition at line 503 of file openmmio.py.

Here is the call graph for this function:

8.5.3.6 def forcebalance.abinitio.AbInitio.energy_force_transformer (*self, i*) [inherited]

Definition at line 459 of file abinitio.py.

Here is the call graph for this function:

8.5.3.7 def forcebalance.abinitio.AbInitio.energy_force_transformer_all (*self*) [inherited]

Definition at line 442 of file abinitio.py.

Here is the call graph for this function:

8.5.3.8 def forcebalance.abinitio.AbInitio.get (*self, mvals, AGrad* = False, *AHess* = False) [inherited]

Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.

See abinitio for an example.

Reimplemented from forcebalance.target.Target.

Definition at line 1100 of file abinitio.py.

8.5.3.9 def forcebalance.abinitio.AbInitio.get_energy_force_ (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

LPW 06-30-2013.

This subroutine builds the objective function (and optionally its derivatives) from a general simulation software. This is in contrast to using GROMACS-X2, which computes the objective function and prints it out; then 'get' only needs to call GROMACS and read it in.

This subroutine interfaces with simulation software 'drivers'. The driver is only expected to give the energy and forces.

Now this subroutine may sound trivial since the objective function is simply a least-squares quantity (M-Q)^2 - but there are a number of nontrivial considerations. I will list them here.

0) Polytensor formulation: Because there may exist covariance between different components of the force (or covariance between the energy and the force), we build the objective function by taking outer products of vectors that have the form [E F_1x F_1y F_1z F_2x F_2y ...], and then we trace it with the inverse of the covariance matrix to get the objective function.

This version implements both the polytensor formulation and the standard formulation.

1) Boltzmann weights and normalization: Each snapshot has its own Boltzmann weight, which may or may not be normalized. This subroutine does the normalization automatically.

2) Subtracting out the mean energy gap: The zero-point energy difference between reference data and simulation is meaningless. This subroutine subtracts it out.

3) Hybrid ensembles: This program builds a combined objective function from both MM and QM ensembles, which is rigorously better than using a single ensemble.

Note that this subroutine does not do EVERYTHING that GROMACS-X2 can do, which includes:

1) Internal coordinate systems 2) 'Sampling correction' (deprecated, since it doesn't seem to work) 3) Analytic derivatives

In the previous code (ForTune) this subroutine used analytic first derivatives of the energy and force to build the derivatives of the objective function. Here I will take a simplified approach, because building the derivatives are cumbersome. For now we will return the objective function ONLY. A two-point central difference should give us the first and diagonal second derivative anyhow.

Todo Parallelization over snapshots is not implemented yet

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient
in	*AHess*	Switch to turn on analytic Hessian

Returns

Answer Contribution to the objective function

Definition at line 534 of file abinitio.py.

8.5.3.10 def forcebalance.target.Target.get_G (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.5.3.11 def forcebalance.target.Target.get_H (*self*, *mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.5.3.12 def forcebalance.abinitio.AbInitio.get_resp_ (*self*, *mvals*, *AGrad* = `False`, *AHess* = `False`) `[inherited]`

Electrostatic potential fitting.

Implements the RESP objective function. (In Python so obviously not optimized.) This function takes the mathematical parameter values and returns the charges on the ATOMS (fancy mapping going on)

Definition at line 1001 of file abinitio.py.

8.5.3.13 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) `[inherited]`

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.5.3.14 def forcebalance.abinitio.AbInitio.indicate (*self*) [inherited]

Definition at line 422 of file abinitio.py.

Here is the call graph for this function:

8.5.3.15 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.5.3.16 def forcebalance.openmmio.AbInitio_OpenMM.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory, by default does nothing.

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 489 of file openmmio.py.

Here is the call graph for this function:

8.5.3.17 def forcebalance.target.Target.printcool_table (*self*, *data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.5.3.18 def forcebalance.abinitio.AbInitio.read_reference_data (*self*) `[inherited]`

Read the reference ab initio data from a file such as qdata.txt.

Todo Add an option for picking any slice out of qdata.txt, helpful for cross-validation

Todo Closer integration of reference data with program - leave behind the qdata.txt format? (For now, I like the readability of qdata.txt)

After reading in the information from qdata.txt, it is converted into the GROMACS energy units (kind of an arbitrary choice); forces (kind of a misnomer in qdata.txt) are multipled by -1 to convert gradients to forces.

We also subtract out the mean energies of all energy arrays because energy/force matching does not account for zero-point energy differences between MM and QM (i.e. energy of electrons in core orbitals).

The configurations in force/energy matching typically come from a the thermodynamic ensemble of the MM force field at some temperature (by running MD, for example), and for many reasons it is helpful to introduce non-Boltzmann weights

in front of these configurations. There are two options: WHAM Boltzmann weights (for combining the weights of several simulations together) and QM Boltzmann weights (for converting MM weights into QM weights). Note that the two sets of weights 'stack'; i.e. they can be used at the same time.

A 'hybrid' ensemble is possible where we use 50% MM and 50% QM weights. Please read more in LPW and Troy Van Voorhis, JCP Vol. 133, Pg. 231101 (2010), doi:10.1063/1.3519043.

Todo The WHAM Boltzmann weights are generated by external scripts (wanalyze.py and make-wham-data.sh) and passed in; perhaps these scripts can be added to the ForceBalance distribution or integrated more tightly.

Finally, note that using non-Boltzmann weights degrades the statistical information content of the snapshots. This problem will generally become worse if the ensemble to which we're reweighting is dramatically different from the one we're sampling from. We end up with a set of Boltzmann weights like [1e-9, 1e-9, 1.0, 1e-9, 1e-9 ...] and this is essentially just one snapshot. I believe Troy is working on something to cure this problem.

Here, we have a measure for the information content of our snapshots, which comes easily from the definition of information entropy:

S = -1∗Sum_i(P_i∗log(P_i)) InfoContent = exp(-S)

With uniform weights, InfoContent is equal to the number of snapshots; with horrible weights, InfoContent is closer to one.

Definition at line 317 of file abinitio.py.

8.5.3.19 def forcebalance.openmmio.AbInitio_OpenMM.read_topology (*self*)

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 479 of file openmmio.py.

8.5.3.20 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.5.3.21 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.5.3.22 def forcebalance.target.Target.sget (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.5.3.23 def forcebalance.target.Target.stage (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.5.3.24 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.5.3.25 def forcebalance.target.Target.wq_complete (*self*) `[inherited]`

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.5.4 Member Data Documentation

8.5.4.1 forcebalance::abinitio.AbInitio::AtomLists `[inherited]`

This is a default-dict containing a number of atom-wise lists, such as the residue number of each atom, the mass of each atom, and so on.

Reimplemented in forcebalance.gmxio.AbInitio_GMX.

Definition at line 92 of file abinitio.py.

8.5.4.2 forcebalance::abinitio.AbInitio::e_err `[inherited]`

Qualitative Indicator: average energy error (in kJ/mol)

Definition at line 85 of file abinitio.py.

8.5.4.3 forcebalance::abinitio.AbInitio::e_err_pct `[inherited]`

Definition at line 85 of file abinitio.py.

8.5.4.4 forcebalance::abinitio.AbInitio::e_ref [inherited]

Definition at line 534 of file abinitio.py.

8.5.4.5 forcebalance::abinitio.AbInitio::emd0 [inherited]

Energies of the sampling simulation.

Definition at line 79 of file abinitio.py.

8.5.4.6 forcebalance::abinitio.AbInitio::eqm [inherited]

Reference (QM) energies.

Definition at line 78 of file abinitio.py.

8.5.4.7 forcebalance::abinitio.AbInitio::esp_err [inherited]

Qualitative Indicator: "relative RMS" for electrostatic potential.

Definition at line 87 of file abinitio.py.

8.5.4.8 forcebalance::abinitio.AbInitio::espval [inherited]

ESP values.

Definition at line 82 of file abinitio.py.

8.5.4.9 forcebalance::abinitio.AbInitio::espxyz [inherited]

ESP grid points.

Definition at line 81 of file abinitio.py.

8.5.4.10 forcebalance::abinitio.AbInitio::f_err [inherited]

Qualitative Indicator: average force error (fractional)

Definition at line 86 of file abinitio.py.

8.5.4.11 forcebalance::abinitio.AbInitio::f_err_pct [inherited]

Definition at line 86 of file abinitio.py.

8.5.4.12 forcebalance::abinitio.AbInitio::f_ref [inherited]

Definition at line 534 of file abinitio.py.

8.5.4.13 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.5.4.14 forcebalance::abinitio.AbInitio::fitatoms [inherited]

Definition at line 317 of file abinitio.py.

8.5.4.15 forcebalance::abinitio.AbInitio::force [inherited]

Definition at line 317 of file abinitio.py.

8.5.4.16 forcebalance::abinitio.AbInitio::force_map [inherited]

Definition at line 204 of file abinitio.py.

8.5.4.17 forcebalance::abinitio.AbInitio::fqm [inherited]

Reference (QM) forces.

Definition at line 80 of file abinitio.py.

8.5.4.18 forcebalance::abinitio.AbInitio::fref [inherited]

Definition at line 317 of file abinitio.py.

8.5.4.19 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.5.4.20 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.5.4.21 forcebalance::abinitio.AbInitio::invdists [inherited]

Definition at line 1001 of file abinitio.py.

8.5.4.22 forcebalance::abinitio.AbInitio::nesp [inherited]

Definition at line 317 of file abinitio.py.

8.5.4.23 forcebalance::abinitio.AbInitio::new_vsites [inherited]

Read in the topology.

Read in the reference data Prepare the temporary directory The below two options are related to whether we want to rebuild virtual site positions. Rebuild the distance matrix if virtual site positions have changed

Definition at line 97 of file abinitio.py.

8.5.4.24 forcebalance::abinitio.AbInitio::nf_err [inherited]

Definition at line 87 of file abinitio.py.

8.5.4.25 forcebalance::abinitio.AbInitio::nf_err_pct [inherited]

Definition at line 87 of file abinitio.py.

8.5.4.26 forcebalance::abinitio.AbInitio::nf_ref [inherited]

Definition at line 534 of file abinitio.py.

8.5.4.27 forcebalance::abinitio.AbInitio::nftqm [inherited]

Definition at line 317 of file abinitio.py.

8.5.4.28 forcebalance::abinitio.AbInitio::nnf [inherited]

Definition at line 204 of file abinitio.py.

8.5.4.29 forcebalance::abinitio.AbInitio::nparticles [inherited]

The number of (atoms + drude particles + virtual sites)

Definition at line 90 of file abinitio.py.

8.5.4.30 forcebalance::abinitio.AbInitio::ns [inherited]

Read in the trajectory file.

Definition at line 89 of file abinitio.py.

8.5.4.31 forcebalance::abinitio.AbInitio::ntq [inherited]

Definition at line 204 of file abinitio.py.

8.5.4.32 forcebalance::abinitio.AbInitio::objective [inherited]

Definition at line 1100 of file abinitio.py.

8.5.4.33 forcebalance::openmmio.AbInitio_OpenMM::platform

Initialize the SuperClass!

Set the device to the environment variable or zero otherwise.

Set the simulation platform

Definition at line 428 of file openmmio.py.

8.5.4.34 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.5.4.35 forcebalance::abinitio.AbInitio::qfnm [inherited]

The qdata.txt file that contains the QM energies and forces.

Definition at line 83 of file abinitio.py.

8.5.4.36 forcebalance::abinitio.AbInitio::qmatoms [inherited]

The number of atoms in the QM calculation (Irrelevant if not fitting forces)

Definition at line 84 of file abinitio.py.

8.5.4.37 forcebalance::abinitio.AbInitio::qmboltz_wts [inherited]

QM Boltzmann weights.

Definition at line 77 of file abinitio.py.

8.5.4.38 forcebalance::abinitio.AbInitio::respterm [inherited]

Definition at line 1001 of file abinitio.py.

8.5.4.39 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.5.4.40 forcebalance::abinitio.AbInitio::save_vmvals [inherited]

Save the mvals from the last time we updated the vsites.

Definition at line 98 of file abinitio.py.

8.5.4.41 forcebalance::openmmio.AbInitio_OpenMM::simulation

Create the simulation object within this class itself.

Definition at line 430 of file openmmio.py.

8.5.4.42 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.5.4.43 forcebalance::openmmio.AbInitio_OpenMM::topology_flag

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 479 of file openmmio.py.

8.5.4.44 forcebalance::abinitio.AbInitio::tq_err [inherited]

Definition at line 534 of file abinitio.py.

8.5.4.45 forcebalance::abinitio.AbInitio::tq_err_pct [inherited]

Definition at line 87 of file abinitio.py.

8.5.4.46 forcebalance::abinitio.AbInitio::tq_ref [inherited]

Definition at line 534 of file abinitio.py.

8.5.4.47 forcebalance::abinitio.AbInitio::traj [inherited]

Definition at line 89 of file abinitio.py.

8.5.4.48 forcebalance::openmmio.AbInitio_OpenMM::trajfnm

Name of the trajectory, we need this BEFORE initializing the SuperClass.

Definition at line 426 of file openmmio.py.

8.5.4.49 forcebalance::abinitio.AbInitio::use_nft [inherited]

Whether to compute net forces and torques, or not.

Definition at line 88 of file abinitio.py.

8.5.4.50 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.5.4.51 forcebalance::abinitio.AbInitio::w_energy [inherited]

Definition at line 534 of file abinitio.py.

8.5.4.52 forcebalance::abinitio.AbInitio::w_force [inherited]

Definition at line 317 of file abinitio.py.

8.5.4.53 forcebalance::abinitio.AbInitio::w_netforce [inherited]

Definition at line 534 of file abinitio.py.

8.5.4.54 forcebalance::abinitio.AbInitio::w_resp [inherited]

Definition at line 1001 of file abinitio.py.

8.5.4.55 forcebalance::abinitio.AbInitio::w_torque [inherited]

Definition at line 534 of file abinitio.py.

8.5.4.56 forcebalance::abinitio.AbInitio::whamboltz [inherited]

Definition at line 317 of file abinitio.py.

8.5.4.57 forcebalance::abinitio.AbInitio::whamboltz_wts [inherited]

Initialize the base class.

Number of snapshots Whether to use WHAM Boltzmann weights Whether to use the Sampling Correction Whether to match Absolute Energies (make sure you know what you're doing) Whether to use the Covariance Matrix Whether to use QM Boltzmann weights The temperature for QM Boltzmann weights Number of atoms that we are fitting Whether to fit Energies. Whether to fit Forces. Whether to fit Electrostatic Potential. Weights for the three components. Option for how much data to write to disk. Whether to do energy and force calculations for the whole trajectory, or to do one calculation per snapshot. OpenMM-only option - whether to run the energies and forces internally. Whether we have virtual sites (set at the global option level) WHAM Boltzmann weights

Definition at line 76 of file abinitio.py.

8.5.4.58 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

8.5.4.59 forcebalance::openmmio.AbInitio_OpenMM::xyz_omms

Definition at line 430 of file openmmio.py.

The documentation for this class was generated from the following file:

- openmmio.py

8.6 forcebalance.tinkerio.AbInitio_TINKER Class Reference

Subclass of Target for force and energy matching using TINKER.

Inheritance diagram for forcebalance.tinkerio.AbInitio_TINKER:

Collaboration diagram for forcebalance.tinkerio.AbInitio_TINKER:

Public Member Functions

- def __init__

  Initialization; define a few core concepts.
- def prepare_temp_directory

  Prepare the temporary directory, by default does nothing.
- def energy_force_driver
- def energy_driver_all
- def energy_force_driver_all
- def read_topology
- def build_invdist
- def compute_netforce_torque
- def read_reference_data

  Read the reference ab initio data from a file such as qdata.txt.
- def indicate
- def energy_force_transformer_all
- def energy_force_transformer
- def get_energy_force_

  LPW 06-30-2013.
- def get_resp_

  Electrostatic potential fitting.
- def get

  Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.

- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- trajfnm

  Name of the trajectory.
- all_at_once

  all_at_once is not implemented.
- whamboltz_wts

  Initialize the base class.
- qmboltz_wts

  QM Boltzmann weights.
- eqm

  Reference (QM) energies.
- emd0

  Energies of the sampling simulation.
- fqm

  Reference (QM) forces.
- espxyz

  ESP grid points.
- espval

  ESP values.
- qfnm

  The qdata.txt file that contains the QM energies and forces.
- qmatoms

  The number of atoms in the QM calculation (Irrelevant if not fitting forces)
- e_err

  Qualitative Indicator: average energy error (in kJ/mol)
- e_err_pct

- f_err

  Qualitative Indicator: average force error (fractional)
- f_err_pct
- esp_err

  Qualitative Indicator: "relative RMS" for electrostatic potential.
- nf_err
- nf_err_pct
- tq_err_pct
- use_nft

  Whether to compute net forces and torques, or not.
- ns

  Read in the trajectory file.
- traj
- nparticles

  The number of (atoms + drude particles + virtual sites)
- AtomLists

  This is a default-dict containing a number of atom-wise lists, such as the residue number of each atom, the mass of each atom, and so on.
- new_vsites

  Read in the topology.
- save_vmvals

  Save the mvals from the last time we updated the vsites.
- topology_flag
- force_map
- nnf
- ntq
- force
- w_force
- nesp
- fitatoms
- whamboltz
- nftqm
- fref
- w_energy
- w_netforce
- w_torque
- e_ref
- f_ref
- nf_ref
- tq_ref
- tq_err
- w_resp
- invdists
- respterm
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.

- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.6.1 Detailed Description

Subclass of Target for force and energy matching using TINKER.

Implements the prepare and energy_force_driver methods.

Definition at line 295 of file tinkerio.py.

8.6.2 Constructor & Destructor Documentation

8.6.2.1 def forcebalance.tinkerio.AbInitio_TINKER.__init__ (*self, options, tgt_opts, forcefield*)

Initialization; define a few core concepts.

Todo Obtain the number of true atoms (or the particle -> atom mapping) from the force field.

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 298 of file tinkerio.py.

8.6.3 Member Function Documentation

8.6.3.1 def forcebalance.abinitio.AbInitio.build_invdist (*self, mvals*) [inherited]

Definition at line 168 of file abinitio.py.

Here is the call graph for this function:

8.6.3.2 def forcebalance.abinitio.AbInitio.compute_netforce_torque (*self, xyz, force, QM* = False) [inherited]

Definition at line 204 of file abinitio.py.

8.6.3.3 def forcebalance.tinkerio.AbInitio_TINKER.energy_driver_all (*self*)

Definition at line 331 of file tinkerio.py.

Here is the call graph for this function:

8.6.3.4 def forcebalance.tinkerio.AbInitio_TINKER.energy_force_driver (*self, shot*)

Definition at line 315 of file tinkerio.py.

Here is the call graph for this function:

8.6.3.5 def forcebalance.tinkerio.AbInitio_TINKER.energy_force_driver_all (*self*)

Definition at line 344 of file tinkerio.py.

Here is the call graph for this function:

8.6.3.6 def forcebalance.abinitio.AbInitio.energy_force_transformer (*self, i*) [inherited]

Definition at line 459 of file abinitio.py.

Here is the call graph for this function:

8.6.3.7 def forcebalance.abinitio.AbInitio.energy_force_transformer_all (*self*) [inherited]

Definition at line 442 of file abinitio.py.

Here is the call graph for this function:

8.6.3.8 def forcebalance.abinitio.AbInitio.get (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.

See abinitio for an example.

Reimplemented from forcebalance.target.Target.

Definition at line 1100 of file abinitio.py.

8.6.3.9 def forcebalance.abinitio.AbInitio.get_energy_force_ (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

LPW 06-30-2013.

This subroutine builds the objective function (and optionally its derivatives) from a general simulation software. This is in contrast to using GROMACS-X2, which computes the objective function and prints it out; then 'get' only needs to call GROMACS and read it in.

This subroutine interfaces with simulation software 'drivers'. The driver is only expected to give the energy and forces.

Now this subroutine may sound trivial since the objective function is simply a least-squares quantity (M-Q)^2 - but there are a number of nontrivial considerations. I will list them here.

0) Polytensor formulation: Because there may exist covariance between different components of the force (or covariance between the energy and the force), we build the objective function by taking outer products of vectors that have the form [E F_1x F_1y F_1z F_2x F_2y ...], and then we trace it with the inverse of the covariance matrix to get the objective function.

This version implements both the polytensor formulation and the standard formulation.

1) Boltzmann weights and normalization: Each snapshot has its own Boltzmann weight, which may or may not be normalized. This subroutine does the normalization automatically.

2) Subtracting out the mean energy gap: The zero-point energy difference between reference data and simulation is meaningless. This subroutine subtracts it out.

3) Hybrid ensembles: This program builds a combined objective function from both MM and QM ensembles, which is rigorously better than using a single ensemble.

Note that this subroutine does not do EVERYTHING that GROMACS-X2 can do, which includes:

1) Internal coordinate systems 2) 'Sampling correction' (deprecated, since it doesn't seem to work) 3) Analytic derivatives

In the previous code (ForTune) this subroutine used analytic first derivatives of the energy and force to build the derivatives of the objective function. Here I will take a simplified approach, because building the derivatives are cumbersome. For now we will return the objective function ONLY. A two-point central difference should give us the first and diagonal second derivative anyhow.

Todo Parallelization over snapshots is not implemented yet

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient
in	*AHess*	Switch to turn on analytic Hessian

Returns

Answer Contribution to the objective function

Definition at line 534 of file abinitio.py.

8.6.3.10 def forcebalance.target.Target.get_G (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.6.3.11 def forcebalance.target.Target.get_H (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.6.3.12 def forcebalance.abinitio.AbInitio.get_resp_ (*self*, *mvals*, *AGrad* = `False`, *AHess* = `False`) `[inherited]`

Electrostatic potential fitting.

Implements the RESP objective function. (In Python so obviously not optimized.) This function takes the mathematical parameter values and returns the charges on the ATOMS (fancy mapping going on)

Definition at line 1001 of file abinitio.py.

8.6.3.13 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) `[inherited]`

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.6.3.14 def forcebalance.abinitio.AbInitio.indicate (*self*) [inherited]

Definition at line 422 of file abinitio.py.

Here is the call graph for this function:

8.6.3.15 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.6.3.16 def forcebalance.tinkerio.AbInitio_TINKER.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory, by default does nothing.

Reimplemented from forcebalance.abinitio.AbInitio.

Definition at line 307 of file tinkerio.py.

Here is the call graph for this function:

8.6.3.17 def forcebalance.target.Target.printcool_table (*self*, *data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.6.3.18 def forcebalance.abinitio.AbInitio.read_reference_data (*self*) `[inherited]`

Read the reference ab initio data from a file such as qdata.txt.

Todo Add an option for picking any slice out of qdata.txt, helpful for cross-validation

Todo Closer integration of reference data with program - leave behind the qdata.txt format? (For now, I like the readability of qdata.txt)

After reading in the information from qdata.txt, it is converted into the GROMACS energy units (kind of an arbitrary choice); forces (kind of a misnomer in qdata.txt) are multipled by -1 to convert gradients to forces.

We also subtract out the mean energies of all energy arrays because energy/force matching does not account for zero-point energy differences between MM and QM (i.e. energy of electrons in core orbitals).

The configurations in force/energy matching typically come from a the thermodynamic ensemble of the MM force field at some temperature (by running MD, for example), and for many reasons it is helpful to introduce non-Boltzmann weights

in front of these configurations. There are two options: WHAM Boltzmann weights (for combining the weights of several simulations together) and QM Boltzmann weights (for converting MM weights into QM weights). Note that the two sets of weights 'stack'; i.e. they can be used at the same time.

A 'hybrid' ensemble is possible where we use 50% MM and 50% QM weights. Please read more in LPW and Troy Van Voorhis, JCP Vol. 133, Pg. 231101 (2010), doi:10.1063/1.3519043.

Todo The WHAM Boltzmann weights are generated by external scripts (wanalyze.py and make-wham-data.sh) and passed in; perhaps these scripts can be added to the ForceBalance distribution or integrated more tightly.

Finally, note that using non-Boltzmann weights degrades the statistical information content of the snapshots. This problem will generally become worse if the ensemble to which we're reweighting is dramatically different from the one we're sampling from. We end up with a set of Boltzmann weights like [1e-9, 1e-9, 1.0, 1e-9, 1e-9 ...] and this is essentially just one snapshot. I believe Troy is working on something to cure this problem.

Here, we have a measure for the information content of our snapshots, which comes easily from the definition of information entropy:

S = -1∗Sum_i(P_i∗log(P_i)) InfoContent = exp(-S)

With uniform weights, InfoContent is equal to the number of snapshots; with horrible weights, InfoContent is closer to one.

Definition at line 317 of file abinitio.py.

8.6.3.19 def forcebalance.abinitio.AbInitio.read_topology (*self*) [inherited]

Reimplemented in forcebalance.gmxio.AbInitio_GMX, and forcebalance.openmmio.AbInitio_OpenMM.

Definition at line 164 of file abinitio.py.

8.6.3.20 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.6.3.21 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.6.3.22 def forcebalance.target.Target.sget (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.6.3.23 def forcebalance.target.Target.stage (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.6.3.24 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.6.3.25 def forcebalance.target.Target.wq_complete (*self*) `[inherited]`

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.6.4 Member Data Documentation

8.6.4.1 forcebalance::tinkerio.AbInitio_TINKER::all_at_once

all_at_once is not implemented.

Definition at line 300 of file tinkerio.py.

8.6.4.2 forcebalance::abinitio.AbInitio::AtomLists `[inherited]`

This is a default-dict containing a number of atom-wise lists, such as the residue number of each atom, the mass of each atom, and so on.

Reimplemented in forcebalance.gmxio.AbInitio_GMX.

Definition at line 92 of file abinitio.py.

8.6.4.3 forcebalance::abinitio.AbInitio::e_err `[inherited]`

Qualitative Indicator: average energy error (in kJ/mol)

Definition at line 85 of file abinitio.py.

8.6.4.4 forcebalance::abinitio.AbInitio::e_err_pct [inherited]

Definition at line 85 of file abinitio.py.

8.6.4.5 forcebalance::abinitio.AbInitio::e_ref [inherited]

Definition at line 534 of file abinitio.py.

8.6.4.6 forcebalance::abinitio.AbInitio::emd0 [inherited]

Energies of the sampling simulation.

Definition at line 79 of file abinitio.py.

8.6.4.7 forcebalance::abinitio.AbInitio::eqm [inherited]

Reference (QM) energies.

Definition at line 78 of file abinitio.py.

8.6.4.8 forcebalance::abinitio.AbInitio::esp_err [inherited]

Qualitative Indicator: "relative RMS" for electrostatic potential.

Definition at line 87 of file abinitio.py.

8.6.4.9 forcebalance::abinitio.AbInitio::espval [inherited]

ESP values.

Definition at line 82 of file abinitio.py.

8.6.4.10 forcebalance::abinitio.AbInitio::espxyz [inherited]

ESP grid points.

Definition at line 81 of file abinitio.py.

8.6.4.11 forcebalance::abinitio.AbInitio::f_err [inherited]

Qualitative Indicator: average force error (fractional)

Definition at line 86 of file abinitio.py.

8.6.4.12 forcebalance::abinitio.AbInitio::f_err_pct [inherited]

Definition at line 86 of file abinitio.py.

8.6.4.13 forcebalance::abinitio.AbInitio::f_ref [inherited]

Definition at line 534 of file abinitio.py.

8.6.4.14 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.6.4.15 forcebalance::abinitio.AbInitio::fitatoms [inherited]

Definition at line 317 of file abinitio.py.

8.6.4.16 forcebalance::abinitio.AbInitio::force [inherited]

Definition at line 317 of file abinitio.py.

8.6.4.17 forcebalance::abinitio.AbInitio::force_map [inherited]

Definition at line 204 of file abinitio.py.

8.6.4.18 forcebalance::abinitio.AbInitio::fqm [inherited]

Reference (QM) forces.

Definition at line 80 of file abinitio.py.

8.6.4.19 forcebalance::abinitio.AbInitio::fref [inherited]

Definition at line 317 of file abinitio.py.

8.6.4.20 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.6.4.21 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.6.4.22 forcebalance::abinitio.AbInitio::invdists [inherited]

Definition at line 1001 of file abinitio.py.

8.6.4.23 forcebalance::abinitio.AbInitio::nesp [inherited]

Definition at line 317 of file abinitio.py.

8.6.4.24 forcebalance::abinitio.AbInitio::new_vsites [inherited]

Read in the topology.

Read in the reference data Prepare the temporary directory The below two options are related to whether we want to rebuild virtual site positions. Rebuild the distance matrix if virtual site positions have changed

Definition at line 97 of file abinitio.py.

8.6.4.25 forcebalance::abinitio.AbInitio::nf_err [inherited]

Definition at line 87 of file abinitio.py.

8.6.4.26 forcebalance::abinitio.AbInitio::nf_err_pct [inherited]

Definition at line 87 of file abinitio.py.

8.6.4.27 forcebalance::abinitio.AbInitio::nf_ref [inherited]

Definition at line 534 of file abinitio.py.

8.6.4.28 forcebalance::abinitio.AbInitio::nftqm [inherited]

Definition at line 317 of file abinitio.py.

8.6.4.29 forcebalance::abinitio.AbInitio::nnf [inherited]

Definition at line 204 of file abinitio.py.

8.6.4.30 forcebalance::abinitio.AbInitio::nparticles [inherited]

The number of (atoms + drude particles + virtual sites)

Definition at line 90 of file abinitio.py.

8.6.4.31 forcebalance::abinitio.AbInitio::ns [inherited]

Read in the trajectory file.

Definition at line 89 of file abinitio.py.

8.6.4.32 forcebalance::abinitio.AbInitio::ntq [inherited]

Definition at line 204 of file abinitio.py.

8.6.4.33 forcebalance::abinitio.AbInitio::objective [inherited]

Definition at line 1100 of file abinitio.py.

8.6.4.34 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.6.4.35 forcebalance::abinitio.AbInitio::qfnm [inherited]

The qdata.txt file that contains the QM energies and forces.

Definition at line 83 of file abinitio.py.

8.6.4.36 forcebalance::abinitio.AbInitio::qmatoms [inherited]

The number of atoms in the QM calculation (Irrelevant if not fitting forces)

Definition at line 84 of file abinitio.py.

8.6.4.37 forcebalance::abinitio.AbInitio::qmboltz_wts [inherited]

QM Boltzmann weights.

Definition at line 77 of file abinitio.py.

8.6.4.38 forcebalance::abinitio.AbInitio::respterm [inherited]

Definition at line 1001 of file abinitio.py.

8.6.4.39 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.6.4.40 forcebalance::abinitio.AbInitio::save_vmvals [inherited]

Save the mvals from the last time we updated the vsites.

Definition at line 98 of file abinitio.py.

8.6.4.41 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.6.4.42 forcebalance::abinitio.AbInitio::topology_flag [inherited]

Reimplemented in forcebalance.gmxio.AbInitio_GMX, and forcebalance.openmmio.AbInitio_OpenMM.

Definition at line 164 of file abinitio.py.

8.6.4.43 forcebalance::abinitio.AbInitio::tq_err [inherited]

Definition at line 534 of file abinitio.py.

8.6.4.44 forcebalance::abinitio.AbInitio::tq_err_pct [inherited]

Definition at line 87 of file abinitio.py.

8.6.4.45 forcebalance::abinitio.AbInitio::tq_ref [inherited]

Definition at line 534 of file abinitio.py.

8.6.4.46 forcebalance::abinitio.AbInitio::traj [inherited]

Definition at line 89 of file abinitio.py.

8.6.4.47 forcebalance::tinkerio.AbInitio_TINKER::trajfnm

Name of the trajectory.

Definition at line 299 of file tinkerio.py.

8.6.4.48 forcebalance::abinitio.AbInitio::use_nft [inherited]

Whether to compute net forces and torques, or not.

Definition at line 88 of file abinitio.py.

8.6.4.49 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.6.4.50 forcebalance::abinitio.AbInitio::w_energy [inherited]

Definition at line 534 of file abinitio.py.

8.6.4.51 forcebalance::abinitio.AbInitio::w_force [inherited]

Definition at line 317 of file abinitio.py.

8.6.4.52 forcebalance::abinitio.AbInitio::w_netforce [inherited]

Definition at line 534 of file abinitio.py.

8.6.4.53 forcebalance::abinitio.AbInitio::w_resp [inherited]

Definition at line 1001 of file abinitio.py.

8.6.4.54 forcebalance::abinitio.AbInitio::w_torque [inherited]

Definition at line 534 of file abinitio.py.

8.6.4.55 forcebalance::abinitio.AbInitio::whamboltz [inherited]

Definition at line 317 of file abinitio.py.

8.6.4.56 forcebalance::abinitio.AbInitio::whamboltz_wts [inherited]

Initialize the base class.

Number of snapshots Whether to use WHAM Boltzmann weights Whether to use the Sampling Correction Whether to match Absolute Energies (make sure you know what you're doing) Whether to use the Covariance Matrix Whether to use QM Boltzmann weights The temperature for QM Boltzmann weights Number of atoms that we are fitting Whether to fit Energies. Whether to fit Forces. Whether to fit Electrostatic Potential. Weights for the three components. Option for how much data to write to disk. Whether to do energy and force calculations for the whole trajectory, or to do one calculation per snapshot. OpenMM-only option - whether to run the energies and forces internally. Whether we have virtual sites (set at the global option level) WHAM Boltzmann weights

Definition at line 76 of file abinitio.py.

8.6.4.57 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- tinkerio.py

8.7 forcebalance.forcefield.BackedUpDict Class Reference

Public Member Functions

- def __init__
- def __missing__

Public Attributes

- backup_dict

8.7.1 Detailed Description

Definition at line 175 of file forcefield.py.

8.7.2 Constructor & Destructor Documentation

8.7.2.1 def forcebalance.forcefield.BackedUpDict.__init__ (*self, backup_dict*)

Definition at line 176 of file forcefield.py.

8.7.3 Member Function Documentation

8.7.3.1 def forcebalance.forcefield.BackedUpDict.__missing__ (*self, key*)

Definition at line 179 of file forcefield.py.

Here is the call graph for this function:

8.7.4 Member Data Documentation

8.7.4.1 forcebalance::forcefield.BackedUpDict::backup_dict

Definition at line 176 of file forcefield.py.

The documentation for this class was generated from the following file:

- forcefield.py

8.8 forcebalance.BaseClass Class Reference

Provides some nifty functions that are common to all ForceBalance classes.

Inheritance diagram for forcebalance.BaseClass:

Public Member Functions

- def __init__
- def set_option

Public Attributes

- PrintOptionDict
- verbose_options

8.8.1 Detailed Description

Provides some nifty functions that are common to all ForceBalance classes.

Definition at line 26 of file __init__.py.

8.8.2 Constructor & Destructor Documentation

8.8.2.1 def forcebalance.BaseClass.__init__ (*self, options*)

Definition at line 28 of file __init__.py.

8.8.3 Member Function Documentation

8.8.3.1 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = `None`, *val* = `None`, *default* = `None`, *forceprint* = `False`)

Definition at line 32 of file __init__.py.

8.8.4 Member Data Documentation

8.8.4.1 forcebalance.BaseClass::PrintOptionDict

Definition at line 28 of file __init__.py.

8.8.4.2 forcebalance.BaseClass::verbose_options

Definition at line 28 of file __init__.py.

The documentation for this class was generated from the following file:

- __init__.py

8.9 forcebalance.BaseReader Class Reference

The 'reader' class.

Inheritance diagram for forcebalance.BaseReader:

Public Member Functions

- def __init__
- def Split

- def Whites
- def feed
- def build_pid

  Returns the parameter type (e.g.

Public Attributes

- ln
- itype
- suffix
- pdict
- adict

  The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.
- molatom

  The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.
- Molecules
- AtomTypes

8.9.1 Detailed Description

The 'reader' class.

It serves two main functions:

1) When parsing a text force field file, the 'feed' method is called once for every line. Calling the 'feed' method stores the internal variables that are needed for making the unique parameter identifier.

2) The 'reader' also stores the 'pdict' dictionary, which is needed for building the matrix of rescaling factors. This is not needed for the XML force fields, so in XML force fields pdict is replaced with a string called "XML_Override".

Definition at line 64 of file __init__.py.

8.9.2 Constructor & Destructor Documentation

8.9.2.1 def forcebalance.BaseReader.__init__ (*self, fnm*)

Reimplemented in forcebalance.openmmio.OpenMM_Reader, forcebalance.gmxio.ITP_Reader, forcebalance.psi4io.Grid_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.psi4io.GBS_Reader, forcebalance.qchemio.QCIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 66 of file __init__.py.

8.9.3 Member Function Documentation

8.9.3.1 def forcebalance.BaseReader.build_pid (*self, pfld*)

Returns the parameter type (e.g.

K in BONDSK) based on the current interaction type.

Both the 'pdict' dictionary (see gmxio.pdict) and the interaction type 'state' (here, BONDS) are needed to get the parameter type.

If, however, 'pdict' does not contain the ptype value, a suitable substitute is simply the field number.

Note that if the interaction type state is not set, then it defaults to the file name, so a generic parameter ID is 'filename.-line_num.field_num'

Reimplemented in forcebalance.psi4io.Grid_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 107 of file __init__.py.

8.9.3.2 def forcebalance.BaseReader.feed (*self, line*)

Reimplemented in forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.-Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.Q-CIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 88 of file __init__.py.

Here is the call graph for this function:

8.9.3.3 def forcebalance.BaseReader.Split (*self, line*)

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 82 of file __init__.py.

Here is the call graph for this function:

8.9.3.4 def forcebalance.BaseReader.Whites (*self, line*)

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 85 of file __init__.py.

Here is the call graph for this function:

8.9.4 Member Data Documentation

8.9.4.1 forcebalance.BaseReader::adict

The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.

Reimplemented in forcebalance.amberio.FrcMod_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 67 of file __init__.py.

8.9.4.2 forcebalance.BaseReader::AtomTypes

Definition at line 71 of file __init__.py.

8.9.4.3 forcebalance.BaseReader::itype

Reimplemented in forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.QCIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 66 of file __init__.py.

8.9.4.4 forcebalance.BaseReader::ln

Definition at line 66 of file __init__.py.

8.9.4.5 forcebalance.BaseReader::molatom

The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.

self.moleculedict = OrderedDict() The listing of 'RES:ATOMNAMES' for atom names in the line This is obviously a placeholder.

Reimplemented in forcebalance.gmxio.ITP_Reader, and forcebalance.amberio.Mol2_Reader.

Definition at line 71 of file __init__.py.

8.9.4.6 forcebalance.BaseReader::Molecules

Definition at line 71 of file __init__.py.

8.9.4.7 forcebalance.BaseReader::pdict

Reimplemented in forcebalance.openmmio.OpenMM_Reader, forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.QCIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 66 of file __init__.py.

8.9.4.8 forcebalance.BaseReader::suffix

Reimplemented in forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.QCIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 66 of file __init__.py.

The documentation for this class was generated from the following file:

- __init__.py

8.10 forcebalance.binding.BindingEnergy Class Reference

Improved subclass of Target for fitting force fields to binding energies.

Inheritance diagram for forcebalance.binding.BindingEnergy:

Collaboration diagram for forcebalance.binding.BindingEnergy:

Public Member Functions

- def __init__

  All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)
- def indicate
- def get

  Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- inter_opts
- PrintDict
- RMSDDict
- rmsd_part
- energy_part
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.10.1 Detailed Description

Improved subclass of Target for fitting force fields to binding energies.

Definition at line 123 of file binding.py.

8.10.2 Constructor & Destructor Documentation

8.10.2.1 def forcebalance.binding.BindingEnergy.__init__ (*self, options, tgt_opts, forcefield*)

All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)

If we want to add attributes that are more specific (i.e. a set of reference forces for force matching), they are added in the subclass AbInitio that inherits from Target.

Reimplemented from forcebalance.target.Target.

Reimplemented in forcebalance.tinkerio.BindingEnergy_TINKER.

Definition at line 126 of file binding.py.

8.10.3 Member Function Documentation

8.10.3.1 def forcebalance.binding.BindingEnergy.get (*self, mvals, AGrad* = `False`, *AHess* = `False`)

Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.

See abinitio for an example.

Reimplemented from forcebalance.target.Target.

Definition at line 162 of file binding.py.

8.10.3.2 def forcebalance.target.Target.get_G (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.10.3.3 def forcebalance.target.Target.get_H (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.10.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.10.3.5 def forcebalance.binding.BindingEnergy.indicate (*self*)

Definition at line 156 of file binding.py.

Here is the call graph for this function:

8.10.3.6 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.10.3.7 def forcebalance.target.Target.printcool_table (*self, data* = OrderedDict([]), *headings* = [], *banner* = None, *footnote* = None, *color* = 0) [inherited]

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.10.3.8 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.10.3.9 def forcebalance.BaseClass.set_option (*self*, *in_dict*, *src_key*, *dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.10.3.10 def forcebalance.target.Target.sget (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) `[inherited]`

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.10.3.11 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) `[inherited]`

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.10.3.12 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.10.3.13 def forcebalance.target.Target.wq_complete (*self*) `[inherited]`

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.10.4 Member Data Documentation

8.10.4.1 forcebalance::binding.BindingEnergy::energy_part

Definition at line 162 of file binding.py.

8.10.4.2 forcebalance::target.Target::FF `[inherited]`

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.10.4.3 forcebalance::target.Target::gct `[inherited]`

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.10.4.4 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.10.4.5 forcebalance::binding.BindingEnergy::inter_opts

Definition at line 126 of file binding.py.

8.10.4.6 forcebalance::binding.BindingEnergy::objective

Definition at line 162 of file binding.py.

8.10.4.7 forcebalance::binding.BindingEnergy::PrintDict

Definition at line 162 of file binding.py.

8.10.4.8 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.10.4.9 forcebalance::binding.BindingEnergy::rmsd_part

Definition at line 162 of file binding.py.

8.10.4.10 forcebalance::binding.BindingEnergy::RMSDDict

Definition at line 162 of file binding.py.

8.10.4.11 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.10.4.12 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.10.4.13 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.10.4.14 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- binding.py

8.11 forcebalance.tinkerio.BindingEnergy_TINKER Class Reference

Subclass of BindingEnergy for binding energy matching using TINKER.

Inheritance diagram for forcebalance.tinkerio.BindingEnergy_TINKER:

Collaboration diagram for forcebalance.tinkerio.BindingEnergy_TINKER:

Public Member Functions

- def __init__

  All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)
- def prepare_temp_directory
- def system_driver
- def indicate
- def get

  Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

Stages the directory for the target, and then launches Work Queue processes if any.

- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.

- def printcool_table

  Print target information in an organized table format.

- def set_option

Public Attributes

- optprog
- inter_opts
- PrintDict
- RMSDDict
- rmsd_part
- energy_part
- objective
- tempdir

  Root directory of the whole project.

- rundir

  The directory in which the simulation is running - this can be updated.

- FF

  Need the forcefield (here for now)

- xct

  Counts how often the objective function was computed.

- gct

  Counts how often the gradient was computed.

- hct

  Counts how often the Hessian was computed.

- PrintOptionDict
- verbose_options

8.11.1 Detailed Description

Subclass of BindingEnergy for binding energy matching using TINKER.

Definition at line 484 of file tinkerio.py.

8.11.2 Constructor & Destructor Documentation

8.11.2.1 def forcebalance.tinkerio.BindingEnergy_TINKER.__init__ (*self, options, tgt_opts, forcefield*)

All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)

If we want to add attributes that are more specific (i.e. a set of reference forces for force matching), they are added in the subclass AbInitio that inherits from Target.

Reimplemented from forcebalance.binding.BindingEnergy.

Definition at line 487 of file tinkerio.py.

Here is the call graph for this function:

8.11.3 Member Function Documentation

8.11.3.1 def forcebalance.binding.BindingEnergy.get (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.

See abinitio for an example.

Reimplemented from forcebalance.target.Target.

Definition at line 162 of file binding.py.

8.11.3.2 def forcebalance.target.Target.get_G (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.11.3.3 def forcebalance.target.Target.get_H (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.11.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = None) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.11.3.5 def forcebalance.binding.BindingEnergy.indicate (*self*) [inherited]

Definition at line 156 of file binding.py.

Here is the call graph for this function:

8.11.3.6 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.11.3.7 def forcebalance.tinkerio.BindingEnergy_TINKER.prepare_temp_directory (*self, options, tgt_opts*)

Definition at line 491 of file tinkerio.py.

Here is the call graph for this function:

8.11.3.8 def forcebalance.target.Target.printcool_table (*self*, *data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.11.3.9 def forcebalance.target.Target.refresh_temp_directory (*self*) `[inherited]`

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.11.3.10 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.11.3.11 def forcebalance.target.Target.sget (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.11.3.12 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.11.3.13 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.11.3.14 def forcebalance.tinkerio.BindingEnergy_TINKER.system_driver (*self, sysname*)

Definition at line 545 of file tinkerio.py.

Here is the call graph for this function:

8.11.3.15 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.11.4 Member Data Documentation

8.11.4.1 forcebalance::binding.BindingEnergy::energy_part [inherited]

Definition at line 162 of file binding.py.

8.11.4.2 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.11.4.3 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.11.4.4 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.11.4.5 forcebalance::binding.BindingEnergy::inter_opts [inherited]

Definition at line 126 of file binding.py.

8.11.4.6 forcebalance::binding.BindingEnergy::objective [inherited]

Definition at line 162 of file binding.py.

8.11.4.7 forcebalance::tinkerio.BindingEnergy_TINKER::optprog

Definition at line 491 of file tinkerio.py.

8.11.4.8 forcebalance::binding.BindingEnergy::PrintDict [inherited]

Definition at line 162 of file binding.py.

8.11.4.9 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.11.4.10 forcebalance::binding.BindingEnergy::rmsd_part [inherited]

Definition at line 162 of file binding.py.

8.11.4.11 forcebalance::binding.BindingEnergy::RMSDDict [inherited]

Definition at line 162 of file binding.py.

8.11.4.12 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.11.4.13 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.11.4.14 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.11.4.15 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- tinkerio.py

8.12 forcebalance.output.CleanFileHandler Class Reference

File handler that does not write terminal escape codes and carriage returns to files.

Public Member Functions

- def emit

8.12.1 Detailed Description

File handler that does not write terminal escape codes and carriage returns to files.

Use this when writing to a file that will probably not be viewed in a terminal

Definition at line 69 of file output.py.

8.12.2 Member Function Documentation

8.12.2.1 def forcebalance.output.CleanFileHandler.emit (*self, record*)

Definition at line 70 of file output.py.

The documentation for this class was generated from the following file:

- output.py

8.13 forcebalance.output.CleanStreamHandler Class Reference

Similar to RawStreamHandler except it does not write terminal escape codes.

Public Member Functions

- def __init__
- def emit

8.13.1 Detailed Description

Similar to RawStreamHandler except it does not write terminal escape codes.

Use this for 'plain' terminal output without any fancy colors or formatting

Definition at line 56 of file output.py.

8.13.2 Constructor & Destructor Documentation

8.13.2.1 def forcebalance.output.CleanStreamHandler.__init__ (*self, stream* = `sys.stdout`)

Definition at line 57 of file output.py.

8.13.3 Member Function Documentation

8.13.3.1 def forcebalance.output.CleanStreamHandler.emit (*self, record*)

Definition at line 60 of file output.py.

The documentation for this class was generated from the following file:

- output.py

8.14 forcebalance.counterpoise.Counterpoise Class Reference

Target subclass for matching the counterpoise correction.

Inheritance diagram for forcebalance.counterpoise.Counterpoise:

Collaboration diagram for forcebalance.counterpoise.Counterpoise:

Public Member Functions

- def __init__

  To instantiate Counterpoise, we read the coordinates and counterpoise data.
- def loadxyz

  Parse an XYZ file which contains several xyz coordinates, and return their elements.
- def load_cp

  Load in the counterpoise data, which is easy; the file consists of floating point numbers separated by newlines.
- def get

  Gets the objective function for fitting the counterpoise correction.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- xyzs

  Number of snapshots.
- cpqm

  Counterpoise correction data.
- na

  Number of atoms.
- ns
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.14.1 Detailed Description

Target subclass for matching the counterpoise correction.

Definition at line 33 of file counterpoise.py.

8.14.2 Constructor & Destructor Documentation

8.14.2.1 def forcebalance.counterpoise.Counterpoise.__init__ (*self, options, tgt_opts, forcefield*)

To instantiate Counterpoise, we read the coordinates and counterpoise data.

Reimplemented from forcebalance.target.Target.

Definition at line 37 of file counterpoise.py.

8.14.3 Member Function Documentation

8.14.3.1 def forcebalance.counterpoise.Counterpoise.get (*self, mvals, AGrad* = `False`, *AHess* = `False`)

Gets the objective function for fitting the counterpoise correction.

As opposed to AbInitio_GMXX2, which calls an external program, this script actually computes the empirical interaction given the force field parameters.

It loops through the snapshots and atom pairs, and computes pairwise contributions to an energy term according to hard-coded functional forms.

One potential issue is that we go through all atom pairs instead of looking only at atom pairs between different fragments. This means that even for two infinitely separated fragments it will predict a finite CP correction. While it might be okay to apply such a potential in practice, there will be some issues for the fitting. Thus, we assume the last snapshot to be CP-free and subtract that value of the potential back out.

Note that forces and parametric derivatives are not implemented.

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient (not implemented)
in	*AHess*	Switch to turn on analytic Hessian (not implemented)

Returns

Answer Contribution to the objective function

Reimplemented from forcebalance.target.Target.

Definition at line 124 of file counterpoise.py.

8.14.3.2 def forcebalance.target.Target.get_G (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.14.3.3 def forcebalance.target.Target.get_H (*self, mvals =* None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.14.3.4 def forcebalance.target.Target.get_X (*self, mvals =* None) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.14.3.5 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.14.3.6 def forcebalance.counterpoise.Counterpoise.load_cp (*self, fnm*)

Load in the counterpoise data, which is easy; the file consists of floating point numbers separated by newlines.

Definition at line 95 of file counterpoise.py.

8.14.3.7 def forcebalance.counterpoise.Counterpoise.loadxyz (*self, fnm*)

Parse an XYZ file which contains several xyz coordinates, and return their elements.

Parameters

in	*fnm*	The input XYZ file name

Returns

elem A list of chemical elements in the XYZ file
xyzs A list of XYZ coordinates (number of snapshots times number of atoms)

Todo I should probably put this into a more general library for reading coordinates.

Definition at line 63 of file counterpoise.py.

8.14.3.8 def forcebalance.target.Target.printcool_table (*self*, *data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.14.3.9 def forcebalance.target.Target.refresh_temp_directory (*self*) `[inherited]`

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.14.3.10 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.14.3.11 def forcebalance.target.Target.sget (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.14.3.12 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.14.3.13 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.14.3.14 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.14.4 Member Data Documentation

8.14.4.1 forcebalance::counterpoise.Counterpoise::cpqm

Counterpoise correction data.

Definition at line 40 of file counterpoise.py.

8.14.4.2 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.14.4.3 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.14.4.4 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.14.4.5 forcebalance::counterpoise.Counterpoise::na

Number of atoms.

Definition at line 64 of file counterpoise.py.

8.14.4.6 forcebalance::counterpoise.Counterpoise::ns

Definition at line 64 of file counterpoise.py.

8.14.4.7 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.14.4.8 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.14.4.9 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.14.4.10 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.14.4.11 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

8.14.4.12 forcebalance::counterpoise.Counterpoise::xyzs

Number of snapshots.

XYZ elements and coordinates

Definition at line 39 of file counterpoise.py.

The documentation for this class was generated from the following file:

- counterpoise.py

8.15 forcebalance.engine.Engine Class Reference

Base class for all engines.

Inheritance diagram for forcebalance.engine.Engine:

Collaboration diagram for forcebalance.engine.Engine:

Public Member Functions

- def __init__
- def prepare
- def evaluate_snapshots

  Evaluate properties over a collection of snapshots.
- def evaluate_optimized

  Evaluate properties on the optimized geometry.
- def set_option

Public Attributes

- name

- target
- root
- PrintOptionDict
- verbose_options

8.15.1 Detailed Description

Base class for all engines.

1. Introduction

In ForceBalance an Engine represents a molecular dynamics code and the calculations that may be carried out with that code.

The Engine implements methods that execute operations such as:

- Input: trajectory object
- Return: energy over trajectory
- Return: energy and force over trajectory
- Return: electrostatic potential over trajectory
- How about:
- evaluate_snapshots(Molecule, Energy=True, Force=True, ESP=True) where all information passed in belongs in the Molecule object. :)
- Return a dictionary

- Input: molecular geometry,
- Return: optimized geometry
- Return: vibrational modes at optimized geometry
- Return: multipole moments at optimized geometry
- evaluate_optimized(Molecule, Energy=True, Frequencies=True, Moments=True)

- Engine objects may be initialized using a molecule object and a force field object.

2. Purpose

Previously system calls to MD software have been made by the Target. Duplication of code was occurring, because different Targets were carrying out the same type of calculation.

3. Also

Target objects should contain Engine objects, because OpenMM Engine objects need to be initialized at the start of a calculation.

Definition at line 60 of file engine.py.

8.15.2 Constructor & Destructor Documentation

8.15.2.1 def forcebalance.engine.Engine.__init__(*self, name = "engine", kwargs*)

Reimplemented in forcebalance.gmxio.GMX.

Definition at line 63 of file engine.py.

8.15.3 Member Function Documentation

8.15.3.1 def forcebalance.engine.Engine.evaluate_optimized (*self, M*)

Evaluate properties on the optimized geometry.

Definition at line 86 of file engine.py.

8.15.3.2 def forcebalance.engine.Engine.evaluate_snapshots (*self, M*)

Evaluate properties over a collection of snapshots.

Definition at line 80 of file engine.py.

Here is the call graph for this function:

8.15.3.3 def forcebalance.engine.Engine.prepare ( )

Definition at line 74 of file engine.py.

Here is the call graph for this function:

8.15.3.4 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = `None`, *val* = `None`, *default* = `None`, *forceprint* = `False`) `[inherited]`

Definition at line 32 of file __init__.py.

8.15.4 Member Data Documentation

8.15.4.1 forcebalance::engine.Engine::name

Definition at line 63 of file engine.py.

8.15.4.2 forcebalance.BaseClass::PrintOptionDict `[inherited]`

Definition at line 28 of file __init__.py.

8.15.4.3 forcebalance::engine.Engine::root

Definition at line 63 of file engine.py.

8.15.4.4 forcebalance::engine.Engine::target

Definition at line 63 of file engine.py.

8.15.4.5 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

The documentation for this class was generated from the following file:

- engine.py

8.16 forcebalance.forcefield.FF Class Reference

Force field class.

Inheritance diagram for forcebalance.forcefield.FF:

Collaboration diagram for forcebalance.forcefield.FF:

Public Member Functions

- def __init__

Instantiation of force field class.

- def addff

  Parse a force field file and add it to the class.
- def addff_txt

  Parse a text force field and create several important instance variables.
- def addff_xml

  Parse an XML force field file and create important instance variables.
- def make

  Create a new force field using provided parameter values.
- def make_redirect
- def find_spacings
- def create_pvals

  Converts mathematical to physical parameters.
- def create_mvals

  Converts physical to mathematical parameters.
- def rsmake

  Create the rescaling factors for the coordinate transformation in parameter space.
- def mktransmat

  Create the transformation matrix to rescale and rotate the mathematical parameters.
- def list_map

  Create the plist, which is like a reversed version of the parameter map.
- def print_map

  Prints out the (physical or mathematical) parameter indices, IDs and values in a visually appealing way.
- def assign_p0

  Assign physical parameter values to the 'pvals0' array.
- def assign_field

  Record the locations of a parameter in a txt file; [[file name, line number, field number, and multiplier]].
- def __eq__
- def set_option

Public Attributes

- ffdata

  As these options proliferate, the force field class becomes less standalone.
- ffdata_isxml
- map

  The mapping of interaction type -> parameter number.
- plist

  The listing of parameter number -> interaction types.
- patoms

  A listing of parameter number -> atoms involved.
- pfields

  A list where pfields[pnum] = ['file',line,field,mult,cmd], basically a new way to modify force field files; when we modify the force field file, we go to the specific line/field in a given file and change the number.
- rs

  List of rescaling factors.
- tm

The transformation matrix for mathematical -> physical parameters.

- tml

  The transpose of the transformation matrix.
- excision

  Indices to exclude from optimization / Hessian inversion.
- np

  The total number of parameters.
- pvals0

  Initial value of physical parameters.
- Readers

  A dictionary of force field reader classes.
- atomnames

  A list of atom names (this is new, for ESP fitting)
- FFAtomTypes

  WORK IN PROGRESS ## This is a dictionary of {'AtomType':{'Mass' : float, 'Charge' : float, 'ParticleType' : string ('A', 'S', or 'D'), 'AtomicNumber' : int}}.
- FFMolecules
- redirect

  Creates plist from map.
- linedestroy_save

  Destruction dictionary (experimental).
- parmdestroy_save
- linedestroy_this
- parmdestroy_this
- tinkerprm
- openmmxml
- qmap
- qid
- qid2
- PrintOptionDict
- verbose_options

8.16.1 Detailed Description

Force field class.

This class contains all methods for force field manipulation. To create an instance of this class, an input file is required containing the list of force field file names. Everything else inside this class pertaining to force field generation is self-contained.

For details on force field parsing, see the detailed documentation for addff.

Definition at line 196 of file forcefield.py.

8.16.2 Constructor & Destructor Documentation

8.16.2.1 def forcebalance.forcefield.FF.__init__ (*self, options, verbose* = `True`)

Instantiation of force field class.

Many variables here are initialized to zero, but they are filled out by methods like addff, rsmake, and mktransmat.

Definition at line 204 of file forcefield.py.

Here is the call graph for this function:

8.16.3 Member Function Documentation

8.16.3.1 def forcebalance.forcefield.FF.__eq__ (*self, other*)

Definition at line 1145 of file forcefield.py.

8.16.3.2 def forcebalance.forcefield.FF.addff (*self, ffname*)

Parse a force field file and add it to the class.

First, figure out the type of force field file. This is done either by explicitly specifying the type using for example, `ffname force_field.xml:openmm` or we figure it out by looking at the file extension.

Next, parse the file. Currently we support two classes of files - text and XML. The two types are treated very differently; for XML we use the parsers in libxml (via the python lxml module), and for text files we have our own in-house parsing class. Within text files, there is also a specialized GROMACS and TINKER parser as well as a generic text parser.

The job of the parser is to determine the following things: 1) Read the user-specified selection of parameters being fitted 2) Build a mapping (dictionary) of `parameter identifier -> index in parameter vector` 3) Build a list of physical parameter values 4) Figure out where to replace the parameter values in the force field file when the values are changed 5) Figure out which parameters need to be repeated or sign-flipped

Generally speaking, each parameter value in the force field file has a `unique parameter identifier` . `The identifier consists of three parts - the interaction type, the parameter subtype (within that interaction type), and the atoms involved.`

```
--- If XML: ---

The force field file is read in using the lxml Python module.  Specify which
parameter you want to fit using by adding a 'parameterize' element to the end
of the force field XML file, like so.

        <AmoebaVdwForce type="BUFFERED-14-7">
           <Vdw class="74" sigma="0.2655" epsilon="0.056484" reduction="0.910"
      parameterize="sigma, epsilon, reduction" />

In this example, the parameter identifier would look like Vdw/74/epsilon .

--- If GROMACS (.itp) or TINKER (.prm) :  ---

Follow the rules in the ITP_Reader or Tinker_Reader derived class.  Read the
documentation in the class documentation or the 'feed' method to learn more.
In all cases the parameter is tagged using # PARM 3  (where # denotes a comment,
the word PARM stays the same, and 3 is the field number starting from zero.)

--- If normal text :  ---
```

```
The parameter identifier is simply built using the file name, line number, and
field.  Thus, the identifier is unique but completely noninformative (which is
not ideal for our purposes, but it works.)
--- Endif ---
```

Warning

```
My program currently assumes that we are only using one MM program per
job.  If we use CHARMM and GROMACS to perform simulations as part of the
same TARGET, we will get messed up.  Maybe this needs to be fixed in the
future, with program prefixes to parameters like C_ , G_ ..  or simply
unit conversions, you get the idea.
I don't think the multiplier actually works for analytic derivatives unless
the interaction calculator knows the multiplier as well.  I'm sure I can
make this work in the future if necessary.
```

Parameters

in	*ffname*	Name of the force field file

Definition at line 395 of file forcefield.py.

8.16.3.3 def forcebalance.forcefield.FF.addff_txt (*self, ffname, fftype*)

Parse a text force field and create several important instance variables.

Each line is processed using the 'feed' method as implemented in the reader class. This essentially allows us to create the correct parameter identifier (pid), because the pid comes from more than the current line, it also depends on the section that we're in.

When 'PARM' or 'RPT' is encountered, we do several things:

- Build the parameter identifier and insert it into the map
- Point to the file name, line number, and field where the parameter may be modified

Additionally, when 'PARM' is encountered:

- Store the physical parameter value (this is permanent; it's the original value)
- Increment the total number of parameters

When 'RPT' is encountered we don't expand the parameter vector because this parameter is a copy of an existing one. If the parameter identifier is preceded by MINUS_, we chop off the prefix but remember that the sign needs to be flipped.

Definition at line 465 of file forcefield.py.

Here is the call graph for this function:

8.16.3.4 def forcebalance.forcefield.FF.addff_xml (*self, ffname*)

Parse an XML force field file and create important instance variables.

This was modeled after addff_txt, but XML and text files are fundamentally different, necessitating two different methods.

We begin with an _ElementTree object. We search through the tree for the 'parameterize' and 'parameter_repeat' keywords. Each time the keyword is encountered, we do the same four actions that I describe in addff_txt.

It's hard to specify precisely the location in an XML file to change a force field parameter. I can create a list of tree elements (essentially pointers to elements within a tree), but this method breaks down when I copy the tree because I have no way to refer to the copied tree elements. Fortunately, lxml gives me a way to represent a tree using a flat list, and my XML file 'locations' are represented using the positions in the list.

Warning

> The sign-flip hasn't been implemented yet. This shouldn't matter unless your calculation contains repeated parameters with opposite sign.

Definition at line 573 of file forcefield.py.

Here is the call graph for this function:

8.16.3.5 def forcebalance.forcefield.FF.assign_field (*self, idx, fnm, ln, pfld, mult, cmd* = `None`)

Record the locations of a parameter in a txt file; [[file name, line number, field number, and multiplier]].

Note that parameters can have multiple locations because of the repetition functionality.

Parameters

in	*idx*	The index of the parameter.
in	*fnm*	The file name of the parameter field.
in	*ln*	The line number within the file (or the node index in the flattened xml)
in	*pfld*	The field within the line (or the name of the attribute in the xml)
in	*mult*	The multiplier (this is usually 1.0)

Definition at line 1139 of file forcefield.py.

Here is the call graph for this function:

8.16.3.6 def forcebalance.forcefield.FF.assign_p0 (*self, idx, val*)

Assign physical parameter values to the 'pvals0' array.

Parameters

in	*idx*	The index to which we assign the parameter value.
in	*val*	The parameter value to be inserted.

Definition at line 1121 of file forcefield.py.

Here is the call graph for this function:

8.16.3.7 def forcebalance.forcefield.FF.create_mvals (*self, pvals*)

Converts physical to mathematical parameters.

We create the inverse transformation matrix using SVD.

Parameters

in	*pvals*	The physical parameters

Returns

mvals The mathematical parameters

Definition at line 854 of file forcefield.py.

Here is the call graph for this function:

8.16.3.8 def forcebalance.forcefield.FF.create_pvals (*self, mvals*)

Converts mathematical to physical parameters.

First, mathematical parameters are rescaled and rotated by multiplying by the transformation matrix, followed by adding the original physical parameters.

Parameters

in	*mvals*	The mathematical parameters

Returns

pvals The physical parameters

Definition at line 819 of file forcefield.py.

Here is the call graph for this function:

8.16.3.9 def forcebalance.forcefield.FF.find_spacings (*self*)

Definition at line 774 of file forcefield.py.

Here is the call graph for this function:

8.16.3.10 def forcebalance.forcefield.FF.list_map (*self*)

Create the plist, which is like a reversed version of the parameter map.

More convenient for printing.

Definition at line 1097 of file forcefield.py.

Here is the call graph for this function:

8.16.3.11 def forcebalance.forcefield.FF.make (*self, vals, use_pvals* = `False`, *printdir* = `None`, *precision* = `12`)

Create a new force field using provided parameter values.

This big kahuna does a number of things: 1) Creates the physical parameters from the mathematical parameters 2) Creates force fields with physical parameters substituted in 3) Prints the force fields to the specified file.

It does NOT store the mathematical parameters in the class state (since we can only hold one set of parameters).

Parameters

in	*printdir*	The directory that the force fields are printed to; as usual this is relative to the project root directory.
in	*vals*	Input parameters. I previously had an option where it uses stored values in the class state, but I don't think that's a good idea anymore.
in	*use_pvals*	Switch for whether to bypass the coordinate transformation and use physical parameters directly.

Definition at line 621 of file forcefield.py.

Here is the call graph for this function:

8.16.3.12 def forcebalance.forcefield.FF.make_redirect (*self, mvals*)

Definition at line 733 of file forcefield.py.

Here is the call graph for this function:

8.16.3.13 def forcebalance.forcefield.FF.mktransmat (*self*)

Create the transformation matrix to rescale and rotate the mathematical parameters.

For point charge parameters, project out perturbations that change the total charge.

First build these:

'qmap' : Just a list of parameter indices that point to charges.

'qid' : For each parameter in the qmap, a list of the affected atoms :) A potential target for the molecule-specific thang.

Then make this:

'qtrans2' : A transformation matrix that rotates the charge parameters. The first row is all zeros (because it corresponds to increasing the charge on all atoms) The other rows correspond to changing one of the parameters and decreasing all of the others equally such that the overall charge is preserved.

'qmat2' : An identity matrix with 'qtrans2' pasted into the right place

'transmat': 'qmat2' with rows and columns scaled using self.rs

'excision': Parameter indices that need to be 'cut out' because they are irrelevant and mess with the matrix diagonalization

Todo Only project out changes in total charge of a molecule, and perhaps generalize to fragments of molecules or other types of parameters.

The AMOEBA selection of charge depends not only on the atom type, but what that atom is bonded to.

Definition at line 947 of file forcefield.py.

8.16.3.14 def forcebalance.forcefield.FF.print_map (*self*, *vals* = `None`, *precision* = `4`)

Prints out the (physical or mathematical) parameter indices, IDs and values in a visually appealing way.

Definition at line 1109 of file forcefield.py.

Here is the call graph for this function:

8.16.3.15 def forcebalance.forcefield.FF.rsmake (*self*, *printfacs* = `True`)

Create the rescaling factors for the coordinate transformation in parameter space.

The proper choice of rescaling factors (read: prior widths in maximum likelihood analysis) is still a black art. This is a topic of current research.

Todo Pass in rsfactors through the input file

Parameters

in	*printfacs*	List for printing out the resecaling factors

Definition at line 871 of file forcefield.py.

Here is the call graph for this function:

8.16.3.16 def forcebalance.BaseClass.set_option (*self*, *in_dict*, *src_key*, *dest_key* = `None`, *val* = `None`, *default* = `None`, *forceprint* = `False`) `[inherited]`

Definition at line 32 of file __init__.py.

8.16.4 Member Data Documentation

8.16.4.1 forcebalance::forcefield.FF::atomnames

A list of atom names (this is new, for ESP fitting)

Definition at line 231 of file forcefield.py.

8.16.4.2 forcebalance::forcefield.FF::excision

Indices to exclude from optimization / Hessian inversion.

Some customized constraints here.

Quadrupoles must be traceless

Definition at line 227 of file forcefield.py.

8.16.4.3 forcebalance::forcefield.FF::FFAtomTypes

WORK IN PROGRESS ## This is a dictionary of {'AtomType':{'Mass' : float, 'Charge' : float, 'ParticleType' : string ('A', 'S', or 'D'), 'AtomicNumber' : int}}.

Definition at line 233 of file forcefield.py.

8.16.4.4 forcebalance::forcefield.FF::ffdata

As these options proliferate, the force field class becomes less standalone.

I need to think of a good solution here... The root directory of the project File names of force fields Directory containing force fields, relative to project directory Priors given by the user :) Whether to constrain the charges. Whether to constrain the charges. Switch for AMOEBA direct or mutual. Switch for rigid water molecules Bypass the transformation and use physical parameters directly The content of all force field files are stored in memory

Definition at line 216 of file forcefield.py.

8.16.4.5 forcebalance::forcefield.FF::ffdata_isxml

Definition at line 216 of file forcefield.py.

8.16.4.6 forcebalance::forcefield.FF::FFMolecules

Definition at line 233 of file forcefield.py.

8.16.4.7 forcebalance::forcefield.FF::linedestroy_save

Destruction dictionary (experimental).

Definition at line 240 of file forcefield.py.

8.16.4.8 forcebalance::forcefield.FF::linedestroy_this

Definition at line 240 of file forcefield.py.

8.16.4.9 forcebalance::forcefield.FF::map

The mapping of interaction type -> parameter number.

Definition at line 217 of file forcefield.py.

8.16.4.10 forcebalance::forcefield.FF::np

The total number of parameters.

Definition at line 228 of file forcefield.py.

8.16.4.11 forcebalance::forcefield.FF::openmmxml

Definition at line 395 of file forcefield.py.

8.16.4.12 forcebalance::forcefield.FF::parmdestroy_save

Definition at line 240 of file forcefield.py.

8.16.4.13 forcebalance::forcefield.FF::parmdestroy_this

Definition at line 240 of file forcefield.py.

8.16.4.14 forcebalance::forcefield.FF::patoms

A listing of parameter number -> atoms involved.

Definition at line 219 of file forcefield.py.

8.16.4.15 forcebalance::forcefield.FF::pfields

A list where pfields[pnum] = ['file',line,field,mult,cmd], basically a new way to modify force field files; when we modify the force field file, we go to the specific line/field in a given file and change the number.

Definition at line 223 of file forcefield.py.

8.16.4.16 forcebalance::forcefield.FF::plist

The listing of parameter number -> interaction types.

Definition at line 218 of file forcefield.py.

8.16.4.17 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.16.4.18 forcebalance::forcefield.FF::pvals0

Initial value of physical parameters.

Definition at line 229 of file forcefield.py.

8.16.4.19 forcebalance::forcefield.FF::qid

Definition at line 947 of file forcefield.py.

8.16.4.20 forcebalance::forcefield.FF::qid2

Definition at line 947 of file forcefield.py.

8.16.4.21 forcebalance::forcefield.FF::qmap

Definition at line 947 of file forcefield.py.

8.16.4.22 forcebalance::forcefield.FF::Readers

A dictionary of force field reader classes.

Definition at line 230 of file forcefield.py.

8.16.4.23 forcebalance::forcefield.FF::redirect

Creates plist from map.

Prints the plist to screen. Make the rescaling factors. Make the transformation matrix. Redirection dictionary (experi-

mental).

Definition at line 239 of file forcefield.py.

8.16.4.24 forcebalance::forcefield.FF::rs

List of rescaling factors.

Takes the dictionary 'BONDS':{3:'B', 4:'K'}, 'VDW':{4:'S', 5:'T'}, and turns it into a list of term types ['BONDSB','BOND-SK','VDWS','VDWT'].

The array of rescaling factors

Definition at line 224 of file forcefield.py.

8.16.4.25 forcebalance::forcefield.FF::tinkerprm

Definition at line 395 of file forcefield.py.

8.16.4.26 forcebalance::forcefield.FF::tm

The transformation matrix for mathematical -> physical parameters.

Definition at line 225 of file forcefield.py.

8.16.4.27 forcebalance::forcefield.FF::tml

The transpose of the transformation matrix.

Definition at line 226 of file forcefield.py.

8.16.4.28 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

The documentation for this class was generated from the following file:

- forcefield.py

8.17 forcebalance.output.ForceBalanceLogger Class Reference

This logger starts out with a default handler that writes to stdout addHandler removes this default the first time another handler is added.

Public Member Functions

- def __init__
- def addHandler
- def removeHandler

Public Attributes

- defaultHandler

8.17.1 Detailed Description

This logger starts out with a default handler that writes to stdout addHandler removes this default the first time another handler is added.

This is used for forcebalance package level logging, where a logger should always be present unless otherwise specified. To silence, add a NullHandler We also by default set the log level to INFO (logging.Logger starts at WARNING)

Definition at line 10 of file output.py.

8.17.2 Constructor & Destructor Documentation

8.17.2.1 def forcebalance.output.ForceBalanceLogger.__init__ (*self, name*)

Definition at line 11 of file output.py.

8.17.3 Member Function Documentation

8.17.3.1 def forcebalance.output.ForceBalanceLogger.addHandler (*self, hdlr*)

Definition at line 17 of file output.py.

Here is the call graph for this function:

8.17.3.2 def forcebalance.output.ForceBalanceLogger.removeHandler (*self, hdlr*)

Definition at line 23 of file output.py.

Here is the call graph for this function:

8.17.4 Member Data Documentation

8.17.4.1 forcebalance::output.ForceBalanceLogger::defaultHandler

Definition at line 11 of file output.py.

The documentation for this class was generated from the following file:

- output.py

8.18 forcebalance.amberio.FrcMod_Reader Class Reference

Finite state machine for parsing FrcMod force field file.

Inheritance diagram for forcebalance.amberio.FrcMod_Reader:

Collaboration diagram for forcebalance.amberio.FrcMod_Reader:

Public Member Functions

- def __init__
- def Split
- def Whites
- def feed
- def build_pid

  Returns the parameter type (e.g.

Public Attributes

- pdict

  The parameter dictionary (defined in this file)
- atom

The atom numbers in the interaction (stored in the parser)

- dihe

  Whether we're inside the dihedral section.

- adict

  The frcmod file never has any atoms in it.

- itype
- suffix
- ln
- molatom

  The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.

- Molecules
- AtomTypes

8.18.1 Detailed Description

Finite state machine for parsing FrcMod force field file.

Definition at line 99 of file amberio.py.

8.18.2 Constructor & Destructor Documentation

8.18.2.1 def forcebalance.amberio.FrcMod_Reader.__init__ (*self, fnm*)

Reimplemented from forcebalance.BaseReader.

Definition at line 101 of file amberio.py.

8.18.3 Member Function Documentation

8.18.3.1 def forcebalance.BaseReader.build_pid (*self, pfld*) [inherited]

Returns the parameter type (e.g.

K in BONDSK) based on the current interaction type.

Both the 'pdict' dictionary (see gmxio.pdict) and the interaction type 'state' (here, BONDS) are needed to get the parameter type.

If, however, 'pdict' does not contain the ptype value, a suitable substitute is simply the field number.

Note that if the interaction type state is not set, then it defaults to the file name, so a generic parameter ID is 'filename.-line_num.field_num'

Reimplemented in forcebalance.psi4io.Grid_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 107 of file __init__.py.

8.18.3.2 def forcebalance.amberio.FrcMod_Reader.feed (*self, line*)

Reimplemented from forcebalance.BaseReader.

Definition at line 119 of file amberio.py.

8.18.3.3 def forcebalance.amberio.FrcMod_Reader.Split (*self, line*)

Reimplemented from forcebalance.BaseReader.

Definition at line 113 of file amberio.py.

Here is the call graph for this function:

8.18.3.4 def forcebalance.amberio.FrcMod_Reader.Whites (*self, line*)

Reimplemented from forcebalance.BaseReader.

Definition at line 116 of file amberio.py.

Here is the call graph for this function:

8.18.4 Member Data Documentation

8.18.4.1 forcebalance::amberio.FrcMod_Reader::adict

The frcmod file never has any atoms in it.

Reimplemented from forcebalance.BaseReader.

Definition at line 105 of file amberio.py.

8.18.4.2 forcebalance::amberio.FrcMod_Reader::atom

The atom numbers in the interaction (stored in the parser)

Definition at line 103 of file amberio.py.

8.18.4.3 forcebalance.BaseReader::AtomTypes [inherited]

Definition at line 71 of file __init__.py.

8.18.4.4 forcebalance::amberio.FrcMod_Reader::dihe

Whether we're inside the dihedral section.

Definition at line 104 of file amberio.py.

8.18.4.5 forcebalance::amberio.FrcMod_Reader::itype

Reimplemented from forcebalance.BaseReader.

Definition at line 119 of file amberio.py.

8.18.4.6 forcebalance.BaseReader::ln [inherited]

Definition at line 66 of file __init__.py.

8.18.4.7 forcebalance.BaseReader::molatom [inherited]

The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.

self.moleculedict = OrderedDict() The listing of 'RES:ATOMNAMES' for atom names in the line This is obviously a placeholder.

Reimplemented in forcebalance.gmxio.ITP_Reader, and forcebalance.amberio.Mol2_Reader.

Definition at line 71 of file __init__.py.

8.18.4.8 forcebalance.BaseReader::Molecules [inherited]

Definition at line 71 of file __init__.py.

8.18.4.9 forcebalance::amberio.FrcMod_Reader::pdict

The parameter dictionary (defined in this file)

Reimplemented from forcebalance.BaseReader.

Definition at line 102 of file amberio.py.

8.18.4.10 forcebalance::amberio.FrcMod_Reader::suffix

Reimplemented from forcebalance.BaseReader.

Definition at line 119 of file amberio.py.

The documentation for this class was generated from the following file:

- amberio.py

8.19 forcebalance.psi4io.GBS_Reader Class Reference

Interaction type -> Parameter Dictionary.

Inheritance diagram for forcebalance.psi4io.GBS_Reader:

Collaboration diagram for forcebalance.psi4io.GBS_Reader:

Public Member Functions

- def __init__
- def build_pid

  Returns the parameter type (e.g.
- def feed

  Feed in a line.
- def Split
- def Whites
- def feed

Public Attributes

- element
- amom
- last_amom
- basis_number
- contraction_number
- adict

  The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.
- isdata
- destroy
- ln
- itype
- suffix
- pdict
- molatom

  The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.
- Molecules
- AtomTypes

8.19.1 Detailed Description

Interaction type -> Parameter Dictionary.

pdict = {'Exponent':{0:'A', 1:'C'}, 'BASSP' :{0:'A', 1:'B', 2:'C'} } Finite state machine for parsing basis set files.

Definition at line 35 of file psi4io.py.

8.19.2 Constructor & Destructor Documentation

8.19.2.1 def forcebalance.psi4io.GBS_Reader.__init__ (*self, fnm* = `None`)

Reimplemented from forcebalance.BaseReader.

Definition at line 37 of file psi4io.py.

8.19.3 Member Function Documentation

8.19.3.1 def forcebalance.psi4io.GBS_Reader.build_pid (*self, pfld*)

Returns the parameter type (e.g.

K in BONDSK) based on the current interaction type.

Both the 'pdict' dictionary (see gmxio.pdict) and the interaction type 'state' (here, BONDS) are needed to get the parameter type.

If, however, 'pdict' does not contain the ptype value, a suitable substitute is simply the field number.

Note that if the interaction type state is not set, then it defaults to the file name, so a generic parameter ID is 'filename.-line_num.field_num'

Reimplemented from forcebalance.BaseReader.

Definition at line 48 of file psi4io.py.

Here is the call graph for this function:

8.19.3.2 def forcebalance.psi4io.GBS_Reader.feed (*self, line, linindep* = `False`)

Feed in a line.

Parameters

in	*line*	The line of data

Definition at line 61 of file psi4io.py.

Here is the call graph for this function:

8.19.3.3 def forcebalance.BaseReader.feed (*self, line*) [inherited]

Reimplemented in forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.QCIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 88 of file __init__.py.

Here is the call graph for this function:

8.19.3.4 def forcebalance.BaseReader.Split (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 82 of file __init__.py.

Here is the call graph for this function:

8.19.3.5 def forcebalance.BaseReader.Whites (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 85 of file __init__.py.

Here is the call graph for this function:

8.19.4 Member Data Documentation

8.19.4.1 forcebalance::psi4io.GBS_Reader::adict

The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.

Reimplemented from forcebalance.BaseReader.

Definition at line 37 of file psi4io.py.

8.19.4.2 forcebalance::psi4io.GBS_Reader::amom

Definition at line 37 of file psi4io.py.

8.19.4.3 forcebalance.BaseReader::AtomTypes [inherited]

Definition at line 71 of file __init__.py.

8.19.4.4 forcebalance::psi4io.GBS_Reader::basis_number

Definition at line 37 of file psi4io.py.

8.19.4.5 forcebalance::psi4io.GBS_Reader::contraction_number

Definition at line 37 of file psi4io.py.

8.19.4.6 forcebalance::psi4io.GBS_Reader::destroy

Definition at line 37 of file psi4io.py.

8.19.4.7 forcebalance::psi4io.GBS_Reader::element

Definition at line 37 of file psi4io.py.

8.19.4.8 forcebalance::psi4io.GBS_Reader::isdata

Definition at line 37 of file psi4io.py.

8.19.4.9 forcebalance.BaseReader::itype [inherited]

Reimplemented in forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.QCIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 66 of file __init__.py.

8.19.4.10 forcebalance::psi4io.GBS_Reader::last_amom

Definition at line 37 of file psi4io.py.

8.19.4.11 forcebalance.BaseReader::ln [inherited]

Definition at line 66 of file __init__.py.

8.19.4.12 forcebalance.BaseReader::molatom [inherited]

The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.

self.moleculedict = OrderedDict() The listing of 'RES:ATOMNAMES' for atom names in the line This is obviously a placeholder.

Reimplemented in forcebalance.gmxio.ITP_Reader, and forcebalance.amberio.Mol2_Reader.

Definition at line 71 of file __init__.py.

8.19.4.13 forcebalance.BaseReader::Molecules [inherited]

Definition at line 71 of file __init__.py.

8.19.4.14 forcebalance.BaseReader::pdict [inherited]

Reimplemented in forcebalance.openmmio.OpenMM_Reader, forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.QCIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 66 of file __init__.py.

8.19.4.15 forcebalance.BaseReader::suffix [inherited]

Reimplemented in forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.QCIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 66 of file __init__.py.

The documentation for this class was generated from the following file:

- psi4io.py

8.20 forcebalance.custom_io.Gen_Reader Class Reference

Finite state machine for parsing custom GROMACS force field files.

Inheritance diagram for forcebalance.custom_io.Gen_Reader:

Collaboration diagram for forcebalance.custom_io.Gen_Reader:

Public Member Functions

- def __init__
- def feed

  Feed in a line.
- def Split
- def Whites
- def build_pid

  Returns the parameter type (e.g.

Public Attributes

- sec

  The current section that we're in.
- pdict

  The parameter dictionary (defined in this file)
- itype

- suffix
- ln
- adict

  The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.
- molatom

  The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.
- Molecules
- AtomTypes

8.20.1 Detailed Description

Finite state machine for parsing custom GROMACS force field files.

This class is instantiated when we begin to read in a file. The feed(line) method updates the state of the machine, giving it information like the residue we're currently on, the nonbonded interaction type, and the section that we're in. Using this information we can look up the interaction type and parameter type for building the parameter ID.

Definition at line 41 of file custom_io.py.

8.20.2 Constructor & Destructor Documentation

8.20.2.1 def forcebalance.custom_io.Gen_Reader.__init__ (*self, fnm*)

Reimplemented from forcebalance.BaseReader.

Definition at line 43 of file custom_io.py.

8.20.3 Member Function Documentation

8.20.3.1 def forcebalance.BaseReader.build_pid (*self, pfld*) [inherited]

Returns the parameter type (e.g.

K in BONDSK) based on the current interaction type.

Both the 'pdict' dictionary (see gmxio.pdict) and the interaction type 'state' (here, BONDS) are needed to get the parameter type.

If, however, 'pdict' does not contain the ptype value, a suitable substitute is simply the field number.

Note that if the interaction type state is not set, then it defaults to the file name, so a generic parameter ID is 'filename.-line_num.field_num'

Reimplemented in forcebalance.psi4io.Grid_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 107 of file __init__.py.

8.20.3.2 def forcebalance.custom_io.Gen_Reader.feed (*self, line*)

Feed in a line.

Parameters

in	*line*	The line of data

Reimplemented from forcebalance.BaseReader.

Definition at line 57 of file custom_io.py.

8.20.3.3 def forcebalance.BaseReader.Split (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 82 of file __init__.py.

Here is the call graph for this function:

8.20.3.4 def forcebalance.BaseReader.Whites (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 85 of file __init__.py.

Here is the call graph for this function:

8.20.4 Member Data Documentation

8.20.4.1 forcebalance.BaseReader::adict [inherited]

The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.

Reimplemented in forcebalance.amberio.FrcMod_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 67 of file __init__.py.

8.20.4.2 forcebalance.BaseReader::AtomTypes [inherited]

Definition at line 71 of file __init__.py.

8.20.4.3 forcebalance::custom_io.Gen_Reader::itype

Reimplemented from forcebalance.BaseReader.

Definition at line 57 of file custom_io.py.

8.20.4.4 forcebalance.BaseReader::ln [inherited]

Definition at line 66 of file __init__.py.

8.20.4.5 forcebalance.BaseReader::molatom [inherited]

The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.

self.moleculedict = OrderedDict() The listing of 'RES:ATOMNAMES' for atom names in the line This is obviously a placeholder.

Reimplemented in forcebalance.gmxio.ITP_Reader, and forcebalance.amberio.Mol2_Reader.

Definition at line 71 of file __init__.py.

8.20.4.6 forcebalance.BaseReader::Molecules [inherited]

Definition at line 71 of file __init__.py.

8.20.4.7 forcebalance::custom_io.Gen_Reader::pdict

The parameter dictionary (defined in this file)

Reimplemented from forcebalance.BaseReader.

Definition at line 45 of file custom_io.py.

8.20.4.8 forcebalance::custom_io.Gen_Reader::sec

The current section that we're in.

Definition at line 44 of file custom_io.py.

8.20.4.9 forcebalance::custom_io.Gen_Reader::suffix

Reimplemented from forcebalance.BaseReader.

Definition at line 57 of file custom_io.py.

The documentation for this class was generated from the following file:

- custom_io.py

8.21 forcebalance.gmxio.GMX Class Reference

Derived from Engine object for carrying out general purpose GROMACS calculations.

Inheritance diagram for forcebalance.gmxio.GMX:

Collaboration diagram for forcebalance.gmxio.GMX:

Public Member Functions

- def __init__
- def callgmx

  Call GROMACS; prepend the gmxpath to the call to the GROMACS program.
- def prepare

  Prepare the calculation.
- def energy_force_driver

  Computes the energy and force using GROMACS for a single snapshot.

- def energy_force_driver_all

  Computes the energy and force using GROMACS over a trajectory.
- def generate_vsite_positions
- def prepare
- def evaluate_snapshots

  Evaluate properties over a collection of snapshots.
- def evaluate_optimized

  Evaluate properties on the optimized geometry.
- def set_option

Public Attributes

- gmxsuffix

  Disable some optimizations.
- gmxpath

  The directory containing GROMACS executables (e.g.
- srcdir

  Attempt to determine file names of .gro, .top, and .mdp files.
- top
- mdp
- mol
- AtomMask

  First move into the temp directory if specified by the input arguments.
- AtomLists
- name
- target
- root
- PrintOptionDict
- verbose_options

8.21.1 Detailed Description

Derived from Engine object for carrying out general purpose GROMACS calculations.

Definition at line 461 of file gmxio.py.

8.21.2 Constructor & Destructor Documentation

8.21.2.1 def forcebalance.gmxio.GMX.__init__ (*self*, *name* = "gmx", *kwargs*)

Reimplemented from forcebalance.engine.Engine.

Definition at line 462 of file gmxio.py.

8.21.3 Member Function Documentation

8.21.3.1 def forcebalance.gmxio.GMX.callgmx (*self, command, stdin* = `None`, *print_to_screen* = `False`, *print_command* = `False`, *kwargs*)

Call GROMACS; prepend the gmxpath to the call to the GROMACS program.

Definition at line 511 of file gmxio.py.

Here is the call graph for this function:

8.21.3.2 def forcebalance.gmxio.GMX.energy_force_driver (*self, shot*)

Computes the energy and force using GROMACS for a single snapshot.

Definition at line 583 of file gmxio.py.

Here is the call graph for this function:

8.21.3.3 def forcebalance.gmxio.GMX.energy_force_driver_all (*self*)

Computes the energy and force using GROMACS over a trajectory.

Definition at line 605 of file gmxio.py.

Here is the call graph for this function:

8.21.3.4 def forcebalance.engine.Engine.evaluate_optimized (*self, M*) `[inherited]`

Evaluate properties on the optimized geometry.

Definition at line 86 of file engine.py.

8.21.3.5 def forcebalance.engine.Engine.evaluate_snapshots (*self, M*) `[inherited]`

Evaluate properties over a collection of snapshots.

Definition at line 80 of file engine.py.

Here is the call graph for this function:

8.21.3.6 def forcebalance.gmxio.GMX.generate_vsite_positions (*self*)

Definition at line 627 of file gmxio.py.

Here is the call graph for this function:

8.21.3.7 def forcebalance.engine.Engine.prepare ( ) [inherited]

Definition at line 74 of file engine.py.

Here is the call graph for this function:

8.21.3.8 def forcebalance.gmxio.GMX.prepare (*self*)

Prepare the calculation.

Write conformation to the temporary directory. Read the topology.

Definition at line 523 of file gmxio.py.

Here is the call graph for this function:

8.21.3.9 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.21.4 Member Data Documentation

8.21.4.1 forcebalance::gmxio.GMX::AtomLists

Definition at line 527 of file gmxio.py.

8.21.4.2 forcebalance::gmxio.GMX::AtomMask

First move into the temp directory if specified by the input arguments.

Link files into the temp directory because it's good for reproducibility. Write the appropriate coordinate files. Call grompp followed by gmxdump to read the trajectory

Definition at line 527 of file gmxio.py.

8.21.4.3 forcebalance::gmxio.GMX::gmxpath

The directory containing GROMACS executables (e.g.

mdrun)

Definition at line 465 of file gmxio.py.

8.21.4.4 forcebalance::gmxio.GMX::gmxsuffix

Disable some optimizations.

The suffix to GROMACS executables, e.g. '_d' for double precision.

Definition at line 464 of file gmxio.py.

8.21.4.5 forcebalance::gmxio.GMX::mdp

Definition at line 466 of file gmxio.py.

8.21.4.6 forcebalance::gmxio.GMX::mol

Definition at line 466 of file gmxio.py.

8.21.4.7 forcebalance::engine.Engine::name [inherited]

Definition at line 63 of file engine.py.

8.21.4.8 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.21.4.9 forcebalance::engine.Engine::root [inherited]

Definition at line 63 of file engine.py.

8.21.4.10 forcebalance::gmxio.GMX::srcdir

Attempt to determine file names of .gro, .top, and .mdp files.

Definition at line 466 of file gmxio.py.

8.21.4.11 forcebalance::engine.Engine::target [inherited]

Definition at line 63 of file engine.py.

8.21.4.12 forcebalance::gmxio.GMX::top

Definition at line 466 of file gmxio.py.

8.21.4.13 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

The documentation for this class was generated from the following file:

- gmxio.py

8.22 forcebalance.psi4io.Grid_Reader Class Reference

Finite state machine for parsing DVR grid files.

Inheritance diagram for forcebalance.psi4io.Grid_Reader:

Collaboration diagram for forcebalance.psi4io.Grid_Reader:

Public Member Functions

- def __init__
- def build_pid

  Returns the parameter type (e.g.
- def feed

  Feed in a line.
- def Split
- def Whites
- def feed

Public Attributes

- element
- point
- radii
- isdata
- ln
- itype
- suffix
- pdict
- adict

  The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.
- molatom

  The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.
- Molecules
- AtomTypes

8.22.1 Detailed Description

Finite state machine for parsing DVR grid files.

Definition at line 247 of file psi4io.py.

8.22.2 Constructor & Destructor Documentation

8.22.2.1 def forcebalance.psi4io.Grid_Reader.__init__ (*self, fnm* = `None`)

Reimplemented from forcebalance.BaseReader.

Definition at line 249 of file psi4io.py.

8.22.3 Member Function Documentation

8.22.3.1 def forcebalance.psi4io.Grid_Reader.build_pid (*self, pfld*)

Returns the parameter type (e.g.

K in BONDSK) based on the current interaction type.

Both the 'pdict' dictionary (see gmxio.pdict) and the interaction type 'state' (here, BONDS) are needed to get the parameter type.

If, however, 'pdict' does not contain the ptype value, a suitable substitute is simply the field number.

Note that if the interaction type state is not set, then it defaults to the file name, so a generic parameter ID is 'filename.-line_num.field_num'

Reimplemented from forcebalance.BaseReader.

Definition at line 255 of file psi4io.py.

Here is the call graph for this function:

8.22.3.2 def forcebalance.BaseReader.feed (*self, line*) [inherited]

Reimplemented in forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.-Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.Q-CIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 88 of file __init__.py.

Here is the call graph for this function:

8.22.3.3 def forcebalance.psi4io.Grid_Reader.feed (*self, line, linindep* = `False`)

Feed in a line.

Parameters

in	*line*	The line of data

Definition at line 270 of file psi4io.py.

8.22.3.4 def forcebalance.BaseReader.Split (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 82 of file __init__.py.

Here is the call graph for this function:

8.22.3.5 def forcebalance.BaseReader.Whites (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 85 of file __init__.py.

Here is the call graph for this function:

8.22.4 Member Data Documentation

8.22.4.1 forcebalance.BaseReader::adict [inherited]

The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.

Reimplemented in forcebalance.amberio.FrcMod_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 67 of file __init__.py.

8.22.4.2 forcebalance.BaseReader::AtomTypes [inherited]

Definition at line 71 of file __init__.py.

8.22.4.3 forcebalance::psi4io.Grid_Reader::element

Definition at line 249 of file psi4io.py.

8.22.4.4 forcebalance::psi4io.Grid_Reader::isdata

Definition at line 270 of file psi4io.py.

8.22.4.5 forcebalance.BaseReader::itype [inherited]

Reimplemented in forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.QCIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 66 of file __init__.py.

8.22.4.6 forcebalance.BaseReader::ln [inherited]

Definition at line 66 of file __init__.py.

8.22.4.7 forcebalance.BaseReader::molatom [inherited]

The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.

self.moleculedict = OrderedDict() The listing of 'RES:ATOMNAMES' for atom names in the line This is obviously a placeholder.

Reimplemented in forcebalance.gmxio.ITP_Reader, and forcebalance.amberio.Mol2_Reader.

Definition at line 71 of file __init__.py.

8.22.4.8 forcebalance.BaseReader::Molecules [inherited]

Definition at line 71 of file __init__.py.

8.22.4.9 forcebalance.BaseReader::pdict [inherited]

Reimplemented in forcebalance.openmmio.OpenMM_Reader, forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.QCIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 66 of file __init__.py.

8.22.4.10 forcebalance::psi4io.Grid_Reader::point

Definition at line 249 of file psi4io.py.

8.22.4.11 forcebalance::psi4io.Grid_Reader::radii

Definition at line 249 of file psi4io.py.

8.22.4.12 forcebalance.BaseReader::suffix [inherited]

Reimplemented in forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.QCIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 66 of file __init__.py.

The documentation for this class was generated from the following file:

- psi4io.py

8.23 forcebalance.interaction.Interaction Class Reference

Subclass of Target for fitting force fields to interaction energies.

Inheritance diagram for forcebalance.interaction.Interaction:

Collaboration diagram for forcebalance.interaction.Interaction:

Public Member Functions

- def __init__

  All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)
- def read_reference_data

  Read the reference ab initio data from a file such as qdata.txt.
- def prepare_temp_directory

  Prepare the temporary directory, by default does nothing.
- def indicate
- def get

  Evaluate objective function.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.

- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- select1

  Number of snapshots.
- select2

  Set fragment 2.
- eqm

  Set upper cutoff energy.
- label

  Snapshot label, useful for graphing.
- qfnm

  The qdata.txt file that contains the QM energies and forces.
- e_err

  Qualitative Indicator: average energy error (in kJ/mol)
- e_err_pct
- ns

  Read in the trajectory file.
- traj
- divisor

  Read in the reference data.
- prefactor
- weight
- emm
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.23.1 Detailed Description

Subclass of Target for fitting force fields to interaction energies.

Currently TINKER is supported.

We introduce the following concepts:

- The number of snapshots
- The reference interaction energies and the file they belong in (qdata.txt)

This subclass contains the 'get' method for building the objective function from any simulation software (a driver to run the program and read output is still required).

Definition at line 35 of file interaction.py.

8.23.2 Constructor & Destructor Documentation

8.23.2.1 def forcebalance.interaction.Interaction.__init__ (*self, options, tgt_opts, forcefield*)

All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)

If we want to add attributes that are more specific (i.e. a set of reference forces for force matching), they are added in the subclass AbInitio that inherits from Target.

Reimplemented from forcebalance.target.Target.

Reimplemented in forcebalance.gmxio.Interaction_GMX, forcebalance.tinkerio.Interaction_TINKER, and forcebalance.openmmio.Interaction_OpenMM.

Definition at line 38 of file interaction.py.

8.23.3 Member Function Documentation

8.23.3.1 def forcebalance.interaction.Interaction.get (*self, mvals, AGrad* = `False`, *AHess* = `False`)

Evaluate objective function.

Reimplemented from forcebalance.target.Target.

Definition at line 163 of file interaction.py.

8.23.3.2 def forcebalance.target.Target.get_G (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.23.3.3 def forcebalance.target.Target.get_H (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.23.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) `[inherited]`

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.23.3.5 def forcebalance.interaction.Interaction.indicate (*self*)

Definition at line 147 of file interaction.py.

Here is the call graph for this function:

8.23.3.6 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.23.3.7 def forcebalance.interaction.Interaction.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory, by default does nothing.

Reimplemented in forcebalance.gmxio.Interaction_GMX, forcebalance.tinkerio.Interaction_TINKER, and forcebalance.openmmio.Interaction_OpenMM.

Definition at line 144 of file interaction.py.

8.23.3.8 def forcebalance.target.Target.printcool_table (*self, data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) [inherited]

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.23.3.9 def forcebalance.interaction.Interaction.read_reference_data (*self*)

Read the reference ab initio data from a file such as qdata.txt.

After reading in the information from qdata.txt, it is converted into the GROMACS/OpenMM units (kJ/mol for energy, kJ/mol/nm force).

Definition at line 125 of file interaction.py.

Here is the call graph for this function:

8.23.3.10 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.23.3.11 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.23.3.12 def forcebalance.target.Target.sget (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.23.3.13 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.23.3.14 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.23.3.15 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.23.4 Member Data Documentation

8.23.4.1 forcebalance::interaction.Interaction::divisor

Read in the reference data.

Prepare the temporary directory

Definition at line 53 of file interaction.py.

8.23.4.2 forcebalance::interaction.Interaction::e_err

Qualitative Indicator: average energy error (in kJ/mol)

Definition at line 50 of file interaction.py.

8.23.4.3 forcebalance::interaction.Interaction::e_err_pct

Definition at line 50 of file interaction.py.

8.23.4.4 forcebalance::interaction.Interaction::emm

Definition at line 163 of file interaction.py.

8.23.4.5 forcebalance::interaction.Interaction::eqm

Set upper cutoff energy.

Reference (QM) interaction energies

Definition at line 47 of file interaction.py.

8.23.4.6 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.23.4.7 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.23.4.8 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.23.4.9 forcebalance::interaction.Interaction::label

Snapshot label, useful for graphing.

Definition at line 48 of file interaction.py.

8.23.4.10 forcebalance::interaction.Interaction::ns

Read in the trajectory file.

Definition at line 51 of file interaction.py.

8.23.4.11 forcebalance::interaction.Interaction::objective

Definition at line 163 of file interaction.py.

8.23.4.12 forcebalance::interaction.Interaction::prefactor

Definition at line 53 of file interaction.py.

8.23.4.13 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.23.4.14 forcebalance::interaction.Interaction::qfnm

The qdata.txt file that contains the QM energies and forces.

Definition at line 49 of file interaction.py.

8.23.4.15 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.23.4.16 forcebalance::interaction.Interaction::select1

Number of snapshots.

Do we call Q-Chem for dielectric energies? (Currently needs to be fixed) Do we put the reference energy into the denominator? Do we put the reference energy into the denominator? What is the energy denominator? Set fragment 1

Definition at line 44 of file interaction.py.

8.23.4.17 forcebalance::interaction.Interaction::select2

Set fragment 2.

Definition at line 45 of file interaction.py.

8.23.4.18 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.23.4.19 forcebalance::interaction.Interaction::traj

Definition at line 51 of file interaction.py.

8.23.4.20 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.23.4.21 forcebalance::interaction.Interaction::weight

Definition at line 163 of file interaction.py.

8.23.4.22 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- interaction.py

8.24 forcebalance.gmxio.Interaction_GMX Class Reference

Subclass of Interaction for interaction energy matching using GROMACS.

Inheritance diagram for forcebalance.gmxio.Interaction_GMX:

Collaboration diagram for forcebalance.gmxio.Interaction_GMX:

Public Member Functions

- def __init__

  All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)
- def prepare_temp_directory

  Prepare the temporary directory, by default does nothing.
- def interaction_driver

  Computes the energy and force using GROMACS for a single snapshot.
- def interaction_driver_all

  Computes the energy and force using GROMACS for a trajectory.
- def read_reference_data

  Read the reference ab initio data from a file such as qdata.txt.
- def indicate
- def get

  Evaluate objective function.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- trajfnm

  Name of the trajectory.
- topfnm
- Dielectric
- Diel_B
- select1

  Number of snapshots.
- select2

  Set fragment 2.
- eqm

Set upper cutoff energy.

- label

  Snapshot label, useful for graphing.
- qfnm

  The qdata.txt file that contains the QM energies and forces.
- e_err

  Qualitative Indicator: average energy error (in kJ/mol)
- e_err_pct
- ns

  Read in the trajectory file.
- traj
- divisor

  Read in the reference data.
- prefactor
- weight
- emm
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.24.1 Detailed Description

Subclass of Interaction for interaction energy matching using GROMACS.

Definition at line 732 of file gmxio.py.

8.24.2 Constructor & Destructor Documentation

8.24.2.1 def forcebalance.gmxio.Interaction_GMX.__init__ (*self, options, tgt_opts, forcefield*)

All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)

If we want to add attributes that are more specific (i.e. a set of reference forces for force matching), they are added in the subclass AbInitio that inherits from Target.

Reimplemented from forcebalance.interaction.Interaction.

Definition at line 734 of file gmxio.py.

Here is the call graph for this function:

8.24.3 Member Function Documentation

8.24.3.1 def forcebalance.interaction.Interaction.get (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

Evaluate objective function.

Reimplemented from forcebalance.target.Target.

Definition at line 163 of file interaction.py.

8.24.3.2 def forcebalance.target.Target.get_G (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.24.3.3 def forcebalance.target.Target.get_H (*self, mvals =* None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.24.3.4 def forcebalance.target.Target.get_X (*self, mvals =* None) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.24.3.5 def forcebalance.interaction.Interaction.indicate (*self*) [inherited]

Definition at line 147 of file interaction.py.

Here is the call graph for this function:

8.24.3.6 def forcebalance.gmxio.Interaction_GMX.interaction_driver (*self, shot*)

Computes the energy and force using GROMACS for a single snapshot.

This does not require GROMACS-X2.

Definition at line 765 of file gmxio.py.

8.24.3.7 def forcebalance.gmxio.Interaction_GMX.interaction_driver_all (*self, dielectric* = `False`)

Computes the energy and force using GROMACS for a trajectory.

This does not require GROMACS-X2.

Definition at line 770 of file gmxio.py.

Here is the call graph for this function:

8.24.3.8 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.24.3.9 def forcebalance.gmxio.Interaction_GMX.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory, by default does nothing.

Reimplemented from forcebalance.interaction.Interaction.

Definition at line 742 of file gmxio.py.

Here is the call graph for this function:

8.24.3.10 def forcebalance.target.Target.printcool_table (*self, data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) [inherited]

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.24.3.11 def forcebalance.interaction.Interaction.read_reference_data (*self*) [inherited]

Read the reference ab initio data from a file such as qdata.txt.

After reading in the information from qdata.txt, it is converted into the GROMACS/OpenMM units (kJ/mol for energy, kJ/mol/nm force).

Definition at line 125 of file interaction.py.

Here is the call graph for this function:

8.24.3.12 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.24.3.13 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.24.3.14 def forcebalance.target.Target.sget (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.24.3.15 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.24.3.16 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.24.3.17 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.24.4 Member Data Documentation

8.24.4.1 forcebalance::gmxio.Interaction_GMX::Diel_B

Definition at line 770 of file gmxio.py.

8.24.4.2 forcebalance::gmxio.Interaction_GMX::Dielectric

Definition at line 735 of file gmxio.py.

8.24.4.3 forcebalance::interaction.Interaction::divisor [inherited]

Read in the reference data.

Prepare the temporary directory

Definition at line 53 of file interaction.py.

8.24.4.4 forcebalance::interaction.Interaction::e_err [inherited]

Qualitative Indicator: average energy error (in kJ/mol)

Definition at line 50 of file interaction.py.

8.24.4.5 forcebalance::interaction.Interaction::e_err_pct [inherited]

Definition at line 50 of file interaction.py.

8.24.4.6 forcebalance::interaction.Interaction::emm [inherited]

Definition at line 163 of file interaction.py.

8.24.4.7 forcebalance::interaction.Interaction::eqm [inherited]

Set upper cutoff energy.

Reference (QM) interaction energies

Definition at line 47 of file interaction.py.

8.24.4.8 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.24.4.9 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.24.4.10 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.24.4.11 forcebalance::interaction.Interaction::label [inherited]

Snapshot label, useful for graphing.

Definition at line 48 of file interaction.py.

8.24.4.12 forcebalance::interaction.Interaction::ns [inherited]

Read in the trajectory file.

Definition at line 51 of file interaction.py.

8.24.4.13 forcebalance::interaction.Interaction::objective [inherited]

Definition at line 163 of file interaction.py.

8.24.4.14 forcebalance::interaction.Interaction::prefactor [inherited]

Definition at line 53 of file interaction.py.

8.24.4.15 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.24.4.16 forcebalance::interaction.Interaction::qfnm [inherited]

The qdata.txt file that contains the QM energies and forces.

Definition at line 49 of file interaction.py.

8.24.4.17 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.24.4.18 forcebalance::interaction.Interaction::select1 [inherited]

Number of snapshots.

Do we call Q-Chem for dielectric energies? (Currently needs to be fixed) Do we put the reference energy into the denominator? Do we put the reference energy into the denominator? What is the energy denominator? Set fragment 1

Definition at line 44 of file interaction.py.

8.24.4.19 forcebalance::interaction.Interaction::select2 [inherited]

Set fragment 2.

Definition at line 45 of file interaction.py.

8.24.4.20 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.24.4.21 forcebalance::gmxio.Interaction_GMX::topfnm

Definition at line 735 of file gmxio.py.

8.24.4.22 forcebalance::interaction.Interaction::traj [inherited]

Definition at line 51 of file interaction.py.

8.24.4.23 forcebalance::gmxio.Interaction_GMX::trajfnm

Name of the trajectory.

Definition at line 735 of file gmxio.py.

8.24.4.24 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.24.4.25 forcebalance::interaction.Interaction::weight [inherited]

Definition at line 163 of file interaction.py.

8.24.4.26 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- gmxio.py

8.25 forcebalance.openmmio.Interaction_OpenMM Class Reference

Subclass of Target for interaction matching using OpenMM.

Inheritance diagram for forcebalance.openmmio.Interaction_OpenMM:

Collaboration diagram for forcebalance.openmmio.Interaction_OpenMM:

Public Member Functions

- def __init__

  All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)
- def prepare_temp_directory

  Prepare the temporary directory, by default does nothing.
- def energy_driver_all
- def interaction_driver_all
- def read_reference_data

  Read the reference ab initio data from a file such as qdata.txt.
- def indicate
- def get

  Evaluate objective function.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- trajfnm

  Name of the trajectory file containing snapshots.
- simulations

  Dictionary of simulation objects (dimer, fraga, fragb)
- platform

  Set up three OpenMM System objects.
- select1

  Number of snapshots.
- select2

  Set fragment 2.
- eqm

  Set upper cutoff energy.

- label

  Snapshot label, useful for graphing.
- qfnm

  The qdata.txt file that contains the QM energies and forces.
- e_err

  Qualitative Indicator: average energy error (in kJ/mol)
- e_err_pct
- ns

  Read in the trajectory file.
- traj
- divisor

  Read in the reference data.
- prefactor
- weight
- emm
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.25.1 Detailed Description

Subclass of Target for interaction matching using OpenMM.

Definition at line 560 of file openmmio.py.

8.25.2 Constructor & Destructor Documentation

8.25.2.1 def forcebalance.openmmio.Interaction_OpenMM.__init__ (*self, options, tgt_opts, forcefield*)

All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)

If we want to add attributes that are more specific (i.e. a set of reference forces for force matching), they are added in the subclass AbInitio that inherits from Target.

Reimplemented from forcebalance.interaction.Interaction.

Definition at line 563 of file openmmio.py.

8.25.3 Member Function Documentation

8.25.3.1 def forcebalance.openmmio.Interaction_OpenMM.energy_driver_all (*self, mode*)

Definition at line 625 of file openmmio.py.

Here is the call graph for this function:

8.25.3.2 def forcebalance.interaction.Interaction.get (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

Evaluate objective function.

Reimplemented from forcebalance.target.Target.

Definition at line 163 of file interaction.py.

8.25.3.3 def forcebalance.target.Target.get_G (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.25.3.4 def forcebalance.target.Target.get_H (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.25.3.5 def forcebalance.target.Target.get_X (*self*, *mvals* = None) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.25.3.6 def forcebalance.interaction.Interaction.indicate (*self*) [inherited]

Definition at line 147 of file interaction.py.

Here is the call graph for this function:

8.25.3.7 def forcebalance.openmmio.Interaction_OpenMM.interaction_driver_all (*self, dielectric* = `False`)

Definition at line 679 of file openmmio.py.

8.25.3.8 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.25.3.9 def forcebalance.openmmio.Interaction_OpenMM.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory, by default does nothing.

Reimplemented from forcebalance.interaction.Interaction.

Definition at line 571 of file openmmio.py.

8.25.3.10 def forcebalance.target.Target.printcool_table (*self*, *data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.25.3.11 def forcebalance.interaction.Interaction.read_reference_data (*self*) `[inherited]`

Read the reference ab initio data from a file such as qdata.txt.

After reading in the information from qdata.txt, it is converted into the GROMACS/OpenMM units (kJ/mol for energy, kJ/mol/nm force).

Definition at line 125 of file interaction.py.

Here is the call graph for this function:

8.25.3.12 def forcebalance.target.Target.refresh_temp_directory (*self*) `[inherited]`

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.25.3.13 def forcebalance.BaseClass.set_option (*self*, *in_dict*, *src_key*, *dest_key* = `None`, *val* = `None`, *default* = `None`, *forceprint* = `False`) [inherited]

Definition at line 32 of file __init__.py.

8.25.3.14 def forcebalance.target.Target.sget (*self*, *mvals*, *AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.25.3.15 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.25.3.16 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.25.3.17 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.25.4 Member Data Documentation

8.25.4.1 forcebalance::interaction.Interaction::divisor [inherited]

Read in the reference data.

Prepare the temporary directory

Definition at line 53 of file interaction.py.

8.25.4.2 forcebalance::interaction.Interaction::e_err [inherited]

Qualitative Indicator: average energy error (in kJ/mol)

Definition at line 50 of file interaction.py.

8.25.4.3 forcebalance::interaction.Interaction::e_err_pct [inherited]

Definition at line 50 of file interaction.py.

8.25.4.4 forcebalance::interaction.Interaction::emm [inherited]

Definition at line 163 of file interaction.py.

8.25.4.5 forcebalance::interaction.Interaction::eqm [inherited]

Set upper cutoff energy.

Reference (QM) interaction energies

Definition at line 47 of file interaction.py.

8.25.4.6 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.25.4.7 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.25.4.8 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.25.4.9 forcebalance::interaction.Interaction::label [inherited]

Snapshot label, useful for graphing.

Definition at line 48 of file interaction.py.

8.25.4.10 forcebalance::interaction.Interaction::ns [inherited]

Read in the trajectory file.

Definition at line 51 of file interaction.py.

8.25.4.11 forcebalance::interaction.Interaction::objective [inherited]

Definition at line 163 of file interaction.py.

8.25.4.12 forcebalance::openmmio.Interaction_OpenMM::platform

Set up three OpenMM System objects.

Set the device to the environment variable or zero otherwise.

TODO: The following code should not be repeated everywhere. Set the simulation platform

Definition at line 574 of file openmmio.py.

8.25.4.13 forcebalance::interaction.Interaction::prefactor [inherited]

Definition at line 53 of file interaction.py.

8.25.4.14 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.25.4.15 forcebalance::interaction.Interaction::qfnm [inherited]

The qdata.txt file that contains the QM energies and forces.

Definition at line 49 of file interaction.py.

8.25.4.16 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.25.4.17 forcebalance::interaction.Interaction::select1 [inherited]

Number of snapshots.

Do we call Q-Chem for dielectric energies? (Currently needs to be fixed) Do we put the reference energy into the denominator? Do we put the reference energy into the denominator? What is the energy denominator? Set fragment 1

Definition at line 44 of file interaction.py.

8.25.4.18 forcebalance::interaction.Interaction::select2 [inherited]

Set fragment 2.

Definition at line 45 of file interaction.py.

8.25.4.19 forcebalance::openmmio.Interaction_OpenMM::simulations

Dictionary of simulation objects (dimer, fraga, fragb)

Definition at line 565 of file openmmio.py.

8.25.4.20 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.25.4.21 forcebalance::interaction.Interaction::traj [inherited]

Definition at line 51 of file interaction.py.

8.25.4.22 forcebalance::openmmio.Interaction_OpenMM::trajfnm

Name of the trajectory file containing snapshots.

Definition at line 564 of file openmmio.py.

8.25.4.23 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.25.4.24 forcebalance::interaction.Interaction::weight [inherited]

Definition at line 163 of file interaction.py.

8.25.4.25 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- openmmio.py

8.26 forcebalance.tinkerio.Interaction_TINKER Class Reference

Subclass of Target for interaction matching using TINKER.

Inheritance diagram for forcebalance.tinkerio.Interaction_TINKER:

Collaboration diagram for forcebalance.tinkerio.Interaction_TINKER:

Public Member Functions

- def __init__

  All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)
- def prepare_temp_directory

  Prepare the temporary directory, by default does nothing.
- def energy_driver_all
- def interaction_driver_all
- def read_reference_data

  Read the reference ab initio data from a file such as qdata.txt.
- def indicate
- def get

  Evaluate objective function.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- trajfnm

  Name of the trajectory.
- select1

  Number of snapshots.
- select2

  Set fragment 2.
- eqm

  Set upper cutoff energy.
- label

  Snapshot label, useful for graphing.
- qfnm

  The qdata.txt file that contains the QM energies and forces.

- e_err

  Qualitative Indicator: average energy error (in kJ/mol)
- e_err_pct
- ns

  Read in the trajectory file.
- traj
- divisor

  Read in the reference data.
- prefactor
- weight
- emm
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.26.1 Detailed Description

Subclass of Target for interaction matching using TINKER.

Definition at line 583 of file tinkerio.py.

8.26.2 Constructor & Destructor Documentation

8.26.2.1 def forcebalance.tinkerio.Interaction_TINKER.__init__ (*self, options, tgt_opts, forcefield*)

All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)

If we want to add attributes that are more specific (i.e. a set of reference forces for force matching), they are added in the subclass AbInitio that inherits from Target.

Reimplemented from forcebalance.interaction.Interaction.

Definition at line 586 of file tinkerio.py.

8.26.3 Member Function Documentation

8.26.3.1 def forcebalance.tinkerio.Interaction_TINKER.energy_driver_all (*self*, *select* = `None`)

Definition at line 599 of file tinkerio.py.

Here is the call graph for this function:

8.26.3.2 def forcebalance.interaction.Interaction.get (*self*, *mvals*, *AGrad* = `False`, *AHess* = `False`) `[inherited]`

Evaluate objective function.

Reimplemented from forcebalance.target.Target.

Definition at line 163 of file interaction.py.

8.26.3.3 def forcebalance.target.Target.get_G (*self*, *mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.26.3.4 def forcebalance.target.Target.get_H (*self, mvals =* None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.26.3.5 def forcebalance.target.Target.get_X (*self, mvals =* None) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.26.3.6 def forcebalance.interaction.Interaction.indicate (*self*) [inherited]

Definition at line 147 of file interaction.py.

Here is the call graph for this function:

8.26.3.7 def forcebalance.tinkerio.Interaction_TINKER.interaction_driver_all (*self, dielectric* = `False`)

Definition at line 616 of file tinkerio.py.

8.26.3.8 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.26.3.9 def forcebalance.tinkerio.Interaction_TINKER.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory, by default does nothing.

Reimplemented from forcebalance.interaction.Interaction.

Definition at line 591 of file tinkerio.py.

8.26.3.10 def forcebalance.target.Target.printcool_table (*self*, *data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.26.3.11 def forcebalance.interaction.Interaction.read_reference_data (*self*) `[inherited]`

Read the reference ab initio data from a file such as qdata.txt.

After reading in the information from qdata.txt, it is converted into the GROMACS/OpenMM units (kJ/mol for energy, kJ/mol/nm force).

Definition at line 125 of file interaction.py.

Here is the call graph for this function:

8.26.3.12 def forcebalance.target.Target.refresh_temp_directory (*self*) `[inherited]`

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.26.3.13 def forcebalance.BaseClass.set_option (*self*, *in_dict*, *src_key*, *dest_key* = `None`, *val* = `None`, *default* = `None`, *forceprint* = `False`) [inherited]

Definition at line 32 of file __init__.py.

8.26.3.14 def forcebalance.target.Target.sget (*self*, *mvals*, *AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.26.3.15 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.26.3.16 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.26.3.17 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.26.4 Member Data Documentation

8.26.4.1 forcebalance::interaction.Interaction::divisor [inherited]

Read in the reference data.

Prepare the temporary directory

Definition at line 53 of file interaction.py.

8.26.4.2 forcebalance::interaction.Interaction::e_err [inherited]

Qualitative Indicator: average energy error (in kJ/mol)

Definition at line 50 of file interaction.py.

8.26.4.3 forcebalance::interaction.Interaction::e_err_pct [inherited]

Definition at line 50 of file interaction.py.

8.26.4.4 forcebalance::interaction.Interaction::emm [inherited]

Definition at line 163 of file interaction.py.

8.26.4.5 forcebalance::interaction.Interaction::eqm [inherited]

Set upper cutoff energy.

Reference (QM) interaction energies

Definition at line 47 of file interaction.py.

8.26.4.6 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.26.4.7 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.26.4.8 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.26.4.9 forcebalance::interaction.Interaction::label [inherited]

Snapshot label, useful for graphing.

Definition at line 48 of file interaction.py.

8.26.4.10 forcebalance::interaction.Interaction::ns [inherited]

Read in the trajectory file.

Definition at line 51 of file interaction.py.

8.26.4.11 forcebalance::interaction.Interaction::objective [inherited]

Definition at line 163 of file interaction.py.

8.26.4.12 forcebalance::interaction.Interaction::prefactor [inherited]

Definition at line 53 of file interaction.py.

8.26.4.13 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.26.4.14 forcebalance::interaction.Interaction::qfnm [inherited]

The qdata.txt file that contains the QM energies and forces.

Definition at line 49 of file interaction.py.

8.26.4.15 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.26.4.16 forcebalance::interaction.Interaction::select1 [inherited]

Number of snapshots.

Do we call Q-Chem for dielectric energies? (Currently needs to be fixed) Do we put the reference energy into the denominator? Do we put the reference energy into the denominator? What is the energy denominator? Set fragment 1

Definition at line 44 of file interaction.py.

8.26.4.17 forcebalance::interaction.Interaction::select2 [inherited]

Set fragment 2.

Definition at line 45 of file interaction.py.

8.26.4.18 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.26.4.19 forcebalance::interaction.Interaction::traj [inherited]

Definition at line 51 of file interaction.py.

8.26.4.20 forcebalance::tinkerio.Interaction_TINKER::trajfnm

Name of the trajectory.

Definition at line 587 of file tinkerio.py.

8.26.4.21 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.26.4.22 forcebalance::interaction.Interaction::weight [inherited]

Definition at line 163 of file interaction.py.

8.26.4.23 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- tinkerio.py

8.27 forcebalance.gmxio.ITP_Reader Class Reference

Finite state machine for parsing GROMACS force field files.

Inheritance diagram for forcebalance.gmxio.ITP_Reader:

Collaboration diagram for forcebalance.gmxio.ITP_Reader:

Public Member Functions

- def __init__
- def feed

  Given a line, determine the interaction type and the atoms involved (the suffix).
- def Split
- def Whites
- def build_pid

  Returns the parameter type (e.g.

Public Attributes

- sec

  The current section that we're in.
- nbtype

  Nonbonded type.
- mol

The current molecule (set by the moleculetype keyword)

- pdict

  The parameter dictionary (defined in this file)
- atomnames

  Listing of all atom names in the file, (probably unnecessary)
- atomtypes

  Listing of all atom types in the file, (probably unnecessary)
- atomtype_to_mass

  A dictionary of atomic masses.
- itype
- suffix
- molatom

  The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.
- ln
- adict

  The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.
- Molecules
- AtomTypes

8.27.1 Detailed Description

Finite state machine for parsing GROMACS force field files.

We open the force field file and read all of its lines. As we loop through the force field file, we look for two types of tags: (1) section markers, in GMX indicated by [section_name], which allows us to determine the section, and (2) parameter tags, indicated by the 'PARM' or 'RPT' keywords.

As we go through the file, we figure out the atoms involved in the interaction described on each line.

When a 'PARM' keyword is indicated, it is followed by a number which is the field in the line to be modified, starting with zero. Based on the field number and the section name, we can figure out the parameter type. With the parameter type and the atoms in hand, we construct a 'parameter identifier' or pid which uniquely identifies that parameter. We also store the physical parameter value in an array called 'pvals0' and the precise location of that parameter (by filename, line number, and field number) in a list called 'pfields'.

An example: Suppose in 'my_ff.itp' I encounter the following on lines 146 and 147:

```
[ angletypes ]
CA   CB   O   1   109.47  350.00  ; PARM 4 5
```

From reading `[ angletypes ]` I know I'm in the 'angletypes' section.

On the next line, I notice two parameters on fields 4 and 5.

From the atom types, section type and field number I know the parameter IDs are `'ANGLESBCACBO'` and `'ANGLESKCACBO'`.

After building `map={'ANGLESBCACBO':1,'ANGLESKCACBO':2}`, I store the values in an array: `pvals0=array([109.47,350.00])`, and I put the parameter locations in pfields: `pfields=[['my_ff.itp',147,4,1.0],['my_ff.itp',146,5,1.0]]`. The 1.0 is a 'multiplier' and I will explain it below.

Note that in the creation of parameter IDs, we run into the issue that the atoms involved in the interaction may be labeled in reverse order (e.g. `OCACB`). Thus, we store both the normal and the reversed parameter ID in the map.

Parameter repetition and multiplier:

If `'RPT'` is encountered in the line, it is always in the syntax: `'RPT 4 ANGLESBCACAH 5 MINUS_ANGLESKCACAH /RPT'`. In this case, field 4 is replaced by the stored parameter value corresponding to `ANGLESBCACAH` and field 5 is replaced by -1 times the stored value of `ANGLESKCACAH`. Now I just picked this as an example, I don't think people actually want a negative angle force constant .. :) the `MINUS` keyword does come in handy for assigning atomic charges and virtual site positions. In order to achieve this, a multiplier of -1.0 is stored into pfields instead of 1.0.

Todo Note that I can also create the opposite virtual site position by changing the atom labeling, woo!

Definition at line 277 of file gmxio.py.

8.27.2 Constructor & Destructor Documentation

8.27.2.1 def forcebalance.gmxio.ITP_Reader.__init__ (*self, fnm*)

Reimplemented from forcebalance.BaseReader.

Definition at line 280 of file gmxio.py.

8.27.3 Member Function Documentation

8.27.3.1 def forcebalance.BaseReader.build_pid (*self, pfld*) [inherited]

Returns the parameter type (e.g.

K in BONDSK) based on the current interaction type.

Both the 'pdict' dictionary (see gmxio.pdict) and the interaction type 'state' (here, BONDS) are needed to get the parameter type.

If, however, 'pdict' does not contain the ptype value, a suitable substitute is simply the field number.

Note that if the interaction type state is not set, then it defaults to the file name, so a generic parameter ID is 'filename.line_num.field_num'

Reimplemented in forcebalance.psi4io.Grid_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 107 of file __init__.py.

8.27.3.2 def forcebalance.gmxio.ITP_Reader.feed (*self, line*)

Given a line, determine the interaction type and the atoms involved (the suffix).

For example, we want

```
H O H 5 1.231258497536e+02 4.269161426840e+02 -1.033397697685e-02 1.304674117410e+04
; PARM 4 5 6 7
```

to give us itype = 'UREY_BRADLEY' and suffix = 'HOH'

If we are in a TypeSection, it returns a list of atom types;

If we are in a TopolSection, it returns a list of atom names.

The section is essentially a case statement that picks out the appropriate interaction type and makes a list of the atoms involved

Note that we can call gmxdump for this as well, but I prefer to read the force field file directly.

ToDo: [atoms] section might need to be more flexible to accommodate optional fields

Reimplemented from forcebalance.BaseReader.

Definition at line 318 of file gmxio.py.

8.27.3.3 def forcebalance.BaseReader.Split (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 82 of file __init__.py.

Here is the call graph for this function:

8.27.3.4 def forcebalance.BaseReader.Whites (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 85 of file __init__.py.

Here is the call graph for this function:

8.27.4 Member Data Documentation

8.27.4.1 forcebalance.BaseReader::adict [inherited]

The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.

Reimplemented in forcebalance.amberio.FrcMod_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 67 of file __init__.py.

8.27.4.2 forcebalance::gmxio.ITP_Reader::atomnames

Listing of all atom names in the file, (probably unnecessary)

Definition at line 285 of file gmxio.py.

8.27.4.3 forcebalance::gmxio.ITP_Reader::atomtype_to_mass

A dictionary of atomic masses.

Definition at line 287 of file gmxio.py.

8.27.4.4 forcebalance.BaseReader::AtomTypes [inherited]

Definition at line 71 of file __init__.py.

8.27.4.5 forcebalance::gmxio.ITP_Reader::atomtypes

Listing of all atom types in the file, (probably unnecessary)

Definition at line 286 of file gmxio.py.

8.27.4.6 forcebalance::gmxio.ITP_Reader::itype

Reimplemented from forcebalance.BaseReader.

Definition at line 318 of file gmxio.py.

8.27.4.7 forcebalance.BaseReader::ln [inherited]

Definition at line 66 of file __init__.py.

8.27.4.8 forcebalance::gmxio.ITP_Reader::mol

The current molecule (set by the moleculetype keyword)

Definition at line 283 of file gmxio.py.

8.27.4.9 forcebalance::gmxio.ITP_Reader::molatom

The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.

self.moleculedict = OrderedDict() The listing of 'RES:ATOMNAMES' for atom names in the line This is obviously a placeholder.

Reimplemented from forcebalance.BaseReader.

Definition at line 318 of file gmxio.py.

8.27.4.10 forcebalance.BaseReader::Molecules [inherited]

Definition at line 71 of file __init__.py.

8.27.4.11 forcebalance::gmxio.ITP_Reader::nbtype

Nonbonded type.

Definition at line 282 of file gmxio.py.

8.27.4.12 forcebalance::gmxio.ITP_Reader::pdict

The parameter dictionary (defined in this file)

Reimplemented from forcebalance.BaseReader.

Definition at line 284 of file gmxio.py.

8.27.4.13 forcebalance::gmxio.ITP_Reader::sec

The current section that we're in.

Definition at line 281 of file gmxio.py.

8.27.4.14 forcebalance::gmxio.ITP_Reader::suffix

Reimplemented from forcebalance.BaseReader.

Definition at line 318 of file gmxio.py.

The documentation for this class was generated from the following file:

- gmxio.py

8.28 forcebalance.leastsq.LeastSquares Class Reference

Subclass of Target for general least squares fitting.

Inheritance diagram for forcebalance.leastsq.LeastSquares:

Collaboration diagram for forcebalance.leastsq.LeastSquares:

Public Member Functions

- def __init__

  All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)
- def indicate
- def get

  LPW 05-30-2012.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- call_derivatives

  Number of snapshots.
- MAQ

  Dictionary for derivative terms.
- D
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.28.1 Detailed Description

Subclass of Target for general least squares fitting.

Definition at line 35 of file leastsq.py.

8.28.2 Constructor & Destructor Documentation

8.28.2.1 def forcebalance.leastsq.LeastSquares.__init__ (*self, options, tgt_opts, forcefield*)

All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)

If we want to add attributes that are more specific (i.e. a set of reference forces for force matching), they are added in the subclass AbInitio that inherits from Target.

Reimplemented from forcebalance.target.Target.

Reimplemented in forcebalance.psi4io.THCDF_Psi4.

Definition at line 38 of file leastsq.py.

8.28.3 Member Function Documentation

8.28.3.1 def forcebalance.leastsq.LeastSquares.get (*self, mvals, AGrad* = `False`, *AHess* = `False`)

LPW 05-30-2012.

This subroutine builds the objective function (and optionally its derivatives) from a general software.

This subroutine interfaces with simulation software 'drivers'. The driver is expected to give exact values, fitting values, and weights.

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient
in	*AHess*	Switch to turn on analytic Hessian

Returns

Answer Contribution to the objective function

Reimplemented from forcebalance.target.Target.

Definition at line 74 of file leastsq.py.

8.28.3.2 def forcebalance.target.Target.get_G (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.28.3.3 def forcebalance.target.Target.get_H (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.28.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.28.3.5 def forcebalance.leastsq.LeastSquares.indicate (*self*)

Reimplemented in forcebalance.psi4io.THCDF_Psi4.

Definition at line 53 of file leastsq.py.

Here is the call graph for this function:

8.28.3.6 def forcebalance.target.Target.link_from_tempdir (*self*, *absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.28.3.7 def forcebalance.target.Target.printcool_table (*self*, *data* = OrderedDict([]), *headings* = [], *banner* = None, *footnote* = None, *color* = 0) [inherited]

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.28.3.8 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.28.3.9 def forcebalance.BaseClass.set_option (*self*, *in_dict*, *src_key*, *dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.28.3.10 def forcebalance.target.Target.sget (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) `[inherited]`

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.28.3.11 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) `[inherited]`

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.28.3.12 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.28.3.13 def forcebalance.target.Target.wq_complete (*self*) `[inherited]`

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.28.4 Member Data Documentation

8.28.4.1 forcebalance::leastsq.LeastSquares::call_derivatives

Number of snapshots.

Which parameters are differentiated?

Definition at line 40 of file leastsq.py.

8.28.4.2 forcebalance::leastsq.LeastSquares::D

Definition at line 75 of file leastsq.py.

8.28.4.3 forcebalance::target.Target::FF `[inherited]`

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.28.4.4 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.28.4.5 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.28.4.6 forcebalance::leastsq.LeastSquares::MAQ

Dictionary for derivative terms.

Definition at line 75 of file leastsq.py.

8.28.4.7 forcebalance::leastsq.LeastSquares::objective

Definition at line 75 of file leastsq.py.

8.28.4.8 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.28.4.9 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.28.4.10 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.28.4.11 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.28.4.12 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- leastsq.py

8.29 forcebalance.nifty.LineChunker Class Reference

Public Member Functions

- def __init__
- def push
- def close
- def nomnom
- def __enter__
- def __exit__

Public Attributes

- callback
- buf

8.29.1 Detailed Description

Definition at line 850 of file nifty.py.

8.29.2 Constructor & Destructor Documentation

8.29.2.1 def forcebalance.nifty.LineChunker.__init__ (*self, callback*)

Definition at line 851 of file nifty.py.

8.29.3 Member Function Documentation

8.29.3.1 def forcebalance.nifty.LineChunker.__enter__ (*self*)

Definition at line 870 of file nifty.py.

8.29.3.2 def forcebalance.nifty.LineChunker.__exit__ (*self, args, kwargs*)

Definition at line 873 of file nifty.py.

Here is the call graph for this function:

8.29.3.3 def forcebalance.nifty.LineChunker.close (*self*)

Definition at line 859 of file nifty.py.

8.29.3.4 def forcebalance.nifty.LineChunker.nomnom (*self*)

Definition at line 863 of file nifty.py.

8.29.3.5 def forcebalance.nifty.LineChunker.push (*self, data*)

Definition at line 855 of file nifty.py.

8.29.4 Member Data Documentation

8.29.4.1 forcebalance::nifty.LineChunker::buf

Definition at line 851 of file nifty.py.

8.29.4.2 forcebalance::nifty.LineChunker::callback

Definition at line 851 of file nifty.py.

The documentation for this class was generated from the following file:

- nifty.py

8.30 forcebalance.liquid.Liquid Class Reference

Subclass of Target for liquid property matching.

Inheritance diagram for forcebalance.liquid.Liquid:

Collaboration diagram for forcebalance.liquid.Liquid:

Public Member Functions

- def __init__

  Create an instance of the class.
- def read_data
- def npt_simulation

  Submit a NPT simulation to the Work Queue.
- def indicate
- def objective_term
- def submit_jobs
- def get

  Fitting of liquid bulk properties.
- def polarization_correction

  Return the self-polarization correction as described in Berendsen et al., JPC 1987.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

This method determines whether the Work Queue tasks for the current target have completed.

- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- do_self_pol
- extra_output

  Read the reference data.
- SavedMVal

  Saved force field mvals for all iterations.
- SavedTraj

  Saved trajectories for all iterations and all temperatures :)
- MBarEnergy

  Evaluated energies for all trajectories (i.e.
- nptpfx
- nptfiles
- nptsfx
- last_traj
- RefData
- PhasePoints
- Labels
- w_rho

  Density.
- w_hvap
- w_alpha
- w_kappa
- w_cp
- w_eps0
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.30.1 Detailed Description

Subclass of Target for liquid property matching.

Definition at line 51 of file liquid.py.

8.30.2 Constructor & Destructor Documentation

8.30.2.1 def forcebalance.liquid.Liquid.__init__ (*self, options, tgt_opts, forcefield*)

Create an instance of the class.

Reimplemented from forcebalance.target.Target.

Reimplemented in forcebalance.gmxio.Liquid_GMX, forcebalance.openmmio.Liquid_OpenMM, and forcebalance.tinkerio.Liquid_TINKER.

Definition at line 56 of file liquid.py.

8.30.3 Member Function Documentation

8.30.3.1 def forcebalance.liquid.Liquid.get (*self, mvals, AGrad* = `True`, *AHess* = `True`)

Fitting of liquid bulk properties.

This is the current major direction of development for ForceBalance. Basically, fitting the QM energies / forces alone does not always give us the best simulation behavior. In many cases it makes more sense to try and reproduce some experimentally known data as well.

In order to reproduce experimentally known data, we need to run a simulation and compare the simulation result to experiment. The main challenge here is that the simulations are computationally intensive (i.e. they require energy and force evaluations), and furthermore the results are noisy. We need to run the simulations automatically and remotely (i.e. on clusters) and a good way to calculate the derivatives of the simulation results with respect to the parameter values.

This function contains some experimentally known values of the density and enthalpy of vaporization (Hvap) of liquid water. It launches the density and Hvap calculations on the cluster, and gathers the results / derivatives. The actual calculation of results / derivatives is done in a separate file.

After the results come back, they are gathered together to form an objective function.

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient
in	*AHess*	Switch to turn on analytic Hessian

Returns

Answer Contribution to the objective function Fill in the weight matrix with MBAR weights where MBAR was run, and equal weights otherwise.

Reimplemented from forcebalance.target.Target.

Definition at line 401 of file liquid.py.

8.30.3.2 def forcebalance.target.Target.get_G (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.30.3.3 def forcebalance.target.Target.get_H (*self*, *mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.30.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.30.3.5 def forcebalance.liquid.Liquid.indicate (*self*)

Definition at line 254 of file liquid.py.

8.30.3.6 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.30.3.7 def forcebalance.liquid.Liquid.npt_simulation (*self, temperature, pressure, simnum*)

Submit a NPT simulation to the Work Queue.

Reimplemented in forcebalance.tinkerio.Liquid_TINKER.

Definition at line 233 of file liquid.py.

Here is the call graph for this function:

8.30.3.8 def forcebalance.liquid.Liquid.objective_term (*self, points, expname, calc, err, grad, name =* "Quantity", *SubAverage =* False)

Definition at line 258 of file liquid.py.

Here is the call graph for this function:

8.30.3.9 def forcebalance.liquid.Liquid.polarization_correction (*self, mvals*)

Return the self-polarization correction as described in Berendsen et al., JPC 1987.

Reimplemented in forcebalance.gmxio.Liquid_GMX, and forcebalance.openmmio.Liquid_OpenMM.

Definition at line 759 of file liquid.py.

8.30.3.10 def forcebalance.target.Target.printcool_table (*self, data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.30.3.11 def forcebalance.liquid.Liquid.read_data (*self*)

Definition at line 141 of file liquid.py.

8.30.3.12 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.30.3.13 def forcebalance.BaseClass.set_option (*self*, *in_dict*, *src_key*, *dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.30.3.14 def forcebalance.target.Target.sget (*self*, *mvals*, *AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.30.3.15 def forcebalance.target.Target.stage (*self*, *mvals*, *AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) `[inherited]`

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.30.3.16 def forcebalance.liquid.Liquid.submit_jobs (*self*, *mvals*, *AGrad* = `True`, *AHess* = `True`)

Reimplemented from forcebalance.target.Target.

Definition at line 336 of file liquid.py.

Here is the call graph for this function:

8.30.3.17 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.30.4 Member Data Documentation

8.30.4.1 forcebalance::liquid.Liquid::do_self_pol

Definition at line 56 of file liquid.py.

8.30.4.2 forcebalance::liquid.Liquid::extra_output

Read the reference data.

Prepare the temporary directory Extra platform-dependent data to send back

Reimplemented in forcebalance.gmxio.Liquid_GMX.

Definition at line 59 of file liquid.py.

8.30.4.3 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.30.4.4 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.30.4.5 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.30.4.6 forcebalance::liquid.Liquid::Labels

Definition at line 141 of file liquid.py.

8.30.4.7 forcebalance::liquid.Liquid::last_traj

Definition at line 62 of file liquid.py.

8.30.4.8 forcebalance::liquid.Liquid::MBarEnergy

Evaluated energies for all trajectories (i.e.

all iterations and all temperatures), using all mvals

Definition at line 62 of file liquid.py.

8.30.4.9 forcebalance::liquid.Liquid::nptfiles

Definition at line 62 of file liquid.py.

8.30.4.10 forcebalance::liquid.Liquid::nptpfx

Reimplemented in forcebalance.gmxio.Liquid_GMX.

Definition at line 62 of file liquid.py.

8.30.4.11 forcebalance::liquid.Liquid::nptsfx

Definition at line 62 of file liquid.py.

8.30.4.12 forcebalance::liquid.Liquid::PhasePoints

Definition at line 141 of file liquid.py.

8.30.4.13 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.30.4.14 forcebalance::liquid.Liquid::RefData

Definition at line 141 of file liquid.py.

8.30.4.15 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.30.4.16 forcebalance::liquid.Liquid::SavedMVal

Saved force field mvals for all iterations.

Definition at line 60 of file liquid.py.

8.30.4.17 forcebalance::liquid.Liquid::SavedTraj

Saved trajectories for all iterations and all temperatures :)

Definition at line 61 of file liquid.py.

8.30.4.18 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.30.4.19 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.30.4.20 forcebalance::liquid.Liquid::w_alpha

Definition at line 408 of file liquid.py.

8.30.4.21 forcebalance::liquid.Liquid::w_cp

Definition at line 408 of file liquid.py.

8.30.4.22 forcebalance::liquid.Liquid::w_eps0

Definition at line 408 of file liquid.py.

8.30.4.23 forcebalance::liquid.Liquid::w_hvap

Definition at line 408 of file liquid.py.

8.30.4.24 forcebalance::liquid.Liquid::w_kappa

Definition at line 408 of file liquid.py.

8.30.4.25 forcebalance::liquid.Liquid::w_rho

Density.

Enthalpy of vaporization. Thermal expansion coefficient. Isothermal compressibility. Isobaric heat capacity. Static dielectric constant. Estimation of errors.

Definition at line 408 of file liquid.py.

8.30.4.26 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- liquid.py

8.31 forcebalance.gmxio.Liquid_GMX Class Reference

Inheritance diagram for forcebalance.gmxio.Liquid_GMX:

Collaboration diagram for forcebalance.gmxio.Liquid_GMX:

Public Member Functions

- def __init__

  Create an instance of the class.
- def prepare_temp_directory

  Prepare the temporary directory by copying in important files.
- def polarization_correction

  Return the self-polarization correction as described in Berendsen et al., JPC 1987.
- def read_data
- def npt_simulation

  Submit a NPT simulation to the Work Queue.
- def indicate
- def objective_term
- def submit_jobs
- def get

  Fitting of liquid bulk properties.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

Back up the temporary directory if desired, delete it and then create a new one.

- def sget

  Stages the directory for the target, and then calls 'get'.

- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.

- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.

- def printcool_table

  Print target information in an organized table format.

- def set_option

Public Attributes

- liquid_fnm
- liquid_conf
- liquid_traj
- gas_fnm
- nptpfx
- engine
- extra_output

  Read the reference data.

- do_self_pol
- SavedMVal

  Saved force field mvals for all iterations.

- SavedTraj

  Saved trajectories for all iterations and all temperatures :)

- MBarEnergy

  Evaluated energies for all trajectories (i.e.

- nptfiles
- nptsfx
- last_traj
- RefData
- PhasePoints
- Labels
- w_rho

  Density.

- w_hvap
- w_alpha
- w_kappa
- w_cp
- w_eps0
- tempdir

  Root directory of the whole project.

- rundir

  The directory in which the simulation is running - this can be updated.

- FF

  Need the forcefield (here for now)

- xct

Counts how often the objective function was computed.

- gct

  Counts how often the gradient was computed.

- hct

  Counts how often the Hessian was computed.

- PrintOptionDict
- verbose_options

8.31.1 Detailed Description

Definition at line 681 of file gmxio.py.

8.31.2 Constructor & Destructor Documentation

8.31.2.1 def forcebalance.gmxio.Liquid_GMX.__init__ (*self, options, tgt_opts, forcefield*)

Create an instance of the class.

Reimplemented from forcebalance.liquid.Liquid.

Definition at line 682 of file gmxio.py.

8.31.3 Member Function Documentation

8.31.3.1 def forcebalance.liquid.Liquid.get (*self, mvals, AGrad* = `True`, *AHess* = `True`) [inherited]

Fitting of liquid bulk properties.

This is the current major direction of development for ForceBalance. Basically, fitting the QM energies / forces alone does not always give us the best simulation behavior. In many cases it makes more sense to try and reproduce some experimentally known data as well.

In order to reproduce experimentally known data, we need to run a simulation and compare the simulation result to experiment. The main challenge here is that the simulations are computationally intensive (i.e. they require energy and force evaluations), and furthermore the results are noisy. We need to run the simulations automatically and remotely (i.e. on clusters) and a good way to calculate the derivatives of the simulation results with respect to the parameter values.

This function contains some experimentally known values of the density and enthalpy of vaporization (Hvap) of liquid water. It launches the density and Hvap calculations on the cluster, and gathers the results / derivatives. The actual calculation of results / derivatives is done in a separate file.

After the results come back, they are gathered together to form an objective function.

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient
in	*AHess*	Switch to turn on analytic Hessian

Returns

Answer Contribution to the objective function Fill in the weight matrix with MBAR weights where MBAR was run, and equal weights otherwise.

Reimplemented from forcebalance.target.Target.

Definition at line 401 of file liquid.py.

8.31.3.2 def forcebalance.target.Target.get_G (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.31.3.3 def forcebalance.target.Target.get_H (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.31.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = None) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.31.3.5 def forcebalance.liquid.Liquid.indicate (*self*) [inherited]

Definition at line 254 of file liquid.py.

8.31.3.6 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.31.3.7 def forcebalance.liquid.Liquid.npt_simulation (*self, temperature, pressure, simnum*) [inherited]

Submit a NPT simulation to the Work Queue.

Reimplemented in forcebalance.tinkerio.Liquid_TINKER.

Definition at line 233 of file liquid.py.

Here is the call graph for this function:

8.31.3.8 def forcebalance.liquid.Liquid.objective_term (*self, points, expname, calc, err, grad, name =* "Quantity", *SubAverage =* False) [inherited]

Definition at line 258 of file liquid.py.

Here is the call graph for this function:

8.31.3.9 def forcebalance.gmxio.Liquid_GMX.polarization_correction (*self, mvals*)

Return the self-polarization correction as described in Berendsen et al., JPC 1987.

Reimplemented from forcebalance.liquid.Liquid.

Definition at line 726 of file gmxio.py.

Here is the call graph for this function:

8.31.3.10 def forcebalance.gmxio.Liquid_GMX.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory by copying in important files.

Definition at line 709 of file gmxio.py.

Here is the call graph for this function:

8.31.3.11 def forcebalance.target.Target.printcool_table (*self, data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.31.3.12 def forcebalance.liquid.Liquid.read_data (*self*) [inherited]

Definition at line 141 of file liquid.py.

8.31.3.13 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.31.3.14 def forcebalance.BaseClass.set_option (*self*, *in_dict*, *src_key*, *dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.31.3.15 def forcebalance.target.Target.sget (*self*, *mvals*, *AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.31.3.16 def forcebalance.target.Target.stage (*self*, *mvals*, *AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.31.3.17 def forcebalance.liquid.Liquid.submit_jobs (*self, mvals, AGrad* = `True`, *AHess* = `True`) `[inherited]`

Reimplemented from forcebalance.target.Target.

Definition at line 336 of file liquid.py.

Here is the call graph for this function:

8.31.3.18 def forcebalance.target.Target.wq_complete (*self*) `[inherited]`

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.31.4 Member Data Documentation

8.31.4.1 forcebalance::liquid.Liquid::do_self_pol `[inherited]`

Definition at line 56 of file liquid.py.

8.31.4.2 forcebalance::gmxio.Liquid_GMX::engine

Definition at line 682 of file gmxio.py.

8.31.4.3 forcebalance::gmxio.Liquid_GMX::extra_output

Read the reference data.

Prepare the temporary directory Extra platform-dependent data to send back

Reimplemented from forcebalance.liquid.Liquid.

Definition at line 682 of file gmxio.py.

8.31.4.4 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.31.4.5 forcebalance::gmxio.Liquid_GMX::gas_fnm

Definition at line 682 of file gmxio.py.

8.31.4.6 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.31.4.7 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.31.4.8 forcebalance::liquid.Liquid::Labels [inherited]

Definition at line 141 of file liquid.py.

8.31.4.9 forcebalance::liquid.Liquid::last_traj [inherited]

Definition at line 62 of file liquid.py.

8.31.4.10 forcebalance::gmxio.Liquid_GMX::liquid_conf

Definition at line 682 of file gmxio.py.

8.31.4.11 forcebalance::gmxio.Liquid_GMX::liquid_fnm

Definition at line 682 of file gmxio.py.

8.31.4.12 forcebalance::gmxio.Liquid_GMX::liquid_traj

Definition at line 682 of file gmxio.py.

8.31.4.13 forcebalance::liquid.Liquid::MBarEnergy [inherited]

Evaluated energies for all trajectories (i.e.

all iterations and all temperatures), using all mvals

Definition at line 62 of file liquid.py.

8.31.4.14 forcebalance::liquid.Liquid::nptfiles [inherited]

Definition at line 62 of file liquid.py.

8.31.4.15 forcebalance::gmxio.Liquid_GMX::nptpfx

Reimplemented from forcebalance.liquid.Liquid.

Definition at line 682 of file gmxio.py.

8.31.4.16 forcebalance::liquid.Liquid::nptsfx [inherited]

Definition at line 62 of file liquid.py.

8.31.4.17 forcebalance::liquid.Liquid::PhasePoints [inherited]

Definition at line 141 of file liquid.py.

8.31.4.18 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.31.4.19 forcebalance::liquid.Liquid::RefData [inherited]

Definition at line 141 of file liquid.py.

8.31.4.20 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.31.4.21 forcebalance::liquid.Liquid::SavedMVal [inherited]

Saved force field mvals for all iterations.

Definition at line 60 of file liquid.py.

8.31.4.22 forcebalance::liquid.Liquid::SavedTraj [inherited]

Saved trajectories for all iterations and all temperatures :)

Definition at line 61 of file liquid.py.

8.31.4.23 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.31.4.24 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.31.4.25 forcebalance::liquid.Liquid::w_alpha [inherited]

Definition at line 408 of file liquid.py.

8.31.4.26 forcebalance::liquid.Liquid::w_cp [inherited]

Definition at line 408 of file liquid.py.

8.31.4.27 forcebalance::liquid.Liquid::w_eps0 [inherited]

Definition at line 408 of file liquid.py.

8.31.4.28 forcebalance::liquid.Liquid::w_hvap [inherited]

Definition at line 408 of file liquid.py.

8.31.4.29 forcebalance::liquid.Liquid::w_kappa [inherited]

Definition at line 408 of file liquid.py.

8.31.4.30 forcebalance::liquid.Liquid::w_rho [inherited]

Density.

Enthalpy of vaporization. Thermal expansion coefficient. Isothermal compressibility. Isobaric heat capacity. Static dielectric constant. Estimation of errors.

Definition at line 408 of file liquid.py.

8.31.4.31 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- gmxio.py

8.32 forcebalance.openmmio.Liquid_OpenMM Class Reference

Inheritance diagram for forcebalance.openmmio.Liquid_OpenMM:

Collaboration diagram for forcebalance.openmmio.Liquid_OpenMM:

Public Member Functions

- def __init__

  Create an instance of the class.
- def prepare_temp_directory

  Prepare the temporary directory by copying in important files.
- def polarization_correction

  Return the self-polarization correction as described in Berendsen et al., JPC 1987.
- def read_data
- def npt_simulation

  Submit a NPT simulation to the Work Queue.
- def indicate
- def objective_term
- def submit_jobs
- def get

  Fitting of liquid bulk properties.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- mpdb
- platform
- msim
- liquid_fnm
- liquid_conf
- liquid_traj
- gas_fnm
- engine
- do_self_pol
- extra_output

  Read the reference data.

- SavedMVal

  Saved force field mvals for all iterations.
- SavedTraj

  Saved trajectories for all iterations and all temperatures :)
- MBarEnergy

  Evaluated energies for all trajectories (i.e.
- nptpfx
- nptfiles
- nptsfx
- last_traj
- RefData
- PhasePoints
- Labels
- w_rho

  Density.
- w_hvap
- w_alpha
- w_kappa
- w_cp
- w_eps0
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.32.1 Detailed Description

Definition at line 349 of file openmmio.py.

8.32.2 Constructor & Destructor Documentation

8.32.2.1 def forcebalance.openmmio.Liquid_OpenMM.__init__ (*self, options, tgt_opts, forcefield*)

Create an instance of the class.

Reimplemented from forcebalance.liquid.Liquid.

Definition at line 350 of file openmmio.py.

8.32.3 Member Function Documentation

8.32.3.1 def forcebalance.liquid.Liquid.get (*self, mvals, AGrad* = `True`, *AHess* = `True`) [inherited]

Fitting of liquid bulk properties.

This is the current major direction of development for ForceBalance. Basically, fitting the QM energies / forces alone does not always give us the best simulation behavior. In many cases it makes more sense to try and reproduce some experimentally known data as well.

In order to reproduce experimentally known data, we need to run a simulation and compare the simulation result to experiment. The main challenge here is that the simulations are computationally intensive (i.e. they require energy and force evaluations), and furthermore the results are noisy. We need to run the simulations automatically and remotely (i.e. on clusters) and a good way to calculate the derivatives of the simulation results with respect to the parameter values.

This function contains some experimentally known values of the density and enthalpy of vaporization (Hvap) of liquid water. It launches the density and Hvap calculations on the cluster, and gathers the results / derivatives. The actual calculation of results / derivatives is done in a separate file.

After the results come back, they are gathered together to form an objective function.

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient
in	*AHess*	Switch to turn on analytic Hessian

Returns

Answer Contribution to the objective function Fill in the weight matrix with MBAR weights where MBAR was run, and equal weights otherwise.

Reimplemented from forcebalance.target.Target.

Definition at line 401 of file liquid.py.

8.32.3.2 def forcebalance.target.Target.get_G (*self, mvals* = `None`) [inherited]

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_-pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.32.3.3 def forcebalance.target.Target.get_H (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.32.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = None) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.32.3.5 def forcebalance.liquid.Liquid.indicate (*self*) [inherited]

Definition at line 254 of file liquid.py.

8.32.3.6 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.32.3.7 def forcebalance.liquid.Liquid.npt_simulation (*self, temperature, pressure, simnum*) [inherited]

Submit a NPT simulation to the Work Queue.

Reimplemented in forcebalance.tinkerio.Liquid_TINKER.

Definition at line 233 of file liquid.py.

Here is the call graph for this function:

8.32.3.8 def forcebalance.liquid.Liquid.objective_term (*self, points, expname, calc, err, grad, name =* "Quantity", *SubAverage =* False) [inherited]

Definition at line 258 of file liquid.py.

Here is the call graph for this function:

8.32.3.9 def forcebalance.openmmio.Liquid_OpenMM.polarization_correction (*self, mvals*)

Return the self-polarization correction as described in Berendsen et al., JPC 1987.

Reimplemented from forcebalance.liquid.Liquid.

Definition at line 398 of file openmmio.py.

Here is the call graph for this function:

8.32.3.10 def forcebalance.openmmio.Liquid_OpenMM.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory by copying in important files.

Definition at line 391 of file openmmio.py.

Here is the call graph for this function:

8.32.3.11 def forcebalance.target.Target.printcool_table (*self, data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.

banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.32.3.12 def forcebalance.liquid.Liquid.read_data (*self*) [inherited]

Definition at line 141 of file liquid.py.

8.32.3.13 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.32.3.14 def forcebalance.BaseClass.set_option (*self*, *in_dict*, *src_key*, *dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.32.3.15 def forcebalance.target.Target.sget (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.32.3.16 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.32.3.17 def forcebalance.liquid.Liquid.submit_jobs (*self, mvals, AGrad* = `True`, *AHess* = `True`) `[inherited]`

Reimplemented from forcebalance.target.Target.

Definition at line 336 of file liquid.py.

Here is the call graph for this function:

8.32.3.18 def forcebalance.target.Target.wq_complete (*self*) `[inherited]`

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.32.4 Member Data Documentation

8.32.4.1 forcebalance::liquid.Liquid::do_self_pol `[inherited]`

Definition at line 56 of file liquid.py.

8.32.4.2 forcebalance::openmmio.Liquid_OpenMM::engine

Definition at line 350 of file openmmio.py.

8.32.4.3 forcebalance::liquid.Liquid::extra_output [inherited]

Read the reference data.

Prepare the temporary directory Extra platform-dependent data to send back

Reimplemented in forcebalance.gmxio.Liquid_GMX.

Definition at line 59 of file liquid.py.

8.32.4.4 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.32.4.5 forcebalance::openmmio.Liquid_OpenMM::gas_fnm

Definition at line 350 of file openmmio.py.

8.32.4.6 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.32.4.7 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.32.4.8 forcebalance::liquid.Liquid::Labels [inherited]

Definition at line 141 of file liquid.py.

8.32.4.9 forcebalance::liquid.Liquid::last_traj [inherited]

Definition at line 62 of file liquid.py.

8.32.4.10 forcebalance::openmmio.Liquid_OpenMM::liquid_conf

Definition at line 350 of file openmmio.py.

8.32.4.11 forcebalance::openmmio.Liquid_OpenMM::liquid_fnm

Definition at line 350 of file openmmio.py.

8.32.4.12 forcebalance::openmmio.Liquid_OpenMM::liquid_traj

Definition at line 350 of file openmmio.py.

8.32.4.13 forcebalance::liquid.Liquid::MBarEnergy [inherited]

Evaluated energies for all trajectories (i.e.

all iterations and all temperatures), using all mvals

Definition at line 62 of file liquid.py.

8.32.4.14 forcebalance::openmmio.Liquid_OpenMM::mpdb

Definition at line 350 of file openmmio.py.

8.32.4.15 forcebalance::openmmio.Liquid_OpenMM::msim

Definition at line 350 of file openmmio.py.

8.32.4.16 forcebalance::liquid.Liquid::nptfiles [inherited]

Definition at line 62 of file liquid.py.

8.32.4.17 forcebalance::liquid.Liquid::nptpfx [inherited]

Reimplemented in forcebalance.gmxio.Liquid_GMX.

Definition at line 62 of file liquid.py.

8.32.4.18 forcebalance::liquid.Liquid::nptsfx [inherited]

Definition at line 62 of file liquid.py.

8.32.4.19 forcebalance::liquid.Liquid::PhasePoints [inherited]

Definition at line 141 of file liquid.py.

8.32.4.20 forcebalance::openmmio.Liquid_OpenMM::platform

Definition at line 350 of file openmmio.py.

8.32.4.21 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.32.4.22 forcebalance::liquid.Liquid::RefData [inherited]

Definition at line 141 of file liquid.py.

8.32.4.23 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.32.4.24 forcebalance::liquid.Liquid::SavedMVal [inherited]

Saved force field mvals for all iterations.

Definition at line 60 of file liquid.py.

8.32.4.25 forcebalance::liquid.Liquid::SavedTraj [inherited]

Saved trajectories for all iterations and all temperatures :)

Definition at line 61 of file liquid.py.

8.32.4.26 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.32.4.27 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.32.4.28 forcebalance::liquid.Liquid::w_alpha [inherited]

Definition at line 408 of file liquid.py.

8.32.4.29 forcebalance::liquid.Liquid::w_cp [inherited]

Definition at line 408 of file liquid.py.

8.32.4.30 forcebalance::liquid.Liquid::w_eps0 [inherited]

Definition at line 408 of file liquid.py.

8.32.4.31 forcebalance::liquid.Liquid::w_hvap [inherited]

Definition at line 408 of file liquid.py.

8.32.4.32 forcebalance::liquid.Liquid::w_kappa [inherited]

Definition at line 408 of file liquid.py.

8.32.4.33 forcebalance::liquid.Liquid::w_rho [inherited]

Density.

Enthalpy of vaporization. Thermal expansion coefficient. Isothermal compressibility. Isobaric heat capacity. Static dielectric constant. Estimation of errors.

Definition at line 408 of file liquid.py.

8.32.4.34 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- openmmio.py

8.33 forcebalance.tinkerio.Liquid_TINKER Class Reference

Inheritance diagram for forcebalance.tinkerio.Liquid_TINKER:

Collaboration diagram for forcebalance.tinkerio.Liquid_TINKER:

Public Member Functions

- def __init__

  Create an instance of the class.
- def prepare_temp_directory

  Prepare the temporary directory by copying in important files.
- def npt_simulation

  Submit a NPT simulation to the Work Queue.
- def read_data
- def indicate
- def objective_term
- def submit_jobs
- def get

  Fitting of liquid bulk properties.
- def polarization_correction

  Return the self-polarization correction as described in Berendsen et al., JPC 1987.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- DynDict
- DynDict_New
- do_self_pol
- extra_output

  Read the reference data.
- SavedMVal

  Saved force field mvals for all iterations.
- SavedTraj

  Saved trajectories for all iterations and all temperatures :)
- MBarEnergy

  Evaluated energies for all trajectories (i.e.

- nptpfx
- nptfiles
- nptsfx
- last_traj
- RefData
- PhasePoints
- Labels
- w_rho

  Density.
- w_hvap
- w_alpha
- w_kappa
- w_cp
- w_eps0
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.33.1 Detailed Description

Definition at line 233 of file tinkerio.py.

8.33.2 Constructor & Destructor Documentation

8.33.2.1 def forcebalance.tinkerio.Liquid_TINKER.__init__ (*self, options, tgt_opts, forcefield*)

Create an instance of the class.

Reimplemented from forcebalance.liquid.Liquid.

Definition at line 234 of file tinkerio.py.

8.33.3 Member Function Documentation

8.33.3.1 def forcebalance.liquid.Liquid.get (*self, mvals, AGrad* = `True`, *AHess* = `True`) [inherited]

Fitting of liquid bulk properties.

This is the current major direction of development for ForceBalance. Basically, fitting the QM energies / forces alone does not always give us the best simulation behavior. In many cases it makes more sense to try and reproduce some experimentally known data as well.

In order to reproduce experimentally known data, we need to run a simulation and compare the simulation result to experiment. The main challenge here is that the simulations are computationally intensive (i.e. they require energy and force evaluations), and furthermore the results are noisy. We need to run the simulations automatically and remotely (i.e. on clusters) and a good way to calculate the derivatives of the simulation results with respect to the parameter values.

This function contains some experimentally known values of the density and enthalpy of vaporization (Hvap) of liquid water. It launches the density and Hvap calculations on the cluster, and gathers the results / derivatives. The actual calculation of results / derivatives is done in a separate file.

After the results come back, they are gathered together to form an objective function.

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient
in	*AHess*	Switch to turn on analytic Hessian

Returns

Answer Contribution to the objective function Fill in the weight matrix with MBAR weights where MBAR was run, and equal weights otherwise.

Reimplemented from forcebalance.target.Target.

Definition at line 401 of file liquid.py.

8.33.3.2 def forcebalance.target.Target.get_G (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_-pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.33.3.3 def forcebalance.target.Target.get_H (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.33.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) `[inherited]`

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.33.3.5 def forcebalance.liquid.Liquid.indicate (*self*) [inherited]

Definition at line 254 of file liquid.py.

8.33.3.6 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.33.3.7 def forcebalance.tinkerio.Liquid_TINKER.npt_simulation (*self, temperature, pressure, simnum*)

Submit a NPT simulation to the Work Queue.

Reimplemented from forcebalance.liquid.Liquid.

Definition at line 261 of file tinkerio.py.

Here is the call graph for this function:

8.33.3.8 def forcebalance.liquid.Liquid.objective_term (*self, points, expname, calc, err, grad, name =* "Quantity", *SubAverage =* False) [inherited]

Definition at line 258 of file liquid.py.

Here is the call graph for this function:

8.33.3.9 def forcebalance.liquid.Liquid.polarization_correction (*self, mvals*) [inherited]

Return the self-polarization correction as described in Berendsen et al., JPC 1987.

Reimplemented in forcebalance.gmxio.Liquid_GMX, and forcebalance.openmmio.Liquid_OpenMM.

Definition at line 759 of file liquid.py.

8.33.3.10 def forcebalance.tinkerio.Liquid_TINKER.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory by copying in important files.

Definition at line 243 of file tinkerio.py.

Here is the call graph for this function:

8.33.3.11 def forcebalance.target.Target.printcool_table (*self, data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) [inherited]

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.33.3.12 def forcebalance.liquid.Liquid.read_data (*self*) [inherited]

Definition at line 141 of file liquid.py.

8.33.3.13 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.33.3.14 def forcebalance.BaseClass.set_option (*self*, *in_dict*, *src_key*, *dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.33.3.15 def forcebalance.target.Target.sget (*self*, *mvals*, *AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.33.3.16 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.33.3.17 def forcebalance.liquid.Liquid.submit_jobs (*self, mvals, AGrad* = `True`, *AHess* = `True`) [inherited]

Reimplemented from forcebalance.target.Target.

Definition at line 336 of file liquid.py.

Here is the call graph for this function:

8.33.3.18 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.33.4 Member Data Documentation

8.33.4.1 forcebalance::liquid.Liquid::do_self_pol [inherited]

Definition at line 56 of file liquid.py.

8.33.4.2 forcebalance::tinkerio.Liquid_TINKER::DynDict

Definition at line 234 of file tinkerio.py.

8.33.4.3 forcebalance::tinkerio.Liquid_TINKER::DynDict_New

Definition at line 234 of file tinkerio.py.

8.33.4.4 forcebalance::liquid.Liquid::extra_output [inherited]

Read the reference data.

Prepare the temporary directory Extra platform-dependent data to send back

Reimplemented in forcebalance.gmxio.Liquid_GMX.

Definition at line 59 of file liquid.py.

8.33.4.5 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.33.4.6 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.33.4.7 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.33.4.8 forcebalance::liquid.Liquid::Labels [inherited]

Definition at line 141 of file liquid.py.

8.33.4.9 forcebalance::liquid.Liquid::last_traj [inherited]

Definition at line 62 of file liquid.py.

8.33.4.10 forcebalance::liquid.Liquid::MBarEnergy [inherited]

Evaluated energies for all trajectories (i.e.

all iterations and all temperatures), using all mvals

Definition at line 62 of file liquid.py.

8.33.4.11 forcebalance::liquid.Liquid::nptfiles [inherited]

Definition at line 62 of file liquid.py.

8.33.4.12 forcebalance::liquid.Liquid::nptpfx [inherited]

Reimplemented in forcebalance.gmxio.Liquid_GMX.

Definition at line 62 of file liquid.py.

8.33.4.13 forcebalance::liquid.Liquid::nptsfx [inherited]

Definition at line 62 of file liquid.py.

8.33.4.14 forcebalance::liquid.Liquid::PhasePoints [inherited]

Definition at line 141 of file liquid.py.

8.33.4.15 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.33.4.16 forcebalance::liquid.Liquid::RefData [inherited]

Definition at line 141 of file liquid.py.

8.33.4.17 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.33.4.18 forcebalance::liquid.Liquid::SavedMVal [inherited]

Saved force field mvals for all iterations.

Definition at line 60 of file liquid.py.

8.33.4.19 forcebalance::liquid.Liquid::SavedTraj [inherited]

Saved trajectories for all iterations and all temperatures :)

Definition at line 61 of file liquid.py.

8.33.4.20 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.33.4.21 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.33.4.22 forcebalance::liquid.Liquid::w_alpha [inherited]

Definition at line 408 of file liquid.py.

8.33.4.23 forcebalance::liquid.Liquid::w_cp [inherited]

Definition at line 408 of file liquid.py.

8.33.4.24 forcebalance::liquid.Liquid::w_eps0 [inherited]

Definition at line 408 of file liquid.py.

8.33.4.25 forcebalance::liquid.Liquid::w_hvap [inherited]

Definition at line 408 of file liquid.py.

8.33.4.26 forcebalance::liquid.Liquid::w_kappa [inherited]

Definition at line 408 of file liquid.py.

8.33.4.27 forcebalance::liquid.Liquid::w_rho [inherited]

Density.

Enthalpy of vaporization. Thermal expansion coefficient. Isothermal compressibility. Isobaric heat capacity. Static dielectric constant. Estimation of errors.

Definition at line 408 of file liquid.py.

8.33.4.28 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- tinkerio.py

8.34 forcebalance.Mol2.mol2 Class Reference

This is to manage one mol2 series of lines on the form:

Public Member Functions

- def __init__
- def __repr__
- def out
- def set_mol_name

  bond identifier (integer, starting from 1)
- def set_num_atoms

  number of atoms (integer)
- def set_num_bonds

  number of bonds (integer)
- def set_num_subst

  number of substructures (integer)
- def set_num_feat

  number of features (integer)
- def set_num_sets

  number of sets (integer)
- def set_mol_type

  bond identifier (integer, starting from 1)
- def set_charge_type

  bond identifier (integer, starting from 1)
- def parse

  Parse a series of text lines, and setup compound information.
- def get_atom

  return the atom instance given its atom identifier
- def get_bonded_atoms

  return a dictionnary of atom instances bonded to the atom, and their types
- def set_donnor_acceptor_atoms

  modify atom types to specify donnor, acceptor, or both

Public Attributes

- mol_name
- num_atoms
- num_bonds
- num_subst
- num_feat
- num_sets
- mol_type
- charge_type
- comments
- atoms
- bonds

8.34.1 Detailed Description

This is to manage one mol2 series of lines on the form:

```
@<TRIPOS>MOLECULE
CDK2.xray.inh1.1E9H
 34 37 0 0 0
SMALL
GASTEIGER
Energy = 0

@<TRIPOS>ATOM
      1 C1          5.4790   42.2880   49.5910 C.ar    1  <1>         0.0424
      2 C2          4.4740   42.6430   50.5070 C.ar    1  <1>         0.0447
@<TRIPOS>BOND
     1     1     2   ar
     2     1     6   ar
```

Definition at line 288 of file Mol2.py.

8.34.2 Constructor & Destructor Documentation

8.34.2.1 def forcebalance.Mol2.mol2.__init__ (*self, data*)

Definition at line 289 of file Mol2.py.

8.34.3 Member Function Documentation

8.34.3.1 def forcebalance.Mol2.mol2.__repr__ (*self*)

Definition at line 305 of file Mol2.py.

Here is the call graph for this function:

8.34.3.2 def forcebalance.Mol2.mol2.get_atom (*self, id*)

return the atom instance given its atom identifier

Definition at line 461 of file Mol2.py.

Here is the call graph for this function:

8.34.3.3 def forcebalance.Mol2.mol2.get_bonded_atoms (*self, id*)

return a dictionnary of atom instances bonded to the atom, and their types

Definition at line 475 of file Mol2.py.

8.34.3.4 def forcebalance.Mol2.mol2.out (*self, f* = `sys.stdout`)

Definition at line 325 of file Mol2.py.

Here is the call graph for this function:

8.34.3.5 def forcebalance.Mol2.mol2.parse (*self, data*)

Parse a series of text lines, and setup compound information.

Definition at line 405 of file Mol2.py.

Here is the call graph for this function:

8.34.3.6 def forcebalance.Mol2.mol2.set_charge_type (*self, charge_type* = `None`)

bond identifier (integer, starting from 1)

Definition at line 395 of file Mol2.py.

Here is the call graph for this function:

8.34.3.7 def forcebalance.Mol2.mol2.set_donnor_acceptor_atoms (*self, verbose* = 0)

modify atom types to specify donnor, acceptor, or both

Definition at line 490 of file Mol2.py.

Here is the call graph for this function:

8.34.3.8 def forcebalance.Mol2.mol2.set_mol_name (*self, mol_name* = None)

bond identifier (integer, starting from 1)

Definition at line 332 of file Mol2.py.

Here is the call graph for this function:

8.34.3.9 def forcebalance.Mol2.mol2.set_mol_type (*self, mol_type* = None)

bond identifier (integer, starting from 1)

Definition at line 386 of file Mol2.py.

Here is the call graph for this function:

8.34.3.10 def forcebalance.Mol2.mol2.set_num_atoms (*self, num_atoms* = `None`)

number of atoms (integer)

Definition at line 341 of file Mol2.py.

Here is the call graph for this function:

8.34.3.11 def forcebalance.Mol2.mol2.set_num_bonds (*self, num_bonds* = `None`)

number of bonds (integer)

Definition at line 350 of file Mol2.py.

Here is the call graph for this function:

8.34.3.12 def forcebalance.Mol2.mol2.set_num_feat (*self, num_feat* = `None`)

number of features (integer)

Definition at line 368 of file Mol2.py.

Here is the call graph for this function:

8.34.3.13 def forcebalance.Mol2.mol2.set_num_sets (*self, num_sets* = `None`)

number of sets (integer)

Definition at line 377 of file Mol2.py.

Here is the call graph for this function:

8.34.3.14 def forcebalance.Mol2.mol2.set_num_subst (*self, num_subst* = None)

number of substructures (integer)

Definition at line 359 of file Mol2.py.

Here is the call graph for this function:

8.34.4 Member Data Documentation

8.34.4.1 forcebalance::Mol2.mol2::atoms

Definition at line 289 of file Mol2.py.

8.34.4.2 forcebalance::Mol2.mol2::bonds

Definition at line 289 of file Mol2.py.

8.34.4.3 forcebalance::Mol2.mol2::charge_type

Definition at line 289 of file Mol2.py.

8.34.4.4 forcebalance::Mol2.mol2::comments

Definition at line 289 of file Mol2.py.

8.34.4.5 forcebalance::Mol2.mol2::mol_name

Definition at line 289 of file Mol2.py.

8.34.4.6 forcebalance::Mol2.mol2::mol_type

Definition at line 289 of file Mol2.py.

8.34.4.7 forcebalance::Mol2.mol2::num_atoms

Definition at line 289 of file Mol2.py.

8.34.4.8 forcebalance::Mol2.mol2::num_bonds

Definition at line 289 of file Mol2.py.

8.34.4.9 forcebalance::Mol2.mol2::num_feat

Definition at line 289 of file Mol2.py.

8.34.4.10 forcebalance::Mol2.mol2::num_sets

Definition at line 289 of file Mol2.py.

8.34.4.11 forcebalance::Mol2.mol2::num_subst

Definition at line 289 of file Mol2.py.

The documentation for this class was generated from the following file:

- Mol2.py

8.35 forcebalance.Mol2.mol2_atom Class Reference

This is to manage mol2 atomic lines on the form: 1 C1 5.4790 42.2880 49.5910 C.ar 1 <1> 0.0424.

Public Member Functions

- def __init__

  if data is passed, it will be installed
- def parse

  split the text line into a series of properties
- def __repr__

  assemble the properties as a text line, and return it
- def set_atom_id

  atom identifier (integer, starting from 1)
- def set_atom_name

  The name of the atom (string)
- def set_crds

  the coordinates of the atom
- def set_atom_type

  The mol2 type of the atom.
- def set_subst_id

  substructure identifier
- def set_subst_name

  substructure name
- def set_charge

  atomic charge
- def set_status_bit

  Never to use (in theory)

Public Attributes

- atom_id
- atom_name
- x
- y
- z
- atom_type
- subst_id
- subst_name
- charge
- status_bit

8.35.1 Detailed Description

This is to manage mol2 atomic lines on the form: 1 C1 5.4790 42.2880 49.5910 C.ar 1 <1> 0.0424.

Definition at line 32 of file Mol2.py.

8.35.2 Constructor & Destructor Documentation

8.35.2.1 def forcebalance.Mol2.mol2_atom.__init__ (*self*, *data* = `None`)

if data is passed, it will be installed

Definition at line 37 of file Mol2.py.

8.35.3 Member Function Documentation

8.35.3.1 def forcebalance.Mol2.mol2_atom.__repr__ (*self*)

assemble the properties as a text line, and return it

Definition at line 78 of file Mol2.py.

Here is the call graph for this function:

8.35.3.2 def forcebalance.Mol2.mol2_atom.parse (*self*, *data*)

split the text line into a series of properties

Definition at line 56 of file Mol2.py.

Here is the call graph for this function:

8.35.3.3 def forcebalance.Mol2.mol2_atom.set_atom_id (*self, atom_id* = None)

atom identifier (integer, starting from 1)

Definition at line 90 of file Mol2.py.

Here is the call graph for this function:

8.35.3.4 def forcebalance.Mol2.mol2_atom.set_atom_name (*self, atom_name* = None)

The name of the atom (string)

Definition at line 99 of file Mol2.py.

Here is the call graph for this function:

8.35.3.5 def forcebalance.Mol2.mol2_atom.set_atom_type (*self, atom_type* = None)

The mol2 type of the atom.

Definition at line 119 of file Mol2.py.

Here is the call graph for this function:

8.35.3.6 def forcebalance.Mol2.mol2_atom.set_charge (*self, charge* = None)

atomic charge

Definition at line 146 of file Mol2.py.

8.35.3.7 def forcebalance.Mol2.mol2_atom.set_crds (*self, x* = None, *y* = None, *z* = None)

the coordinates of the atom

Definition at line 108 of file Mol2.py.

Here is the call graph for this function:

8.35.3.8 def forcebalance.Mol2.mol2_atom.set_status_bit (*self, status_bit* = `None`)

Never to use (in theory)

Definition at line 155 of file Mol2.py.

Here is the call graph for this function:

8.35.3.9 def forcebalance.Mol2.mol2_atom.set_subst_id (*self, subst_id* = `None`)

substructure identifier

Definition at line 128 of file Mol2.py.

Here is the call graph for this function:

8.35.3.10 def forcebalance.Mol2.mol2_atom.set_subst_name (*self, subst_name* = `None`)

substructure name

Definition at line 137 of file Mol2.py.

Here is the call graph for this function:

8.35.4 Member Data Documentation

8.35.4.1 forcebalance::Mol2.mol2_atom::atom_id

Definition at line 37 of file Mol2.py.

8.35.4.2 forcebalance::Mol2.mol2_atom::atom_name

Definition at line 37 of file Mol2.py.

8.35.4.3 forcebalance::Mol2.mol2_atom::atom_type

Definition at line 37 of file Mol2.py.

8.35.4.4 forcebalance::Mol2.mol2_atom::charge

Definition at line 37 of file Mol2.py.

8.35.4.5 forcebalance::Mol2.mol2_atom::status_bit

Definition at line 37 of file Mol2.py.

8.35.4.6 forcebalance::Mol2.mol2_atom::subst_id

Definition at line 37 of file Mol2.py.

8.35.4.7 forcebalance::Mol2.mol2_atom::subst_name

Definition at line 37 of file Mol2.py.

8.35.4.8 forcebalance::Mol2.mol2_atom::x

Definition at line 37 of file Mol2.py.

8.35.4.9 forcebalance::Mol2.mol2_atom::y

Definition at line 37 of file Mol2.py.

8.35.4.10 forcebalance::Mol2.mol2_atom::z

Definition at line 37 of file Mol2.py.

The documentation for this class was generated from the following file:

- Mol2.py

8.36 forcebalance.Mol2.mol2_bond Class Reference

This is to manage mol2 bond lines on the form: 1 1 2 ar.

Public Member Functions

- def __init__

  if data is passed, it will be installed
- def __repr__
- def parse

  split the text line into a series of properties
- def set_bond_id

  bond identifier (integer, starting from 1)
- def set_origin_atom_id

  the origin atom identifier (integer)
- def set_target_atom_id

  the target atom identifier (integer)

- def set_bond_type

  bond type (string) one of: 1 = single 2 = double 3 = triple am = amide ar = aromatic du = dummy un = unknown nc = not connected
- def set_status_bit

  Never to use (in theory)

Public Attributes

- bond_id
- origin_atom_id
- target_atom_id
- bond_type
- status_bit

8.36.1 Detailed Description

This is to manage mol2 bond lines on the form: 1 1 2 ar.

Definition at line 172 of file Mol2.py.

8.36.2 Constructor & Destructor Documentation

8.36.2.1 def forcebalance.Mol2.mol2_bond.__init__ (*self, data* = `None`)

if data is passed, it will be installed

Definition at line 177 of file Mol2.py.

8.36.3 Member Function Documentation

8.36.3.1 def forcebalance.Mol2.mol2_bond.__repr__ (*self*)

Definition at line 186 of file Mol2.py.

Here is the call graph for this function:

8.36.3.2 def forcebalance.Mol2.mol2_bond.parse (*self, data*)

split the text line into a series of properties

Definition at line 197 of file Mol2.py.

8.36.3.3 def forcebalance.Mol2.mol2_bond.set_bond_id (*self, bond_id* = None)

bond identifier (integer, starting from 1)

Definition at line 214 of file Mol2.py.

Here is the call graph for this function:

8.36.3.4 def forcebalance.Mol2.mol2_bond.set_bond_type (*self, bond_type* = None)

bond type (string) one of: 1 = single 2 = double 3 = triple am = amide ar = aromatic du = dummy un = unknown nc = not connected

Definition at line 250 of file Mol2.py.

8.36.3.5 def forcebalance.Mol2.mol2_bond.set_origin_atom_id (*self, origin_atom_id* = None)

the origin atom identifier (integer)

Definition at line 223 of file Mol2.py.

8.36.3.6 def forcebalance.Mol2.mol2_bond.set_status_bit (*self, status_bit* = None)

Never to use (in theory)

Definition at line 259 of file Mol2.py.

Here is the call graph for this function:

8.36.3.7 def forcebalance.Mol2.mol2_bond.set_target_atom_id (*self, target_atom_id* = None)

the target atom identifier (integer)

Definition at line 232 of file Mol2.py.

Here is the call graph for this function:

8.36.4 Member Data Documentation

8.36.4.1 forcebalance::Mol2.mol2_bond::bond_id

Definition at line 177 of file Mol2.py.

8.36.4.2 forcebalance::Mol2.mol2_bond::bond_type

Definition at line 177 of file Mol2.py.

8.36.4.3 forcebalance::Mol2.mol2_bond::origin_atom_id

Definition at line 177 of file Mol2.py.

8.36.4.4 forcebalance::Mol2.mol2_bond::status_bit

Definition at line 197 of file Mol2.py.

8.36.4.5 forcebalance::Mol2.mol2_bond::target_atom_id

Definition at line 177 of file Mol2.py.

The documentation for this class was generated from the following file:

- Mol2.py

8.37 forcebalance.amberio.Mol2_Reader Class Reference

Finite state machine for parsing Mol2 force field file.

Inheritance diagram for forcebalance.amberio.Mol2_Reader:

Collaboration diagram for forcebalance.amberio.Mol2_Reader:

Public Member Functions

- def __init__
- def feed
- def Split
- def Whites
- def build_pid

  Returns the parameter type (e.g.

Public Attributes

- pdict

  The parameter dictionary (defined in this file)
- atom

  The atom numbers in the interaction (stored in the parser)
- atomnames

  The mol2 file provides a list of atom names.
- section

  The section that we're in.
- mol
- itype
- suffix
- molatom

  The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.
- ln
- adict

  The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.
- Molecules
- AtomTypes

8.37.1 Detailed Description

Finite state machine for parsing Mol2 force field file.

(just for parameterizing the charges)

Definition at line 43 of file amberio.py.

8.37.2 Constructor & Destructor Documentation

8.37.2.1 def forcebalance.amberio.Mol2_Reader.__init__ (*self, fnm*)

Reimplemented from forcebalance.BaseReader.

Definition at line 45 of file amberio.py.

8.37.3 Member Function Documentation

8.37.3.1 def forcebalance.BaseReader.build_pid (*self, pfld*) [inherited]

Returns the parameter type (e.g.

K in BONDSK) based on the current interaction type.

Both the 'pdict' dictionary (see gmxio.pdict) and the interaction type 'state' (here, BONDS) are needed to get the parameter type.

If, however, 'pdict' does not contain the ptype value, a suitable substitute is simply the field number.

Note that if the interaction type state is not set, then it defaults to the file name, so a generic parameter ID is 'filename.-line_num.field_num'

Reimplemented in forcebalance.psi4io.Grid_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 107 of file __init__.py.

8.37.3.2 def forcebalance.amberio.Mol2_Reader.feed (*self, line*)

Reimplemented from forcebalance.BaseReader.

Definition at line 59 of file amberio.py.

8.37.3.3 def forcebalance.BaseReader.Split (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 82 of file __init__.py.

Here is the call graph for this function:

8.37.3.4 def forcebalance.BaseReader.Whites (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 85 of file __init__.py.

Here is the call graph for this function:

8.37.4 Member Data Documentation

8.37.4.1 forcebalance.BaseReader::adict [inherited]

The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.

Reimplemented in forcebalance.amberio.FrcMod_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 67 of file __init__.py.

8.37.4.2 forcebalance::amberio.Mol2_Reader::atom

The atom numbers in the interaction (stored in the parser)

Definition at line 47 of file amberio.py.

8.37.4.3 forcebalance::amberio.Mol2_Reader::atomnames

The mol2 file provides a list of atom names.

Definition at line 48 of file amberio.py.

8.37.4.4 forcebalance.BaseReader::AtomTypes [inherited]

Definition at line 71 of file __init__.py.

8.37.4.5 forcebalance::amberio.Mol2_Reader::itype

Reimplemented from forcebalance.BaseReader.

Definition at line 59 of file amberio.py.

8.37.4.6 forcebalance.BaseReader::ln [inherited]

Definition at line 66 of file __init__.py.

8.37.4.7 forcebalance::amberio.Mol2_Reader::mol

Definition at line 49 of file amberio.py.

8.37.4.8 forcebalance::amberio.Mol2_Reader::molatom

The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.

self.moleculedict = OrderedDict() The listing of 'RES:ATOMNAMES' for atom names in the line This is obviously a placeholder.

Reimplemented from forcebalance.BaseReader.

Definition at line 59 of file amberio.py.

8.37.4.9 forcebalance.BaseReader::Molecules [inherited]

Definition at line 71 of file __init__.py.

8.37.4.10 forcebalance::amberio.Mol2_Reader::pdict

The parameter dictionary (defined in this file)

Reimplemented from forcebalance.BaseReader.

Definition at line 46 of file amberio.py.

8.37.4.11 forcebalance::amberio.Mol2_Reader::section

The section that we're in.

Definition at line 49 of file amberio.py.

8.37.4.12 forcebalance::amberio.Mol2_Reader::suffix

Reimplemented from forcebalance.BaseReader.

Definition at line 59 of file amberio.py.

The documentation for this class was generated from the following file:

- amberio.py

8.38 forcebalance.mol2io.Mol2_Reader Class Reference

Finite state machine for parsing Mol2 force field file.

Inheritance diagram for forcebalance.mol2io.Mol2_Reader:

Collaboration diagram for forcebalance.mol2io.Mol2_Reader:

Public Member Functions

- def __init__
- def feed
- def Split
- def Whites
- def build_pid

  Returns the parameter type (e.g.

Public Attributes

- pdict

  The parameter dictionary (defined in this file)
- atom

  The atom numbers in the interaction (stored in the parser)
- itype
- suffix
- ln
- adict

  The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.
- molatom

  The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.
- Molecules
- AtomTypes

8.38.1 Detailed Description

Finite state machine for parsing Mol2 force field file.

(just for parameterizing the charges)

Definition at line 22 of file mol2io.py.

8.38.2 Constructor & Destructor Documentation

8.38.2.1 def forcebalance.mol2io.Mol2_Reader.__init__ (*self, fnm*)

Reimplemented from forcebalance.BaseReader.

Definition at line 24 of file mol2io.py.

8.38.3 Member Function Documentation

8.38.3.1 def forcebalance.BaseReader.build_pid (*self, pfld*) [inherited]

Returns the parameter type (e.g.

K in BONDSK) based on the current interaction type.

Both the 'pdict' dictionary (see gmxio.pdict) and the interaction type 'state' (here, BONDS) are needed to get the parameter type.

If, however, 'pdict' does not contain the ptype value, a suitable substitute is simply the field number.

Note that if the interaction type state is not set, then it defaults to the file name, so a generic parameter ID is 'filename.-line_num.field_num'

Reimplemented in forcebalance.psi4io.Grid_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 107 of file __init__.py.

8.38.3.2 def forcebalance.mol2io.Mol2_Reader.feed (*self, line*)

Reimplemented from forcebalance.BaseReader.

Definition at line 32 of file mol2io.py.

8.38.3.3 def forcebalance.BaseReader.Split (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 82 of file __init__.py.

Here is the call graph for this function:

8.38.3.4 def forcebalance.BaseReader.Whites (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 85 of file __init__.py.

Here is the call graph for this function:

8.38.4 Member Data Documentation

8.38.4.1 forcebalance.BaseReader::adict [inherited]

The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.

Reimplemented in forcebalance.amberio.FrcMod_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 67 of file __init__.py.

8.38.4.2 forcebalance::mol2io.Mol2_Reader::atom

The atom numbers in the interaction (stored in the parser)

Definition at line 26 of file mol2io.py.

8.38.4.3 forcebalance.BaseReader::AtomTypes [inherited]

Definition at line 71 of file __init__.py.

8.38.4.4 forcebalance::mol2io.Mol2_Reader::itype

Reimplemented from forcebalance.BaseReader.

Definition at line 32 of file mol2io.py.

8.38.4.5 forcebalance.BaseReader::ln [inherited]

Definition at line 66 of file __init__.py.

8.38.4.6 forcebalance.BaseReader::molatom [inherited]

The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.

self.moleculedict = OrderedDict() The listing of 'RES:ATOMNAMES' for atom names in the line This is obviously a placeholder.

Reimplemented in forcebalance.gmxio.ITP_Reader, and forcebalance.amberio.Mol2_Reader.

Definition at line 71 of file __init__.py.

8.38.4.7 forcebalance.BaseReader::Molecules [inherited]

Definition at line 71 of file __init__.py.

8.38.4.8 forcebalance::mol2io.Mol2_Reader::pdict

The parameter dictionary (defined in this file)

Reimplemented from forcebalance.BaseReader.

Definition at line 25 of file mol2io.py.

8.38.4.9 forcebalance::mol2io.Mol2_Reader::suffix

Reimplemented from forcebalance.BaseReader.

Definition at line 32 of file mol2io.py.

The documentation for this class was generated from the following file:

- mol2io.py

8.39 forcebalance.Mol2.mol2_set Class Reference

Public Member Functions

- def __init__

  A collection is organized as a dictionnary of compounds self.num_compounds : the number of compounds self.-compounds : the dictionnary of compounds data : the data to setup the set subset: it is possible to specify a subset of the compounds to load, based on their mol_name identifiers.
- def parse

  parse a list of lines, detect compounds, load them only load the subset if specified.

Public Attributes

- num_compounds
- comments
- compounds

8.39.1 Detailed Description

Definition at line 568 of file Mol2.py.

8.39.2 Constructor & Destructor Documentation

8.39.2.1 def forcebalance.Mol2.mol2_set.__init__ (*self, data* = `None`, *subset* = `None`)

A collection is organized as a dictionnary of compounds self.num_compounds : the number of compounds self.-compounds : the dictionnary of compounds data : the data to setup the set subset: it is possible to specify a subset of the compounds to load, based on their mol_name identifiers.

Definition at line 577 of file Mol2.py.

8.39.3 Member Function Documentation

8.39.3.1 def forcebalance.Mol2.mol2_set.parse (*self, data, subset* = `None`)

parse a list of lines, detect compounds, load them only load the subset if specified.

Definition at line 621 of file Mol2.py.

8.39.4 Member Data Documentation

8.39.4.1 forcebalance::Mol2.mol2_set::comments

Definition at line 577 of file Mol2.py.

8.39.4.2 forcebalance::Mol2.mol2_set::compounds

Definition at line 577 of file Mol2.py.

8.39.4.3 forcebalance::Mol2.mol2_set::num_compounds

Definition at line 577 of file Mol2.py.

The documentation for this class was generated from the following file:

- Mol2.py

8.40 forcebalance.molecule.Molecule Class Reference

Lee-Ping's general file format conversion class.

Public Member Functions

- def __len__

  Return the number of frames in the trajectory.
- def __getattr__

  Whenever we try to get a class attribute, it first tries to get the attribute from the Data dictionary.
- def __setattr__

  Whenever we try to get a class attribute, it first tries to get the attribute from the Data dictionary.
- def __getitem__

  The Molecule class has list-like behavior, so we can get slices of it.
- def __delitem__

  Similarly, in order to delete a frame, we simply perform item deletion on framewise variables.
- def __iter__

  List-like behavior for looping over trajectories.
- def __add__

  Add method for Molecule objects.
- def __iadd__

  Add method for Molecule objects.
- def append
- def __init__

  To create the Molecule object, we simply define the table of file reading/writing functions and read in a file if it is provided.
- def require
- def write
- def center_of_mass
- def radius_of_gyration
- def load_frames
- def edit_qcrems
- def add_quantum

- def add_virtual_site

  Add a virtual site to the system.
- def replace_peratom

  Replace all of the data for a certain attribute in the system from orig to want.
- def replace_peratom_conditional

  Replace all of the data for a attribute key2 from orig to want, contingent on key1 being equal to cond.
- def atom_select

  Return a copy of the object with certain atoms selected.
- def atom_stack

  Return a copy of the object with another molecule object appended.
- def align_by_moments

  Align molecules using the "moment of inertia." Note that we're following the MSMBuilder convention of using all ones for the masses.
- def align

  Align molecules.
- def build_topology

  A bare-bones implementation of the bond graph capability in the nanoreactor code.
- def measure_dihedrals

  Return a series of dihedral angles, given four atom indices numbered from zero.
- def all_pairwise_rmsd

  Find pairwise RMSD (super slow, not like the one in MSMBuilder.)
- def pathwise_rmsd

  Find RMSD between frames along path.
- def ref_rmsd

  Find RMSD to a reference frame.
- def align_center
- def openmm_positions

  Returns the Cartesian coordinates in the Molecule object in a list of OpenMM-compatible positions, so it is possible to type simulation.context.setPositions(Mol.openmm_positions()[0]) or something like that.
- def openmm_boxes

  Returns the periodic box vectors in the Molecule object in a list of OpenMM-compatible boxes, so it is possible to type simulation.context.setPeriodicBoxVectors(Mol.openmm_boxes()[0]) or something like that.
- def split

  Split the molecule object into a number of separate files (chunks), either by specifying the number of frames per chunk or the number of chunks.
- def read_xyz

  Parse a .xyz file which contains several xyz coordinates, and return their elements.
- def read_mdcrd

  Parse an AMBER .mdcrd file.
- def read_qdata
- def read_mol2
- def read_dcd
- def read_com

  Parse a Gaussian .com file and return a SINGLE-ELEMENT list of xyz coordinates (no multiple file support)
- def read_arc

  Read a TINKER .arc file.
- def read_gro

  Read a GROMACS .gro file.

- def read_charmm

  Read a CHARMM .cor (or .crd) file.
- def read_qcin

  Read a Q-Chem input file.
- def read_pdb

  Loads a PDB and returns a dictionary containing its data.
- def read_qcesp
- def read_qcout

  Q-Chem output file reader, adapted for our parser.
- def write_qcin
- def write_xyz
- def write_molproq
- def write_mdcrd
- def write_arc
- def write_gro
- def write_dcd
- def write_pdb

  Save to a PDB.
- def write_qdata

  Text quantum data format.
- def require_resid
- def require_resname
- def require_boxes

Public Attributes

- Read_Tab

  The table of file readers.
- Write_Tab

  The table of file writers.
- Funnel

  A funnel dictionary that takes redundant file types and maps them down to a few.
- positive_resid

  Creates entries like 'gromacs' : 'gromacs' and 'xyz' : 'xyz' in the Funnel.
- built_bonds
- Data
- comms

  Read in stuff if we passed in a file name, otherwise return an empty instance.
- topology

  Make sure the comment line isn't too long for i in range(len(self.comms)): self.comms[i] = self.comms[i][:100] if len(self.comms[i]) > 100 else self.comms[i] Attempt to build the topology for small systems.
- molecules
- fout

  Fill in comments.
- resid
- resname
- boxes

8.40.1 Detailed Description

Lee-Ping's general file format conversion class.

The purpose of this class is to read and write chemical file formats in a way that is convenient for research. There are highly general file format converters out there (e.g. catdcd, openbabel) but I find that writing my own class can be very helpful for specific purposes. Here are some things this class can do:

- Convert a .gro file to a .xyz file, or a .pdb file to a .dcd file. Data is stored internally, so any readable file can be converted into any writable file as long as there is sufficient information to write that file.
- Accumulate information from different files. For example, we may read A.gro to get a list of coordinates, add quantum settings from a B.in file, and write A.in (this gives us a file that we can use to run QM calculations)
- Concatenate two trajectories together as long as they're compatible. This is done by creating two Molecule objects and then simply adding them. Addition means two things: (1) Information fields missing from each class, but present in the other, are added to the sum, and (2) Appendable or per-frame fields (i.e. coordinates) are concatenated together.
- Slice trajectories using reasonable Python language. That is to say, MyMolecule[1:10] returns a new Molecule object that contains frames 2 through 10.

Next step: Read in Q-Chem output data using this too!

Special variables: These variables cannot be set manually because there is a special method associated with getting them.

na = The number of atoms. You'll get this if you use MyMol.na or MyMol['na']. na = The number of snapshots. You'll get this if you use MyMol.ns or MyMol['ns'].

Unit system: Angstroms.

Definition at line 662 of file molecule.py.

8.40.2 Constructor & Destructor Documentation

8.40.2.1 def forcebalance.molecule.Molecule.__init__ (*self, fnm* = `None`, *ftype* = `None`, *positive_resid* = `True`, *build_topology* = `True`, *kwargs*)

To create the Molecule object, we simply define the table of file reading/writing functions and read in a file if it is provided.

Definition at line 832 of file molecule.py.

8.40.3 Member Function Documentation

8.40.3.1 def forcebalance.molecule.Molecule.__add__ (*self, other*)

Add method for Molecule objects.

Definition at line 771 of file molecule.py.

Here is the call graph for this function:

8.40.3.2 def forcebalance.molecule.Molecule.__delitem__ (*self, key*)

Similarly, in order to delete a frame, we simply perform item deletion on framewise variables.

Definition at line 751 of file molecule.py.

Here is the call graph for this function:

8.40.3.3 def forcebalance.molecule.Molecule.__getattr__ (*self, key*)

Whenever we try to get a class attribute, it first tries to get the attribute from the Data dictionary.

Definition at line 682 of file molecule.py.

Here is the call graph for this function:

8.40.3.4 def forcebalance.molecule.Molecule.__getitem__ (*self, key*)

The Molecule class has list-like behavior, so we can get slices of it.

If we say MyMolecule[0:10], then we'll return a copy of MyMolecule with frames 0 through 9.

Definition at line 730 of file molecule.py.

Here is the call graph for this function:

8.40.3.5 def forcebalance.molecule.Molecule.__iadd__ (*self, other*)

Add method for Molecule objects.

Definition at line 801 of file molecule.py.

Here is the call graph for this function:

8.40.3.6 def forcebalance.molecule.Molecule.__iter__ (*self*)

List-like behavior for looping over trajectories.

Note that these values are returned by reference. Note that this is intended to be more efficient than __getitem__, so when we loop over a trajectory, it's best to go "for m in M" instead of "for i in range(len(M)): m = M[i]"

Definition at line 760 of file molecule.py.

Here is the call graph for this function:

8.40.3.7 def forcebalance.molecule.Molecule.__len__ (*self*)

Return the number of frames in the trajectory.

Definition at line 666 of file molecule.py.

8.40.3.8 def forcebalance.molecule.Molecule.__setattr__ (*self, key, value*)

Whenever we try to get a class attribute, it first tries to get the attribute from the Data dictionary.

Definition at line 718 of file molecule.py.

Here is the call graph for this function:

8.40.3.9 def forcebalance.molecule.Molecule.add_quantum (*self, other*)

Definition at line 1014 of file molecule.py.

Here is the call graph for this function:

8.40.3.10 def forcebalance.molecule.Molecule.add_virtual_site (*self, idx, kwargs*)

Add a virtual site to the system.

This does NOT set the position of the virtual site; it sits at the origin.

Definition at line 1026 of file molecule.py.

8.40.3.11 def forcebalance.molecule.Molecule.align (*self, smooth* = `False`, *center* = `True`, *select* = `None`)

Align molecules.

Has the option to create smooth trajectories (align each frame to the previous one) or to align each frame to the first one.

Also has the option to remove the center of mass.

Provide a list of atom indices to align along selected atoms.

Definition at line 1166 of file molecule.py.

Here is the call graph for this function:

8.40.3.12 def forcebalance.molecule.Molecule.align_by_moments (*self*)

Align molecules using the "moment of inertia." Note that we're following the MSMBuilder convention of using all ones for the masses.

Definition at line 1145 of file molecule.py.

8.40.3.13 def forcebalance.molecule.Molecule.align_center (*self*)

Definition at line 1364 of file molecule.py.

8.40.3.14 def forcebalance.molecule.Molecule.all_pairwise_rmsd (*self*)

Find pairwise RMSD (super slow, not like the one in MSMBuilder.)

Definition at line 1315 of file molecule.py.

Here is the call graph for this function:

8.40.3.15 def forcebalance.molecule.Molecule.append (*self, other*)

Definition at line 825 of file molecule.py.

Here is the call graph for this function:

8.40.3.16 def forcebalance.molecule.Molecule.atom_select (*self, atomslice*)

Return a copy of the object with certain atoms selected.

Takes an integer, list or array as argument.

Definition at line 1064 of file molecule.py.

Here is the call graph for this function:

8.40.3.17 def forcebalance.molecule.Molecule.atom_stack (*self, other*)

Return a copy of the object with another molecule object appended.

WARNING: This function may invalidate stuff like QM energies.

Definition at line 1101 of file molecule.py.

Here is the call graph for this function:

8.40.3.18 def forcebalance.molecule.Molecule.build_topology (*self, sn* = `None`, *Fac* = `1.2`)

A bare-bones implementation of the bond graph capability in the nanoreactor code.

Returns a NetworkX graph that depicts the molecular topology, which might be useful for stuff. Provide, optionally, the frame number used to compute the topology.

Definition at line 1191 of file molecule.py.

Here is the call graph for this function:

8.40.3.19 def forcebalance.molecule.Molecule.center_of_mass (*self*)

Definition at line 971 of file molecule.py.

8.40.3.20 def forcebalance.molecule.Molecule.edit_qcrems (*self, in_dict, subcalc* = `None`)

Definition at line 1005 of file molecule.py.

Here is the call graph for this function:

8.40.3.21 def forcebalance.molecule.Molecule.load_frames (*self, fnm*)

Definition at line 998 of file molecule.py.

Here is the call graph for this function:

8.40.3.22 def forcebalance.molecule.Molecule.measure_dihedrals (*self, i, j, k, l*)

Return a series of dihedral angles, given four atom indices numbered from zero.

Definition at line 1288 of file molecule.py.

Here is the call graph for this function:

8.40.3.23 def forcebalance.molecule.Molecule.openmm_boxes (*self*)

Returns the periodic box vectors in the Molecule object in a list of OpenMM-compatible boxes, so it is possible to type simulation.context.setPeriodicBoxVectors(Mol.openmm_boxes()[0]) or something like that.

Definition at line 1390 of file molecule.py.

8.40.3.24 def forcebalance.molecule.Molecule.openmm_positions (*self*)

Returns the Cartesian coordinates in the Molecule object in a list of OpenMM-compatible positions, so it is possible to type simulation.context.setPositions(Mol.openmm_positions()[0]) or something like that.

Definition at line 1373 of file molecule.py.

8.40.3.25 def forcebalance.molecule.Molecule.pathwise_rmsd (*self*)

Find RMSD between frames along path.

Definition at line 1333 of file molecule.py.

Here is the call graph for this function:

8.40.3.26 def forcebalance.molecule.Molecule.radius_of_gyration (*self*)

Definition at line 975 of file molecule.py.

Here is the call graph for this function:

8.40.3.27 def forcebalance.molecule.Molecule.read_arc (*self, fnm*)

Read a TINKER .arc file.

Parameters

in	*fnm*	The input file name

Returns

xyzs A list for the XYZ coordinates.
resid The residue ID numbers. These are not easy to get!
elem A list of chemical elements in the XYZ file
comms A single-element list for the comment.
tinkersuf The suffix that comes after lines in the XYZ coordinates; this is usually topology info

Definition at line 1671 of file molecule.py.

Here is the call graph for this function:

8.40.3.28 def forcebalance.molecule.Molecule.read_charmm (*self, fnm*)

Read a CHARMM .cor (or .crd) file.

Definition at line 1815 of file molecule.py.

Here is the call graph for this function:

8.40.3.29 def forcebalance.molecule.Molecule.read_com (*self, fnm*)

Parse a Gaussian .com file and return a SINGLE-ELEMENT list of xyz coordinates (no multiple file support)

Parameters

in	*fnm*	The input file name

Returns

elem A list of chemical elements in the XYZ file
comms A single-element list for the comment.
xyzs A single-element list for the XYZ coordinates.
charge The total charge of the system.
mult The spin multiplicity of the system.

Definition at line 1627 of file molecule.py.

Here is the call graph for this function:

8.40.3.30 def forcebalance.molecule.Molecule.read_dcd (*self, fnm*)

Definition at line 1588 of file molecule.py.

Here is the call graph for this function:

8.40.3.31 def forcebalance.molecule.Molecule.read_gro (*self, fnm*)

Read a GROMACS .gro file.

Definition at line 1735 of file molecule.py.

Here is the call graph for this function:

8.40.3.32 def forcebalance.molecule.Molecule.read_mdcrd (*self, fnm*)

Parse an AMBER .mdcrd file.

This requires at least the number of atoms. This will FAIL for monatomic trajectories (but who the heck makes those?)

Parameters

in	*fnm*	The input file name

Returns

xyzs A list of XYZ coordinates (number of snapshots times number of atoms)
boxes Boxes (if present.)

Definition at line 1478 of file molecule.py.

Here is the call graph for this function:

8.40.3.33 def forcebalance.molecule.Molecule.read_mol2 (*self, fnm*)

Definition at line 1539 of file molecule.py.

Here is the call graph for this function:

8.40.3.34 def forcebalance.molecule.Molecule.read_pdb (*self, fnm*)

Loads a PDB and returns a dictionary containing its data.

Definition at line 1998 of file molecule.py.

Here is the call graph for this function:

8.40.3.35 def forcebalance.molecule.Molecule.read_qcesp (*self, fnm*)

Definition at line 2073 of file molecule.py.

8.40.3.36 def forcebalance.molecule.Molecule.read_qcin (*self, fnm*)

Read a Q-Chem input file.

These files can be very complicated, and I can't write a completely general parser for them. It is important to keep our goal in mind:

1) The main goal is to convert a trajectory to Q-Chem input files with identical calculation settings.

2) When we print the Q-Chem file, we should preserve the line ordering of the 'rem' section, but also be able to add 'rem' options at the end.

3) We should accommodate the use case that the Q-Chem file may have follow-up calculations delimited by '@@'.

4) We can read in all of the xyz's as a trajectory, but only the Q-Chem settings belonging to the first xyz will be saved.

Definition at line 1884 of file molecule.py.

Here is the call graph for this function:

8.40.3.37 def forcebalance.molecule.Molecule.read_qcout (*self, fnm, maxopt* = `1`)

Q-Chem output file reader, adapted for our parser.

Q-Chem output files are very flexible and there's no way I can account for all of them. Here's what I am able to account for:

A list of:

- Coordinates
- Energies
- Forces

Calling with maxopt = 1 will result in a successful read (with warning) even when maximum optimization cycles are reached.

Note that each step in a geometry optimization counts as a frame.

As with all Q-Chem output files, note that successive calculations can have different numbers of atoms.

Definition at line 2105 of file molecule.py.

Here is the call graph for this function:

8.40.3.38 def forcebalance.molecule.Molecule.read_qdata (*self, fnm*)

Definition at line 1503 of file molecule.py.

Here is the call graph for this function:

8.40.3.39 def forcebalance.molecule.Molecule.read_xyz (*self, fnm*)

Parse a .xyz file which contains several xyz coordinates, and return their elements.

Parameters

in	*fnm*	The input file name

Returns

elem A list of chemical elements in the XYZ file
comms A list of comments.
xyzs A list of XYZ coordinates (number of snapshots times number of atoms)

Definition at line 1431 of file molecule.py.

Here is the call graph for this function:

8.40.3.40 def forcebalance.molecule.Molecule.ref_rmsd (*self, i*)

Find RMSD to a reference frame.

Definition at line 1350 of file molecule.py.

8.40.3.41 def forcebalance.molecule.Molecule.replace_peratom (*self, key, orig, want*)

Replace all of the data for a certain attribute in the system from orig to want.

Definition at line 1043 of file molecule.py.

8.40.3.42 def forcebalance.molecule.Molecule.replace_peratom_conditional (*self, key1, cond, key2, orig, want*)

Replace all of the data for a attribute key2 from orig to want, contingent on key1 being equal to cond.

For instance: replace H1 with H2 if resname is SOL.

Definition at line 1054 of file molecule.py.

Here is the call graph for this function:

8.40.3.43 def forcebalance.molecule.Molecule.require (*self, args*)

Definition at line 922 of file molecule.py.

Here is the call graph for this function:

8.40.3.44 def forcebalance.molecule.Molecule.require_boxes (*self*)

Definition at line 2595 of file molecule.py.

8.40.3.45 def forcebalance.molecule.Molecule.require_resid (*self*)

Definition at line 2582 of file molecule.py.

8.40.3.46 def forcebalance.molecule.Molecule.require_resname (*self*)

Definition at line 2590 of file molecule.py.

8.40.3.47 def forcebalance.molecule.Molecule.split (*self, fnm =* `None`, *ftype =* `None`, *method =* `"chunks"`, *num =* `None`)

Split the molecule object into a number of separate files (chunks), either by specifying the number of frames per chunk or the number of chunks.

Only relevant for "trajectories". The type of file may be specified; if they aren't specified then the original file type is used.

The output file names are [name].[numbers].[extension] where [name] can be specified by passing 'fnm' or taken from the object's 'fnm' attribute by default. [numbers] are integers ranging from the lowest to the highest chunk number, prepended by zeros.

If the number of chunks / frames is not specified, then one file is written for each frame.

Returns

fnms A list of the file names that were written.

Definition at line 1413 of file molecule.py.

Here is the call graph for this function:

8.40.3.48 def forcebalance.molecule.Molecule.write (*self, fnm =* `None`, *ftype =* `None`, *append =* `False`, *select =* `None`)

Definition at line 937 of file molecule.py.

Here is the call graph for this function:

8.40.3.49 def forcebalance.molecule.Molecule.write_arc (*self, select*)

Definition at line 2373 of file molecule.py.

8.40.3.50 def forcebalance.molecule.Molecule.write_dcd (*self, select*)

Definition at line 2412 of file molecule.py.

Here is the call graph for this function:

8.40.3.51 def forcebalance.molecule.Molecule.write_gro (*self, select*)

Definition at line 2385 of file molecule.py.

Here is the call graph for this function:

8.40.3.52 def forcebalance.molecule.Molecule.write_mdcrd (*self, select*)

Definition at line 2362 of file molecule.py.

Here is the call graph for this function:

8.40.3.53 def forcebalance.molecule.Molecule.write_molproq (*self, select*)

Definition at line 2350 of file molecule.py.

Here is the call graph for this function:

8.40.3.54 def forcebalance.molecule.Molecule.write_pdb (*self, select*)

Save to a PDB.

Copied wholesale from MSMBuilder. COLUMNS TYPE FIELD DEFINITION ---------- 7-11 int serial Atom serial number. 13-16 string name Atom name. 17 string altLoc Alternate location indicator. 18-20 (17-21 KAB) string resName Residue name. 22 string chainID Chain identifier. 23-26 int resSeq Residue sequence number. 27 string iCode Code for insertion of residues. 31-38 float x Orthogonal coordinates for X in Angstroms. 39-46 float y Orthogonal coordinates for Y in Angstroms. 47-54 float z Orthogonal coordinates for Z in Angstroms. 55-60 float occupancy Occupancy. 61-66 float tempFactor Temperature factor. 73-76 string segID Segment identifier, left-justified. 77-78 string element Element symbol, right-justified. 79-80 string charge Charge on the atom.

CRYST1 line, added by Lee-Ping COLUMNS TYPE FIELD DEFINITION ---------- 7-15 float a a (Angstroms). 16-24 float b b (Angstroms). 25-33 float c c (Angstroms). 34-40 float alpha alpha (degrees). 41-47 float beta beta (degrees). 48-54 float gamma gamma (degrees). 56-66 string sGroup Space group. 67-70 int z Z value.

Definition at line 2468 of file molecule.py.

Here is the call graph for this function:

8.40.3.55 def forcebalance.molecule.Molecule.write_qcin (*self, select*)

Definition at line 2293 of file molecule.py.

Here is the call graph for this function:

8.40.3.56 def forcebalance.molecule.Molecule.write_qdata (*self, select*)

Text quantum data format.

Definition at line 2561 of file molecule.py.

Here is the call graph for this function:

8.40.3.57 def forcebalance.molecule.Molecule.write_xyz (*self, select*)

Definition at line 2339 of file molecule.py.

Here is the call graph for this function:

8.40.4 Member Data Documentation

8.40.4.1 forcebalance::molecule.Molecule::boxes

Definition at line 2595 of file molecule.py.

8.40.4.2 forcebalance::molecule.Molecule::built_bonds

Definition at line 838 of file molecule.py.

8.40.4.3 forcebalance::molecule.Molecule::comms

Read in stuff if we passed in a file name, otherwise return an empty instance.

Try to determine from the file name using the extension. Actually read the file. Set member variables. Create a list of comment lines if we don't already have them from reading the file.

Definition at line 843 of file molecule.py.

8.40.4.4 forcebalance::molecule.Molecule::Data

Definition at line 838 of file molecule.py.

8.40.4.5 forcebalance::molecule.Molecule::fout

Fill in comments.

I needed to add in this line because the DCD writer requires the file name, but the other methods don't.

Definition at line 940 of file molecule.py.

8.40.4.6 forcebalance::molecule.Molecule::Funnel

A funnel dictionary that takes redundant file types and maps them down to a few.

Definition at line 836 of file molecule.py.

8.40.4.7 forcebalance::molecule.Molecule::molecules

Definition at line 847 of file molecule.py.

8.40.4.8 forcebalance::molecule.Molecule::positive_resid

Creates entries like 'gromacs' : 'gromacs' and 'xyz' : 'xyz' in the Funnel.

Definition at line 838 of file molecule.py.

8.40.4.9 forcebalance::molecule.Molecule::Read_Tab

The table of file readers.

Definition at line 833 of file molecule.py.

8.40.4.10 forcebalance::molecule.Molecule::resid

Definition at line 2582 of file molecule.py.

8.40.4.11 forcebalance::molecule.Molecule::resname

Definition at line 2590 of file molecule.py.

8.40.4.12 forcebalance::molecule.Molecule::topology

Make sure the comment line isn't too long for i in range(len(self.comms)): self.comms[i] = self.comms[i][:100] if len(self.comms[i]) $>$ 100 else self.comms[i] Attempt to build the topology for small systems.

:)

Definition at line 847 of file molecule.py.

8.40.4.13 forcebalance::molecule.Molecule::Write_Tab

The table of file writers.

Definition at line 834 of file molecule.py.

The documentation for this class was generated from the following file:

- molecule.py

8.41 forcebalance.molecule.MolfileTimestep Class Reference

Wrapper for the timestep C structure used in molfile plugins.

8.41.1 Detailed Description

Wrapper for the timestep C structure used in molfile plugins.

Definition at line 474 of file molecule.py.

The documentation for this class was generated from the following file:

- molecule.py

8.42 forcebalance.moments.Moments Class Reference

Subclass of Target for fitting force fields to multipole moments (from experiment or theory).

Inheritance diagram for forcebalance.moments.Moments:

Collaboration diagram for forcebalance.moments.Moments:

Public Member Functions

- def __init__

  Initialization.
- def read_reference_data

  Read the reference data from a file.
- def prepare_temp_directory

  Prepare the temporary directory.
- def indicate

  Print qualitative indicator.
- def unpack_moments
- def get

  Evaluate objective function.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

This method determines whether the Work Queue tasks for the current target have completed.

- def printcool_table

  Print target information in an organized table format.

- def set_option

Public Attributes

- denoms
- mfnm

  The mdata.txt file that contains the moments.

- ref_moments
- na

  Number of atoms.

- ref_eigvals
- ref_eigvecs
- calc_moments
- objective
- tempdir

  Root directory of the whole project.

- rundir

  The directory in which the simulation is running - this can be updated.

- FF

  Need the forcefield (here for now)

- xct

  Counts how often the objective function was computed.

- gct

  Counts how often the gradient was computed.

- hct

  Counts how often the Hessian was computed.

- PrintOptionDict
- verbose_options

8.42.1 Detailed Description

Subclass of Target for fitting force fields to multipole moments (from experiment or theory).

Currently Tinker is supported.

Definition at line 30 of file moments.py.

8.42.2 Constructor & Destructor Documentation

8.42.2.1 def forcebalance.moments.Moments.__init__ (*self, options, tgt_opts, forcefield*)

Initialization.

Reimplemented from forcebalance.target.Target.

Reimplemented in forcebalance.tinkerio.Moments_TINKER.

Definition at line 35 of file moments.py.

8.42.3 Member Function Documentation

8.42.3.1 def forcebalance.moments.Moments.get (*self, mvals, AGrad* = `False`, *AHess* = `False`)

Evaluate objective function.

Reimplemented from forcebalance.target.Target.

Definition at line 173 of file moments.py.

8.42.3.2 def forcebalance.target.Target.get_G (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.42.3.3 def forcebalance.target.Target.get_H (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.42.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.42.3.5 def forcebalance.moments.Moments.indicate (*self*)

Print qualitative indicator.

Definition at line 141 of file moments.py.

Here is the call graph for this function:

8.42.3.6 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.42.3.7 def forcebalance.moments.Moments.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory.

Reimplemented in forcebalance.tinkerio.Moments_TINKER.

Definition at line 136 of file moments.py.

8.42.3.8 def forcebalance.target.Target.printcool_table (*self, data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.42.3.9 def forcebalance.moments.Moments.read_reference_data (*self*)

Read the reference data from a file.

Definition at line 67 of file moments.py.

8.42.3.10 def forcebalance.target.Target.refresh_temp_directory (*self*) `[inherited]`

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.42.3.11 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = `None`, *val* = `None`, *default* = `None`, *forceprint* = `False`) [inherited]

Definition at line 32 of file __init__.py.

8.42.3.12 def forcebalance.target.Target.sget (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.42.3.13 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.42.3.14 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.42.3.15 def forcebalance.moments.Moments.unpack_moments (*self, moment_dict*)

Definition at line 167 of file moments.py.

Here is the call graph for this function:

8.42.3.16 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.42.4 Member Data Documentation

8.42.4.1 forcebalance::moments.Moments::calc_moments

Definition at line 173 of file moments.py.

8.42.4.2 forcebalance::moments.Moments::denoms

Definition at line 35 of file moments.py.

8.42.4.3 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.42.4.4 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.42.4.5 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.42.4.6 forcebalance::moments.Moments::mfnm

The mdata.txt file that contains the moments.

Definition at line 36 of file moments.py.

8.42.4.7 forcebalance::moments.Moments::na

Number of atoms.

Definition at line 68 of file moments.py.

8.42.4.8 forcebalance::moments.Moments::objective

Definition at line 173 of file moments.py.

8.42.4.9 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.42.4.10 forcebalance::moments.Moments::ref_eigvals

Definition at line 68 of file moments.py.

8.42.4.11 forcebalance::moments.Moments::ref_eigvecs

Definition at line 68 of file moments.py.

8.42.4.12 forcebalance::moments.Moments::ref_moments

Definition at line 36 of file moments.py.

8.42.4.13 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.42.4.14 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.42.4.15 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.42.4.16 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- moments.py

8.43 forcebalance.tinkerio.Moments_TINKER Class Reference

Subclass of Target for multipole moment matching using TINKER.

Inheritance diagram for forcebalance.tinkerio.Moments_TINKER:

Collaboration diagram for forcebalance.tinkerio.Moments_TINKER:

Public Member Functions

- def __init__

  Initialization.
- def prepare_temp_directory

  Prepare the temporary directory.
- def moments_driver
- def read_reference_data

  Read the reference data from a file.
- def indicate

  Print qualitative indicator.
- def unpack_moments
- def get

  Evaluate objective function.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

Stages the directory for the target, and then calls 'get'.

- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- denoms
- mfnm

  The mdata.txt file that contains the moments.
- ref_moments
- na

  Number of atoms.
- ref_eigvals
- ref_eigvecs
- calc_moments
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.43.1 Detailed Description

Subclass of Target for multipole moment matching using TINKER.

Definition at line 403 of file tinkerio.py.

8.43.2 Constructor & Destructor Documentation

8.43.2.1 def forcebalance.tinkerio.Moments_TINKER.__init__ (*self, options, tgt_opts, forcefield*)

Initialization.

Reimplemented from forcebalance.moments.Moments.

Definition at line 406 of file tinkerio.py.

Here is the call graph for this function:

8.43.3 Member Function Documentation

8.43.3.1 def forcebalance.moments.Moments.get (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

Evaluate objective function.

Reimplemented from forcebalance.target.Target.

Definition at line 173 of file moments.py.

8.43.3.2 def forcebalance.target.Target.get_G (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.43.3.3 def forcebalance.target.Target.get_H (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.43.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) `[inherited]`

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.43.3.5 def forcebalance.moments.Moments.indicate (*self*) [inherited]

Print qualitative indicator.

Definition at line 141 of file moments.py.

Here is the call graph for this function:

8.43.3.6 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.43.3.7 def forcebalance.tinkerio.Moments_TINKER.moments_driver (*self*)

Definition at line 422 of file tinkerio.py.

Here is the call graph for this function:

8.43.3.8 def forcebalance.tinkerio.Moments_TINKER.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory.

Reimplemented from forcebalance.moments.Moments.

Definition at line 411 of file tinkerio.py.

Here is the call graph for this function:

8.43.3.9 def forcebalance.target.Target.printcool_table (*self, data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) [inherited]

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.43.3.10 def forcebalance.moments.Moments.read_reference_data (*self*) [inherited]

Read the reference data from a file.

Definition at line 67 of file moments.py.

8.43.3.11 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.43.3.12 def forcebalance.BaseClass.set_option (*self*, *in_dict*, *src_key*, *dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.43.3.13 def forcebalance.target.Target.sget (*self*, *mvals*, *AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.43.3.14 def forcebalance.target.Target.stage (*self*, *mvals*, *AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.43.3.15 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.43.3.16 def forcebalance.moments.Moments.unpack_moments (*self, moment_dict*) `[inherited]`

Definition at line 167 of file moments.py.

Here is the call graph for this function:

8.43.3.17 def forcebalance.target.Target.wq_complete (*self*) `[inherited]`

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.43.4 Member Data Documentation

8.43.4.1 forcebalance::moments.Moments::calc_moments [inherited]

Definition at line 173 of file moments.py.

8.43.4.2 forcebalance::moments.Moments::denoms [inherited]

Definition at line 35 of file moments.py.

8.43.4.3 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.43.4.4 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.43.4.5 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.43.4.6 forcebalance::moments.Moments::mfnm [inherited]

The mdata.txt file that contains the moments.

Definition at line 36 of file moments.py.

8.43.4.7 forcebalance::moments.Moments::na [inherited]

Number of atoms.

Definition at line 68 of file moments.py.

8.43.4.8 forcebalance::moments.Moments::objective [inherited]

Definition at line 173 of file moments.py.

8.43.4.9 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.43.4.10 forcebalance::moments.Moments::ref_eigvals [inherited]

Definition at line 68 of file moments.py.

8.43.4.11 forcebalance::moments.Moments::ref_eigvecs [inherited]

Definition at line 68 of file moments.py.

8.43.4.12 forcebalance::moments.Moments::ref_moments [inherited]

Definition at line 36 of file moments.py.

8.43.4.13 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.43.4.14 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.43.4.15 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.43.4.16 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- tinkerio.py

8.44 forcebalance.gmxqpio.Monomer_QTPIE Class Reference

Subclass of Target for monomer properties of QTPIE (implemented within gromacs WCV branch).

Inheritance diagram for forcebalance.gmxqpio.Monomer_QTPIE:

Collaboration diagram for forcebalance.gmxqpio.Monomer_QTPIE:

Public Member Functions

- def __init__

  All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)
- def indicate

  Print qualitative indicator.
- def prepare_temp_directory
- def unpack_moments

- def get

  Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- ref_moments
- weights
- calc_moments
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.44.1 Detailed Description

Subclass of Target for monomer properties of QTPIE (implemented within gromacs WCV branch).

Definition at line 130 of file gmxqpio.py.

8.44.2 Constructor & Destructor Documentation

8.44.2.1 def forcebalance.gmxqpio.Monomer_QTPIE.__init__ (*self, options, tgt_opts, forcefield*)

All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)

If we want to add attributes that are more specific (i.e. a set of reference forces for force matching), they are added in the subclass AbInitio that inherits from Target.

Reimplemented from forcebalance.target.Target.

Definition at line 132 of file gmxqpio.py.

8.44.3 Member Function Documentation

8.44.3.1 def forcebalance.gmxqpio.Monomer_QTPIE.get (*self, mvals, AGrad* = `False`, *AHess* = `False`)

Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.

See abinitio for an example.

Reimplemented from forcebalance.target.Target.

Definition at line 221 of file gmxqpio.py.

8.44.3.2 def forcebalance.target.Target.get_G (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_-pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.44.3.3 def forcebalance.target.Target.get_H (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.44.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.44.3.5 def forcebalance.gmxqpio.Monomer_QTPIE.indicate (*self*)

Print qualitative indicator.

Definition at line 179 of file gmxqpio.py.

Here is the call graph for this function:

8.44.3.6 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.44.3.7 def forcebalance.gmxqpio.Monomer_QTPIE.prepare_temp_directory (*self, options, tgt_opts*)

Definition at line 200 of file gmxqpio.py.

Here is the call graph for this function:

8.44.3.8 def forcebalance.target.Target.printcool_table (*self*, *data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.44.3.9 def forcebalance.target.Target.refresh_temp_directory (*self*) `[inherited]`

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.44.3.10 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.44.3.11 def forcebalance.target.Target.sget (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.44.3.12 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.44.3.13 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.44.3.14 def forcebalance.gmxqpio.Monomer_QTPIE.unpack_moments (*self, moment_dict*)

Definition at line 217 of file gmxqpio.py.

Here is the call graph for this function:

8.44.3.15 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.44.4 Member Data Documentation

8.44.4.1 forcebalance::gmxqpio.Monomer_QTPIE::calc_moments

Definition at line 221 of file gmxqpio.py.

8.44.4.2 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.44.4.3 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.44.4.4 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.44.4.5 forcebalance::gmxqpio.Monomer_QTPIE::objective

Definition at line 221 of file gmxqpio.py.

8.44.4.6 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.44.4.7 forcebalance::gmxqpio.Monomer_QTPIE::ref_moments

Definition at line 132 of file gmxqpio.py.

8.44.4.8 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.44.4.9 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.44.4.10 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.44.4.11 forcebalance::gmxqpio.Monomer_QTPIE::weights

Definition at line 132 of file gmxqpio.py.

8.44.4.12 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- gmxqpio.py

8.45 forcebalance.objective.Objective Class Reference

Objective function.

Inheritance diagram for forcebalance.objective.Objective:

Collaboration diagram for forcebalance.objective.Objective:

Public Member Functions

- def __init__
- def Target_Terms
- def Indicate

  Print objective function contributions.
- def Full
- def set_option

Public Attributes

- Targets

  Work Queue Port (The specific target itself may or may not actually use this.)
- FF

  The force field (it seems to be everywhere)
- Penalty

  Initialize the penalty function.

- WTot

  Obtain the denominator.
- ObjDict
- ObjDict_Last
- PrintOptionDict
- verbose_options

8.45.1 Detailed Description

Objective function.

The objective function is a combination of contributions from the different fitting targets. Basically, it loops through the targets, gets their contributions to the objective function and then sums all of them (although more elaborate schemes are conceivable). The return value is the same data type as calling the target itself: a dictionary containing the objective function, the gradient and the Hessian.

The penalty function is also computed here; it keeps the parameters from straying too far from their initial values.

Parameters

in	*mvals*	The mathematical parameters that enter into computing the objective function
in	*Order*	The requested order of differentiation

Definition at line 114 of file objective.py.

8.45.2 Constructor & Destructor Documentation

8.45.2.1 def forcebalance.objective.Objective.__init__ (*self, options, tgt_opts, forcefield*)

Definition at line 115 of file objective.py.

Here is the call graph for this function:

8.45.3 Member Function Documentation

8.45.3.1 def forcebalance.objective.Objective.Full (*self, mvals, Order* = `0`, *verbose* = `False`)

Definition at line 260 of file objective.py.

Here is the call graph for this function:

8.45.3.2 def forcebalance.objective.Objective.Indicate (*self*)

Print objective function contributions.

Definition at line 222 of file objective.py.

Here is the call graph for this function:

8.45.3.3 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = `None`, *val* = `None`, *default* = `None`, *forceprint* = `False`) `[inherited]`

Definition at line 32 of file __init__.py.

8.45.3.4 def forcebalance.objective.Objective.Target_Terms (*self, mvals, Order* = `0`, *verbose* = `False`)

Definition at line 162 of file objective.py.

Here is the call graph for this function:

8.45.4 Member Data Documentation

8.45.4.1 forcebalance::objective.Objective::FF

The force field (it seems to be everywhere)

Definition at line 119 of file objective.py.

8.45.4.2 forcebalance::objective.Objective::ObjDict

Definition at line 121 of file objective.py.

8.45.4.3 forcebalance::objective.Objective::ObjDict_Last

Definition at line 121 of file objective.py.

8.45.4.4 forcebalance::objective.Objective::Penalty

Initialize the penalty function.

Definition at line 120 of file objective.py.

8.45.4.5 forcebalance.BaseClass::PrintOptionDict `[inherited]`

Definition at line 28 of file __init__.py.

8.45.4.6 forcebalance::objective.Objective::Targets

Work Queue Port (The specific target itself may or may not actually use this.)

Asynchronous objective function evaluation (i.e. execute Work Queue and local objective concurrently.) The list of fitting targets

Definition at line 118 of file objective.py.

8.45.4.7 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.45.4.8 forcebalance::objective.Objective::WTot

Obtain the denominator.

Definition at line 121 of file objective.py.

The documentation for this class was generated from the following file:

- objective.py

8.46 forcebalance.openmmio.OpenMM_Reader Class Reference

Class for parsing OpenMM force field files.

Inheritance diagram for forcebalance.openmmio.OpenMM_Reader:

Collaboration diagram for forcebalance.openmmio.OpenMM_Reader:

Public Member Functions

- def __init__
- def build_pid

  Build the parameter identifier (see _link_ for an example)
- def Split
- def Whites
- def feed
- def build_pid

  Returns the parameter type (e.g.

Public Attributes

- pdict

  Initialize the superclass.
- ln
- itype
- suffix
- adict

  The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.
- molatom

  The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.
- Molecules
- AtomTypes

8.46.1 Detailed Description

Class for parsing OpenMM force field files.

Definition at line 324 of file openmmio.py.

8.46.2 Constructor & Destructor Documentation

8.46.2.1 def forcebalance.openmmio.OpenMM_Reader.__init__ (*self, fnm*)

Reimplemented from forcebalance.BaseReader.

Definition at line 325 of file openmmio.py.

Here is the call graph for this function:

8.46.3 Member Function Documentation

8.46.3.1 def forcebalance.BaseReader.build_pid (*self, pfld*) [inherited]

Returns the parameter type (e.g.

K in BONDSK) based on the current interaction type.

Both the 'pdict' dictionary (see gmxio.pdict) and the interaction type 'state' (here, BONDS) are needed to get the parameter type.

If, however, 'pdict' does not contain the ptype value, a suitable substitute is simply the field number.

Note that if the interaction type state is not set, then it defaults to the file name, so a generic parameter ID is 'filename.-line_num.field_num'

Reimplemented in forcebalance.psi4io.Grid_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 107 of file __init__.py.

8.46.3.2 def forcebalance.openmmio.OpenMM_Reader.build_pid (*self, element, parameter*)

Build the parameter identifier (see _link_ for an example)

Todo Add a link here

Definition at line 334 of file openmmio.py.

Here is the call graph for this function:

8.46.3.3 def forcebalance.BaseReader.feed (*self, line*) [inherited]

Reimplemented in forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.-Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.Q-

CIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 88 of file __init__.py.

Here is the call graph for this function:

8.46.3.4 def forcebalance.BaseReader.Split (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 82 of file __init__.py.

Here is the call graph for this function:

8.46.3.5 def forcebalance.BaseReader.Whites (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 85 of file __init__.py.

Here is the call graph for this function:

8.46.4 Member Data Documentation

8.46.4.1 forcebalance.BaseReader::adict [inherited]

The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.

Reimplemented in forcebalance.amberio.FrcMod_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 67 of file __init__.py.

8.46.4.2 forcebalance.BaseReader::AtomTypes [inherited]

Definition at line 71 of file __init__.py.

8.46.4.3 forcebalance.BaseReader::itype [inherited]

Reimplemented in forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.QCIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 66 of file __init__.py.

8.46.4.4 forcebalance.BaseReader::ln [inherited]

Definition at line 66 of file __init__.py.

8.46.4.5 forcebalance.BaseReader::molatom [inherited]

The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.

self.moleculedict = OrderedDict() The listing of 'RES:ATOMNAMES' for atom names in the line This is obviously a placeholder.

Reimplemented in forcebalance.gmxio.ITP_Reader, and forcebalance.amberio.Mol2_Reader.

Definition at line 71 of file __init__.py.

8.46.4.6 forcebalance.BaseReader::Molecules [inherited]

Definition at line 71 of file __init__.py.

8.46.4.7 forcebalance::openmmio.OpenMM_Reader::pdict

Initialize the superclass.

:) The parameter dictionary (defined in this file)

Reimplemented from forcebalance.BaseReader.

Definition at line 327 of file openmmio.py.

8.46.4.8 forcebalance.BaseReader::suffix [inherited]

Reimplemented in forcebalance.gmxio.ITP_Reader, forcebalance.amberio.FrcMod_Reader, forcebalance.tinkerio.Tinker_Reader, forcebalance.amberio.Mol2_Reader, forcebalance.custom_io.Gen_Reader, forcebalance.qchemio.QCIn_Reader, and forcebalance.mol2io.Mol2_Reader.

Definition at line 66 of file __init__.py.

The documentation for this class was generated from the following file:

- openmmio.py

8.47 forcebalance.optimizer.Optimizer Class Reference

Optimizer class.

Inheritance diagram for forcebalance.optimizer.Optimizer:

Collaboration diagram for forcebalance.optimizer.Optimizer:

Public Member Functions

- def __init__

  Create an Optimizer object.
- def Run

  Call the appropriate optimizer.
- def MainOptimizer

  The main ForceBalance adaptive trust-radius pseudo-Newton optimizer.
- def step

  Computes the next step in the parameter space.
- def NewtonRaphson

  Optimize the force field parameters using the Newton-Raphson method (.
- def BFGS

  Optimize the force field parameters using the BFGS method; currently the recommended choice (.
- def ScipyOptimizer

  Driver for SciPy optimizations.
- def GeneticAlgorithm

Genetic algorithm, under development.

- def Simplex

  Use SciPy's built-in simplex algorithm to optimize the parameters.
- def Powell

  Use SciPy's built-in Powell direction-set algorithm to optimize the parameters.
- def Anneal

  Use SciPy's built-in simulated annealing algorithm to optimize the parameters.
- def ConjugateGradient

  Use SciPy's built-in simulated annealing algorithm to optimize the parameters.
- def Scan_Values

  Scan through parameter values.
- def ScanMVals

  Scan through the mathematical parameter space.
- def ScanPVals

  Scan through the physical parameter space.
- def SinglePoint

  A single-point objective function computation.
- def Gradient

  A single-point gradient computation.
- def Hessian

  A single-point Hessian computation.
- def FDCheckG

  Finite-difference checker for the objective function gradient.
- def FDCheckH

  Finite-difference checker for the objective function Hessian.
- def readchk

  Read the checkpoint file for the main optimizer.
- def writechk

  Write the checkpoint file for the main optimizer.
- def set_option

Public Attributes

- OptTab

  A list of all the things we can ask the optimizer to do.
- Objective

  The root directory.
- bhyp

  Whether the penalty function is hyperbolic.
- FF

  The force field itself.
- excision

  The indices to be excluded from the Hessian update.
- np

  Number of parameters.
- mvals0

  The original parameter values.

- chk

  Put data into the checkpoint file.
- H
- dx
- Val
- Grad
- Hess
- Penalty
- PrintOptionDict
- verbose_options

8.47.1 Detailed Description

Optimizer class.

Contains several methods for numerical optimization.

For various reasons, the optimizer depends on the force field and fitting targets (i.e. we cannot treat it as a fully independent numerical optimizer). The dependency is rather weak which suggests that I can remove it someday.

Definition at line 44 of file optimizer.py.

8.47.2 Constructor & Destructor Documentation

8.47.2.1 def forcebalance.optimizer.Optimizer.__init__ (*self, options, Objective, FF*)

Create an Optimizer object.

The optimizer depends on both the FF and the fitting targets so there is a chain of dependencies: FF --> FitSim --> Optimizer, and FF --> Optimizer

Here's what we do:

- Take options from the parser
- Pass in the objective function, force field, all fitting targets

Definition at line 57 of file optimizer.py.

8.47.3 Member Function Documentation

8.47.3.1 def forcebalance.optimizer.Optimizer.Anneal (*self*)

Use SciPy's built-in simulated annealing algorithm to optimize the parameters.

See also

Optimizer::ScipyOptimizer

Definition at line 784 of file optimizer.py.

8.47.3.2 def forcebalance.optimizer.Optimizer.BFGS (*self*)

Optimize the force field parameters using the BFGS method; currently the recommended choice (.

See also

MainOptimizer)

Definition at line 605 of file optimizer.py.

8.47.3.3 def forcebalance.optimizer.Optimizer.ConjugateGradient (*self*)

Use SciPy's built-in simulated annealing algorithm to optimize the parameters.

See also

Optimizer::ScipyOptimizer

Definition at line 789 of file optimizer.py.

8.47.3.4 def forcebalance.optimizer.Optimizer.FDCheckG (*self*)

Finite-difference checker for the objective function gradient.

For each element in the gradient, use a five-point finite difference stencil to compute a finite-difference derivative, and compare it to the analytic result.

Definition at line 885 of file optimizer.py.

Here is the call graph for this function:

8.47.3.5 def forcebalance.optimizer.Optimizer.FDCheckH (*self*)

Finite-difference checker for the objective function Hessian.

For each element in the Hessian, use a five-point stencil in both parameter indices to compute a finite-difference derivative, and compare it to the analytic result.

This is meant to be a foolproof checker, so it is pretty slow. We could write a faster checker if we assumed we had accurate first derivatives, but it's better to not make that assumption.

The second derivative is computed by double-wrapping the objective function via the 'wrap2' function.

Definition at line 917 of file optimizer.py.

Here is the call graph for this function:

8.47.3.6 def forcebalance.optimizer.Optimizer.GeneticAlgorithm (*self*)

Genetic algorithm, under development.

It currently works but a genetic algorithm is more like a concept; i.e. there is no single way to implement it.

Todo Massive parallelization hasn't been implemented yet

Definition at line 681 of file optimizer.py.

Here is the call graph for this function:

8.47.3.7 def forcebalance.optimizer.Optimizer.Gradient (*self*)

A single-point gradient computation.

Definition at line 863 of file optimizer.py.

Here is the call graph for this function:

8.47.3.8 def forcebalance.optimizer.Optimizer.Hessian (*self*)

A single-point Hessian computation.

Definition at line 871 of file optimizer.py.

Here is the call graph for this function:

8.47.3.9 def forcebalance.optimizer.Optimizer.MainOptimizer (*self, b_BFGS* = 0)

The main ForceBalance adaptive trust-radius pseudo-Newton optimizer.

Tried and true in many situations. :)

Usually this function is called with the BFGS or NewtonRaphson method. The NewtonRaphson method is consistently the best method I have, because I always provide at least an approximate Hessian to the objective function. The BFGS method is vestigial and currently does not work.

BFGS is a pseudo-Newton method in the sense that it builds an approximate Hessian matrix from the gradient information in previous steps; Newton-Raphson requires the actual Hessian matrix. However, the algorithms are similar in that they both compute the step by inverting the Hessian and multiplying by the gradient.

The method adaptively changes the step size. If the step is sufficiently good (i.e. the objective function goes down by a large fraction of the predicted decrease), then the step size is increased; if the step is bad, then it rejects the step and tries again.

The optimization is terminated after either a function value or step size tolerance is reached.

Parameters

in	*b_BFGS*	Switch to use BFGS (True) or Newton-Raphson (False)

Definition at line 229 of file optimizer.py.

8.47.3.10 def forcebalance.optimizer.Optimizer.NewtonRaphson (*self*)

Optimize the force field parameters using the Newton-Raphson method (.

See also

MainOptimizer)

Definition at line 600 of file optimizer.py.

Here is the call graph for this function:

8.47.3.11 def forcebalance.optimizer.Optimizer.Powell (*self*)

Use SciPy's built-in Powell direction-set algorithm to optimize the parameters.

See also

Optimizer::ScipyOptimizer

Definition at line 779 of file optimizer.py.

8.47.3.12 def forcebalance.optimizer.Optimizer.readchk (*self*)

Read the checkpoint file for the main optimizer.

Definition at line 945 of file optimizer.py.

8.47.3.13 def forcebalance.optimizer.Optimizer.Run (*self*)

Call the appropriate optimizer.

This is the method we might want to call from an executable.

Definition at line 168 of file optimizer.py.

Here is the call graph for this function:

8.47.3.14 def forcebalance.optimizer.Optimizer.Scan_Values (*self, MathPhys* = 1)

Scan through parameter values.

This option is activated using the inputs:

```
scan[mp]vals
scan_vals low:hi:nsteps
scan_idxnum (number) -or-
scan_idxname (name)
```

This method goes to the specified parameter indices and scans through the supplied values, evaluating the objective function at every step.

I hope this method will be useful for people who just want to look at changing one or two parameters and seeing how it affects the force field performance.

Todo Maybe a multidimensional grid can be done.

Parameters

in	*MathPhys*	Switch to use mathematical (True) or physical (False) parameters.

Definition at line 815 of file optimizer.py.

Here is the call graph for this function:

8.47.3.15 def forcebalance.optimizer.Optimizer.ScanMVals (*self*)

Scan through the mathematical parameter space.

See also

Optimizer::ScanValues

Definition at line 847 of file optimizer.py.

Here is the call graph for this function:

8.47.3.16 def forcebalance.optimizer.Optimizer.ScanPVals (*self*)

Scan through the physical parameter space.

See also

Optimizer::ScanValues

Definition at line 852 of file optimizer.py.

8.47.3.17 def forcebalance.optimizer.Optimizer.ScipyOptimizer (*self, Algorithm* = "None")

Driver for SciPy optimizations.

Using any of the SciPy optimizers requires that SciPy is installed. This method first defines several wrappers around the objective function that the SciPy optimizers can use. Then it calls the algorith mitself.

Parameters

in	*Algorithm*	The optimization algorithm to use, for example 'powell', 'simplex' or 'anneal'

Definition at line 618 of file optimizer.py.

Here is the call graph for this function:

8.47.3.18 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.47.3.19 def forcebalance.optimizer.Optimizer.Simplex (*self*)

Use SciPy's built-in simplex algorithm to optimize the parameters.

See also

Optimizer::ScipyOptimizer

Definition at line 774 of file optimizer.py.

Here is the call graph for this function:

8.47.3.20 def forcebalance.optimizer.Optimizer.SinglePoint (*self*)

A single-point objective function computation.

Definition at line 857 of file optimizer.py.

Here is the call graph for this function:

8.47.3.21 def forcebalance.optimizer.Optimizer.step (*self, xk, data, trust*)

Computes the next step in the parameter space.

There are lots of tricks here that I will document later.

Parameters

in	*G*	The gradient
in	*H*	The Hessian
in	*trust*	The trust radius

Definition at line 421 of file optimizer.py.

8.47.3.22 def forcebalance.optimizer.Optimizer.writechk (*self*)

Write the checkpoint file for the main optimizer.

Definition at line 957 of file optimizer.py.

8.47.4 Member Data Documentation

8.47.4.1 forcebalance::optimizer.Optimizer::bhyp

Whether the penalty function is hyperbolic.

Definition at line 85 of file optimizer.py.

8.47.4.2 forcebalance::optimizer.Optimizer::chk

Put data into the checkpoint file.

Definition at line 230 of file optimizer.py.

8.47.4.3 forcebalance::optimizer.Optimizer::dx

Definition at line 423 of file optimizer.py.

8.47.4.4 forcebalance::optimizer.Optimizer::excision

The indices to be excluded from the Hessian update.

Definition at line 87 of file optimizer.py.

8.47.4.5 forcebalance::optimizer.Optimizer::FF

The force field itself.

Definition at line 86 of file optimizer.py.

8.47.4.6 forcebalance::optimizer.Optimizer::Grad

Definition at line 423 of file optimizer.py.

8.47.4.7 forcebalance::optimizer.Optimizer::H

Definition at line 423 of file optimizer.py.

8.47.4.8 forcebalance::optimizer.Optimizer::Hess

Definition at line 423 of file optimizer.py.

8.47.4.9 forcebalance::optimizer.Optimizer::mvals0

The original parameter values.

Sometimes the optimizer doesn't return anything (i.e.

in the case of a single point calculation) In these situations, don't do anything Check derivatives by finite difference after the optimization is over (for good measure)

Definition at line 89 of file optimizer.py.

8.47.4.10 forcebalance::optimizer.Optimizer::np

Number of parameters.

Definition at line 88 of file optimizer.py.

8.47.4.11 forcebalance::optimizer.Optimizer::Objective

The root directory.

The job type Initial step size trust radius Minimum trust radius (for noisy objective functions) Lower bound on Hessian eigenvalue (below this, we add in steepest descent) Guess value for Brent Step size for numerical finite difference Number of steps to average over Function value convergence threshold Step size convergence threshold Gradient convergence threshold Maximum number of optimization steps For scan[mp]vals: The parameter index to scan over For scan[mp]vals: The parameter name to scan over, it just looks up an index For scan[mp]vals: The values that are fed into the scanner Name of the checkpoint file that we're reading in Name of the checkpoint file that we're writing out Whether to write the checkpoint file at every step Adaptive trust radius adjustment factor Adaptive trust radius adjustment damping Whether to print gradient during each step of the optimization Whether to print Hessian during each step of the optimization Whether to print parameters during each step of the optimization Error tolerance (if objective function rises by less than this, then the optimizer will forge ahead!) Search tolerance (The nonlinear search will stop if the change is below this threshold) The objective function (needs to pass in when I instantiate)

Definition at line 84 of file optimizer.py.

8.47.4.12 forcebalance::optimizer.Optimizer::OptTab

A list of all the things we can ask the optimizer to do.

Definition at line 58 of file optimizer.py.

8.47.4.13 forcebalance::optimizer.Optimizer::Penalty

Definition at line 423 of file optimizer.py.

8.47.4.14 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.47.4.15 forcebalance::optimizer.Optimizer::Val

Definition at line 423 of file optimizer.py.

8.47.4.16 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

The documentation for this class was generated from the following file:

- optimizer.py

8.48 forcebalance.objective.Penalty Class Reference

Penalty functions for regularizing the force field optimizer.

Public Member Functions

- def __init__
- def compute
- def L2_norm

  Harmonic L2-norm constraints.
- def HYP

  Hyperbolic constraints.
- def FUSE
- def FUSE_BARRIER
- def FUSE_L0

Public Attributes

- fadd
- fmul
- a
- b
- FF
- ptyp
- Pen_Tab

- spacings

  Find exponential spacings.

Static Public Attributes

- dictionary Pen_Names

8.48.1 Detailed Description

Penalty functions for regularizing the force field optimizer.

The purpose for this module is to improve the behavior of our optimizer; essentially, our problem is fraught with 'linear dependencies', a.k.a. directions in the parameter space that the objective function does not respond to. This would happen if a parameter is just plain useless, or if there are two or more parameters that describe the same thing.

To accomplish these objectives, a penalty function is added to the objective function. Generally, the more the parameters change (i.e. the greater the norm of the parameter vector), the greater the penalty. Note that this is added on after all of the other contributions have been computed. This only matters if the penalty 'multiplies' the objective function: Obj + Obj∗Penalty, but we also have the option of an additive penalty: Obj + Penalty.

Statistically, this is called regularization. If the penalty function is the norm squared of the parameter vector, it is called ridge regression. There is also the option of using simply the norm, and this is called lasso, but I think it presents problems for the optimizer that I need to work out.

Note that the penalty functions can be considered as part of a 'maximum likelihood' framework in which we assume a PRIOR PROBABILITY of the force field parameters around their initial values. The penalty function is related to the prior by an exponential. Ridge regression corresponds to a Gaussian prior and lasso corresponds to an exponential prior. There is also 'elastic net regression' which interpolates between Gaussian and exponential using a tuning parameter.

Our priors are adjustable too - there is one parameter, which is the width of the distribution. We can even use a noninformative prior for the distribution widths (hyperprior!). These are all important things to consider later.

Importantly, note that here there is no code that treats the distribution width. That is because the distribution width is wrapped up in the rescaling factors, which is essentially a coordinate transformation on the parameter space. More documentation on this will follow, perhaps in the 'rsmake' method.

Definition at line 317 of file objective.py.

8.48.2 Constructor & Destructor Documentation

8.48.2.1 def forcebalance.objective.Penalty.__init__ (*self, User_Option, ForceField, Factor_Add* = `0.0`, *Factor_Mult* = `0.0`, *Factor_B* = `0.1`, *Alpha* = `1.0`)

Definition at line 323 of file objective.py.

8.48.3 Member Function Documentation

8.48.3.1 def forcebalance.objective.Penalty.compute (*self, mvals, Objective*)

Definition at line 349 of file objective.py.

Here is the call graph for this function:

8.48.3.2 def forcebalance.objective.Penalty.FUSE (*self, mvals*)

Definition at line 409 of file objective.py.

Here is the call graph for this function:

8.48.3.3 def forcebalance.objective.Penalty.FUSE_BARRIER (*self, mvals*)

Definition at line 450 of file objective.py.

Here is the call graph for this function:

8.48.3.4 def forcebalance.objective.Penalty.FUSE_L0 (*self, mvals*)

Definition at line 492 of file objective.py.

Here is the call graph for this function:

8.48.3.5 def forcebalance.objective.Penalty.HYP (*self, mvals*)

Hyperbolic constraints.

Depending on the 'b' parameter, the smaller it is, the closer we are to an L1-norm constraint. If we use these, we expect a properly-behaving optimizer to make several of the parameters very nearly zero (which would be cool).

Parameters

in	*mvals*	The parameter vector

Returns

DC0 The hyperbolic penalty
DC1 The gradient
DC2 The Hessian

Definition at line 401 of file objective.py.

Here is the call graph for this function:

8.48.3.6 def forcebalance.objective.Penalty.L2_norm (*self, mvals*)

Harmonic L2-norm constraints.

These are the ones that I use the most often to regularize my optimization.

Parameters

in	*mvals*	The parameter vector

Returns

DC0 The norm squared of the vector
DC1 The gradient of DC0
DC2 The Hessian (just a constant)

Definition at line 381 of file objective.py.

Here is the call graph for this function:

8.48.4 Member Data Documentation

8.48.4.1 forcebalance::objective.Penalty::a

Definition at line 323 of file objective.py.

8.48.4.2 forcebalance::objective.Penalty::b

Definition at line 323 of file objective.py.

8.48.4.3 forcebalance::objective.Penalty::fadd

Definition at line 323 of file objective.py.

8.48.4.4 forcebalance::objective.Penalty::FF

Definition at line 323 of file objective.py.

8.48.4.5 forcebalance::objective.Penalty::fmul

Definition at line 323 of file objective.py.

8.48.4.6 dictionary forcebalance::objective.Penalty::Pen_Names [static]

Initial value:

```
{'HYP' : 1, 'HYPER' : 1, 'HYPERBOLIC' : 1, 'L1' : 1, 'HYPERBOLA' : 1,
                    'PARA' : 2, 'PARABOLA' : 2, 'PARABOLIC' : 2, 'L2': 2, '
      QUADRATIC' : 2,
                    'FUSE' : 3, 'FUSION' : 3, 'FUSE_L0' : 4, 'FUSION_L0' : 4,
       'FUSION-L0' : 4,
                    'FUSE-BARRIER' : 5, 'FUSE-BARRIER' : 5, 'FUSE_BARRIER' :
      5, 'FUSION_BARRIER' : 5}
```

Definition at line 318 of file objective.py.

8.48.4.7 forcebalance::objective.Penalty::Pen_Tab

Definition at line 323 of file objective.py.

8.48.4.8 forcebalance::objective.Penalty::ptyp

Definition at line 323 of file objective.py.

8.48.4.9 forcebalance::objective.Penalty::spacings

Find exponential spacings.

Definition at line 324 of file objective.py.

The documentation for this class was generated from the following file:

- objective.py

8.49 forcebalance.nifty.Pickler_LP Class Reference

A subclass of the python Pickler that implements pickling of _ElementTree types.

Public Member Functions

- def __init__

8.49.1 Detailed Description

A subclass of the python Pickler that implements pickling of _ElementTree types.

Definition at line 500 of file nifty.py.

8.49.2 Constructor & Destructor Documentation

8.49.2.1 def forcebalance.nifty.Pickler_LP.__init__ (*self, file, protocol* = None)

Definition at line 501 of file nifty.py.

Here is the call graph for this function:

The documentation for this class was generated from the following file:

- nifty.py

8.50 forcebalance.qchemio.QCIn_Reader Class Reference

Finite state machine for parsing Q-Chem input files.

Inheritance diagram for forcebalance.qchemio.QCIn_Reader:

Collaboration diagram for forcebalance.qchemio.QCIn_Reader:

Public Member Functions

- def __init__
- def feed

  Feed in a line.
- def Split
- def Whites
- def build_pid

  Returns the parameter type (e.g.

Public Attributes

- atom
- snum
- cnum
- shell
- pdict
- sec
- itype
- suffix
- ln
- adict

  The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.
- molatom

  The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.
- Molecules
- AtomTypes

8.50.1 Detailed Description

Finite state machine for parsing Q-Chem input files.

Definition at line 31 of file qchemio.py.

8.50.2 Constructor & Destructor Documentation

8.50.2.1 def forcebalance.qchemio.QCIn_Reader.__init__ (*self, fnm*)

Reimplemented from forcebalance.BaseReader.

Definition at line 33 of file qchemio.py.

8.50.3 Member Function Documentation

8.50.3.1 def forcebalance.BaseReader.build_pid (*self, pfld*) [inherited]

Returns the parameter type (e.g.

K in BONDSK) based on the current interaction type.

Both the 'pdict' dictionary (see gmxio.pdict) and the interaction type 'state' (here, BONDS) are needed to get the parameter type.

If, however, 'pdict' does not contain the ptype value, a suitable substitute is simply the field number.

Note that if the interaction type state is not set, then it defaults to the file name, so a generic parameter ID is 'filename.-line_num.field_num'

Reimplemented in forcebalance.psi4io.Grid_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 107 of file __init__.py.

8.50.3.2 def forcebalance.qchemio.QCIn_Reader.feed (*self, line*)

Feed in a line.

Parameters

in	*line*	The line of data

Reimplemented from forcebalance.BaseReader.

Definition at line 48 of file qchemio.py.

8.50.3.3 def forcebalance.BaseReader.Split (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 82 of file __init__.py.

Here is the call graph for this function:

8.50.3.4 def forcebalance.BaseReader.Whites (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 85 of file __init__.py.

Here is the call graph for this function:

8.50.4 Member Data Documentation

8.50.4.1 forcebalance.BaseReader::adict [inherited]

The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.

Reimplemented in forcebalance.amberio.FrcMod_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 67 of file __init__.py.

8.50.4.2 forcebalance::qchemio.QCIn_Reader::atom

Definition at line 33 of file qchemio.py.

8.50.4.3 forcebalance.BaseReader::AtomTypes [inherited]

Definition at line 71 of file __init__.py.

8.50.4.4 forcebalance::qchemio.QCIn_Reader::cnum

Definition at line 33 of file qchemio.py.

8.50.4.5 forcebalance::qchemio.QCIn_Reader::itype

Reimplemented from forcebalance.BaseReader.

Definition at line 48 of file qchemio.py.

8.50.4.6 forcebalance.BaseReader::ln [inherited]

Definition at line 66 of file __init__.py.

8.50.4.7 forcebalance.BaseReader::molatom [inherited]

The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.

self.moleculedict = OrderedDict() The listing of 'RES:ATOMNAMES' for atom names in the line This is obviously a placeholder.

Reimplemented in forcebalance.gmxio.ITP_Reader, and forcebalance.amberio.Mol2_Reader.

Definition at line 71 of file __init__.py.

8.50.4.8 forcebalance.BaseReader::Molecules [inherited]

Definition at line 71 of file __init__.py.

8.50.4.9 forcebalance::qchemio.QCIn_Reader::pdict

Reimplemented from forcebalance.BaseReader.

Definition at line 33 of file qchemio.py.

8.50.4.10 forcebalance::qchemio.QCIn_Reader::sec

Definition at line 48 of file qchemio.py.

8.50.4.11 forcebalance::qchemio.QCIn_Reader::shell

Definition at line 33 of file qchemio.py.

8.50.4.12 forcebalance::qchemio.QCIn_Reader::snum

Definition at line 33 of file qchemio.py.

8.50.4.13 forcebalance::qchemio.QCIn_Reader::suffix

Reimplemented from forcebalance.BaseReader.

Definition at line 48 of file qchemio.py.

The documentation for this class was generated from the following file:

- qchemio.py

8.51 forcebalance.output.RawFileHandler Class Reference

Exactly like output.FileHandler except it does no extra formatting before sending logging messages to the file.

Public Member Functions

- def emit

8.51.1 Detailed Description

Exactly like output.FileHandler except it does no extra formatting before sending logging messages to the file.

This is more compatible with how output has been displayed in ForceBalance.

Definition at line 47 of file output.py.

8.51.2 Member Function Documentation

8.51.2.1 def forcebalance.output.RawFileHandler.emit (*self, record*)

Definition at line 48 of file output.py.

The documentation for this class was generated from the following file:

- output.py

8.52 forcebalance.output.RawStreamHandler Class Reference

Exactly like output.StreamHandler except it does no extra formatting before sending logging messages to the stream.

Public Member Functions

- def __init__
- def emit

8.52.1 Detailed Description

Exactly like output.StreamHandler except it does no extra formatting before sending logging messages to the stream.

This is more compatible with how output has been displayed in ForceBalance. Default stream has also been changed from stderr to stdout

Definition at line 34 of file output.py.

8.52.2 Constructor & Destructor Documentation

8.52.2.1 def forcebalance.output.RawStreamHandler.__init__ (*self, stream* = `sys.stdout`)

Definition at line 35 of file output.py.

Here is the call graph for this function:

8.52.3 Member Function Documentation

8.52.3.1 def forcebalance.output.RawStreamHandler.emit (*self, record*)

Definition at line 38 of file output.py.

The documentation for this class was generated from the following file:

- output.py

8.53 forcebalance.psi4io.RDVR3_Psi4 Class Reference

Subclass of Target for R-DVR3 grid fitting.

Inheritance diagram for forcebalance.psi4io.RDVR3_Psi4:

Collaboration diagram for forcebalance.psi4io.RDVR3_Psi4:

Public Member Functions

- def __init__

  All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)
- def indicate
- def submit_jobs

  Create a grid file and a psi4 input file in the absolute path and submit it to the work queue.
- def driver

- def get

  LPW 04-17-2013.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- objfiles

  Which parameters are differentiated?
- objvals
- elements
- molecules
- callderivs
- factor
- bidirect
- tdir
- objd
- gradd
- hdiagd
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.53.1 Detailed Description

Subclass of Target for R-DVR3 grid fitting.

Main features:

- Multiple molecules are treated as a single target.
- R-DVR3 can only print out the objective function, it cannot print out the residual vector.
- We should be smart enough to mask derivatives.

Definition at line 296 of file psi4io.py.

8.53.2 Constructor & Destructor Documentation

8.53.2.1 def forcebalance.psi4io.RDVR3_Psi4.__init__ (*self, options, tgt_opts, forcefield*)

All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)

If we want to add attributes that are more specific (i.e. a set of reference forces for force matching), they are added in the subclass AbInitio that inherits from Target.

Reimplemented from forcebalance.target.Target.

Definition at line 299 of file psi4io.py.

8.53.3 Member Function Documentation

8.53.3.1 def forcebalance.psi4io.RDVR3_Psi4.driver (*self, mvals, d*)

Definition at line 412 of file psi4io.py.

Here is the call graph for this function:

8.53.3.2 def forcebalance.psi4io.RDVR3_Psi4.get (*self, mvals, AGrad* = `False`, *AHess* = `False`)

LPW 04-17-2013.

This subroutine builds the objective function from Psi4.

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient
in	*AHess*	Switch to turn on analytic Hessian

Returns

Answer Contribution to the objective function

Reimplemented from forcebalance.target.Target.

Definition at line 449 of file psi4io.py.

8.53.3.3 def forcebalance.target.Target.get_G (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.53.3.4 def forcebalance.target.Target.get_H (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.53.3.5 def forcebalance.target.Target.get_X (*self*, *mvals* = None) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.53.3.6 def forcebalance.psi4io.RDVR3_Psi4.indicate (*self*)

Definition at line 339 of file psi4io.py.

Here is the call graph for this function:

8.53.3.7 def forcebalance.target.Target.link_from_tempdir (*self*, *absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.53.3.8 def forcebalance.target.Target.printcool_table (*self*, *data* = OrderedDict([]), *headings* = [], *banner* = None, *footnote* = None, *color* = 0) [inherited]

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.53.3.9 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.53.3.10 def forcebalance.BaseClass.set_option (*self*, *in_dict*, *src_key*, *dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.53.3.11 def forcebalance.target.Target.sget (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.53.3.12 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.53.3.13 def forcebalance.psi4io.RDVR3_Psi4.submit_jobs (*self, mvals, AGrad* = `True`, *AHess* = `True`)

Create a grid file and a psi4 input file in the absolute path and submit it to the work queue.

Reimplemented from forcebalance.target.Target.

Definition at line 348 of file psi4io.py.

8.53.3.14 def forcebalance.target.Target.wq_complete (*self*) `[inherited]`

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.53.4 Member Data Documentation

8.53.4.1 forcebalance::psi4io.RDVR3_Psi4::bidirect

Definition at line 300 of file psi4io.py.

8.53.4.2 forcebalance::psi4io.RDVR3_Psi4::callderivs

Definition at line 300 of file psi4io.py.

8.53.4.3 forcebalance::psi4io.RDVR3_Psi4::elements

Definition at line 300 of file psi4io.py.

8.53.4.4 forcebalance::psi4io.RDVR3_Psi4::factor

Definition at line 300 of file psi4io.py.

8.53.4.5 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.53.4.6 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.53.4.7 forcebalance::psi4io.RDVR3_Psi4::gradd

Definition at line 449 of file psi4io.py.

8.53.4.8 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.53.4.9 forcebalance::psi4io.RDVR3_Psi4::hdiagd

Definition at line 449 of file psi4io.py.

8.53.4.10 forcebalance::psi4io.RDVR3_Psi4::molecules

Definition at line 300 of file psi4io.py.

8.53.4.11 forcebalance::psi4io.RDVR3_Psi4::objd

Definition at line 449 of file psi4io.py.

8.53.4.12 forcebalance::psi4io.RDVR3_Psi4::objective

Definition at line 449 of file psi4io.py.

8.53.4.13 forcebalance::psi4io.RDVR3_Psi4::objfiles

Which parameters are differentiated?

Definition at line 300 of file psi4io.py.

8.53.4.14 forcebalance::psi4io.RDVR3_Psi4::objvals

Definition at line 300 of file psi4io.py.

8.53.4.15 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.53.4.16 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.53.4.17 forcebalance::psi4io.RDVR3_Psi4::tdir

Definition at line 348 of file psi4io.py.

8.53.4.18 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.53.4.19 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.53.4.20 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- psi4io.py

8.54 forcebalance.target.RemoteTarget Class Reference

Inheritance diagram for forcebalance.target.RemoteTarget:

Collaboration diagram for forcebalance.target.RemoteTarget:

Public Member Functions

- def __init__

  All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)
- def submit_jobs
- def get

  Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.
- def indicate
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- r_options
- r_tgt_opts
- remote_indicate
- id_string
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.54.1 Detailed Description

Definition at line 406 of file target.py.

8.54.2 Constructor & Destructor Documentation

8.54.2.1 def forcebalance.target.RemoteTarget.__init__ (*self, options, tgt_opts, forcefield*)

All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)

If we want to add attributes that are more specific (i.e. a set of reference forces for force matching), they are added in the subclass AbInitio that inherits from Target.

Reimplemented from forcebalance.target.Target.

Definition at line 407 of file target.py.

8.54.3 Member Function Documentation

8.54.3.1 def forcebalance.target.RemoteTarget.get (*self, mvals, AGrad* = `False`, *AHess* = `False`)

Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.

See abinitio for an example.

Reimplemented from forcebalance.target.Target.

Definition at line 452 of file target.py.

8.54.3.2 def forcebalance.target.Target.get_G (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.54.3.3 def forcebalance.target.Target.get_H (*self*, *mvals* = `None`) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.54.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) `[inherited]`

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.54.3.5 def forcebalance.target.RemoteTarget.indicate (*self*)

Definition at line 458 of file target.py.

8.54.3.6 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.54.3.7 def forcebalance.target.Target.printcool_table (*self, data* = OrderedDict([]), *headings* = [], *banner* = None, *footnote* = None, *color* = 0) [inherited]

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.54.3.8 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.54.3.9 def forcebalance.BaseClass.set_option (*self*, *in_dict*, *src_key*, *dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.54.3.10 def forcebalance.target.Target.sget (*self*, *mvals*, *AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.54.3.11 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.54.3.12 def forcebalance.target.RemoteTarget.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`)

Reimplemented from forcebalance.target.Target.

Definition at line 422 of file target.py.

Here is the call graph for this function:

8.54.3.13 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.54.4 Member Data Documentation

8.54.4.1 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.54.4.2 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.54.4.3 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.54.4.4 forcebalance::target.RemoteTarget::id_string

Definition at line 422 of file target.py.

8.54.4.5 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.54.4.6 forcebalance::target.RemoteTarget::r_options

Definition at line 407 of file target.py.

8.54.4.7 forcebalance::target.RemoteTarget::r_tgt_opts

Definition at line 407 of file target.py.

8.54.4.8 forcebalance::target.RemoteTarget::remote_indicate

Definition at line 407 of file target.py.

8.54.4.9 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.54.4.10 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.54.4.11 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.54.4.12 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- target.py

8.55 forcebalance.target.Target Class Reference

Base class for all fitting targets.

Inheritance diagram for forcebalance.target.Target:

Collaboration diagram for forcebalance.target.Target:

Public Member Functions

- def __init__

  All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.

- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def get

  Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.
- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.55.1 Detailed Description

Base class for all fitting targets.

In ForceBalance a Target is defined as a set of reference data plus a corresponding method to simulate that data using the force field.

The 'computable quantities' may include energies and forces where the reference values come from QM calculations (energy and force matching), energies from an EDA analysis (Maybe in the future, FDA?), molecular properties (like polarizability, refractive indices, multipole moments or vibrational frequencies), relative entropies, and bulk properties. Single-molecule or bulk properties can even come from the experiment!

The central idea in ForceBalance is that each quantity makes a contribution to the overall objective function. So we can build force fields that fit several quantities at once, rather than putting all of our chips behind energy and force matching. In the future ForceBalance may even include multiobjective optimization into the optimizer.

The optimization is done by way of minimizing an 'objective function', which is comprised of squared differences between the computed and reference values. These differences are not computed in this file, but rather in subclasses that use Target as a base class. Thus, the contents of Target itself are meant to be as general as possible, because the pertinent variables apply to all types of fitting targets.

An important node: Target requires that all subclasses have a method get(self,mvals,AGrad=False,AHess=False) that does the following:

Inputs: mvals = The parameter vector, which modifies the force field (Note to self: We include mvals with each Target because we can create copies of the force field and do finite difference derivatives) AGrad, AHess = Boolean switches for computing analytic gradients and Hessians

Outputs: Answer = {'X': Number, 'G': numpy.array(np), 'H': numpy.array((np,np)) } 'X' = The objective function itself 'G' = The gradient, elements not computed analytically are zero 'H' = The Hessian, elements not computed analytically are zero

This is the only global requirement of a Target. Obviously 'get' itself is not defined here, because its calculation will depend entirely on specifically which target we wish to use. However, this should give us a unified framework which will faciliate rapid implementation of Targets.

Future work: Robert suggested that I could enable automatic detection of which parameters need to be computed by finite difference. Not a bad idea. :)

Definition at line 75 of file target.py.

8.55.2 Constructor & Destructor Documentation

8.55.2.1 def forcebalance.target.Target.__init__ (*self, options, tgt_opts, forcefield*)

All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)

If we want to add attributes that are more specific (i.e. a set of reference forces for force matching), they are added in the subclass AbInitio that inherits from Target.

Reimplemented in forcebalance.gmxio.Interaction_GMX, forcebalance.gmxio.Liquid_GMX, forcebalance.gmxio.AbInitio_GMX, forcebalance.tinkerio.Interaction_TINKER, forcebalance.openmmio.Interaction_OpenMM, forcebalance.tinkerio.BindingEnergy_TINKER, forcebalance.openmmio.AbInitio_OpenMM, forcebalance.target.RemoteTarget, forcebalance.tinkerio.Moments_TINKER, forcebalance.openmmio.Liquid_OpenMM, forcebalance.psi4io.RDVR3_Psi4, forcebalance.tinkerio.AbInitio_TINKER, forcebalance.tinkerio.Liquid_TINKER, forcebalance.amberio.AbInitio_AMBER, forcebalance.gmxqpio.Monomer_QTPIE, forcebalance.binding.BindingEnergy, forcebalance.psi4io.THCDF_Psi4, forcebalance.abinitio.AbInitio, forcebalance.liquid.Liquid, forcebalance.abinitio_internal.AbInitio_Internal, forcebalance.interaction.Interaction, forcebalance.leastsq.LeastSquares, forcebalance.counterpoise.Counterpoise, forcebalance.moments.Moments, and forcebalance.vibration.Vibration.

Definition at line 92 of file target.py.

Here is the call graph for this function:

8.55.3 Member Function Documentation

8.55.3.1 def forcebalance.target.Target.get (*self, mvals, AGrad* = `False`, *AHess* = `False`)

Every target must be able to return a contribution to the objective function - however, this must be implemented in the specific subclass.

See abinitio for an example.

Reimplemented in forcebalance.abinitio.AbInitio, forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, forcebalance.liquid.Liquid, forcebalance.gmxqpio.Monomer_QTPIE, forcebalance.moments.Moments, forcebalance.interaction.Interaction, forcebalance.binding.BindingEnergy, forcebalance.counterpoise.Counterpoise, forcebalance.vibration.Vibration, and forcebalance.leastsq.LeastSquares.

Definition at line 254 of file target.py.

Here is the call graph for this function:

8.55.3.2 def forcebalance.target.Target.get_G (*self, mvals* = `None`)

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.55.3.3 def forcebalance.target.Target.get_H (*self*, *mvals* = `None`)

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.55.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`)

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.55.3.5 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*)

Definition at line 213 of file target.py.

8.55.3.6 def forcebalance.target.Target.printcool_table (*self, data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`)

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.55.3.7 def forcebalance.target.Target.refresh_temp_directory (*self*)

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.55.3.8 def forcebalance.BaseClass.set_option (*self*, *in_dict*, *src_key*, *dest_key* = `None`, *val* = `None`, *default* = `None`, *forceprint* = `False`) [inherited]

Definition at line 32 of file __init__.py.

8.55.3.9 def forcebalance.target.Target.sget (*self*, *mvals*, *AGrad* = `False`, *AHess* = `False`, *customdir* = `None`)

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.55.3.10 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`)

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.55.3.11 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`)

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.55.3.12 def forcebalance.target.Target.wq_complete (*self*)

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.55.4 Member Data Documentation

8.55.4.1 forcebalance::target.Target::FF

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.55.4.2 forcebalance::target.Target::gct

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.55.4.3 forcebalance::target.Target::hct

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.55.4.4 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.55.4.5 forcebalance::target.Target::rundir

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.55.4.6 forcebalance::target.Target::tempdir

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.55.4.7 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.55.4.8 forcebalance::target.Target::xct

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- target.py

8.56 forcebalance.psi4io.THCDF_Psi4 Class Reference

Inheritance diagram for forcebalance.psi4io.THCDF_Psi4:

Collaboration diagram for forcebalance.psi4io.THCDF_Psi4:

Public Member Functions

- def __init__

  All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)
- def prepare_temp_directory
- def indicate
- def write_nested_destroy
- def driver
- def get

  LPW 05-30-2012.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

Stages the directory for the target, and then launches Work Queue processes if any.

- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.

- def printcool_table

  Print target information in an organized table format.

- def set_option

Public Attributes

- Molecules
- throw_outs
- Elements
- GBSfnm

  Psi4 basis set file.

- DATfnm

  Psi4 input file for calculation of linear dependencies This is actually a file in 'forcefield' until we can figure out a better system.

- MP2_Energy

  Actually run PSI4.

- DF_Energy
- call_derivatives

  Number of snapshots.

- MAQ

  Dictionary for derivative terms.

- D
- objective
- tempdir

  Root directory of the whole project.

- rundir

  The directory in which the simulation is running - this can be updated.

- FF

  Need the forcefield (here for now)

- xct

  Counts how often the objective function was computed.

- gct

  Counts how often the gradient was computed.

- hct

  Counts how often the Hessian was computed.

- PrintOptionDict
- verbose_options

8.56.1 Detailed Description

Definition at line 97 of file psi4io.py.

8.56.2 Constructor & Destructor Documentation

8.56.2.1 def forcebalance.psi4io.THCDF_Psi4.__init__ (*self, options, tgt_opts, forcefield*)

All options here are intended to be usable by every conceivable type of target (in other words, only add content here if it's widely applicable.)

If we want to add attributes that are more specific (i.e. a set of reference forces for force matching), they are added in the subclass AbInitio that inherits from Target.

Reimplemented from forcebalance.leastsq.LeastSquares.

Definition at line 99 of file psi4io.py.

8.56.3 Member Function Documentation

8.56.3.1 def forcebalance.psi4io.THCDF_Psi4.driver (*self*)

Definition at line 172 of file psi4io.py.

Here is the call graph for this function:

8.56.3.2 def forcebalance.leastsq.LeastSquares.get (*self, mvals, AGrad* = `False`, *AHess* = `False`) `[inherited]`

LPW 05-30-2012.

This subroutine builds the objective function (and optionally its derivatives) from a general software.

This subroutine interfaces with simulation software 'drivers'. The driver is expected to give exact values, fitting values, and weights.

Parameters

in	*mvals*	Mathematical parameter values
in	*AGrad*	Switch to turn on analytic gradient
in	*AHess*	Switch to turn on analytic Hessian

Returns

Answer Contribution to the objective function

Reimplemented from forcebalance.target.Target.

Definition at line 74 of file leastsq.py.

8.56.3.3 def forcebalance.target.Target.get_G (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.56.3.4 def forcebalance.target.Target.get_H (*self*, *mvals* = None) [inherited]

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.56.3.5 def forcebalance.target.Target.get_X (*self*, *mvals* = None) [inherited]

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.56.3.6 def forcebalance.psi4io.THCDF_Psi4.indicate (*self*)

Reimplemented from forcebalance.leastsq.LeastSquares.

Definition at line 152 of file psi4io.py.

Here is the call graph for this function:

8.56.3.7 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.56.3.8 def forcebalance.psi4io.THCDF_Psi4.prepare_temp_directory (*self, options, tgt_opts*)

Definition at line 141 of file psi4io.py.

Here is the call graph for this function:

8.56.3.9 def forcebalance.target.Target.printcool_table (*self*, *data* = `OrderedDict([])`, *headings* = `[]`, *banner* = `None`, *footnote* = `None`, *color* = `0`) `[inherited]`

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.56.3.10 def forcebalance.target.Target.refresh_temp_directory (*self*) `[inherited]`

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.56.3.11 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.56.3.12 def forcebalance.target.Target.sget (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.56.3.13 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.56.3.14 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.56.3.15 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.56.3.16 def forcebalance.psi4io.THCDF_Psi4.write_nested_destroy (*self, fnm, linedestroy*)

Definition at line 157 of file psi4io.py.

Here is the call graph for this function:

8.56.4 Member Data Documentation

8.56.4.1 forcebalance::leastsq.LeastSquares::call_derivatives [inherited]

Number of snapshots.

Which parameters are differentiated?

Definition at line 40 of file leastsq.py.

8.56.4.2 forcebalance::leastsq.LeastSquares::D [inherited]

Definition at line 75 of file leastsq.py.

8.56.4.3 forcebalance::psi4io.THCDF_Psi4::DATfnm

Psi4 input file for calculation of linear dependencies This is actually a file in 'forcefield' until we can figure out a better system.

Definition at line 102 of file psi4io.py.

8.56.4.4 forcebalance::psi4io.THCDF_Psi4::DF_Energy

Definition at line 175 of file psi4io.py.

8.56.4.5 forcebalance::psi4io.THCDF_Psi4::Elements

Definition at line 99 of file psi4io.py.

8.56.4.6 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.56.4.7 forcebalance::psi4io.THCDF_Psi4::GBSfnm

Psi4 basis set file.

Definition at line 100 of file psi4io.py.

8.56.4.8 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.56.4.9 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.56.4.10 forcebalance::leastsq.LeastSquares::MAQ [inherited]

Dictionary for derivative terms.

Definition at line 75 of file leastsq.py.

8.56.4.11 forcebalance::psi4io.THCDF_Psi4::Molecules

Definition at line 99 of file psi4io.py.

8.56.4.12 forcebalance::psi4io.THCDF_Psi4::MP2_Energy

Actually run PSI4.

Read in the commented linindep.gbs file and ensure that these same lines are commented in the new .gbs file Now build a "Frankenstein" .gbs file composed of the original .gbs file but with data from the linindep.gbs file!

Definition at line 175 of file psi4io.py.

8.56.4.13 forcebalance::leastsq.LeastSquares::objective [inherited]

Definition at line 75 of file leastsq.py.

8.56.4.14 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.56.4.15 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.56.4.16 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.56.4.17 forcebalance::psi4io.THCDF_Psi4::throw_outs

Definition at line 99 of file psi4io.py.

8.56.4.18 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.56.4.19 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- psi4io.py

8.57 forcebalance.tinkerio.Tinker_Reader Class Reference

Finite state machine for parsing TINKER force field files.

Inheritance diagram for forcebalance.tinkerio.Tinker_Reader:

Collaboration diagram for forcebalance.tinkerio.Tinker_Reader:

Public Member Functions

- def __init__
- def feed

  Given a line, determine the interaction type and the atoms involved (the suffix).
- def Split
- def Whites
- def build_pid

  Returns the parameter type (e.g.

Public Attributes

- pdict

  The parameter dictionary (defined in this file)
- atom

  The atom numbers in the interaction (stored in the TINKER parser)
- itype
- suffix
- ln
- adict

  The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.
- molatom

  The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.
- Molecules
- AtomTypes

8.57.1 Detailed Description

Finite state machine for parsing TINKER force field files.

This class is instantiated when we begin to read in a file. The feed(line) method updates the state of the machine, informing it of the current interaction type. Using this information we can look up the interaction type and parameter type for building the parameter ID.

Definition at line 66 of file tinkerio.py.

8.57.2 Constructor & Destructor Documentation

8.57.2.1 def forcebalance.tinkerio.Tinker_Reader.__init__ (*self, fnm*)

Reimplemented from forcebalance.BaseReader.

Definition at line 68 of file tinkerio.py.

8.57.3 Member Function Documentation

8.57.3.1 def forcebalance.BaseReader.build_pid (*self, pfld*) [inherited]

Returns the parameter type (e.g.

K in BONDSK) based on the current interaction type.

Both the 'pdict' dictionary (see gmxio.pdict) and the interaction type 'state' (here, BONDS) are needed to get the parameter type.

If, however, 'pdict' does not contain the ptype value, a suitable substitute is simply the field number.

Note that if the interaction type state is not set, then it defaults to the file name, so a generic parameter ID is 'filename.-line_num.field_num'

Reimplemented in forcebalance.psi4io.Grid_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 107 of file __init__.py.

8.57.3.2 def forcebalance.tinkerio.Tinker_Reader.feed (*self, line*)

Given a line, determine the interaction type and the atoms involved (the suffix).

TINKER generally has stuff like this:

```
bond-cubic              -2.55
bond-quartic            3.793125

vdw           1               3.4050     0.1100
vdw           2               2.6550     0.0135      0.910 # PARM 4

multipole     2    1    2               0.25983
                                        -0.03859    0.00000   -0.05818
                                        -0.03673
                                         0.00000   -0.10739
                                        -0.00203    0.00000    0.14412
```

The '#PARM 4' has no effect on TINKER but it indicates that we are tuning the fourth field on the line (the 0.910 value).

Todo Put the rescaling factors for TINKER parameters in here. Currently we're using the initial value to determine the rescaling factor which is not very good.

Every parameter line is prefaced by the interaction type except for 'multipole' which is on multiple lines. Because the lines that come after 'multipole' are predictable, we just determine the current line using the previous line.

Random note: Unit of force is kcal / mole / angstrom squared.

Reimplemented from forcebalance.BaseReader.

Definition at line 109 of file tinkerio.py.

8.57.3.3 def forcebalance.BaseReader.Split (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 82 of file __init__.py.

Here is the call graph for this function:

8.57.3.4 def forcebalance.BaseReader.Whites (*self, line*) [inherited]

Reimplemented in forcebalance.amberio.FrcMod_Reader.

Definition at line 85 of file __init__.py.

Here is the call graph for this function:

8.57.4 Member Data Documentation

8.57.4.1 forcebalance.BaseReader::adict [inherited]

The mapping of (this residue, atom number) to (atom name) for building atom-specific interactions in [bonds], [angles] etc.

Reimplemented in forcebalance.amberio.FrcMod_Reader, and forcebalance.psi4io.GBS_Reader.

Definition at line 67 of file __init__.py.

8.57.4.2 forcebalance::tinkerio.Tinker_Reader::atom

The atom numbers in the interaction (stored in the TINKER parser)

Definition at line 70 of file tinkerio.py.

8.57.4.3 forcebalance.BaseReader::AtomTypes [inherited]

Definition at line 71 of file __init__.py.

8.57.4.4 forcebalance::tinkerio.Tinker_Reader::itype

Reimplemented from forcebalance.BaseReader.

Definition at line 109 of file tinkerio.py.

8.57.4.5 forcebalance.BaseReader::ln [inherited]

Definition at line 66 of file __init__.py.

8.57.4.6 forcebalance.BaseReader::molatom [inherited]

The mapping of (molecule name) to a dictionary of of atom types for the atoms in that residue.

self.moleculedict = OrderedDict() The listing of 'RES:ATOMNAMES' for atom names in the line This is obviously a placeholder.

Reimplemented in forcebalance.gmxio.ITP_Reader, and forcebalance.amberio.Mol2_Reader.

Definition at line 71 of file __init__.py.

8.57.4.7 forcebalance.BaseReader::Molecules [inherited]

Definition at line 71 of file __init__.py.

8.57.4.8 forcebalance::tinkerio.Tinker_Reader::pdict

The parameter dictionary (defined in this file)

Reimplemented from forcebalance.BaseReader.

Definition at line 69 of file tinkerio.py.

8.57.4.9 forcebalance::tinkerio.Tinker_Reader::suffix

Reimplemented from forcebalance.BaseReader.

Definition at line 109 of file tinkerio.py.

The documentation for this class was generated from the following file:

- tinkerio.py

8.58 forcebalance.nifty.Unpickler_LP Class Reference

A subclass of the python Unpickler that implements unpickling of _ElementTree types.

Public Member Functions

- def __init__

8.58.1 Detailed Description

A subclass of the python Unpickler that implements unpickling of _ElementTree types.

Definition at line 524 of file nifty.py.

8.58.2 Constructor & Destructor Documentation

8.58.2.1 def forcebalance.nifty.Unpickler_LP.__init__ (*self, file*)

Definition at line 525 of file nifty.py.

Here is the call graph for this function:

The documentation for this class was generated from the following file:

- nifty.py

8.59 forcebalance.vibration.Vibration Class Reference

Subclass of Target for fitting force fields to vibrational spectra (from experiment or theory).

Inheritance diagram for forcebalance.vibration.Vibration:

Collaboration diagram for forcebalance.vibration.Vibration:

Public Member Functions

- def __init__

  Initialization.
- def read_reference_data

  Read the reference vibrational data from a file.
- def prepare_temp_directory

  Prepare the temporary directory, by default does nothing.
- def indicate

  Print qualitative indicator.
- def get

  Evaluate objective function.
- def get_X

  Computes the objective function contribution without any parametric derivatives.
- def get_G

  Computes the objective function contribution and its gradient.
- def get_H

  Computes the objective function contribution and its gradient / Hessian.
- def link_from_tempdir
- def refresh_temp_directory

  Back up the temporary directory if desired, delete it and then create a new one.
- def sget

  Stages the directory for the target, and then calls 'get'.
- def submit_jobs
- def stage

  Stages the directory for the target, and then launches Work Queue processes if any.
- def wq_complete

  This method determines whether the Work Queue tasks for the current target have completed.

- def printcool_table

  Print target information in an organized table format.
- def set_option

Public Attributes

- vfnm

  The vdata.txt file that contains the vibrations.
- na

  Number of atoms.
- ref_eigvals
- ref_eigvecs
- calc_eigvals
- objective
- tempdir

  Root directory of the whole project.
- rundir

  The directory in which the simulation is running - this can be updated.
- FF

  Need the forcefield (here for now)
- xct

  Counts how often the objective function was computed.
- gct

  Counts how often the gradient was computed.
- hct

  Counts how often the Hessian was computed.
- PrintOptionDict
- verbose_options

8.59.1 Detailed Description

Subclass of Target for fitting force fields to vibrational spectra (from experiment or theory).

Currently Tinker is supported.

Definition at line 30 of file vibration.py.

8.59.2 Constructor & Destructor Documentation

8.59.2.1 def forcebalance.vibration.Vibration.__init__ (*self, options, tgt_opts, forcefield*)

Initialization.

Reimplemented from forcebalance.target.Target.

Definition at line 35 of file vibration.py.

8.59.3 Member Function Documentation

8.59.3.1 def forcebalance.vibration.Vibration.get (*self, mvals, AGrad* = `False`, *AHess* = `False`)

Evaluate objective function.

Reimplemented from forcebalance.target.Target.

Definition at line 111 of file vibration.py.

8.59.3.2 def forcebalance.target.Target.get_G (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient.

First the low-level 'get' method is called with the analytic gradient switch turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on. Alternately we can compute the gradient elements and diagonal Hessian elements at the same time using central difference if 'fdhessdiag' is turned on.

Definition at line 172 of file target.py.

Here is the call graph for this function:

8.59.3.3 def forcebalance.target.Target.get_H (*self, mvals* = `None`) `[inherited]`

Computes the objective function contribution and its gradient / Hessian.

First the low-level 'get' method is called with the analytic gradient and Hessian both turned on. Then we loop through the fd1_pids and compute the corresponding elements of the gradient by finite difference, if the 'fdgrad' switch is turned on.

This is followed by looping through the fd2_pids and computing the corresponding Hessian elements by finite difference. Forward finite difference is used throughout for the sake of speed.

Definition at line 195 of file target.py.

Here is the call graph for this function:

8.59.3.4 def forcebalance.target.Target.get_X (*self*, *mvals* = `None`) `[inherited]`

Computes the objective function contribution without any parametric derivatives.

Definition at line 155 of file target.py.

Here is the call graph for this function:

8.59.3.5 def forcebalance.vibration.Vibration.indicate (*self*)

Print qualitative indicator.

Definition at line 102 of file vibration.py.

Here is the call graph for this function:

8.59.3.6 def forcebalance.target.Target.link_from_tempdir (*self, absdestdir*) [inherited]

Definition at line 213 of file target.py.

8.59.3.7 def forcebalance.vibration.Vibration.prepare_temp_directory (*self, options, tgt_opts*)

Prepare the temporary directory, by default does nothing.

Definition at line 97 of file vibration.py.

8.59.3.8 def forcebalance.target.Target.printcool_table (*self, data* = OrderedDict([]), *headings* = [], *banner* = None, *footnote* = None, *color* = 0) [inherited]

Print target information in an organized table format.

Implemented 6/30 because multiple targets are already printing out tabulated information in very similar ways. This

method is a simple wrapper around printcool_dictionary.

The input should be something like:

Parameters

data	Column contents in the form of an OrderedDict, with string keys and list vals. The key is printed in the leftmost column and the vals are printed in the other columns. If non-strings are passed, they will be converted to strings (not recommended).
headings	Column headings in the form of a list. It must be equal to the number to the list length for each of the "vals" in OrderedDict, plus one. Use "\n" characters to specify long column names that may take up more than one line.
banner	Optional heading line, which will be printed at the top in the title.
footnote	Optional footnote line, which will be printed at the bottom.

Definition at line 367 of file target.py.

Here is the call graph for this function:

8.59.3.9 def forcebalance.vibration.Vibration.read_reference_data (*self*)

Read the reference vibrational data from a file.

Definition at line 57 of file vibration.py.

8.59.3.10 def forcebalance.target.Target.refresh_temp_directory (*self*) [inherited]

Back up the temporary directory if desired, delete it and then create a new one.

Definition at line 219 of file target.py.

Here is the call graph for this function:

8.59.3.11 def forcebalance.BaseClass.set_option (*self, in_dict, src_key, dest_key* = None, *val* = None, *default* = None, *forceprint* = False) [inherited]

Definition at line 32 of file __init__.py.

8.59.3.12 def forcebalance.target.Target.sget (*self, mvals, AGrad* = False, *AHess* = False, *customdir* = None) [inherited]

Stages the directory for the target, and then calls 'get'.

The 'get' method should not worry about the directory that it's running in.

Definition at line 266 of file target.py.

Here is the call graph for this function:

8.59.3.13 def forcebalance.target.Target.stage (*self, mvals, AGrad* = `False`, *AHess* = `False`, *customdir* = `None`) [inherited]

Stages the directory for the target, and then launches Work Queue processes if any.

The 'get' method should not worry about the directory that it's running in.

Definition at line 301 of file target.py.

Here is the call graph for this function:

8.59.3.14 def forcebalance.target.Target.submit_jobs (*self, mvals, AGrad* = `False`, *AHess* = `False`) [inherited]

Reimplemented in forcebalance.target.RemoteTarget, forcebalance.psi4io.RDVR3_Psi4, and forcebalance.liquid.Liquid.

Definition at line 291 of file target.py.

8.59.3.15 def forcebalance.target.Target.wq_complete (*self*) [inherited]

This method determines whether the Work Queue tasks for the current target have completed.

Definition at line 331 of file target.py.

Here is the call graph for this function:

8.59.4 Member Data Documentation

8.59.4.1 forcebalance::vibration.Vibration::calc_eigvals

Definition at line 111 of file vibration.py.

8.59.4.2 forcebalance::target.Target::FF [inherited]

Need the forcefield (here for now)

Definition at line 109 of file target.py.

8.59.4.3 forcebalance::target.Target::gct [inherited]

Counts how often the gradient was computed.

Definition at line 111 of file target.py.

8.59.4.4 forcebalance::target.Target::hct [inherited]

Counts how often the Hessian was computed.

Definition at line 112 of file target.py.

8.59.4.5 forcebalance::vibration.Vibration::na

Number of atoms.

Definition at line 58 of file vibration.py.

8.59.4.6 forcebalance::vibration.Vibration::objective

Definition at line 111 of file vibration.py.

8.59.4.7 forcebalance.BaseClass::PrintOptionDict [inherited]

Definition at line 28 of file __init__.py.

8.59.4.8 forcebalance::vibration.Vibration::ref_eigvals

Definition at line 58 of file vibration.py.

8.59.4.9 forcebalance::vibration.Vibration::ref_eigvecs

Definition at line 58 of file vibration.py.

8.59.4.10 forcebalance::target.Target::rundir [inherited]

The directory in which the simulation is running - this can be updated.

Directory of the current iteration; if not None, then the simulation runs under temp/target_name/iteration_number The 'customdir' is customizable and can go below anything.

Definition at line 108 of file target.py.

8.59.4.11 forcebalance::target.Target::tempdir [inherited]

Root directory of the whole project.

Name of the target Type of target Relative weight of the target Switch for finite difference gradients Switch for finite difference Hessians Switch for FD gradients + Hessian diagonals How many seconds to sleep (if any) Parameter types that trigger FD gradient elements Parameter types that trigger FD Hessian elements Finite difference step size Whether to make backup files Relative directory of target Temporary (working) directory; it is temp/(target_name) Used for storing temporary variables that don't change through the course of the optimization

Definition at line 107 of file target.py.

8.59.4.12 forcebalance.BaseClass::verbose_options [inherited]

Definition at line 28 of file __init__.py.

8.59.4.13 forcebalance::vibration.Vibration::vfnm

The vdata.txt file that contains the vibrations.

Definition at line 36 of file vibration.py.

8.59.4.14 forcebalance::target.Target::xct [inherited]

Counts how often the objective function was computed.

Definition at line 110 of file target.py.

The documentation for this class was generated from the following file:

- vibration.py

8.60 forcebalance.tinkerio.Vibration_TINKER Class Reference

Subclass of Target for vibrational frequency matching using TINKER.

Inheritance diagram for forcebalance.tinkerio.Vibration_TINKER:

Collaboration diagram for forcebalance.tinkerio.Vibration_TINKER:

Public Member Functions

- def __init__
- def prepare_temp_directory
- def vibration_driver

8.60.1 Detailed Description

Subclass of Target for vibrational frequency matching using TINKER.

Provides optimized geometry, vibrational frequencies (in cm-1), and eigenvectors.

Definition at line 353 of file tinkerio.py.

8.60.2 Constructor & Destructor Documentation

8.60.2.1 def forcebalance.tinkerio.Vibration_TINKER.__init__ (*self, options, tgt_opts, forcefield*)

Definition at line 356 of file tinkerio.py.

Here is the call graph for this function:

8.60.3 Member Function Documentation

8.60.3.1 def forcebalance.tinkerio.Vibration_TINKER.prepare_temp_directory (*self, options, tgt_opts*)

Definition at line 361 of file tinkerio.py.

Here is the call graph for this function:

8.60.3.2 def forcebalance.tinkerio.Vibration_TINKER.vibration_driver (*self*)

Definition at line 371 of file tinkerio.py.

Here is the call graph for this function:

The documentation for this class was generated from the following file:

- tinkerio.py

9 File Documentation

9.1 __init__.py File Reference

Classes

- class forcebalance.BaseClass

  Provides some nifty functions that are common to all ForceBalance classes.
- class forcebalance.BaseReader

  The 'reader' class.

Packages

- namespace forcebalance

Variables

- tuple forcebalance.__version__ = pkg_resources.get_distribution("forcebalance")

9.2 abinitio.py File Reference

Classes

- class forcebalance.abinitio.AbInitio

  Subclass of Target for fitting force fields to ab initio data.

Packages

- namespace forcebalance::abinitio

  Ab-initio fitting module (energies, forces, resp).

Functions

- def forcebalance::abinitio.weighted_variance

  A more generalized version of build_objective which is callable for derivatives, but the covariance is not there anymore.
- def forcebalance::abinitio.weighted_variance2

  A bit of a hack, since we have to subtract out two mean quantities to get Hessian elements.
- def forcebalance::abinitio.build_objective

  This function builds an objective function (number) from the complicated polytensor and covariance matrices.

Variables

- tuple forcebalance::abinitio.logger = getLogger(__name__)

9.3 abinitio_internal.py File Reference

Classes

- class forcebalance.abinitio_internal.AbInitio_Internal

  Subclass of Target for force and energy matching using an internal implementation.

Packages

- namespace forcebalance::abinitio_internal

  Internal implementation of energy matching (for TIP3P water only)

9.4 amberio.py File Reference

Classes

- class forcebalance.amberio.Mol2_Reader

  Finite state machine for parsing Mol2 force field file.
- class forcebalance.amberio.FrcMod_Reader

  Finite state machine for parsing FrcMod force field file.
- class forcebalance.amberio.AbInitio_AMBER

  Subclass of Target for force and energy matching using AMBER.

Packages

- namespace forcebalance::amberio

  AMBER force field input/output.

Functions

- def forcebalance::amberio.is_mol2_atom

Variables

- tuple forcebalance::amberio.logger = getLogger(__name__)
- dictionary forcebalance::amberio.mol2_pdict = {'COUL':{'Atom':[1], 8:''}}
- dictionary forcebalance::amberio.frcmod_pdict

9.5 api.dox File Reference

9.6 binding.py File Reference

Classes

- class forcebalance.binding.BindingEnergy

  Improved subclass of Target for fitting force fields to binding energies.

Packages

- namespace forcebalance::binding

  Binding energy fitting module.

Functions

- def forcebalance::binding.parse_interactions

  Parse through the interactions input file.

Variables

- tuple forcebalance::binding.logger = getLogger(__name__)

9.7 chemistry.py File Reference

Packages

- namespace forcebalance::chemistry

Functions

- def forcebalance::chemistry.LookupByMass
- def forcebalance::chemistry.BondStrengthByLength

Variables

- tuple forcebalance::chemistry.BondEnergies = defaultdict(lambda:defaultdict(dict))
- list forcebalance::chemistry.Radii

  Covalent radii from Cordero et al.
- dictionary forcebalance::chemistry.PeriodicTable
- list forcebalance::chemistry.Elements
- list forcebalance::chemistry.BondChars = ['-','=','3']
- string forcebalance::chemistry.data_from_web
- tuple forcebalance::chemistry.line = line.expandtabs()
- tuple forcebalance::chemistry.BE = float(line.split()[1])
- tuple forcebalance::chemistry.L = float(line.split()[2])
- tuple forcebalance::chemistry.atoms = re.split('[-=3]', line.split()[0])
- list forcebalance::chemistry.A = atoms[0]
- list forcebalance::chemistry.B = atoms[1]
- tuple forcebalance::chemistry.bo = BondChars.index(re.findall('[-=3]', line.split()[0])[0])

9.8 contact.py File Reference

Packages

- namespace forcebalance::contact

Functions

- def forcebalance::contact.atom_distances

  For each frame in xyzlist, compute the (euclidean) distance between pairs of atoms whos indices are given in contacts.
- def forcebalance::contact.residue_distances

  For each frame in xyzlist, and for each pair of residues in the array contact, compute the distance between the closest pair of atoms such that one of them belongs to each residue.

9.9 counterpoise.py File Reference

Classes

- class forcebalance.counterpoise.Counterpoise

  Target subclass for matching the counterpoise correction.

Packages

- namespace forcebalance::counterpoise

  Match an empirical potential to the counterpoise correction for basis set superposition error (BSSE).

Variables

- tuple forcebalance::counterpoise.logger = getLogger(__name__)

9.10 custom_io.py File Reference

Classes

- class forcebalance.custom_io.Gen_Reader

  Finite state machine for parsing custom GROMACS force field files.

Packages

- namespace forcebalance::custom_io

  Custom force field parser.

Variables

- list forcebalance::custom_io.cptypes = [None, 'CPGAUSS', 'CPEXPG', 'CPGEXP']

  Types of counterpoise correction.
- list forcebalance::custom_io.ndtypes = [None]

  Types of NDDO correction.
- dictionary forcebalance::custom_io.fdict

  Section -> Interaction type dictionary.
- dictionary forcebalance::custom_io.pdict

  Interaction type -> Parameter Dictionary.

9.11 engine.py File Reference

Classes

- class forcebalance.engine.Engine

  Base class for all engines.

Packages

- namespace forcebalance::engine

Variables

- tuple forcebalance::engine.logger = getLogger(__name__)

9.12 finite_difference.py File Reference

Packages

- namespace forcebalance::finite_difference

Functions

- def forcebalance::finite_difference.f1d2p

  A two-point finite difference stencil.
- def forcebalance::finite_difference.f1d5p

  A highly accurate five-point finite difference stencil for computing derivatives of a function.
- def forcebalance::finite_difference.f1d7p

  A highly accurate seven-point finite difference stencil for computing derivatives of a function.
- def forcebalance::finite_difference.f12d7p
- def forcebalance::finite_difference.f12d3p

  A three-point finite difference stencil.
- def forcebalance::finite_difference.in_fd

  Invoking this function from anywhere will tell us whether we're being called by a finite-difference function.
- def forcebalance::finite_difference.fdwrap

  A function wrapper for finite difference designed for differentiating 'get'-type functions.
- def forcebalance::finite_difference.fdwrap_G

  A driver to fdwrap for gradients (see documentation for fdwrap) Inputs: tgt = The Target containing the objective function that we want to differentiate mvals0 = The 'central' values of the mathematical parameters - i.e.
- def forcebalance::finite_difference.fdwrap_H

  A driver to fdwrap for Hessians (see documentation for fdwrap) Inputs: tgt = The Target containing the objective function that we want to differentiate mvals0 = The 'central' values of the mathematical parameters - i.e.

Variables

- tuple forcebalance::finite_difference.logger = getLogger(__name__)

9.13 forcefield.py File Reference

Classes

- class forcebalance.forcefield.BackedUpDict
- class forcebalance.forcefield.FF

  Force field class.

Packages

- namespace forcebalance::forcefield

  Force field module.

Functions

- def forcebalance::forcefield.determine_fftype

  Determine the type of a force field file.
- def forcebalance::forcefield.rs_override

  This function takes in a dictionary (rsfactors) and a string (termtype).

Variables

- tuple forcebalance::forcefield.logger = getLogger(__name__)
- dictionary forcebalance::forcefield.FF_Extensions
- dictionary forcebalance::forcefield.FF_IOModules

9.14 gmxio.py File Reference

Classes

- class forcebalance.gmxio.ITP_Reader

  Finite state machine for parsing GROMACS force field files.
- class forcebalance.gmxio.GMX

  Derived from Engine object for carrying out general purpose GROMACS calculations.
- class forcebalance.gmxio.AbInitio_GMX

  Subclass of AbInitio for force and energy matching using normal GROMACS.
- class forcebalance.gmxio.Liquid_GMX
- class forcebalance.gmxio.Interaction_GMX

  Subclass of Interaction for interaction energy matching using GROMACS.

Packages

- namespace forcebalance::gmxio

  GROMACS input/output.

Functions

- def forcebalance::gmxio.edit_mdp

  Create or edit a Gromacs MDP file.
- def forcebalance::gmxio.parse_atomtype_line

  Parses the 'atomtype' line.
- def forcebalance::gmxio.rm_gmx_baks

Variables

- tuple forcebalance::gmxio.logger = getLogger(__name__)
- list forcebalance::gmxio.nftypes = [None, 'VDW', 'VDW_BHAM']

  VdW interaction function types.
- list forcebalance::gmxio.pftypes = [None, 'VPAIR', 'VPAIR_BHAM']

  Pairwise interaction function types.

- list forcebalance::gmxio.bftypes = [None, 'BONDS', 'G96BONDS', 'MORSE']

  Bonded interaction function types.
- list forcebalance::gmxio.aftypes

  Angle interaction function types.
- list forcebalance::gmxio.dftypes = [None, 'PDIHS', 'IDIHS', 'RBDIHS', 'PIMPDIHS', 'FOURDIHS', None, None, 'TABDIHS', 'PDIHMULS']

  Dihedral interaction function types.
- dictionary forcebalance::gmxio.fdict

  Section -> Interaction type dictionary.
- dictionary forcebalance::gmxio.pdict

  Interaction type -> Parameter Dictionary.
- string forcebalance::gmxio.shot_mdp

9.15 gmxqpio.py File Reference

Classes

- class forcebalance.gmxqpio.Monomer_QTPIE

  Subclass of Target for monomer properties of QTPIE (implemented within gromacs WCV branch).

Packages

- namespace forcebalance::gmxqpio
- namespace forcebalance::gmxio

  GROMACS input/output.

Functions

- def forcebalance::gmxqpio.get_monomer_properties

Variables

- tuple forcebalance::gmxqpio.logger = getLogger(__name__)

9.16 interaction.py File Reference

Classes

- class forcebalance.interaction.Interaction

  Subclass of Target for fitting force fields to interaction energies.

Packages

- namespace forcebalance::interaction

  Interaction energy fitting module.

Variables

- tuple forcebalance::interaction.logger = getLogger(__name__)

9.17 leastsq.py File Reference

Classes

- class forcebalance.leastsq.LeastSquares

  Subclass of Target for general least squares fitting.

Packages

- namespace forcebalance::leastsq
- namespace forcebalance::abinitio

  Ab-initio fitting module (energies, forces, resp).

Functions

- def forcebalance::leastsq.CheckBasis
- def forcebalance::leastsq.LastMvals

Variables

- tuple forcebalance::leastsq.logger = getLogger(__name__)
- forcebalance::leastsq.CHECK_BASIS = False
- forcebalance::leastsq.LAST_MVALS = None

9.18 liquid.py File Reference

Classes

- class forcebalance.liquid.Liquid

  Subclass of Target for liquid property matching.

Packages

- namespace forcebalance::liquid

  Matching of liquid bulk properties.

Functions

- def forcebalance::liquid.weight_info

Variables

- tuple forcebalance::liquid.logger = getLogger(__name__)

9.19 Mol2.py File Reference

Classes

- class forcebalance.Mol2.mol2_atom

  This is to manage mol2 atomic lines on the form: 1 C1 5.4790 42.2880 49.5910 C.ar 1 <1> 0.0424.
- class forcebalance.Mol2.mol2_bond

  This is to manage mol2 bond lines on the form: 1 1 2 ar.
- class forcebalance.Mol2.mol2

  This is to manage one mol2 series of lines on the form:
- class forcebalance.Mol2.mol2_set

Packages

- namespace forcebalance::Mol2

Variables

- tuple forcebalance::Mol2.data = mol2_set(sys.argv[1], subset=["RNAse.xray.inh8.1QHC"])

9.20 mol2io.py File Reference

Classes

- class forcebalance.mol2io.Mol2_Reader

  Finite state machine for parsing Mol2 force field file.

Packages

- namespace forcebalance::mol2io

  Mol2 I/O.

Variables

- dictionary forcebalance::mol2io.mol2_pdict = {'COUL':{'Atom':[1], 6:''}}

9.21 molecule.py File Reference

Classes

- class forcebalance.molecule.MolfileTimestep

  Wrapper for the timestep C structure used in molfile plugins.
- class forcebalance.molecule.Molecule

  Lee-Ping's general file format conversion class.

Packages

- namespace forcebalance::molecule

Functions

- def forcebalance::molecule.getElement
- def forcebalance::molecule.elem_from_atomname

  Given an atom name, attempt to get the element in most cases.
- def forcebalance::molecule.nodematch
- def forcebalance::molecule.isint

  ONLY matches integers! If you have a decimal point? None shall pass!
- def forcebalance::molecule.isfloat

  Matches ANY number; it can be a decimal, scientific notation, integer, or what have you.
- def forcebalance::molecule.BuildLatticeFromLengthsAngles

  This function takes in three lattice lengths and three lattice angles, and tries to return a complete box specification.
- def forcebalance::molecule.BuildLatticeFromVectors

  This function takes in three lattice vectors and tries to return a complete box specification.
- def forcebalance::molecule.format_xyz_coord

  Print a line consisting of (element, x, y, z) in accordance with .xyz file format.
- def forcebalance::molecule.format_gro_coord

  Print a line in accordance with .gro file format, with six decimal points of precision.
- def forcebalance::molecule.format_xyzgen_coord

  Print a line consisting of (element, p, q, r, s, t, ...) where (p, q, r) are arbitrary atom-wise data (this might happen, for instance, with atomic charges)
- def forcebalance::molecule.format_gro_box

  Print a line corresponding to the box vector in accordance with .gro file format.
- def forcebalance::molecule.is_gro_coord

  Determines whether a line contains GROMACS data or not.
- def forcebalance::molecule.is_charmm_coord

  Determines whether a line contains CHARMM data or not.
- def forcebalance::molecule.is_gro_box

  Determines whether a line contains a GROMACS box vector or not.
- def forcebalance::molecule.add_strip_to_mat
- def forcebalance::molecule.pvec
- def forcebalance::molecule.grouper

  Groups a big long iterable into groups of ten or what have you.
- def forcebalance::molecule.even_list

  Creates a list of number sequences divided as evenly as possible.
- def forcebalance::molecule.both
- def forcebalance::molecule.diff
- def forcebalance::molecule.either
- def forcebalance::molecule.EulerMatrix

  Constructs an Euler matrix from three Euler angles.
- def forcebalance::molecule.ComputeOverlap

  Computes an 'overlap' between two molecules based on some fictitious density.
- def forcebalance::molecule.AlignToDensity

  Computes a "overlap density" from two frames.
- def forcebalance::molecule.AlignToMoments

  Pre-aligns molecules to 'moment of inertia'.
- def forcebalance::molecule.get_rotate_translate
- def forcebalance::molecule.cartesian_product2

  Form a Cartesian product of two NumPy arrays.
- def forcebalance::molecule.main

Variables

- tuple forcebalance::molecule::FrameVariableNames
- tuple forcebalance::molecule.AtomVariableNames = set(['elem', 'partial_charge', 'atomname', 'atomtype', 'tinkersuf', 'resid', 'resname', 'qcsuf', 'qm_ghost', 'chain', 'altloc', 'icode'])
- tuple forcebalance::molecule.MetaVariableNames = set(['fnm', 'ftype', 'qcrems', 'qctemplate', 'charge', 'mult', 'bonds'])
- tuple forcebalance::molecule.QuantumVariableNames = set(['qcrems', 'qctemplate', 'charge', 'mult', 'qcsuf', 'qm_ghost'])
- forcebalance::molecule.AllVariableNames = QuantumVariableNames|AtomVariableNames|MetaVariableNames|FrameVariableNames
- list forcebalance::molecule.Radii
- list forcebalance::molecule.Elements
- tuple forcebalance::molecule.PeriodicTable
- float forcebalance::molecule.bohrang = 0.529177249

  One bohr equals this many angstroms.
- tuple forcebalance::molecule.splitter = re.compile(r'(\s+|\S+)')
- tuple forcebalance::molecule.Box = namedtuple('Box',['a','b','c','alpha','beta','gamma','A','B','C','V'])
- int forcebalance::molecule.radian = 180
- forcebalance::molecule::Alive

9.22 moments.py File Reference

Classes

- class forcebalance.moments.Moments

  Subclass of Target for fitting force fields to multipole moments (from experiment or theory).

Packages

- namespace forcebalance::moments

  Multipole moment fitting module.

Variables

- tuple forcebalance::moments.logger = getLogger(__name__)

9.23 nifty.py File Reference

Classes

- class forcebalance.nifty.Pickler_LP

  A subclass of the python Pickler that implements pickling of _ElementTree types.
- class forcebalance.nifty.Unpickler_LP

  A subclass of the python Unpickler that implements unpickling of _ElementTree types.
- class forcebalance.nifty.LineChunker

Packages

- namespace forcebalance::nifty

  Nifty functions, intended to be imported by any module within ForceBalance.

Functions

- def forcebalance::nifty.pvec1d

  Printout of a 1-D vector.
- def forcebalance::nifty.pmat2d

  Printout of a 2-D matrix.
- def forcebalance::nifty.encode
- def forcebalance::nifty.segments
- def forcebalance::nifty.commadash
- def forcebalance::nifty.uncommadash
- def forcebalance::nifty.printcool

  Cool-looking printout for slick formatting of output.
- def forcebalance::nifty.printcool_dictionary

  See documentation for printcool; this is a nice way to print out keys/values in a dictionary.
- def forcebalance::nifty.isint

  ONLY matches integers! If you have a decimal point? None shall pass!
- def forcebalance::nifty.isfloat

  Matches ANY number; it can be a decimal, scientific notation, what have you CAUTION - this will also match an integer.
- def forcebalance::nifty.isdecimal

  Matches things with a decimal only; see isint and isfloat.
- def forcebalance::nifty.floatornan

  Returns a big number if we encounter NaN.
- def forcebalance::nifty.col

  Given any list, array, or matrix, return a 1-column matrix.
- def forcebalance::nifty.row

  Given any list, array, or matrix, return a 1-row matrix.
- def forcebalance::nifty.flat

  Given any list, array, or matrix, return a single-index array.
- def forcebalance::nifty.orthogonalize

  Given two vectors vec1 and vec2, project out the component of vec1 that is along the vec2-direction.
- def forcebalance::nifty.invert_svd

  Invert a matrix using singular value decomposition.
- def forcebalance::nifty.get_least_squares
- def forcebalance::nifty.statisticalInefficiency

  Compute the (cross) statistical inefficiency of (two) timeseries.
- def forcebalance::nifty.lp_dump

  Use this instead of pickle.dump for pickling anything that contains _ElementTree types.
- def forcebalance::nifty.lp_load

  Use this instead of pickle.load for unpickling anything that contains _ElementTree types.
- def forcebalance::nifty.getWorkQueue
- def forcebalance::nifty.getWQIds
- def forcebalance::nifty.createWorkQueue
- def forcebalance::nifty.destroyWorkQueue

- def forcebalance::nifty.queue_up

  Submit a job to the Work Queue.
- def forcebalance::nifty.queue_up_src_dest

  Submit a job to the Work Queue.
- def forcebalance::nifty.wq_wait1

  This function waits ten seconds to see if a task in the Work Queue has finished.
- def forcebalance::nifty.wq_wait

  This function waits until the work queue is completely empty.
- def forcebalance::nifty.onefile
- def forcebalance::nifty.GoInto
- def forcebalance::nifty.allsplit
- def forcebalance::nifty.Leave
- def forcebalance::nifty.MissingFileInspection
- def forcebalance::nifty.LinkFile
- def forcebalance::nifty.CopyFile
- def forcebalance::nifty.link_dir_contents
- def forcebalance::nifty.remove_if_exists

  Remove the file if it exists (doesn't return an error).
- def forcebalance::nifty.which
- def forcebalance::nifty.warn_press_key
- def forcebalance::nifty.warn_once

  Prints a warning but will only do so once in a given run.
- def forcebalance::nifty.concurrent_map

  Similar to the bultin function map().
- def forcebalance::nifty.multiopen

  This function be given any of several variable types (single file name, file object, or list of lines, or a list of the above) and give a list of files:

Variables

- tuple forcebalance::nifty.logger = getLogger(__name__)
- float forcebalance::nifty.kb = 0.0083144100163

  Boltzmann constant.
- float forcebalance::nifty.eqcgmx = 2625.5002

  Q-Chem to GMX unit conversion for energy.
- float forcebalance::nifty.fqcgmx = 49621.9

  Q-Chem to GMX unit conversion for force.
- float forcebalance::nifty.bohrang = 0.529177249

  One bohr equals this many angstroms.
- string forcebalance::nifty.XMLFILE = 'x'

  Pickle uses 'flags' to pickle and unpickle different variable types.
- forcebalance::nifty.WORK_QUEUE = None
- tuple forcebalance::nifty.WQIDS = defaultdict(list)
- list forcebalance::nifty.specific_lst
- tuple forcebalance::nifty.specific_dct = dict(list(itertools.chain(*[[(j,i[1]) for j in i[0]] for i in specific_lst])))

9.24 objective.py File Reference

Classes

- class forcebalance.objective.Objective

  Objective function.
- class forcebalance.objective.Penalty

  Penalty functions for regularizing the force field optimizer.

Packages

- namespace forcebalance::objective

  ForceBalance objective function.

Variables

- tuple forcebalance::objective.logger = getLogger(__name__)
- dictionary forcebalance::objective.Implemented_Targets

  The table of implemented Targets.
- list forcebalance::objective.Letters = ['X','G','H']

  This is the canonical lettering that corresponds to : objective function, gradient, Hessian.

9.25 openmmio.py File Reference

Classes

- class forcebalance.openmmio.OpenMM_Reader

  Class for parsing OpenMM force field files.
- class forcebalance.openmmio.Liquid_OpenMM
- class forcebalance.openmmio.AbInitio_OpenMM

  Subclass of AbInitio for force and energy matching using OpenMM.
- class forcebalance.openmmio.Interaction_OpenMM

  Subclass of Target for interaction matching using OpenMM.

Packages

- namespace forcebalance::openmmio

  OpenMM input/output.

Functions

- def forcebalance::openmmio.get_dipole

  Return the current dipole moment in Debye.
- def forcebalance::openmmio.ResetVirtualSites

  Given a set of OpenMM-compatible positions and a System object, compute the correct virtual site positions according to the System.
- def forcebalance::openmmio.CopyAmoebaBondParameters

- def forcebalance::openmmio.CopyAmoebaOutOfPlaneBendParameters
- def forcebalance::openmmio.CopyAmoebaAngleParameters
- def forcebalance::openmmio.CopyAmoebaInPlaneAngleParameters
- def forcebalance::openmmio.CopyAmoebaVdwParameters
- def forcebalance::openmmio.CopyAmoebaMultipoleParameters
- def forcebalance::openmmio.CopyHarmonicBondParameters
- def forcebalance::openmmio.CopyHarmonicAngleParameters
- def forcebalance::openmmio.CopyPeriodicTorsionParameters
- def forcebalance::openmmio.CopyNonbondedParameters
- def forcebalance::openmmio.do_nothing
- def forcebalance::openmmio.CopySystemParameters

  Copy parameters from one system (i.e.
- def forcebalance::openmmio.UpdateSimulationParameters
- def forcebalance::openmmio.SetAmoebaVirtualExclusions
- def forcebalance::openmmio.MTSVVVRIntegrator

  Create a multiple timestep velocity verlet with velocity randomization (VVVR) integrator.

Variables

- tuple forcebalance::openmmio.logger = getLogger(__name__)
- dictionary forcebalance::openmmio.suffix_dict
- string forcebalance::openmmio.pdict = "XML_Override"

  pdict is a useless variable if the force field is XML.

9.26 optimizer.py File Reference

Classes

- class forcebalance.optimizer.Optimizer

  Optimizer class.

Packages

- namespace forcebalance::optimizer

  Optimization algorithms.

Functions

- def forcebalance::optimizer.Counter
- def forcebalance::optimizer.GoodStep

Variables

- tuple forcebalance::optimizer.logger = getLogger(__name__)
- int forcebalance::optimizer.ITERATION_NUMBER = 0
- int forcebalance::optimizer.GOODSTEP = 0

9.27 output.py File Reference

Classes

- class forcebalance.output.ForceBalanceLogger

  This logger starts out with a default handler that writes to stdout addHandler removes this default the first time another handler is added.
- class forcebalance.output.RawStreamHandler

  Exactly like output.StreamHandler except it does no extra formatting before sending logging messages to the stream.
- class forcebalance.output.RawFileHandler

  Exactly like output.FileHandler except it does no extra formatting before sending logging messages to the file.
- class forcebalance.output.CleanStreamHandler

  Similar to RawStreamHandler except it does not write terminal escape codes.
- class forcebalance.output.CleanFileHandler

  File handler that does not write terminal escape codes and carriage returns to files.

Packages

- namespace forcebalance::output

9.28 parser.py File Reference

Packages

- namespace forcebalance::parser

  Input file parser for ForceBalance jobs.

Functions

- def forcebalance::parser.read_mvals
- def forcebalance::parser.read_pvals
- def forcebalance::parser.read_priors
- def forcebalance::parser.read_internals
- def forcebalance::parser.printsection

  Print out a section of the input file in a parser-compliant and readable format.
- def forcebalance::parser.parse_inputs

  Parse through the input file and read all user-supplied options.

Variables

- tuple forcebalance::parser.logger = getLogger(__name__)
- dictionary forcebalance::parser.gen_opts_types

  Default general options.
- dictionary forcebalance::parser.tgt_opts_types

  Default fitting target options.
- tuple forcebalance::parser.all_opts_names = list(itertools.chain(∗[i.keys() for i in gen_opts_types.values()]))
- list forcebalance::parser.iocc = []

  Check for uniqueness of option names.

- dictionary forcebalance::parser.gen_opts_defaults = {}

  Default general options - basically a collapsed veresion of gen_opts_types.
- dictionary forcebalance::parser.subdict = {}
- dictionary forcebalance::parser.tgt_opts_defaults = {}

  Default target options - basically a collapsed version of tgt_opts_types.
- dictionary forcebalance::parser.bkwd = {"simtype" : "type", "masterfile" : "binding_txt"}

  Option maps for maintaining backward compatibility.
- list forcebalance::parser.mainsections = ["SIMULATION","TARGET","OPTIONS","END","NONE"]

  Listing of sections in the input file.
- dictionary forcebalance::parser.ParsTab

  ParsTab that refers to subsection parsers.

9.29 psi4io.py File Reference

Classes

- class forcebalance.psi4io.GBS_Reader

  Interaction type -> Parameter Dictionary.
- class forcebalance.psi4io.THCDF_Psi4
- class forcebalance.psi4io.Grid_Reader

  Finite state machine for parsing DVR grid files.
- class forcebalance.psi4io.RDVR3_Psi4

  Subclass of Target for R-DVR3 grid fitting.

Packages

- namespace forcebalance::psi4io

  PSI4 force field input/output.

Variables

- tuple forcebalance::psi4io.logger = getLogger(__name__)

9.30 PT.py File Reference

Packages

- namespace forcebalance::PT

Variables

- dictionary forcebalance::PT::PeriodicTable
- list forcebalance::PT.Elements

9.31 qchemio.py File Reference

Classes

- class forcebalance.qchemio.QCIn_Reader

  Finite state machine for parsing Q-Chem input files.

Packages

- namespace forcebalance::qchemio

  Q-Chem input file parser.

Functions

- def forcebalance::qchemio.QChem_Dielectric_Energy

Variables

- tuple forcebalance::qchemio.logger = getLogger(__name__)
- list forcebalance::qchemio.ndtypes = [None]

  Types of counterpoise correction cptypes = [None, 'BASS', 'BASSP'] Types of NDDO correction.
- dictionary forcebalance::qchemio.pdict

  Section -> Interaction type dictionary.

9.32 target.py File Reference

Classes

- class forcebalance.target.Target

  Base class for all fitting targets.
- class forcebalance.target.RemoteTarget

Packages

- namespace forcebalance::target

Variables

- tuple forcebalance::target.logger = getLogger(__name__)

9.33 tinkerio.py File Reference

Classes

- class forcebalance.tinkerio.Tinker_Reader

  Finite state machine for parsing TINKER force field files.
- class forcebalance.tinkerio.Liquid_TINKER

- class forcebalance.tinkerio.AbInitio_TINKER

  Subclass of Target for force and energy matching using TINKER.
- class forcebalance.tinkerio.Vibration_TINKER

  Subclass of Target for vibrational frequency matching using TINKER.
- class forcebalance.tinkerio.Moments_TINKER

  Subclass of Target for multipole moment matching using TINKER.
- class forcebalance.tinkerio.BindingEnergy_TINKER

  Subclass of BindingEnergy for binding energy matching using TINKER.
- class forcebalance.tinkerio.Interaction_TINKER

  Subclass of Target for interaction matching using TINKER.

Packages

- namespace forcebalance::tinkerio

  TINKER input/output.

Functions

- def forcebalance::tinkerio.write_key_with_prm

  Copies a TINKER .key file but changes the parameter keyword as necessary to reflect the ForceBalance settings.
- def forcebalance::tinkerio.modify_key

  Performs in-place modification of a TINKER .key file.

Variables

- tuple forcebalance::tinkerio.logger = getLogger(__name__)
- dictionary forcebalance::tinkerio.pdict

9.34 vibration.py File Reference

Classes

- class forcebalance.vibration.Vibration

  Subclass of Target for fitting force fields to vibrational spectra (from experiment or theory).

Packages

- namespace forcebalance::vibration

  Vibrational mode fitting module.

Variables

- tuple forcebalance::vibration.logger = getLogger(__name__)