Money Laundering Is Not an Outlier: Detecting Illicit Bitcoin Transactions Without Illicit Labels

Team G13

李尚哲 314580057　呂丞頤 314580055　黃駿甯 314580075　吳美真 414551035
孫傅康 112550176　傅維雨 112550149　張凱華 315554024　李玠廷 315554034

https://github.com/leeshuncher/DataMiningHW2

Abstract

Compliance teams at cryptocurrency exchanges must flag laundering transactions, yet confirmed illicit labels are scarce and late, while licit counterparties are easy to label. On the Elliptic Bitcoin graph (203,769 transactions, 49 time steps) we show that illicit transactions are *not* outliers: only 1.7% exceed a 3σ rule versus 22.3% of licit ones, so one-class detectors rank them *below* normal (test ROC-AUC 0.17). We therefore separate labeled licit from unlabeled transactions (LvU), a positive-unlabeled detector that never sees an illicit label during fitting. On a chronological test split, LvU reaches PR-AUC 0.546 ± 0.024 ($8.4\times$ prevalence) and 82% precision in its top 100 alerts, recovering 69% of supervised XGBoost's PR-AUC. Ablations show that 1% illicit contamination of the licit labels destroys this gain, and every method fails after a dark-market shutdown.

1 Introduction

Scenario and stakeholders. Virtual-asset service providers must screen the transactions they touch for money laundering. Every alert goes to a compliance analyst, who decides whether to freeze funds and file a suspicious-activity report. A missed laundering transaction (FN) exposes the provider to regulatory penalties; a false alert (FP) costs analyst time from a fixed weekly review budget.

Motivation. Supervised detectors work well on Bitcoin data (Weber et al., 2019) but need confirmed illicit labels, which take investigations and arrive late, whereas *normal* labels are cheap (known exchanges and miners are tagged automatically). One-class models trained on licit data, which treat anomalies as rare points far from normal data (Chandola et al., 2009), look like the natural label-free choice, yet Lorenz et al. (2020) found that they perform poorly and that illicit instances are not actually outlying. We quantify this failure, explain it, and turn the explanation into a detector.

Definition of anomaly. The unit of detection is one Bitcoin transaction (a graph node). A transaction is anomalous if the Elliptic labels attribute it to an illicit entity (scams, malware, ransomware, Ponzi schemes, terrorist organisations); it is normal if attributed to a licit entity (exchanges, wallet providers, miners). Example normal sample: tx 378120377 (step 16, licit; `local_53`$=0.92$, in/out degree 0/2). Example anomaly: tx 232014511 (step 1, illicit; `local_53`$=-0.49$, degree 1/1).

Research question. *Can a detector fitted without any illicit label rank illicit Bitcoin transactions above licit ones on future time steps, even though illicit transactions are not outliers?*

Contributions. (C1) We show that illicit transactions are less extreme than licit ones (1.7% vs. 22.3% beyond 3σ), which inverts one-class detectors to ROC-AUC 0.17–0.20 (§4, §7). (C2) A licit-vs-unlabeled (LvU) detector reaches test PR-AUC 0.546 and P@100 0.82 without illicit labels, significantly above label-free baselines and below supervised ones (§7). (C3) It is robust to the unlabeled pool size but collapses when 1% of licit labels are wrong (§7.1). (C4) 42% of its misses fall after a dark-market shutdown, a blind spot shared with supervised models (§8).

2 Related Work

Data category and literature. Our data are a *graph*: transactions are nodes and payment flows are directed edges, so each node has relational context. Weber et al. (2019) released the Elliptic data set and compared supervised models on a 70:30 temporal split (Table 1); Random Forest on all features gave the best illicit F1 (0.788), ahead of graph convolutional networks. EvolveGCN (Pareja et al.,

Work	Paradigm	Method	Ill. F1
Weber et al. (2019)	supervised	RF, AF	0.788
Weber et al. (2019)	supervised	GCN	0.628
Lorenz et al. (2020)	unsupervised	LOF (best)	$\leq$0.19
Lorenz et al. (2020)	unsupervised	IF	$\leq$0.01
Ours	PU, no ill. labels	LvU	0.398
Ours	supervised (T3a)	RF, AF	0.541

Table 1: Prior results on Elliptic (illicit-class F1). Prior work trains on steps 1–34; we train on 1–29 and tune τ on 30–34, so numbers give context, not a direct comparison.

2020) models the graph sequence over time and reports that no model recovers after the dark-market shutdown. Lorenz et al. (2020) found that seven unsupervised detectors reach illicit F1 of at most 0.19 (LOF), and proposed active learning, which matches a supervised baseline with 5% of the labels. Positive-unlabeled (PU) learning trains a classifier from one labeled class plus unlabeled data (Elkan and Noto, 2008; Bekker and Davis, 2020); Deep SAD (Ruff et al., 2020) instead uses a few labeled anomalies.

Positioning and method selection. Tier 1 assumes anomalies are extreme in some feature (3σ rule) or nothing at all (random score). Tier 2 assumes illicit mass is over-represented in unlabeled relative to licit data (our LvU); we also report the one-class Isolation Forest (Liu et al., 2008), which assumes anomalies are easy to isolate. Tier 3 uses full supervision: Random Forest (Breiman, 2001) as in Weber et al. (2019), and XGBoost (Chen and Guestrin, 2016). Unlike prior work, we fit without illicit labels, explain *why* outlier detectors invert, and analyse failures per transaction.

3 Task Definition and Data

Data set. We use the Elliptic Data Set (Weber et al., 2019), obtained from the official Kaggle release (license CC BY-NC-ND 4.0); our repository downloads and checksums it. It contains $N = 203{,}769$ transactions and 234,355 edges in 49 time steps about two weeks apart; edges never cross time steps. Each node has $D = 166$ anonymised features: the time step, 93 local features (LF; e.g. fees, input/output counts and volumes) and 72 aggregates over one-hop neighbours (AF). We add in/out degree from the edge list.

Labels. Ground truth comes from a heuristics-based labelling of the entities behind each transaction (Weber et al., 2019): 4,545 illicit, 42,019 licit, and 157,205 *unknown*. Labels may be noisy (heuristic, entity-level attribution), and unknown transactions contain both classes; they are never evaluated, but LvU uses them as unlabeled training data. The paradigm is semi-supervised: licit labels and unlabeled data for fitting, illicit labels only for validation-based selection.

Split	Steps	Tx	Licit	Illicit	Unknown	Ill./lab.
train	1–29	120,804	23,510	2,871	94,423	10.9%
val	30–34	15,461	2,922	591	11,948	16.8%
test	35–49	67,504	15,587	1,083	50,834	6.5%
all	1–49	203,769	42,019	4,545	157,205	9.8%

Table 2: Chronological split shared by all methods.

Class imbalance. Overall, 2.2% of transactions are illicit; among labeled ones the ratio is 9.8% vs. 90.2% (1 : 9.2), and on the test split 6.5% (1 : 14.4). A model that predicts "always licit" reaches 93.5% test accuracy with zero recall, so we never report accuracy. We use threshold-free ranking metrics (PR-AUC) and choose τ to maximise F1 rather than relying on a 0.5 cut-off.

4 Exploratory Feature Analysis

All statistics use the training split only (Figure 1).

Distribution contrast. Figure 1a shows `local_53`, the feature with the largest Kolmogorov–Smirnov (KS) distance between classes (0.66, mutual information 0.21 nats). Most illicit transactions sit on a single value (-0.49, shared by 83% of illicit but 18% of licit training transactions), whereas licit values spread over the whole range. Figure 1b is the key observation: only 1.7% of illicit transactions have any local feature beyond 3σ of the licit distribution, against 22.3% of licit transactions. In PCA space (Figure 1c), illicit points occupy one compact region; licit points scatter over many clusters.

Separability and redundancy. Local features separate the classes better than neighbour aggregates (mean KS 0.38 vs. 0.27; 63 vs. 30 features with KS > 0.3; mean MI 0.088 vs. 0.060 nats) and degree (0.20). 89 feature pairs have $|r| > 0.95$, and licit behaviour drifts moderately within training (mean KS 0.11, steps 1–14 vs. 15–29).

Hypotheses. **H1**: Outlier-based scores (3σ, Isolation Forest, Mahalanobis) will rank illicit transac-




Figure 1: Training split only. (a) The most separating feature: illicit transactions concentrate on one value. (b) Cumulative share of the largest $|z|$-score (w.r.t. licit statistics): illicit transactions are *less* extreme than licit ones; dashed line = 3σ. (c) PCA fitted on licit data: illicit points form a compact cluster inside the region occupied by licit ones.




Figure 2: LvU pipeline. No illicit label is used for fitting; labeled illicit transactions of the validation steps only set τ.

tions *below* licit ones. **H2**: A model that contrasts licit data with unlabeled data will rank them above, because the compact illicit mode is denser in the unlabeled pool than among labeled licit transactions. **H3**: Neighbour aggregates and degree will add little to local features. We test H1–H2 in §7–7.1 and H3 in §7.1.

5 Method

Pipeline. Figure 2 shows the Tier 2 pipeline. The input is the 93 local features of a transaction, used as released (already scaled); the time step is dropped so that the model cannot memorise periods. We build a training set from the training steps: every labeled licit transaction gets target $t = 0$ and every unknown transaction gets $t = 1$ (23,510 vs. 94,423 rows). Illicit training transactions are *not* used. An XGBoost classifier (300 trees, depth 6, learning rate 0.1, row/column subsampling 0.8) learns $\hat{P}(t{=}1 \mid x)$.

Anomaly score. The score is $s(x) = \hat{P}(t{=}1 \mid x)$. For a well-calibrated classifier, s is monotone in the density ratio $p_{\mathcal{U}}(x)/p_{\mathcal{L}}(x)$. If the unknown pool is a mixture $p_{\mathcal{U}} = \pi\, p_{\text{ill}} + (1-\pi)\, p_{\text{lic}}$ and labeled licit data follow p_{lic}, the ratio equals $(1-\pi)+\pi\, p_{\text{ill}}(x)/p_{\text{lic}}(x)$ and therefore ranks transactions exactly by how much more likely they are under the illicit than the licit distribution (Elkan and Noto, 2008). Unlike an outlier score, this ranking rewards a dense illicit mode that licit data rarely reach (H2).

Threshold and error costs. τ is the score that maximises F1 on the labeled transactions of validation steps 30–34; the test split is never used. An FN lets laundered funds pass (regulatory risk); an FP costs analyst minutes. Because an FN is costlier, we accept the recall-leaning τ that F1 selects: about 2.5 false alerts per caught transaction at 65% recall (alternatives in §7.1).

6 Experimental Setup

Split and leakage prevention. All methods share one chronological split by time step (Table 2): train 1–29, validation 30–34, test 35–49. The train+validation/test boundary is the 70:30 split of Weber et al. (2019). One-class models fit licit training rows only; LvU fits licit and unknown training rows; supervised models fit labeled training rows. Scalers (3σ, LOF, kNN) are fit on licit training rows; the test set is scored once per seed.

Configurations. LvU hyperparameters were chosen by validation PR-AUC over feature set $\in$ {LF, AF, AF+degree}, depth $\in \{4, 6, 8\}$ and trees $\in \{100, 300\}$ (best: LF, 6, 300; validation PR-AUC 0.901). Isolation Forest uses 200 trees with `max_samples` $\in \{256, 2048\}$ (best: 2048, LF). Random Forest follows Weber et al. (2019) (50 trees, 50 features per split, AF); XGBoost uses the same settings as LvU on AF. Every stochastic method runs with 5 seeds. Software: Python 3.13,

scikit-learn 1.9 (Pedregosa et al., 2011), XGBoost 3.4; hardware: 4 vCPUs, 16 GB RAM, no GPU.

Metrics. (1) **PR-AUC** (average precision) is our primary metric: it ignores the large number of easy true negatives and is informative under imbalance (Saito and Rehmsmeier, 2015); its random baseline equals the prevalence. (2) **P@100**, the precision of the 100 highest-scored test transactions, models a fixed analyst budget. (3) **F1@τ** evaluates the deployed decision. ROC-AUC is reported to show inversion (< 0.5).

7 Results

Main comparison. Table 3 supports H1: the 3σ rule and the one-class Isolation Forest rank illicit transactions below licit ones (ROC-AUC 0.33 and 0.17) and fall under the random baseline in PR-AUC. Their val-tuned τ degenerates to "alert on everything" (F1 0.12, as for random scores). LvU supports H2: PR-AUC rises to 0.546 ± 0.024 (8.4× prevalence) and 82% of its top-100 alerts are illicit. The gap to the best label-free baseline (T1a) is significant (paired t-test over seeds, $p < 10^{-5}$; bootstrap 95% CI of the PR-AUC gap [0.450, 0.513]).

Against Tier 3. Supervised models remain clearly better: XGBoost reaches PR-AUC 0.790 and RF 0.767; the gaps to LvU are significant (bootstrap CI vs. XGBoost $[-0.268, -0.218]$, $p < 10^{-4}$). LvU recovers 69% of XGBoost's PR-AUC without a single illicit label. It loses because it learns "unlabeled-like" rather than "illicit": licit transactions resembling the unlabeled mass also score high (§8). RF's F1 varies across seeds (0.42–0.80) while its PR-AUC does not: a τ tuned on validation steps with 16.8% prevalence transfers poorly to a 6.5% test period. All models train in under 6 s and score in 1–12 μs per transaction, so cost does not separate them.

7.1 Controlled Ablations

A1: contamination of the normal labels (AD-specific). Replacing just 1% of the licit training rows with illicit ones (235 rows) cuts PR-AUC from 0.546 to 0.142, far beyond the seed std. Because illicit transactions form one compact mode, a few hundred of them labeled $t = 0$ suffice to tell the classifier that this mode is "licit". This is an honest negative result: LvU needs clean licit labels.

A2: size of the unlabeled pool (AD-specific). Using 5% of the unknown pool (4.7k rows) gives the same PR-AUC (0.546); all differences are within one std, so a small unlabeled sample already contains the illicit mode.




Figure 3: Illicit F1 per test step (lines, left axis) and number of illicit transactions (bars, right axis). Every method collapses after the dark-market shutdown at step 43. The one-class IF rises only because it alerts on everything.

A3: scoring function (AD-specific). Holding features and data fixed, outlier scores invert (Isolation Forest 0.037, Mahalanobis with Ledoit–Wolf shrinkage (Ledoit and Wolf, 2004) 0.038). Local density scores, LOF (Breunig et al., 2000) and a kNN density ratio between licit and unlabeled data, recover some signal (0.19). The classifier-based density ratio is best (0.546).

A4: graph features. Adding the 72 neighbour aggregates changes PR-AUC by $+0.011$ and adding degree by -0.037, both within about one seed std; this supports H3. AF raises recall but lowers F1, because the validation threshold transfers worse.

Threshold strategy. For the same scores (Table 5), the label-free 95th-percentile rule doubles the alerts (F1 0.27); a budget of 30 alerts per step gives the highest precision (0.48) at 20% recall.

8 Analysis

Temporal failure. Figure 3 reproduces the observation of Weber et al. (2019): after a dark market closes at step 43, every model fails. LvU's F1 drops from 0.50 (steps 35–42) to 0.01 (43–49), and its PR-AUC from 0.743 to 0.025, which equals the prevalence (Table 3). Only 15.6% of test illicit transactions fall in steps 43–49, but they account for 42% of the misses of LvU. Of the 398 misses (seed 0, $\tau = 0.970$), 69% are also missed by super-

Tier	Method	PR-AUC	ROC-AUC	F1@τ	P@100	PR-AUC by period steps 35–42	PR-AUC by period 43–49	Fit (s)	Score (μs/tx)
T1a	Random score	0.065±0.001	0.495±0.006	0.122±0.000	0.060±0.017	0.091	0.027	0.1	0.0
T1b	3σ rule (max $\|z\|$)	0.053	0.326	0.010	0.040	0.075	0.028	0.1	0.2
T2′	One-class Isolation Forest	0.038±0.000	0.170±0.008	0.121±0.002	0.000	0.053	0.021	0.7	11.9
T2	**LvU classifier (ours)**	0.546±0.024	0.865±0.002	0.398±0.011	0.822±0.020	0.743	0.025	4.6	1.5
T3a	Random Forest (sup.)	0.767±0.003	0.891±0.004	0.541±0.138	**1.000**	0.897	0.028	5.7	2.2
T3b	XGBoost (sup.)	**0.790±0.001**	**0.922±0.002**	**0.675±0.056**	**1.000**	**0.914**	0.036	2.8	1.7
prevalence (= random PR-AUC)		0.065				0.092	0.025		

Table 3: Test results (labeled transactions of steps 35–49), mean ± std over 5 seeds (deterministic methods: one run). F1 uses τ tuned on validation (3σ rule: $\tau = 3$). Best per column in bold. Period columns split the test set at the dark-market shutdown (step 43).

Setting	PR-AUC	Δ	F1@τ
A1: illicit rows hidden in licit side			
0% (ours)	0.546±0.024	—	0.398
1%	0.142±0.007	−0.404	0.246
5%	0.098±0.003	−0.448	0.207
10%	0.091±0.004	−0.455	0.196
A2: fraction of unlabeled pool used			
5%	0.546±0.018	+0.000	0.406
25%	0.520±0.047	−0.026	0.425
50%	0.551±0.040	+0.005	0.418
100% (ours)	0.546±0.024	—	0.398
A3: label-free scoring function			
one-class IF	0.037±0.000	−0.509	0.122
one-class Mahalanobis	0.038	−0.508	0.122
one-class LOF	0.190	−0.356	0.139
PU kNN ratio	0.194	−0.352	0.188
PU classifier (ours)	0.546±0.024	—	0.398
A4: feature set			
LF, 93 local (ours)	0.546±0.024	—	0.398
AF (+72 aggregates)	0.557±0.037	+0.011	0.296
AF + in/out degree	0.509±0.043	−0.037	0.316

Table 4: Ablations of LvU on the test split, one factor at a time (5 seeds unless deterministic; F1: mean). Δ = PR-AUC change vs. the full method.

τ rule	Alerts	Precision	Recall	F1
best F1 on val (ours)	2459	0.288	0.650	0.398
95th pct. licit train	5420	0.159	0.797	0.266
top-30 per time step	450	0.484	0.201	0.284

Table 5: Alert rules for LvU on the test split (15 steps); mean of 5 seeds, std ≤0.04.

vised RF: the blind spot lies in the data, not in our label-free setting.

Failure cases. Table 6 lists four test errors. #1 is a complete inversion: an illicit transaction with $s = 0.014$ whose `local_53`= 1.81 lies above 99.6% of illicit but at the 63rd percentile of licit training transactions; RF misses it too (0.04). Cases #2 (FN) and #4 (FP) receive the identical score 0.970, just at τ. They share 73 of 93 local features (L2 distance 4.1 vs. a median of 10.2 to licit transactions), yet carry opposite labels. No threshold can separate them; this points to label noise or to entities that reuse the same wallet software. #3 is a confident FP ($s = 1.000$): a licit transaction sitting on the illicit mode `local_53`= −0.49, which RF correctly scores 0.03. Without illicit labels, LvU cannot learn which parts of the unlabeled mass are illicit. **Shared pattern**: errors come from overlapping modes and post-shutdown drift, not model capacity; the first fix we would try is a few analyst-confirmed labels from the new period (active learning, Lorenz et al., 2020), not a larger model.

Interpretability. We explain LvU with exact TreeSHAP (Lundberg et al., 2020) (Figure 4). Globally, `local_53`, `local_47` and `local_76` dominate; `local_53` is also the top EDA feature, so the model uses the illicit mode found in §4. For the flagged tx 162428632 ($s = 1.000$; RF agrees, 0.94), `local_53`= −0.49 adds 1.23 log-odds and five further local features each add 0.4–0.9. An analyst would see that the transaction matches a pattern common in illicit flows, a reason to review but not proof; anonymised features limit trust until their meaning is disclosed.

Practical impact. At the validation threshold, LvU raises 2,459 alerts over 15 steps (about 164 per two-week step) and catches 65% (about 704) of the 1,083 illicit test transactions; 71% of its alerts are false. With a budget of 30 alerts per step, 48% of alerts are illicit, 7.4× the yield of random review. Supervised RF catches ≈100 more with fewer alerts; LvU is a cold-start triage tool for providers without confirmed illicit cases.

#	Type	txId	Step	$s(x)$	Top-SHAP feature	RF	Likely cause
1	FN	97069571	40	0.014	local_48= 0.09	0.04	licit-typical profile
2	FN	73003591	42	0.970	local_53= −0.49	0.76	73/93 features equal #4
3	FP	169360875	45	1.000	local_53= −0.49	0.03	licit tx in illicit mode
4	FP	73160604	42	0.970	local_53= −0.49	0.41	73/93 features equal #2

Table 6: Failure cases of LvU (seed 0, $\tau = 0.970$). RF = supervised Random Forest score (mean of seeds; its mean $\tau \approx 0.37$). Top-SHAP = local feature with the largest attribution for this transaction.




Figure 4: TreeSHAP attributions of LvU (seed 0) in log-odds of $t = 1$. (a) Mean |SHAP| over test illicit transactions. (b) The highest-scored true positive: its value on the illicit mode `local_53`$= -0.49$ contributes most.

9 Conclusion and Limitations

Key findings. Yes, with qualifications. A detector fitted only on licit and unlabeled transactions ranks illicit Bitcoin transactions far above chance on future steps (PR-AUC 0.546 vs. 0.065; P@100 0.82), whereas outlier detectors invert (ROC-AUC 0.17), because illicit transactions form a compact, non-extreme mode. It reaches 69% of supervised PR-AUC, but it fails after the dark-market shutdown, like every model we tested.

Reflection and future work. The decision that mattered most was testing outlyingness in EDA (Figure 1b); starting again, we would do it before implementing any one-class model. Next steps: (i) query analyst labels for the highest-scoring unlabeled transactions after a drift alarm, to address the post-shutdown misses; (ii) estimate the class prior π of the unlabeled pool (Bekker and Davis, 2020) to calibrate τ across periods.

Limitations. *Data coverage*: one blockchain and 49 two-week steps (undisclosed calendar dates), with entity-level heuristic labels and anonymised features; 77% of transactions are unlabeled, so all scores refer to labeled ones only. *Assumptions*: LvU assumes clean licit labels (A1 shows 1% noise is fatal) and that the unlabeled pool contains the illicit modes of the future, which fails after the shutdown. *Generalisation*: the outlier inversion may not hold for fraud types that are genuinely extreme (e.g. large one-off thefts).

Deployment considerations. *Concept drift*: illicit behaviour changed abruptly at step 43; retrain every few steps and monitor with a small labeled audit sample, since scores alone do not reveal a collapse. *Latency and privacy*: scoring takes $\approx$1.5 μs per transaction, far below block times; blockchain data are public, but linking addresses to people falls under data-protection and AML rules.

Contributions of Each Member

- 李尚哲 (314580057): EDA; vetted the topic.
- 呂丞頤 (314580055): assessed candidate topics.
- 黃駿甯 (314580075): presentation slides.
- 吳美真 (414551035): drafted the paper.
- 孫傅康 (112550176): code, slides, coordination.
- 傅維雨 (112550149): coordination, paper review.
- 張凱華 (315554024): paper review, topic vetting.
- 李玠廷 (315554034): obtained the dataset.

AI usage statement. We used Claude Code for code and drafting; the team chose the question and verified every number and citation.

References

Jessa Bekker and Jesse Davis. 2020. Learning from positive and unlabeled data: A survey. *Machine Learning*, 109(4):719–760.

Leo Breiman. 2001. Random forests. *Machine Learning*, 45(1):5–32.

Markus M. Breunig, Hans-Peter Kriegel, Raymond T. Ng, and Jörg Sander. 2000. LOF: Identifying density-based local outliers. In *Proceedings of the 2000 ACM SIGMOD International Conference on Management of Data*, pages 93–104.

Varun Chandola, Arindam Banerjee, and Vipin Kumar. 2009. Anomaly detection: A survey. *ACM Computing Surveys*, 41(3):15:1–15:58.

Tianqi Chen and Carlos Guestrin. 2016. XGBoost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 785–794.

Charles Elkan and Keith Noto. 2008. Learning classifiers from only positive and unlabeled data. In *Proceedings of the 14th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 213–220.

Olivier Ledoit and Michael Wolf. 2004. A well-conditioned estimator for large-dimensional covariance matrices. *Journal of Multivariate Analysis*, 88(2):365–411.

Fei Tony Liu, Kai Ming Ting, and Zhi-Hua Zhou. 2008. Isolation forest. In *Proceedings of the Eighth IEEE International Conference on Data Mining (ICDM)*, pages 413–422.

Joana Lorenz, Maria Inês Silva, David Aparício, João Tiago Ascensão, and Pedro Bizarro. 2020. Machine learning methods to detect money laundering in the Bitcoin blockchain in the presence of label scarcity. In *Proceedings of the First ACM International Conference on AI in Finance (ICAIF)*.

Scott M. Lundberg, Gabriel Erion, Hugh Chen, Alex DeGrave, Jordan M. Prutkin, Bala Nair, Ronit Katz, Jonathan Himmelfarb, Nisha Bansal, and Su-In Lee. 2020. From local explanations to global understanding with explainable AI for trees. *Nature Machine Intelligence*, 2(1):56–67.

Aldo Pareja, Giacomo Domeniconi, Jie Chen, Tengfei Ma, Toyotaro Suzumura, Hiroki Kanezashi, Tim Kaler, Tao B. Schardl, and Charles E. Leiserson. 2020. EvolveGCN: Evolving graph convolutional networks for dynamic graphs. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 5363–5370.

Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, Jake Vanderplas, Alexandre Passos, David Cournapeau, Matthieu Brucher, Matthieu Perrot, and Édouard Duchesnay. 2011. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830.

Lukas Ruff, Robert A. Vandermeulen, Nico Görnitz, Alexander Binder, Emmanuel Müller, Klaus-Robert Müller, and Marius Kloft. 2020. Deep semi-supervised anomaly detection. In *International Conference on Learning Representations (ICLR)*.

Takaya Saito and Marc Rehmsmeier. 2015. The precision-recall plot is more informative than the ROC plot when evaluating binary classifiers on imbalanced datasets. *PLoS ONE*, 10(3):e0118432.

Mark Weber, Giacomo Domeniconi, Jie Chen, Daniel Karl I. Weidele, Claudio Bellei, Tom Robinson, and Charles E. Leiserson. 2019. Anti-money laundering in bitcoin: Experimenting with graph convolutional networks for financial forensics. In *KDD '19 Workshop on Anomaly Detection in Finance*. ArXiv:1908.02591.