
Reduced, Reused and Recycled: The Life of a Dataset in Machine Learning Research

Bernard Koch

University of California, Los Angeles
bernardkoch@ucla.edu

Emily Denton

Google Research, New York
dentone@google.com

Alex Hanna

Google Research, San Francisco
alexhanna@google.com

Jacob G. Foster

University of California, Los Angeles
foster@soc.ucla.edu

Abstract

1 Benchmark datasets play a central role in the organization of machine learning
2 research. They coordinate researchers around shared research problems and serve
3 as a measure of progress towards shared goals. Despite the foundational role of
4 benchmarking practices in this field, relatively little attention has been paid to the
5 dynamics of benchmark dataset use and reuse, within or across machine learning
6 subcommunities. In this paper, we dig into these dynamics. We study how dataset
7 usage patterns differ across machine learning subcommunities and across time
8 from 2015-2020. We find increasing concentration on fewer and fewer datasets
9 within task communities, significant adoption of datasets from other tasks, and
10 concentration across the field on datasets that have been introduced by researchers
11 situated within a small number of elite institutions. Our results have implications
12 for scientific evaluation, AI ethics, and equity/access within the field.

13 1 Introduction

14 Datasets form the backbone of machine learning research (MLR). They are deeply integrated into
15 work practices of machine learning researchers, serving as resources for training and testing machine
16 learning models. Datasets also play a central role in the organization of MLR as a scientific field.
17 Benchmark datasets provide stable points of comparison and coordinate scientists around shared
18 research problems. Improved performance on benchmarks is considered a key signal for collective
19 progress. Such performance is thus an important form of scientific capital, sought after by individual
20 researchers and used to evaluate and rank their contributions.

21 Datasets exemplify machine learning tasks, typically through a collection of input and output pairs
22 [1]. When they institutionalize benchmark datasets, task communities implicitly endorse these data
23 as meaningful abstractions of a task or problem domain. The institutionalization of benchmarks
24 influences the behavior of both researchers and end-users [2]. Because advancement on established
25 benchmarks is viewed as an indicator of progress, researchers are encouraged to make design
26 choices that maximize performance on benchmarks, as this increases the legitimacy of their work.
27 Institutionalization signals to industry adopters that models can be expected to perform in the real
28 world as they do on the benchmark datasets. Close alignment of benchmark datasets with “real world”
29 tasks is thus critical to accurate measurement of collective scientific progress and to safe, ethical, and
30 effective deployment of models in the wild.

31 Given their central role in the social and scientific organization of MLR, benchmark datasets have
32 also become a central object of critical inquiry in recent years [3]. Dataset audits have revealed

Submitted to the 35th Conference on Neural Information Processing Systems (NeurIPS 2021) Track on Datasets and Benchmarks. Do not distribute.

concerning biases that have direct implications for algorithmic bias and harms [4, 5, 6, 7]. Problematic categorical schemas have been identified in popular image datasets, including poorly-formulated categories and the inclusion of derogatory and offensive labels [8, 9]. Research into the disciplinary norms of dataset development have revealed troubling practices around dataset development and dissemination, like unstandardized documentation and maintenance practices [10, 11, 12]. There is also growing concern about the limitations of existing datasets and standard metrics for evaluating model behavior in real-world settings and assessing scientific progress in a problem domain [13, 14].

Despite the increase in critical attention to benchmark datasets, surprisingly little attention has been paid to patterns of dataset use and reuse across the field as a whole. In this paper, we dig into these dynamics. We study how dataset usage patterns differ across machine learning subcommunities and across time (from 2015-2020) in the Papers With Code (PWC) corpus.¹ More specifically, we study machine learning subcommunities that have formed around different machine learning tasks (e.g., *Sentiment Analysis* and *Facial Recognition*) and examine: (i) the extent to which research within task communities is concentrated or distributed across different benchmark datasets; (ii) patterns of dataset creation and adoption between different task communities; and (iii) the institutional origins of the most dominant datasets.

We find increasing concentration on fewer and fewer datasets within most task communities. Consistent with this finding, the majority of papers within most tasks use datasets that were originally created for other tasks over ones created explicitly for their own task, even though most tasks have created more datasets than they have imported. Lastly, we find that these dominant datasets have been introduced by researchers at just a handful of elite institutions.

The remainder of this paper is organized as follows. First, we motivate our research questions by underscoring the critical importance of benchmarks in coordinating machine learning research. Second, we describe our analyses on the PWC corpus, a catalog of datasets and their usage jointly curated by the machine learning community (manually) and by Facebook AI Research (algorithmically). We then present our findings and discuss their implications for scientific validity, the ethical usage of MLR, and inequity within the field. We close by offering recommendations for possible reform efforts for the field.

2 Related Work: Scientific, Social, and Ethical Importance of Datasets

Following Schlangen [1], we understand machine learning benchmarks as community resources against which models are evaluated and compared. Benchmarks typically formalize a particular task through a dataset and associated quantitative metric of evaluation. The practice was originally introduced to MLR after the “AI Winter” of the 1980s by government funders seeking to more accurately assess the value received on grants [15, 16]. Today, benchmarking is the dominant paradigm for scientific evaluation in MLR, and the field collectively views upward trends on benchmarks as noisy but meaningful indicators of scientific progress [2, 1, 17]. Over time, MLR has evolved strong norms to facilitate widespread benchmarking, including the development of open-access datasets, formal competitions and challenges, and accompanying “black-box” software that allows researchers to test their algorithms on benchmark datasets with minimal effort.

The establishment of benchmark datasets as shared evaluative resources across the MLR community has unique advantages for coordinating scientists around common goals. First, barriers to participation in MLR are reduced, since well-resourced institutions can shoulder the costs of dataset curation and annotation.² Second, by reducing otherwise complex comparisons to a single agreed-upon measure, the scientific community can easily align on the value of research contributions and assess whether progress is being made on a particular task [19, 20]. Finally, a complete commitment to benchmarking has allowed MLR to relax reliance on slower institutions for evaluating progress like peer-review, qualitative or heuristic evaluation, or theoretical integration. Together, these advantages have contributed to MLR’s unprecedented transformation into a “rapid discovery science” in the past decade [21].

¹<https://paperswithcode.com>

²However, machine learning model development still remains a resource-intensive activity [18].

While there are clear advantages to benchmarking as a methodology for comparing algorithms and measuring progress, there are growing concerns about benchmarking cultures in MLR that tend to valorize state-of-the-art (SOTA) results on established benchmark datasets over other forms of quantitative or qualitative analysis. The necessity of SOTA results on well-established benchmarks for publication has been identified as a barrier to the development of new ideas [22]. There have been growing calls for more rigorous and comprehensive empirical analysis of models beyond standard top-line metrics, including reporting model size, energy consumption, fairness metrics, and more [23, 24, 25, 26]. The standard benchmarking paradigm also contributes to issues with underspecification in ML pipelines; a given level of performance on a held-out benchmark test set doesn’t guarantee that a model has learned the appropriate causal structure of a problem [14]. In short, while community alignment on benchmarks and metrics can enable rapid algorithmic advancement, excessive focus on singular metrics at the expense of more comprehensive forms of rigorous evaluation can lead the community astray and risk the development of models that poorly generalize to the real world.

The MLR community has begun to reflect on the utility of established benchmarks and their appropriateness for evaluative purposes. For example, the Fashion-MNIST dataset was introduced because the original MNIST dataset came to be perceived as over-utilized and too easy [27], and the utility of ImageNet — one of the most influential ML benchmarks in existence — as a meaningful measure of progress has been a focus of critical examination in the past few years [28, 29]. SOTA-chasing concerns are also compounded by the great capacity ML algorithms have to be “right for the wrong reason” [30], enabling SOTA results that rely on “shortcuts” rather than learning the causal structure dictated by the task [13]. Bender et al. suggest the NLP community may have been “led down the garden path” by over-focusing on “beating” benchmark tasks with models that can easily manipulate linguistic form without any real capacity for language understanding [31]. Recent dataset audits have also revealed that established benchmark datasets tend to reflect very narrow — typically white, male, Western — slices of the world [4, 5, 6, 7, 9]. Thus, over-concentration of research on a small number of datasets and metrics can distort perceptions of progress within the field and have serious ethical implications for communities impacted by deployed models. Despite these discussions, little empirical work has considered whether over-concentration of research on a small number of datasets is a systemic issue across MLR. This prompts our first research question:

RQ1: How concentrated are machine learning task communities on specific datasets, and has this changed over time?

There are also growing concerns regarding the gap between benchmark datasets and the problem domains in which they are used to evaluate progress. For example, Scheuerman et al. found that computer vision datasets tend to be developed in a manner that is decontextualized from a particular task or application area [12]. Supposedly “general purpose” benchmarks are often valued within the field, though the precise bounds of what makes a dataset suitable for general evaluative purposes remains unclear [17]. These observations prompt our second research question:

RQ2: How frequently do machine learning researchers borrow datasets from other tasks instead of using one created explicitly for that task?

Despite widespread recognition that datasets are critical to the advancement of the field, careful dataset development is often undervalued and disincentivized, especially relative to algorithmic contributions [32, 12]. Given the high value the MLR community places on SOTA performance on established benchmarks, researchers are also incentivized to reuse recognizable benchmarks to legitimize their contributions. Dataset development is also time- and labor-intensive, making large-scale dataset development potentially inaccessible to lower-resourced institutions. These observations prompt our final research question:

RQ3: What institutions are responsible for the major ML benchmarks in circulation?

Our paper makes two distinct contributions to the literature. First, it provides a concise, multi-dimensional discussion of the pros and cons of benchmarking as an evaluation paradigm in MLR, drawing on earlier work as well as insights from the sociology of science. Second, and more substantially, it provides the first field-level, quantitative analysis of benchmarking practice in MLR.

3 Data

Our primary data source is Papers With Code (PWC), an open source repository for machine learning papers, datasets, and evaluation tables created by researchers at Facebook AI Research. PWC is largely community-contributed — anyone can add a benchmarking result or a task, provided the benchmarking result is publicly available in a pre-print repository, conference proceeding, or journal. Once tasks and datasets are introduced by humans, PWC scrapes arXiv using keyword searches to find other examples of the task or uses of the dataset.

We downloaded the complete PWC dataset on 06/16/2021 (licensed under CC BY-SA 4.0). In this study, we focus primarily on the “Datasets” archive, as well as papers utilizing those datasets. Each dataset in the archive is associated with metadata such as the modality of the dataset (e.g., texts, images, video, graphs), the date the dataset was introduced, and the paper title that introduced the dataset (if relevant). We found 4,384 datasets on the site and scraped 60,647 papers that PWC associates with those datasets using a PWC internal API (see Figure A2 for a truncated histogram of usage across datasets).

In PWC papers, benchmarks and datasets are associated with tasks (e.g., *Object Recognition*, *Machine Translation*). Because we are interested in the dynamics of dataset usage (both within and across task communities), our first two analyses are restricted to datasets and dataset usages published in papers annotated with tasks. We call the task the dataset was originally designed for the “origin task” and the task of the paper using the dataset the “destination task.” For example, ImageNet [33], was introduced as a benchmark for *Object Recognition* and *Object Localization* (origin tasks), but is now regularly utilized as a benchmark for *Image Generation* (destination task) among many others.

PWC includes a taxonomy of tasks and subtasks. The graph is cyclic, making it hard to disentangle dataset transfer between broad tasks and finer-grained tasks. For each transfer, we record the transfer between the origin and destination. We also record the transfer between the origin’s parents and the destination’s parents. This approach allows us to accurately capture transfer dynamics between larger tasks (e.g., *Image Classification* and *Image Generation*), and between finer-grained tasks (e.g., *Image-to-Image Translation* and *Image Inpainting* which are both children of *Image Generation*).

We took three additional steps to pre-process the data. First, we only consider datasets that are used by others at least once. Second, because we found dataset usages in PWC to be noisy (i.e., a paper would be associated with a dataset if the corresponding dataset name appeared multiple times in the paper), we dropped dataset usages where the dataset-using paper shared no tasks in common with the dataset itself.³ Second, we found 640 papers that introduced a dataset but were not associated with a task. Two authors manually annotated the top 90 most widely-used dataset papers with origin tasks (see GitHub for justifications and appendix for details). We dropped the remaining 550 dataset papers (accounting for only 10.2% of total usages).

Datasets for Analysis 1 and 2 (RQ1, RQ2): To minimize double-counting of dataset usages across parent tasks and child subtasks, we chose to focus exclusively on parent tasks in PWC. The outcome measures we use in these analyses (Gini, Adoption Proportion, and Creation Proportion) are biased in small samples, so we used only parent tasks above the median size of 34 papers (see GitHub for the list of tasks). Because these tasks were larger, we also felt that parent tasks tended to be more widely-recognized as coherent task communities. Table 1 presents descriptive statistics for the data used in each analysis. Analysis 1 explores dataset usage within tasks, so it includes datasets that are introduced in papers as well as those that are not (e.g., introduced on a website or competition). Analysis 2 explores the transfer of datasets between origin and destination tasks. This dataset is smaller because we can only determine the original task for a dataset if it is introduced in a paper (Table 1). In the appendix, we describe robustness checks that remove some of these cleaning steps; these choices minimally affect our results.

Dataset for Analysis 3 (RQ3): To study the distribution of widely-utilized datasets across institutions, we linked all dataset-introducing papers to the Microsoft Academic Graph (MAG) [34]. Analyses were performed on dataset usages for which the dataset’s last author affiliation was annotated in MAG (Table 1). We again imposed the restriction that usages must share a labeled task with the dataset, but again found it had minimal effects on the results (see appendix).

³Datasets in PWC are labeled with all tasks they are used for, not just the origin tasks. We focus on datasets introduced in papers so that we can identify tasks associated with the paper as origin tasks.

Analysis	# Datasets	# Usages	# Tasks	# Papers
1	2,063	49,008	133	26,691
2	960	33,034	133	20,747
3	1,933	43,140	N/A	26,535

Table 1: Descriptive statistics for data used in the three analyses. Note that the number of dataset usages is larger than the number of papers because many papers use multiple datasets.

The datasets, a datasheet [10], and code for curation/analysis can be found at https://github.com/kochbj/Reduced_Reused_Recycled.

4 Methods and Findings

4.1 Analysis 1 (RQ1): Concentration in Task Communities on Datasets

4.1.1 Methods

To measure how concentrated task communities are on certain datasets (RQ1), we calculated the Gini coefficient across the distribution of observed dataset usages within each task. Gini is a continuous measure of dispersion in frequency distributions. The metric is frequently used in social science to study inequality [35].⁴ The Gini score varies between 0 and 1, with 0 indicating that the papers within a task use all datasets in equal proportions, and 1 indicating that only a single dataset is used across all dataset-using papers. Gini is calculated as the average absolute difference in the usage of all pairs of datasets used in the task, divided by the average usage of datasets. Formally, if x_i is the number of usages of dataset i out of all n datasets used in the task, then the Gini coefficient of dataset usage is,

$$G = \frac{\sum_{i=1}^n \sum_{j=1}^n |x_i - x_j|}{2 \sum_{i=1}^n \sum_{j=1}^n x_j} = \frac{\sum_{i=1}^n \sum_{j=1}^n |x_i - x_j|}{2n \sum_{j=1}^n x_j} = \frac{\sum_{i=1}^n \sum_{j=1}^n |x_i - x_j|}{2n^2 \bar{x}} \quad (1)$$

Because Gini can be biased in small samples [36], we use the sample-corrected Gini, $G_s = \frac{n}{n-1}G$, and excluded tasks (or task-years when disaggregating by time) with fewer than 10 papers.

Regression Model 1: In addition to descriptive statistics, we built a regression model to assess the extent to which observed trends in Gini from year-to-year could be attributable to confounding variables like task size, task age, or other task-specific traits at that time. Our outcome is G_s in each task year from 2015-2020 (Figure A5 shows PWC coverage is limited for papers published before 2015). Our predictors of interest are:

1. **Year** (since we are interested in trends in concentration over time)
2. **CV, NLP, Methods**⁵ (three dummy variables indicating whether the task belongs to the Computer Vision, Natural Language Processing, or Methodology categories in PWC).

To absorb additional heterogeneity, we also included the following control covariates:

1. **Task size** in number of dataset-using/introducing papers for that task in that year
2. **Task age** (because younger tasks may have higher Gini coefficients)
3. **Random intercepts for each task** (because we have repeated observations over time)

We use beta regression to model Gini because the beta distribution is very flexible, between 0 and 1, and commonly used for this purpose [35]. However, we apply the smoothing transformation in [37] to deal with the occasional task-year where the Gini is 0. We use a model with the following interactions:

$$\begin{aligned} \text{Beta}(G_s) = & \alpha + \beta_1 \text{Year} + \beta_2 \text{Task Size} + \beta_3 \text{Task Age} + \\ & \beta_4 \text{CV} + \beta_5 \text{NLP} + \beta_6 \text{Methods} + \beta_7 \text{Year} * \text{Task Size} + \\ & \beta_8 \text{CV} * \text{Year} + \beta_9 \text{NLP} * \text{Year} + \beta_{10} \text{Methods} * \text{Year} \end{aligned}$$

⁴To give some indication of the range of Gini, the country with the lowest Gini for income inequality according to the World Bank [LINK] is Slovenia with a Gini of 24.6. The country with the highest Gini inequality is South Africa at 63. The U.S. has a Gini of 41.4.

⁵Example "Methods" tasks in PWC include Transfer Learning, Domain Adaptation, and AutoML.

217 This model was chosen among a set of nested models with two- and three-way interactions because
 218 it had the lowest Akaike information criterion (AIC) and Bayesian information criterion (BIC). See
 219 the appendix for model selection criteria and Table A1 for fit statistics.

220 4.1.2 Findings

221 Controlling for task age, task size, and task-specific effects, Model 1 finds significant evidence for
 222 increasing concentration in task communities for the full dataset over time, predicting a marginal
 223 increase in Gini of .113 from 2015-2020 (Figure 1 top green; Table A2). This trend is also visible
 224 in the overall distributions of Gini coefficients over this period (Figure 1 bottom). By 2020, the
 225 median Gini coefficient for a task was .60. There are no statistically significant differences between
 226 Computer Vision and Methodology tasks compared to the full sample (Figure 1 top, Figure A1), but
 227 Model 1 suggests increases in concentration are attenuated for Natural Language Processing task
 228 communities (Figure 1 top orange). We note that this is the only result that varies somewhat with our
 229 model specification; while the rate of increasing concentration in NLP tasks is always significantly
 230 lower than the rest of the dataset, the sign and slope of this change does vary somewhat across models.
 231 We discuss this point in the appendix.

232 4.2 Analysis 2 (RQ2): Changes in Rates of Adoption and Creation of Datasets Over Time

233 4.2.1 Methods

234 We created two proportions to better understand patterns of dataset usage and creation within tasks as
 235 outcomes:

$$\text{Adoption Proportion} = \frac{\text{\# of Papers Using Datasets from Other Tasks}}{\text{\# of Papers Using Datasets from Other Tasks} + \text{\# of Papers Using Datasets from this Task}}$$

$$\text{Creation Proportion} = \frac{\text{\# of Datasets Created Within this Task}}{\text{\# of Datasets Created within this Task} + \text{\# of Datasets Imported from Other Tasks}}$$

236 **Aggregated Descriptive Analyses:** We first computed these proportions for each of the 133 parent
 237 tasks aggregated across all years, and subsetting these by the “Computer Vision,” “Natural Language
 238 Processing,” and “Methodology” categories.

239 **Regression Models 2A & 2B:** Because we chose to formulate our outcomes as fractions of discrete
 240 events, logistic regression is the most theoretically appropriate model for these data. We used a mixed
 241 effects logistic regression to model these outcomes with the same predictors as Model 1.

242 4.2.2 Findings

243 The top row of Figure 2 shows a wide variance in adoption proportions in both the full sample and the
 244 subcategories. Within the full sample, more than half of task communities use adopted datasets at least
 245 57.8% of the time. However, this number varies dramatically across the three PWC subcategories. In
 246 more than half of Computer Vision communities, authors adopt at least 71.9% of their datasets from
 247 a different task. The equivalent statistic in Methodology tasks is 74.1%. Conversely, half of Natural
 248 Language Processing communities adopt datasets less than 27.4% of the time.

249 In the bottom row of Figure 2, we see a largely inverted trend. Of all unique datasets used in a task
 250 community, 62.5% are created specifically for that task in more than half of tasks. Within Computer
 251 Vision and Methods tasks, the median is lower at 53.3% and 52.6%, with similar distributions across
 252 tasks. Most strikingly, 76.0% of datasets are created specifically for the task in more than half of NLP
 253 communities, with a much tighter variance.

254 We were unable to recover convincing evidence for trends in adoption or creation proportions either
 255 way (Regression Models 2A & 2B) because of a lack of data (results not shown). Disaggregating
 256 tasks over time creates a significant number of task-years with no events, and these metrics are
 257 undefined in those circumstances.



Figure 1: **Top: Predicted concentration on datasets across task communities over time.** Gini predicted by Model 1 holding task size/age at means. Green plots show the estimated effects of the full dataset, other colors are fixed effects for categories. 95% confidence intervals shown. **Bottom: Distributions of concentrations.** Higher Gini indicates greater concentration on fewer datasets. We observe significant spread of Gini across tasks, with the median increasing over time.




Figure 2: **Adoption (Top) and Creation (Bottom) Proportions for PWC Parent Tasks.** Full dataset in green, tasks in the Computer Vision category in purple, Methods tasks in red, and Natural Language Processing tasks in orange. Red dot and line in boxplot indicate median. Width of violins indicates distribution of tasks.

259

260 4.3 Analysis 3 (RQ3): Concentration in Dataset-Introducing Institutions Over Time

261 4.3.1 Methods

262 To look at trends in Gini inequality across institutions and datasets over time for the larger set of
 263 dataset-using papers, we calculated the Gini coefficient G_s in each year for dataset usages both by
 264 dataset and by institution. We regressed this Gini on year, as well as residuals capturing variance in
 265 the size of PWC that is not correlated with time (see appendix), using a standard beta regression. We
 266 also mapped dataset-introducing institutions using the longitude and latitude coordinates provided for
 267 the last author's institution on Microsoft Academic.

268 4.3.2 Findings

269 Overall, we find that widely-used datasets are introduced by only a handful of elite institutions (Figure
 270 3 left). In fact, over 50% of dataset usages in PWC as of June 2021 can be attributed to just twelve
 271 institutions. Moreover, this concentration on elite institutions as measured through Gini has increased
 272 to over .80 in recent years (Figure 3right red). This trend is also observed in Gini concentration on
 273 datasets in PWC more generally (Figure 3right black).




Figure 3: **Increases in concentration of dataset usages on institutions and datasets (non-task specific) over time.** Left: Map of dataset usages per institution as of June 2021. Dot size indicates number of usages. Blue dots indicates for-profit institutions and orange dots indicate not-for-profit. Institutions accounting for 50%+ usages labeled. Right: Gini coefficient for concentration of dataset usages across the whole PWC dataset over time for both institutions and datasets. Ribbons indicate 95% CI and dot size indicates number of usages that year.

274 5 Discussion

275 In this paper, we find that task communities are heavily concentrated on a limited number of datasets,
 276 and that this concentration has been increasing over time (see Figure 1). Moreover, a significant
 277 portion of the datasets being used for benchmarking purposes within these communities were
 278 originally developed for a different task (see Figure 2). This result is striking given the fact that
 279 communities *are* creating new datasets — in most cases more than the unique number that have been
 280 imported from other tasks — but the newly created datasets are being used at lower rates. When
 281 examining PWC without disaggregating by task, we find that there is increasing inequality in dataset
 282 usage globally, and that more than 50% of all dataset usages in our sample of 43,140 corresponded to
 283 datasets introduced by twelve elite, primarily Western, institutions.

284 NLP tasks differ somewhat from PWC as a whole: the broader trend of increasing concentration
 285 on a few datasets is moderated in NLP communities, new datasets are created at higher rates, and
 286 outside datasets are used at lower rates. One possible explanation for these findings is that NLP
 287 task communities in our dataset tend to be bigger than other task communities (median size of
 288 76 dataset usages compared to 55). While we find very modest evidence of correlations between
 289 task size and adoption or creation proportions overall (Kendall’s $\tau = -.008$, $p = .89$; $\tau = .014$,
 290 $p = .81$ respectively), these correlations are stronger within NLP tasks (Kendall’s $\tau = -.10$, $p = .45$;
 291 $\tau = .09$, $p = .50$ respectively). It is possible that larger NLP communities are more coherent and thus
 292 generate and use their own datasets at higher rates than other task communities. Another possibility is
 293 that NLP datasets are easier to curate because the data are more accessible, easier to label, or smaller.
 294 The resolution of this puzzle is beyond the scope of this paper, but the distinct nature of NLP datasets
 295 provides an interesting direction for future work.

296 For our broader findings, there are valid reasons to expect widespread adoption and concentration on
 297 key datasets. First, a certain degree of research focus on a particular benchmark is both necessary
 298 and healthy to establish the validity and utility of the benchmark (or in some cases, to contest these
 299 properties) and to gain community alignment around the benchmark as a meaningful measure of
 300 progress. Second, the curation of large-scale datasets is not just costly in terms of resources, but may
 301 require unique or privileged data (e.g., anonymized medical records, self-driving car logs) accessible
 302 to only a few elite academic and corporate institutions. Nevertheless, the extent of concentration we
 303 observe poses questions relating to the scientific rigor and ecological validity of machine learning
 304 research and underscores benchmarking as a potential driver for inequality in the field. In the
 305 remainder of this section we discuss our findings in relation to these two broad themes and outline
 306 recommendations that can be enacted at an individual and institutional level. We close by discussing
 307 limitations of this analysis and outlining directions for future work.

308 5.1 Scientific Rigor and Ecological Validity of MLR

309 The heavy concentration of research on a small number of datasets for each task community is a fairly
 310 unsurprising result given the value placed on SOTA performance in established benchmark datasets —




Figure 4: **Top datasets used across *Image Generation* and *Face Recognition* task communities:** (a) Origin task communities of top *Image Generation* datasets. Only 7.49% of *Image Generation* papers in PWC evaluate on datasets developed for *Image Generation*. (b) Names of top *Image Generation* datasets. Only one of the top datasets, FFHQ [38], was developed for the task. (c) The small number of datasets in usage within the high stakes domain of *Face Recognition*. Two of the datasets, MegaFace [39] and MS-Celeb-1M [40] (in white), have been recently retracted, the latter due to serious ethical violations [41].

a valuation that incentivizes individual researchers to concentrate on maximizing performance gains on well-established benchmarks. However, as discussed in Section 2, over-concentration of research efforts on established benchmark datasets risks distorting measures of progress. Moreover, as the rate of technology transfer has accelerated, benchmarks have been increasingly used by industry practitioners to assess the suitability and robustness of different algorithms for live deployment in production settings. This transition has transformed epistemic concerns about overfitting datasets into ethical ones. For example, critical research on datasets for facial recognition, analysis, and classification has repeatedly highlighted the lack of diversity in standard benchmark datasets used to evaluate progress [4], even as the technologies are applied in law enforcement contexts that adversely affect underrepresented populations [42]. Figure 4c shows the top datasets in usage within the *Face Recognition* community. Here, we see a significant amount of high stakes research being concentrated on a small number of datasets, many of which contain significant racial and gender biases [4, 43]. An in-depth examination of bias within the top benchmark datasets in use within different task communities is outside the scope of this work. However, the systemic nature of bias concerns in ML datasets compounds the epistemic concerns associated with highly concentrated research.

Our findings also indicate that datasets regularly transfer between different task communities. On the most extreme end, the majority of the benchmark datasets in circulation for some task communities were created for other tasks. For example, Figure 4 plots the dataset usages of *Image Generation* papers on PWC broken down by dataset name (Figure 4b) and origin task (Figure 4a). We observe only one of the datasets heavily used in the *Image Generation* community was designed specifically for this task. The widespread practice of adopting established datasets to train and evaluate models in new problem domains isn’t inherently a problem. However, this practice does raise potential concerns regarding the extent to which datasets are appropriately aligned with a given problem space. Moreover, given the widespread prevalence of systematic biases in the most prominent ML datasets, adopting existing datasets, rather than investing in careful curation of new datasets, risks further entrenching existing biases.

Our findings on creation and adoption rates are quite nuanced, and the extent to which high adoption rates raise significant concerns to ecological validity are yet to be determined. Furthermore, it is worth distinguishing between at least two forms of dataset adoption that seem to be conflated in the PWC data. On the one hand, we observe how datasets that have been developed for one task become *adapted* in some form for a new task through, for example, the addition of new annotations. On the other hand, we observe some datasets being *imported* whole cloth from one task community to another. Each of these forms of dataset adoption raises potentially unique concerns regarding the validity of the benchmark in a given context. That said, our results add empirical support to the growing body of scholarship calling for dataset development and use to be rooted in context [3, 12], which is particularly important for application-oriented tasks.

This paper complements and supports the growing calls to include forms of qualitative and quantitative evaluations beyond top-line benchmark metrics [23, 24, 25, 26]. Given the observed high concentration of research on a small number of benchmark datasets, we believe diversifying forms of evaluation is especially important to avoid overfitting to existing datasets and misrepresenting progress in the field.

5.2 Social Stratification in MLR

The extent of concentration we observe underscores that benchmarking is also a vehicle for inequality in science. The *prima facie* scientific validity granted by SOTA benchmarking is generically confounded with the social credibility researchers obtain by showing they can compete on a widely recognized dataset, even if a more context-specific benchmark might be more technically appropriate. We posit that these dynamics creates a “Matthew Effect” (i.e. “the rich get richer and the poor get poorer”) where successful benchmarks, and the elite institutions that introduce them, gain outsized stature within the field [44].

To the extent that benchmarks shape the types of questions that get asked and the algorithms that get produced, current benchmarking practices offer a mechanism through which a small number of elite corporate, government, and academic institutions shape the research agenda and values of the field. Empirical support for this claim is beyond the scope of this paper, but there is work within the sociology of science and technology showing that government and corporate institutions tend to support research that serves (at least in part) their own interests [45].

There is nothing *a priori* scientifically invalid about powerful institutions being interested in datasets or research agendas that would benefit them. However, issues arise when the values of these institutions are not aligned with those of other ML stakeholders (i.e., academics, civil society). For example, Dotan and Milli argue that deep learning’s reliance on large datasets has forced MLR to confront decisions about the extent to which it is willing to violate privacy to acquire/curate data [2]. Corporate and government institutions have objectives that may come into conflict with privacy (e.g., surveillance), and their weighting of these priorities is likely to be different from those held by academics or AI’s broader societal stakeholders. Returning to the Facial Recognition example in Figure 4c, four of the eight datasets (33.69% of total usages) were exclusively funded by corporations, the US military, or the Chinese government (MS-Celeb-1M, CASIA-Webface, IJB-A, VggFace2). MS-Celeb-1M was ultimately withdrawn because of controversy surrounding the value of privacy for different stakeholders [41].

The recently introduced NeurIPS Dataset and Benchmark Track is a clear example of an intervention that shifts incentive structures within the MLR community by rewarding dataset development and other forms of data work. We believe these sorts of interventions can play a critical role in incentivizing careful dataset development that is meaningfully aligned with problem domains. However, our finding that a small number of well-resourced institutions are responsible for most benchmarks in circulation today has implications for data-oriented interventions in the field. Our research suggests that simply calling for ML researchers to develop more datasets, and shifting incentive structures so that dataset development is valued and rewarded may not be enough to diversify dataset usage and the perspectives that are ultimately shaping and setting MLR research agendas. In addition to incentivizing dataset development, we advocate for equity-oriented policy interventions that prioritize significant funding for people in less-resourced institutions to create high-quality datasets. This would diversify — from a social and cultural perspective — the benchmark datasets being used to evaluate modern ML methods.

5.3 Limitations and Future Work

Because our findings rely on a unique community-curated resource, one of the limitations of this study is that our results are contingent on the structure and coverage of PWC. Sensitivity analyses suggest that while PWC’s coverage of ML publications is not perfect and exhibits some recency bias, the omitted papers tend to be low impact. Moreover, the crowdsourced taxonomy of parent-child task relations in PWC may be subjective and/or noisy, especially for small or new tasks.⁶ To increase our confidence in task annotations, we focused our analyses on larger, higher-level task communities and considered dataset usages invalid if they did not share a task label with the dataset. Lastly, we find that the concentration trends in Regression 1 are largely robust to model specification and our choice of Gini as an outcome. See the appendix for details on design choices and sensitivity analyses.

Finally, we emphasize that our findings are highly nuanced. We report trends that our analyses revealed, but refrain from imposing normative judgements on many of these trends. For example, the high rates of adoption raise potential concerns and point to an important future area of examination. The mere fact that datasets travel between task communities is not necessarily problematic, and indeed the widespread sharing of datasets has been central to methodological advancements in the field. We hope this work will offer a foundation for future empirical work examining the details of dataset transfer and the context-specific implications of our findings.

6 Conclusion

Benchmark datasets play a powerful role in the social organization of the field of machine learning. In this work, we empirically examine patterns of creation, adoption, and usage within and across MLR task communities. We find that benchmarking practices are heavily concentrated on a small number of datasets for each task community and heavily concentrated on datasets originating from a small number of well-resourced institutions across the field as a whole. We also find that many benchmark datasets flow between multiple task communities and are leveraged to evaluate progress on tasks for which the data was not explicitly designed. We hope this analysis will inform community-wide initiatives to shift patterns of dataset development and use so as to enable more rigorous, ethical, and socially informed research.

⁶The full list of parent tasks and parent/child relations is available in the GitHub.

References

- [1] David Schlangen. Targeting the benchmark: On methodology in current natural language processing research. *arXiv preprint*, 2007.04792, 2020.
- [2] Ravit Dotan and Smitha Milli. Value-laden disciplinary shifts in machine learning. In *Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency*, FAT* '20, page 294, New York, NY, USA, 2020. Association for Computing Machinery.
- [3] Amandalynne Paullada, Inioluwa Deborah Raji, Emily M. Bender, Emily Denton, and Alex Hanna. Data and its (dis)contents: A survey of dataset development and use in machine learning research. *NeurIPS Workshop on Machine Learning Retrospectives, Surveys, and Meta-analyses*, 2020.
- [4] Joy Buolamwini and Timnit Gebru. Gender shades: Intersectional accuracy disparities in commercial gender classification. In Sorelle A. Friedler and Christo Wilson, editors, *Proceedings of Machine Learning Research*, volume 81, pages 77–91, New York, NY, USA, 23–24 Feb 2018. PMLR.
- [5] S. Shankar, Yoni Halpern, Eric Breck, J. Atwood, Jimbo Wilson, and D. Sculley. No classification without representation: Assessing geodiversity issues in open data sets for the developing world. *arXiv preprint*, 1711.08536, 2017.
- [6] Jieyu Zhao, Tianlu Wang, Mark Yatskar, Vicente Ordonez, and Kai-Wei Chang. Gender bias in coreference resolution: Evaluation and debiasing methods. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers)*, pages 15–20, New Orleans, Louisiana, June 2018. Association for Computational Linguistics.
- [7] Lucas Dixon, John Li, Jeffrey Sorensen, Nithum Thain, and Lucy Vasserman. Measuring and mitigating unintended bias in text classification. In *Proceedings of the 2018 AAAI/ACM Conference on AI, Ethics, and Society*, pages 67–73, 2018.
- [8] Kate Crawford and Trevor Paglen. Excavating ai: The politics of images in machine learning training sets. <https://www.excavating.ai/>, 2019.
- [9] Abeba Birhane and Vinay Uday Prabhu. Large image datasets: A pyrrhic win for computer vision? In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 1537–1547, 2021.
- [10] Timnit Gebru, Jamie Morgenstern, Briana Vecchione, Jennifer Wortman Vaughan, Hanna Wallach, Hal Daumé III, and Kate Crawford. Datasheets for datasets. *arXiv preprint arXiv:1803.09010*, 2018.
- [11] R. Stuart Geiger, Kevin Yu, Yanlai Yang, Mindy Dai, Jie Qiu, Rebekah Tang, and Jenny Huang. Garbage in, garbage out? do machine learning application papers in social computing report where human-labeled training data comes from? In *Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency*, FAT* '20, page 325–336, New York, NY, USA, 2020. Association for Computing Machinery.
- [12] Morgan Klaus Scheuerman, Emily Denton, and Alex Hanna. Do datasets have politics? Disciplinary values in computer vision dataset development. In *The 24th ACM Conference on Computer-Supported Cooperative Work and Social Computing (CSCW)*, 2021.
- [13] Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel, Matthias Bethge, and Felix A Wichmann. Shortcut learning in deep neural networks. *arXiv preprint*, 2004.07780, 2020.
- [14] Alexander D’Amour, Katherine A. Heller, Dan Moldovan, Ben Adlam, Babak Alipanahi, Alex Beutel, Christina Chen, Jonathan Deaton, Jacob Eisenstein, Matthew D. Hoffman, Farhad Hormozdiari, Neil Houlsby, Shaobo Hou, Ghassen Jerfel, Alan Karthikesalingam, Mario Lucic, Yi-An Ma, Cory Y. McLean, Diana Mincu, Akinori Mitani, Andrea Montanari, Zachary Nado,

- 466 Vivek Natarajan, Christopher Nielson, Thomas F. Osborne, Rajiv Raman, Kim Ramasamy, Rory
 467 Sayres, Jessica Schrouff, Martin Seneviratne, Shannon Sequeira, Harini Suresh, Victor Veitch,
 468 Max Vladymyrov, Xuezhi Wang, Kellie Webster, Steve Yadlowsky, Taedong Yun, Xiaohua
 469 Zhai, and D. Sculley. Underspecification presents challenges for credibility in modern machine
 470 learning. *arXiv preprint*, 2011.03395, 2020.
- 471 [15] Kenneth Ward Church. Emerging trends: A tribute to Charles Wayne. *Natural Language*
 472 *Engineering*, 24(1):155–160, 2018.
- 473 [16] Kenneth Ward Church and Joel Hestness. A survey of 25 years of evaluation. *Natural Language*
 474 *Engineering*, 25(6):753–767, 2019.
- 475 [17] Deborah I Raji, Emily M. Bender, Amandalynne Paullada, Emily Denton, and Alex Hanna.
 476 Ai and the everything in the whole wide world benchmark. *NeurIPS Workshop on Machine*
 477 *Learning Retrospectives, Surveys, and Meta-analyses*, 2020.
- 478 [18] Dario Amodei, Danny Hernandez, Girish Sastry, Jack Clark, Greg Brockman, and Ilya Sutskever.
 479 Ai and compute. <https://openai.com/blog/ai-and-compute/>, 2018.
- 480 [19] Susan Elliott Sim. *A theory of benchmarking with applications to software reverse engineering*.
 481 University of Toronto, 2003.
- 482 [20] S.E. Sim, S. Easterbrook, and R.C. Holt. Using benchmarking to advance research: a challenge
 483 to software engineering. In *25th International Conference on Software Engineering, 2003.*
 484 *Proceedings.*, pages 74–83, 2003.
- 485 [21] Randall Collins. Why the social sciences won’t become high-consensus, rapid-discovery science.
 486 *Sociological forum*, 9(2):155–177, 1994.
- 487 [22] Tom Simonite. Google’s AI guru wants computers to think more like brains. *Wired*, 2018.
- 488 [23] D. Sculley, Jasper Snoek, Alexander B. Wiltschko, and A. Rahimi. Winner’s curse? on pace,
 489 progress, and empirical rigor. In *The Sixth International Conference on Learning Representa-*
 490 *tions (ICLR)*, 2018.
- 491 [24] Roy Schwartz, Jesse Dodge, Noah A. Smith, and Oren Etzioni. Green AI. *arXiv preprint*,
 492 1907.10597, 2019.
- 493 [25] Jesse Dodge, Suchin Gururangan, Dallas Card, Roy Schwartz, and Noah A. Smith. Show your
 494 work: Improved reporting of experimental results. In *Proceedings of the 2019 Conference on*
 495 *Empirical Methods in Natural Language Processing and the 9th International Joint Conference*
 496 *on Natural Language Processing (EMNLP-IJCNLP)*, pages 2185–2194, Hong Kong, China,
 497 November 2019. Association for Computational Linguistics.
- 498 [26] Kawin Ethayarajh and Dan Jurafsky. Utility is in the eye of the user: A critique of nlp
 499 leaderboards. *arXiv preprint*, 2009.13888, 2020.
- 500 [27] Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for
 501 benchmarking machine learning algorithms. *arXiv preprint*, 1708.07747, 2017.
- 502 [28] L. Beyer, Olivier J. H’enaiff, Alexander Kolesnikov, Xiaohua Zhai, and Aäron van den Oord.
 503 Are we done with imagenet? *arXiv preprint*, 2006.07159, 2020.
- 504 [29] Dimitris Tsipras, Shibani Santurkar, Logan Engstrom, Andrew Ilyas, and Aleksander Madry.
 505 From imagenet to image classification: Contextualizing progress on benchmarks. *International*
 506 *Conference on Machine Learning (ICML)*, 2020.
- 507 [30] Benjamin Heinzerling. NLP’s Clever Hans moment has arrived. *The Gradient*, 2019.
- 508 [31] Emily M. Bender, Timnit Gebru, Angelina McMillan-Major, and Shmargaret Shmitchell. On
 509 the dangers of stochastic parrots: Can language models be too big? 🦜. In *Proceedings of FAccT*
 510 *2021*, 2021.

- 511 [32] Nithya Sambasivan, Shivani Kapania, Hannah Highfill, Diana Akrong, Praveen Kumar Paritosh,
512 and Lora Mois Aroyo. "everyone wants to do the model work, not the data work": Data cascades
513 in high-stakes ai. 2021.
- 514 [33] J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. ImageNet: A Large-Scale
515 Hierarchical Image Database. In *Proceedings of the IEEE/CVF Conference on Computer Vision
516 and Pattern Recognition (CVPR)*, 2009.
- 517 [34] Kuansan Wang, Zhihong Shen, Chiyuan Huang, Chieh-Han Wu, Yuxiao Dong, and Anshul
518 Kanakia. Microsoft academic graph: When experts are not enough. *Quantitative Science
519 Studies*, 1(1):396–413, 2020.
- 520 [35] James B. McDonald and Michael Ransom. *The Generalized Beta Distribution as a Model
521 for the Distribution of Income: Estimation of Related Measures of Inequality*, pages 147–166.
522 Springer New York, New York, NY, 2008.
- 523 [36] George Deltas. The small-sample bias of the gini coefficient: results and implications for
524 empirical research. *Review of economics and statistics*, 85(1):226–234, 2003.
- 525 [37] Michael Smithson and Jay Verkuilen. A better lemon squeezer? maximum-likelihood regression
526 with beta-distributed dependent variables. *Psychological methods*, 11(1):54, 2006.
- 527 [38] Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for genera-
528 tive adversarial networks. In *2019 IEEE/CVF Conference on Computer Vision and Pattern
529 Recognition (CVPR)*, pages 4396–4405, 2019.
- 530 [39] Ira Kemelmacher-Shlizerman, Steven M Seitz, Daniel Miller, and Evan Brossard. The megaface
531 benchmark: 1 million faces for recognition at scale. In *Proceedings of the IEEE Conference on
532 Computer Vision and Pattern Recognition*, pages 4873–4882, 2016.
- 533 [40] Yandong Guo, Lei Zhang, Yuxiao Hu, Xiaodong He, and Jianfeng Gao. Ms-celeb-1m: A
534 dataset and benchmark for large-scale face recognition. In *Proceedings of the 14th European
535 Conference on Computer Vision (ECCV)*, volume 9907, pages 87–102, 10 2016.
- 536 [41] Jules. Harvey, Adam. LaPlace. Exposing.ai. <https://exposing.ai>, 2021.
- 537 [42] Clare Garvie, Alvaro Bedoya, and Jonathan Frankle. The perpetual line-up: Unregulated police
538 face recognition in america. Technical report, Georgetown Law, Center on Privacy Technology,
539 2016.
- 540 [43] Mei Wang, Weihong Deng, Jiani Hu, Xunqiang Tao, and Yaohai Huang. Racial faces in the wild:
541 Reducing racial bias by information maximization adaptation network. In *2019 IEEE/CVF
542 International Conference on Computer Vision (ICCV)*, pages 692–702, 2019.
- 543 [44] R.K. Merton and N.W. Storer. *The Sociology of Science: Theoretical and Empirical Investiga-
544 tions*. Phoenix books. University of Chicago Press, 1973.
- 545 [45] Naomi Oreskes. *Science on a Mission: How Military Funding Shaped What We Do and Don't
546 Know about the Ocean*. University of Chicago Press, 2021.
- 547 [46] Evelyn C Pielou. The measurement of diversity in different types of biological collections.
548 *Journal of theoretical biology*, 13:131–144, 1966.