


Explainable AI : Shapley Values

A Unified Approach to Interpreting Model
Predictions

Scott Lundberg, Su-In Lee

Need for Explainable AI



Need for Explainable AI

Some of the articles of GDPR can be interpreted as requiring explanation of the decision made by a machine learning algorithm, when it is applied to a human subject.

UW Prof. Pedro Domingos, a leading AI researcher, started a firestorm with his tweet



Pedro Domingos

@pmddomingos




Starting May 25, the European Union will require algorithms to explain their output, making deep learning illegal.

11:59 AM - Jan 29, 2018


♡ 344 💬 249 people are talking about this



Complicated AI Model



Explainable model: Additive feature attribution model



$$g(z') = \sum_{i=1}^M \phi_i z'_i,$$

where $z' \in \{0, 1\}^M$, M is the number of simplified input features, and $\phi_i \in \mathbb{R}$.

Additive feature attribution methods

LIME

Ribeiro et al. 2016

DeepLIFT

Shrikumar et al. 2016

Shapley reg.
values

Lipovetsky et al. 2001

Σ

Relevance prop.

Bach et al. 2015

QII

Datta et al. 2016


Shapley
sampling

Štrumbelj et al. 2011


Path
expectations

Saabas 2014


Additive feature attribution methods



Why additive feature attribution methods may work




Complex models are inherently complex!



But a single prediction involves only a small piece of that complexity.

SHapley Additive exPlanation - (SHAP) values (1)



Base rate

Prediction for John

20%

55%

0


$E[f(x)]$

$f(x)$




How did we get here?

SHapley Additive exPlanation (SHAP) values (2)



SHapley Additive exPlanation (SHAP) values (2)



SHapley Additive exPlanation (SHAP) values (3) – phi values

$$\text{Explain model} = \sum_{i=1}^{m \text{ features}} \varphi_i X_i$$


where X_i an input and φ_i is the effect of X_i on the model.

$$\varphi_{age} = \langle f(\text{age} \cup \text{features}_{\text{some}}) - f(\text{features}_{\text{some}}) \rangle_{\text{shapley values}}$$

f is your model output, eg accuracy, squared error
 $\text{features}_{\text{some}}$ is the set containing subset of features


SHapley Additive exPlanation (SHAP) values (4) – phi values

$$\varphi_{pink} = \langle f(pink \cup features_{some}) - f(features_{some}) \rangle_{shapley\ values}$$




SHapley Additive exPlanation (SHAP) values (4) – phi values ϕ

$$\varphi_{\text{pink}} = \text{weight_avg}(\text{img1}, \text{img2})$$



Another Example : VGG16



SHapley Additive exPlanation (SHAP)
values (5) – solved using weighted
linear regression

$$\phi = (X^T W X)^{-1} X^T W y$$


X is the feature binary vector of all combinations of
 X

W is weights for each example


y is model output for X

Applying to Mnist (1)

- Mnist model with 4 convolutional layers and 2 dense layers.
- Accuracy is 99.6%
- Split image to 7*7 pixels for shapley computation
- Sampled 7367 combinations for each test image
 - ~ all -1 pixel images, ${}^{49}C_1 = 49$
 - ~ all -2 pixel images, ${}^{49}C_2 = 1176$
 - ~ all -3 pixel images, ${}^{49}C_3 = 6142$




Applying to Mnist (2) – Global analysis




Applying to Mnist (3) – Individual analysis (a)

Test Example: 359


Predicted Digit: 4 (58%),
Actual Digit: 9 (40%)




Median pic of
all digit 4




Median shapley value
of all digit 4




Test Example : 359
shapley value for digit 4




Median pic of
all digit 9



Median shapley value
of all digit 9




Test Example : 359
shapley value for digit 9




Applying to Mnist (3) – Individual analysis (b)


Test Example: 2130
Predicted Digit: 9 (93%),
Actual Digit: 4 (6%)




Median pic of
all digit 9




Median shapley value
of all digit 9




Test Example : 2130
shapley value for digit 9




Median pic of
all digit 4



Median shapley value
of all digit 4




Test Example : 2130
shapley value for digit 4




Applying to Mnist (3) – Individual analysis (c)

Test Example: 2293


Predicted Digit: 4 (98%),
Actual Digit: 9 (0%)




Median pic of
all digit 4




Median shapley value
of all digit 4




Test Example : 2293
shapley value for digit 4




Median pic of
all digit 9



Median shapley value
of all digit 9




Test Example : 2293
shapley value for digit 9



Drawbacks

- Computationally intensive, requires to compute 2^m examples for m features followed by inverse of $m \times m$ matrix.
 - ~ I only sampled 10^3 out of 10^{14} combinations
- How do you appropriately remove a feature ?




- Method does not explain inner workings, rather it is a model upon a model to explain the final output.

Summary


1.

Need for Explainable AI



2.

Additive feature attribution methods




3. Intuition


$$g(z') = \sum_{i=1}^M \phi_i z'_i,$$

$$\phi_{\text{pink}} = \text{weight_avg}(\text{mean pic of class 0} - \text{mean pic of class 1})$$

4. Analysis of global predictions



5. Analysis of each prediction



6. Drawbacks



Another application : Transfer-learned Inception3 model

