

1. Description

1.1. Project

| Project Name | MCU_Project |
|-----------------|-------------------|
| Board Name | STM32F411E-DISCO |
| Generated with: | STM32CubeMX 6.6.1 |
| Date | 10/17/2022 |


1.2. MCU

| MCU Series | STM32F4 |
|----------------|---------------|
| MCU Line | STM32F411 |
| MCU name | STM32F411VETx |
| MCU Package | LQFP100 |
| MCU Pin number | 100 |

1.3. Core(s) information

| Core(s) | Arm Cortex-M4 |
|---------|---------------|

2. Pinout Configuration




3. Pins Configuration

| Pin Number LQFP100 | Pin Name (function after reset) | Pin Type | Alternate Function(s) | Label |
|-----------------------|---------------------------------------|----------|--------------------------|------------------|
| 6 | VBAT | Power | | |
| 8 | PC14-OSC32_IN | I/O | RCC_OSC32_IN | PC14-OSC32_IN |
| 9 | PC15-OSC32_OUT | I/O | RCC_OSC32_OUT | PC15-OSC32_OUT |
| 10 | VSS | Power | | |
| 11 | VDD | Power | | |
| 12 | PH0 - OSC_IN | I/O | RCC_OSC_IN | PH0-OSC_IN |
| 13 | PH1 - OSC_OUT | I/O | RCC_OSC_OUT | PH1-OSC_OUT |
| 14 | NRST | Reset | | |
| 19 | VDD | Power | | |
| 20 | VSSA | Power | | |
| 21 | VREF+ | Power | | |
| 22 | VDDA | Power | | |
| 24 | PA1 | I/O | ADC1_IN1 | |
| 25 | PA2 | I/O | USART2_TX | |
| 26 | PA3 | I/O | ADC1_IN3 | |
| 27 | VSS | Power | | |
| 28 | VDD | Power | | |
| 30 | PA5 | I/O | ADC1_IN5 | |
| 31 | PA6 | I/O | ADC1_IN6 | |
| 48 | VCAP1 | Power | | |
| 49 | VSS | Power | | |
| 50 | VDD | Power | | |
| 59 | PD12 * | I/O | GPIO_Output | LD4 [Green Led] |
| 60 | PD13 * | I/O | GPIO_Output | LD3 [Orange Led] |
| 61 | PD14 * | I/O | GPIO_Output | LD5 [Red Led] |
| 62 | PD15 * | I/O | GPIO_Output | LD6 [Blue Led] |
| 63 | PC6 | I/O | USART6_TX | |
| 64 | PC7 | I/O | USART6_RX | |
| 68 | PA9 | I/O | USART1_TX | |
| 69 | PA10 | I/O | USART1_RX | |
| 72 | PA13 | I/O | SYS_JTMS-SWDIO | SWDIO |
| 73 | VCAP2 | Power | | |
| 74 | VSS | Power | | |
| 75 | VDD | Power | | |
| 76 | PA14 | I/O | SYS_JTCK-SWCLK | SWCLK |
| 87 | PD6 | I/O | USART2_RX | |

| Pin Number LQFP100 | Pin Name (function after reset) | Pin Type | Alternate Function(s) | Label |
|-----------------------|---------------------------------------|----------|--------------------------|-------|
| 94 | воото | Boot | | |
| 99 | VSS | Power | | |
| 100 | VDD | Power | | |

^{*} The pin is affected with an I/O function

4. Clock Tree Configuration



5. Software Project

5.1. Project Settings

| Name | Value | |
|-----------------------------------|---|--|
| Project Name | MCU_Project | |
| Project Folder | F:\SEMG_Mechanical_Arm\code\MCU_Project\MCU_Project | |
| Toolchain / IDE | MDK-ARM V5.32 | |
| Firmware Package Name and Version | STM32Cube FW_F4 V1.25.2 | |
| Application Structure | Advanced | |
| Generate Under Root | No | |
| Do not generate the main() | No | |
| Minimum Heap Size | 0x200 | |
| Minimum Stack Size | 0x400 | |

5.2. Code Generation Settings

| Name | Value |
|---|---|
| STM32Cube MCU packages and embedded software | Copy all used libraries into the project folder |
| Generate peripheral initialization as a pair of '.c/.h' files | Yes |
| Backup previously generated files when re-generating | No |
| Keep User Code when re-generating | Yes |
| Delete previously generated files when not re-generated | Yes |
| Set all free pins as analog (to optimize the power | No |
| consumption) | |
| Enable Full Assert | Yes |

5.3. Advanced Settings - Generated Function Calls

| Rank | Function Name | Peripheral Instance Name |
|------|---------------------|--------------------------|
| 1 | MX_GPIO_Init | GPIO |
| 2 | MX_DMA_Init | DMA |
| 3 | SystemClock_Config | RCC |
| 4 | MX_ADC1_Init | ADC1 |
| 5 | MX_USART1_UART_Init | USART1 |
| 6 | MX_USART2_UART_Init | USART2 |
| 7 | MX_USART6_UART_Init | USART6 |
| 8 | MX_TIM2_Init | TIM2 |
| 9 | MX_TIM3_Init | TIM3 |

| MCU_Project Project |
|----------------------|
| Configuration Report |

6. Power Consumption Calculator report

6.1. Microcontroller Selection

| Series | STM32F4 |
|-----------|---------------|
| Line | STM32F411 |
| мси | STM32F411VETx |
| Datasheet | DS10314_Rev6 |

6.2. Parameter Selection

| Temperature | 25 |
|-------------|-----|
| Vdd | 1.7 |

6.3. Battery Selection

| Battery | Li-SOCL2(A3400) |
|-------------------|-----------------|
| Capacity | 3400.0 mAh |
| Self Discharge | 0.08 %/month |
| Nominal Voltage | 3.6 V |
| Max Cont Current | 100.0 mA |
| Max Pulse Current | 200.0 mA |
| Cells in series | 1 |
| Cells in parallel | 1 |


6.4. Sequence

| Step | Step1 | Step2 |
|------------------------|-------------|-----------------------|
| Mode | RUN | STOP |
| Vdd | 1.7 | 1.7 |
| Voltage Source | Battery | Battery |
| Range | Scale1-High | No Scale |
| Fetch Type | SRAM | n/a |
| CPU Frequency | 100 MHz | 0 Hz |
| Clock Configuration | HSE PLL | Regulator_LPLV Flash- |
| | | PwrDwn |
| Clock Source Frequency | 4 MHz | 0 Hz |
| Peripherals | | |
| Additional Cons. | 0 mA | 0 mA |
| Average Current | 12.7 mA | 9 μΑ |
| Duration | 0.1 ms | 0.9 ms |
| DMIPS | 125.0 | 0.0 |
| Ta Max | 104.07 | 105 |
| Category | In DS Table | In DS Table |

6.5. Results

| Sequence Time | 1 ms | Average Current | 1.28 mA |
|---------------|---------------|-----------------|-------------|
| Battery Life | 3 months, 19 | Average DMIPS | 125.0 DMIPS |
| | days, 6 hours | | |

6.6. Chart



7. Peripherals and Middlewares Configuration

7.1. ADC1 mode: IN1 mode: IN3 mode: IN5 mode: IN6

mode: Vrefint Channel7.1.1. Parameter Settings:

ADCs_Common_Settings:

Mode Independent mode

ADC_Settings:

Clock Prescaler PCLK2 divided by 4

Resolution 12 bits (15 ADC Clock cycles)

Data AlignmentRight alignmentScan Conversion ModeEnabledContinuous Conversion ModeDisabled

Discontinuous Conversion Mode Enabled *

Number Of Discontinuous Conversions 1

DMA Continuous Requests Enabled *

End Of Conversion Selection EOC flag at the end of single channel conversion

ADC_Regular_ConversionMode:

Number Of Conversion 5 *

External Trigger Conversion Source

Timer 2 Trigger Out event *

External Trigger Conversion Edge

Trigger detection on the rising edge

Rank 1

Channel 1
Sampling Time 28 Cycles *

<u>Rank</u> **2** *

Channel 3 *
Sampling Time 28 Cycles *

<u>Rank</u> 3 *

Channel Channel 5 *
Sampling Time 28 Cycles *

<u>Rank</u> 4 *

Channel 6 *
Sampling Time 28 Cycles *

<u>Rank</u> 5 *

Channel Vrefint *

Sampling Time 28 Cycles *

ADC_Injected_ConversionMode:

Number Of Conversions 0

WatchDog:

Enable Analog WatchDog Mode false

7.2. RCC

High Speed Clock (HSE): BYPASS Clock Source Low Speed Clock (LSE): Crystal/Ceramic Resonator

7.2.1. Parameter Settings:

System Parameters:

VDD voltage (V) 3.3
Instruction Cache Enabled
Prefetch Buffer Enabled
Data Cache Enabled

Flash Latency(WS) 3 WS (4 CPU cycle)

RCC Parameters:

HSI Calibration Value 16

TIM Prescaler Selection Disabled

HSE Startup Timout Value (ms) 100

LSE Startup Timout Value (ms) 5000

Power Parameters:

Power Regulator Voltage Scale Power Regulator Voltage Scale 1

7.3. SYS

Debug: Serial Wire

Timebase Source: SysTick

7.4. TIM2

Clock Source: Internal Clock

7.4.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 1000-1 *

Counter Mode Up

Counter Period (AutoReload Register - 32 bits value) 5-1 *

Internal Clock Division (CKD)

auto-reload preload

No Division

Disable

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit) Disable (Trigger input effect not delayed)

Trigger Event Selection Update Event *

7.5. TIM3

Clock Source : Internal Clock

7.5.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 10000-1 *

Counter Mode Up

Counter Period (AutoReload Register - 16 bits value) 1000-1 *

Internal Clock Division (CKD) No Division auto-reload preload Disable

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit) Disable (Trigger input effect not delayed)

Trigger Event Selection Reset (UG bit from TIMx_EGR)

7.6. USART1

Mode: Asynchronous

7.6.1. Parameter Settings:

Basic Parameters:

Baud Rate 9600 *

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

Advanced Parameters:

Data Direction Receive and Transmit

Over Sampling 16 Samples

7.7. USART2

Mode: Asynchronous

7.7.1. Parameter Settings:

Basic Parameters:

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

Advanced Parameters:

Data Direction Receive and Transmit

Over Sampling 16 Samples

7.8. **USART6**

Mode: Asynchronous

7.8.1. Parameter Settings:

Basic Parameters:

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

Advanced Parameters:

Data Direction Receive and Transmit

Over Sampling 16 Samples

^{*} User modified value

8. System Configuration

8.1. GPIO configuration

| IP | Pin | Signal | GPIO mode | GPIO pull/up pull down | Max Speed | User Label |
|--------|------------------------|--------------------|------------------------------|-----------------------------|--------------|------------------|
| ADC1 | PA1 | ADC1_IN1 | Analog mode | No pull-up and no pull-down | n/a | |
| | PA3 | ADC1_IN3 | Analog mode | No pull-up and no pull-down | n/a | |
| | PA5 | ADC1_IN5 | Analog mode | No pull-up and no pull-down | n/a | |
| | PA6 | ADC1_IN6 | Analog mode | No pull-up and no pull-down | n/a | |
| RCC | PC14- OSC32_IN | RCC_OSC32_IN | n/a | n/a | n/a | PC14-OSC32_IN |
| | PC15- OSC32_OU T | RCC_OSC32_O UT | n/a | n/a | n/a | PC15-OSC32_OUT |
| | PH0 - OSC_IN | RCC_OSC_IN | n/a | n/a | n/a | PH0-OSC_IN |
| | PH1 - OSC_OUT | RCC_OSC_OUT | n/a | n/a | n/a | PH1-OSC_OUT |
| SYS | PA13 | SYS_JTMS- SWDIO | n/a | n/a | n/a | SWDIO |
| | PA14 | SYS_JTCK- SWCLK | n/a | n/a | n/a | SWCLK |
| USART1 | PA9 | USART1_TX | Alternate Function Push Pull | No pull-up and no pull-down | Very High | |
| | PA10 | USART1_RX | Alternate Function Push Pull | No pull-up and no pull-down | Very High | |
| USART2 | PA2 | USART2_TX | Alternate Function Push Pull | No pull-up and no pull-down | Very High | |
| | PD6 | USART2_RX | Alternate Function Push Pull | No pull-up and no pull-down | Very High | |
| USART6 | PC6 | USART6_TX | Alternate Function Push Pull | No pull-up and no pull-down | Very High | |
| | PC7 | USART6_RX | Alternate Function Push Pull | No pull-up and no pull-down | Very High | |
| GPIO | PD12 | GPIO_Output | Output Push Pull | No pull-up and no pull-down | Low | LD4 [Green Led] |
| | PD13 | GPIO_Output | Output Push Pull | No pull-up and no pull-down | Low | LD3 [Orange Led] |
| | PD14 | GPIO_Output | Output Push Pull | No pull-up and no pull-down | Low | LD5 [Red Led] |
| | PD15 | GPIO_Output | Output Push Pull | No pull-up and no pull-down | Low | LD6 [Blue Led] |

8.2. DMA configuration

| DMA request | Stream | Direction | Priority |
|-------------|--------------|----------------------|----------|
| ADC1 | DMA2_Stream0 | Peripheral To Memory | High * |

ADC1: DMA2_Stream0 DMA request Settings:

Mode: Circular *
Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable *
Peripheral Data Width: Half Word
Memory Data Width: Half Word

8.3. NVIC configuration

8.3.1. NVIC

| Interrupt Table | Enable | Preenmption Priority | SubPriority | |
|---|----------|----------------------|-------------|--|
| Non maskable interrupt | true | 0 | 0 | |
| Hard fault interrupt | true | 0 | 0 | |
| Memory management fault | true | 0 | 0 | |
| Pre-fetch fault, memory access fault | true | 0 | 0 | |
| Undefined instruction or illegal state | true | 0 | 0 | |
| System service call via SWI instruction | true | 0 | 0 | |
| Debug monitor | true | 0 | 0 | |
| Pendable request for system service | true | 0 | 0 | |
| System tick timer | true | 15 | 0 | |
| ADC1 global interrupt | true | 0 | 0 | |
| TIM3 global interrupt | true 10 | | 0 | |
| USART1 global interrupt | true 3 0 | | | |
| USART2 global interrupt | true | 0 | | |
| DMA2 stream0 global interrupt | true | 2 | 0 | |
| USART6 global interrupt | true 6 | | 0 | |
| PVD interrupt through EXTI line 16 | unused | | | |
| Flash global interrupt | unused | | | |
| RCC global interrupt | unused | | | |
| TIM2 global interrupt | unused | | | |
| FPU global interrupt | unused | | | |

8.3.2. NVIC Code generation


| Enabled interrupt Table | Select for init sequence ordering | Generate IRQ handler | Call HAL handler |
|---|-----------------------------------|-------------------------|------------------|
| Non maskable interrupt | false | true | false |
| Hard fault interrupt | false | true | false |
| Memory management fault | false | true | false |
| Pre-fetch fault, memory access fault | false | true | false |
| Undefined instruction or illegal state | false | true | false |
| System service call via SWI instruction | false | true | false |
| Debug monitor | false | true | false |
| Pendable request for system service | false | true | false |
| System tick timer | false | true | true |
| ADC1 global interrupt | false | true | true |
| TIM3 global interrupt | false | true | true |
| USART1 global interrupt | false | true | true |
| USART2 global interrupt | false | true | true |

| Enabled interrupt Table | Select for init sequence ordering | Generate IRQ handler | Call HAL handler |
|-------------------------------|-----------------------------------|-------------------------|------------------|
| DMA2 stream0 global interrupt | false | true | true |
| USART6 global interrupt | false | true | true |

^{*} User modified value

9. System Views

- 9.1. Category view
- 9.1.1. Current



10. Docs & Resources

Type Link

Presentations https://www.st.com/resource/en/product_presentation/stm32-

stm8_embedded_software_solutions.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32_eval-

tools_portfolio.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32_stm8_functi

onal-safety-packages.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32-

stm8_software_development_tools.pdf

Training Material https://www.st.com/resource/en/sales_guide/sg_sc2154.pdf

Flyers https://www.st.com/resource/en/flyer/flnucleolrwan.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32f4x1.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32nucleo.pdf

Flyers https://www.st.com/resource/en/flyer/flstmcsuite.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32trust.pdf

Product https://www.st.com/resource/en/certification_document/stm32_authenticat

Certifications ion_can.pdf

Application Notes https://www.st.com/resource/en/application_note/an1181-electrostatic-

discharge-sensitivity-measurement-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an1709-emc-design-

guide-for-stm8-stm32-and-legacy-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2606-stm32-

microcontroller-system-memory-boot-mode-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2639-soldering-

recommendations-and-package-information-for-leadfree-ecopack-mcus-

and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2834-how-to-get-the-

best-adc-accuracy-in-stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2867-oscillator-

design-guide-for-stm8afals-stm32-mcus-and-mpus-stmicroelectronics.pdf

- Application Notes https://www.st.com/resource/en/application_note/an2945-stm8s-and-stm32-mcus-a-consistent-832bit-product-line-for-painless-migration-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3070-managing-the-driver-enable-signal-for-rs485-and-iolink-communications-with-the-stm32s-usart-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3126-audio-and-waveform-generation-using-the-dac-in-stm32-products-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3154-can-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3155-usart-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3156-usb-dfu-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3364-migration-and-compatibility-guidelines-for-stm32-microcontroller-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3997-audio-playback-and-recording-using-the-stm32f4discovery-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3998-pdm-audio-software-decoding-on-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4013-stm32-crossseries-timer-overview-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4031-using-the-stm32f2-stm32f4-and-stm32f7-series-dma-controller-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4221-i2c-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4229-how-to-implement-a-vocoder-solution-using-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4230-stm32-

- microcontroller-random-number-generation-validation-using-the-nist-statistical-test-suite-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4277-using-stm32-device-pwm-shutdown-features-for-motor-control-and-digital-power-conversion-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4286-spi-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4488-getting-started-with-stm32f4xxxx-mcu-hardware-development-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4566-extending-the-dac-performance-of-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4616-migrating-from-stm32f401-and-stm32f411-lines-to-stm32l4-series-and-stm32l4-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4646-peripheral-interconnections-on-stm32f401-and-stm32f411-lines-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4655-virtually-increasing-the-number-of-serial-communication-peripherals-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4739-stm32cube-firmware-examples-for-stm32f4-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4750-handling-of-soft-errors-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4759-using-the-hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4776-generalpurpose-timer-cookbook-for-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4803-highspeed-si-simulations-using-ibis-and-boardlevel-simulations-using-hyperlynx-si-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4838-managing-

- memory-protection-unit-in-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4850-stm32-mcusspreadspectrum-clock-generation-principles-properties-andimplementation-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4879-usb-hardware-and-pcb-guidelines-using-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4904-migration-of-microcontroller-applications-from-stm32f1-series-to-stm32f4-access-lines-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4908-stm32-usart-automatic-baud-rate-detection-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4989-stm32-microcontroller-debug-toolbox-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4995-using-anelectromyogram-technique-to-detect-muscle-activitystmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5027-interfacing-pdm-digital-microphones-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5036-thermal-management-guidelines-for-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5073-receiving-spdif-audio-stream-with-the-stm32f4f7h7-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5156-introduction-to-stm32-microcontrollers-security-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5225-usb-typec-power-delivery-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5543-enhanced-methods-to-handle-spi-communication-on-stm32-devices-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4899-stm32microcontroller-gpio-hardware-settings-and-lowpower-consumptionstmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an1202_freertos_guide-

for related Tools freertos-guide-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an1602_semihosting_in for related Tools _truestudio-how-to-do-semihosting-in-truestudio-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an1801_stm32cubeprog for related Tools rammer in truestudio-installing-stm32cubeprogrammer-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/atollic_editing_keyboard

for related Tools _shortcuts-atollic-editing-keyboard-shortcuts-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/iar_to_atollic_truestudio

for related Tools __migration_guide-truestudio-for-arm-migration-guide-iar-embedded-

& Software workbench-to-truestudio-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/stm32cubemx_installatio

for related Tools n_in_truestudio-stm32cubemx-installation-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2656-stm32f10xxx-

for related Tools Icd-glass-driver-firmware-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an2790-tft-lcd-

for related Tools interfacing-with-the-highdensity-stm32f10xxx-fsmc-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3078-stm32-for related Tools inapplication-programming-over-the-ic-bus-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3116-stm32s-adc-

for related Tools modes-and-their-applications-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3174-implementing-

for related Tools receivers-for-infrared-remote-control-protocols-using-stm32f10xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3241-qvga-tftlcd-

for related Tools direct-drive-using-the-stm32f10xx-fsmc-peripheral-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3307-guidelines-for-for related Tools obtaining-iec-60335-class-b-certification-for-any-stm32-application-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3364-migration-and-

for related Tools compatibility-guidelines-for-stm32-microcontroller-applications-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3965-

for related Tools stm32f40xstm32f41x-inapplication-programming-using-the-usart-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3969-eeprom-

for related Tools emulation-in-stm32f40xstm32f41x-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3990-upgrading-

for related Tools stm32f4discovery-board-firmware-using-a-usb-key-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3997-audio-playback-

for related Tools and-recording-using-the-stm32f4discovery-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3998-pdm-audio-

for related Tools software-decoding-on-stm32-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4044-floating-point-

for related Tools unit-demonstration-on-stm32-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4187-using-the-crc-

for related Tools peripheral-in-the-stm32-family-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4323-getting-started-

for related Tools with-stemwin-library-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4365-using-stm32f4-

for related Tools mcu-power-modes-with-best-dynamic-efficiency-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4435-guidelines-forfor related Tools obtaining-ulcsaiec-607301603351-class-b-certification-in-any-stm32-

& Software application-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4457-implementingan-emulated-uart-on-stm32f4-microcontrollers-stmicroelectronics.pdf for related Tools

& Software

& Software

& Software

Application Notes https://www.st.com/resource/en/application_note/an4499-stm32-for related Tools nrf51822-bluetooth-low-energy-system-solution-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application_note/an4502-stm32for related Tools smbuspmbus-embedded-software-expansion-for-stm32cube-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4515-using-batchfor related Tools acquisition-mode-bam-to-maximize-power-efficiency-on-stm32f410stm32f411-stm32f412-stm32f413-microcontroller-lines-

stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4657-stm32for related Tools inapplication-programming-iap-using-the-usart-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4666-parallelfor related Tools synchronous-transmission-using-gpio-and-dma-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application_note/an4678-full-duplex-spifor related Tools emulation-for-stm32f4-microcontrollers-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application note/an4701-proprietaryfor related Tools code-readout-protection-on-microcontrollers-of-the-stm32f4-series-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4739-stm32cubefor related Tools firmware-examples-for-stm32f4-series-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4758-proprietaryfor related Tools code-readout-protection-on-stm32l4-stm32l4-stm32g4-and-stm32wb-

& Software series-mcus-stmicroelectronics.pdf Application Notes https://www.st.com/resource/en/application_note/an4759-using-the-

for related Tools hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-

& Software stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4841-digital-signal-for related Tools processing-for-stm32-microcontrollers-using-cmsis-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4968-proprietary-for related Tools code-read-out-protection-pcrop-on-stm32f72xxx-and-stm32f73xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5054-secure-for related Tools programming-using-stm32cubeprogrammer-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5056-integration-

for related Tools guide-for-the-xcubesbsfu-stm32cube-expansion-package-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5360-getting-started-

for related Tools with-projects-based-on-the-stm32mp1-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5361-getting-started-

for related Tools with-projects-based-on-dualcore-stm32h7-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application note/an5394-getting-started-

for related Tools with-projects-based-on-the-stm32l5-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5418-how-to-build-a-for related Tools simple-usbpd-sink-application-with-stm32cubemx-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5426-migrating-

for related Tools graphics-middleware-projects-from-stm32cubemx-540-to-stm32cubemx-

& Software 550-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5464-position-control-

for related Tools of-a-threephase-permanent-magnet-motor-using-xcubemcsdk-or-

& Software xcubemcsdkful-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5564-getting-started-

for related Tools with-projects-based-on-dualcore-stm32wl-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5698-adapting-thefor related Tools xcubestl-functional-safety-package-for-stm32-iec-61508-compliant-to-

& Software other-safety-standards-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5731-stm32cubemx-

for related Tools and-stm32cubeide-threadsafe-solution-stmicroelectronics.pdf

& Software

Design Notes & https://www.st.com/resource/en/design_tip/dt0088-fir-filter-design-by-

sampling-windowing-and-modulating-the-sinc-function-**Tips**

stmicroelectronics.pdf

https://www.st.com/resource/en/design_tip/dt0089-the-goertzel-algorithm-Design Notes &

to-compute-individual-terms-of-the-discrete-fourier-transform-dft-**Tips**

stmicroelectronics.pdf

Design Notes & https://www.st.com/resource/en/design_tip/dt0091-lattice-wave-digital-

Tips filter-design-and-automatic-c-code-generation-stmicroelectronics.pdf

https://www.st.com/resource/en/design_tip/dt0092-lattice-wave-digital-Design Notes &

Tips filter-test-and-performance-verification-stmicroelectronics.pdf

Device Option https://www.st.com/resource/en/device option list/opl stm32f411 512k.zi

Lists

Errata Sheets https://www.st.com/resource/en/errata_sheet/es0287-stm32f411xc-and-

stm32f411xe-device-limitations-stmicroelectronics.pdf

Datasheet https://www.st.com/resource/en/datasheet/dm00115249.pdf

Programming https://www.st.com/resource/en/programming manual/pm0214-stm32-Manuals cortexm4-mcus-and-mpus-programming-manual-stmicroelectronics.pdf

Reference https://www.st.com/resource/en/reference_manual/rm0383-

Manuals stm32f411xce-advanced-armbased-32bit-mcus-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical note/tn0516-overview-of-the-

& Articles stm32f0xf100xxf103xx-and-stm32f2xxf30xf4xx-mcus-pmsm-singledual-

foc-sdk-v40-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1163-description-of-

& Articles wlcsp-for-microcontrollers-and-recommendations-for-its-use-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1204-tape-and-reel-

& Articles shipping-media-for-stm32-microcontrollers-in-bga-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1205-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-fpn-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1206-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-qfp-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1207-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-so-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1208-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-tssop-and-ssop-

packages-stmicroelectronics.pdf