BoiAro REST API — Complete Documentation v2

Flutter Integration Reference

Version: 2.0
Date: 2026-04-05
Base URL: `https://kxpqejmjfnzhqcefyued.supabase.co/functions/v1/mobile-api`

Global Rules

Required Headers (every request)

Header	Value
`apikey`	`eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZiI6Imt4cHFlam1qZm56aHFjZWZ5dWVkIiwicm9s`
`Content-Type`	`application/json`
`Authorization`	`Bearer <access_token>`

Response Envelope

All responses are JSON. Success responses vary per endpoint. Error responses always follow:

```
{ "error": "Human-readable error message" }
```

HTTP Status Codes

Code	Meaning
`200`	Success
`201`	Resource created
`400`	Bad request / missing params
`401`	Authentication required
`403`	Forbidden (deactivated/deleted account)
`404`	Resource not found
`422`	Validation error (e.g. weak password)
`500`	Internal server error

Pagination Convention

Paginated endpoints accept:

- `limit` (int, default 20, max 50)
- `offset` (int, default 0)

And return `total` (int or null) alongside the data array.

1. Authentication

POST /auth/signup

Create a new user account. Email verification is required before login.

Field	Details
Auth required	No
Path params	None
Query params	None

Request body:

Field	Type	Required	Description
`email`	string	✅	User email address
`password`	string	✅	Min 6 characters
`display_name`	string	❌	User display name

```
{
  "email": "rahim@example.com",
  "password": "SecurePass123!",
  "display_name": "রহিম আহমেদ"
}
```

Success (201):

```
{
  "user_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "email": "rahim@example.com",
  "message": "Please verify your email"
}
```

Error (400):

```
{ "error": "email and password required" }
```

Error (422):

```
{ "error": "Password should be at least 6 characters" }
```

POST /auth/login

Sign in with email/password. Returns JWT tokens.

Field	Details
Auth required	No

Request body:

Field	Type	Required	Description
`email`	string	✅	Registered email
`password`	string	✅	Account password

```
{
  "email": "rahim@example.com",
  "password": "SecurePass123!"
}
```

Success (200):

```
{
  "access_token": "eyJhbGciOiJIUzI1NiIs...",
  "refresh_token": "v1_refresh_abc123def456...",
  "expires_in": 3600,
  "user": {
    "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
    "email": "rahim@example.com"
  }
}
```

Response field	Type	Description
`access_token`	string	JWT for Authorization header, expires in `expires_in` seconds
`refresh_token`	string	Use with `/auth/refresh` to get a new access token
`expires_in`	int	Token lifetime in seconds (typically 3600)
`user.id`	uuid	User's unique ID
`user.email`	string	User's email

Error (401):

```
{ "error": "Invalid login credentials" }
```

Error (403):

```
{ "error": "Account deactivated. Contact support." }
```

```
{ "error": "Account has been deleted. Contact support." }
```

POST /auth/refresh

Refresh an expired access token using the refresh token.

Field	Details
Auth required	No

Request body:

Field	Type	Required
`refresh_token`	string	✅

```
{ "refresh_token": "v1_refresh_abc123def456..." }
```

Success (200):

```
{
  "access_token": "eyJhbGciOiJIUzI1NiIs...",
  "refresh_token": "v1_refresh_newtoken789...",
  "expires_in": 3600
}
```

Error (401):

```
{ "error": "Invalid Refresh Token: Refresh Token Not Found" }
```

POST /auth/logout

Server-side logout acknowledgment. Client should discard tokens.

Field	Details
Auth required	🔒 Yes

Request body: None (empty `{}`)

Success (200):

```
{ "message": "Logged out" }
```

POST /auth/reset-password

Send a password reset email.

Field	Details
Auth required	No

Request body:

Field	Type	Required
`email`	string	✅

```
{ "email": "rahim@example.com" }
```

Success (200):

```
{ "message": "Password reset email sent" }
```

POST /auth/update-password

Set a new password for the currently authenticated user.

Field	Details
Auth required	🔒 Yes

Request body:

Field	Type	Required
`password`	string	✅

```
{ "password": "NewSecurePass456!" }
```

Success (200):

```
{ "message": "Password updated" }
```

Error (422):

```
{ "error": "Password should be at least 6 characters" }
```

---

2. User Profile

GET /profile

Get the current user's profile.

Field	Details
Auth required	🔒 Yes
Query params	None

Success (200):

```
{
  "user_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "display_name": "রহিম আহমেদ",
  "full_name": "Rahim Ahmed Khan",
  "avatar_url": "https://storage.example.com/avatars/rahim.jpg",
  "bio": "বই পড়তে ভালোবাসি",
  "preferred_language": "bn",
  "referral_code": "A1B2C3D4",
  "created_at": "2026-01-15T10:30:00.000Z"
}
```

Field	Type	Nullable	Description
`user_id`	uuid	No	User's unique ID
`display_name`	string	Yes	Public display name
`full_name`	string	Yes	Full legal name
`avatar_url`	string	Yes	Profile picture URL
`bio`	string	Yes	User bio text
`preferred_language`	string	Yes	`"bn"` or `"en"`
`referral_code`	string	Yes	User's referral code
`created_at`	ISO 8601	No	Account creation time

Error (404):

```
{ "error": "Profile not found" }
```

PATCH /profile

Update profile fields. Only send fields you want to change.

Field	Details
Auth required	🔒 Yes

Allowed fields:

Field	Type	Description
`display_name`	string	Public display name
`full_name`	string	Full name
`avatar_url`	string	Profile picture URL
`bio`	string	Bio text
`preferred_language`	string	`"bn"` or `"en"`

Request body:

```
{
  "display_name": "নতুন নাম",
  "preferred_language": "en"
}
```

Success (200):

```
{ "message": "Profile updated" }
```

GET /profile/roles

Get the authenticated user's assigned roles.

Field	Details
Auth required	🔒 Yes

Success (200):

```
{ "roles": ["user", "writer"] }
```

Field	Type	Description
`roles`	string[]	Array of role strings. Possible values: `"user"`, `"writer"`, `"narrator"`, `"publisher"`, `"admin"`, `"moderator"`

---

3. Books & Content Discovery

GET /books

List books with pagination and optional filters. **No auth required.**

Query params:

Param	Type	Default	Description
`limit`	int	20	Results per page (max 50)
`offset`	int	0	Pagination offset
`category_id`	uuid	—	Filter by category
`featured`	`"true"`	—	Featured books only
`free`	`"true"`	—	Free books only
`q`	string	—	Search by title (Bangla or English)

Success (200):

```
{
  "books": [
    {
      "id": "b1234567-89ab-cdef-0123-456789abcdef",
      "title": "চাঁদের পাহাড়",
      "title_en": "Chander Pahar",
      "slug": "chander-pahar",
      "cover_url": "https://storage.example.com/covers/chander-pahar.jpg",
      "rating": 4.5,
      "total_reads": 1200,
      "is_free": false,
      "is_featured": true,
      "is_bestseller": true,
      "is_new": false,
      "is_premium": true,
      "language": "Bangla",
      "published_date": "2025-06-15",
      "created_at": "2026-01-10T08:00:00.000Z",
      "author_id": "auth-uuid",
      "category_id": "cat-uuid",
      "authors": {
        "id": "auth-uuid",
        "name": "বিভূতিভূষণ বন্দ্যোপাধ্যায়",
        "avatar_url": "https://..."
      },
      "categories": {
        "id": "cat-uuid",
        "name": "উপন্যাস",
        "name_en": "Novel"
      }
    }
  ],
  "total": 156,
  "limit": 20,
  "offset": 0
}
```

Field	Type	Description
`books`	array	Array of book objects
`total`	int|null	Total matching books (for pagination)
`limit`	int	Applied limit
`offset`	int	Applied offset

Each book object:

Field	Type	Description
`id`	uuid	Book unique ID
`title`	string	Bangla title
`title_en`	string|null	English title
`slug`	string	URL-friendly slug
`cover_url`	string|null	Cover image URL
`rating`	float|null	Average rating (0–5)
`total_reads`	int|null	Total read count
`is_free`	bool	Whether the book is free
`is_featured`	bool	Featured flag
`is_bestseller`	bool	Bestseller flag
`is_new`	bool	Recently published
`is_premium`	bool	Premium content flag
`language`	string	Book language
`published_date`	string|null	Publication date
`authors`	object|null	Nested author `{id, name, avatar_url}`
`categories`	object|null	Nested category `{id, name, name_en}`

GET /books/{id_or_slug}

Get full book details including all available formats. **No auth required.**

Field	Details
Path params	`id_or_slug` — UUID or slug string

Success (200):

```
{
  "id": "b1234567-89ab-cdef-0123-456789abcdef",
  "title": "চাঁদের পাহাড়",
  "title_en": "Chander Pahar",
  "slug": "chander-pahar",
  "description": "A classic adventure novel...",
  "description_bn": "একটি ক্লাসিক অ্যাডভেঞ্চার উপন্যাস...",
  "cover_url": "https://...",
  "rating": 4.5,
  "reviews_count": 15,
  "total_reads": 1200,
  "is_free": false,
  "is_featured": true,
  "is_bestseller": true,
  "is_new": false,
  "is_premium": true,
  "language": "Bangla",
  "published_date": "2025-06-15",
  "tags": ["adventure", "classic", "bangla"],
  "coin_price": 50,
  "submission_status": "approved",
  "created_at": "2026-01-10T08:00:00.000Z",
  "authors": {
    "id": "auth-uuid",
    "name": "বিভূতিভূষণ বন্দ্যোপাধ্যায়",
    "name_en": "Bibhutibhushan Bandyopadhyay",
    "avatar_url": "https://...",
    "bio": "বিখ্যাত বাংলা ঔপন্যাসিক..."
  },
  "categories": {
    "id": "cat-uuid",
    "name": "উপন্যাস",
    "name_en": "Novel",
    "icon": "BookOpen",
    "color": "from-amber-50 to-orange-50"
  },
  "formats": [
    {
      "id": "fmt-uuid-1",
      "format": "ebook",
      "price": 90,
      "original_price": 120,
      "discount": 25,
      "coin_price": 50,
      "duration": null,
      "pages": 320,
      "file_size": "2.5 MB",
      "in_stock": null,
      "stock_count": null,
      "is_available": true,
      "preview_percentage": 15,
      "preview_chapters": 2,
      "narrator_id": null,
      "narrators": null
    },
    {
      "id": "fmt-uuid-2",
      "format": "audiobook",
      "price": 150,
      "original_price": null,
      "discount": null,
      "coin_price": 80,
      "duration": "5:30:00",
      "pages": null,
      "file_size": null,
      "in_stock": null,
      "stock_count": null,
      "is_available": true,
      "preview_percentage": 5,
      "preview_chapters": null,
      "narrator_id": "narr-uuid",
      "narrators": {
        "id": "narr-uuid",
```

```
          "name": "ফিউরেল্লা নূর পায়েল",
          "avatar_url": "https://..."
        }
      },
      {
        "id": "fmt-uuid-3",
        "format": "hardcopy",
        "price": 350,
        "original_price": 450,
        "discount": 22,
        "coin_price": null,
        "duration": null,
        "pages": 320,
        "file_size": null,
        "in_stock": true,
        "stock_count": 45,
        "is_available": true,
        "preview_percentage": null,
        "preview_chapters": null,
        "narrator_id": null,
        "narrators": null
      }
    ]
  }
```

Format object fields:

Field	Type	Description
`id`	uuid	Format record ID
`format`	string	`"ebook"`, `"audiobook"`, or `"hardcopy"`
`price`	float|null	Price in BDT
`original_price`	float|null	Original price before discount
`discount`	float|null	Discount percentage
`coin_price`	int|null	Price in coins (for coin unlock)
`duration`	string|null	Audiobook duration (HH:MM:SS)
`pages`	int|null	Page count for ebook/hardcopy
`file_size`	string|null	File size string
`in_stock`	bool|null	Hardcopy stock status
`stock_count`	int|null	Available stock quantity
`is_available`	bool	Whether this format is active
`preview_percentage`	int|null	Preview % allowed (e.g. 15 = 15%)
`preview_chapters`	int|null	Number of free preview chapters
`narrator_id`	uuid|null	Narrator ID (audiobook only)
`narrators`	object|null	Nested `{id, name, avatar_url}`

Error (404):

```
{ "error": "Book not found" }
```

GET /categories

List all active categories. **No auth required.**

Success (200):

```
{
  "categories": [
    {
      "id": "cat-uuid",
      "name": "উপন্যাস",
      "name_bn": "উপন্যাস",
      "name_en": "Novel",
      "icon": "BookOpen",
      "color": "from-amber-50 to-orange-50",
      "slug": "novel",
      "is_featured": true,
      "is_trending": false,
      "priority": 1
    }
  ]
}
```

Field	Type	Description
`id`	uuid	Category ID
`name`	string	Primary name
`name_bn`	string|null	Bangla name
`name_en`	string|null	English name
`icon`	string|null	Lucide icon name
`color`	string|null	Tailwind gradient classes
`slug`	string|null	URL slug
`is_featured`	bool	Featured on homepage
`is_trending`	bool	Currently trending
`priority`	int	Sort order (lower = first)

GET /authors

List authors with pagination. **No auth required.**

Query params:

Param	Type	Default	Description
`limit`	int	20	Max 50
`offset`	int	0	Pagination offset

Success (200):

```
{
  "authors": [
    {
      "id": "auth-uuid",
      "name": "বিভূতিভূষণ বন্দ্যোপাধ্যায়",
      "name_en": "Bibhutibhushan Bandyopadhyay",
      "avatar_url": "https://...",
      "bio": "বিখ্যাত বাংলা ঔপন্যাসিক ও ছোটগল্পকার...",
      "genre": "Adventure, Fiction",
      "is_featured": true,
      "is_trending": false,
      "priority": 1
    }
  ],
  "total": 42,
  "limit": 20,
  "offset": 0
}
```

Field	Type	Description
`id`	uuid	Author ID
`name`	string	Bangla name
`name_en`	string|null	English name
`avatar_url`	string|null	Photo URL
`bio`	string|null	Biography text
`genre`	string|null	Genre specialization
`is_featured`	bool	Featured author
`is_trending`	bool	Currently trending
`priority`	int	Sort order

GET /authors/{id}

Get a single author's details. **No auth required.**

Field	Details
Path params	`id` — author UUID

Success (200):

```
{
  "id": "auth-uuid",
  "name": "বিভূতিভূষণ বন্দ্যোপাধ্যায়",
  "name_en": "Bibhutibhushan Bandyopadhyay",
  "avatar_url": "https://...",
  "bio": "বিখ্যাত বাংলা ঔপন্যাসিক...",
  "genre": "Adventure, Fiction",
  "is_featured": true,
  "is_trending": false
}
```

Error (404):

```
{ "error": "Author not found" }
```

GET /narrators

List all active narrators. **No auth required.**

Success (200):

```
{
  "narrators": [
    {
      "id": "narr-uuid",
      "name": "ফিউরেল্লা নূর পায়েল",
      "name_en": "Fiurella Noor Payel",
      "avatar_url": "https://...",
      "bio": "পেশাদার অডিওবুক বর্ণনাকারী...",
      "specialty": "Fiction, Drama",
      "rating": 4.8,
      "is_featured": true,
      "is_trending": false
    }
  ]
}
```

Field	Type	Description
`id`	uuid	Narrator ID
`name`	string	Bangla name
`name_en`	string|null	English name
`avatar_url`	string|null	Photo URL
`bio`	string|null	Biography
`specialty`	string|null	Genre specialty
`rating`	float|null	Average rating (0–5)
`is_featured`	bool	Featured narrator
`is_trending`	bool	Trending

GET /publishers

List all active publishers. **No auth required.**

Success (200):

```
{
  "publishers": [
    {
      "id": "pub-uuid",
      "name": "আনন্দ পাবলিশার্স",
      "name_en": "Ananda Publishers",
      "logo_url": "https://...",
      "description": "বাংলা ভাষার অন্যতম শীর্ষ প্রকাশনা সংস্থা...",
      "is_verified": true,
      "is_featured": true
    }
  ]
}
```

Field	Type	Description
`id`	uuid	Publisher ID
`name`	string	Bangla name
`name_en`	string|null	English name
`logo_url`	string|null	Logo URL
`description`	string|null	Description
`is_verified`	bool	Verified publisher
`is_featured`	bool	Featured

GET /search

Search books by title. **No auth required.**

Query params:

Param	Type	Required	Description
`q`	string	✅	Search query, min 2 characters

Success (200):

```
{
  "results": [
    {
      "id": "book-uuid",
      "title": "চাঁদের পাহাড়",
      "title_en": "Chander Pahar",
      "slug": "chander-pahar",
      "cover_url": "https://...",
      "rating": 4.5,
      "is_free": false,
      "authors": {
        "name": "বিভূতিভূষণ বন্দ্যোপাধ্যায়"
      }
    }
  ]
}
```

Error (400):

```
{ "error": "Search query too short (min 2 chars)" }
```

GET /homepage

Fetch all homepage sections in a single call. **No auth required.** Recommended for the app home screen.

Success (200):

```
{
  "featured": [
    { "id": "uuid", "title": "চাঁদের পাহাড়", "slug": "chander-pahar", "cover_url": "https://...", "rating": 4.5, "authors": {
"name": "বিভূতিভূষণ" } }
  ],
  "trending": [
    { "id": "uuid", "title": "পথের পাঁচালী", "slug": "pather-panchali", "cover_url": "https://...", "rating": 4.7, "total_read
s": 5200, "authors": { "name": "বিভূতিভূষণ" } }
  ],
  "free": [
    { "id": "uuid", "title": "গীতাঞ্জলি", "slug": "gitanjali", "cover_url": "https://...", "rating": 4.9, "authors": { "name":
"রবীন্দ্রনাথ" } }
  ],
  "new": [
    { "id": "uuid", "title": "নতুন বই", "slug": "notun-boi", "cover_url": "https://...", "rating": 4.0, "authors": { "name":
"নতুন লেখক" } }
  ]
}
```

Each section is an array of up to 10 books. Each book has: `id`, `title`, `slug`, `cover_url`, `rating`, `authors.name`. The `trending` section also includes `total_reads`.

---

4. Audiobook Tracks

GET /books/{book_id}/tracks

List audiobook tracks for a book. **No auth required.**

Field	Details
Path params	`book_id` — UUID

Success (200):

```json
{
  "tracks": [
    {
      "id": "track-uuid-1",
      "track_number": 1,
      "title": "অধ্যায় ১ - শুরু",
      "duration": "12:30",
      "is_preview": true,
      "media_type": "audio",
      "chapter_price": null,
      "status": "active"
    },
    {
      "id": "track-uuid-2",
      "track_number": 2,
      "title": "অধ্যায় ২ - যাত্রা",
      "duration": "15:45",
      "is_preview": false,
      "media_type": "audio",
      "chapter_price": 10,
      "status": "active"
    }
  ]
}
```

Field	Type	Description
`id`	uuid	Track ID
`track_number`	int	Sequential track number
`title`	string	Chapter/track title
`duration`	string|null	Duration string (MM:SS or HH:MM:SS)
`is_preview`	bool	Whether marked as preview
`media_type`	string	`"audio"` or `"video"`
`chapter_price`	int|null	Per-chapter coin price
`status`	string	Track status

Returns `{ "tracks": [] }` if no audiobook format exists.

---

5. Access Control

POST /access/check

Check if user has access to a specific book format. 🔒 **Auth required.**

Request body:

Field	Type	Required	Description
`book_id`	uuid	✅	Book ID
`format`	string	✅	`"ebook"`, `"audiobook"`, or `"hardcopy"`

```json
{ "book_id": "book-uuid", "format": "ebook" }
```

Success (200):

```
{
  "has_access": true,
  "access_method": "purchase",
  "is_free": false,
  "has_subscription": false,
  "has_purchase": true,
  "has_unlock": false
}
```

Response depends on the `check_hybrid_access` database function. Key fields:

Field	Type	Description
`has_access`	bool	Whether user can access full content
`access_method`	string	How access was granted: `"purchase"`, `"subscription"`, `"coin_unlock"`, `"free"`, `"none"`

GET /access/preview-eligibility

Check preview availability for any book/format. **No auth required.** Use this to configure preview UI.

Query params:

Param	Type	Default	Description
`book_id`	uuid	—	✅ Required
`format`	string	`"ebook"`	`"ebook"` or `"audiobook"`

Success (200):

```
{
  "is_free": false,
  "preview_percentage": 15,
  "preview_chapters": 2,
  "price": 90,
  "guest_preview_allowed": true
}
```

Field	Type	Description
`is_free`	bool	Book is completely free
`preview_percentage`	int	Percentage of content available as preview
`preview_chapters`	int	Number of free chapters
`price`	float	Price in BDT
`guest_preview_allowed`	bool	Always `true` — guests can preview

6. Secure Content URLs

POST /content/ebook-url

Get a time-limited signed URL for full ebook file access. 🔒 **Auth required + purchase/unlock.**

Request body:

Field	Type	Required
`book_id`	uuid	✅

```
{ "book_id": "book-uuid" }
```

Success (200):

```
{
  "signed_url": "https://storage.example.com/ebooks/book.pdf?token=abc123&expires=1712345678",
  "mime_type": "application/pdf",
  "expires_in": 300
}
```

Field	Type	Description
`signed_url`	string	Time-limited download URL
`mime_type`	string	File MIME type
`expires_in`	int	URL validity in seconds

Error (401):

```
{ "error": "Authentication required" }
```

Error (500):

```
{ "error": "Failed to get secure URL" }
```

POST /content/audio-url

Get a signed URL for a specific audio track. **Works for both guests (preview) and authenticated users (full access).**

Request body:

Field	Type	Required	Description
`book_id`	uuid	✅	Book ID
`track_number`	int	❌	Track to fetch (default: 1)

```
{ "book_id": "book-uuid", "track_number": 1 }
```

Success (200):

```
{
  "signed_url": "https://storage.example.com/audio/track1.mp3?token=xyz&expires=1712345678",
  "expires_in": 300
}
```

Note: Guest users receive the same URL but the Flutter app must enforce the preview duration limit client-side (using `preview_percentage` from `/access/preview-eligibility`).

POST /content/batch-audio-urls

Get signed URLs for all tracks at once. 🔒 **Auth required.**

Request body:

Field	Type	Required
`book_id`	uuid	✅

```
{ "book_id": "book-uuid" }
```

Success (200):

```
{
  "urls": {
    "1": { "signed_url": "https://...", "expires_in": 300 },
    "2": { "signed_url": "https://...", "expires_in": 300 },
    "3": { "signed_url": "https://...", "expires_in": 300 }
  },
  "full_access": true
}
```

---

7. Reading & Listening Progress

GET /progress/reading

Get reading progress for a specific book. 🔒 **Auth required.**

Query params:

Param	Type	Required
`book_id`	uuid	✅

Success (200):

```
{
  "id": "progress-uuid",
  "user_id": "user-uuid",
  "book_id": "book-uuid",
  "current_page": 45,
  "total_pages": 320,
  "percentage": 14,
  "last_read_at": "2026-04-05T12:30:00.000Z",
  "created_at": "2026-04-01T10:00:00.000Z"
}
```

Returns default if no progress exists:

```
{ "current_page": 0, "total_pages": 0, "percentage": 0 }
```

Field	Type	Description
`current_page`	int	Last read page number
`total_pages`	int	Total pages in the book
`percentage`	int	Read percentage (0–100)
`last_read_at`	ISO 8601	Timestamp of last reading session

PUT /progress/reading

Save or update reading progress. 🔒 **Auth required.**

Request body:

Field	Type	Required	Description
`book_id`	uuid	✅	Book ID
`current_page`	int	✅	Current page number
`total_pages`	int	✅	Total pages

```
{
  "book_id": "book-uuid",
  "current_page": 78,
  "total_pages": 320
}
```

Success (200):

```
{ "message": "Progress saved", "percentage": 24 }
```

GET /progress/listening

Get listening progress for a specific audiobook. 🔒 **Auth required.**

Query params:

Param	Type	Required
`book_id`	uuid	✅

Success (200):

```
{
  "id": "progress-uuid",
  "user_id": "user-uuid",
  "book_id": "book-uuid",
  "current_track": 3,
  "position_seconds": 180,
  "total_seconds": 750,
  "last_listened_at": "2026-04-05T14:00:00.000Z"
}
```

Returns default if no progress exists:

```
{ "current_track": 1, "position_seconds": 0 }
```

Field	Type	Description
`current_track`	int	Current track number
`position_seconds`	int	Playback position in seconds within current track
`total_seconds`	int	Total duration in seconds of current track
`last_listened_at`	ISO 8601	Last listening timestamp

PUT /progress/listening

Save or update listening progress. 🔒 **Auth required.**

Request body:

Field	Type	Required	Description
`book_id`	uuid	✅	Book ID
`track_number`	int	❌	Current track (default: 1)
`position_seconds`	int	❌	Playback position in seconds
`total_seconds`	int	❌	Total track duration in seconds

```
{
  "book_id": "book-uuid",
  "track_number": 3,
  "position_seconds": 245,
  "total_seconds": 750
}
```

Success (200):

```
{ "message": "Listening progress saved" }
```

---

8. Bookmarks

GET /bookmarks

Get all bookmarked books. 🔒 **Auth required.**

Success (200):

```
{
  "bookmarks": [
    {
      "id": "bookmark-uuid",
      "book_id": "book-uuid",
      "created_at": "2026-04-03T10:00:00.000Z",
      "books": {
        "id": "book-uuid",
        "title": "চাঁদের পাহাড়",
        "cover_url": "https://...",
        "slug": "chander-pahar"
      }
    }
  ]
}
```

POST /bookmarks

Add a book to bookmarks. 🔒 **Auth required.**

Request body:

Field	Type	Required
`book_id`	uuid	✅

```
{ "book_id": "book-uuid" }
```

Success (201):

```
{ "message": "Bookmarked" }
```

DELETE /bookmarks/{book_id}

Remove a bookmark. 🔒 **Auth required.**

Field	Details
Path params	`book_id` — UUID of the book

Success (200):

```
{ "message": "Bookmark removed" }
```

---

9. Reviews & Comments

GET /books/{book_id}/reviews

Get book reviews. **No auth required.**

Success (200):

```
{
  "reviews": [
    {
      "id": "review-uuid",
      "rating": 5,
      "comment": "অসাধারণ বই! সবাইকে পড়তে বলছি।",
      "created_at": "2026-04-01T15:00:00.000Z",
      "user_id": "user-uuid",
      "profiles": {
        "display_name": "রহিম আহমেদ",
        "avatar_url": "https://..."
      }
    }
  ]
}
```

POST /reviews

Submit a review/rating. 🔒 **Auth required.**

Request body:

Field	Type	Required	Description
`book_id`	uuid	✅	Book ID
`rating`	int	✅	Rating 1–5
`comment`	string	❌	Review text

```
{
  "book_id": "book-uuid",
  "rating": 5,
  "comment": "অসাধারণ বই!"
}
```

Success (200): Returns the review data from the database function.

GET /books/{book_id}/comments

Get book comments (threaded). **No auth required.**

Success (200):

```
{
  "comments": [
    {
      "id": "comment-uuid",
      "comment": "এই বইটা কি মোবাইলে পড়া যায়?",
      "created_at": "2026-04-02T08:00:00.000Z",
      "user_id": "user-uuid",
      "parent_id": null,
      "profiles": {
        "display_name": "করিম",
        "avatar_url": "https://..."
      }
    },
    {
      "id": "reply-uuid",
      "comment": "হ্যাঁ, BoiAro অ্যাপে পড়তে পারবেন!",
      "created_at": "2026-04-02T09:00:00.000Z",
      "user_id": "other-uuid",
      "parent_id": "comment-uuid",
      "profiles": {
        "display_name": "জাহিদ",
        "avatar_url": null
      }
    }
  ]
}
```

Field	Type	Description
`parent_id`	uuid|null	`null` = top-level comment, uuid = reply to that comment

---

POST /comments

Post a comment or reply. 🔒 **Auth required.**

Request body:

Field	Type	Required	Description
`book_id`	uuid	✅	Book ID
`comment`	string	✅	Comment text
`parent_id`	uuid	❌	Parent comment ID for replies

```
{
  "book_id": "book-uuid",
  "comment": "দারুণ বই!",
  "parent_id": null
}
```

Success (201):

```
{
  "id": "new-comment-uuid",
  "comment": "দারুণ বই!",
  "created_at": "2026-04-05T16:00:00.000Z"
}
```

---

10. Orders & Payments

POST /orders

Create a new order. 🔒 **Auth required.**

Request body:

Field	Type	Required	Description
`items`	array	✅	Array of items to order
`items[].book_id`	uuid	✅	Book ID
`items[].format`	string	✅	`"ebook"`, `"audiobook"`, or `"hardcopy"`
`items[].quantity`	int	❌	Quantity (default: 1)
`shipping_address`	object	❌	Shipping info (for hardcopy)
`payment_method`	string	❌	`"online"` (default) or `"cod"`

```
{
  "items": [
    { "book_id": "book-uuid-1", "format": "ebook", "quantity": 1 },
    { "book_id": "book-uuid-2", "format": "hardcopy", "quantity": 2 }
  ],
  "shipping_address": {
    "name": "রহিম আহমেদ",
    "address": "৫৩ মিরপুর রোড, ঢাকা",
    "phone": "01712345678"
  },
  "payment_method": "online"
}
```

Success (201):

```
{
  "order": {
    "id": "order-uuid",
    "order_number": "BOI-20260405-0001",
    "total_amount": 790,
    "status": "pending"
  }
}
```

Error (400):

```
{ "error": "items required" }
```

```
{ "error": "Format not found: book-uuid/audiobook" }
```

GET /orders

Get order history. 🔒 **Auth required.**

Success (200):

```json
{
  "orders": [
    {
      "id": "order-uuid",
      "order_number": "BOI-20260405-0001",
      "total_amount": 790,
      "status": "confirmed",
      "payment_method": "online",
      "created_at": "2026-04-05T10:00:00.000Z"
    },
    {
      "id": "order-uuid-2",
      "order_number": "BOI-20260404-0003",
      "total_amount": 90,
      "status": "pending",
      "payment_method": "online",
      "created_at": "2026-04-04T14:00:00.000Z"
    }
  ]
}
```

Field	Type	Description
`id`	uuid	Order ID
`order_number`	string	Human-readable order number
`total_amount`	float	Total in BDT
`status`	string	`"pending"`, `"awaiting_payment"`, `"confirmed"`, `"paid"`, `"processing"`, `"shipped"`, `"delivered"`, `"completed"`, `"cancelled"`, `"payment_failed"`
`payment_method`	string	`"online"` or `"cod"`
`created_at`	ISO 8601	Order creation time

GET /orders/{order_id}

Get full order details with items. 🔒 **Auth required.**

Field	Details
Path params	`order_id` — UUID

Success (200):

```
{
  "id": "order-uuid",
  "order_number": "BOI-20260405-0001",
  "user_id": "user-uuid",
  "total_amount": 790,
  "status": "confirmed",
  "payment_method": "online",
  "shipping_name": "রহিম আহমেদ",
  "shipping_address": "৫৩ মিরপুর রোড, ঢাকা",
  "shipping_phone": "01712345678",
  "shipping_city": "Dhaka",
  "shipping_zip": "1216",
  "created_at": "2026-04-05T10:00:00.000Z",
  "updated_at": "2026-04-05T10:05:00.000Z",
  "order_items": [
    {
      "id": "item-uuid",
      "book_id": "book-uuid",
      "format": "ebook",
      "quantity": 1,
      "unit_price": 90,
      "total_price": 90,
      "books": {
        "id": "book-uuid",
        "title": "চাঁদের পাহাড়",
        "cover_url": "https://...",
        "slug": "chander-pahar"
      }
    }
  ]
}
```

Error (404):

```
{ "error": "Order not found" }
```

POST /payments/initiate

Initiate SSLCommerz payment for an order. 🔒 **Auth required.**

Request body:

Field	Type	Required
`order_id`	uuid	✅

```
{ "order_id": "order-uuid" }
```

Success (200):

```
{
  "success": true,
  "gateway_url": "https://securepay.sslcommerz.com/gwprocess/v4?...",
  "session_key": "SSLsession123..."
}
```

Field	Type	Description
`gateway_url`	string	Redirect user to this URL to complete payment
`session_key`	string	SSLCommerz session key

Flutter integration: Open `gateway_url` in a WebView. After payment, user is redirected back to the app's callback URL with `?status=success|failed|cancelled&order_id=...`.

Error (500):

```
{ "error": "Payment initiation failed" }
```

POST /payments/demo

Demo/test payment — instantly marks order as paid. 🔒 **Auth required. Development only.**

Request body:

```
{ "order_id": "order-uuid" }
```

Success (200):

```
{ "message": "Payment completed (demo)" }
```

---

11. Wallet & Coins

GET /wallet

Get coin balance. 🔒 **Auth required.**

Success (200):

```
{
  "balance": 250,
  "total_earned": 500,
  "total_spent": 250
}
```

Field	Type	Description
`balance`	int	Current coin balance
`total_earned`	int	Lifetime coins earned
`total_spent`	int	Lifetime coins spent

GET /wallet/transactions

Get coin transaction history. 🔒 **Auth required.**

Query params:

Param	Type	Default	Description
`limit`	int	50	Max 100

Success (200):

```
{
  "transactions": [
    {
      "id": "tx-uuid-1",
      "amount": 10,
      "type": "earn",
      "description": "Daily login reward",
      "source": "daily_reward",
      "created_at": "2026-04-05T06:00:00.000Z",
      "expires_at": "2026-07-05T06:00:00.000Z"
    },
    {
      "id": "tx-uuid-2",
      "amount": -50,
      "type": "spend",
      "description": "Content unlock - ebook",
      "source": "content_unlock",
      "created_at": "2026-04-04T15:00:00.000Z",
      "expires_at": null
    }
  ]
}
```

Field	Type	Description
`id`	uuid	Transaction ID
`amount`	int	Positive = earned, Negative = spent
`type`	string	`"earn"` or `"spend"`
`description`	string	Human-readable description
`source`	string|null	Source: `"daily_reward"`, `"ad_reward"`, `"content_unlock"`, `"purchase"`, `"referral"`, etc.
`created_at`	ISO 8601	Transaction time
`expires_at`	ISO 8601|null	Coin expiry (null = never)

POST /wallet/claim-daily

Claim daily login reward coins. 🔒 **Auth required.**

Request body: None (empty `{}`)

Success (200): Returns reward data from the `claim_daily_login_reward` database function.

```
{
  "success": true,
  "coins_awarded": 5,
  "streak_day": 3,
  "message": "Day 3 reward claimed!"
}
```

POST /wallet/claim-ad

Claim ad watch reward. 🔒 **Auth required.**

Request body:

Field	Type	Required	Description
`placement`	string	❌	Ad placement key (default: `"general"`)

```
{ "placement": "general" }
```

Success (200): Returns reward data from the `claim_ad_reward` database function.

POST /wallet/unlock

Unlock content using coins. 🔒 **Auth required.**

Request body:

Field	Type	Required	Description
`book_id`	uuid	✅	Book to unlock
`format`	string	✅	`"ebook"` or `"audiobook"`
`coin_cost`	int	✅	Coins to spend (from book format's `coin_price`)

```
{
  "book_id": "book-uuid",
  "format": "ebook",
  "coin_cost": 50
}
```

Success (200):

```
{ "message": "Unlocked successfully" }
```

Already unlocked:

```
{ "message": "Already unlocked", "already_unlocked": true }
```

Error (400):

```
{ "error": "Coin deduction failed: insufficient balance" }
```

GET /coin-packages

List available coin purchase packages. **No auth required.**

Success (200):

```json
{
  "packages": [
    {
      "id": "pkg-uuid-1",
      "name": "স্টার্টার",
      "coins": 50,
      "bonus_coins": 0,
      "price": 49,
      "is_featured": false,
      "sort_order": 1
    },
    {
      "id": "pkg-uuid-2",
      "name": "পপুলার",
      "coins": 200,
      "bonus_coins": 30,
      "price": 149,
      "is_featured": true,
      "sort_order": 2
    }
  ]
}
```

Field	Type	Description
`id`	uuid	Package ID
`name`	string	Package name
`coins`	int	Base coins included
`bonus_coins`	int	Extra bonus coins
`price`	float	Price in BDT
`is_featured`	bool	Highlighted package
`sort_order`	int	Display order

---

12. Library

GET /library/purchases

Get user's purchased books. 🔒 **Auth required.**

Query params:

Param	Type	Description
`format`	string	Filter: `"ebook"`, `"audiobook"`, or `"hardcopy"`

Success (200):

```
{
  "purchases": [
    {
      "id": "purchase-uuid",
      "book_id": "book-uuid",
      "format": "ebook",
      "status": "active",
      "created_at": "2026-04-01T10:00:00.000Z",
      "books": {
        "id": "book-uuid",
        "title": "চাঁদের পাহাড়",
        "cover_url": "https://...",
        "slug": "chander-pahar",
        "authors": { "name": "বিভূতিভূষণ" }
      }
    }
  ]
}
```

GET /library/unlocks

Get books unlocked with coins. 🔒 **Auth required.**

Success (200):

```
{
  "unlocks": [
    {
      "id": "unlock-uuid",
      "book_id": "book-uuid",
      "format": "ebook",
      "unlock_method": "coin",
      "created_at": "2026-04-02T12:00:00.000Z",
      "books": {
        "id": "book-uuid",
        "title": "পথের পাঁচালী",
        "cover_url": "https://...",
        "slug": "pather-panchali"
      }
    }
  ]
}
```

GET /library/continue-reading

Get books with in-progress reading. 🔒 **Auth required.**

Success (200):

```
{
  "items": [
    {
      "book_id": "book-uuid",
      "current_page": 78,
      "total_pages": 320,
      "percentage": 24,
      "last_read_at": "2026-04-05T12:30:00.000Z",
      "books": {
        "id": "book-uuid",
        "title": "চাঁদের পাহাড়",
        "cover_url": "https://...",
        "slug": "chander-pahar",
        "authors": { "name": "বিভূতিভূষণ" }
      }
    }
  ]
}
```

Returns books where `0 < percentage < 100`, sorted by most recently read. Max 10 items.

GET /library/continue-listening

Get audiobooks with in-progress listening. 🔒 **Auth required.**

Success (200):

```
{
  "items": [
    {
      "book_id": "book-uuid",
      "current_track": 3,
      "position_seconds": 245,
      "last_listened_at": "2026-04-05T14:00:00.000Z",
      "books": {
        "id": "book-uuid",
        "title": "পথের পাঁচালী",
        "cover_url": "https://...",
        "slug": "pather-panchali"
      }
    }
  ]
}
```

Max 10 items, sorted by most recently listened.

---

13. Subscriptions

GET /subscriptions/plans

List active subscription plans. **No auth required.**

Success (200):

```
{
  "plans": [
    {
      "id": "plan-uuid",
      "name": "প্রিমিয়াম মাসিক",
      "description": "সকল ইবুক ও অডিওবুকে সীমাহীন প্রবেশাধিকার",
      "price": 199,
      "duration_days": 30,
      "access_type": "all",
      "features": ["unlimited_ebooks", "unlimited_audiobooks", "no_ads"],
      "is_active": true
    }
  ]
}
```

Field	Type	Description
`id`	uuid	Plan ID
`name`	string	Plan name
`description`	string|null	Plan description
`price`	float	Price in BDT
`duration_days`	int	Subscription duration
`access_type`	string	Content access level
`features`	string[]|null	Feature list
`is_active`	bool	Plan availability

GET /subscriptions/my

Get current user's subscriptions. 🔒 **Auth required.**

Success (200):

```
{
  "subscriptions": [
    {
      "id": "sub-uuid",
      "plan_id": "plan-uuid",
      "status": "active",
      "start_date": "2026-04-01",
      "end_date": "2026-05-01",
      "subscription_plans": {
        "name": "প্রিমিয়াম মাসিক",
        "access_type": "all"
      }
    }
  ]
}
```

Field	Type	Description
`status`	string	`"active"`, `"expired"`, `"cancelled"`
`start_date`	date	Subscription start
`end_date`	date	Subscription end

---

14. Notifications

GET /notifications

Get user notifications. 🔒 **Auth required.** Returns most recent 50.

Success (200):

```
{
  "notifications": [
    {
      "id": "notif-uuid",
      "title": "নতুন বই প্রকাশিত!",
      "message": "আপনার পছন্দের লেখকের নতুন বই এসেছে।",
      "type": "new_book",
      "is_read": false,
      "created_at": "2026-04-05T08:00:00.000Z"
    }
  ]
}
```

Field	Type	Description
`id`	uuid	Notification ID
`title`	string	Notification title
`message`	string	Notification body
`type`	string	Type: `"new_book"`, `"order_update"`, `"reward"`, `"system"`, etc.
`is_read`	bool	Read status
`created_at`	ISO 8601	Notification time

POST /notifications/read

Mark notifications as read. 🔒 **Auth required.**

Request body:

Field	Type	Required	Description
`ids`	uuid[]	❌	Specific notification IDs. If omitted/empty, marks ALL as read.

Mark specific:

```
{ "ids": ["notif-uuid-1", "notif-uuid-2"] }
```

Mark all:

```
{}
```

Success (200):

```
{ "message": "Marked as read" }
```

---

15. Integration Flows

Flow 1: Guest Browsing & Preview

```
1. GET /homepage                          → Home screen data
2. GET /categories                        → Category list
3. GET /books?category_id=xxx             → Browse category
4. GET /books/{slug}                      → Book detail page
5. GET /access/preview-eligibility?book_id=xxx&format=ebook  → Preview config
6. GET /books/{book_id}/tracks            → Audiobook track list
7. POST /content/audio-url                → Get preview audio (no auth)
   Body: { "book_id": "xxx", "track_number": 1 }
8. → User hits preview limit → Show "Sign in to continue" paywall
```

Flow 2: Authentication & Profile

```
1. POST /auth/signup                      → Create account
   Body: { "email": "...", "password": "...", "display_name": "..." }
2. → User verifies email via link
3. POST /auth/login                       → Get tokens
   Body: { "email": "...", "password": "..." }
4. GET /profile                           → Load profile
5. GET /profile/roles                     → Check roles
6. → Store access_token + refresh_token securely
7. → Before token expires: POST /auth/refresh
```

Flow 3: Purchase & Payment

```
1. POST /orders                           → Create order
   Body: { "items": [{ "book_id": "xxx", "format": "ebook" }] }
2. POST /payments/initiate                → Get payment URL
   Body: { "order_id": "<order_id from step 1>" }
3. → Open gateway_url in WebView
4. → User completes payment on SSLCommerz
5. → Redirect back to app with ?status=success&order_id=xxx
6. GET /orders/{order_id}                 → Verify order status
7. POST /access/check                     → Confirm access granted
   Body: { "book_id": "xxx", "format": "ebook" }
8. POST /content/ebook-url                → Get full content URL
```

Flow 4: Coin Unlock

```
1. GET /wallet                          → Check balance
2. GET /books/{slug}                    → Get coin_price from formats
3. POST /wallet/unlock                  → Unlock content
   Body: { "book_id": "xxx", "format": "ebook", "coin_cost": 50 }
4. POST /content/ebook-url              → Get full content URL
```

Flow 5: Reading Session

```
1. GET /progress/reading?book_id=xxx      → Resume position
2. POST /content/ebook-url                → Get signed URL
3. → User reads in app
4. PUT /progress/reading                  → Save progress periodically
   Body: { "book_id": "xxx", "current_page": 120, "total_pages": 320 }
```

Flow 6: Listening Session

```
1. GET /progress/listening?book_id=xxx    → Resume position
2. GET /books/{book_id}/tracks            → Track listing
3. POST /content/batch-audio-urls         → Get all track URLs
4. → User listens in app
5. PUT /progress/listening                → Save progress periodically
   Body: { "book_id": "xxx", "track_number": 3, "position_seconds": 245, "total_seconds": 750 }
```

16. Flutter Helper Class

```
import 'dart:convert';
import 'package:http/http.dart' as http;

class BoiAroApi {
  static const _baseUrl =
      'https://kxpqejmjfnzhqcefyued.supabase.co/functions/v1/mobile-api';
  static const _apiKey =
      'eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZiI6Imt4cHFlam1qZm56aHFjZWZ5dWVkIiwicm9sZSI6ImFub24i
LCJpYXQiOjE3NzQzMzA0NjUsImV4cCI6MjA4OTkwNjQ2NX0.PSM2xT9QPzJmBU5yP7uKnQxVAvbpevAGF8wFw43i9to';

  String? accessToken;
  String? refreshToken;

  Map<String, String> get _headers => {
        'Content-Type': 'application/json',
        'apikey': _apiKey,
        if (accessToken != null) 'Authorization': 'Bearer $accessToken',
      };

  Future<Map<String, dynamic>> _get(String path,
      [Map<String, String>? queryParams]) async {
    final uri = Uri.parse('$_baseUrl/$path')
        .replace(queryParameters: queryParams);
    final res = await http.get(uri, headers: _headers);
    return jsonDecode(res.body);
  }

  Future<Map<String, dynamic>> _post(String path,
      [Map<String, dynamic>? body]) async {
    final res = await http.post(
      Uri.parse('$_baseUrl/$path'),
      headers: _headers,
      body: body != null ? jsonEncode(body) : '{}',
    );
    return jsonDecode(res.body);
  }

  Future<Map<String, dynamic>> _patch(String path,
      Map<String, dynamic> body) async {
    final res = await http.patch(
      Uri.parse('$_baseUrl/$path'),
      headers: _headers,
      body: jsonEncode(body),
    );
    return jsonDecode(res.body);
  }

  Future<Map<String, dynamic>> _put(String path,
      Map<String, dynamic> body) async {
    final res = await http.put(
      Uri.parse('$_baseUrl/$path'),
      headers: _headers,
      body: jsonEncode(body),
    );
    return jsonDecode(res.body);
  }

  Future<Map<String, dynamic>> _delete(String path) async {
    final res = await http.delete(Uri.parse('$_baseUrl/$path'), headers: _headers);
    return jsonDecode(res.body);
  }

  // ─── Auth ───
  Future<Map<String, dynamic>> signup(
      String email, String password, String? displayName) =>
      _post('auth/signup', {
        'email': email, 'password': password,
        if (displayName != null) 'display_name': displayName,
```

```
    });

  Future<Map<String, dynamic>> login(String email, String password) async {
    final data = await _post('auth/login', {'email': email, 'password': password});
    if (data.containsKey('access_token')) {
      accessToken = data['access_token'];
      refreshToken = data['refresh_token'];
    }
    return data;
  }

  Future<Map<String, dynamic>> refresh() async {
    final data = await _post('auth/refresh', {'refresh_token': refreshToken});
    if (data.containsKey('access_token')) {
      accessToken = data['access_token'];
      refreshToken = data['refresh_token'];
    }
    return data;
  }

  Future<Map<String, dynamic>> logout() => _post('auth/logout');
  Future<Map<String, dynamic>> resetPassword(String email) =>
      _post('auth/reset-password', {'email': email});

  // ─── Profile ───
  Future<Map<String, dynamic>> getProfile() => _get('profile');
  Future<Map<String, dynamic>> updateProfile(Map<String, dynamic> updates) =>
      _patch('profile', updates);
  Future<Map<String, dynamic>> getRoles() => _get('profile/roles');

  // ─── Discovery ───
  Future<Map<String, dynamic>> getHomepage() => _get('homepage');
  Future<Map<String, dynamic>> getBooks({int limit = 20, int offset = 0,
      String? categoryId, bool? featured, bool? free, String? query}) =>
      _get('books', {
        'limit': '$limit', 'offset': '$offset',
        if (categoryId != null) 'category_id': categoryId,
        if (featured == true) 'featured': 'true',
        if (free == true) 'free': 'true',
        if (query != null) 'q': query,
      });
  Future<Map<String, dynamic>> getBook(String idOrSlug) =>
      _get('books/$idOrSlug');
  Future<Map<String, dynamic>> getCategories() => _get('categories');
  Future<Map<String, dynamic>> getAuthors({int limit = 20, int offset = 0}) =>
      _get('authors', {'limit': '$limit', 'offset': '$offset'});
  Future<Map<String, dynamic>> getAuthor(String id) => _get('authors/$id');
  Future<Map<String, dynamic>> getNarrators() => _get('narrators');
  Future<Map<String, dynamic>> getPublishers() => _get('publishers');
  Future<Map<String, dynamic>> search(String query) =>
      _get('search', {'q': query});

  // ─── Tracks ───
  Future<Map<String, dynamic>> getTracks(String bookId) =>
      _get('books/$bookId/tracks');

  // ─── Access ───
  Future<Map<String, dynamic>> checkAccess(String bookId, String format) =>
      _post('access/check', {'book_id': bookId, 'format': format});
  Future<Map<String, dynamic>> previewEligibility(String bookId,
      [String format = 'ebook']) =>
      _get('access/preview-eligibility',
          {'book_id': bookId, 'format': format});

  // ─── Content URLs ───
  Future<Map<String, dynamic>> getEbookUrl(String bookId) =>
      _post('content/ebook-url', {'book_id': bookId});
  Future<Map<String, dynamic>> getAudioUrl(String bookId,
      [int trackNumber = 1]) =>
      _post('content/audio-url',
          {'book_id': bookId, 'track_number': trackNumber});
  Future<Map<String, dynamic>> getBatchAudioUrls(String bookId) =>
      _post('content/batch-audio-urls', {'book_id': bookId});

  // ─── Progress ───
```

```
  Future<Map<String, dynamic>> getReadingProgress(String bookId) =>
      _get('progress/reading', {'book_id': bookId});
  Future<Map<String, dynamic>> saveReadingProgress(
      String bookId, int currentPage, int totalPages) =>
      _put('progress/reading', {
        'book_id': bookId,
        'current_page': currentPage,
        'total_pages': totalPages,
      });
  Future<Map<String, dynamic>> getListeningProgress(String bookId) =>
      _get('progress/listening', {'book_id': bookId});
  Future<Map<String, dynamic>> saveListeningProgress(
      String bookId, int track, int positionSec, int totalSec) =>
      _put('progress/listening', {
        'book_id': bookId,
        'track_number': track,
        'position_seconds': positionSec,
        'total_seconds': totalSec,
      });

  // ─── Bookmarks ───
  Future<Map<String, dynamic>> getBookmarks() => _get('bookmarks');
  Future<Map<String, dynamic>> addBookmark(String bookId) =>
      _post('bookmarks', {'book_id': bookId});
  Future<Map<String, dynamic>> removeBookmark(String bookId) =>
      _delete('bookmarks/$bookId');

  // ─── Reviews & Comments ───
  Future<Map<String, dynamic>> getReviews(String bookId) =>
      _get('books/$bookId/reviews');
  Future<Map<String, dynamic>> postReview(
      String bookId, int rating, [String? comment]) =>
      _post('reviews', {
        'book_id': bookId, 'rating': rating,
        if (comment != null) 'comment': comment,
      });
  Future<Map<String, dynamic>> getComments(String bookId) =>
      _get('books/$bookId/comments');
  Future<Map<String, dynamic>> postComment(
      String bookId, String comment, [String? parentId]) =>
      _post('comments', {
        'book_id': bookId, 'comment': comment,
        if (parentId != null) 'parent_id': parentId,
      });

  // ─── Orders ───
  Future<Map<String, dynamic>> createOrder(
      List<Map<String, dynamic>> items,
      {Map<String, dynamic>? shipping, String paymentMethod = 'online'}) =>
      _post('orders', {
        'items': items,
        if (shipping != null) 'shipping_address': shipping,
        'payment_method': paymentMethod,
      });
  Future<Map<String, dynamic>> getOrders() => _get('orders');
  Future<Map<String, dynamic>> getOrder(String orderId) =>
      _get('orders/$orderId');
  Future<Map<String, dynamic>> initiatePayment(String orderId) =>
      _post('payments/initiate', {'order_id': orderId});

  // ─── Wallet ───
  Future<Map<String, dynamic>> getWallet() => _get('wallet');
  Future<Map<String, dynamic>> getTransactions([int limit = 50]) =>
      _get('wallet/transactions', {'limit': '$limit'});
  Future<Map<String, dynamic>> claimDaily() => _post('wallet/claim-daily');
  Future<Map<String, dynamic>> claimAdReward([String placement = 'general']) =>
      _post('wallet/claim-ad', {'placement': placement});
  Future<Map<String, dynamic>> unlockContent(
      String bookId, String format, int coinCost) =>
      _post('wallet/unlock', {
        'book_id': bookId, 'format': format, 'coin_cost': coinCost,
      });
  Future<Map<String, dynamic>> getCoinPackages() => _get('coin-packages');

  // ─── Library ───
```

```
    Future<Map<String, dynamic>> getPurchases([String? format]) =>
        _get('library/purchases', {if (format != null) 'format': format});
    Future<Map<String, dynamic>> getUnlocks() => _get('library/unlocks');
    Future<Map<String, dynamic>> getContinueReading() =>
        _get('library/continue-reading');
    Future<Map<String, dynamic>> getContinueListening() =>
        _get('library/continue-listening');

    // ─── Subscriptions ───
    Future<Map<String, dynamic>> getPlans() => _get('subscriptions/plans');
    Future<Map<String, dynamic>> getMySubscriptions() =>
        _get('subscriptions/my');

    // ─── Notifications ───
    Future<Map<String, dynamic>> getNotifications() => _get('notifications');
    Future<Map<String, dynamic>> markRead([List<String>? ids]) =>
        _post('notifications/read', {if (ids != null) 'ids': ids});
  }
```

---

17. Important Notes for Flutter Developer

1. **Token Management:** Store `access_token` and `refresh_token` securely (e.g. `flutter_secure_storage`). Access tokens expire in ~1 hour. Call `/auth/refresh` proactively.
2. **Guest vs Auth:** Books, categories, authors, narrators, publishers, search, homepage, preview eligibility, audio preview URLs, coin packages, subscription plans, reviews, and comments all work **without authentication**.
3. **Preview Enforcement:** Audio preview duration is enforced **client-side**. Use `preview_percentage` from `/access/preview-eligibility` to calculate the cutoff time. Stop playback and show paywall when the user reaches the limit.
4. **apikey Header:** Include the `apikey` header in **every** request (both guest and authenticated).
5. **Pagination:** Use `limit` (max 50) and `offset`. Check `total` for calculating page count.
6. **Error Handling:** All errors return `{ "error": "message" }`. Check HTTP status code first, then parse the error message.
7. **Signed URLs Expire:** Content URLs from `/content/*` endpoints expire in ~5 minutes. Request new URLs as needed.
8. **No SDK Required:** This API is 100% standard REST. Any HTTP client works.
9. **Payment WebView:** For SSLCommerz, open `gateway_url` in a WebView. Handle the redirect callback URL to detect payment result.
10. **Image URLs:** `cover_url`, `avatar_url`, `logo_url` are full HTTPS URLs. Load them directly with `CachedNetworkImage` or similar.