
Git Bash Commands - II

1. Viewing File Content

Command	What it Does
<code>cat filename</code>	Displays the contents of a file in the terminal.

2. Writing Text to a File Using echo

Command	What it Does
<code>echo "text-content" > filename</code>	Writes text to a file. If the file does not exist, it will be created.
<code>echo "text" >> filename</code>	Appends text to an existing file without deleting previous content.

3. Writing Text Using cat

Command	What it Does
<code>cat > filename</code>	Creates a file and allows us to type text directly in the terminal.
Steps: <code>cat > file.txt</code> Type your text here Press Ctrl + D to save and exit	
<code>cat >> filename</code>	Adds text to an existing file without deleting previous content.
Steps: <code>cat >> file.txt</code> Type additional text Press Ctrl + D to save	

4. Copy Content from One File to Another

Command	What it Does
<code>cat file1.txt > file2.txt</code>	Copies the content of file1.txt into file2.txt.

5. Editing a File Using Nano Editor

Command	What it Does
<code>nano file.txt</code>	Opens the Nano text editor to create or edit a file.
Opens Steps in Nano Editor: <code>Save the file</code> <code>Ctrl + O</code> <code>Exit the editor</code> <code>Ctrl + X</code>	

Using Vi Editor

The **vi** editor (**v**isual editor) is a screen-oriented command-line text editor and the default editor for most Unix and Linux operating systems.

It is used to create, edit, and manage text files directly from the terminal/cli.

Modes of Operation

Vi operates primarily in two modes:

- **Command Mode:** This is the default mode when you open a file. Keystrokes are interpreted as commands for navigation, deletion, copying, and pasting, not as text input.
- **Insert Mode:** In this mode, characters typed are added directly to the text file. You enter this mode by pressing keys like **i** (insert at cursor) or **a** (append after cursor) while in command mode.

To switch back to Command Mode from Insert Mode, you must press the **Esc key**.

Case Sensitivity

vi is case-sensitive; commands typed in uppercase may have different effects than those in lowercase.

Vim

Vim ("**V**i **I**Mproved") is an enhanced version that builds upon Vi's core functionality with many additional features. Vim is the recommended choice for most users and is often the actual program run when you type vi in modern Linux distributions.

1. Check the default editor via Git

```
git var GIT_EDITOR
```

2. Set vi editor as the default editor for Git Bash

```
git config --global core.editor "vi"
```

3. Opening a File

```
vi filename.txt
```

Examples

```
vi file1.txt
```

```
vi program.java
```

If the file does not exist, `vi` will create it.

4. Enter Insert Mode (to type text)

Command	What it Does
<code>i</code>	Inserts text before the current cursor.
<code>I</code>	Inserts text at the beginning of line.

a	Insert text after the current cursor.
A	Insert text at the end of the current line.
o	Creates a new line for text entry below cursor location and switches to insert mode.
O	Creates a new line for text entry above cursor location and switches to insert mode.

To return to Normal Mode, press:

Esc

5. Save and Quit Commands

Press Esc first, then type : before typing the following commands:

Command	What it Does
:w	Save File
:q	Quit
:wq	Save and quit

<code>:x</code>	Save and quit
<code>:q!</code>	Quit without saving.

6. Delete Commands

Command	What it Does
<code>x</code>	Delete character
<code>dd</code>	Delete current line
<code>d\$</code>	Delete from cursor to end of line
<code>d0</code>	Delete from cursor to start of line
<code>:q!</code>	Quit without saving.

7. Copy and Paste Commands

Command	What it Does
y	Delete character
P	Delete current line
P	Delete from cursor to end of line
d0	Delete from cursor to start of line