

Table of Contents

- [1. <article>](#)
- [2. <section>](#)
- [3. <figure> y <figcaption>](#)
- [4. <input type="date">](#)
- [5. <details> y <summary>](#)

1. Tag: <article>

Use Case: Independent, self-contained content (blog post, comment). Should make sense if extracted from the site context.

Example Code

```
<article class="post">
  <h2>New Trends in Web Design</h2>
  <p>The use of Flexbox and Grid continues to increase...</p>
  <footer>Published on 2025-01-01</footer>
</article>
```

Browser Output

Nuevas Tendencias en Diseño Web

El uso de Flexbox y Grid sigue en aumento...

Publicado el 2025-01-01

W3C Documentation

[<article> Specification \(W3C\)](#)

2. Tag: <section>

Use Case: Groups logically related content within a document. It should generally have its own heading.

Example Code

```
<section id="about-us">
  <h2>About Us</h2>
  <p>We are an initiative dedicated to web education.</p>
</section>
```

Browser Output

Sobre Nosotros

Somos una iniciativa dedicada a la educación web.

W3C Documentation

[<section> Specification \(W3C\)](#)

3. Tags: <figure> and <figcaption>

Use Case: Used to mark content referenced from the main body, such as photos, diagrams, or code, and its caption or title (`figcaption`).

Example Code

```
<figure>
  
  <figcaption>Figure 1: Website Flowchart.</figcaption>
</figure>
```

Browser Output (The desired image would be in the image logo)




Diagrama de flujo

Figura 1: Diagrama de flujo del sitio web.

W3C Documentation

[<figure> Specification \(W3C\)](#)


4. Tag: <input type="date">

Use Case: Creates a form field that allows the user to select a date using a native browser visual selector (calendar).

Example Code

```
<label for="reservation-date">Select a date:</label>
<input type="date" id="reservation-date" name="reservation">
```

Browser Output



Selecciona una fecha: dd / mm / aaaa ☰

W3C Documentation

[<input type="date"> Specification \(W3C\)](#)

5. Tags: <details> and <summary>

Use Case: Allows creating an interactive disclosure widget where the user can open and close additional content (useful for FAQs).

Example Code

```
<details>
  <summary>See more about the activity</summary>
  <p>This activity is mandatory for the 1st trimester.</p>
</details>
```

Browser Output

► Ver más sobre la actividad

W3C Documentation

[<details> and <summary> Specification \(W3C\)](#)

© 2025/26 IES La Marisma. Markup Languages Project.