


# Colorize linux programs output



## Colorize linux program output

You can colorize linux bash shell or any linux program like **echo**, **sed**, **grep** and another with this simple steps:

1. You need type ASCII **ESC** character before your colorized text
2. **ESC** character has to be followed by **[**
3. After that you can write one or two numbers separated by **;**
  - First number is one of:
    - **color-mode**: It modifies the style of color NOT text. For example make the color bright or darker.
      - 0 - normal (default)
      - 1 - lighter than normal
      - 2 - darker than normal
    - **text-mode**: This mode is for modifying the style of text NOT color.
      - 3 - italic
      - 4 - underline
      - 5 - blinking (slow)
      - 6 - blinking (fast)
      - 7 - reverse
      - 8 - hide
      - 9 - cross-out
  - Second number is **color-code** separated by **;** from first number is **ANSI color code** . eg. 31 for red color, 34 for blue color for **3/4 bit ANSI color code** . Color is one of:
    - **foreground mode** - This mode is for colorizing the foreground.
    - **background mode** - This mode is for colorizing the background.

second number - **color-code** in step 3 is **3/4 bit** or **8 bit** or **24 bit** **ANSI color code**

4. Then you have to write `m` char
5. You can get back to standard output with `ESC[0m`

0 is appended if you omit it in step 5 - e.g. you can write `ESC[m` in bash

MyBlueLinux.com

ESC you can type escape character to your console or linux program with some of ASCII code.


Decimal	Octal	Hex	Binary	Value	Description	Carret notation	Escape sequence in bash or C
027	033	1B	0001 1011	ESC	escape	^[	\e

### 3/4bit ANSI Color

The below table shows a summary of 3/4 bit version of ANSI color.


color-mode	octal	hex	bash	description	example (ESC in octal)	NOTE	
	0	\033[0m	\x1b[0m	\e[0m	reset any affect	echo -e "\033[0m"	0m equals to m
	1	\033[1m			light (= bright)	echo -e "\033[1m####\033[m"	-
	2	\033[2m			dark (= fade)	echo -e "\033[2m####\033[m"	-
text-mode	~			~	~	~	~
	3	\033[3m			italic	echo -e "\033[3m####\033[m"	
	4	\033[4m			underline	echo -e "\033[4m####\033[m"	
	5	\033[5m			blink (slow)	echo -e "\033[5m####\033[m"	
	6	\033[6m			blink (fast)	?	not wildly support
	7	\033[7m			reverse	echo -e "\033[7m####\033[m"	it affects the background/foreground
	8	\033[8m			hide	echo -e "\033[8m####\033[m"	it affects the background/foreground
	9	\033[9m			cross	echo -e "\033[9m####\033[m"	
foreground	all below examples are with omitted color/text mode - default is 0						
	30	\033[30m			black	echo -e "\033[30m####\033[m"	
	31	\033[31m			red	echo -e "\033[31m####\033[m"	
	32	\033[32m			green	echo -e "\033[32m####\033[m"	
	33	\033[33m			yellow	echo -e "\033[33m####\033[m"	
	34	\033[34m			blue	echo -e "\033[34m####\033[m"	
	35	\033[35m			purple	echo -e "\033[35m####\033[m"	real name: magenta = reddish-purple
	36	\033[36m			cyan	echo -e "\033[36m####\033[m"	
	37	\033[37m			white	echo -e "\033[37m####\033[m"	
	38	8/24		This is for special use of 8-bit or 24-bit			
background	all below examples are with omitted color/text mode - default is 0						
	40	\033[40m			black	echo -e "\033[40m####\033[m"	
	41	\033[41m			red	echo -e "\033[41m####\033[m"	
	42	\033[42m			green	echo -e "\033[42m####\033[m"	
	43	\033[43m			yellow	echo -e "\033[43m####\033[m"	
	44	\033[44m			blue	echo -e "\033[44m####\033[m"	
	45	\033[45m			purple	echo -e "\033[45m####\033[m"	real name: magenta = reddish-purple
	46	\033[46m			cyan	echo -e "\033[46m####\033[m"	
	47	\033[47m			white	echo -e "\033[47m####\033[m"	
	48	8/24		This is for special use of 8-bit or 24-bit			

foreground 4-bit summary in a .gif:



3/4 bit foreground bash color output

background 4-bit summary in a .gif



3/4 bit background bash color output

## 8 bit ANSI Colors

The below table shows a summary of **8 bit** version of **ANSI color**. where **\$** is **color/text mode**

foreground	octal	hex	bash	description	example	NOTE
0-7	\033[\$;38	\x1b[\$;38	\e[\$;38	standard. normal	echo -e '\033[0;38;1m#####\033[m'	red color
8-15				underline	echo -e '\033[4;38;10m#####\033[m'	light green
16-231				reverse	echo -e '\033[7;38;226m#####\033[m'	yellow plus green
232-255					echo -e '\033[0;38;242m#####\033[m'	from black to white
background	octal	hex	bash	description	example	NOTE
0-7				standard. normal	echo -e '\033[0;48;1m#####\033[m'	
8-15					echo -e '\033[0;48;9m#####\033[m'	
16-231					echo -e '\033[0;48;45m#####\033[m'	
232-255					echo -e '\033[0;48;242m#####\033[m'	from black to white

Here is quick test with 8bit color and underline text mode:

```
~] for code in {0..255}; do echo -e "\e[4;38;${code}m $code: Test"; done
```

## linux bash in color

You can colorize output from **echo** , **printf** programs or you can colorize special bash variables like **PS0**, **PS1**, **PS2** (prompt) and **PS4** also.

Echo and printf use a **octal ascii code** or **C escape sequence** for **ESC** char.

Here is end sequence with **octal ESC** escape sequence:

```
end="\033[0m"
```

Remeber that **\033** is ASCII octal escape sequence. Maybe in another program you has to use another escape sequence for **ESC** char.

## Examples

This 4 examples do same colored output:

```
echo -e "My favorite colors are \033[31m red \033[0m and \033[32m green \033[0m "  
echo -e "My favorite colors are \033[0;31m red \033[0m and \033[0;32m green \033[0m"  
echo -e "My favorite colors are \e[31m red \e[0m and \e[32m green \e[0m "  
echo -e "My favorite colors are \e[0;31m red \e[0m and \e[0;32m green \e[0m"
```

- **\033** or **\e** - escape code for **ESC** char
- **[** - ESC character has to be followed by **[** (step 2)
- color/text mode is ommited - default is **0** or we type exactly **0** color/text mode
- **31** - **color-code** from step 3 for 3/4 bit ansi red color, **32** for green color
- **m** - m char from step 4
- **\033[0m** or **\e[0m** - ending sequence for **ESC** char

produce:

```

root@a:~# echo -e "My favorite colors are \033[31m red \033[0m and \033[32m green \033[0m "
My favorite colors are  red  and  green
root@a:~# echo -e "My favorite colors are \033[0;31m red \033[0m and \033[0;32m green \033[0m"
My favorite colors are  red  and  green
root@a:~# echo -e "My favorite colors are \e[31m red \e[0m and \e[32m green \e[0m "
My favorite colors are  red  and  green
root@a:~# echo -e "My favorite colors are \e[0;31m red \e[0m and \e[0;32m green \e[0m"
My favorite colors are  red  and  green

```

echo colored output

Example for red/green 3/4 bit ansi color code and underline text mode:

```

echo -e "My favorite colors are \033[4;31m red \033[0m and \033[4;32m green \033[0m"
echo -e "My favorite colors are \e[4;31m red \e[0m and \e[4;32m green \e[0m"

```

- `\033` or `\e` - escape code for ESC char
- `[` - ESC character has to be followed by `[` (step 2)
- `4` - color/text mode is number 4 - underline text
- `31` - **color-code** from step 3 for 3/4 bit ansi red color, `32` for green color
- `m` - m char from step 4
- `\033[0m` or `\e[0m` - ending sequence for ESC char

produce:

```

root@a:~# echo -e "My favorite colors are \033[4;31m red \033[0m and \033[4;32m green \033[0m"
My favorite colors are  red  and  green
root@a:~# echo -e "My favorite colors are \e[4;31m red \e[0m and \e[4;32m green \e[0m"
My favorite colors are  red  and  green

```

echo colored output 2

If you are using the echo command, be sure to use the `-e` flag to allow backslash escapes.

The same is for `printf` utility:

```

~] printf "My favorite colors are \033[31m red \033[0m , \033[32m green \033[0m and \033[44m blue \033[0m \n"
~] printf "My favorite colors are \e[31m red \e[0m , \e[32m green \e[0m and \e[44m blue \e[0m \n"

```

```

root@openvpn:~# printf "My favorite colors are \033[31m red \033[0m , \033[32m green \033[0m and \033[44m blue \033[0m \n"
My favorite colors are  red  ,  green  and  blue
root@openvpn:~# printf "My favorite colors are \e[31m red \e[0m , \e[32m green \e[0m and \e[44m blue \e[0m \n"
My favorite colors are  red  ,  green  and  blue

```

colored printf output

## bash exception

If you are going to use these colored codes in your special bash variables

- PS0
- PS1
- PS2 - prompt
- PS4

you should add **extra escape characters** so that bash can interpret them correctly. You should add `[` before any starting ANSI code and add `]` after any ending ones.

example:

in regular usage: `\033[32mThis is in green\033[0m`

for PS0/1/2/4: `[\033[32m]This is in green[\033[m]`

- `[` is for start of a sequence of **non-printable** characters
- `]` is for end of a sequence of **non-printable** characters

## sed colored output

Here is information from [sed](#) manual page:

```
\xxxx
```

So, for **ESC** char we have to this escape sequence: `\033`

Here is another very important information for `&` char and `\1` through `\9` for sed substitution statement:

```
s/regexp/replacement/
```

Attempt to match regexp against the pattern space. If successful, replace that portion matched with replacement. The replace

### examples how colorize sed regex match

```
~] echo "one two three four five" | sed 's/two/\033[1;31m&\033[0m/g'
```

```
~] one two three four five
```

**two** - regex that we can try match  
**\033** - octal ascci escape sequence for ESC char  
**[1;31m** - color-mode 1 - lighter than normal and color-code 31 for red color in 3/4 bit ansi color code  
**&** - special character & to refer to that portion of the regex pattern space which matched  
**[0m** - end sequence




linux


bash

«Previous article


Next article »




Architecture



Bash



Databases



Debian

#### SUBSCRIBE FOR NEW ARTICLES

@ Email Address

SUBSCRIBE

#### ALSO ON MYBLUELINUX-COM

Debian Linux and LSI MegaRAID SAS

3 years ago · 2 comments

napis description-o com je clanok

How Create Bootstrap Tables in Hugo

5 years ago · 2 comments

Do you know, how create very nice bootstrap tables in Hugo static ...

NumPy I Visual

4 years

NumPy is library widely u

0 Comments

 Анатолий Суворин

Start the discussion...



Share

Best Newest Oldest

Be the first to comment.

[Subscribe](#) [Privacy](#) [Do Not Sell My Data](#)