

Quotes and escaping

Quoting and escaping are important, as they influence the way Bash acts upon your input. There are three recognized types:

- **per-character escaping** using a backslash: `\$stuff`
- **weak quoting** with double-quotes: `"stuff"`
- **strong quoting** with single-quotes: `'stuff'`

All three forms have the very same purpose: **They give you general control over parsing, expansion and expansion results.**

Besides these basic variants, there are some special quoting methods (like interpreting ANSI-C escapes in a string) you'll meet below.

⚠ **ATTENTION** ⚠ The quote characters (`"` , double quote and `'` , single quote) are a syntax element that influence parsing. It is not related to the quote characters passed as text to the command line! The syntax quotes are removed before the command is called! Example:

```
### NO NO NO: this passes three strings:
###      (1) "my
###      (2) multiword
###      (3) argument"
MYARG="\my multiword argument\"
somecommand $MYARG

### THIS IS NOT (!) THE SAME AS ###
command "my multiword argument"

### YOU NEED ###
MYARG="my multiword argument"
command "$MYARG"
```

Per-character escaping

Per-character escaping is useful in on expansions and substitutions. In general, a character that has a special meaning to Bash, like the dollar-sign (`$`) can be masked to not have a special meaning using the backslash:

```
echo \$HOME is set to \"$HOME\"
```

- `\$HOME` won't expand because it's not in variable-expansion syntax anymore
- The backslash changes the quotes into literals - otherwise Bash would interpret them

The sequence `\<newline>` (an unquoted backslash, followed by a `<newline>` character) is interpreted as **line continuation**. It is removed from the input stream and thus effectively ignored. Use it to beautify your code:

```
# escapestr_sed()
# read a stream from stdin and escape characters in text that could b
# e interpreted as
# special characters by sed
escape_sed() {
    sed \
    -e 's/\\/\\\\/g' \
    -e 's/\&/\\&/g'
}
```

The backslash can be used to mask every character that has a special meaning to bash. Exception: Inside a single-quoted string (see below).

Weak quoting

Inside a weak-quoted string there's **no special interpretation of**:

- spaces as word-separators (on initial command line splitting and on word splitting!)
- single-quotes to introduce strong-quoting (see below)
- characters for pattern matching
- tilde expansion
- pathname expansion
- process substitution

Everything else, especially parameter expansion, is performed!

```
ls -l ""
```

Will not be expanded. `ls` gets the literal `*` as argument. It will, unless you have a file named `*`, spit out an error.

```
echo "Your PATH is: $PATH"
```

Will work as expected. `$PATH` is expanded, because it's double (weak) quoted.

If a backslash in double quotes ("weak quoting") occurs, there are 2 ways to deal with it

- if the backslash is followed by a character that would have a special meaning even inside double-quotes, the backslash is removed and the following character loses its special meaning
- if the backslash is followed by a character without special meaning, the backslash is not removed

In particular this means that `"\$"` will become `$`, but `"\x"` will become `\x`.

Strong quoting

Strong quoting is very easy to explain:

Inside a single-quoted string **nothing** is interpreted, except the single-quote that closes the string.

```
echo 'Your PATH is: $PATH'
```

`$PATH` won't be expanded, it's interpreted as ordinary text because it's surrounded by strong quotes.

In practise that means, to produce a text like `Here's my test...` as a single-quoted string, you have to leave and re-enter the single quoting to get the character `" ' "` as literal text:

```
# WRONG
echo 'Here's my test...'

# RIGHT
echo 'Here\'\'s my test...'

# ALTERNATIVE: It's also possible to mix-and-match quotes for readability:
echo "Here's my test"
```

ANSI C like strings

Bash provides another quoting mechanism: Strings that contain ANSI C-like escape sequences. The Syntax is:

```
$'string'
```

where the following escape sequences are decoded in `string` :

Code	Meaning
<code>\"</code>	double-quote
<code>\'</code>	single-quote
<code>\\</code>	backslash
<code>\a</code>	terminal alert character (bell)
<code>\b</code>	backspace
<code>\e</code>	escape (<u>ASCII</u> () 033)
<code>\E</code>	escape (<u>ASCII</u> () 033) \E is non-standard
<code>\f</code>	form feed
<code>\n</code>	newline
<code>\r</code>	carriage return

Code	Meaning
<code>\t</code>	horizontal tab
<code>\v</code>	vertical tab
<code>\cx</code>	a control-x character, for example, <code>\$'\cZ'</code> to print the control sequence composed of Ctrl-Z (<code>^Z</code>)
<code>\uXXXX</code>	Interprets <code>XXXX</code> as a hexadecimal number and prints the corresponding character from the character set (4 digits) (Bash 4.2-alpha)
<code>\UXXXXXXXX</code>	Interprets <code>XXXX</code> as a hexadecimal number and prints the corresponding character from the character set (8 digits) (Bash 4.2-alpha)
<code>\nnn</code>	the eight-bit character whose value is the octal value <code>nnn</code> (one to three digits)
<code>\xHH</code>	the eight-bit character whose value is the hexadecimal value <code>HH</code> (one or two hex digits)

This is especially useful when you want to pass special characters as arguments to some programs, like passing a newline to `sed`.

The resulting text is treated as if it were **single-quoted**. No further expansion happens.

The `'...'` syntax comes from `ksh93`, but is portable to most modern shells including `pdksh`. A specification (<http://austingroupbugs.net/view.php?id=249#c590>) for it was accepted for SUS issue 7. There are still some stragglers, such as most `ash` variants including `dash`, (except `busybox` built with "bash compatibility" features).

I18N/L10N

A dollar-sign followed by a double-quoted string, for example

```
echo $"generating database..."
```

means `I18N`. If there is a translation available for that string, it is used instead of the given text. If not, or if the locale is `C / POSIX`, the dollar sign is simply ignored, which results in a normal double quoted string.

If the string was replaced (translated), the result is double quoted.

In case you're a C programmer: The purpose of `$"..."` is the same as for `gettext()` or `_()`.

For useful examples to localize your scripts, please see Appendix I of the Advanced Bash Scripting Guide (<http://tldp.org/LDP/abs/html/localization.html>).

Attention: There is a security hole. Please read the `gettext` documentation (http://www.gnu.org/software/gettext/manual/html_node/bash.html)

Common mistakes

String lists in for-loops

The classic for loop uses a list of words to iterate through. The list can also be in a variable:

```
mylist="DOG CAT BIRD HORSE"
```

WRONG way to iterate through this list:

```
for animal in "$mylist"; do
    echo $animal
done
```

Why? Due to the double-quotes, technically, the expansion of `$mylist` is seen as **one word**. The for loop iterates exactly one time, with `animal` set to the whole list.

RIGHT way to iterate through this list:

```
for animal in $mylist; do
    echo $animal
done
```

Working out the test-command

The command `test` or `[...]` (the classic test command) is an ordinary command, so ordinary syntax rules apply. Let's take string comparison as an example:

```
[ WORD = WORD ]
```

The `]` at the end is a convenience; if you type `which [` you will see that there is in fact a binary file with that name. So if we were writing this as a test command it would be:

```
test WORD = WORD
```

When you compare variables, it's wise to quote them. Let's create a test string with spaces:

```
mystring="my string"
```

And now check that string against the word "testword":

```
[ $mystring = testword ] # WRONG!
```

This fails! These are too many arguments for the string comparison test. After expansion is performed, you really execute:

```
[ my string = testword ]
test my string = testword
```

Which is wrong, because `my` and `string` are two separate arguments.

So what you really want to do is:

```
[ "$mystring" = testword ] # RIGHT!
```

```
test 'my string' = testword
```

Now the command has three parameters, which makes sense for a binary (two argument) operator.

Hint: Inside the conditional expression (`[[]`) Bash doesn't perform word splitting, and thus you don't need to quote your variable references - they are always seen as "one word".

See also

- Internal: Some words about words...
- Internal: Word splitting
- Internal: Introduction to expansions and substitutions
- External: Grymore: Shellquoting (<http://www.grymoire.com/Unix/Quote.html>)

Discussion

Szilvi, [2012/09/02 19:56\(\)](#), [2012/09/03 09:19\(\)](#)

Thanks for posting this Great article! It really helped my see these magic things of bash more clearly. But I still have a problem that I can't solve. I'll post it here, maybe someone can help me.

So here is it: I have a test folder with some subfolders:

```
# find .  
.  
./etc  
./etc/a  
./a  
./a/b  
./e  
./c  
./c/d
```

I want to list all folders and files except the etc folder and its contents I'll use this command, and i get exactly what i want:

```
# find . ! -wholename "./etc*"
.
./a
./a/b
./e
./c
./c/d
```

Till this point it's fine. But inside a bash script I NEED THIS AS STRING because i'm building up the condition based on some internal values. Now look at this:

```
# cond='! -wholename "./etc*"'
```

And when i run find again...

```
# find . $cond
.
./etc
./etc/a
./a
./a/b
./e
./c
./c/d
```

...it lists the etc folder and its contents which it shouldn't.

I'm sure it's a quotation problem, and i tried all variations i know, but i wasn't able to solve the problem. Where is the mistake?

I appreciate your help Szilvi

Jan Schampera, 2012/09/03 09:27 ()

Yea, this is a quoting problem.

The text you write in the variable (`"./etc"`) is really text. The quotes you give on commandline (`find . ! -wholename "./etc*"`) is **syntax**. You can't "store syntax in variables". The syntax (quoting) is used to tell Bash what a word is when it can't automatically detect it (and especially here, to not make Bash expand the wildcard itself, but to pass it as text to `find`).

In general, you should construct an array where every element contains one "word" and the whole array forms the arguments you want to pass to `find` :

```
cond=( ! -wholename "./etc*" )
# use it
find ... "${cond[@]}" ...
```

The most correct fix would be using the `-prune` test/action from `find` , anyways. Please see the find article on Greg's wiki (<http://mywiki.woledge.org/UsingFind>)

Aaron, [2012/10/20 00:01 \(\)](#), [2012/10/20 10:59 \(\)](#)

From command line this works

```
mailx -s "GM $HOST Case Logs for Ticket" aaron.brandt@XXXXX.com
</home/ab007652/tmp/GM.$HOST.$$ \r.\r
```

But from within a script it doesn't, How come?

Doesn't work.. I have a problem with old version of mail so this is the only work around

```
# for your records.
    printf "\n\E[1;33mSend your trouble shooting to the ticke
t?\033[m [y/N] "
    read -e TICKET
if [ "$TICKET" == "y" ];
    then
        mailx -s "Ticket #: $TKT" smc@XXXX.com </home/ab007652/tmp/GM.$HOST.$$ \r.\r
    else
        mailx -s "GM $HOST Case Logs for Ticket: $TKT" $USR@XXXX.com </home/ab007652/tmp/GM.$HOST.$$ \r.\r
    fi
```

Jan Schampera, [2012/10/20 11:01 \(\)](#)

What is this `\r.\r` there? Just give mailx the text file as input and test.

Aaron, [2012/10/20 15:37 \(\)](#)

Those are carriage returns, If I use `mailx -s "Ticket #: $TKT" smc@XXXX.com </home/ab007652/tmp/GM.$HOST.$$` by itself it just hangs until I issue the "."

From a bash prompt the `\r.\r` works but if I use it in a script it does not. It is as if the `\r.\r` isn't even there.

If I use `mail -s` it doesn't include the subject line only `mailx -s` does.

Jan Schampera, [2012/10/20 16:49 \(\)](#)

The best way for you would be writing a mail (in mail format, with headers etc.) and deliver it with your MTA's `sendmail -oi` (or equivalent).



Everything else is too much guessing.

sshaw (<http://github.com/sshaw>), [2013/12/31 03:14 \(\)](#)


```
set -x
```

Is a good way for one to debug and/or better understand bash quoting:

```
~ >dirs='/etc /tmp'
~ >(set -x; ls "$dirs" > /dev/null)
+ ls '/etc /tmp'
ls: /etc /tmp: No such file or directory
~ >(set -x; ls $dirs > /dev/null)
+ ls /etc /tmp
~ >dirs="/etc/*"
~ >(set -x; ls "$dirs" > /dev/null)
+ ls '/etc/*'
ls: /etc/*: No such file or directory
~ >(set -x; ls $dirs > /dev/null)
+ ls /etc/RemoteManagement.launchd /etc/afpovertcp.cfg /etc/alias
es
# ...
```

 syntax/quoting.txt  Last modified: 2019/10/30 17:39 by ersen

This site is supported by Performing Databases - your experts for
database administration

Bash Hackers Wiki



Except where otherwise noted, content on this wiki is licensed under the following license:
GNU Free Documentation License 1.3