

confstr - Man Page

get configurable variables

Prolog

This manual page is part of the POSIX Programmer's Manual. The Linux implementation of this interface may differ (consult the corresponding Linux manual page for details of Linux behavior), or the interface may not be implemented on Linux.

Synopsis

```
#include <unistd.h>
```

```
size_t confstr(int name, char *buf, size_t len);
```

Description

The *confstr()* function shall return configuration-defined string values. Its use and purpose are similar to *sysconf()*, but it is used where string values rather than numeric values are returned.

The *name* argument represents the system variable to be queried. The implementation shall support the following name values, defined in *<unistd.h>*. It may support others:

```
_CS_PATH  
_CS_POSIX_V7_ILP32_OFF32_CFLAGS  
_CS_POSIX_V7_ILP32_OFF32_LDFLAGS  
_CS_POSIX_V7_ILP32_OFF32_LIBS  
_CS_POSIX_V7_ILP32_OFFBIG_CFLAGS  
_CS_POSIX_V7_ILP32_OFFBIG_LDFLAGS  
_CS_POSIX_V7_ILP32_OFFBIG_LIBS  
_CS_POSIX_V7_LP64_OFF64_CFLAGS  
_CS_POSIX_V7_LP64_OFF64_LDFLAGS  
_CS_POSIX_V7_LP64_OFF64_LIBS  
_CS_POSIX_V7_LPBIG_OFFBIG_CFLAGS  
_CS_POSIX_V7_LPBIG_OFFBIG_LDFLAGS  
_CS_POSIX_V7_LPBIG_OFFBIG_LIBS  
_CS_POSIX_V7_THREADS_CFLAGS  
_CS_POSIX_V7_THREADS_LDFLAGS  
_CS_POSIX_V7_WIDTH_RESTRICTED_ENVS  
_CS_V7_ENV  
_CS_POSIX_V6_ILP32_OFF32_CFLAGS  
_CS_POSIX_V6_ILP32_OFF32_LDFLAGS  
_CS_POSIX_V6_ILP32_OFF32_LIBS  
_CS_POSIX_V6_ILP32_OFFBIG_CFLAGS  
_CS_POSIX_V6_ILP32_OFFBIG_LDFLAGS  
_CS_POSIX_V6_ILP32_OFFBIG_LIBS  
_CS_POSIX_V6_LP64_OFF64_CFLAGS  
_CS_POSIX_V6_LP64_OFF64_LDFLAGS
```

confstr - Man Page

```
_CS_POSIX_V6_LPBIG_OFFBIG_LIBS
_CS_POSIX_V6_WIDTH_RESTRICTED_ENVS
_CS_V6_ENV
```

If *len* is not 0, and if *name* has a configuration-defined value, *confstr()* shall copy that value into the *len*-byte buffer pointed to by *buf*. If the string to be returned is longer than *len* bytes, including the terminating null, then *confstr()* shall truncate the string to *len*-1 bytes and null-terminate the result. The application can detect that the string was truncated by comparing the value returned by *confstr()* with *len*.

If *len* is 0 and *buf* is a null pointer, then *confstr()* shall still return the integer value as defined below, but shall not return a string. If *len* is 0 but *buf* is not a null pointer, the result is unspecified.

After a call to:

```
confstr(_CS_V7_ENV, buf, sizeof(buf))
```

the string stored in *buf* shall contain a <space>-separated list of the variable=value environment variable pairs an implementation requires as part of specifying a conforming environment, as described in the implementations' conformance documentation.

If the implementation supports the POSIX shell option, the string stored in *buf* after a call to:

```
confstr(_CS_PATH, buf, sizeof(buf))
```

can be used as a value of the *PATH* environment variable that accesses all of the standard utilities of POSIX.1-2008, that are provided in a manner accessible via the *exec* family of functions, if the return value is less than or equal to *sizeof(buf)*.

Return Value

If *name* has a configuration-defined value, *confstr()* shall return the size of buffer that would be needed to hold the entire configuration-defined value including the terminating null. If this return value is greater than *len*, the string returned in *buf* is truncated.

If *name* is invalid, *confstr()* shall return 0 and set *errno* to indicate the error.

If *name* does not have a configuration-defined value, *confstr()* shall return 0 and leave *errno* unchanged.

Errors

The *confstr()* function shall fail if:

confstr - Man Page

The following sections are informative.

Examples

None.

Application Usage

An application can distinguish between an invalid *name* parameter value and one that corresponds to a configurable variable that has no configuration-defined value by checking if *errno* is modified. This mirrors the behavior of *sysconf()*.

The original need for this function was to provide a way of finding the configuration-defined default value for the environment variable *PATH*. Since *PATH* can be modified by the user to include directories that could contain utilities replacing the standard utilities in the Shell and Utilities volume of POSIX.1-2017, applications need a way to determine the system-supplied *PATH* environment variable value that contains the correct search path for the standard utilities.

An application could use:

```
confstr(name, (char *)NULL, (size_t)0)
```

to find out how big a buffer is needed for the string value; use *malloc()* to allocate a buffer to hold the string; and call *confstr()* again to get the string. Alternately, it could allocate a fixed, static buffer that is big enough to hold most answers (perhaps 512 or 1024 bytes), but then use *malloc()* to allocate a larger buffer if it finds that this is too small.

Rationale

Application developers can normally determine any configuration variable by means of reading from the stream opened by a call to:

```
popen("command -p getconf variable", "r");
```

The *confstr()* function with a *name* argument of *_CS_PATH* returns a string that can be used as a *PATH* environment variable setting that will reference the standard shell and utilities as described in the Shell and Utilities volume of POSIX.1-2017.

The *confstr()* function copies the returned string into a buffer supplied by the application instead of returning a pointer to a string. This allows a cleaner function in some implementations (such as those with lightweight threads) and resolves questions about when the application must copy the string returned.

confstr - Man Page

None.

See Also

`exec`, `fpathconf()`, `sysconf()`

The Base Definitions volume of POSIX.1-2017, `<unistd.h>`

The Shell and Utilities volume of POSIX.1-2017, `c99`

Copyright

Portions of this text are reprinted and reproduced in electronic form from IEEE Std 1003.1-2017, Standard for Information Technology -- Portable Operating System Interface (POSIX), The Open Group Base Specifications Issue 7, 2018 Edition, Copyright (C) 2018 by the Institute of Electrical and Electronics Engineers, Inc and The Open Group. In the event of any discrepancy between this version and the original IEEE and The Open Group Standard, the original IEEE and The Open Group Standard is the referee document. The original Standard can be obtained online at <http://www.opengroup.org/unix/online.html> .

Any typographical or formatting errors that appear in this page are most likely to have been introduced during the conversion of the source files to man page format. To report such errors, see https://www.kernel.org/doc/man-pages/reporting_bugs.html .

Referenced By

`exec(3p)`, `fpathconf(3p)`, `getconf(1p)`, `poll.h(0p)`, `stddef.h(0p)`, `sysconf(3p)`, `sys_types.h(0p)`, `termios.h(0p)`, `unistd.h(0p)`, `wchar.h(0p)`.

2017 IEEE/The Open Group POSIX Programmer's Manual

confstr - Man Page

[Home](#) [Blog](#) [About](#)