

Раздел «Парадигмы» . SortHaskell :

### Сортировка qsort и msort на Haskell

```
module Sort where

mergeSort [] = []
mergeSort [x] = [x]

mergeSort xs | size > 0 =
    merge (mergeSort front) (mergeSort back)
    where
        size = length xs `div` 2
        front = take size xs
        back = drop size xs

merge :: Ord a => [a] -> [a] -> [a]
merge (x : xs) (y : ys)
    | x <= y    = x : merge xs (y : ys)
    | x > y     = y : merge (x : xs) ys
merge [] ys = ys
merge xs [] = xs

qsort []      = []
qsort (x:xs) = qsort elts_lt_x ++ [x] ++ qsort elts_greq_x
    where
        elts_lt_x    = [y | y <- xs, y < x]
        elts_greq_x = [y | y <- xs, y >= x]

-- ArtemVoroztsov - 22 Apr 2005
Copyright © 2003-2022 by the contributing authors.
```

Поиск

 Поиск

Раздел  
«Парадигмы»

Инструменты:

Поиск  
Изменения  
Index  
Статистика

Разделы

Информация  
Алгоритмы  
Язык Си  
Язык Ruby  
Язык  
Ассемблера  
E! Judge  
Парадигмы  
Образование  
Сети  
Objective C

Logon>>