

NAME

unistd.h – standard symbolic constants and types

SYNOPSIS

```
#include <unistd.h>
```

DESCRIPTION

The `<unistd.h>` header defines miscellaneous symbolic constants and types, and declares miscellaneous functions. The actual values of the constants are unspecified except as shown. The contents of this header are shown below.

Version Test Macros

The `<unistd.h>` header shall define the following symbolic constants. The values shall be suitable for use in `#if` preprocessing directives.

`_POSIX_VERSION`


Integer value indicating version of this standard (C-language binding) to which the implementation conforms. For implementations conforming to POSIX.1-2017, the value shall be 200809L.


`_POSIX2_VERSION`

Integer value indicating version of the Shell and Utilities volume of POSIX.1 to which the implementation conforms. For implementations conforming to POSIX.1-2017, the value shall be 200809L. For profile implementations that define `_POSIX_SUBPROFILE` (see [Subprofiling Considerations](#)) in `<unistd.h>`, `_POSIX2_VERSION` may be left undefined or be defined with the value -1 to indicate that the Shell and Utilities volume of POSIX.1 is not supported. In this case, a call to `sysconf(_SC_2_VERSION)` shall return either 200809L or -1 indicating that the Shell and Utilities volume of POSIX.1 is or is not, respectively, supported at runtime.

The `<unistd.h>` header shall define the following symbolic constant only if the implementation supports the XSI option; see [XSI Conformance](#). If defined, its value shall be suitable for use in `#if` preprocessing directives.

`_XOPEN_VERSION`

[XSI] 

Integer value indicating version of the X/Open Portability Guide to which the implementation conforms. The value shall be 700. 

Constants for Options and Option Groups


The following symbolic constants, if defined in `<unistd.h>`, shall have a value of -1, 0, or greater, unless otherwise specified below. For profile implementations that define `_POSIX_SUBPROFILE` (see [Subprofiling Considerations](#)) in `<unistd.h>`, constants described below as always having a value greater than zero need not be defined and, if defined, may have a value of -1, 0, or greater. The values shall be suitable for use in `#if` preprocessing directives.

If a symbolic constant is not defined or is defined with the value -1, the option is not supported for compilation. If it is defined with a value greater than zero, the option shall always be supported when the application is executed. If it is defined with the value zero,

the option shall be supported for compilation and might or might not be supported at runtime. See [Options](#) for further information about the conformance requirements of these three categories of support.

`_POSIX_ADVISORY_INFO`

[ADV] 

The implementation supports the Advisory Information option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 

`_POSIX_ASYNCHRONOUS_IO`

The implementation supports asynchronous input and output. This symbol shall always be set to the value 200809L.

`_POSIX_BARRIERS`

The implementation supports barriers. This symbol shall always be set to the value 200809L.


`_POSIX_CHOWN_RESTRICTED`


The use of [chown\(\)](#) and [fchown\(\)](#) is restricted to a process with appropriate privileges, and to changing the group ID of a file only to the effective group ID of the process or to one of its supplementary group IDs. This symbol shall be defined with a value other than -1.

`_POSIX_CLOCK_SELECTION`


The implementation supports clock selection. This symbol shall always be set to the value 200809L.


`_POSIX_CPUTIME`

[CPT] 


The implementation supports the Process CPU-Time Clocks option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


`_POSIX_FSYNC`

[FSC] 

The implementation supports the File Synchronization option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 

`_POSIX_IPV6`

[IP6] 

The implementation supports the IPv6 option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 

`_POSIX_JOB_CONTROL`


The implementation supports job control. This symbol shall always be set to a value greater than zero.

`_POSIX_MAPPED_FILES`

The implementation supports memory mapped Files. This symbol shall always be set to the value 200809L.


`_POSIX_MEMLOCK`

[ML] 

The implementation supports the Process Memory Locking option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 

`_POSIX_MEMLOCK_RANGE`


[MLR] 


The implementation supports the Range Memory Locking option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 

`_POSIX_MEMORY_PROTECTION`

The implementation supports memory protection. This symbol shall always be set to the value 200809L.


`_POSIX_MESSAGE_PASSING`

[MSG] 

The implementation supports the Message Passing option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 

`_POSIX_MONOTONIC_CLOCK`


[MON] 


The implementation supports the Monotonic Clock option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by `sysconf()` shall either be -1 or 200809L. 

_POSIX_NO_TRUNC

Pathname components longer than {NAME_MAX} generate an error. This symbol shall be defined with a value other than -1.


_POSIX_PRIORITIZED_IO

[PIQ] 

The implementation supports the Prioritized Input and Output option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by `sysconf()` shall either be -1 or 200809L. 


_POSIX_PRIORITY_SCHEDULING

[PS] 

The implementation supports the Process Scheduling option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by `sysconf()` shall either be -1 or 200809L. 

_POSIX_RAW_SOCKETS

[RS] 

The implementation supports the Raw Sockets option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by `sysconf()` shall either be -1 or 200809L. 

_POSIX_READER_WRITER_LOCKS

The implementation supports read-write locks. This symbol shall always be set to the value 200809L.

_POSIX_REALTIME_SIGNALS

The implementation supports realtime signals. This symbol shall always be set to the value 200809L.

_POSIX_REGEX

The implementation supports the Regular Expression Handling option. This symbol shall always be set to a value greater than zero.

_POSIX_SAVED_IDS


Each process has a saved set-user-ID and a saved set-group-ID. This symbol shall always be set to a value greater than zero.

_POSIX_SEMAPHORES

The implementation supports semaphores. This symbol shall always be set to the value 200809L.

_POSIX_SHARED_MEMORY_OBJECTS


[SHM] 


The implementation supports the Shared Memory Objects option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by `sysconf()` shall either be -1 or 200809L. 

_POSIX_SHELL

The implementation supports the POSIX shell. This symbol shall always be set to a value greater than zero.

_POSIX_SPAWN

[SPN] 


The implementation supports the Spawn option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by `sysconf()` shall either be -1 or 200809L. 

_POSIX_SPIN_LOCKS

The implementation supports spin locks. This symbol shall always be set to the value 200809L.


_POSIX_SPORADIC_SERVER

[SS] 


The implementation supports the Process Sporadic Server option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by `sysconf()` shall either be -1 or 200809L. 

_POSIX_SYNCHRONIZED_IO


[SIO] 

The implementation supports the Synchronized Input and Output option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by `sysconf()` shall either be -1 or 200809L. 


`_POSIX_THREAD_ATTR_STACKADDR`[TSA] 


The implementation supports the Thread Stack Address Attribute option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


`_POSIX_THREAD_ATTR_STACKSIZE`[TSS] 

The implementation supports the Thread Stack Size Attribute option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


`_POSIX_THREAD_CPU_TIME`[TCT] 

The implementation supports the Thread CPU-Time Clocks option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


`_POSIX_THREAD_PRIO_INHERIT`[TPI] 

The implementation supports the Non-Robust Mutex Priority Inheritance option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


`_POSIX_THREAD_PRIO_PROTECT`[TPP] 

The implementation supports the Non-Robust Mutex Priority Protection option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


`_POSIX_THREAD_PRIORITY_SCHEDULING`[TPS] 

The implementation supports the Thread Execution Scheduling option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


`_POSIX_THREAD_PROCESS_SHARED`[TSH] 

The implementation supports the Thread Process-Shared Synchronization option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 

`_POSIX_THREAD_ROBUST_PRIO_INHERIT`[RPI] 

The implementation supports the Robust Mutex Priority Inheritance option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


`_POSIX_THREAD_ROBUST_PRIO_PROTECT`[RPP] 

The implementation supports the Robust Mutex Priority Protection option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 

`_POSIX_THREAD_SAFE_FUNCTIONS`

The implementation supports thread-safe functions. This symbol shall always be set to the value 200809L.

`_POSIX_THREAD_SPORADIC_SERVER`[TSP] 

The implementation supports the Thread Sporadic Server option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 

`_POSIX_THREADS`

The implementation supports threads. This symbol shall always be set to the value 200809L.

`_POSIX_TIMEOUTS`


The implementation supports timeouts. This symbol shall always be set to the value 200809L.

`_POSIX_TIMERS`

The implementation supports timers. This symbol shall always be set to the value 200809L.


`_POSIX_TRACE`

[OB_TRC] 

The implementation supports the Trace option. If this symbol is defined in *<unistd.h>*, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


_POSIX_TRACE_EVENT_FILTER

[OB_TEE] 

The implementation supports the Trace Event Filter option. If this symbol is defined in *<unistd.h>*, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


_POSIX_TRACE_INHERIT

[OB_TRI] 

The implementation supports the Trace Inherit option. If this symbol is defined in *<unistd.h>*, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


_POSIX_TRACE_LOG

[OB_TRL] 

The implementation supports the Trace Log option. If this symbol is defined in *<unistd.h>*, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


_POSIX_TYPED_MEMORY_OBJECTS

[TYM] 

The implementation supports the Typed Memory Objects option. If this symbol is defined in *<unistd.h>*, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


_POSIX_V6_ILP32_OFF32

[OB] 

The implementation provides a C-language compilation environment with 32-bit **int**, **long**, **pointer**, and **off_t** types. 


_POSIX_V6_ILP32_OFFBIG

[OB] 

The implementation provides a C-language compilation environment with 32-bit **int**, **long**, and **pointer** types and an **off_t** type using at least 64 bits. 

_POSIX_V6_LP64_OFF64

[OB] 

The implementation provides a C-language compilation environment with 32-bit **int** and 64-bit **long**, **pointer**, and **off_t** types. 

_POSIX_V6_LP64_OFFBIG

[OB] 

The implementation provides a C-language compilation environment with an **int** type using at least 32 bits and **long**, **pointer**, and **off_t** types using at least 64 bits. 

_POSIX_V7_ILP32_OFF32

The implementation provides a C-language compilation environment with 32-bit **int**, **long**, **pointer**, and **off_t** types.

_POSIX_V7_ILP32_OFFBIG

The implementation provides a C-language compilation environment with 32-bit **int**, **long**, and **pointer** types and an **off_t** type using at least 64 bits.

_POSIX_V7_LP64_OFF64

The implementation provides a C-language compilation environment with 32-bit **int** and 64-bit **long**, **pointer**, and **off_t** types.

_POSIX_V7_LP64_OFFBIG


The implementation provides a C-language compilation environment with an **int** type using at least 32 bits and **long**, **pointer**, and **off_t** types using at least 64 bits.

_POSIX2_C_BIND

The implementation supports the C-Language Binding option. This symbol shall always have the value 200809L.

_POSIX2_C_DEV


[CD] 

The implementation supports the C-Language Development Utilities option. If this symbol is defined in *<unistd.h>*, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


_POSIX2_CHAR_TERM

The implementation supports the Terminal Characteristics option. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or a value greater than zero.

_POSIX2_FORT_DEV[FD] 


The implementation supports the FORTRAN Development Utilities option. If this symbol is defined in <unistd.h>, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


_POSIX2_FORT_RUN[FR] 


The implementation supports the FORTRAN Runtime Utilities option. If this symbol is defined in <unistd.h>, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


_POSIX2_LOCALEDEF

The implementation supports the creation of locales by the [localedef](#) utility. If this symbol is defined in <unistd.h>, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L.


_POSIX2_PBS[OB BE] 

The implementation supports the Batch Environment Services and Utilities option. If this symbol is defined in <unistd.h>, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


_POSIX2_PBS_ACCOUNTING[OB BE] 

The implementation supports the Batch Accounting option. If this symbol is defined in <unistd.h>, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


_POSIX2_PBS_CHECKPOINT[OB BE] 

The implementation supports the Batch Checkpoint/Restart option. If this symbol is defined in <unistd.h>, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


_POSIX2_PBS_LOCATE[OB BE] 

The implementation supports the Locate Batch Job Request option. If this symbol is defined in <unistd.h>, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


_POSIX2_PBS_MESSAGE[OB BE] 

The implementation supports the Batch Job Message Request option. If this symbol is defined in <unistd.h>, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 


_POSIX2_PBS_TRACK[OB BE] 

The implementation supports the Track Batch Job Request option. If this symbol is defined in <unistd.h>, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 

_POSIX2_SW_DEV[SD] 

The implementation supports the Software Development Utilities option. If this symbol is defined in <unistd.h>, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 

_POSIX2_UPE[UP] 

The implementation supports the User Portability Utilities option. If this symbol is defined in <unistd.h>, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall either be -1 or 200809L. 

_XOPEN_CRYPT[XSI] 

The implementation supports the X/Open Encryption Option Group.

_XOPEN_ENH_I18N

The implementation supports the Issue 4, Version 2 Enhanced Internationalization Option Group. This symbol shall always be set to a value other than -1.


_XOPEN_REALTIME

The implementation supports the X/Open Realtime Option Group.

_XOPEN_REALTIME_THREADS


The implementation supports the X/Open Realtime Threads Option Group.

`_XOPEN_SHM`

The implementation supports the Issue 4, Version 2 Shared Memory Option Group. This symbol shall always be set to a value other than -1. 

`_XOPEN_STREAMS`

[\[OB_XSR\]](#) 


The implementation supports the XSI STREAMS Option Group. 


`_XOPEN_UNIX`

[\[XSI\]](#) 

The implementation supports the XSI option. 

`_XOPEN_UUCP`

[\[UU\]](#) 

The implementation supports the UUCP Utilities option. If this symbol is defined in `<unistd.h>`, it shall be defined to be -1, 0, or 200809L. The value of this symbol reported by [sysconf\(\)](#) shall be either -1 or 200809L. 

Execution-Time Symbolic Constants

If any of the following symbolic constants are not defined in the `<unistd.h>` header, the value shall vary depending on the file to which it is applied. If defined, they shall have values suitable for use in `#if` preprocessing directives.

If any of the following symbolic constants are defined to have value -1 in the `<unistd.h>` header, the implementation shall not provide the option on any file; if any are defined to have a value other than -1 in the `<unistd.h>` header, the implementation shall provide the option on all applicable files.

All of the following values, whether defined as symbolic constants in `<unistd.h>` or not, may be queried with respect to a specific file using the [pathconf\(\)](#) or [fpathconf\(\)](#) functions:

`_POSIX_ASYNC_IO`

Asynchronous input or output operations may be performed for the associated file.

`_POSIX_PRIO_IO`

Prioritized input or output operations may be performed for the associated file.

`_POSIX_SYNC_IO`

Synchronized input or output operations may be performed for the associated file.

If the following symbolic constants are defined in the `<unistd.h>` header, they apply to files and all paths in all file systems on the implementation:

`_POSIX_TIMESTAMP_RESOLUTION`

The resolution in nanoseconds for all file timestamps.

`_POSIX2_SYMLINKS`

Symbolic links can be created.

Constants for Functions

The `<unistd.h>` header shall define NULL as described in [<stddef.h>](#).

The `<unistd.h>` header shall define the following symbolic constants for use with the [access\(\)](#) function. The values shall be suitable for use in `#if` preprocessing directives.

`F_OK`

Test for existence of file.

`R_OK`

Test for read permission.

`W_OK`

Test for write permission.

`X_OK`

Test for execute (search) permission.

The constants `F_OK`, `R_OK`, `W_OK`, and `X_OK` and the expressions `R_OK|W_OK`, `R_OK|X_OK`, and `R_OK|W_OK|X_OK` shall all have distinct values.

The `<unistd.h>` header shall define the following symbolic constants for the [`confstr\(\)`](#) function:

`_CS_PATH`

This is the value for the `PATH` environment variable that finds all of the standard utilities that are provided in a manner accessible via the `exec` family of functions.

`_CS_POSIX_V7_ILP32_OFF32_CFLAGS`

If `sysconf(_SC_V7_ILP32_OFF32)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of initial options to be given to the [`c99`](#) utility to build an application using a programming model with 32-bit **int**, **long**, **pointer**, and **off_t** types.

`_CS_POSIX_V7_ILP32_OFF32_LDFLAGS`

If `sysconf(_SC_V7_ILP32_OFF32)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of final options to be given to the [`c99`](#) utility to build an application using a programming model with 32-bit **int**, **long**, **pointer**, and **off_t** types.

`_CS_POSIX_V7_ILP32_OFF32_LIBS`

If `sysconf(_SC_V7_ILP32_OFF32)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of libraries to be given to the [`c99`](#) utility to build an application using a programming model with 32-bit **int**, **long**, **pointer**, and **off_t** types.

`_CS_POSIX_V7_ILP32_OFFBIG_CFLAGS`

If `sysconf(_SC_V7_ILP32_OFFBIG)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of initial options to be given to the [`c99`](#) utility to build an application using a programming model with 32-bit **int**, **long**, and **pointer** types, and an **off_t** type using at least 64 bits.

`_CS_POSIX_V7_ILP32_OFFBIG_LDFLAGS`

If `sysconf(_SC_V7_ILP32_OFFBIG)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of final options to be given to the [`c99`](#) utility to build an application using a programming model with 32-bit **int**, **long**, and **pointer** types, and an **off_t** type using at least 64 bits.

`_CS_POSIX_V7_ILP32_OFFBIG_LIBS`

If `sysconf(_SC_V7_ILP32_OFFBIG)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of libraries to be given to the [`c99`](#) utility to build an application using a programming model with 32-bit **int**, **long**, and **pointer** types, and an **off_t** type using at least 64 bits.

`_CS_POSIX_V7_LP64_OFF64_CFLAGS`

If `sysconf(_SC_V7_LP64_OFF64)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of initial options to be given to the [`c99`](#) utility to build an application using a programming model with 32-bit **int** and 64-bit **long**, **pointer**, and **off_t** types.

`_CS_POSIX_V7_LP64_OFF64_LDFLAGS`

If `sysconf(_SC_V7_LP64_OFF64)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of final options to be given to the [`c99`](#) utility to build an application using a programming model with 32-bit **int** and 64-bit **long**, **pointer**, and **off_t** types.

`_CS_POSIX_V7_LP64_OFF64_LIBS`

If `sysconf(_SC_V7_LP64_OFF64)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of libraries to be given to the [`c99`](#) utility to build an application using a programming model with 32-bit **int** and 64-bit **long**, **pointer**, and **off_t** types.

`_CS_POSIX_V7_LPBIG_OFFBIG_CFLAGS`

If `sysconf(_SC_V7_LPBIG_OFFBIG)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of initial options to be given to the [`c99`](#) utility to build an application using a programming model with an **int** type using at least 32 bits and **long**, **pointer**, and **off_t** types using at least 64 bits.

`_CS_POSIX_V7_LPBIG_OFFBIG_LDFLAGS`

If `sysconf(_SC_V7_LPBIG_OFFBIG)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of final options to be given to the [`c99`](#) utility to build an application using a programming model with an **int** type using at least 32 bits and **long**, **pointer**, and **off_t** types using at least 64 bits.

`_CS_POSIX_V7_LPBIG_OFFBIG_LIBS`

If `sysconf(_SC_V7_LPBIG_OFFBIG)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of libraries to be given to the [`c99`](#) utility to build

an application using a programming model with an **int** type using at least 32 bits and **long**, **pointer**, and **off_t** types using at least 64 bits.

_CS_POSIX_V7_THREADS_CFLAGS

If `sysconf(_SC_POSIX_THREADS)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of initial options to be given to the [c99](#) utility to build a multi-threaded application. These flags are in addition to those associated with any of the other `_CS_POSIX_V7*_CFLAGS` values used to specify particular type size programming environments.

_CS_POSIX_V7_THREADS_LDFLAGS

If `sysconf(_SC_POSIX_THREADS)` returns -1, the meaning of this value is unspecified. Otherwise, this value is the set of final options to be given to the [c99](#) utility to build a multi-threaded application. These flags are in addition to those associated with any of the other `_CS_POSIX_V7*_LDFLAGS` values used to specify particular type size programming environments.

_CS_POSIX_V7_WIDTH_RESTRICTED_ENVS

This value is a <newline>-separated list of names of programming environments supported by the implementation in which the widths of the **blksize_t**, **cc_t**, **mode_t**, **nfds_t**, **pid_t**, **ptrdiff_t**, **size_t**, **speed_t**, **ssize_t**, **suseconds_t**, **tcflag_t**, **wchar_t**, and **wint_t** types are no greater than the width of type **long**. The format of each name shall be suitable for use with the [getconf](#) -v option.

_CS_V7_ENV

This is the value that provides the environment variable information (other than that provided by `_CS_PATH`) that is required by the implementation to create a conforming environment, as described in the implementation's conformance documentation.

[08] ☒ The following symbolic constants are reserved for compatibility with Issue 6:

_CS_POSIX_V6_ILP32_OFF32_CFLAGS
_CS_POSIX_V6_ILP32_OFF32_LDFLAGS
_CS_POSIX_V6_ILP32_OFF32_LIBS
_CS_POSIX_V6_ILP32_OFFBIG_CFLAGS
_CS_POSIX_V6_ILP32_OFFBIG_LDFLAGS
_CS_POSIX_V6_ILP32_OFFBIG_LIBS
_CS_POSIX_V6_LP64_OFF64_CFLAGS
_CS_POSIX_V6_LP64_OFF64_LDFLAGS
_CS_POSIX_V6_LP64_OFF64_LIBS
_CS_POSIX_V6_LPBIG_OFFBIG_CFLAGS
_CS_POSIX_V6_LPBIG_OFFBIG_LDFLAGS
_CS_POSIX_V6_LPBIG_OFFBIG_LIBS
_CS_POSIX_V6_WIDTH_RESTRICTED_ENVS
_CS_V6_ENV

☒

The <unistd.h> header shall define `SEEK_CUR`, `SEEK_END`, and `SEEK_SET` as described in [<stdio.h>](#).

[XS1] ☒ The <unistd.h> header shall define the following symbolic constants as possible values for the *function* argument to the [lockf\(\)](#) function:

F_LOCK

Lock a section for exclusive use.

F_TEST

Test section for locks by other processes.

F_TLOCK

Test and lock a section for exclusive use.

F_ULOCK

Unlock locked sections.

☒

The <unistd.h> header shall define the following symbolic constants for [pathconf\(\)](#):

_PC_2_SYMLINKS

```

_PC_ALLOC_SIZE_MIN
_PC_ASYNC_IO
_PC_CHOWN_RESTRICTED
_PC_FILESIZEBITS
_PC_LINK_MAX
_PC_MAX_CANON
_PC_MAX_INPUT
_PC_NAME_MAX
_PC_NO_TRUNC
_PC_PATH_MAX
_PC_PIPE_BUF
_PC_PRIO_IO
_PC_REC_INCR_XFER_SIZE
_PC_REC_MAX_XFER_SIZE
_PC_REC_MIN_XFER_SIZE
_PC_REC_XFER_ALIGN
_PC_SYMLINK_MAX
_PC_SYNC_IO
_PC_TIMESTAMP_RESOLUTION
_PC_VDISABLE

```

The `<unistd.h>` header shall define the following symbolic constants for [`sysconf\(\)`](#):

```

_SC_2_C_BIND
_SC_2_C_DEV
_SC_2_CHAR_TERM
_SC_2_FORT_DEV
_SC_2_FORT_RUN
_SC_2_LOCALEDEF
_SC_2_PBS
_SC_2_PBS_ACCOUNTING
_SC_2_PBS_CHECKPOINT
_SC_2_PBS_LOCATE
_SC_2_PBS_MESSAGE
_SC_2_PBS_TRACK
_SC_2_SW_DEV
_SC_2_UPE
_SC_2_VERSION
_SC_ADVISORY_INFO
_SC_AIO_LISTIO_MAX
_SC_AIO_MAX
_SC_AIO_PRIO_DELTA_MAX
_SC_ARG_MAX
_SC_ASYNCHRONOUS_IO
_SC_ATEXIT_MAX
_SC_BARRIERS
_SC_BC_BASE_MAX
_SC_BC_DIM_MAX
_SC_BC_SCALE_MAX
_SC_BC_STRING_MAX
_SC_CHILD_MAX
_SC_CLK_TCK
_SC_CLOCK_SELECTION
_SC_COLL_WEIGHTS_MAX
_SC_CPUTIME
_SC_DELAYTIMER_MAX
_SC_EXPR_NEST_MAX
_SC_FSYNC
_SC_GETGR_R_SIZE_MAX
_SC_GETPW_R_SIZE_MAX
_SC_HOST_NAME_MAX
_SC_IOV_MAX
_SC_IPV6
_SC_JOB_CONTROL

```

```
_SC_LINE_MAX
_SC_LOGIN_NAME_MAX
_SC_MAPPED_FILES
_SC_MEMLOCK
_SC_MEMLOCK_RANGE
_SC_MEMORY_PROTECTION
_SC_MESSAGE_PASSING
_SC_MONOTONIC_CLOCK
_SC_MQ_OPEN_MAX
_SC_MQ_PRIO_MAX
_SC_NGROUPS_MAX
_SC_OPEN_MAX
_SC_PAGE_SIZE
_SC_PAGESIZE
_SC_PRIORITIZED_IO
_SC_PRIORITY_SCHEDULING
_SC_RAW_SOCKETS
_SC_RE_DUP_MAX
_SC_READER_WRITER_LOCKS
_SC_REALTIME_SIGNALS
_SC_REGEX
_SC_RTSIG_MAX
_SC_SAVED_IDS
_SC_SEM_NSEMS_MAX
_SC_SEM_VALUE_MAX
_SC_SEMAPHORES
_SC_SHARED_MEMORY_OBJECTS
_SC_SHELL
_SC_SIGQUEUE_MAX
_SC_SPAWN
_SC_SPIN_LOCKS
_SC_SPARADIC_SERVER
_SC_SS_REPL_MAX
_SC_STREAM_MAX
_SC_SYMLINK_MAX
_SC_SYNCHRONIZED_IO
_SC_THREAD_ATTR_STACKADDR
_SC_THREAD_ATTR_STACKSIZE
_SC_THREAD_CPUTIME
_SC_THREAD_DESTRUCTOR_ITERATIONS
_SC_THREAD_KEYS_MAX
_SC_THREAD_PRIO_INHERIT
_SC_THREAD_PRIO_PROTECT
_SC_THREAD_PRIORITY_SCHEDULING
_SC_THREAD_PROCESS_SHARED
_SC_THREAD_ROBUST_PRIO_INHERIT
_SC_THREAD_ROBUST_PRIO_PROTECT
_SC_THREAD_SAFE_FUNCTIONS
_SC_THREAD_SPARADIC_SERVER
_SC_THREAD_STACK_MIN
_SC_THREAD_THREADS_MAX
_SC_THREADS
_SC_TIMEOUTS
_SC_TIMER_MAX
_SC_TIMERS
_SC_TRACE
_SC_TRACE_EVENT_FILTER
_SC_TRACE_EVENT_NAME_MAX
_SC_TRACE_INHERIT
_SC_TRACE_LOG
_SC_TRACE_NAME_MAX
_SC_TRACE_SYS_MAX
_SC_TRACE_USER_EVENT_MAX
_SC_TTY_NAME_MAX
_SC_TYPED_MEMORY_OBJECTS
```

```

_SC_TZNAME_MAX
_SC_V7_ILP32_OFF32
_SC_V7_ILP32_OFFBIG
_SC_V7_LP64_OFF64
_SC_V7_LPBIG_OFFBIG
[OB]
_SC_V6_ILP32_OFF32
_SC_V6_ILP32_OFFBIG
_SC_V6_LP64_OFF64
_SC_V6_LPBIG_OFFBIG
<X
_SC_VERSION
_SC_XOPEN_CRYPT
_SC_XOPEN_ENH_I18N
_SC_XOPEN_REALTIME
_SC_XOPEN_REALTIME_THREADS
_SC_XOPEN_SHM
_SC_XOPEN_STREAMS
_SC_XOPEN_UNIX
_SC_XOPEN_UUCP
_SC_XOPEN_VERSION

```

The two constants `_SC_PAGESIZE` and `_SC_PAGE_SIZE` may be defined to have the same value.

The `<unistd.h>` header shall define the following symbolic constants for file streams:

```

STDERR_FILENO
    File number of stderr; 2.
STDIN_FILENO
    File number of stdin; 0.
STDOUT_FILENO
    File number of stdout; 1.

```

The `<unistd.h>` header shall define the following symbolic constant for terminal special character handling:

```

_POSIX_VDISABLE
    This symbol shall be defined to be the value of a character that shall disable terminal
    special character handling as described in Special Control Characters. This symbol
    shall always be set to a value other than -1.

```

Type Definitions

The `<unistd.h>` header shall define the `size_t`, `ssize_t`, `uid_t`, `gid_t`, `off_t`, and `pid_t` types as described in [<sys/types.h>](#).

The `<unistd.h>` header shall define the `intptr_t` type as described in [<stdint.h>](#).

Declarations

The following shall be declared as functions and may also be defined as macros. Function prototypes shall be provided.

```

int      access(const char *, int);
unsigned alarm(unsigned);
int      chdir(const char *);
int      chown(const char *, uid_t, gid_t);
int      close(int);
size_t   confstr(int, char *, size_t);
[XSI]
char      *crypt(const char *, const char *);
<X


```

```


int      dup(int);

int      dup2(int, int);
void     _exit(int);
[XSI]
void     encrypt(char [64], int);
<X>
int      execl(const char *, const char *, ...);
int      execl_e(const char *, const char *, ...);
int      execlp(const char *, const char *, ...);
int      execv(const char *, char *const []);
int      execve(const char *, char *const [], char *const []);
int      execvp(const char *, char *const []);
int      faccessat(int, const char *, int, int);
int      fchdir(int);
int      fchown(int, uid_t, gid_t);
int      fchownat(int, const char *, uid_t, gid_t, int);
[SIO]
int      fdatsync(int);
<X>
int      fexecve(int, char *const [], char *const []);
pid_t    fork(void);
long     fpathconf(int, int);
[FSC]
int      fsync(int);
<X>
int      ftruncate(int, off_t);
char     *getcwd(char *, size_t);
gid_t    getegid(void);
uid_t    geteuid(void);
gid_t    getgid(void);
int      getgroups(int, gid_t []);
[XSI]
long     gethostid(void);
<X>
int      gethostname(char *, size_t);
char     *getlogin(void);
int      getlogin_r(char *, size_t);
int      getopt(int, char * const [], const char *);
pid_t    getpgid(pid_t);
pid_t    getpgrp(void);
pid_t    getpid(void);
pid_t    getppid(void);
pid_t    getsid(pid_t);
uid_t    getuid(void);
int      isatty(int);
int      lchown(const char *, uid_t, gid_t);
int      link(const char *, const char *);
int      linkat(int, const char *, int, const char *, int);
[XSI]
int      lockf(int, int, off_t);
<X>
off_t    lseek(int, off_t, int);

```









[XSI] 

```



int      nice(int);

long     pathconf(const char *, int);
int      pause(void);
int      pipe(int [2]);
ssize_t  pread(int, void *, size_t, off_t);
ssize_t  pwrite(int, const void *, size_t, off_t);
ssize_t  read(int, void *, size_t);
ssize_t  readlink(const char *restrict, char *restrict, size_t);
ssize_t  readlinkat(int, const char *restrict, char *restrict, size_t);
int      rmdir(const char *);
int      setegid(gid_t);
int      seteuid(uid_t);
int      setgid(gid_t);

```

```

int      setpgid(pid_t, pid_t);
[OB XSI] 
pid_t    setpgrp(void);

[XSI] 
int      setregid(gid_t, gid_t);
int      setreuid(uid_t, uid_t);

pid_t    setsid(void);
int      setuid(uid_t);
unsigned sleep(unsigned);
[XSI] 
void     swab(const void *restrict, void *restrict, ssize_t);

int      symlink(const char *, const char *);
int      symlinkat(const char *, int, const char *);
[XSI] 
void     sync(void);

long     sysconf(int);
pid_t    tcgetpgrp(int);
int      tcsetpgrp(int, pid_t);
int      truncate(const char *, off_t);
char     *ttyname(int);
int      ttyname_r(int, char *, size_t);
int      unlink(const char *);
int      unlinkat(int, const char *, int);
ssize_t  write(int, const void *, size_t);

```

[OB]  Implementations may also include the [pthread_atfork\(\)](#) prototype as defined in [<pthread.h>](#). Implementations may also include the [ctermid\(\)](#) prototype as defined in [<stdio.h>](#). 

The <unistd.h> header shall declare the following external variables:

```

extern char *optarg;
extern int  opterr, optind, optopt;

```


Inclusion of the `<unistd.h>` header may make visible all symbols from the headers [`<stddef.h>`](#), [`<stdint.h>`](#), and [`<stdio.h>`](#).

The following sections are informative.

APPLICATION USAGE

POSIX.1-2017 only describes the behavior of systems that claim conformance to it. However, application developers who want to write applications that adapt to other versions of this standard (or to systems that do not conform to any POSIX standard) may find it useful to code them so as to conditionally compile different code depending on the value of `_POSIX_VERSION`, for example:

```
#if _POSIX_VERSION >= 200112L
/* Use the newer function that copes with large files. */
off_t pos=ftello(fp);
#else
/* Either this is an old version of POSIX, or _POSIX_VERSION is
   not even defined, so use the traditional function. */
long pos=ftell(fp);
#endif
```

Earlier versions of POSIX.1-2017 and of the Single UNIX Specification can be identified by the following macros:

```
POSIX.1-1988 standard
    _POSIX_VERSION==198808L
POSIX.1-1990 standard
    _POSIX_VERSION==199009L
ISO POSIX-1:1996 standard
    _POSIX_VERSION==199506L
Single UNIX Specification, Version 1
    _XOPEN_UNIX and _XOPEN_VERSION==4
Single UNIX Specification, Version 2
    _XOPEN_UNIX and _XOPEN_VERSION==500
ISO POSIX-1:2001 and Single UNIX Specification, Version 3
    _POSIX_VERSION==200112L, plus (if the XSI option is supported) _XOPEN_UNIX and
    _XOPEN_VERSION==600
```

POSIX.1-2017 does not make any attempt to define application binary interaction with the underlying operating system. However, application developers may find it useful to query `_SC_VERSION` at runtime via [`sysconf\(\)`](#) to determine whether the current version of the operating system supports the necessary functionality as in the following program fragment:

```
if (sysconf(_SC_VERSION) < 200809L) {
    fprintf(stderr, "POSIX.1-2008 system required, terminating \n");
    exit(1);
}
```

New applications should not use `_XOPEN_SHM` or `_XOPEN_ENH_I18N`.

RATIONALE

As POSIX.1-2017 evolved, certain options became sufficiently standardized that it was concluded that simply requiring one of the option choices was simpler than retaining the option. However, for backwards-compatibility, the option flags (with required constant values) are retained.

Version Test Macros

The standard developers considered altering the definition of `_POSIX_VERSION` and removing `_SC_VERSION` from the specification of [sysconf\(\)](#) since the utility to an application was deemed by some to be minimal, and since the implementation of the functionality is potentially problematic. However, they recognized that support for existing application binaries is a concern to manufacturers, application developers, and the users of implementations conforming to POSIX.1-2017.

While the example using `_SC_VERSION` in the APPLICATION USAGE section does not provide the greatest degree of imaginable utility to the application developer or user, it is arguably better than a **core** file or some other equally obscure result. (It is also possible for implementations to encode and recognize application binaries compiled in various POSIX.1-conforming environments, and modify the semantics of the underlying system to conform to the expectations of the application.) For the reasons outlined in the preceding paragraphs and in the APPLICATION USAGE section, the standard developers elected to retain the `_POSIX_VERSION` and `_SC_VERSION` functionality.

Compile-Time Symbolic Constants for System-Wide Options

POSIX.1-2017 includes support in certain areas for the newly adopted policy governing options and stubs.

This policy provides flexibility for implementations in how they support options. It also specifies how conforming applications can adapt to different implementations that support different sets of options. It allows the following:

1. If an implementation has no interest in supporting an option, it does not have to provide anything associated with that option beyond the announcement that it does not support it.
2. An implementation can support a partial or incompatible version of an option (as a non-standard extension) as long as it does not claim to support the option.
3. An application can determine whether the option is supported. A strictly conforming application must check this announcement mechanism before first using anything associated with the option.

There is an important implication of this policy. POSIX.1-2017 cannot dictate the behavior of interfaces associated with an option when the implementation does not claim to support the option. In particular, it cannot require that a function associated with an unsupported option will fail if it does not perform as specified. However, this policy does not prevent a standard from requiring certain functions to always be present, but that they shall always fail on some implementations. The [setpgid\(\)](#) function in the POSIX.1-1990 standard, for example, is considered appropriate.

The POSIX standards include various options, and the C-language binding support for an option implies that the implementation must supply data types and function interfaces. An application must be able to discover whether the implementation supports each option.

Any application must consider the following three cases for each option:

1. Option never supported.

The implementation advertises at compile time that the option will never be supported. In this case, it is not necessary for the implementation to supply any of the data types or function interfaces that are provided only as part of the option. The implementation might provide data types and functions that are similar to those defined by POSIX.1-2017, but there is no guarantee for any particular behavior.

2. Option always supported.

The implementation advertises at compile time that the option will always be supported. In this case, all data types and function interfaces shall be available and shall operate as specified.

3. Option might or might not be supported.

Some implementations might not provide a mechanism to specify support of options at compile time. In addition, the implementation might be unable or unwilling to specify support or non-support

at compile time. In either case, any application that might use the option at runtime must be able to compile and execute. The implementation must provide, at compile time, all data types and function interfaces that are necessary to allow this. In this situation, there must be a mechanism that allows the application to query, at runtime, whether the option is supported. If the application attempts to use the option when it is not supported, the result is unspecified unless explicitly specified otherwise in POSIX.1-2017.

FUTURE DIRECTIONS

None.

SEE ALSO

[<limits.h>](#), [<stddef.h>](#), [<stdint.h>](#), [<stdio.h>](#), [<sys/socket.h>](#), [<sys/types.h>](#), [<termios.h>](#), [<wctype.h>](#)

XSH [access](#), [alarm](#), [chown](#), [close](#), [confstr](#), [crypt](#), [ctermid](#), [dup](#), [_Exit](#), [encrypt](#), [exec](#), [fchdir](#), [fchown](#), [fdatasync](#), [fork](#), [fpathconf](#), [fsync](#), [ftruncate](#), [getcwd](#), [getegid](#), [geteuid](#), [getgid](#), [getgroups](#), [gethostid](#), [gethostname](#), [getlogin](#), [getopt](#), [getpgid](#), [getpgrp](#), [getpid](#), [getppid](#), [getsid](#), [getuid](#), [isatty](#), [lchown](#), [link](#), [lockf](#), [lseek](#), [nice](#), [pause](#), [pipe](#), [read](#), [readlink](#), [rmdir](#), [setegid](#), [seteuid](#), [setgid](#), [setpgid](#), [setpgrp](#), [setregid](#), [setreuid](#), [setsid](#), [setuid](#), [sleep](#), [swab](#), [symlink](#), [sync](#), [sysconf](#), [tcgetpgrp](#), [tcsetpgrp](#), [truncate](#), [ttyname](#), [unlink](#), [write](#)

CHANGE HISTORY

First released in Issue 1. Derived from Issue 1 of the SVID.

Issue 5

The DESCRIPTION is updated for alignment with the POSIX Realtime Extension and the POSIX Threads Extension.

The symbolic constants `_XOPEN_REALTIME` and `_XOPEN_REALTIME_THREADS` are added. `_POSIX2_C_BIND`, `_XOPEN_ENH_I18N`, and `_XOPEN_SHM` must now be set to a value other than `-1` by a conforming implementation.

Large File System extensions are added.

The type of the argument to `sbrk()` is changed from `int` to `intptr_t`.

`_XBS_` constants are added to the list of constants for Options and Option Groups, to the list of constants for the [confstr\(\)](#) function, and to the list of constants to the [sysconf\(\)](#) function. These are all marked EX.

Issue 6

`_POSIX2_C_VERSION` is removed.

The Open Group Corrigendum U026/4 is applied, adding the prototype for [fdatasync\(\)](#).

The Open Group Corrigendum U026/1 is applied, adding the symbols `_SC_XOPEN_LEGACY`, `_SC_XOPEN_REALTIME`, and `_SC_XOPEN_REALTIME_THREADS`.

The symbols `_XOPEN_STREAMS` and `_SC_XOPEN_STREAMS` are added to support the XSI STREAMS Option Group.

Text in the DESCRIPTION relating to conformance requirements is moved elsewhere in IEEE Std 1003.1-2001.

The LEGACY symbol `_SC_PASS_MAX` is removed.

The following new requirements on POSIX implementations derive from alignment with the Single UNIX Specification:

- The `_CS_POSIX_*` and `_CS_XBS5_*` constants are added for the [confstr\(\)](#) function.
- The `_SC_XBS5_*` constants are added for the [sysconf\(\)](#) function.
- The symbolic constants `F_ULOCK`, `F_LOCK`, `F_TLOCK`, and `F_TEST` are added.
- The `uid_t`, `gid_t`, `off_t`, `pid_t`, and `useconds_t` types are mandated.

The [gethostname\(\)](#) prototype is added for sockets.

A new section is added for System-Wide Options.

Function prototypes for [setegid\(\)](#) and [seteuid\(\)](#) are added.

Option symbolic constants are added for `_POSIX_ADVISORY_INFO`, `_POSIX_CPUTIME`, `_POSIX_SPAWN`, `_POSIX_SPORADIC_SERVER`, `_POSIX_THREAD_CPUTIME`, `_POSIX_THREAD_SPORADIC_SERVER`, and `_POSIX_TIMEOUTS`, and [pathconf\(\)](#) variables are added for `_PC_ALLOC_SIZE_MIN`, `_PC_REC_INCR_XFER_SIZE`, `_PC_REC_MAX_XFER_SIZE`, `_PC_REC_MIN_XFER_SIZE`, and `_PC_REC_XFER_ALIGN` for alignment with IEEE Std 1003.1d-1999.

The following are added for alignment with IEEE Std 1003.1j-2000:

- Option symbolic constants `_POSIX_BARRIERS`, `_POSIX_CLOCK_SELECTION`, `_POSIX_MONOTONIC_CLOCK`, `_POSIX_READER_WRITER_LOCKS`, `_POSIX_SPIN_LOCKS`, and `_POSIX_TYPED_MEMORY_OBJECTS`
- [sysconf\(\)](#) variables `_SC_BARRIERS`, `_SC_CLOCK_SELECTION`, `_SC_MONOTONIC_CLOCK`, `_SC_READER_WRITER_LOCKS`, `_SC_SPIN_LOCKS`, and `_SC_TYPED_MEMORY_OBJECTS`

The `_SC_XBS5` macros associated with the ISO/IEC 9899:1990 standard are marked LEGACY, and new equivalent `_SC_V6` macros associated with the ISO/IEC 9899:1999 standard are introduced.

The [getwd\(\)](#) function is marked LEGACY.

The **restrict** keyword is added to the prototypes for [readlink\(\)](#) and [swab\(\)](#).

Constants for options are now harmonized, so when supported they take the year of approval of IEEE Std 1003.1-2001 as the value.

The following are added for alignment with IEEE Std 1003.1q-2000:

- Optional symbolic constants `_POSIX_TRACE`, `_POSIX_TRACE_EVENT_FILTER`, `_POSIX_TRACE_LOG`, and `_POSIX_TRACE_INHERIT`
- The [sysconf\(\)](#) symbolic constants `_SC_TRACE`, `_SC_TRACE_EVENT_FILTER`, `_SC_TRACE_LOG`, and `_SC_TRACE_INHERIT`

The [brk\(\)](#) and [sbrk\(\)](#) LEGACY functions are removed.

The Open Group Base Resolution bwg2001-006 is applied, which reworks the XSI versioning information.

The Open Group Base Resolution bwg2001-008 is applied, changing the *namelen* parameter for [gethostname\(\)](#) from `socklen_t` to `size_t`.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/2 is applied, changing ``Thread Stack Address Size'' to ``Thread Stack Size Attribute''.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/20 is applied, adding the `_POSIX_IPV6`, `_SC_V6`, and `_SC_RAW_SOCKETS` symbols.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/21 is applied, correcting the description in ``Constants for Functions'' for the `_CS_POSIX_V6_LP64_OFF64_CFLAGS`, `_CS_POSIX_V6_LP64_OFF64_LDFLAGS`, and `_CS_POSIX_V6_LP64_OFF64_LIBS` symbols.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/22 is applied, removing the shading for the `_PC*` and `_SC*` constants, since these are mandatory on all implementations.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/23 is applied, adding the `_PC_SYMLINK_MAX` and `_SC_SYMLINK_MAX` constants.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/24 is applied, correcting the shading and margin code for the [fsync\(\)](#) function.

IEEE Std 1003.1-2001/Cor 1-2002, item XBD/TC1/D6/25 is applied, adding the following text to the APPLICATION USAGE section: ``New applications should not use _XOPEN_SHM or _XOPEN_ENH_I18N.'`'.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/29 is applied, clarifying the requirements for when constants for Options and Option Groups can be defined or undefined.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/30 is applied, changing the _V6_ILP32_OFF32, _V6_ILP32_OFFBIG, _V6_LP64_OFF64, and _V6_LPBIG_OFFBIG symbols to _POSIX_V6_ILP32_OFF32, _POSIX_V6_ILP32_OFFBIG, _POSIX_V6_LP64_OFF64, and _POSIX_V6_LPBIG_OFFBIG, respectively. This is for consistency with the [sysconf\(\)](#) and [c99](#) reference pages.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/31 is applied, adding that the format of names of programming environments can be obtained using the [getconf -v](#) option.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/32 is applied, deleting the _SC_FILE_LOCKING, _SC_2_C_VERSION, and _SC_XOPEN_XCU_VERSION constants.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/33 is applied, adding _SC_SS_REPL_MAX, _SC_TRACE_EVENT_NAME_MAX, _SC_TRACE_NAME_MAX, _SC_TRACE_SYS_MAX, and _SC_TRACE_USER_EVENT_MAX to the list of symbolic constants for [sysconf\(\)](#).

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/34 is applied, updating the prototype for the [symlink\(\)](#) function to match that in the System Interfaces volume of IEEE Std 1003.1-2001.

IEEE Std 1003.1-2001/Cor 2-2004, item XBD/TC2/D6/35 is applied, adding _PC_2_SYMLINKS to the symbolic constants list for [pathconf\(\)](#). This corresponds to the definition of POSIX2_SYMLINKS in the Shell and Utilities volume of IEEE Std 1003.1-2001.

Issue 7

Austin Group Interpretations 1003.1-2001 #026 and #047 are applied.

Austin Group Interpretation 1003.1-2001 #166 is applied to permit an additional compiler flag to enable threads.

Austin Group Interpretation 1003.1-2001 #178 is applied, clarifying the values allowed for _POSIX2_CHAR_TERM.

SD5-XBD-ERN-41 is applied, adding the _POSIX2_SYMLINKS constant.

SD5-XBD-ERN-76 and SD5-XBD-ERN-77 are applied.

Symbols to support the UUCP Utilities option are added.

The variables for the supported programming environments are updated to be V7.

The LEGACY and obsolescent symbols are removed.

The [faccessat\(\)](#), [fchownat\(\)](#), [fexecve\(\)](#), [linkat\(\)](#), [readlinkat\(\)](#), [symlinkat\(\)](#), and [unlinkat\(\)](#) functions are added from The Open Group Technical Standard, 2006, Extended API Set Part 2.

The _POSIX_TRACE* constants from the Trace option are marked obsolescent.

The _POSIX2_PBS* constants from the Batch Environment Services and Utilities option are marked obsolescent.

Functionality relating to the Asynchronous Input and Output, Barriers, Clock Selection, Memory Mapped Files, Memory Protection, Realtime Signals Extension, Semaphores, Spin Locks, Threads, Timeouts, and Timers options is moved to the Base.

Functionality relating to the Thread Priority Protection and Thread Priority Inheritance options is changed to be Non-Robust Mutex or Robust Mutex Priority Protection and Non-Robust Mutex or Robust Mutex Priority Inheritance, respectively.

This reference page is clarified with respect to macros and symbolic constants.

Changes are made related to support for finegrained timestamps and the
_POSIX_TIMESTAMP_RESOLUTION constant is added.

The _SC_THREAD_ROBUST_PRIO_INHERIT and _SC_THREAD_ROBUST_PRIO_PROTECT symbolic constants are added.

POSIX.1-2008, Technical Corrigendum 1, XBD/TC1-2008/0078 [311], XBD/TC1-2008/0079 [209], and XBD/TC1-2008/0080 [360] are applied.

POSIX.1-2008, Technical Corrigendum 2, XBD/TC2-2008/0085 [783], XBD/TC2-2008/0086 [911], and XBD/TC2-2008/0087 [566] are applied.

End of informative text.

[return to top of page](#)

UNIX ® is a registered Trademark of The Open Group.
POSIX™ is a Trademark of The IEEE.
Copyright © 2001-2018 IEEE and The Open Group, All Rights Reserved
[[Main Index](#) | [XBD](#) | [XSH](#) | [XCU](#) | [XRAT](#)]

[<<< Previous](#)

[Home](#)

[Next >>>](#)
