

getpgrp - Man Page

получить идентификатор группы процессов вызывающего процесса

Пролог

Эта страница руководства является частью Руководства программиста POSIX. Реализация этого интерфейса в Linux может отличаться (обратитесь к соответствующей странице руководства Linux для получения подробной информации о поведении Linux), или интерфейс может быть не реализован в Linux.

Синопсис

```
#include <unistd.h>
```

```
pid_t getpgrp(void);
```

Описание

Функция *getpgrp()* возвращает идентификатор группы процессов вызывающего процесса.

Возвращаемое значение

Функция *getpgrp()* всегда должна быть успешной, и возвращаемое значение не зарезервировано для указания ошибки.

Ошибки

Ошибки не определены.

getpgrp - Man Page

Примеры

Нет.

Применение

Нет.

Обоснование

4.3 BSD предоставляет функцию *getpgrp()*, которая возвращает идентификатор группы процессов для указанного процесса. Хотя эта функция поддерживает управление заданиями, все известные оболочки управления заданиями всегда указывают вызывающий процесс с этой функцией. Таким образом, достаточно более простой системы V *getpgrp()*, а дополнительная сложность 4.3 BSD *getpgrp()* обеспечивается расширением XSI *getpgid()* .

Будущие направления

Нет.

См . также

исполнитель, *fork()*, *getpgid()*, *getpid()*, *getppid()*, *убить()*,
setpgid(), *setsid()*

The Base Definitions volume of POSIX.1-2017, *<sys_types.h>*, *<unistd.h>*

getpgrp - Man Page

Portions of this text are reprinted and reproduced in electronic form from IEEE Std 1003.1-2017, Standard for Information Technology -- Portable Operating System Interface (POSIX), The Open Group Base Specifications Issue 7, 2018 Edition, Copyright (C) 2018 by the Institute of Electrical and Electronics Engineers, Inc and The Open Group. In the event of any discrepancy between this version and the original IEEE and The Open Group Standard, the original IEEE and The Open Group Standard is the referee document. The original Standard can be obtained online at <http://www.opengroup.org/unix/online.html> .

Any typographical or formatting errors that appear in this page are most likely to have been introduced during the conversion of the source files to man page format. To report such errors, see https://www.kernel.org/doc/man-pages/reporting_bugs.html .

Referenced By

`getpgid(3p)`, `getpid(3p)`, `getppid(3p)`, `setpgid(3p)`, `unistd.h(0p)`.

2017 IEEE/The Open Group POSIX Programmer's Manual

getpgrp - Man Page

[Главная](#) [Блог](#) [0 нас](#)