

chdir - Man Page

change working directory

Prolog

This manual page is part of the POSIX Programmer's Manual. The Linux implementation of this interface may differ (consult the corresponding Linux manual page for details of Linux behavior), or the interface may not be implemented on Linux.

Synopsis

```
#include <unistd.h>
```

```
int chdir(const char *path);
```

Description

The `chdir()` function shall cause the directory named by the pathname pointed to by the `path` argument to become the current working directory; that is, the starting point for path searches for pathnames not beginning with '/'.

Return Value

Upon successful completion, 0 shall be returned. Otherwise, -1 shall be returned, the current working directory shall remain unchanged, and `errno` shall be set to indicate the error.

Errors

The `chdir()` function shall fail if:

EACCES

Search permission is denied for any component of the pathname.

ELOOP

A loop exists in symbolic links encountered during resolution of the `path` argument.

ENAMETOOLONG

The length of a component of a pathname is longer than {NAME_MAX}.

ENOENT

A component of `path` does not name an existing directory or `path` is an empty string.

ENOTDIR

chdir - Man Page

The `chdir()` function may fail if:

ELOOP

More than {SYMLINK_MAX} symbolic links were encountered during resolution of the *path* argument.

ENAMETOOLONG

The length of a pathname exceeds {PATH_MAX}, or pathname resolution of a symbolic link produced an intermediate result with a length that exceeds {PATH_MAX}.

The following sections are informative.

Examples

Changing the Current Working Directory

The following example makes the value pointed to by **directory**, `/tmp`, the current working directory.

```
#include <unistd.h>
...
char *directory = "/tmp";
int ret;

ret = chdir (directory);
```

Application Usage

None.

Rationale

The `chdir()` function only affects the working directory of the current process.

Future Directions

None.

See Also

[getcwd\(\)](#)

The Base Definitions volume of POSIX.1-2017, [<unistd.h>](#)

chdir - Man Page

Portions of this text are reprinted and reproduced in electronic form from IEEE Std 1003.1-2017, Standard for Information Technology -- Portable Operating System Interface (POSIX), The Open Group Base Specifications Issue 7, 2018 Edition, Copyright (C) 2018 by the Institute of Electrical and Electronics Engineers, Inc and The Open Group. In the event of any discrepancy between this version and the original IEEE and The Open Group Standard, the original IEEE and The Open Group Standard is the referee document. The original Standard can be obtained online at <http://www.opengroup.org/unix/online.html> .

Any typographical or formatting errors that appear in this page are most likely to have been introduced during the conversion of the source files to man page format. To report such errors, see https://www.kernel.org/doc/man-pages/reporting_bugs.html .

Referenced By

`cd(1p)`, `fchdir(3p)`.

2017 IEEE/The Open Group POSIX Programmer's Manual

chdir - Man Page

[Home](#) [Blog](#) [About](#)