

# getgid - Man Page

*get the real group ID*

## Prolog

This manual page is part of the POSIX Programmer's Manual. The Linux implementation of this interface may differ (consult the corresponding Linux manual page for details of Linux behavior), or the interface may not be implemented on Linux.

## Synopsis

```
#include <unistd.h>
```

```
gid_t getgid(void);
```

## Description

The *getgid()* function shall return the real group ID of the calling process. The *getgid()* function shall not modify *errno*.

## Return Value

The *getgid()* function shall always be successful and no return value is reserved to indicate an error.

## Errors

No errors are defined.

*The following sections are informative.*

# getgid - Man Page

None.

## Application Usage

None.

## Rationale

In a conforming environment, *getgid()* will always succeed. It is possible for implementations to provide an extension where a process in a non-conforming environment will not be associated with a user or group ID. It is recommended that such implementations return (**gid\_t**)-1 and set *errno* to indicate such an environment; doing so does not violate this standard, since such an environment is already an extension.

## Future Directions

None.

## See Also

`getegid()`, `geteuid()`, `getuid()`, `setegid()`, `seteuid()`, `setgid()`,  
`setregid()`, `setreuid()`, `setuid()`

The Base Definitions volume of POSIX.1-2017, `<sys_types.h>`, `<unistd.h>`

## Copyright

# getgid - Man Page

PORTABLE OPERATING SYSTEM INTERFACE (POSIX), THE OPEN GROUP BASE SPECIFICATIONS ISSUE 7, 2018 EDITION, Copyright (C) 2018 by the Institute of Electrical and Electronics Engineers, Inc and The Open Group. In the event of any discrepancy between this version and the original IEEE and The Open Group Standard, the original IEEE and The Open Group Standard is the referee document. The original Standard can be obtained online at <http://www.opengroup.org/unix/online.html> .

Any typographical or formatting errors that appear in this page are most likely to have been introduced during the conversion of the source files to man page format. To report such errors, see [https://www.kernel.org/doc/man-pages/reporting\\_bugs.html](https://www.kernel.org/doc/man-pages/reporting_bugs.html) .

## Referenced By

getegid(3p), geteuid(3p), getuid(3p), id(1p), setegid(3p), seteuid(3p), setgid(3p), setregid(3p), setreuid(3p), setuid(3p), unistd.h(0p).

2017 IEEE/The Open Group POSIX Programmer's Manual

# getgid - Man Page

[Home](#) [Blog](#) [About](#)