

NAME

poll.h - definitions for the poll() function

SYNOPSIS

```
#include <poll.h>
```

DESCRIPTION

The `<poll.h>` header shall define the **pollfd** structure, which shall include at least the following members:

```
int    fd        The following descriptor being polled.
short  events     The input event flags (see below).
short  revents    The output event flags (see below).
```

The `<poll.h>` header shall define the following type through **typedef**:

nfds_t

An unsigned integer type used for the number of file descriptors.

The implementation shall support one or more programming environments in which the width of **nfds_t** is no greater than the width of type **long**. The names of these programming environments can be obtained using the [`confstr\(\)`](#) function or the [`getconf`](#) utility.

The `<poll.h>` header shall define the following symbolic constants, zero or more of which may be OR'ed together to form the *events* or *revents* members in the **pollfd** structure:

```
POLLIN
    Data other than high-priority data may be read without blocking.
POLLRDNORM
    Normal data may be read without blocking.
POLLRDBAND
    Priority data may be read without blocking.
POLLPRI
    High priority data may be read without blocking.
POLLOUT
    Normal data may be written without blocking.
POLLWRNORM
    Equivalent to POLLOUT.
POLLWRBAND
    Priority data may be written.
POLLERR
    An error has occurred (revents only).
POLLHUP
    Device has been disconnected (revents only).
POLLNVAL
    Invalid fd member (revents only).
```

The significance and semantics of normal, priority, and high-priority data are file and device-specific.

The following shall be declared as a function and may also be defined as a macro. A function prototype shall be provided.

```
int poll(struct pollfd [], nfd_t, int);
```

The following sections are informative.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

XSH [confstr](#), [poll](#)

XCU [getconf](#)

CHANGE HISTORY

First released in Issue 4, Version 2.

Issue 6

The description of the symbolic constants is updated to match the [poll\(\)](#) function.

Text related to STREAMS has been moved to the [poll\(\)](#) reference page.

A note is added to the DESCRIPTION regarding the significance and semantics of normal, priority, and high-priority data.

Issue 7

The <poll.h> header is moved from the XSI option to the Base.

End of informative text.

[return to top of page](#)

UNIX ® is a registered Trademark of The Open Group.
POSIX ™ is a Trademark of The IEEE.
Copyright © 2001-2018 IEEE and The Open Group, All Rights Reserved
[[Main Index](#) | [XBD](#) | [XSH](#) | [XCU](#) | [XRAT](#)]

[<<< Previous](#)

[Home](#)

[Next >>>](#)
