

## Lab 4: Binary Search Tree - AVL Tree

### 1 Binary Tree - Binary Search Tree

Each Node of a Binary (Search) Tree is define as follow:

---

```
struct NODE{
    int key;
    NODE* p_left;
    NODE* p_right;
};
```

---

Students are required to implement the following functions:

1. Initialize a NODE from a given value:

- `NODE* createNode(int data)`

2. Pre-order Traversal:

- `void NLR(NODE* pRoot)`

3. In-order Traversal:

- `void LNR(NODE* pRoot)`

4. Post-order Traversal:

- `void LRN(NODE* pRoot)`

5. Level-order Traversal:

- `void LevelOrder(NODE* pRoot)`

6. Find and return a NODE with given value from a given Binary Search Tree:

- `NODE* Search(NODE* pRoot, int x)`

7. Add a NODE with given value into a given Binary Search Tree:

- `void Insert(NODE* &pRoot, int x)`

8. Remove a NODE with given value from a given Binary Search Tree:

- `void Remove(NODE* &pRoot, int x)`

9. Initialize a Binary Search Tree from a given array:

- `NODE* createTree(int a[])`

10. Completely remove a given Binary Search Tree:

- `void removeTree(Node* &pRoot)`

11. Calculate the height of a given Binary Tree;

- `int Height(NODE* pRoot)`

12. Count the number of NODE from a given Binary Tree:

- `int countNode(NODE* pRoot)`

13. Calculate the total value of all NODEs from a given Binary Tree:

- `int sumNode(NODE* pRoot)`

14. Calculate the height of a NODE with given value: *(return -1 if value not exist)*

- `heightNode(NODE* pRoot, int value)`

15. \* Calculate the level of a given NODE:

- `int Level(NODE* pRoot, NODE* p)`

16. \* Count the number leaves from a given Binary Tree:

- `int countLeaf(NODE* pRoot)`

17. \* Count the number of NODE from a given Binary Search Tree which key value is less than a given value:

- `int countLess(NODE* pRoot, int x)`

18. \* Count the number of NODE from a given Binary Search Tree which key value is greater than a given value:

- `int countGreater(NODE* pRoot, int x)`

19. \* Determine if a given Binary Tree is Binary Search Tree:

- `bool isBST(NODE* pRoot)`

20. \* Determine if a given Binary Tree is a Full Binary Search Tree:

- `bool isFullBST(NODE* pRoot)`

## 2 AVL Tree

Each Node of an AVL Tree is define as follow:

---

```
struct NODE{
    int key;
    NODE* p_left;
    NODE* p_right;
    int height;
};
```

---

Students are required to implement the following functions:

1. Initialize aNODEfrom a given value:

- `NODE* createNode(int data)`

2. Add a NODE with given value into a given AVL tree (Notify if the given value existed):

- `void Insert(NODE* &pRoot, int x)`

3. Remove a NODE with given value from a given AVL Tree(Notify if the given value not existed):

- `void Remove(NODE* &pRoot, int x)`

4. Pre-order Traversal (key and height of NODE is required):

- `void NLR(NODE* pRoot)`

5. In-order Traversal (key and height of NODE is required):

- `void LNR(NODE* pRoot)`

6. Post-order Traversal (key and height of NODE is required):

- `void LRN(NODE* pRoot)`

7. Level-order Traversal (key and height of NODE is required):

- `void LevelOrder(NODE* pRoot)`

8. \* Determine if a given Binary Tree is an AVL Tree:

- `bool isAVL(NODE* pRoot)`