

BUS TRANSIT SERVICE RELIABILITY

Understanding the impacts of overlapping bus service on headway delays and determinants of bus bunching

Ehab Diab*
Robert Bertini**
Ahmed M. El-Geneidy***

* University of Toronto, ** California Polytechnic State University, *** McGill University



ABSTRACT

Transit agencies typically **operate several routes** that overlap with each other in order to offer a better **service coverage** to reach various origins destinations and to make the network more convenient.

This research investigates the impacts of bus **route overlapping** on service **headway delay** and **probability of bunching** at the stop-level of analysis.

The study uses **automatic vehicle location (AVL)** and **automatic passenger count (APC)** systems data collected from TriMet, the public transit provider for Portland, Oregon, USA.

It shows that service **overlapping** can **increase** headway delay, with no impacts on service bunching. It also shows headway delay and bunching as a function of **several variables** that rarely explored in the literature.

INTRODUCTION

The data used in our analyses come from a sample of TriMet's AVL and APC archived data system for a bus-corridor, the **Barbur bus corridor, Route 12**.

Route 12 **overlaps with** several routes, including 1, 38, 54, 55, 56, 64 and 94. Since all of TriMet's buses are **outfitted with** AVL/APC, it was possible to calculate the actual headway between all buses at the stop level.

METHODOLOGY

Over **600,000 individual stop-level** records for Route 12 were collected from the TriMet's dispatch system over a **three month period** between September 1, 2014 and November 28, 2014. Another AVL/APC dataset was obtained for all abovementioned overlapping routes.

In this research, we will focus on developing **two statistical models** to capture the effects of the service overlapping:

The first model is a **headway delay model** used to estimate the effects of bus service overlapping at the stop-level of analysis. Headway delay is the **difference** between **actual and scheduled** headway. **Actual headway** is calculated based on departure times from each bus stop.

We also developed a **bus bunching model** to reveal the potential causes of bus bunching and the impacts of service overlapping. The model focuses on the **first locations** where **bunching began to occur**, as well as one stop that was randomly selected from each trip (i.e., one stop per trip) where no bunching occurred, to serve as controls.

ANALYSIS

1 Headway Delay Model

Variable	Coefficients	t-stat	95% Conf. Interval	
			Lower Bound	Upper Bound
Constant	14.06***	4.05	7.26	20.85
Direction	-7.55***	-9.72	-9.07	-6.03
Barbur Blvd	-2.87***	-3.45	-4.49	-1.24
AM peak	-0.15	-0.13	-2.53	2.23
PM peak	-2.06*	-1.69	-4.44	0.33
Night	5.36***	5.37	3.41	7.32
Midnight and early morning	8.98***	5.60	5.84	12.12
Actual stops made	12.45***	12.62	10.52	14.39
Lift	47.15***	10.13	38.02	56.27
Total passenger activity	14.41***	47.22	13.81	15.01
Total passenger activity^2	-0.05***	-14.97	-0.05	-0.04
Passenger load	2.86***	60.74	2.76	2.95
Friction	0.54***	7.91	0.40	0.67
Headway Delay at the start (s)	0.72***	434.35	0.72	0.73
Distance	-0.01***	-10.24	-0.01	0.00
Stop sequence	0.15***	10.27	0.12	0.18
Stop at Time point	-43.44***	-25.20	-46.82	-40.06
After unscheduled stop	15.73***	15.53	13.75	17.72
Near-side stop	3.53***	3.71	1.66	5.40
Midblock stop	10.13**	9.60	8.06	12.20
Signalized intersection	-4.67***	-4.84	-6.56	-2.78
Reserved lanes in operation	-16.66***	-7.96	-20.76	-12.56
Overlapping trips	3.81**	1.81	-0.31	7.93
Scheduled headway (s)	-0.11***	-22.16	-0.12	-0.10
Scheduled headway^2	0.001***	25.00	0.000	0.001
N		445,316		
R2		0.32		
F statistics		(24, 445291.0)	8,661	
F significance (Prob > F)			0.00	

Bold indicates statistical significance
*** Significant at 99% ** Significant at 95% * Significant at 90%


ANALYSIS

2 Bus Bunching Model

Variable	Coefficient	Z	Odds ratio	95% Conf. Interval	
				Lower Bound	Upper Bound
Constant	-3.795	149.73***	0.022		
Direction	1.004	40.16***	2.730	2.001	3.725
Barbur Blvd	-1.036	40.93***	0.355	0.258	0.488
AM peak	-0.044	0.06	0.957	0.683	1.341
PM peak	-0.027	0.03	0.973	0.713	1.329
Night	-0.444	8.77***	0.642	0.478	0.861
Early morning	-1.933	8.78***	0.145	0.040	0.520
Cumulative passenger activity	-0.029	48.11***	0.971	0.963	0.979
Cumulative passenger activity^2	0.000	26.61***	1.001	1.000	1.001
Delay at the start (s)	-0.003	110.77***	0.997	0.996	0.998
Stop sequence	0.035	85.77***	1.035	1.028	1.043
Overlapping trips	0.519	2.00	1.681	0.819	3.451
Scheduled headway (s)	-0.001	38.36***	0.999	0.998	0.999
B1 delay at the start (s)	0.005	386.59***	1.005	1.004	1.005
B1 cumulative passenger activity	0.020	27.30***	1.020	1.013	1.028
B1 cumulative passenger activity ^2	0.000	1.43	1.000	1.000	1.000
B0 delay at the start (s)	0.000	2.38	1.000	1.000	1.001
B0 cumulative passenger activity	-0.010	6.03**	0.991	0.983	0.998
B0 cumulative passenger activity^2	0.000	9.07***	1.000	1.000	1.001
N		8913.00			
Nagelkerke R Square		0.41			
Log likelihood		2653.15			

Bold indicates statistical significance
*** Significant at 99% ** Significant at 95% * Significant at 90%

3 Sensitivity Analysis



Headway delay in relation to scheduled headway

The models indicate that **service overlapping** increases the headway delay by **3.8 seconds**, and accordingly, contributes to passengers' waiting times. This may be understood due to a few reasons.



Headway delay is also a function of **scheduled headway** between trips. Increasing it would decrease the headway delay to a certain extent. The minimum headway delay occurs at a scheduled headway of **20 minutes** at a given bus stop.

Other variables have **a positive effect** in terms of decreasing headway delay, i.e. bus stop placement, reserved lanes, TSP and time points. E.g., **moving bus stops** from near-side to far-side stops will decrease headway delay by 3.5 seconds.

The models indicate that if the **leader bus (B1)** started late that will increase the odds of bunching for the **current bus (B2)** more than its delay. Thus, agencies should **track delays** at the beginnings of routes to decrease the odds of being bunched for the following trip when it is prevented.

ACKNOWLEDGEMENTS

We would like to acknowledge TriMet for providing the data for this project, especially Miles Crumley and Steve Callas for their support during this project. This research was funded by Natural Sciences and Engineering Research Council of Canada (NSERC). The ideas and findings presented in this paper represent the author's views in an academic exercise.



The figure **illustrates bus bunching**, when the bus in question (B2) moves in front of the bus ahead of it (B1). Thus, for each observation, data from the **previous scheduled trip (B1)** and from the **one prior (B0)** are used to better understand the bus bunching phenomenon.

CONCLUSION

This study aims at evaluating the impact of **overlapping services** on headway delay. It analyzes archived data obtained from TriMet's AVL and APC systems using two statistical models.

The paper shows that service overlapping increases headway delay by **3.8 seconds**, with no impacts on service bunching. Headway delay is also a function of **scheduled headway** between trips. Trips **starting late** increase the odds of bunching for the following trip on schedule more than their delay.