

## **Preliminary Product Specification**

**Module name: C0283QGLD-T**

**Issue date: 2007/12/18**

**Version: 1.7**

<b>Customer</b>		
<b>Approved by Customer</b>		
<b>Approved by CMEL</b>		
<b>PD Division</b>	<b>ENG Division</b>	<b>QA Dept</b>

**Note:**

1. The information contained herein may be change without prior notice. It is therefore advisable to contact Chi MEI ELCorp before designed your product based on this specification.

**Reversion History**

<b>Version</b>	<b>Date</b>	<b>Page</b>	<b>Description</b>
Ver.1.0	2007/11/5	All	Preliminary specification was first issued
Ver.1.1	2007/11/5	13	CIE(Red_y) 0.34->0.33, CIE(Red_y) 0.28->0.29
Ver.1.2	2007/11/7	9	Add Image Data format (CPU Interface)
		11	Add RS expression
		13	Add Image Data format (RGB Interface)
		17~19	Add Capacitance Information
Ver.1.3	2007/11/9	20	Mod External Drawing
Ver.1.4	2007/11/22	22	Mod Packing Drawing
Ver.1.5	2007/11/28	14	Mod Electro-Optical Characteristic, V <sub>gh</sub> /V <sub>gl</sub>
Ver.1.6	2007/12/06	14	Mod Electro-Optical Characteristic
		21	Mod Reliability Test
Ver1.7	2007/12/18	14	Mod Electro-Optical Characteristic, V <sub>gh</sub> /V <sub>gl</sub>

## 1. Purpose:

This documentation defines general product specification for OLED module supplied by CMEL. The information described in this technical specification is tentative. Please Contact CMEL's representative while your product is modified.

## 2. General Description:

- Driving Mode: Active Matrix.
- Color Mode: Full Color (262K color)
- Driver IC: S6E63D6, COG Assembly
- Interface:
  1. MPU i80-system 18-/16-/9-/8-bit bus interface
  2. MPU i68-system 18-/16-/9-/8-bit bus interface
  3. Serial data transfer interface
  4. RGB 18-/16-/6-bit bus interface (DOTCLK, VSYNC, HSYNC, DE, DB17-0)
- Application: Cell phone etc..
- RoHS Compatible

## 3. Mechanical Data:

No.	Items	Specification	Unit
1	Diagonal Size	2.83"	Inch
2	Resolution	240 x RGB x 320	
3	Pixel Pitch	0.060 × 0.180	mm
4	Active Area	43.2 x 57.6	mm
5	Outline Area	49.1 x 67.3	mm
6	Thickness	1.75 (Typ) ; 1.95 (Max)	mm
7	Weight	16	g

#### 4. Absolute Maximum ratings:

(VSS=0V)

Item	Symbol	Unit	Value	Note
Power supply voltage 1	VDD3	V	-0.3 ~ + 5.0	
Power supply voltage 2	VCI	V	-0.3 ~ + 5.0	
Input Voltage range	Vin	V	-0.3 ~ VDD+0.5	
Operating temperature	Topr	C	-20 ~ + 60	
Storage temperature	Tstg	C	-40~ + 85	

**Notes:**

(1) Absolute maximum rating is the limit value. When the IC is exposed operation environment beyond this range, the IC do not assure operations and may be damaged permanently, not be able to be recovered.

(2) Absolute maximum rating is guaranteed only when our company's package used.

## 5. Electrical Characteristic:

### 5.1 DC Characteristic

(Ta = -40℃ ~ 85℃, VSS = 0V)

Characteristic	Symbol	CONDITION	MIN	TYP	MAX	Unit	Note
Driving voltage	VGH	-	3.0	-	8.0	V	
	VGL	-	-8.0	-	-3.0	V	
	VINT	-	-4.0	-	-1.0	V	
Logic Operating Voltage	RVDD	-	1.45	1.5	1.55	V	
Operating frequency	fosc	Frame frequency = 60Hz Display line = 320 line	1161.1	1290.2	1419.3	kHz	
1st booster input voltage	VCI1	-	2.1	-	2.75	V	
1st booster output voltage	VLOUT1	Without load	+4.6	-	+5.5	V	
1st booster output efficiency	VLOUT1	I <sub>VLOUT1_LOAD</sub> = 2.3mA	90	95	-	%	
2nd booster output voltage	VLOUT2	Without load		7.8		V	
2nd booster output efficiency	VLOUT2	I <sub>VLOUT2_LOAD</sub> = 0.1mA	90	93	-	%	
3rd booster output voltage	VLOUT3	Without load	-	-10.6	-	V	
3rd booster output efficiency	VLOUT3	I <sub>VLOUT3_LOAD</sub> = 0.1mA	90	93	-	%	
Source Output voltage deviation (channel to channel)	-	-	-	±5	-	mV	
Source Output voltage difference ( nearest channel)	-	20 Gray Pattern	-	5	-	mV	
Output voltage deviation (Chip to Chip)	-	-	-	±15	-	mV	
Output voltage deviation (Chip to Chip)	-	-	-	±15	-	mV	
Source driver output voltage range	Vso	-	0.3	-	4.2	V	
Driving voltage	dVGH	voltage deviation	-	-	300	mV	
	dVGL	voltage deviation	-	-	300	mV	
Current consumption during normal operation	IVDD3	No load, Ta = 25 °C	-	1.0	5.0	uA	*1
	IVCI		-	3.5	4.0	mA	
Stand by mode current	IVDD3	Ta = 25 °C	-	0.1	5.0	uA	
	IVCI		-	10	20	uA	

Note

1. VDD3=1.8V, VCI=2.8V, fosc=1290.2KHz (320 display line), NL[5:0]="10\_1000", SAP[2:0]="101", DC22[2:0]="100", DC12[2:0]="010", BT[1:0]=10, VC[3:0]="1000", VGH[4:0]="10100", VGL[4:0]="10100", VINT[3:0]="0101"

Characteristic	Symbol	CONDITION	MIN	TYP	MAX	Unit	Note
Power Supply Voltage	VCI	Operating Voltage	2.5	2.8	3.3	V	
Power Supply Voltage	VDD3	I/O supply Voltage	1.65	1.8	3.3	V	
Logic High level input voltage	V <sub>IH</sub>		0.7*VDD3		VDD3	V	
Logic Low level input voltage	V <sub>IL</sub>		0.0		0.3*VDD3	V	
Logic High level output voltage	V <sub>OH</sub>	IOUT = -1mA	0.8*VDD3		VDD3	V	
Logic Low level output voltage	V <sub>OL</sub>	IOUT = +1mA	0.0		0.2*VDD3	V	
Analog High level output voltage	EL_ON <sub>OH</sub>	8uA	1.8		VCI	V	
Analog Low level output voltage	EL_ON <sub>OL</sub>	8uA	0		0.3	V	

**Table 81. DC Characteristics 3**

(VDD3 = 1.65~3.3V, VCI = 2.5~3.3V, Ta = 25℃)


Characteristic	Symbol	CONDITION	MIN	TYP	MAX	Unit	Note
VREG1OUT			4.185	4.2	4.215	V	

## 5.2 AC Characteristic

### 5.2.1 CPU interface M68

(VDD = 1.5V, VDD3 = 1.65 to 3.3V, TA = -40 to +85°C)

Characteristic		Symbol	Specification		Unit
			Min.	Max.	
Cycle time	Write	tCYCW68	85	-	ns
	Read	tCYCR68	500	-	ns
Pulse rise / fall time		tR, tF	-	15	ns
Pulse width low	Write	tWLW68	27.5	-	ns
	Read	tWLR68	250	-	ns
Pulse width high	Write	tWHW68	27.5	-	ns
	Read	tWHR68	250	-	ns
RS,RW to CSB, E setup time		tAS68	10	-	ns
RS,RW to CSB, E hold time		tAH68	2	-	ns
CSB to E time		tCW68	15	-	ns
Write data setup time		tWDS68	40	-	ns
Write data hold time		tWDH68	15	-	ns
Read data delay time		tRDD68	-	200	ns
Read data hold time		tRDH68	5	-	ns




**Note : tWHW68 and tWHR68 are determined by the overlap period of low CSB and high E**

### 5.2.2 CPU interface M80

(VDD = 1.5V, VDD3 = 1.65 to 3.3V, TA = -40 to +85°C)


Characteristic		Symbol	Specification		Unit
			Min.	Max.	
Cycle time	Write	tCYCW80	85	-	ns
	Read	tCYCR80	500	-	ns
Pulse rise / fall time		tR, tF	-	15	ns
Pulse width low	Write	tWLW80	27.5	-	ns
	Read	tWLR80	250	-	ns
Pulse width high	Write	tWHW80	27.5	-	ns
	Read	tWHR80	250	-	ns
RS to CSB, WRB(RDB) setup time		tAS80	10	-	ns
RS to CSB, WRB(RDB) hold time		tAH80	2	-	ns
CSB to WRB(RDB) time		tCW80	15	-	ns
Write data setup time		tWDS80	40	-	ns
Write data hold time		tWDH80	15	-	ns
Read data delay time		tRDD80	-	200	ns
Read data hold time		tRDH80	5	-	ns




**Note : tWLW80 and tWLR80 are determined by the overlap period of low CSB and low WRB or low CSB and low RDB**




### Image Data format for 18bit CPU interface (262k color)



### Image Data format for 16bit CPU interface (65k color)




### Image Data format for 9bit CPU interface (262k color)




### Image Data format for 8bit CPU interface (65K color)


Case 1:



Case 2:




### Image Data format for 8bit CPU interface (262K color)




### 5.2.3 SPI Interface

(VDD = 1.5V, VDD3 = 1.65 to 3.3V, TA = -40 to +85°C)

Characteristic	Symbol	Specification		Unit
		Min.	Max.	
Serial clock write cycle time	tSCYC	130	-	ns
Serial clock read cycle time	tSCYC	250	-	ns
Serial clock rise / fall time	tR, tF	-	15	ns
Pulse width high for write	tSCHW	50	-	ns
Pulse width high for read	tSCHR	110	-	ns
Pulse width low for write	tSCLW	50	-	ns
Pulse width low for read	tSCLR	110	-	ns
Chip select setup time	tCSS	20	-	ns
Chip select hold time	tCSH	60	-	ns
Serial input data setup time	tSIDS	30	-	ns
Serial input data hold time	tSIDH	30	-	ns
Serial output data delay time	tSODD	-	130	ns
Serial output data hold time	tSODH	5	-	ns





(Note) RS="0" : Index data

RS="1" : Instruction data


## 5.2.4 RGB Interface

(VDD = 1.5V, VDD3 = 1.65 to 3.3V, TA = -40 to +85°C)

Characteristic	Symbol	Specification		Unit		Unit
		Min.	Max.	Min.	Max.	
DOTCLK cycle time	tDCYC	100	-	55	-	ns
DOTCLK rise / fall time	tR, tF	-	15	-	15	ns
DOTCLK pulse width high	tDCHW	40	-	25	-	ns
DOTCLK pulse width low	tDCLW	40	-	25	-	ns
Vertical sync setup time	tVSY	30	-	30	-	ns
Vertical sync hold time	tVSYH	30	-	30	-	ns
Horizontal sync setup time	tHSY	30	-	30	-	ns
Horizontal sync hold time	tHSYH	30	-	30	-	ns
ENABLE setup time	tENS	30	-	30	-	ns
ENABLE hold time	tENH	20	-	20	-	ns
PD data setup time	tPDS	30	-	30	-	ns
PD data hold time	tPDH	20	-	20	-	ns
HSYNC-ENABLE time	tHE	1	HBP	1	HBP	tDCYC
VSYSNC-HSYNC time	tHV	1	175	1	527	tDCYC

Note

1. HBP is horizontal back-porch.



(When VSPL=0, HSPL=0, DPL=0, EPL=1)




Image Data format for 18bit RGB interface (262k color)




Image Data format for 16bit RGB interface (65k color)





Image Data format for 6bit RGB interface (262k color)



## 6. Electro-Optical Characteristic:

Items	Symbol	Min	Typ.	Max	Unit	Remark
Operating Luminance	L	170	200	230	Cd/m <sup>2</sup>	(1)(5)
Power Consumption	Pon	-	350	400	mW	30% pixels on (1)
Max. Current	Icc	-	-	162	mA	(1)
Response Time	Tres	-	-	50	us	(2)
CIE <sub>x</sub> (White)	W <sub>x</sub>	0.26	0.31	0.36	-	(5)
CIE <sub>y</sub> (White)	W <sub>y</sub>	0.28	0.33	0.38	-	(5)
CIE <sub>x</sub> (Red)	R <sub>x</sub>	0.62	0.66	0.70	-	(5)
CIE <sub>y</sub> (Red)	R <sub>y</sub>	0.29	0.33	0.37	-	(5)
CIE <sub>x</sub> (Green)	G <sub>x</sub>	0.25	0.29	0.33	-	(5)
CIE <sub>y</sub> (Green)	G <sub>y</sub>	0.62	0.66	0.70	-	(5)
CIE <sub>x</sub> (Blue)	B <sub>x</sub>	0.11	0.15	0.19	-	(5)
CIE <sub>y</sub> (Blue)	B <sub>y</sub>	0.12	0.16	0.20	-	(5)
Viewing Angle	VA	160	170	-	Degree	(3)
Contrast	CR	5000:1	10000:1	-		(4)
Operation Lifetime	LTop	20000	-	-	Hrs	(1)(6)

Note:

Measuring surrounding: Dark room

Surrounding temperature: 25°C

IOVCC = 1.65V ~ 3.3V

### 1. Test condition:

a. AR\_VDD= 4.6V+/- 0.03V, AR\_VSS= -4.4V+/- 0.03V


b. IC Initial Register Setting:

R03h: 0x0030 // 16bit mode  
 R10h: 0x0000 // IC standby off  
 R18h: 0x0028 // Frame Rate = 80 Hz  
 RF8h: 0x000F // VGH=+5V  
 RF9h: 0x000F // VGL=-5V  
 R05h: 0x0001 // display on


Gamma Register Setting:

R70h: 0x2580  
 R71h: 0x2780  
 R72h: 0x3380  
 R73h: 0x1D18  
 R74h: 0x1F11  
 R75h: 0x2419  
 R76h: 0x1A14  
 R77h: 0x211A  
 R78h: 0x2013

## 2. Response Time test condition



## 3. Viewing angle test condition:



Viewing Angle= CR>10


## 4. Contrast

$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$

## 5. Optical tester: CA210

6. Brightness of 30% power consumption. Operating Life Time is defined when the luminance has decayed to less than 50% of the initial measured luminance before life test.

7. System Diagram:






**8. Pin Assignment:**

PIN	Symbol	I/O	Description	Remarks
1	AR_VDD	I	Positive voltage for OLED(+4.6V)	
2	AR_VSS	I	Negative voltage for OLED(-4.4V)	
3	VCI	I	Power supply for analog circuit(2.5v~3.3v)	
4	VCI1	O	A reference voltage for 1 <sup>st</sup> booster(connect a 1u/10v capacitance to gnd)	
5	GND	I	Ground	
6	C12M	I	External capacitance connect pin between C12M and C12P (1u/10V)	
7	C12P	I		
8	C11M	I	External capacitance connect pin between C11M and C11P	
9	C11P	I		
10	VLOUT1	O	1 <sup>st</sup> booster output pin. (1u/10V)	
11	C31P	I	External capacitance connect pin between C31M and C31P (1u/10V)	
12	C31M	I		
13	C32P	I	External capacitance connect pin between C32M and C32P (1u/10V)	
14	C32M	I		
15	VLOUT3	O	3 <sup>rd</sup> booster output pin. (1u/16V)	
16	VLOUT2	O	2 <sup>nd</sup> booster output pin. (1u/16V)	
17	C21P	I	External capacitance connect pin between C21M and C21P. (1u/10V)	
18	C21M	I		
19	VGS	I	A reference level for the grayscale voltage generation circuit. (connect to gnd)	
20	IOVCC	I	I/O power supply	
21	SPB	I	Select the CPU interface mode. (0=parallel interface 1=serial interface)	
22	ID_MIB	I	Select the CPU type (0=intel 80x-system 1=motorola 68x-system)	
23	DB17	I/O	BI-directional data bus. When CPU I/F, 18-bit interface : DB 17-0 16-bit interface : DB 17-10 , DB 8-1 9-bit interface : DB 8-0 8-bit interface : DB 8-1	
24	DB16	I/O		
25	DB15	I/O		
26	DB14	I/O		
27	DB13	I/O	When RGB I/F 18-bit interface : DB 17-0 16-bit interface : DB 17-10, DB 8-1 6-bit interface : DB 8-3	
28	DB12	I/O		
29	DB11	I/O		
30	DB10	I/O		
31	DB9	I/O	Fix unused pin to the VSS level	
32	DB8	I/O		
33	DB7	I/O		

34	DB6	I/O		
35	DB5	I/O		
36	DB4	I/O		
37	DB3	I/O		
38	DB2	I/O		
39	DB1	I/O		
40	DB0	I/O		
41	VSYNC	I	Frame-synchronizing signal. (VSPL=0 Low active, VSPL=1 High active) FIX this pin at VSS level if the pin is not used	
42	HSYNC	I	Line-synchronizing signal. (HSPL=0 Low active, HSPL=1 High active) FIX this pin at VSS level if the pin is not used	
43	DOTCLK	I	Input pin for clock signal of external interface : dot clock. DPL=0 Display data is fetched at DOTCLK's rising edge DPL=1 Display data is fetched at DOTCLK's falling edge Fix this pin at VSS level if the pin is not used.	
44	ENABLE	I	Data enablesignal pin for RGB interface.	
			EPL	ENABLE GRAM write GRAM address
			0	0 Valid Updated
			0	1 Invalid Held
			1	0 Invalid Held
			1	1 Valid Updated
45	SDI	I	For a serial peripheral interface(SPI), input data is fetched at the rising edge of the SCL signal, Fix SDI pin at VSS level if the pin is not used.	
46	SDO	I	For a serial peripheral interface (SPI), serves as the serial data olutput pin(SDO), Successive bits are output at the falling edge of the SCL signal.	
47	CSB	I	Chip select signal input pin. 0= driver IC is selected and can be accessed. 1= driver IC is not selected and cannot be accessed.	
448	RW_WRB	I	Pin function	CPU type Pin description
			RW	68-system Read/Write operation selection pin 0=write 1=read
			WRB	80_system Write strobe signal.(Input pin) Data is fetched at the rising edge.
			SCL	SPI The synchronous clock signal
49	RS	I	Register select pin. 0=Index/status, 1=instruction parameter, GRAM data Must be fixed at VDD3 level when not used.	
50	E_RDB	I	Pin Function	CPU type Pin description
			E	68-system Read/Writeoperation enable pin
			RDB	80_system Read strobe signal. Read out data at the low level
			When SPI mode is selected , fix this pin at VDD3 level	
51	RESETB	I	Reset pin initializes the IC when low. Should be reset after power-on.	
52	MVDD	O	Internal power for RAM. Connect a capacitance(1u/10v) to gnd.	
53	VREG1OUT	O	A reference level for the grayscale voltage. Connect a capacitance(1u/10v) to gnd.	
54	VCI	I	Power supply for analog circuit(2.5v~3.3v)	

55	VGH	O	The positive voltage used in the gate driver. Connect a capacitance(1u/10v) to gnd.	
56	VGL	O	The negative voltage used in the gate driver. Connect a capacitance(1u/10v) to gnd.	
57	GND		Ground	
58	X-		For touch screen	
59	Y-		For touch screen	
60	X+		For touch screen	
61	Y+		For touch screen	

## 9. External Dimension:



**10. Reliability Test:**

No.	Items	Specification
1	High Temp. Storage	85°C, 240hrs
2	Low Temp. Storage	-40°C, 240hrs
3	High Temp. Operation	60°C, 240hrs
4	Low Temp. Operation	-20°C, 240hrs
5	High Temp / Humidity Storage	85°C, 85%RH, 240hrs
6	High Temp / Humidity Operation	60°C, 90%RH, 240hrs
7	Thermal shock	-40°C ~85°C (-40°C /30min; transit/3min; 85°C /30min; transit /3min) 1cycle: 66min, 100 cycles
8	Vibration	Frequency: 5~50HZ, 0.5G Scan rate : 1 oct/min Time : 2 hrs/axis Test axis : X, Y, Z
9	Drop	Height: 76cm Sequence : 1 angle、 3 edges and 6 faces Cycles: 1
10	ESD	Air discharge model, ±8kV, 10 times

**Evaluation Criteria**

- No damage to glass or encapsulation
- No drastic change to display
- Defects / Mura follow product specification
- Luminance: Within +/-50% of initial value
- Current consumption: within +/-50% of initial value

## 11. Package:

