## RCET 0253 Systems Analog and Digital Lab Lab 1 Check-Off Sheet

Check-Offs  Action item Date (DD/MM/YY) Status Instructor Ini  1a. Set the oscilloscope to trigger on the Probe Compensation Signal. Demonstrate the difference between free-running and triggered by adjusting the trigger level  1b. Identify trigger level, rise/fall slope setting, and trigger point  2. Demonstrate proper probe compensation  3a. Measure the period, frequency, and amplitude of the signal without using the measure function of the scope				
Action item  Date (DD/MM/YY)  Status  Instructor Ini  1a. Set the oscilloscope to trigger on the Probe Compensation Signal. Demonstrate the difference between free-running and triggered by adjusting the trigger level  1b. Identify trigger level, rise/fall slope setting, and trigger point  2. Demonstrate proper probe compensation  Satisfactory Unsatisfactory  3a. Measure the period, frequency, and amplitude of the signal without using the measure function of the scope	Start Date			
1a. Set the oscilloscope to trigger on the Probe Compensation Signal. Demonstrate the difference between free-running and triggered by adjusting the trigger level       □ Satisfactory □ Unsatisfactory         1b. Identify trigger level, rise/fall slope setting, and trigger point       □ Satisfactory □ Unsatisfactory         2. Demonstrate proper probe compensation       □ Satisfactory □ Unsatisfactory         3a. Measure the period, frequency, and amplitude of the signal without using the measure function of the scope       □ Satisfactory □ Unsatisfactory				
Probe Compensation Signal. Demonstrate the difference between free-running and triggered by adjusting the trigger level  1b. Identify trigger level, rise/fall slope setting, and trigger point  2. Demonstrate proper probe compensation  3a. Measure the period, frequency, and amplitude of the signal without using the measure function of the scope	itials			
and trigger point  2. Demonstrate proper probe compensation  □ Satisfactory □ Unsatisfactory  3a. Measure the period, frequency, and amplitude of the signal without using the measure function of the scope				
3a. Measure the period, frequency, and amplitude of the signal <u>without</u> using the measure function of the scope				
amplitude of the signal <u>without</u> using the measure function of the scope				
3b. Measure the period, frequency, and amplitude of the signal with the measure function of the scope  □ Satisfactory □ Unsatisfactory function of the scope				
3c. Measure the period, frequency, and amplitude of the signal with the cursor function of the scope				
3d. Show how all three methods compare in a table. Explain any discrepancies				
4. Measure tilt & rise time ☐ Satisfactory ☐ Unsatisfactory				
5a. Calculate all voltages, phase angles, and Satisfactory Unsatisfactory frequency response of the circuit.				
5b. Draw the predicted voltage phasor ☐ Satisfactory ☐ Unsatisfactory diagram				
5c. Measure the circuit and compare to the predicted values. Explain discrepancies				
6a. reference the Tektronix Lissajous document and draw predicted Lissajous patterns in your lab book at 0° 360°, 45° 225°, 90° 270°, 135° 315°, 180°				
6b. verify Lissajous patter accuracy using two Channels out of the generator and varying the phase of one.				
6c. Predict and Measure the phase difference				

Check-Off Redo			
(write in Action Item!)	Date (DD/MM/YY)	Status	Instructor Initials
		□ Satisfactory □ Unsatisfactory	
		□ Satisfactory □ Unsatisfactory	
		□ Satisfactory □ Unsatisfactory	
		□ Satisfactory □ Unsatisfactory	
		□ Satisfactory □ Unsatisfactory	
		□ Satisfactory □ Unsatisfactory	
		□ Satisfactory □ Unsatisfactory	
		□ Satisfactory □ Unsatisfactory	
		□ Satisfactory □ Unsatisfactory	
		□ Satisfactory □ Unsatisfactory	
		□ Satisfactory □ Unsatisfactory	