

geopackage

Go [back](#)

Metadata

This extension provides a means to store metadata in a GeoPackage and to relate it to content already in the GeoPackage.

gpkg_extensions

To use this extension, add the following rows to this table.

<i>table_name</i>	<i>column_name</i>	<i>extension_name</i>	<i>definition</i>
gpkg_metadata	NULL	gpkg_metadata	http://www.geopackage.org/spec120/#extension_metadata
gpkg_metadata_reference	NULL	gpkg_metadata	http://www.geopackage.org/spec120/#extension_metadata

gpkg_metadata

Add a row to this table for each metadata document.

Column	Value
id	primary key
md_scope	Metadata Scope - default “dataset”
md_standard_uri	URI reference to the metadata structure definition authority (e.g., http://metadata.ces.mil/dse/ns/GSIP/nmis/2.2.0/doc for NMIS)
mime_type	MIME encoding of metadata (e.g., text/xml)
metadata	The actual metadata document

gpkg_metadata_reference

Add a row to this table for each GeoPackage, table, column, row, or row/column that has a metadata document. Multiple rows can refer to a single `gpkg_metadata` entry. It is also possible for an element (geopackage, table, column, row, or row/column) to have multiple metadata documents.

Column	Value
reference_scope	one of “geopackage”, “table”, “column”, “row”, or “row/col”
table_name	<i>user-defined table name</i> (or NULL for whole GeoPackage)
column_name	for <code>reference_scope</code> of “column” or “row/col”, <i>column name in user-defined table</i> (NULL otherwise)
row_id_value	for <code>reference_scope</code> of “row” or “row/col”, the row ID (NULL otherwise)
timestamp	timestamp value in ISO 8601 format
md_file_id	Foreign key to <code>gpkg_metadata</code>
md_parent_id	Foreign key to the parent metadata document (if applicable, NULL otherwise)

This site is open source. [Improve this page.](#)