
WRITTEN TEST 27/01/2023

First Name: Last Name:

This exam has 2 questions with subparts, corresponding to 30 available points. You have **2 hours** to complete the exam. You cannot consult aids of any kind except for the labs' codes. Write answers legibly in the additional sheets and show all of your work. **Write your name** on the exam itself and on all the extra sheets. Concerning the Eigen implementations, upload only the `.cpp` main files. For the exercises requiring LIS, report the bash commands used to perform the computations in a unique `.txt` file. **Upload the files** following the instructions.

Exercise 1

Consider the problem: find $\mathbf{x} \in \mathbb{R}^n$ such that $A\mathbf{x} = \mathbf{b}$, where $A \in \mathbb{R}^{n \times n}$ and $\mathbf{b} \in \mathbb{R}^n$ are given.

1. Describe the LU factorization of A . Introduce the employed notation.
2. State the necessary and sufficient conditions for the existence and uniqueness of the LU factorization.
3. Describe how the LU factorization is used to compute the approximate solution of $A\mathbf{x} = \mathbf{b}$.
4. State the computational costs and prove the result.
5. Describe how the incomplete LU factorization can be used as preconditioner to accelerate the convergence of a linear iterative method. Introduce the employed notation.
6. Download the square matrices `A_1.mtx` and `A_2.mtx` from the Exam folder in webeep and save them on the `lis-2.0.34/test` folder. Using the BICGSTAB iterative solver available in the LIS library, compute the approximate solution of the linear systems $A_1\mathbf{y} = \mathbf{b}$ and $A_2\mathbf{x} = \mathbf{y}$ up to a tolerance of 10^{-10} , assuming that $\mathbf{y} = (1, 1, \dots, 1)^T$. Report on the sheet the iteration counts and the relative residuals at the last iteration.
7. Explore the *Incomplete Lower-Upper (ILU) factorization* method available in LIS in order to define proper preconditioners for the previous linear systems. Report the number of iterations required to reduce the residual below than 10^{-10} and compare with the results obtained by combining the ILU preconditioner with the Additive Schwarz method.
8. Using again the BICGSTAB solver implemented in LIS, solve the linear system $A_1A_2\mathbf{x} = \mathbf{b}$, with $\mathbf{b} = (1, 1, \dots, 1)^T$. Note that the previous problem can be equivalently written as: find \mathbf{y} such that $A_1\mathbf{y} = \mathbf{b}$ and then find \mathbf{x} such that $A_2\mathbf{x} = \mathbf{y}$.
9. Move the matrices `A_1.mtx` and `A_2.mtx` on the `/shared-folder/iter_sol++` directory. Load the matrices in the new `exer1.cpp` file using the `unsupported/Eigen/SparseExtra` module and compute $A = A_1A_2$. Report on the sheet the matrix size, the number of non-zero entries, and the the Euclidean norm of A .

- Solve the linear system $A\mathbf{x} = \mathbf{b}$, with $\mathbf{b} = (1, 1, \dots, 1)^T$, using both the `SparseLU` method available in `Eigen` and the BICGSTAB method implemented in the `bcgstab.hpp` template. For the BICGSTAB method fix a maximum number of iterations sufficient to reduce the residual below than 10^{-10} and use the diagonal preconditioner provided by `Eigen`. Report on the sheet $\|\bar{\mathbf{x}}_{LU}\|$, $\|\bar{\mathbf{x}}_{BCG}\|$, and $\|\bar{\mathbf{x}}_{LU} - \bar{\mathbf{x}}_{BCG}\|$, where $\bar{\mathbf{x}}_{LU}$ and $\bar{\mathbf{x}}_{BCG}$ are the approximate solution obtained with the LU and BICGSTAB methods, respectively.

Exercise 2

- Consider the following eigenvalue problem: $A\mathbf{x} = \lambda\mathbf{x}$, where $A \in \mathbb{R}^{n \times n}$ is given. Describe the power method for the numerical approximation of the largest in modulus eigenvalue of A . Introduce the notation, describe the algorithm, and state the applicability conditions.
- Prove that, under the condition stated above, the method converges.
- Describe the inverse power method for the numerical approximation of the smallest in modulus eigenvalue of A . Introduce the notation, describe the algorithm, and state the applicability conditions.
- Discuss the computational costs of both the power and inverse power methods.
- Describe the deflation technique. Present the algorithm and the applicability conditions.
- Let A be a $n \times n$ symmetric matrix defined such that

$$A = \begin{pmatrix} 2 & -1 & 0 & 0 & \dots & 0 \\ -1 & 4 & -2 & 0 & \dots & 0 \\ 0 & -2 & \ddots & \ddots & \dots & \vdots \\ 0 & 0 & \ddots & \ddots & \ddots & 0 \\ \vdots & \vdots & \vdots & \ddots & \ddots & -n+1 \\ 0 & 0 & \dots & 0 & -n+1 & 2n \end{pmatrix} + \begin{pmatrix} 0 & 0 & 0 & \dots & 0 & 1 \\ 0 & 0 & \ddots & 0 & 1 & 0 \\ 0 & \ddots & \ddots & \ddots & \ddots & \vdots \\ \vdots & 0 & \ddots & \ddots & \ddots & 0 \\ 0 & 1 & \ddots & \ddots & 0 & 0 \\ 1 & 0 & \dots & 0 & 0 & 0 \end{pmatrix}.$$

Let $n = 200$. In a new file called `exer2.cpp`, define the matrix A in the sparse format. Report on the sheet $\|A\|$ where $\|\cdot\|$ denotes the Euclidean norm.

- Solve the eigenvalue problem $A\mathbf{x} = \lambda\mathbf{x}$ using the proper solver provided by the `Eigen` library. Report on the sheet the two smallest computed eigenvalues of A .
- Export matrix A in the matrix market format using the `unsupported/Eigen/SparseExtra` module (save it as `exer2.mtx`) and move it to the `lis-2.0.34/test` folder. Using the proper iterative solver available in the LIS library compute the smallest eigenvalue of A up to a tolerance of 10^{-12} . Report the computed eigenvalue and motivate the choice made.
- Approximate the second smallest eigenvalue of the `exer2.mtx` matrix up to a tolerance of 10^{-9} . Explore different inner iterative methods and preconditioners (at least 3 alternative strategies). Report on the sheet the iteration counts and the residual at the last iteration.